

Circular Motion of a Stunt Glider

Nathan Tasker

March 25, 2025

Contents

1	Vertical Circle: Loop the loop including Dip and Arch	2
1.1	Achieved	2
1.2	Merit	2
1.3	Excellence	4
2	Banked Corner	4
2.1	Achieved	4
2.2	Merit	4
2.3	Excellence	4
3	Additional Info	4
3.1	Comprehensive Version History	4
3.2	Graphical Analysis Files	4
3.3	L ^A T _E X	4
3.4	Bibliography	4


1 Vertical Circle: Loop the loop including Dip and Arch

1.1 Achieved

The force of gravity is always constant in both magnitude and direction regardless of the glider's velocity or position in the loop (top, bottom, and anywhere else). This is because $|\vec{F}_g| = mg$ where mass (m) and the acceleration of gravity (g) are constants.

Conversely, the force of lift varies in both direction and magnitude as the glider performs the loop the loop. Lift's magnitude ($|\vec{F}_L|$) is greatest at the bottom, $\because |\vec{F}_L| = \frac{1}{2}\rho|\vec{v}|^2AC_L$, $\therefore |\vec{F}_L| \propto v^2$. Because velocity is greatest at bottom, lift force is as well. To maintain circular motion the centripetal force ($|\vec{F}_c| = |\vec{F}_L| - |\vec{F}_g|$) towards the center of the circular path must have a magnitude value great enough to provide necessary centripetal acceleration for the circular path radius, meaning the lift force upwards must at least be greater than the gravity force downwards ($|\vec{F}_L| > |\vec{F}_g|$ in order for $|\vec{F}_c| > 0$).

Lift's magnitude ($|\vec{F}_L|$) is least at the top, because the direction of gravity force is toward the center of the circular path. This means ($|\vec{F}_c| = |\vec{F}_L| + |\vec{F}_g|$).



At the bottom of the vertical circle, the tension force (emulating the lift force, \vec{F}_L) is greatest, which occurs at 15.82 seconds with 5.89N.

Once the force meter (emulating motion of glider) reaches the top of the vertical circle, the tension force is at its least, which - when smoothing the curve of data and reducing random variation/noise - occurs at

Check if sine model or quadratic helps - then return to this section.

During the loop the loop, as the glider ascends, its kinetic energy (E_K) is converted into gravitational potential energy (E_p). As the glider descends, its gravitational potential energy (E_p) is converted back into kinetic energy (E_K).

1.2 Merit

$$E_K = \frac{1}{2}m|\vec{v}|^2 \quad (1)$$

$$\therefore |\vec{v}|^2 \propto E_K \quad (2)$$

$$|\vec{v}| \propto \sqrt{E_K} \quad (3)$$

During the loop the loop, as the glider ascends, its kinetic energy (E_K) is converted into gravitational potential energy (E_p). This decreases its velocity as it is proportional to kinetic energy, which decreased when converted to gravitational potential energy.

As the glider descends, its gravitational potential energy (E_p) is converted back into kinetic energy (E_K). This

increases its velocity as it is proportional to kinetic energy, which increased when the gravitational potential energy was converted back into it.

A glider's ability to successfully perform a vertical loop relies on its ability to provide an adequate lift force, increasing both net and centripetal force.

$$|\vec{F}_L| = \frac{1}{2} \rho |\vec{v}|^2 A C_L \quad (4)$$

$$\therefore |\vec{F}_L| \propto |\vec{v}|^2 \quad (5)$$

Equation (5) shows that velocity is a major factor in the magnitude of the lift force. Without adequate velocity, inadequate lift force is provided for the vertical loop to be successful. As kinetic energy is converted to gravitational potential energy during ascent, if the velocity drops below what is required for the circular path radius its motion will instead imitate that of a projectile.


Other factors include surface area contacting air (A), and the coefficient of lift (C_L , determined by shape and angle of attack).

Fluid density (ρ) is constant.

During motion, 3 forces are acting on the stunt glider:

1. Gravity (\vec{F}_g) (i.e. Weight) always vertically downwards (i.e. toward center of Earth).
2. Lift (\vec{F}_L) perpendicular to direction of velocity, toward the center of the circular path.
3. Air Resistance (\vec{F}_R) (i.e. Friction, Drag) opposite to direction of velocity.

Please note that vector arrow lengths are not perfectly proportionally accurate.



1.3 Excellence

2 Banked Corner

2.1 Achieved

2.2 Merit

2.3 Excellence

3 Additional Info

3.1 Comprehensive Version History

Access to all prior versions of this document during process of creation is publicly available at:
<https://github.com/NathanTaskerPersonal/AS91522>

3.2 Graphical Analysis Files

Access to all graphical analysis files are publically available at:
middletonschoolnz-my.sharepoint.com/...

3.3 L^AT_EX

This document has been entirely written in L^AT_EX; a markup language for mathematical equations and diagrams. I'm more than happy to provide plain text for the entire document for convenience in AI detection.

3.4 Bibliography