



› FOR SOCIETY

SHOWCASE


FHICT TEMPLATE SHOWCASE

Tom 
some@mail.com

2024-05-29

This page is intentionally left blank.

VERSION HISTORY

Version	Date	Author	Changes
1.0	2023-11-04	Tom 	Initial version

This page is intentionally left blank.

SUMMARY

This document will show all the features of the FHICT Template.

In this pre-toc section you can do anything you want, but it will not be shown in the Table of Contents.

IM A HEADING THAT COMES BEFORE THE TABLE OF CONTENTS

You can use your terms here.

W.I.P. (*Work In Progress*)

This page is intentionally left blank.

TABLE OF CONTENTS

1 Examples	1
1.1 Headings Example	1
1.1.1 level 3	1
1.2 Text example	1
1.3 Figures example	1
1.3.1 Image	1
1.3.2 Code	2
1.4 Citations	2
1.5 Tables	3
1.6 Using Terms	4
1.7 Boxes	5
1.7.1 colorful-boxes	5
1.7.2 showybox	5
1.7.3 Custom Boxes	6
1.8 lined_box	6
1.9 sensitive information	6
1.10 Links	7
2 Document options	8
2.1 Title and Subtitle	8
2.2 Authors	8
2.3 Version History	8
2.4 Summary	9
2.5 Table of	10
2.6 Watermark	10
2.7 Bibliography	10
2.8 Citation style	10
2.9 Disabling Table of Contents	10
2.10 Disabling Chapter Numbering	11
2.11 Glossary	11
2.11.1 Setting terms	11
2.11.2 Front vs Back	11
3 Default Included Packages	12
3.1 Codly	12
3.2 colorful-boxes	12
3.3 showybox	12
3.4 Glossarium	12
Glossary	14
References	16
A This is the appendix	18

This page is intentionally left blank.

TABLE OF FIGURES

Figure 1: Figure example	1
--------------------------------	---

This page is intentionally left blank.

TABLE OF LISTINGS

Listing 1: Code example C++	2
Listing 2: Code example Rust	2
Listing 3: Table example	3
Listing 4: Table example with custom colors	4
Listing 5: Custom Boxes Example	6
Listing 6: Title and Subtitle Options	8
Listing 7: Authors Option	8
Listing 8: Authors Option with Missing Email	8
Listing 9: Version History Option	8
Listing 10: Summary Option	9
Listing 11: Table of Figures Option	10
Listing 12: TOF / TOL disabled Option	10
Listing 13: Watermark Option	10
Listing 14: Bibliography Option	10
Listing 15: Citation Style Option	10
Listing 16: Table of Contents Option	10
Listing 17: Chapter Numbering Option	11
Listing 18: Glossary Option	11
Listing 19: Glossary Location Option	11
Listing 20: Codly C++ Example	12
Listing 21: Raw C++ Example	12

This page is intentionally left blank.

1 EXAMPLES

1.1 HEADINGS EXAMPLE

1.1.1 LEVEL 3

1.1.1.1 LEVEL 4

1.1.1.1.1 LEVEL 5

1.1.1.1.1 level 6

Level 6 and higher are not supported in the custom syntax. They will still work, but will have the default styling.

1.2 TEXT EXAMPLE

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguere possit, augeri amplificarique non possit. At etiam Athenis, ut e patre audiebam facete et urbane Stoicos irridente, statua est in quo a nobis philosophia defensa et collaudata est, cum id, quod maxime placeat, facere possimus, omnis voluptas assumenda est, omnis dolor repellendus. Temporibus autem quibusdam et.

1.3 FIGURES EXAMPLE

1.3.1 IMAGE

This is a figure with an image. This will be shown in the list of figures if enabled.



Figure 1: Figure example

1.3.2 CODE

This is a figure with code. This will be shown in the list of listings if enabled.

```
int main() {  
    return 0;  
}
```

C++

Listing 1: Code example C++

```
fn main() {  
    println!("Hello, world!");  
}
```

Rust

Listing 2: Code example Rust

1.4 CITATIONS

This is a citation [1].

1.5 TABLES

There is a helper function called `fhict_table` that can be used to create tables. This function takes two mandatory arguments: `columns` and `content`, and two optional arguments: `top_colored` and `left_colored`.

The `columns` argument is a list of column widths.

The `content` argument is a list of rows. Each row is a list of cells. Each cell is a string.

Header 1	Header 2	Header 3	Header 4
Cell 1	Cell 2	Cell 3	Cell 4
Cell 1	Cell 2		Cell 4

The table above is made with the following code:

```
#fhict_table(  
    columns: (auto, auto, auto, 1fr),  
    content: (  
        ("Header 1", "Header 2", "Header 3", "Header 4"),  
        ("Cell 1", "Cell 2", "Cell 3", "Cell 4"),  
        ("Cell 1", "Cell 2", "", "Cell 4"),  
    ),  
)
```

Listing 3: Table example

The `top_colored` argument is `true` by default, and will color the top row of the table.

The `left_colored` argument is `false` by default, and will color the left column of the table.

You can combine these two arguments to create a table like this:

Header 1	Header 2	Header 3	Header 4
Cell 1	Cell 2	Cell 3	Cell 4
Cell 1	Cell 2		Cell 4

Or disable both to create a table like this:

Header 1	Header 2	Header 3	Header 4
Cell 1	Cell 2	Cell 3	Cell 4
Cell 1	Cell 2		Cell 4

You can also configure the color of the table by using the `background_color_heading`, `background_color`, `text_color_heading` and `text_color` arguments.

You can for example make a table like this:

Header 1	Header 2	Header 3	Header 4
Cell 1	Cell 2	Cell 3	Cell 4
Cell 1	Cell 2		Cell 4

Here is the code snippet for this table:

```
#fhict_table(  
  columns: (auto, auto, auto, lfr),  
  content: (  
    ("Header 1", "Header 2", "Header 3", "Header 4"),  
    ("Cell 1", "Cell 2", "Cell 3", "Cell 4"),  
    ("Cell 1", "Cell 2", "", "Cell 4"),  
  ),  
  background_color_heading: rgb("4272f5"),  
  text_color_heading: rgb("f5a142"),  
  background_color: rgb("f54242"),  
  text_color: rgb("42f5a1"),  
)
```

Listing 4: Table example with custom colors

1.6 USING TERMS

You can quote a term by using one of the following syntaxes:

- `#gls("term")`
- `#glspl("term")`
- `@term`

If you use a term for the first time, it will display the long version of the term. If you use it again, it will display the short version of the term.

For example, the term `#gls("fhict")` will be shown as FHICT (*Fontys Hogeschool ICT*). But the second time you use it, it will be shown as FHICT.

And `@wip` will be shown as W.I.P.. But the second time you use it, it will be shown as W.I.P..

1.7 BOXES

1.7.1 COLORFUL-BOXES

Lorem ipsum dolor sit amet.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

Lorem ipsum dolor sit amet.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

Lorem ipsum dolor sit amet.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

Lorem ipsum dolor sit amet.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

1.7.2 SHOWYBOX

Red-ish showybox with separated sections!

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua quaerat voluptatem. Ut enim aequaleamus.

1.7.3 CUSTOM BOXES

I am a grey box! You can use me for a less intrusive box.

Put whatever you want in here. $I = \frac{V}{R}$

You can also customize the color of the background, stroke and text.

```
#text_box[  
  I am a grey box!  
  You can use me for a less intrusive box.  
  
  Put whatever you want in here. $I = V / R$  
]  
  
#text_box(background-color: fontys_purple_2,  
stroke-color: fontys_purple_1, text-color: fontys_blue_1)[  
  You can also customize the color of the background, stroke and text.  
]
```

Listing 5: Custom Boxes Example

1.8 LINED_BOX

lined_box

This is a lined_box. This box can be used to indicate anything you want.

lined_box, but black

You can also change the color of the lines.

1.9 SENSITIVE INFORMATION

You can censor sensitive information by using the `#sensitive` function. Each character will be replaced by a black rectangle, making it impossible to read or copy the text.



```
#sensitive("I am sensitive information")
```

You can set if the text should be censored or not by setting the `censored` option in the document options.

1 means censored, 0 means not censored.

1.10 LINKS

You can create links by using the `#hlink` function. This function takes two arguments: `url` and `content`. The `url` argument is the url the link should point to. The `content` argument is the text that should be shown in the document and is optional. If the `content` argument is not set, the `url` argument will be used as the content.

The following code will create two links, one with the content "Google" and one with the content "www.google.com". Both links will point to the same url.

```
#hlink("www.google.com", content: "Google")
```

Typst

```
#hlink("www.google.com")
```

[Google](https://www.google.com)

www.google.com

2 DOCUMENT OPTIONS

2.1 TITLE AND SUBTITLE

The title and subtitle can be set by using the following options:

```
title: "YOUR TITLE",  
subtitle: "YOUR SUBTITLE",
```

Typst

Listing 6: Title and Subtitle Options

2.2 AUTHORS

The authors can be set by using the following option:

```
authors: (  
  (  
    name: "YOUR NAME",  
    email: "YOUR EMAIL",  
  ),  
  (  
    name: "YOUR NAME",  
    email: "YOUR EMAIL",  
  ),  
)
```

Typst

Listing 7: Authors Option

At least one author is required, otherwise the cover page will contain an empty white square.

If any one author does not have an email address, the email addresses will not be shown at all on the cover page.

```
authors: (  
  (  
    name: "YOUR NAME",  
  ),  
  (  
    name: "YOUR NAME",  
    email: "YOUR EMAIL",  
  ),  
)
```

Typst

Listing 8: Authors Option with Missing Email

You can also chose to not set any authors. In this case, no authors will be shown on the cover page.

2.3 VERSION HISTORY

The version history can be set by using the following option:

```
version-history: (  
  (  
    name: "YOUR NAME",  
    email: "YOUR EMAIL",  
  ),  
)
```

Typst

```

version: "1.0.0",
date: "2020-01-01",
author: "Jeroen Van De Lange",
changes: "Initial version",
),
(
version: "1.0.1",
date: "2020-01-02",
author: "Jeroen Van De Lange",
changes: "Added a new feature",
),
),

```

Listing 9: Version History Option

The version history is optional. If it is not set, the version history will not be shown.

2.4 SUMMARY

It is possible to add a summary to the document. This can be done by setting the following option:

```

summary: [
    YOUR SUMMARY TEXT
],

```

Listing 10: Summary Option

2.5 TABLE OF ...

On top of the Table of Contents, the template also supports a Table of Figures and a Table of Listings. These can be enabled by setting the following options:

```
table-of-figures: true,  
table-of-listings: true,
```

Typst

Listing 11: Table of Figures Option

You can disable these by settings the options to false, or leaving them out entirely.

```
table-of-figures: false,
```

Typst

Listing 12: TOF / TOL disabled Option

2.6 WATERMARK

The watermark can be set by using the following option:

```
watermark: "YOUR WATERMARK TEXT",
```

Typst

Listing 13: Watermark Option

2.7 BIBLIOGRAPHY

The bibliography can be set by using the following option:

```
bibliography-file: "YOUR BIBLIOGRAPHY FILE",
```

Typst

Listing 14: Bibliography Option

You will need to use a .bib file for this. The template will automatically generate the bibliography based on the citations in the document.

Note that the path to the bibliography file is relative to the *template* document, not the document you are writing.

2.8 CITATION STYLE

The citation style can be set by using the following option:

```
citation-style: "YOUR CITATION STYLE",
```

Typst

Listing 15: Citation Style Option

The standard style is `ieee`.

2.9 DISABLING TABLE OF CONTENTS

For certain extremely small documents, it might be desirable to disable the Table of Contents. This can be done by setting the following option:

```
disable-toc: true,
```

Typst

Listing 16: Table of Contents Option

For normal documents, this option should not be used.

2.10 DISABLING CHAPTER NUMBERING

For certain extremely small documents, it might be desirable to disable the chapter numbering. This can be done by setting the following option:

```
disable-chapter-numbering: true,
```

Typst

Listing 17: Chapter Numbering Option

2.11 GLOSSARY

2.11.1 SETTING TERMS

You can set terms by using the following option:

```
glossary-terms: (  
  (  
    key: "KEY",  
    short: "SHORT",  
    long: "LONG",  
    desc: [DESCRIPTION],  
  ),  
  ...  
)
```

Typst

Listing 18: Glossary Option

`long` and `desc` are optional.

2.11.2 FRONT VS BACK

By default the glossary will be shown in the back of the document. You can change this by setting the following option:

```
glossary-front: true,
```

Typst

Listing 19: Glossary Location Option

If set to `true`, the glossary will be placed after the Table of Contents. If set to `false`, the glossary will be placed after the references.

3 DEFAULT INCLUDED PACKAGES

3.1 CODLY

This package makes code blocks look nicer.

For example, a C++ code block will look like this:

```
int main() {  
    return 0;  
}
```



Listing 20: Codly C++ Example

Instead of something like this:

```
int main() {  
    return 0;  
}
```

Listing 21: Raw C++ Example

3.2 COLORFUL-BOXES

This package adds support for colored boxes.

Examples can be seen here in the Boxes section.

3.3 SHOWYBOX

This package adds support for colored boxes.

Examples can be seen here in the Boxes section.

3.4 GLOSSARIUM

This package handles the glossary.

This page is intentionally left blank.

GLOSSARY

FHICT – Fontys Hogeschool ICT: Fontys University of Applied Sciences 4

W.I.P. – Work In Progress. IV, 4

This page is intentionally left blank.

REFERENCES

- [1] TomVer99, "FHICT typst template." [Online]. Available: <https://github.com/TomVer99/FHICT-typst-template>

This page is intentionally left blank.

A THIS IS THE APPENDIX

In the appendix, only the top-level headings appear in the table of contents.

A.A I WILL NOT APPEAR IN THE TABLE OF CONTENTS