

Communication - I2C

The aim of this project is to create a multi-master I2C bus, with which I can transmit data from the masters to the display. The system must contain 2 master devices and 1 slave, being the sensors and display.

For the purposes of this project, I'll be implementing two DHT11 sensors, and an OLED display. The DHT11 sensors will be used to measure temperature and humidity, and the OLED display will be used to display the data.

Concepts

Hardware based solution

While this does not adhere to the I2C specification, it is a simple solution to the problem. The hardware based solution is based on using GPIO pins to force control of the bus, by directly controlling another master. Due to the requirements of the project, this solution is not applicable.

Token based solution (AKA Token Passing Media Access Control)

An access token is passed in a regular pattern between devices. This token is used to determine which device has control of the bus. The token is passed from device to device, until it reaches the device that wants to take control of the bus. The device that wants control of the bus waits for availability of the token, and then takes control of the bus. The device then performs the required actions, and passes the token to the next device. This goes on until the system shuts down. In pseudocode, this would look like the following:

```
Loop forever
{
    Wait for token
    Take control of the bus
    Verify I have control of the bus
    If I have control of the bus
    {
        Do something
    }
    Relinquish control of the bus
    Pass token to next device
}
```

Register based control

With this concept, the goal of either master is to take control of the bus by writing to the control register. The control register is a 1 byte register, which is located at address 0x00. The control register is used to set the state of the bus. The following states are possible:

Value	Description
0x00	Bus free
0x01	Master 1
0x02	Master 2

The control register is read by all masters. If a master wants to take control of the bus, it writes to the control register. If the bus is free, the master takes control of the bus. If the bus is taken by another master, the master waits until the bus is free. If the bus is taken by itself, the master does nothing.

Feedback

After speaking to Felix, a few things were clarified. While I was initially under the impression that I needed to implement my own low level arbitration, this is not the case, as the Wire Library for Arduino already has an implementation for this. The purpose was to implement a system for dictating masters on the I2C bus.

After a brief discussion of options, we decided that the best option would be to use a register based system. This would allow for the system to be easily expanded, and would allow for the system to be easily debugged.

Implementation

Device Addresses

Device	Address
Temperature	0x01
Humidity	0x02
Display	0x03

Hardware The hardware for this project is as follows:

Quantity	Device	Description
3	Arduino Uno	User for the Master and Slave devices
2	DHT11	Used for temperature and humidity sensing
1	OLED Display	Used for displaying the data

Display

To make my life easier, I have made a function for printing lines to the display. This function will automatically increment the cursor, so that the next line will be printed below the previous line. This function also automatically displays the

data, so that the user does not have to call the display function. The function is as follows:

```
int cursorY = 0;

void PrintLine(String title, int data)
{
    oled.print(title);
    oled.print(data);
    oled.display();
    cursorY += 16;
    oled.setCursor(0,cursorY);
}

void ResetCursor()
{
    oled.setCursor(0,0);
    cursorY = 0;
}
```

This in turn, allows me to simply loop through the data, and print it to the display. The code for this is as follows:

```
void loop()
{
    PrintLine("Temp: ", temp);
    PrintLine("Hum: ", hum);

    oled.clear(PAGE);
    delay(DELAY); // Delay to prevent flooding the bus,
}
```

Receiving I2C

To receive data from the I2C bus, I have created a function that is called when data is received. This function will read the data, and then store it in a register. The function is as follows:

```
void onReceive(int bytes)
{
    int inbound = Wire.read();
    if(incomingData == I2CData::None) // Receive Register
    {
        incomingData = (I2CData)inbound;
    }
    else // Receive Data
```

```

{
  switch(incomingData)
  {
    case I2CData::Temperature:
      Temperature = inbound;
      break;
    case I2CData::Humidity:
      Humidity = inbound;
      break;
  }
  incomingData = I2CData::None;
}
}

```

By always sending two integers, we can denote what the data is. This is done by sending the first integer, indicating what register the data must go to, and the second integer as the data.

```

enum I2CData
{
  None = -1,
  Temperature = 0,
  Humidity = 1
};

```

Sending I2C

To send the data, I have created a function that will send the data to the display. This function is as follows:

```

void SendData(int data)
{
  Wire.beginTransaction(0x03);
  Wire.write(data);
  Wire.endTransmission();
}

```

This function will send the data to the display, and then end the transmission. This will allow the display to receive the data, and then display it.

To use this, I'll call the function twice. While I could have used two writes in the same transmission, I decided against this, as it would make the code more difficult to read.

Side note During the Proftaak, I found myself struggling with the ESP32. As it turns out, the Wire library for the ESP32 is not the same as the Wire library for the arduino. The ESP32 Library does not implement the ability to log onto the bus as a master with an address. This causes the wierd situation

of being forced to log off, log on without an address, write the data and then finally logging back on as a slave.

Showcase

Conclusion

References