

1. What is HTML? What does HTML stands for?

HTML stands for HyperText Markup Language. HTML provides the structure of a webpage. HTML is the standard markup language used to create and structure the content of web pages. It tells the browser how different pieces of content such as headings, paragraphs, images, links, tables, and lists should be structured.

Example:-

```
<h1> welcome to my website </h1>
```

```
<p> This is my first webpage </p>
```

2. Why is HTML called a markup language? Is HTML a programming language?

⇒ HTML is a markup language because it uses tags to mark and organize the content of a webpage.

⇒ HTML not a programming language because it does not contain programming logic such as conditions, loops or calculations.

example:-

```
<p> This is HTML </p>
```

3. Difference between HTML tag and HTML Element?

An HTML tag is a keyword written inside angle brackets `<>`. It tells the

browser how to handle the content.

An HTML element usually consists of an opening tag, content and a closing tag.

Tag :-

<P>

Element :-

<P> Hello world </P>

4. What is <!DOCTYPE html>? Is it an HTML tag?

<!DOCTYPE html> is a DOCTYPE declaration. It tells the browser that the document is written using HTML 5. It is not an HTML tag.

Syntax :-

<!DOCTYPE html>

It is normally written at the very beginning of an HTML document.

B. Explain the basic structure of an HTML document:

The basic structure of an HTML document contains <!DOCTYPE html>, <html>, <head> and <body>

<html> → Root element of the HTML document.

<head> contains information about the webpage, such as title and meta tag.

<body> contains the content displayed on the webpage.


```

<head>
  <title> My page </title>
</head>
<body>
  <h1> Hello </h1>
</body>
</html>

```

6. What are HTML Attributes?

HTML attributes provides additional information about an HTML element. They are usually written inside the opening tag.

Syntax:-

```
<tag attribute = "Value">
```

Example:-

```
<img src = "photo.jpg" alt = "student photo"
width = "200">
```

Here, ~~src~~ src, alt, and width are attributes.

7. What is the difference between src and href?

src:-

src stands for Source. It specifies the location of a resource such as an image.

```
<img src = "photo.jpg">
```

href:-

href specifies the destination of a link.

```
<a href = "https://www.google.com">Google</a>
```

8. What is the purpose of the alt attribute?

It provides alternative text for an image. If the image cannot be displayed the alt text can describe the image. It also helps accessibility.

Example:-

```
<img src = "g.img" alt = "g.im">
```

Here student image is the alternative text.

9. Block-level elements vs Inline elements.

Block level elements normally start on a new line and take the available width.

Examples:-

```
<div> Hello </div>
```

```
<p> Hello </p>
```

```
<h1> Hello </h1>
```

Inline elements normally stay in the same line and take only the space they need.

Examples:-

```
<span> Hello </span>
```

```
<a href = "http://www.google.com"> Google </a>
```

10. What is Semantic HTML?

Semantic HTML means using HTML elements that clearly describe their

meaning and purpose.

Example :-

<header>

<nav>

<section>

<article>

<footer>

• Non-semantic elements do not clearly describe their purpose.

Example :-

<div>

11. Difference between <div> and

<div> is a block-level element. It is mainly used to group larger sections of content.

 is an inline element. It is mainly used to group or style a small part of text.

example :-

<div> This is a section </div>

<p> This is important text </p>

12. What are the different type of html lists?

There are three main types of HTML lists:

1. Unordered list

Displays items with bullets.

 HTML

 CSS

ii) ordered list -

Displays items in order, usually with numbers.

 HTML

 CSS

iii) Description list <dl>

Used to display terms and their descriptions.

<dl>

<dt> HTML </dt>

<dd> Hyper text markup language </dd>

</dl>

13. Explain important HTML table tags.

HTML table are used to display data in rows and columns.

<table> -> creates a table.

<tr> -> creates a table row

<th> creates a table heading

<td> -> creates a table data cell.

<thead> groups the table header.

<tbody> groups the main table content.

<tfoot> groups the table footer.

Example :-

```
<table>
```

```
<thead>
```

```
<tr>
```

```
<th> Name </th>
```

```
<th> course </th>
```

```
</tr>
```

```
</thead>
```

```
<tbody>
```

```
<tr>
```

```
<td> Arun </td>
```

```
<td> Full Stack </td>
```

```
</tr>
```

```
</tbody>
```

```
</table>
```

14. purpose of charset and viewport meta tag.

charset = "UTF-8" tells the browser to use UTF-8 character encoding. It helps display different languages, symbols and emojis correctly.

```
<meta charset = "UTF-8">
```

Viewport meta tag helps the webpage display properly on different screen sizes, especially mobile devices.

```
<meta name = "viewport" content =
```

```
"width=device-width, initial-scale=1.0">
```

15. What is open Graph (OG)?

Open Graph is a set of meta-tag used to control how a webpage appears when its URL

is shared on social media or other platforms.

og:title

Specifies the title shown in the shared preview. Syntax:-

```
<meta property="og:title" content="Full Stack development">
```

og:type

Specifies the type of webpage or content.

```
<meta property="og:type" content="website">
```

og:image

Specifies the image shown in the shared preview.

```
<meta property="og:image" content="course.jpg">
```

og:url

Specifies the URL of the webpage.

```
<meta property="og:url" content="https://example.com/course">
```

og:description

Specifies a short description shown in the shared preview.

```
<meta property="og:description" content="Learn Full Stack Development through practical projects.">
```