Sounding Like Which AI? Machine-Style Overlap of arXiv Abstracts with Language Models of Different Vintages

Natik Chhabra
Independent researcher, Bilaspur, India
ORCID 0009-0004-8786-7703
https://github.com/NatikChhabra/Sounding-Like-Which-AI-

Abstract

We ask not how much text was produced with LLM help but how much writing, by any author, falls on the LLM side of a stylistic boundary, and which LLMs define that side. We define **Machine-Style Overlap** (MSO): the share of documents that a calibrated classifier on style features that ignore content-word identity judges at least as likely to be LLM output as pre-ChatGPT human writing. In 131,448 arXiv abstracts (2015–2026), MSO was 9.2% before ChatGPT and by June 2025 stood 25.4 percentage points (pp) above its pre-ChatGPT trend, far above placebo gaps. Because recent LLMs learn from recent writing, we compare generators by vintage. Against generators whose pretraining data predate ChatGPT, the gap is smaller (7.5 pp; 3.5 pp for the two we ran from titles). Single-generator overlap mostly rose then fell, peaking later for newer (and longer-writing) generators (exploratory rank correlation 0.79, $n = 18$; 0.66 without three added post hoc). A fixed reference set, like a fixed marker-word list (*delve*), can show the shift receding while overlap with newer models still rises. In US school essays, English learners' essays fall in the region less often than their peers'; essay scores explain most of this.

1 Introduction

Corpus studies find traces of LLM-assisted writing in abstracts, peer reviews, press releases and encyclopedias (Kobak et al., 2025; Liang et al., 2024a,b, 2025; Brooks et al., 2024), and LLM-associated words have become more frequent in unscripted speech (Yakura et al., 2026; Anderson et al., 2025). We find that by mid-2025 the share of arXiv abstracts on the LLM side of a calibrated style boundary stood 25.4 pp above its pre-ChatGPT trend, and that whether it was still rising in 2026 depends on which LLMs define the boundary.

Existing measurements answer a *prevalence* question: what fraction of a corpus was produced or modified with an LLM? We ask an *overlap* question: what fraction of a genre's writing, by any author, is stylistically closer to LLM output than to pre-ChatGPT human writing? The two differ in how they handle text written before ChatGPT. Prevalence estimators report a small "LLM share" for it, which studies read as consistent with false positives (Liang et al., 2024b), subtract as baseline misclassification (Lin and Zhu, 2025), or use to calibrate thresholds (Brooks et al., 2024). For a fixed feature map and reference set, we regard that share as a property of the two text distributions and study how it changes over time.

Both questions share a complication that prevalence studies seldom discuss: "LLM style" is defined by whichever models serve as the reference. Recent models are trained on recent text, so a rising overlap with them may mean that writing moved towards the models or that the models learned from the writing. We therefore compare reference generators by *vintage* on a fixed task: models whose pretraining data predate ChatGPT, other models released in 2023–2025, and models released in 2026.

Contributions. (1) We define Machine-Style Overlap (MSO), a classify-and-count quantity (Forman, 2008) that, on pre-ChatGPT writing, equals the false-positive rate of the Bayes classifier; we estimate it with calibrated classifiers and report how the estimate varies across them (§3). (2) We measure it in arXiv abstracts against 19 reference generators released from 2023 to 2026, including four whose pretraining data predate ChatGPT and four released in 2026 (§§4–5). (3) Abstracts moved into the LLM region after 2022 (25.4 pp above trend by June 2025), more in computer science than in mathematics. Placebo dates and instruments trained on earlier years give gaps of

at most 6.5 pp (§6.3). (4) The shift is present, though smaller, against generators unlikely to have learned it from post-ChatGPT writing, GPT-4 alone giving the largest gap; single-generator overlap tends to peak later for newer generators, which also write longer, so the trajectory depends on the reference (§6.4). (5) Secondary results (§§6.5–6.6): words mined from each generator rose until 2025 and mostly fell in 2026; stylistic dispersion did not change beyond its trend once length is fixed; parliamentary speech showed no clear gap; and, contrary to our plan, English learners' essays fall in the region *less* often than their peers'. Our analysis plan was committed to our repository before any result was computed (Appendix A). It stated five hypotheses: pre-ChatGPT MSO is non-zero and differs by field (H1; non-zero follows from imperfect separability, so only the field difference is a test); arXiv MSO rises above its pre-ChatGPT trend (H2), more than in a less-exposed genre (H3) and more in computer science than in mathematics (H4); and learner essays have higher MSO (H5). The vintage analysis, which gives the paper its title, was added after simulated peer review by separate AI sessions (Acknowledgements) and is exploratory.

2 Related Work

Prevalence of LLM-assisted writing. Excess-vocabulary methods compare word frequencies with a counterfactual extrapolated from pre-LLM years (Kobak et al., 2025; Holzwarth et al., 2026; Lee, 2026); distributional methods fit a mixture of human and LLM word distributions (Liang et al., 2024a,b, 2025; Geng and Trotta, 2024); classifier- and detector-based studies label documents (Lin and Zhu, 2025; Brooks et al., 2024; Sun et al., 2025b; Khan et al., 2026). Most target the share of text produced with LLM help. LLM adoption also changes how many papers scientists produce (Kusumegi et al., 2025). Closest to ours, Bentley et al. (2026) track a composite LLM-associated style index alongside vocabulary-complexity measures in arXiv abstracts, and Askitas (2025) finds an abrupt stylometric shift in economics working-paper abstracts in 2023 with an event-study design and a classifier. Chang (2026) shows that PubMed, Wikipedia and Stack Exchange text became more predictable to small language models over 2014–2024, a trend that began before generative AI; our pre-ChatGPT slope, partly a field-mix effect, points the same way. Our estimand differs: a thresholded overlap (the flag rate of a calibrated classifier) whose pre-ChatGPT level is itself of interest. We also exclude content words from the features, since authors react to publicised markers (Geng and Trotta, 2025), and compare reference generators by training-data vintage.

Homogenisation and human adoption. Writing or ideating with instruction-tuned models reduces content diversity across users (Padmakumar and He, 2024; Doshi and Hauser, 2024; Anderson et al., 2024), and LLM rewriting compresses stylistic variance (Sourati et al., 2026). Preference tuning reduces output diversity (Kirk et al., 2024; Wu et al., 2025) and plausibly produces LLM-overused words (Juzek and Ward, 2025). LLM-associated vocabulary has grown in human speech (Yakura et al., 2026; Anderson et al., 2025), academic authors adapt their LLM use once overused words are publicised (Geng and Trotta, 2025), and adoption of LLM revision varies across disciplines and author groups (Lin and Zhu, 2025). Our vintage comparison asks whether human text still provides a reference independent of LLM style.

Style of human and LLM text. LLM text differs systematically from human text in lexico-grammatical features (Reinhart et al., 2025; Muñoz-Ortiz et al., 2024; Berber Sardinha, 2024; Herbold et al., 2023) and in recurring part-of-speech templates (Shaib et al., 2024), but texts cluster by genre more than by source (Rallapalli et al., 2026), so any overlap measure must be genre-specific. Distribution-level comparisons (Pillutla et al., 2021; Yang et al., 2026) evaluate models against human text; we track where human documents fall relative to an LLM region.

Detection and perception. Readers misjudge machine text (Clark et al., 2021; Jakesch et al., 2023; Casal and Kessler, 2023; Gao et al., 2023), and detectors can be evaded (Sadasivan et al., 2025; Krishna et al., 2023; Dugan et al., 2024); we collect no human judgements. Zero-shot detectors use token-likelihood statistics (Hans et al., 2024; Bao et al., 2024), and detection needs more text as machine and human distributions converge (Chakraborty et al., 2024). Off-the-shelf detectors have flagged non-native writing (Liang et al., 2023), although detectors trained on a large writing assessment showed no such bias (Jiang et al., 2024) and false-positive rates on non-native

manuscripts vary widely (Park et al., 2026). Detectors transfer unevenly to unseen generators (Pu et al., 2023; Li et al., 2024), and individual models have distinctive, identifiable output patterns (Sun et al., 2025a), so a style region depends on the models that define it.

3 Machine-Style Overlap

Fix a genre and a feature map ϕ from documents to style vectors. Let P_{pre} be the distribution of $\phi(d)$ for human documents written before ChatGPT's release (30 November 2022; "pre-ChatGPT" throughout), and P_{LLM} the distribution for LLM output in the same genre, an equal-weight mixture over a reference set of generators and prompting styles chosen by us (in practice, each generator is capped at the same number of training texts; §6.4 notes where a region departs from equal weights). For any population S of documents,

$$\text{MSO}(S) = \Pr_{d\sim S}\left[\, p_{\text{LLM}}(\phi(d)) \geq p_{\text{pre}}(\phi(d)) \,\right]. \tag{1}$$

With equal priors the Bayes posterior is $\eta(x) = p_{\text{LLM}}(x)/(p_{\text{LLM}}(x) + p_{\text{pre}}(x))$, so $\text{MSO}(S) = \Pr_S[\eta(\phi(d)) \geq \frac{1}{2}]$; we call $\{x : \eta(x) \geq \frac{1}{2}\}$ the *LLM region*. MSO is the flag rate of the Bayes-optimal classifier, that is, classify-and-count (Forman, 2008) with a calibrated threshold.

Pre-ChatGPT overlap. For $S = P_{\text{pre}}$, MSO is the Bayes classifier's false-positive rate, and the Bayes error is $\frac{1}{2}\big(\text{MSO}(P_{\text{pre}}) + \Pr_{\text{LLM}}[\eta < \frac{1}{2}]\big)$, which is zero only when the two styles are separable and reaches $\frac{1}{2}$ when they coincide. Prevalence studies that subtract a pre-period share as misclassification remove the analogue of this quantity under their own feature map.

Overlap after ChatGPT. For later populations S_t, $\text{MSO}(S_t)$ measures how much writing at time t falls in the region. It says nothing about authorship: a rise is consistent with undisclosed LLM use, with humans adopting LLM style, or both. If a fraction α of documents were LLM output and the rest unchanged human writing, $\text{MSO}(S_t) = \text{FPR} + \alpha(\text{TPR} - \text{FPR})$, where FPR and TPR are the region's false- and true-positive rates; we use this identity only to translate MSO into an implied α for comparison with prevalence studies.

Estimation. We call a trained, calibrated classifier with its 0.5 threshold an *instrument*. A finite instrument only approximates η, and its flag rate is neither an upper nor a lower bound on the Bayes quantity. We therefore report how MSO varies across classifier families, held-out generators, generator sets and thresholds; confidence intervals in the text are document-level bootstrap or regression intervals and exclude this instrument variation.

4 Data

arXiv abstracts. We sampled eight arXiv archives by primary category (cs, math, stat, eess, q-bio, econ, astro-ph, cond-mat; "fields" below). For each field and each month from January 2015 to September 2026, we fetched through the arXiv API all papers submitted in one randomly placed window of consecutive days and drew up to 200 at random. Field-months with at least 200 papers therefore carry equal weight. Smaller fields contribute fewer documents, especially in early years, so the field mix changes (eess: 1.5% of scored abstracts in 2015, 16.2% in 2022); the overall series is a stratified sample, not the arXiv population. The API returns the latest version of each abstract, so we exclude papers first submitted before ChatGPT but revised after it (0.5% of sampled 2016 papers, 7.8% of 2021 and 24.2% of 2022 papers). Recent papers have had less time to be revised, but scoring only never-revised papers barely changes yearly MSO (2024: 27.0% vs 27.8%; 2026: 44.7% vs 44.7%). After removing abstracts under 50 words, 131,448 abstracts remain.

Other human text. *Parliamentary speech:* Australian House of Representatives Hansard (Katz and Alexander, 2023, 2025), up to 150 spoken speeches per month from 2015 to July 2025 (13,725 speeches). *Student essays:* PERSUADE 2.0 (Crossley et al., 2024), 14,797 pre-ChatGPT essays by US students in grades 6–12 on 14 prompts, with English-language-learner (ELL) status and a holistic score. In every genre, half of the pre-ChatGPT documents (the *train pool*) train the instrument and seed LLM prompts; MSO is measured on the rest.

Reference generators. Table 1 lists them. Local models answered three prompt styles, about 150 prompts each: *P1* write the text from a title or topic; *P2* improve the wording of a human draft (LLM-assisted revision); *P3* write the text and "avoid typical AI phrasing". Prompts

were seeded only from train-pool documents; local models used temperature 0.8 and fixed seeds. The 2026 model (Claude Opus 5.5) answered the same prompt instances through sub-agent sessions of 50 prompts each, without control over decoding; it is also the system that drafted this paper (see Acknowledgements). For abstracts we add the RAID generations without adversarial attack (Dugan et al., 2024), written from titles of arXiv papers by six 2023 chat models. The main instrument uses 14 generators, each capped at 450 training texts. Five further open models were added after the second simulated review, for the vintage analysis only: two whose pretraining data predate ChatGPT and three released in 2026. The latter give the 2026 comparison a second source with logged decoding, and each pairs with a 2025 model of the same family. Hansard and essays use the seven local models and the 2026 model.

Generator	Released	Cutoff
RAID, 2023 chat models (Dugan et al., 2024)		
GPT-4 (gpt-4-0613)	2023	Sep 2021[a]
Llama-2-Chat 70B	2023	Sep 2022[b]
ChatGPT (3.5-turbo-0613)	2023	(2021)[c]
Mistral-7B-Instr. v0.1; MPT-30B-chat; Cohere command	2023	
Local; main instrument, all genres		
Mistral 7B Instruct v0.3	2024-05	
Llama 3.1 8B	2024-07	Dec 2023
Phi-4 14B	2024-12	Jun 2024
Gemma 3 12B	2025-03	Aug 2024
Granite 3.3 8B; Qwen3 8B	2025-04	
gpt-oss 20B	2025-08	Jun 2024
Sub-agent sessions; main instrument, all genres		
Claude Opus 5.5 (2026 model)	2026	
Local; vintage analysis only (abstracts, mainly P1)		
Llama-2-Chat 7B	2023-07	Sep 2022[b]
Vicuna 7B v1.5[d]	2023-08	Sep 2022[b]
Qwen3.5 9B	2026-02	
Gemma 4 12B	2026-06	Jan 2025
Granite 4.2 8B	2026-08	

Table 1: Reference generators, with release month (year where only that is documented, approximated for the peak analysis; not public for the 2026 model) and pretraining-data cutoff where the developer states one. [a]OpenAI (2023); [b]Touvron et al. (2023); [c]reported only in secondary sources, so ChatGPT enters the pre-ChatGPT-data region only as a sensitivity check; [d]fine-tuned from Llama 2 (LMSYS, 2023) with the Vicuna recipe of training on user-shared ChatGPT conversations (Zheng et al., 2023). Other dates: Jiang et al. (2023); Mistral AI (2024); Meta (2024); Microsoft (2024); Google DeepMind (2025); Qwen Team (2025); IBM Granite Team (2026); OpenAI (2025); Qwen Team (2026); Google DeepMind (2026b,a).

5 Method

Cleaning. All texts are normalised alike. We remove chat wrappers ("Here's the abstract:"), lines echoing the prompt's title, markdown and trailing notes, and map typographic variants and misdecoded characters to plain equivalents. LaTeX math becomes a placeholder and LaTeX dashes (`--`, `---`) become Unicode dashes: human arXiv abstracts write dashes in LaTeX and chat models in Unicode, a difference that would otherwise separate the sources by encoding alone. Texts are truncated to 250 words.

Features and instruments. Features use no content-word identities, to limit topic sensitivity: per-token rates of closed-class words, coarse part-of-speech trigrams, dependency labels and punctuation marks, plus mean and standard deviation of sentence length, mean word length and lexical diversity (MTLD; McCarthy and Jarvis, 2010), computed with spaCy 3.8 (`en_core_web_sm`). Features present in fewer than 1% of training documents are dropped (top features in Appendix B). The primary instrument is L2-regularised logistic regression (C=0.1) on standardised features with isotonic calibration; the second uses gradient-boosted trees, calibrated the same way. Classes are balanced, so a calibrated probability of 0.5 is a likelihood ratio of one. Cross-validation and calibration folds are grouped so that a revised text and its human source, and all speeches by one parliamentarian, never fall in different folds. For essays we add two instruments: logistic regression on sentence embeddings (all-MiniLM-L6-v2), and a one-feature isotonic classifier on mean token negative log-likelihood (the statistic behind perplexity-based detectors) under Qwen2.5-0.5B or GPT-2 small; GPT-2's training data predate the TOEFL and PERSUADE releases. Both are trained on the same human and LLM essays as the primary instrument.

Time series. We compute monthly MSO and fit an interrupted time-series (ITS) model: weighted least squares with a level shift and slope change at December 2022, with Newey–West (6-lag) standard errors. The *trend gap* is the fitted post-ChatGPT value minus the extrapolated pre-ChatGPT trend in June 2025, a month fixed in code before any time-series result. As robustness checks we vary the pre-trend (quadratic; start in

2017 or 2019; end in 2020), fit the post-ChatGPT line only up to June 2025, hold the field mix fixed, drop abstracts with LaTeX math or with a language-model term (e.g. LLM, ChatGPT, generative AI), compute a nonparametric gap (mean observed January–June 2025 value minus the extrapolated trend), and bootstrap the gap with 12-month residual blocks. Placebo breaks are placed every second month from June 2016 to December 2021, each evaluated 12 months later, and at two fixed dates (November 2019 and 2020) evaluated in June 2022. Drift placebos train the instrument only on human abstracts up to 2016, 2017 or 2018, place a break in the following January and test for a gap in June 2022, 41 to 65 months later and before ChatGPT, so any gap they show reflects instrument ageing or trend misspecification.

Vintage. To compare vintages on a fixed task, we train one instrument per generator on its title-only (P1) outputs (RAID outputs are title-based). A further instrument pools the generators whose pretraining data predate ChatGPT (the *pre-ChatGPT-data region*): GPT-4 and Llama-2-Chat 70B from RAID, plus Llama-2-Chat 7B and Vicuna 7B run locally on P1. Many RAID outputs summarise the paper ("In the paper titled…"); we drop those matching a summary pattern from this region and from each RAID generator's own region (5.4% of the RAID part of this set; up to 32.9% for Cohere's model).

Marker words. We track two lexical series: the share of abstracts containing a published marker word (*delve*, *underscore*, *showcase*, *meticulous*, *intricate*, *intricacies*, *commendable*, *boast*; Kobak et al., 2025; Gray, 2024; Yakura et al., 2026), and, for each reference set, the share containing one of 20 words mined from that set's own outputs: the words with the highest smoothed log ratio of document frequency between the outputs and the human abstracts their prompts were built from, so that most topic words of the prompt set cancel.

6 Results

6.1 Separability of human and LLM text

The instruments separate pre-ChatGPT human text from LLM text well (cross-validated AUC 0.939 for abstracts, 0.968 for speech, 0.988 for essays). Generators held out of training are mostly recognised (arXiv recall from 59.6% for Cohere to 95.6% for GPT-4; Table 4 in Appendix C), but the 2026 model is not: only 20.7% of its abstracts and 36.4% of its essays fall in a region built without it. Its revisions of human drafts are also hard to separate from human text (AUC 0.675). Lexical diversity is the top LLM-typical feature; human abstracts use more coordination, adjectival modifiers and longer sentences (Appendix B).

6.2 Pre-ChatGPT overlap varies by field (H1)

Before ChatGPT, 9.2% (95% CI 8.9–9.5) of arXiv abstracts fell in the LLM region, as did 5.4% (4.9–6.1) of speeches and 4.0% (3.6–4.5) of student essays. The arXiv baseline varies by field (Figure 3 in Appendix F; $\chi^2(7) = 354.55$, $p<0.001$), from 4.4% in astrophysics to 15.3% in economics. Fields also differ in abstract length; reweighting each field to the overall length distribution changes the values to 6.1% and 14.0%, and abstracts without LaTeX math keep astrophysics lowest and economics highest. Before ChatGPT, overall MSO rose by 0.5 pp per year.

6.3 Abstracts moved into the region (H2, H4)

Yearly arXiv MSO ranged from 7.3% to 10.2% in 2015–2021, was 11.1% in 2022, then 17.7%, 27.8% and 40.6% in 2023–2025 and 44.7% in January–September 2026. The monthly series has been roughly flat since late 2025 (Figure 1a); the higher 2026 annual mean depends on the 2026 model (§6.4). The trend gap in June 2025 is 25.4 pp (95% CI 23.2–27.7; block bootstrap 23.3–27.3), 2.1 times the extrapolated trend value. Across the variants in Table 2 that change the threshold, the sample or the trend, the gap stays between 23.5 pp (threshold 0.6) and 29.1 pp (abstracts without LaTeX math); gradient-boosted trees give 29.5 pp. It is smaller when the generators that write closest to human abstracts are left out of the region: without the 2026 model (22.2 pp) or without revisions of human drafts (17.9 pp). The gap does not rest on one feature family. Removing MTLD, the strongest feature, gives 25.4 pp, and removing any one family (closed-class words, part-of-speech trigrams, dependency labels, punctuation or sentence statistics) gives 22.9 to 26.6 pp. Fast-DetectGPT (Bao et al., 2024) with GPT-2 small, a zero-shot detector, separates our human and LLM abstracts poorly (AUC 0.737) and does not track the shift (Appendix D). Of the 34 placebo breaks, 8.8% give a gap with $p < 0.05$, close to the nominal 5%, and the largest gap is 3.2 pp. At the real gap's 30-




Figure 1: Monthly MSO for (a) arXiv abstracts and (b) Australian parliamentary speech (different y-scales), and (c) the share of arXiv abstracts containing a published marker word. Dashed: pre-ChatGPT linear trend, extrapolated. Series (a) rises well above trend, (b) shows a small gap and (c) peaks in 2024.

month horizon, 8.3% give $p < 0.05$ and the largest is 5.8 pp. The three drift placebos give gaps of 6.5, −2.3 and −1.0 pp (Table 2). The positive one comes from the instrument trained on 2015–2016 only, extrapolated over 65 months from a two-year trend. Instrument ageing or trend misspecification can thus produce gaps of up to 6.5 pp, about a quarter of the observed gap; only the −2.3 pp gap has $p < 0.05$. Yearly residuals from the pre-ChatGPT trend stay within ±1 pp through 2022 and reach 28.5 pp in 2025. *Fields (H4).* The gap is largest in computer science (38.1 pp) and quantitative biology (36.2) and smallest in mathematics (10.5) and astrophysics (13.7). Computer science exceeds mathematics by 27.6 pp (CI 22.2–32.9), and all eight field gaps remain significant after Holm correction (all adjusted $p<0.001$). If nothing else had changed, the mixture identity (§3) would imply that 42.1% of computer-science and 7.8% of mathematics abstracts were LLM output in 2024, the ordering that Liang et al. (2024b) report at lower levels (Appendix F).

Variant	Gap (pp)	95% CI or p
Primary (linear trend, ITS)	25.4	23.2–27.7
Threshold 0.4 / 0.6	27.2 / 23.5	
Abstracts without LaTeX math	29.1	26.4–31.8
No language-model terms	23.9	21.9–25.9
Length-reweighted	24.2	22.0–26.3
No dash features	26.1	23.9–28.3
Without the 2026 model	22.2	18.7–25.8
Without revision (P2) texts	17.9	15.7–20.2
Gradient-boosted trees	29.5	27.8–31.3
Equal field weights	26.7	24.0–29.3
Pre-ChatGPT field weights	24.4	22.3–26.5
Post-trend fitted to June 2025	27.5	25.6–29.3
Nonparametric, linear trend	26.3	
quadratic trend	26.9	
trend from 2017	26.5	
trend from 2019	27.4	
trend to 2020	25.4	
Placebos (before ChatGPT; gap in June 2022)		
Break Nov 2019	−1.1	$p = 0.258$
Break Nov 2020	−0.8	$p = 0.335$
Drift, instrument to 2016	6.5	$p = 0.061$
Drift, instrument to 2017	−2.3	$p = 0.020$
Drift, instrument to 2018	−1.0	$p = 0.158$

Table 2: arXiv trend gap in June 2025 (percentage points above the extrapolated pre-ChatGPT trend) under robustness variants. Nonparametric rows: mean January–June 2025 value minus the trend.

6.4 Sounding like which AI?

Generators whose pretraining data predate ChatGPT. The pre-ChatGPT-data region (GPT-4, Llama-2-Chat 70B, Llama-2-Chat 7B and Vicuna 7B on the title-only task) holds models unlikely to have learned their style from post-ChatGPT scientific writing: their 2023 instruction tuning used annotator data or (Vicuna) user-shared ChatGPT conversations and, as far as is documented, no recent abstracts. Abstracts still moved into it: MSO was 6.5% in 2022, 15.5% in 2024 and 17.9% in 2025, and the trend gap is 7.5 pp (CI 4.6–10.4), against 20.3 pp for a title-only region built from the 2024–2025 open models (Figure 2a). Three quarters of the region's training texts come from RAID, so its generators are not equally weighted and the estimate leans on RAID's prompt; the two small local models, run on exactly our prompts, give 3.5 pp (CI 1.5–5.5; other subsets in Appendix E). Alone, GPT-4 gives the largest gap (11.4 pp; Llama-2-Chat 70B 5.5, 7B 3.7, Vicuna 1.4). Part of the shift therefore

points towards generators unlikely to have learned it from recent abstracts. On our own prompts that part is small from titles alone (3.5 pp) but 12.5 pp over all three prompt styles. Drift placebos for this region (instruments trained on abstracts up to 2016, 2017 or 2018) give gaps of 0.5, -1.3 and -2.0 pp. In 2026 its MSO fell back to 11.9%. Because overlap with these generators peaked in 2025, a straight post-ChatGPT line fitted through 2026 understates their June 2025 gap: fitted only to June 2025, the gap is 13.1 pp (two small local models: 7.6 pp), against 22.7 pp for the 2024–2025 open models.

One generator at a time. With the region defined by a single generator on the title-only task, MSO rose from 2022 to 2025 under every generator except Cohere's chat model, whose overlap peaked in 2023Q2. Quarter by quarter, overlap with each other generator but the 2026 model rose and then fell, and the turn tended to come later for newer generators (Figure 2b; peak quarters in Appendix E); under the 2026 model it was still rising in 2026Q3. From 2026Q2 to 2026Q3 overlap fell under every other generator, with or without equal field weights, so the 2026Q2 peaks of gpt-oss and Granite 4.2 may mark a shared fluctuation rather than a turn. Release date and peak quarter have rank correlation 0.79 ($n = 18$; the 2026 model is excluded because its release month is not public). All generators score the same abstracts, so their errors are correlated; a document bootstrap within quarters gives 0.64–0.86 and five training draws 0.79–0.85 (0.73–0.84 with every region trained on 150 texts, as RAID regions otherwise use 450). The correlation is 0.84 with each quarter's abstracts reweighted to the pre-ChatGPT length distribution, 0.81 with equal field weights, 0.82 without the 2023 models and 0.83 with all six RAID models dated mid-2023. Newer generators, however, also write longer (rank correlation 0.70 between release date and median output length), and length predicts the peak about as well (0.73). Given length, the partial correlation of release date and peak is 0.56; vintage and length cannot be separated. The analysis is exploratory. A first test, release date against the 2025-to-2026 change, gave 0.67 on annual means but 0.18 from 2025Q4 (Appendix A). Without the three 2026 open models, added after the pattern was seen, the correlation is 0.66 ($n = 15$, permutation $p = 0.010$; 0.66–0.77 across training draws, 0.57–0.76 with equal training sizes), or 0.37 given length. Individual peak quarters are uncertain by one or two quarters, and by up to five for Cohere's model (Appendix E). Gemma 4 12B (released June 2026) and Granite 4.2 peaked before their release and Qwen3.5 in its release quarter, so authors' use of these models can explain little of the timing. On annual means, MSO fell from 2025 to 2026 under 15 of the 19 generators and rose under gpt-oss (29.4% to 38.5%), Qwen3.5, Granite 4.2 and the 2026 model (29.3% to 39.2%); every change but Gemma 4's is stable across bootstrap, training draws and generator subsamples (Appendix E). In the three 2025–2026 same-family pairs the newer model's change was higher; for Gemma the two intervals overlap. Pretraining cutoff orders the peaks about as well as release date (Appendix E). A region pooling the three 2026 open models, run with logged decoding, also rose (28.9% to 34.9% on annual means), so the late peak does not rest on the uncontrolled generator.

The aggregate 14-generator series (Figure 1a) still rose in 2026, although 12 of its 14 single-generator regions fell. Without the 2026 model it did not (37.9% to 36.8%). Pooled regions also need not follow their members: the seven local models pooled on title-only prompts went from 28.2% to 29.0% (not a stable change), and over all three prompts from 43.3% to 48.4%. If newer generators keep peaking later, any fixed reference set will eventually show the shift receding. Only the pre-ChatGPT-data region avoids the question of who learned from whom.

6.5 Marker words

The share of abstracts with a published marker word rose from 1.1% in 2022 to 5.3% in 2024 and fell to 1.5% in 2026 (Figure 1c); its June 2025 trend gap was 1.9 pp (CI 0.8–3.0). These words come from 2023–2024 models, so we also compare with words mined from the generators that define each style region. For every generator, the share of abstracts using one of the 20 words mined from its own outputs (§5) rose from 2022 to 2025 (for the pre-ChatGPT-data generators, from 17.4% to 34.9%). In 2026 the share fell for 17 of the 19 generators, including gpt-oss and Qwen3.5, under which style overlap rose. It kept rising only for Granite 4.2 (33.6% to 35.6%) and the 2026 model (49.4% to 57.4%); the latter's mined words are ordinary academic vocabulary. Quarterly marker and style peaks follow no consistent order (marker peak earlier for 7, later for 6, same for 5 of 18




Figure 2: (a) Yearly arXiv MSO with the region defined by generators of different vintages (title-only prompts). (b) Quarter in which MSO peaked when the region is defined by one generator at a time, against that generator's release date (open circle: the 2026 model, whose release month is not public; still rising in the last quarter; unlabelled green points: Gemma 3, Granite 3.3 and Qwen3). Overlap with newer generators tends to peak later; the 2026Q2 peaks rest on a fall in 2026Q3 shared by every generator but the 2026 model. The RAID line in (a) pools all six RAID models with summary-style outputs kept, unlike the pre-ChatGPT-data region.

generators). At the document level the published markers and MSO pick out largely different abstracts (point-biserial $r = 0.12$; 5.9% of in-region vs 1.4% of other abstracts contain one).

6.6 Secondary results

Parliamentary speech (H3). The Hansard trend gap is small (1.3 pp, CI −0.7 to 3.4), and the arXiv gap exceeds it by 30.7 pp (CI 28.3–33.2) when both regions use the same eight generators (arXiv gap then 32.1 pp). Hansard is a weak comparison: it fails its own placebo grid (23.5% of breaks with $p < 0.05$) and its gap depends on the pre-trend specification (Appendix G). *Dispersion.* With abstracts cut to 150 words, the stylistic spread of abstracts did not fall faster after ChatGPT than before (2025 gap 0.05, CI −0.36 to 0.51; Appendix H). *Learner essays (H5, not supported).* Our plan predicted higher MSO for English learners, but it is lower (2.3% vs 4.2%; odds ratio 0.55 adjusted for prompt and grade, 0.87 when proficiency is added), and sentence-embedding and perplexity instruments agree in direction. A GPT-2 perplexity instrument reproduces the bias against TOEFL essays reported by Liang et al. (2023), yet flags PERSUADE learners less often than their peers because the learners' writing is less predictable (Appendix I).

7 Discussion

Whether abstracts were still moving towards LLM style in 2026 depends on the reference LLM. Overlap tended to peak later for more recent generators, and under three of the four 2026 generators it peaked in 2026 or was still rising. Words mined from most generators fell meanwhile, so the decline of *delve* need not mean that writing stopped moving. Detectors, prevalence estimators and marker lists built on a fixed set of models may therefore understate recent change; refreshed ones may mistake models' learning from writing for a shift in writing. Our data cannot say why abstracts in 2026 resemble the newest models. Authors' use of the 2026 open models can explain little of those models' peaks: the models may have learned from recent writing, or they and the authors may share the style of commercial models used in 2024–2026, which, apart from the 2026 model, we did not run. Either way, recent LLMs and recent scientific writing may no longer be independent references for each other, a precondition for the recursive dynamics studied in model-collapse work (Shumailov et al., 2024; Gerstgrasser et al., 2024) but not evidence of them.

8 Conclusion

In arXiv abstracts, Machine-Style Overlap rose from 9.2% before ChatGPT to 40.6% in 2025, well above its pre-ChatGPT trend; overlap with generators whose pretraining data predate ChatGPT rose less. Single-generator overlap tended to peak later for more recent generators, so studies of LLM influence on writing should report their reference models' vintage and compare several vintages.

Limitations

MSO is defined relative to a feature map and a researcher-chosen generator set, and its trajectory after 2025 depends on that set's vintage (§6.4). Four generators are from 2026; one of them was run without decoding control in batches of 50 prompts and is the system that drafted this paper. The pre-ChatGPT-data region rests on four generators, three of them built on Llama 2, and their instruction tuning used data from 2023. The vintage comparison holds the task (an abstract from a title) fixed, but not the prompt wording or decoding for RAID, decoding for the 2026 model, or output length. Median lengths are 102 (Vicuna) to 250 words (Llama-2-Chat 70B, at the truncation limit) within the pre-ChatGPT-data region, 90 to 134 for the other RAID models and 138 to 186 for the local 2024–2026 models. Output length rises with release date and predicts the peak quarter about as well, so the vintage pattern is not separated from length. The single-generator regions of the local models share one human training sample. The 2026 model's single region is the least distinct from human abstracts: 17.9% of 2015 abstracts fall in it, against at most 8.3% for any other generator. The three 2026 open models were added after the pattern of the other generators had been seen. Single-generator regions rest on 150 texts each (up to 450 for RAID models), so instrument precision differs by vintage. Cross-validation grouped the 2026 model's outputs by source document, not by session, which may flatter its held-in recall. Mined marker lists contain some topic and register words. Post-ChatGPT "human" documents may be partly LLM-written, so MSO cannot separate LLM use from human adoption of LLM style, and no causal claim is made. The overall arXiv series averages a stratified sample of eight fields (two of them in physics). Changes in authorship, subfields and submission volume may contribute despite stratified sampling and topic and length checks, and excluding papers revised after ChatGPT makes the late pre-period sample more selected. Confidence intervals ignore instrument variation and clustering by field-month. Classifier families agree on population-level MSO for abstracts (22.8% vs 22.6%) but less on individual documents (Cohen's $\kappa = 0.64$; 0.48 for the pre-ChatGPT-data region; speech 0.26, essays 0.29). Both the style and the perplexity instruments flag TOEFL essays far more often than US 8th-grade essays (style: 34.1% vs 5.7%), so the learner result is specific to the PERSUADE population. All text is English and truncated to 250 words. Parliamentary speech differs from abstracts in many ways, and its linear trend fails its own placebo tests. The dispersion measure depends on document length. The learner analysis is cross-sectional, concerns US school learners, and rests on 15 in-region learner essays; its perplexity instruments use two small language models and thresholds calibrated on PERSUADE. The analysis plan was committed to our own repository and never frozen with a third party.

Ethics Statement

The study uses only public datasets under their licences: arXiv metadata, including titles and abstracts (CC0); Australian Hansard (Parliament of Australia, CC BY-NC-ND 4.0), through the database of Katz and Alexander (2025) (CC BY 4.0); PERSUADE 2.0 (CC BY-NC-SA 4.0, whose share-alike terms apply to derived data we release); and RAID and the Hugging Face release of Liang et al. (2023) (MIT). Their US 8th-grade essays come from the authors' GitHub repository, which has no licence file but whose README shows an MIT badge, and derive from the Hewlett Foundation ASAP data, so we release only aggregate results for them. Because Hansard text may not be adapted, we do not release the LLM revisions of speeches (P2). The study involves no human participants. Hansard speakers are members of parliament speaking in public office; we release only speech and speaker identifiers, party and opening sentences, which are already public. PERSUADE essays were de-identified by their creators, the released LLM revisions of them keep that masking, and we release no human-written essays. The local models are used under their licences (Llama 2 and Llama 3.1 community licences, the former also covering Vicuna; Gemma Terms of Use for Gemma 3; MIT for Phi-4; Apache 2.0 for the others, including Gemma 4), all of which permit this research use; some restrict training other models on their outputs, which the data release notes. All local generation (11,730 texts from models of 7 to 21 billion parameters) and all analyses ran on one desktop PC with a consumer GPU (AMD Radeon RX 7800 XT, 16 GB) over two days; GPU-hours were not logged. The learner analysis compares

groups, never individuals, and we caution against using any overlap or detector score to judge an individual writer, or using MSO as a detector.

Acknowledgements: AI Use and Authorship

An AI system (Claude Opus 5.5, Anthropic, used as an agent through Claude Code) carried out most of this study. The human author chose the topic, the goal of a fully disclosed AI-conducted study, and the constraints (public data only, no human participants, local compute), and approved the analysis plan in the working conversation; deviations (Appendix A) were made by the AI system and reported to the author. The AI system proposed the research question, the term "Machine-Style Overlap" and the hypotheses, wrote the analysis plan and all code, generated the local-model texts, ran the analyses, made the figures and drafted all text; no human has edited the text. The same system produced the 2026-model texts (§4), so its own outputs are part of the reference set. Simulated peer review by separate sessions of the same model family, which share its blind spots, informed revisions. Separate AI sessions checked every citing sentence against the cited work's abstract or full text in two full passes (some sources only through metadata or mirrors), with later rechecks of changed sentences. The checks led to rewordings, one removed citation and the replacement of preprints by published versions. Citations were not checked by a human; the human author will read the final paper before release. Every numerical result of our analyses in the paper is inserted automatically from the analysis outputs; a few counts and orderings stated in words were read from the same outputs. Full responsibility for the content, including the citations and the analysis choices, lies with the human author. No AI system is listed as an author.

References

Barrett R. Anderson, Jash Hemant Shah, and Max Kreminski. 2024. Homogenization effects of large language models on human creative ideation. In *Creativity and Cognition*, C&C '24, pages 413–425. ACM.

Bryce Anderson, Riley Galpin, and Tom S. Juzek. 2025. Model misalignment and language change: Traces of AI-associated language in unscripted spoken English. *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, 8(1):179–191.

Nikos Askitas. 2025. The behavioral signature of GenAI in scientific communication. IZA Discussion Paper 18062, Institute of Labor Economics (IZA), Bonn.

Guangsheng Bao, Yanbin Zhao, Zhiyang Teng, Linyi Yang, and Yue Zhang. 2024. Fast-DetectGPT: Efficient zero-shot detection of machine-generated text via conditional probability curvature. In *International Conference on Learning Representations*, pages 24814–24836.

R. Alexander Bentley, Blai Vidiella, Damian J. Ruck, Senjuti Dutta, Kai Li, and Sergi Valverde. 2026. Human–LLM collaboration is transforming complexity metrics in scientific texts. *Preprint*, arXiv:2606.27052.

Tony Berber Sardinha. 2024. AI-generated vs human-authored texts: A multidimensional comparison. *Applied Corpus Linguistics*, 4(1):100083.

Creston Brooks, Samuel Eggert, and Denis Peskoff. 2024. The rise of AI-generated content in Wikipedia. In *Proceedings of the First Workshop on Advancing Natural Language Processing for Wikipedia*, pages 67–79. Association for Computational Linguistics.

J. Elliott Casal and Matt Kessler. 2023. Can linguists distinguish between ChatGPT/AI and human writing?: A study of research ethics and academic publishing. *Research Methods in Applied Linguistics*, 2(3):100068.

Souradip Chakraborty, Amrit Bedi, Sicheng Zhu, Bang An, Dinesh Manocha, and Furong Huang. 2024. Position: On the possibilities of AI-generated text detection. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 6093–6115. PMLR.

Eunsuk Chang. 2026. Human writing and machine patterns: Analyzing a decade of convergence. *Scientometrics*, 131(3):1635–1654.

Elizabeth Clark, Tal August, Sofia Serrano, Nikita Haduong, Suchin Gururangan, and Noah A. Smith. 2021. All that's 'Human' is not gold: Evaluating human evaluation of generated text. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7282–7296. Association for Computational Linguistics.

S.A. Crossley, Y. Tian, P. Baffour, A. Franklin, M. Benner, and U. Boser. 2024. A large-scale corpus for assessing written argumentation: PERSUADE 2.0. *Assessing Writing*, 61:100865.

Anil R. Doshi and Oliver P. Hauser. 2024. Generative AI enhances individual creativity but reduces the collective diversity of novel content. *Science Advances*, 10(28):eadn5290.

Liam Dugan, Alyssa Hwang, Filip Trhlík, Andrew Zhu, Josh Magnus Ludan, Hainiu Xu, Daphne Ippolito, and Chris Callison-Burch. 2024. RAID: A shared benchmark for robust evaluation of machine-generated text detectors. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12463–12492. Association for Computational Linguistics.

George Forman. 2008. Quantifying counts and costs via classification. *Data Mining and Knowledge Discovery*, 17(2):164–206.

Catherine A. Gao, Frederick M. Howard, Nikolay S. Markov, Emma C. Dyer, Siddhi Ramesh, Yuan Luo, and Alexander T. Pearson. 2023. Comparing scientific abstracts generated by ChatGPT to real abstracts with detectors and blinded human reviewers. *npj Digital Medicine*, 6(1):75.

Mingmeng Geng and Roberto Trotta. 2024. Is ChatGPT transforming academics' writing style? *Preprint*, arXiv:2404.08627.

Mingmeng Geng and Roberto Trotta. 2025. Human-LLM Coevolution: Evidence from academic writing. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 12689–12696. Association for Computational Linguistics.

Matthias Gerstgrasser, Rylan Schaeffer, Apratim Dey, Rafael Rafailov, Tomasz Korbak, Henry Sleight, Rajashree Agrawal, John Hughes, Dhruv Bhandarkar Pai, Andrey Gromov, Dan Roberts, Diyi Yang, David L. Donoho, and Sanmi Koyejo. 2024. Is model collapse inevitable? Breaking the curse of recursion by accumulating real and synthetic data. In *First Conference on Language Modeling*.

Google DeepMind. 2025. Gemma 3 model card. `https://ai.google.dev/gemma/docs/core/model_card_3`.

Google DeepMind. 2026a. Gemma 4 12B model card. `https://huggingface.co/google/gemma-4-12B-it`.

Google DeepMind. 2026b. Gemma releases. `https://ai.google.dev/gemma/docs/releases`.

Andrew Gray. 2024. ChatGPT "contamination": Estimating the prevalence of LLMs in the scholarly literature. *Preprint*, arXiv:2403.16887.

Abhimanyu Hans, Avi Schwarzschild, Valeriia Cherepanova, Hamid Kazemi, Aniruddha Saha, Micah Goldblum, Jonas Geiping, and Tom Goldstein. 2024. Spotting LLMs with Binoculars: zero-shot detection of machine-generated text. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 17519–17537. PMLR.

Steffen Herbold, Annette Hautli-Janisz, Ute Heuer, Zlata Kikteva, and Alexander Trautsch. 2023. A large-scale comparison of human-written versus ChatGPT-generated essays. *Scientific Reports*, 13(1):18617.

Lena Holzwarth, Rita González-Márquez, and Dmitry Kobak. 2026. Most biomedical publications show signs of LLM-assisted writing. *Preprint*, arXiv:2608.10715.

IBM Granite Team. 2026. Granite 3.3 8B instruct and Granite 4.2 8B model cards. `https://huggingface.co/ibm-granite`. Granite 3.3 card: `https://huggingface.co/ibm-granite/granite-3.3-8b-instruct`.

Maurice Jakesch, Jeffrey T. Hancock, and Mor Naaman. 2023. Human heuristics for AI-generated language are flawed. *Proceedings of the National Academy of Sciences*, 120(11):e2208839120.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7B. *Preprint*, arXiv:2310.06825.

Yang Jiang, Jiangang Hao, Michael Fauss, and Chen Li. 2024. Detecting ChatGPT-generated essays in a large-scale writing assessment: Is there a bias against non-native English speakers? *Computers & Education*, 217:105070.

Tom S. Juzek and Zina B. Ward. 2025. Why does ChatGPT "delve" so much? Exploring the sources of lexical overrepresentation in large language models. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 6397–6411, Abu Dhabi, UAE. Association for Computational Linguistics.

Lindsay Katz and Rohan Alexander. 2023. Digitization of the Australian Parliamentary Debates, 1998–2022. *Scientific Data*, 10(1):567.

Lindsay Katz and Rohan Alexander. 2025. A new, comprehensive database of all proceedings of the Australian Parliamentary Debates (1998–2025). Zenodo dataset, `https://doi.org/10.5281/zenodo.17351233`.

Farhan Kamrul Khan, Hazem Ibrahim, Nouar AlDahoul, Talal Rahwan, and Yasir Zaki. 2026. Who gets seen in the age of AI? Adoption patterns of large language models in scholarly writing and citation outcomes. *Journal of Informetrics*, 20(4):101869.

Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. 2024. Understanding the effects of RLHF on LLM generalisation and diversity. In *International Conference on Learning Representations*, pages 20620–20653.

Dmitry Kobak, Rita González-Márquez, Emőke-Ágnes Horvát, and Jan Lause. 2025. Delving into LLM-assisted writing in biomedical publications through excess vocabulary. *Science Advances*, 11(27):eadt3813.

Kalpesh Krishna, Yixiao Song, Marzena Karpinska, John Wieting, and Mohit Iyyer. 2023. Paraphrasing evades detectors of AI-generated text, but retrieval is an effective defense. In *Advances in Neural Information Processing Systems 36*, NeurIPS 2023, pages 27469–27500. Neural Information Processing Systems Foundation, Inc. (NeurIPS).

Keigo Kusumegi, Xinyu Yang, Paul Ginsparg, Mathijs de Vaan, Toby Stuart, and Yian Yin. 2025. Scientific production in the era of large language models. *Science*, 390(6779):1240–1243.

Aron Lee. 2026. An LLM-associated register shift in Korean journal abstracts: A morphology-aware excess-vocabulary study, 2018–2026. *Preprint*, arXiv:2609.07447.

Yafu Li, Qintong Li, Leyang Cui, Wei Bi, Zhilin Wang, Longyue Wang, Linyi Yang, Shuming Shi, and Yue Zhang. 2024. MAGE: Machine-generated text detection in the wild. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 36–53, Bangkok, Thailand. Association for Computational Linguistics.

Weixin Liang, Zachary Izzo, Yaohui Zhang, Haley Lepp, Hancheng Cao, Xuandong Zhao, Lingjiao Chen, Haotian Ye, Sheng Liu, Zhi Huang, Daniel McFarland, and James Y. Zou. 2024a. Monitoring AI-modified content at scale: A case study on the impact of ChatGPT on AI conference peer reviews. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 29575–29620. PMLR.

Weixin Liang, Mert Yuksekgonul, Yining Mao, Eric Wu, and James Zou. 2023. GPT detectors are biased against non-native English writers. *Patterns*, 4(7):100779.

Weixin Liang, Yaohui Zhang, Mihai Codreanu, Jiayu Wang, Hancheng Cao, and James Zou. 2025. The widespread adoption of large language model-assisted writing across society. *Patterns*, 6(12):101366.

Weixin Liang, Yaohui Zhang, Zhengxuan Wu, Haley Lepp, Wenlong Ji, Xuandong Zhao, Hancheng Cao, Sheng Liu, Siyu He, Zhi Huang, Diyi Yang, Christopher Potts, Christopher D. Manning, and James Y. Zou. 2024b. Mapping the increasing use of LLMs in scientific papers. In *First Conference on Language Modeling*.

Cong William Lin and Wu Zhu. 2025. Divergent LLM adoption and heterogeneous convergence paths in research writing. *Preprint*, arXiv:2504.13629.

LMSYS. 2023. Vicuna-7B v1.5 model card. https://huggingface.co/lmsys/vicuna-7b-v1.5. Release month from https://github.com/lm-sys/FastChat: August 2023.

Philip M. McCarthy and Scott Jarvis. 2010. MTLD, vocd-D, and HD-D: A validation study of sophisticated approaches to lexical diversity assessment. *Behavior Research Methods*, 42(2):381–392.

Meta. 2024. Llama 3.1 model card. https://github.com/meta-llama/llama-models/blob/main/models/llama3_1/MODEL_CARD.md.

Microsoft. 2024. Phi-4 model card. https://huggingface.co/microsoft/phi-4.

Mistral AI. 2024. Mistral-7B-Instruct-v0.3 model card. https://huggingface.co/mistralai/Mistral-7B-Instruct-v0.3. Release month from the repository history: May 2024.

Alberto Muñoz-Ortiz, Carlos Gómez-Rodríguez, and David Vilares. 2024. Contrasting linguistic patterns in human and LLM-generated news text. *Artificial Intelligence Review*, 57(10):265.

OpenAI. 2023. GPT-4 technical report. *Preprint*, arXiv:2303.08774.

OpenAI. 2025. gpt-oss-120b & gpt-oss-20b model card. *Preprint*, arXiv:2508.10925.

Vishakh Padmakumar and He He. 2024. Does writing with language models reduce content diversity? In *International Conference on Learning Representations*, pages 642–669.

Hyeonchu Park, Gahye Jeong, and Bugeun Kim. 2026. Style as a confound: False positives in AI detection of non-native academic writing. *Preprint*, arXiv:2608.26710.

Krishna Pillutla, Swabha Swayamdipta, Rowan Zellers, John Thickstun, Sean Welleck, Yejin Choi, and Zaid Harchaoui. 2021. MAUVE: Measuring the gap between neural text and human text using divergence frontiers. In *Advances in Neural Information Processing Systems*, volume 34, pages 4816–4828. Curran Associates, Inc.

Xiao Pu, Jingyu Zhang, Xiaochuang Han, Yulia Tsvetkov, and Tianxing He. 2023. On the zero-shot generalization of machine-generated text detectors. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 4799–4808, Singapore. Association for Computational Linguistics.

Qwen Team. 2025. Qwen3-8B model card. https://huggingface.co/Qwen/Qwen3-8B. Release month from https://qwenlm.github.io/blog/qwen3/: April 2025.

Qwen Team. 2026. Qwen3.5-9B model card. https://huggingface.co/Qwen/Qwen3.5-9B.

Swati Rallapalli, Shannon Gallagher, Ronald Yurko, Tyler Brooks, Chuck Loughin, Michele Sezgin, and Violet Turri. 2026. Interpretable stylistic variation in human and LLM writing across genres, models, and decoding strategies. *Preprint*, arXiv:2604.14111.

Alex Reinhart, Ben Markey, Michael Laudenbach, Kachatad Pantusen, Ronald Yurko, Gordon Weinberg, and David West Brown. 2025. Do LLMs write like humans? Variation in grammatical and rhetorical styles. *Proceedings of the National Academy of Sciences*, 122(8):e2422455122.

Vinu Sankar Sadasivan, Aounon Kumar, Sriram Balasubramanian, Wenxiao Wang, and Soheil Feizi. 2025. Can AI-generated text be reliably detected? Stress testing AI text detectors under various attacks. *Transactions on Machine Learning Research*.

Chantal Shaib, Yanai Elazar, Junyi Jessy Li, and Byron C Wallace. 2024. Detection and measurement of syntactic templates in generated text. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6416–6431. Association for Computational Linguistics.

Ilia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. 2024. AI models collapse when trained on recursively generated data. *Nature*, 631(8022):755–759.

Zhivar Sourati, Farzan Karimi-Malekabadi, Meltem Ozcan, Colin McDaniel, Alireza Ziabari, Jackson Trager, Ala N. Tak, Meng Chen, Fred Morstatter, and Morteza Dehghani. 2026. The shrinking landscape of linguistic diversity in the age of large language models. *Nature Human Behaviour*.

Mingjie Sun, Yida Yin, Zhiqiu Xu, J. Zico Kolter, and Zhuang Liu. 2025a. Idiosyncrasies in large language models. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 57854–57885. PMLR.

Zhen Sun, Zongmin Zhang, Xinyue Shen, Ziyi Zhang, Yule Liu, Michael Backes, Yang Zhang, and Xinlei He. 2025b. Are we in the AI-generated text world already? Quantifying and monitoring AIGT on social media. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 22975–23005. Association for Computational Linguistics.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, and 49 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *Preprint*, arXiv:2307.09288.

Fan Wu, Emily Black, and Varun Chandrasekaran. 2025. Generative monoculture in large language models. In *International Conference on Learning Representations*, pages 33068–33107.

Hiromu Yakura, Ezequiel Lopez-Lopez, Levin Brinkmann, Ignacio de la Serna, Lara Kirfel, Prateek Gupta, Ivan Soraperra, Thomas F. Eisenmann, Dirk U. Wulff, and Iyad Rahwan. 2026. Empirical evidence of large language model's influence on human spoken communication. *Preprint*, arXiv:2409.01754v4.

Zini Yang, Emily Wenger, and Richard So. 2026. Where models converge and humans diverge: A coverage framework for distributional pluralism in open-ended generation. *Preprint*, arXiv:2608.05576.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems*, volume 36, pages 46595–46623. Curran Associates, Inc.

A Deviations from the analysis plan

The plan was committed to version control before any result was computed (commit `ef4fa21`); it was never frozen with a third party. (1) arXiv was sampled through the API with a stratified design instead of full harvesting; the first sampler truncated large windows and was replaced (only the second is used); pre-ChatGPT papers revised after ChatGPT are excluded. (2) PERSUADE 2.0 replaced ELLIPSE, which could not be obtained; the essays of Liang et al. (2023) (TOEFL, US 8th-grade and US college) are a different genre and are used only for out-of-genre checks: the perplexity replication and the style check below. The style instrument places 34.1% of TOEFL, 5.7% of 8th-grade and 51.4% of college essays in the PERSUADE-defined region, which shows how genre-specific the region is. (3) Phi-4, Granite and the 2026 model were chosen after an arXiv pilot on partial data and before the first review. A preliminary arXiv run without the 2026 model was committed two minutes before its prompt batches and nine minutes before its texts were merged; the pilot may have informed this choice. Phi-4 and Granite were first used after the first review. Before any Hansard result, a bug in the speech identifiers was fixed (the corpus field we first used as a speech identifier identifies the speaker); an essay pilot on partial generations changed no analysis choice. RAID enters the main region only through its chat models, and each generator is capped at

450 training texts. (4) Added after the first review: LaTeX and encoding normalisation, grouped calibration, generator-set, drift, math, topic, length and dash analyses, the proficiency adjustment, the perplexity instrument and the dispersion measure. (5) Added after the second review: the vintage analysis with Llama-2-Chat 7B and Vicuna 7B; the three 2026 open models (Qwen3.5, Gemma 4, Granite 4.2), added after the single-generator pattern of the other 16 generators had been seen; mined marker words, the placebo grid, pre-trend variants, block bootstrap, further drift origins, Holm correction and the computer science vs mathematics contrast, length-fixed dispersion and GPT-2 perplexity, the event study and the implied-prevalence calculation; a cleaning fix (whole "Title:" lines in LLM outputs are dropped), after which every analysis was re-run. (6) Added after the third review: a second cleaning fix (keyword lines, word-count notes and inline labels), again with a full re-run; quarterly single-generator series, seed ranges and intervals for the 2026 changes, drift placebos for the pre-ChatGPT-data region, a 30-month placebo grid, a never-revised check, feature-family ablations, field-specific detection rates and a zero-shot detector baseline. The rank correlation of release date with the 2025-to-2026 change was computed before the one with the peak quarter; it is 0.67 on annual means but 0.18 ($p = 0.464$) when the change is measured from 2025Q4. Added after a pre-release methods audit: summary-style RAID outputs are also dropped from the single-generator regions (they had been dropped only from the pre-ChatGPT-data region), with the vintage analyses re-run; the post-trend fit to June 2025, fixed field weights, the document bootstrap of peak quarters, generator-side subsamples, tied RAID release months, the peak correlation without the 2026 open models, across training draws, under length or field weights, and given output length, with equal training sizes, the gradient-boosted-trees trend gap, and the cutoff and marker-peak comparisons. (7) The self-test of the paper's own text and the plan's arXiv embedding instrument were dropped. (8) The plan named cs.CL for one comparison; all of cs is used. The June 2025 evaluation month was fixed in code, not in the plan. Hansard was restricted to 2015–2025. H5 was not supported.

B Top features

Table 3 lists the ten largest positive and negative coefficients of the primary arXiv instrument.

LLM-typical	coef.	Human-typical	coef.
MTLD lexical diversity	1.30	dependency conj	−0.49
POS trigram DET_NOUN_VERB	0.60	dependency amod	−0.48
punctuation ,	0.53	word *by*	−0.44
word *that*	0.45	sentence length (mean)	−0.42
dependency det	0.39	word *are*	−0.41
dependency advcl	0.36	dependency aux	−0.41
POS trigram DET_VERB_NOUN	0.33	word *is*	−0.39
POS trigram NOUN_VERB_SCONJ	0.32	dependency ROOT	−0.35
POS trigram PUNCT_PRON_NOUN	0.32	dependency advmod	−0.34
word *these*	0.30	dependency compound	−0.33

Table 3: Largest standardised coefficients of the primary arXiv instrument (logistic regression, 14 generators).

C Held-out-generator recall

Held-out generator	Recall (%)	arXiv MSO (%)
2026 model (Claude Opus 5.5)	20.7	20.6
gpt-oss 20B	65.6	20.8
Qwen3 8B	76.4	22.8
Llama 3.1 8B	83.1	22.6
Mistral 7B v0.3	87.8	23.4
Phi-4 14B	88.9	22.7
Gemma 3 12B	90.0	23.1
Granite 3.3 8B	91.3	22.9
Cohere command (RAID)	59.6	23.4
Mistral-7B-Instr. v0.1 (RAID)	83.9	23.1
Llama-2-Chat 70B (RAID)	91.1	22.8
ChatGPT (RAID)	93.3	23.1
MPT-30B-chat (RAID)	94.6	23.0
GPT-4 (RAID)	95.6	23.3

Table 4: Recall on each generator when it is held out of training, and the resulting MSO of all scored arXiv abstracts (2015–2026; 22.8% with all 14 generators).

D Zero-shot detector

We computed the analytic Fast-DetectGPT criterion (Bao et al., 2024) with GPT-2 small as both sampling and scoring model, calibrated it isotonically on 1,500 pre-ChatGPT human and 1,500 LLM training abstracts, and flagged documents at a calibrated probability of 0.5. It separates the two classes poorly (AUC 0.737). On 600 scored abstracts per year its flag rate was 8.3% in 2015, 11.3% in 2022 and 5.3% in 2026, so it does not track the shift. The larger scoring models of the original method might do better.

E Single-generator peaks

Table 5 gives each single-generator region's peak quarter with its bootstrap range, and the stability

of its 2025-to-2026 change. Overlap peaked between 2024Q3 and 2025Q3 under the 2023 models other than Cohere's, in 2025Q2–Q3 under the 2024 models, in 2025Q4 under Gemma 3, Granite 3.3, Qwen3 and Gemma 4, and in 2026Q1–Q2 under gpt-oss, Qwen3.5 and Granite 4.2; under the 2026 model it was still rising in the last observed quarter, 2026Q3. Each annual change has a document-bootstrap interval that excludes zero and keeps its sign across all training draws and subsamples, except under Gemma 4. On the 9 generators with a stated pretraining cutoff, cutoff and release date order the peaks about equally well (rank correlations 0.59 and 0.62), so we cannot separate the recency of post-training from that of pretraining data. Subsets of the pre-ChatGPT-data region point the same way as the region but differ in size: the RAID models alone give 7.3 pp (8.6 with summary-style outputs kept, 7.4 with ChatGPT added and summaries kept). Measured from 2025Q4 instead of on annual means, only gpt-oss, Granite 4.2, the 2026 model and, barely, Qwen3.5 (+0.4 pp) rose.

F Field results

Figure 3 shows the pre-ChatGPT baseline and the June 2025 trend gap for each field. *Implied prevalence.* Using held-out-generator recall, the implied 2024 shares of §6.3 become 44.4% (computer science) and 8.2% (mathematics). Liang et al. (2024b) estimate 17.5% and 4.9% of abstract sentences by February 2024, the same ordering at lower levels. Implied shares overstate LLM output if partly revised documents enter the region or authors adopt LLM style without an LLM, which the identity cannot tell apart; lower recall in mathematics (75.8% vs 85.8%) would raise its share.




Figure 3: Left: pre-ChatGPT MSO by arXiv field (n of pre-ChatGPT scored abstracts). Right: trend gap in June 2025. Lines are 95% intervals. The baseline is only loosely related to the gap.

G Parliamentary speech

The Hansard trend gap is small and not significant at the primary threshold (1.3 pp, CI −0.7 to 3.4; Figure 1b), about 0.2 times as large as its extrapolated trend value, against 2.1 times for abstracts (0.21 against 1.47 on the logit scale). With the arXiv region rebuilt from the eight generators used for Hansard (arXiv gap 32.1 pp), the difference between the genres is 30.7 pp (CI 28.3–33.2). The Hansard gap is 1.4 pp at threshold 0.6 (CI −0.1 to 2.9), and its nonparametric gap ranges from −3.2 to 3.1 pp across pre-trend specifications. Of its placebo breaks, 23.5% give $p < 0.05$, and the 2022 change of government altered the speaker population six months before ChatGPT. Published marker words also rose in speeches (1.6 pp above trend, CI 0.4–2.8), close to the arXiv marker gap (1.9 pp), so the genres differ in style overlap more than in marker words. We read Hansard as showing no clear change in parliamentary speech, not as a validated control.

H Dispersion

To connect overlap to homogenisation we measured, for each year, the mean Euclidean distance of abstracts to the year's centroid in the feature space standardised on pre-ChatGPT abstracts. On all abstracts, dispersion falls steadily from 34.20 in 2015 to 30.86 in 2026, but abstracts also grew longer, and per-token rates are less noisy in longer texts. With every abstract cut to its first 150 words (abstracts of at least 150 words, 1,200 per year), dispersion declines slowly before ChatGPT (−0.11 per year) and in 2025 lies 0.05 above that trend (bootstrap CI −0.36 to 0.51). The interval

Generator	Peak	80% range	Recurs (%)	2025→26	95% CI	Seeds	Subsamples
GPT-4	2025Q3	2025Q1–2025Q4	33.8	−3.6	−4.5 to −2.6	5/5	10/10
ChatGPT	2025Q1	2025Q1–2025Q2	81.7	−5.1	−5.9 to −4.4	5/5	10/10
MPT-30B-chat	2025Q1	2025Q1–2025Q2	71.4	−3.6	−4.3 to −2.7	5/5	10/10
Llama-2-Chat 70B	2025Q2	2025Q1–2025Q2	59.5	−5.5	−6.4 to −4.7	5/5	10/10
Llama-2-Chat 7B	2025Q1	2024Q3–2025Q2	69.7	−5.2	−6.0 to −4.4	5/5	10/10
Vicuna 7B v1.5	2024Q3	2024Q3–2025Q1	71.1	−2.6	−3.1 to −2.1	5/5	10/10
Mistral-7B-Instr. v0.1	2025Q1	2025Q1–2025Q3	75.7	−5.4	−6.2 to −4.5	5/5	10/10
Cohere command	2023Q2	2023Q2–2024Q3	54.9	−3.0	−3.7 to −2.4	5/5	10/10
Mistral 7B v0.3	2025Q3	2025Q2–2025Q4	49.8	−4.6	−5.6 to −3.6	5/5	10/10
Llama 3.1 8B	2025Q2	2025Q1–2025Q3	44.8	−5.0	−6.0 to −4.0	5/5	10/10
Phi-4 14B	2025Q2	2025Q2–2025Q3	73.8	−4.3	−5.1 to −3.4	5/5	10/10
Gemma 3 12B	2025Q4	2025Q3–2026Q1	46.5	−2.0	−3.1 to −0.9	5/5	10/10
Granite 3.3 8B	2025Q4	2025Q3–2025Q4	60.6	−2.6	−3.7 to −1.7	5/5	10/10
Qwen3 8B	2025Q4	2025Q2–2025Q4	42.8	−3.7	−4.6 to −2.7	5/5	10/10
gpt-oss 20B	2026Q2	2026Q2	94.4	9.0	7.8 to 10.2	5/5	10/10
Qwen3.5 9B	2026Q1	2026Q1–2026Q2	80.6	2.4	1.3 to 3.3	5/5	10/10
Gemma 4 12B	2025Q4	2025Q4–2026Q1	67.8	−0.9	−1.8 to 0.1	4/5	10/10
Granite 4.2 8B	2026Q2	2026Q1–2026Q2	76.8	7.4	6.4 to 8.5	5/5	10/10
2026 model	2026Q3	2026Q3	91.6	9.9	8.7 to 11.0	5/5	10/10

Table 5: Quarter of peak MSO with the region defined by one generator (title-only task; generators in order of release). 80% range and Recurs: 10th–90th percentile of the peak quarter and share of draws in which the observed peak recurs, over 1,000 document bootstraps within quarters; for the 2026 model the peak is the last observed quarter. 2025→26: annual change (pp), with its 95% document-bootstrap interval. Seeds and Subsamples: training draws (of 5, including the estimate's own; for RAID models the 450 generator texts are redrawn too) and refits on 80% of the generator's texts (of 10) whose change has the same sign as the estimate.

excludes an extra decline larger than about three years of the pre-ChatGPT trend, so any faster loss of stylistic spread is small next to the shift towards the LLM region. Diversity of content or ideas may behave differently (Padmakumar and He, 2024; Doshi and Hauser, 2024).

I Learner essays

Our analysis plan predicted that essays by English-language learners would show *higher* MSO. They show lower: 2.3% vs 4.2% (15 of 666 learner essays in the region; odds ratio adjusted for prompt and grade 0.55, CI 0.32–0.95; lower, and significant at $p < 0.05$, in all 10 training draws). Most of the difference is proficiency: adding the holistic essay score reduces the odds ratio to 0.87 (CI 0.50–1.52) and the continuous classifier margin from -0.37 to -0.12 standard deviations (CI -0.21 to -0.03). In essays the LLM region is largely a region of fluent, lexically diverse writing. The other instruments agree in direction (Figure 4). Sentence embeddings flag 5.3% of learner and 10.0% of other essays. Perplexity under GPT-2 separates human from LLM essays less well than style features (AUC 0.830 against 0.988), so it flags 29.2% of all human essays. It flags 15.5% of learner vs 30.6% of other essays (odds ratio 0.47; 0.66, CI 0.52–0.85, after adjusting for proficiency), because these learners' essays are *less* predictable (mean token log-perplexity 3.74 vs 3.43). The same GPT-2 instrument reproduces the bias reported by Liang et al. (2023) on their data: it flags 63.7% of TOEFL essays by non-native test-takers, which are highly predictable (3.07), but 8.0% of US 8th-grade essays (3.72); Qwen2.5-0.5B gives the same pattern (41.8% vs 3.4%). GPT-2's training data predate the public release of the TOEFL essays (and PERSUADE), so that contrast is unlikely to come from memorised test essays, although the 8th-grade essays derive from data public since 2012. The TOEFL essays are predictable and the PERSUADE learners' essays are not, so which learners such a detector flags depends on the population, consistent with detectors that showed no bias in a large writing assessment (Jiang et al., 2024). The TOEFL and 8th-grade sets also differ in genre, prompt, age and length.




Figure 4: Share of held-out pre-ChatGPT student essays flagged by three instruments, by ELL status (ELL $n = 666$, non-ELL $n = 6{,}758$; lines: 95% bootstrap intervals). Levels differ across instruments; all flag learner essays less often.