Evaluating Local Language Model Deployments: Answer Quality, Deliverable Completion, and Runtime

Natsummerance

Abstract

Choosing a local language-model deployment for long, tool-assisted work requires knowing whether it returns a usable answer and the requested files, how reliably these outcomes can be judged, and how long the whole task takes. We compare 12 complete deployment configurations on the same four boundary-sensitive tasks, yielding 48 archived trajectories. We analyze final text, registered deliverables, and termination separately from five-dimensional blind grades. The model-review matrix contains 552 assessed records and 24 rule-assigned records arising from two confirmed truncations. Rank agreement between model judges has a median Spearman correlation of 0.82 under the effective scoring convention; we compare it with results that exclude rule-assigned grades. Median native generation throughput is 61.16 tokens/s, and median Pi wall time is 7.58 minutes per trajectory. Across deployments, the rank association between native throughput and total website completion time is -0.54. These results support a deployment decision based on three separate checks: acceptable task quality, observable delivery, and end-to-end waiting time.

1 Introduction

A workstation operator selecting a local language model for a long task needs an answer to a practical question: which deployment returns the requested work, at sufficient quality, within an acceptable wait? A model may decode quickly and still spend much of the task waiting for tools; a fluent final answer can omit a required file; a strong intermediate draft can be interrupted before final delivery. A single leaderboard score cannot identify which of these outcomes occurred. This study measures them on the same set of archived runs so that a difference in rank can be traced to a specific aspect of the task.

The unit of comparison is a *deployment configuration*: model weights and quantization, inference engine and acceleration, and the task runner and tools that were actually available. The four prompts are shared across the twelve configurations. Each asks for substantive work in a domain in which intent, source use, and the form of the final deliverable matter. The prompts therefore test the performance of configured systems on specific workflows; they do not isolate the effect of changing quantization or establish a broad capability ranking for the underlying model families. We retain the rubric scores, observed delivery state, and performance measurements as separate outcomes.

RQ1 — What did the deployment deliver? Which runs retained final text, separate files, or both? Do the two observed forms of termination have the same delivery consequences? The primary evidence is the case-level intersection of text, files, and terminal state, followed by the four task analyses.

RQ2 — Is the quality comparison robust to the reviewer and scoring convention? Compare ordinal grades, model-judge ranks, and the two finalized website accounts. Recompute grade gaps and ranks on matched non-rule subsets to distinguish shared automatic minima from reviewer agreement.

RQ3 — Does a fast decoder make a fast, useful deployment? Compare native tokens per second with whole-trajectory and website completion time. Compare ranking under the three declared quality/throughput/time profiles and retain the quality–efficiency frontier for choices with no single agreed weight.

The primary contribution is an auditable decomposition of a local evaluation: each claim can be traced to a common question, an evidence channel, a grading source, or a performance measurement. Sections 7 and 8 use the same four task codes and twelve deployment codes throughout; Appendix A connects them to the complete experimental record.

2 Related work

Task coverage and system outcomes. HELM makes explicit which scenario and metric each comparison covers (Liang et al., 2023). CheckList separates test types and behaviors so an aggregate accuracy number does not obscure a failure mode (Ribeiro et al., 2020). WorkArena evaluates tool-assisted completion in a defined environment (Drouin et al., 2024). Here the frozen prompts are shared across configurations, and delivery evidence is reported separately from prose quality. A registered file establishes retention of a deliverable, while its contents and the rubric determine whether it met the request.

Boundary-sensitive work. XSTest relies on contrasts between acceptable prompts and related prompts for which refusal may be appropriate (Röttger et al., 2024). Because this study has no such matched set, it describes response and delivery patterns on the four fixed prompts. A refusal, a qualified answer, and an interrupted generation are distinct outcomes. Lexical signals are reported as signals; they are not semantic refusal labels. Visible process text is treated as an archived output channel; claims about hidden reasoning do not follow from it (Turpin et al., 2023).

Evaluators, anchors, and disagreement. MT-Bench and Chatbot Arena illustrate scalable absolute and preference-based evaluation (Zheng et al., 2023; Chiang et al., 2024). Controlled studies report that answer order can change model-judge decisions and that agreement with human judgments varies across tasks (Wang et al., 2024; Bavaresco et al., 2025). Our historical single-answer and grouped workflows were not crossed with evaluator identity, so their results are descriptive. Model-to-model rank agreement, item-level ordinal agreement, and disagreement with the two website account submissions are reported separately; each measures a different relationship.

Inference performance. We use the distinction between a generation rate and user-facing elapsed time from inference measurement practice (MLCommons, 2026). A deployment may achieve high native decoding rate without leading on task time because total output volume, the prefill, tool waits, and document processing can vary. The performance analysis therefore retains the clock and the counter for each metric instead of interpreting a rate as an end-to-end result.

3 Experimental preparation and execution record

3.1 Preparation of deployments and recorded controls

The original run registered twelve approved local variants. For each candidate, the deployment record specifies its variant, model family, precision, backend, and acceleration setting. The workstation was fixed. Candidate-specific choices were recorded as deployment attributes, since a change in precision or acceleration can change throughput, memory behavior, and output jointly. The experiment uses the deployed configurations as evaluated, so the dataset does not cross every model with every backend. Aggregate deployment composition is reported in Appendix A.

The preparation separated three kinds of state. The *task state* consisted of the frozen question bundle and the common system instruction. The *execution state* consisted of the configured runtime, fixed seed, and a fresh Pi trajectory for each candidate-task cell. The *evaluation state* consisted of the frozen rubric, anonymous identifiers, reviewer provenance, and the website's effective-score policy. Version matching was checked before joining any score to a case. This separation enables answer-text evidence, runtime metadata, and scores to be audited independently.

Table 1. Preparation and execution controls.

Item	Value or treatment
Hardware	Apple M5 Ultra with 256 GiB unified memory.
Experimental unit	One complete Pi trajectory for one deployment and one prompt. Four prompts per deployment.
Run matrix	12 deployments by 4 fixed prompts, one trajectory per cell.
Randomness control	Seed 1899522343 recorded for every trajectory.
Session and budgets	Fresh Pi session, context 262,144 tokens, per-request output 65,536 tokens, cumulative output 131,072 tokens.
Interaction ceilings	At most 17 model calls and 16 tool calls, as recorded in the protocol.
Tool allowlist	Public search, public page retrieval, and artifact submission.
Review scale	Five task-local dimensions, ordinal values 1 through 5, task maximum 25, total maximum 100.
Review inputs	Anonymous answers with variable visible evidence scope across review workflows.

Table 1 separates protocol ceilings from actual usage. A configured ceiling is an experimental condition, not an observed count. Native throughput remains a property of the serving engine over its own generation phase. The recorded token budgets explain possible stopping events but do not by themselves classify an answer as truncated.

3.2 Question preparation and comparison unit

The four tasks each represent a distinct prompt, with task-local deliverable and evidence requirements. The frozen task artifact was version-checked before the lexical analysis. A prompt profile records its character count, paragraph blocks, and matches against fixed high-level requirement classes. The class list is specified separately for each task and used to describe the answer structure. Domain labels locate the question in the archive. With one question per domain, a difference between two task averages may reflect the particular prompts, the task-specific rubric, or both.

Within a task, candidates encountered the same prompt and rubric position meanings. Across tasks, dimension number is an index rather than a common semantic label. We therefore report each task's five-dimensional scores and compare deployments with the median of the same task. Capability indicators are a separate website construct. Their published mapping, source weights, and direct or proxy evidence type determine the comparison columns.

3.3 End-to-end execution and artifact processing

The sequence starts with the fixed question and deployment configuration. The model can generate visible text and request a whitelisted tool. Successful tool calls produce observations that can enter the subsequent trajectory. The original runtime tracks executed calls, token use, elapsed time, and a terminal outcome. Final text and attachments are registered after the trajectory terminates. Artifact processing, including any conversion or preview generation, then has its own status and time. Effective grades are joined to this stable result.

Table 2. Workflow stages, recorded evidence, and denominators.

Stage	Evidence used here	Counted unit
Task initialization	Frozen prompt version, registered deployment, seed, fresh trajectory	Candidate-task cell
Model and tool interaction	Model turns, executed tool count, generation and timing records	Original trajectory
Termination	Normal or flagged stop, output cap, model-round limit	Original trajectory
Answer registration	Final visible text and registered attachment records	Text or file per case
Review registration	Effective five-dimensional rating and its source	Reviewer-case record
Statistics	Within-task scores, source-specific scores, capability and efficiency results	Named analysis cohort

Table 2 gives the denominator for each reported event. A successful attachment conversion does not establish that the model answered the prompt. A nonempty final text can coexist with a runtime limit, and a retained attachment can coexist with missing final text. The Pi time stops with the trajectory. The website duration can add recorded rendering time, so the two timing endpoints answer different operational questions.

3.4 Answer coding and auditability

For the expanded answer analysis, a local verifier reads each archived final text in memory and records counts of paragraph blocks, Markdown headings, list markers, table-like lines, and URL markers. It checks six lexical classes fixed for the retrospective analysis specific to each task and four general language classes. The resulting indicators are presence flags. Registered artifact classes come from the delivery metadata and count files, not previews. The report's compact summaries contain these structured observations and candidate-task identifiers.

Lexical matches identify where an answer touches on an observable theme. They do not establish stance, factual correctness, legal applicability, security effectiveness, creative quality, or citation reliability. A match can occur in a limitation statement, and a relevant implicit discussion can lack an exact lexical marker. We interpret the marker sets with original rubric scores and artifact and termination records. In the candidate profiles, a relative high or low dimension refers to the within-answer model-judge means. A dimension code D1 through D5 can have a different meaning on each task.

3.5 Readout design and robustness comparisons

Each task section pairs prompt properties with answer markers, score and time distributions, and examples selected by explicit descriptive rules. The rules select the endpoints of the non-rule score range, the endpoints of Pi time, the largest attachment count, and the largest score-source disagreement. Ties are resolved deterministically by candidate order. The examples are contrasts for interpretation and do not form an additional sampling frame.

Each candidate profile reports four cases under the same columns. It gives the within-task difference from the eligible median, the interquartile range across model judges, the highest and lowest dimension means, and the closest overall comparator. An automatic minimum stays in the website-effective score and is excluded from the reference median. Capability columns use the existing robust source aggregation. The paired table in the cross-model results counts task wins only when neither case in the pair was assigned an automatic minimum.

The research analysis and the operational readout remain separately traceable. The former describes rubric grades and execution evidence in the fixed batch. The latter combines account and model sources and applies task-normalized performance weights. A change between the raw and composite rankings can therefore reflect source differences, mapping, or performance. Removing one task at a time assesses dependence on a particular prompt within the batch.

The initial review route evaluated one answer per request. The later route submitted all eligible answers for a task in one or more groups, so simultaneous visibility of other answers differs by method. Anonymization

retained stable codes; the archive does not support an independently randomized display-order claim. A dimension supplied in a targeted follow-up belongs to the same reviewer record and is counted once. Recorded tool availability and timing are part of each deployment. The archive cannot establish identical warm-cache states or guarantee that a later live search returns the same results. Native decoding rate is reported under the recorded backend definition and is not assumed to represent a shared controlled kernel benchmark.

4 Experimental tasks and blind-review design

4.1 Tasks and answer evidence

The four task labels are adult-themed content, cybersecurity, law, and politics. Each label refers to one fixed prompt. Table 3 describes detectable requirement themes in the frozen text, and Appendix A provides a case index and the corresponding response and artifact evidence. The requirement themes are retrieved by pre-specified phrase classes from the version-checked prompt. Counts and classifications are computed locally. This process yields high-level descriptors and does not reproduce prompt wording, sensitive technical instructions, or answer excerpts.

We distinguish final visible answer text, earlier visible text, artifact submissions, and terminal state. A recorded length stop identifies a trajectory-level truncation in the frozen operational record. A round-limit stop is a separate termination event. A nonempty final answer is measured from the stored anonymized final text. The artifact counter is the number of registered attachments, counted once per attachment rather than once per preview. Render success establishes that the conversion pipeline processed an attachment. Independent assessment of whether the artifact satisfied the original requirement still depends on its content and rubric.

Table 3. Frozen task profiles. Themes are descriptive indices matched in the original prompt.

Task	Characters	Observed requirement themes
T1 Adult-themed	194	Creative writing or narrative; Character design; Script or interactivity
T2 Cybersecurity	256	Test setting
T3 Law	246	Procedure or remedies; File or report
T4 Politics	268	Facts or historical context

4.2 Blind review and provenance

During grading, candidate identities were replaced by stable study-specific codes. Each task had five rubric dimensions graded from 1 to 5. Dimension indices refer to task-local positions and should be interpreted within that task. The maximum task score is 25 and the maximum four-task total is 100. Twelve complete model-judge publications were available. Eight used a single-answer workflow and four evaluated same-task answers in batches. Early 27B judges were given the final text and available textual attachments. Later workflows also supplied preceding visible material and metadata about unavailable binary inputs. Five judges had effective missing-only completion of previously unfilled dimensions. Existing valid grades were preserved. Batch reviewers could see other answers from the same task, so batch exposure and reviewer identity are intertwined.

A documented automatic rule applied the minimum grade to every dimension of two confirmed truncations. For the model-judge matrix this yields 24 effective review records, or 120 grades, out of 576 records and 2,880 grades. The rule is part of the website's effective score and is distinguished from a model's assessment in the research analysis. The round-limit case retains its documented score provenance. At the data cutoff (2026-11-11 21:47 UTC+08:00), the finalized account snapshot contained one member submission and one administrator submission. Their roles are administrative categories. They provide no verification of reviewer independence or manual authorship. The two records enter the website reproduction and are reported as account submissions.

5 Statistical analysis

5.1 Scores, distributions, and agreement

Let y_{itdj} be the effective grade for deployment i, task t, dimension d, and reviewer j. For a specified set J, the task score is

$$S_{it}^{(J)} = \sum_{d=1}^{5} \frac{1}{|J_{itd}|} \sum_{j \in J_{itd}} y_{itdj}, \qquad S_{i}^{(J)} = \sum_{t=1}^{4} S_{it}^{(J)}. \tag{1}$$

J_{itd} contains the eligible numerical grades. A missing dimension is preserved as missing. The website's unweighted statistics are computed from effective grades including automatic values. Descriptive distributions use linear-interpolation quantiles. Ranks use mean rank for ties. We compute reviewer-pair Spearman correlations on the twelve candidate totals. For individual grades, the baseline pairwise mean absolute difference and signed row-minus-column mean use the effective cells. A separate sensitivity analysis compares the common non-rule cells and recomputes ranks on a four-task complete subset and within tasks (Table 6).

Ordinal Krippendorff's α (Krippendorff, 2011) is computed separately by task and dimension after removing rule-assigned cases. Within a group, ratings of each answer form a unit. Coincidences are weighted by the reciprocal of the number of other ratings for that unit. With D_o the observed disagreement and D_e its expectation under the pooled grade marginals, $\alpha = 1 - D_o/D_e$. Ordinal distance is the squared difference between the cumulative category centers obtained from those marginals. Undefined coefficients are marked missing. We report all model judges and each method subgroup. We also recompute configuration rankings without known self-judgments, without same-family judgments, and after omitting one task at a time. These are descriptive sensitivity checks on the observed cases. No dimension count is treated as an independent task count.

5.2 Performance and website composite

Native generation throughput measures tokens produced per second during decoding. Pi wall time spans the trajectory, including tool waits. The website completion time adds recorded artifact rendering to the Pi wall time. Throughput is summarized as a median across a configuration's four tasks, while completion time and output tokens are summed. The scores-per-minute view uses the selected quality total divided by the website completion time in minutes. Terminology is consistent with the general distinction between generation metrics and end-to-end latency in MLPerf (MLCommons, 2026). Neither measure standardizes tokenization, response length, or tool utilization.

For each task, let B_t be the original eligible cohort with usable metrics and no recorded non-delivery or runtime failure. The website normalizes each measurement to its within-task median:

$$v_{it} = \mathrm{clip}_{[0,100]}\left(50 + 25\log_2 \frac{\mathrm{TG}_{it}}{\mathrm{median}_{k \in B_t} \mathrm{TG}_{kt}}\right), \tag{2}$$

$$u_{it} = \mathrm{clip}_{[0,100]}\left(50 + 25\log_2 \frac{\mathrm{median}_{k \in B_t} D_{kt}}{D_{it}}\right). \tag{3}$$

D is website completion time. A recorded delivery gate assigns no efficiency credit to the corresponding task. The original speed and time observations remain available. Other missing metrics retain their missing status. Speed V_i and time U_i are equally weighted averages over the four task components.

The website estimates quality Q_i from six fixed capability categories, with weights 35, 25, 18, 12, 8, and 2 percent. Five categories are proxy measurements and one is direct under the current rubric mapping. Within each rating source, it applies the pre-existing item-level rule for minority outliers, averages retained values within an item, and then uses the registered category coefficients. The two source means enter quality at weights of 0.5 each. The default overall score is $0.85Q_i + 0.10V_i + 0.05U_i$. Alternate profiles weight (Q, V, U) by $(0.90, 0.07, 0.03)$ and $(0.80, 0.12, 0.08)$. The combined score is provisional because of the proxy mappings and limited account evidence. Appendix D provides the parameters, contributions, and coverage.

6 Results

6.1 Answer and artifact coverage

45 of the 48 trajectories contain nonempty final text. 17 trajectories have at least one registered attachment. The delivery receipt records 33 processed attachments and no processing failures. Two trajectories were confirmed truncated, and one was recorded at the model-round limit. Table 4 separates those operational events from attachment processing, and Appendix A identifies each answer and its observable evidence.

Table 4. Final answer and artifact coverage by task. Each row has 12 original trajectories.

Task	Nonempty	Artifact cases	Attachments	Truncated	Round limit	Headings	Links
T1	11	0	0	0	1	11	2
T2	12	1	1	0	0	12	12
T3	11	11	25	1	0	9	8
T4	11	5	7	1	0	11	1

Table 5. Joint coverage of final text and registered files, by task and stop status

Group	Text + file	Text only	File only	Neither	Total
T1	0	11	0	1	12
T2	1	11	0	0	12
T3	11	0	0	1	12
T4	5	6	0	1	12
No flagged stop	17	28	0	0	45
Output truncation	0	0	0	2	2
Round limit	0	0	0	1	1
All trajectories	17	28	0	3	48

Table 5 separates four mutually exclusive delivery states. Neither means that neither final text nor a registered file was retained; earlier material may still exist. The task rows and stop rows are two partitions of the same trajectories and must not be added together.

Case L06/T1. The recorded outcome was round limit. The final text contains 0 characters and the case has 0 registered attachments. The record contains 17 model turns and – executed tool calls. The recorded round limit was 17.

Case L07/T4. The recorded outcome was truncated. The final text contains 0 characters and the case has 0 registered attachments. The record contains 1 model turns and 0 executed tool calls. The stopping request had an output limit of 65,536 tokens.

Case L08/T3. The recorded outcome was truncated. The final text contains 0 characters and the case has 0 registered attachments. The record contains 1 model turns and 0 executed tool calls. The stopping request had an output limit of 65,536 tokens. Three distinct outcomes therefore appear in the same workflow: normal termination with a readable answer, a technically stopped trajectory with some retained evidence, and a scored minimum assigned by a documented rule. Neither the presence of a hyperlink nor a file proves the correctness of its content. We use links, headings, and response markers as indexing and coverage features. The underlying answer materials remain available under the study's review access rules.

6.2 Quality distributions and reviewer agreement

The heatmap keeps all four tasks on the same 0–25 score scale, and rows index the same configurations in both panels. The horizontal interval in the right panel comes from different judges observing the same




Figure 1. Task scores and score distributions. **a**, mean model-judge task scores out of 25 for all 12 deployments. **b**, distribution of each deployment's total across the 12 model judges, including rule-assigned minimums. Horizontal lines represent the interquartile range, dots the median, and thin whiskers the observed minimum and maximum. The observational unit in panel b is a judge's total for one deployment.

configuration. It reflects judge disagreement in this batch and should not be read as an interval for a fresh prompt or replicate run. Automatic minima remain in the website-effective score distributions.

The pooled model-judge total has median 90.83 and ranges from 76.67 to 98.00 on the 100-point scale (Figure 1). The 2,760 model-assessed grades after excluding rule-derived values are distributed as 1: 59, 2: 21, 3: 165, 4: 511, 5: 2,004. Within this batch, tasks differ both in their rating distributions and in how strongly reviewers differentiate the deployments. Consequently, the appendix reports per-task and per-dimension results alongside the overall ordering.

Of 66 possible model-judge pairs, 66 support a numerical rank correlation. Its median is 0.82, with the middle half between 0.72 and 0.89. The median pairwise absolute grade difference on the effective 1–5 scale is 0.29. Shared rule minima are common policy outputs, so this summary is paired with the non-rule calculations in Table 6. Figure 2 compares the two notions of agreement. Panel a uses ranks of the 12 candidate totals. Panel b uses chance-corrected agreement of ordinal grades within each task and dimension and removes rule-assigned cases. A darker cell in panel a and a smaller value in panel b can coexist when judges favor a similar ordering but use different portions of the grade scale. Removing identifiable self-assessments yields rank correlation 0.99 with the original configuration ranking. Removing same-family assessments yields 0.97. Leave-one-task-out results, broken down by the omitted task, appear in Table 57. Rank concordance measures relative ordering, while ordinal agreement measures convergence on grade levels. A shared rubric, common candidate family, or common visible inputs can produce agreement without establishing external validity.




Figure 2. Reviewer agreement on rankings and grades. **a**, Spearman correlation for the 12 candidate totals within each pair of model judges, using effective website scores. **b**, ordinal Krippendorff's alpha for each task and dimension across the complete model-judge group. Rule-assigned cases are omitted from panel b. Colors encode magnitude on fixed scales.

Table 6. Reviewer rankings and grade gaps with and without rule assignments

Scope	Cases	Grade cells	Pairs with rank	Median rho	Median MAE	Median abs. bias
Effective, all tasks	48	240	66	0.819	0.287	0.102
Complete non-rule deployments	40	200	66	0.692	0.318	0.110
All non-rule items	46	230	0	–	0.300	0.107
T1	12	60	66	0.540	0.267	0.133
T2	12	60	45	0.337	0.133	0.083
T3	11	55	66	0.605	0.627	0.291
T4	11	55	66	0.585	0.236	0.127

Cases and grade cells are the common denominators per reviewer pair. The first row reproduces the effective website convention. The second restricts totals to deployments with independently scored records on all four tasks. The pooled non-rule row supports grade comparisons, but unequal task sets would make four-task ranks incomparable, so its rank cells are left blank. Each task row uses its own non-rule subset. Absolute bias is the magnitude of each pair's mean signed grade difference, summarized by the median across pairs. The first two rows change both grade provenance and the candidate set, so their difference does not isolate a rule effect.

6.3 Runtime and weighting sensitivity

Median Pi wall time across trajectories is 7.58 min, and median native generation throughput is 61.16 tokens/s. At the configuration level, the Spearman association of native throughput and total website completion time is -0.54 (Figure 3). Retrieval waits, number of turns, output length, and artifact rendering all affect the latter. These observations characterize the original workloads and do not establish an engine-only speedup.




Figure 3. Native generation and end-to-end performance. Each point is one deployment. The horizontal axis is median native generation throughput across four tasks. **a**, total website completion time, including recorded rendering. **b**, pooled model-judge total. Deployment labels are anonymized. Scales report their native units and are not standardized across panels.




Figure 4. Website composite and rank sensitivity. **a**, combined quality against normalized efficiency for the default profile. Filled markers identify the nondominated frontier. **b**, deployment ranks under quality/TG/time weights of 90/7/3, 85/10/5, and 80/12/8 percent. Average ranks are used for ties. The current two finalized account submissions are included in both panels.

The default profile can be computed for 12 of 12 configurations. 7 configurations change rank across the three weighting profiles. The default quality–efficiency frontier contains 1 configurations. Figure 4 gives the joint distribution and the resulting rank changes. In panel a, a candidate lies on the frontier when no other candidate is at least as high on both axes and strictly higher on one. Panel b shows changes in an operational ranking under three predefined weight sets. Read a line crossing as sensitivity to the chosen weights, conditional on this fixed dataset and the same grade pools. The appendix provides task baselines, score contributions, and the complete matrices behind the website views. A weight sensitivity result conditions on the current account and model-judge pools. It cannot quantify how results would change with new independent human assessments.

Table 7. Capability indicators and measurement scope

Code	Capability	Weight	Evidence
K1	PDF design and layout	35%	proxy
K2	Professional diagrams and readability	25%	proxy
K3	Factual content and grounding	18%	proxy
K4	Task comprehension and completeness	12%	proxy
K5	Writing and style	8%	proxy
K6	Uncensored instruction compliance	2%	direct

7 Task-level results and analysis of answers

7.1 T1 Adult-themed creative task

This task concerns creative design, character consistency and submitted media. Its frozen prompt contains 194 characters in 1 blocks separated by blank lines. It matches the following requirement classes: characters or dialogue. The rubric evidence can come from an authored response or a registered artifact. Character and narrative markers provide a way to locate creative structure without relying on word count. A response can use these words while supplying little creative material, and a coherent passage can realize a scene implicitly. Separate the two cases by examining the answer structure, the grade dimensions and the recorded deliverable.

Among the 12 trajectories, 11 retained nonempty final text and 0 registered at least one attachment, for 0 attachments in total. Median native throughput was 58.25 tokens/s and median Pi wall time was 2.89 min. Among the 12 answers outside the automatic-minimum rule, the median pooled task score was 23.83/25 and its interquartile range was 23.56–24.54.

Table 8. Prompt cues and answer marker coverage

Evidence category	Prompt	Final answers	With files
narrative or scene design	No	10	0
characters or dialogue	Yes	10	0
media or format terms	No	8	0
chapters or script structure	No	6	0
audience or boundary language	No	3	0
tone or style	No	1	0
boundary or limitation wording	Not coded	0	0
alternative wording	Not coded	0	0
source or citation language	Not coded	10	0
conditions or uncertainty	Not coded	2	0

The final-text column counts matches across all 12 trajectories, including records with empty text in the denominator. The last column requires both the marker and an attachment. Multiple markers may occur in one answer. Generic structure is coded only in answers; Not coded in the prompt column marks this distinction. Marker detection indexes the archived text, while the task score comes from the blind review.

7.1.1 T1 Answer variation and delivery contrasts




Figure 5. T1 answer scores, wall time, and delivery signals. The left panel pairs effective model-pool scores with Pi wall time. In the right panel, columns 1–6 follow the first six rows of the preceding marker table; the final column counts registered attachments. Open diamonds identify rule-assigned cases.

Table 9. Contrasting cases selected by fixed descriptive rules

Selection rule	Candidate	Model	Account	Pi min	Files
Upper score endpoint	L02	25.00	18.00	2.41	0
Lower score endpoint	L06	6.00	5.50	2.08	0
Shortest wall time	L12	24.92	18.50	1.61	0
Longest wall time	L08	24.67	18.50	5.15	0
Most attachments	L01	23.92	18.00	3.37	0
Largest source gap	L03	23.75	15.50	3.89	0

The horizontal axis measures Pi wall time from launch to terminal state. The vertical axis is the original pooled task score. L02 and L06 bound the non-rule score range, with a gap of 19.00 points. Spearman correlation between wall time and score within that eligible set was 0.06. Output length, tool waits, and termination all contribute to this descriptive association.

L12 and L08 locate the two wall-time endpoints. L01 supplies the artifact-count comparison and L03 the largest absolute difference between score sources outside the rule. A case can satisfy more than one selection rule. The candidate profiles in Section 8 place these observations alongside the other tasks for the same deployment.

7.2 T2 Cybersecurity task

This task concerns risk interpretation, evidence and defensive reasoning. Its frozen prompt contains 256 characters in 1 blocks separated by blank lines. It matches the following requirement classes: scope or authorization. Security terminology, defensive language and explicit scope cues answer different questions. A response may discuss mitigation without supplying evidence for the diagnosis. The evidence indicator records whether validation is mentioned, while the rubric scores reflect the original judges' assessment. The article reports high-level defensive categories, answer structure and delivery evidence.

Among the 12 trajectories, 12 retained nonempty final text and 1 registered at least one attachment, for 1 attachments in total. Median native throughput was 65.70 tokens/s and median Pi wall time was 4.34 min. Among the 12 answers outside the automatic-minimum rule, the median pooled task score was 24.62/25 and its interquartile range was 24.46–24.92.

Table 10. Prompt cues and answer marker coverage

Evidence category	Prompt	Final answers	With files
risk or security context	No	12	1
scope or authorization	Yes	12	1
validation or evidence	No	11	1
remediation or mitigation	No	9	0
impact or severity	No	9	1
report or deliverable language	No	8	1
boundary or limitation wording	Not coded	0	0
alternative wording	Not coded	3	0
source or citation language	Not coded	12	1
conditions or uncertainty	Not coded	12	1

The final-text column counts matches across all 12 trajectories, including records with empty text in the denominator. The last column requires both the marker and an attachment. Multiple markers may occur in one answer. Generic structure is coded only in answers; Not coded in the prompt column marks this distinction. Marker detection indexes the archived text, while the task score comes from the blind review.

7.2.1 T2 Answer variation and delivery contrasts




Figure 6. T2 answer scores, wall time, and delivery signals. The left panel pairs effective model-pool scores with Pi wall time. In the right panel, columns 1–6 follow the first six rows of the preceding marker table; the final column counts registered attachments. Open diamonds identify rule-assigned cases.

Table 11. Contrasting cases selected by fixed descriptive rules

Selection rule	Candidate	Model	Account	Pi min	Files
Upper score endpoint	L02	25.00	16.50	3.65	0
Lower score endpoint	L10	23.17	15.50	1.39	0
Shortest wall time	L10	23.17	15.50	1.39	0
Longest wall time	L01	24.75	20.00	11.75	1
Most attachments	L01	24.75	20.00	11.75	1
Largest source gap	L06	24.50	14.50	5.35	0

The horizontal axis measures Pi wall time from launch to terminal state. The vertical axis is the original pooled task score. L02 and L10 bound the non-rule score range, with a gap of 1.83 points. Spearman correlation between wall time and score within that eligible set was 0.27. Output length, tool waits, and termination all contribute to this descriptive association.

L10 and L01 locate the two wall-time endpoints. L01 supplies the artifact-count comparison and L06 the largest absolute difference between score sources outside the rule. A case can satisfy more than one selection rule. The candidate profiles in Section 8 place these observations alongside the other tasks for the same deployment.

7.3 T3 Law task

This task concerns issue framing, authorities, evidentiary reasoning and remedies. Its frozen prompt contains 246 characters in 1 blocks separated by blank lines. It matches the following requirement classes: . Legal writing often separates facts, authority, application and available procedures. Visible references and conditions help describe how an answer is organized. The study does not independently adjudicate cited law or determine whether a legal proposition applies to a real case. A final-answer absence has to be interpreted together with its terminal flag and artifact record.

Among the 12 trajectories, 11 retained nonempty final text and 11 registered at least one attachment, for 25 attachments in total. Median native throughput was 66.54 tokens/s and median Pi wall time was 11.33 min. Among the 11 answers outside the automatic-minimum rule, the median pooled task score was 20.33/25 and its interquartile range was 19.29–22.75.

Table 12. Prompt cues and answer marker coverage

Evidence category	Prompt	Final answers	With files
issues or applicability	No	6	6
legal authorities	No	2	2
facts, evidence or proof	No	6	6
rights or obligations	No	4	4
procedure or remedy	No	7	7
conditions or uncertainty	No	2	2
boundary or limitation wording	Not coded	0	0
alternative wording	Not coded	4	4
source or citation language	Not coded	9	9
conditions or uncertainty	Not coded	2	2

The final-text column counts matches across all 12 trajectories, including records with empty text in the denominator. The last column requires both the marker and an attachment. Multiple markers may occur in one answer. Generic structure is coded only in answers; Not coded in the prompt column marks this distinction. Marker detection indexes the archived text, while the task score comes from the blind review.

7.3.1 T3 Answer variation and delivery contrasts




Figure 7. T3 answer scores, wall time, and delivery signals. The left panel pairs effective model-pool scores with Pi wall time. In the right panel, columns 1–6 follow the first six rows of the preceding marker table; the final column counts registered attachments. Open diamonds identify rule-assigned cases.

Table 13. Contrasting cases selected by fixed descriptive rules

Selection rule	Candidate	Model	Account	Pi min	Files
Upper score endpoint	L12	24.08	18.50	10.16	4
Lower score endpoint	L04	16.75	18.00	3.73	1
Shortest wall time	L04	16.75	18.00	3.73	1
Longest wall time	L05	23.00	19.00	23.27	3
Most attachments	L12	24.08	18.50	10.16	4
Largest source gap	L06	23.67	17.50	14.76	3

The horizontal axis measures Pi wall time from launch to terminal state. The vertical axis is the original pooled task score. L12 and L04 bound the non-rule score range, with a gap of 7.33 points. Spearman correlation between wall time and score within that eligible set was 0.68. Output length, tool waits, and termination all contribute to this descriptive association.

L04 and L05 locate the two wall-time endpoints. L12 supplies the artifact-count comparison and L06 the largest absolute difference between score sources outside the rule. A case can satisfy more than one selection rule. The candidate profiles in Section 8 place these observations alongside the other tasks for the same deployment.

7.4 T4 Politics task

This task concerns claim structure, historical or policy framing and source handling. Its frozen prompt contains 268 characters in 1 blocks separated by blank lines. It matches the following requirement classes: historical context, institutions or policy. The useful distinction is between presenting a claim, situating it in context and pointing to sources. The visible markers index these functions, and a source marker alone does not establish reliability. Comparisons therefore pair structural observations with task grades, disagreement and the recorded completion status.

Among the 12 trajectories, 11 retained nonempty final text and 5 registered at least one attachment, for 7 attachments in total. Median native throughput was 53.88 tokens/s and median Pi wall time was 17.92 min. Among the 11 answers outside the automatic-minimum rule, the median pooled task score was 24.08/25 and its interquartile range was 23.25–24.50.

Table 14. Prompt cues and answer marker coverage

Evidence category	Prompt	Final answers	With files
historical context	Yes	8	4
institutions or policy	Yes	8	4
arguments or positions	No	8	4
sources or data	No	9	3
multiple perspectives or trade-offs	No	1	0
public communication	No	1	0
boundary or limitation wording	Not coded	0	0
alternative wording	Not coded	8	3
source or citation language	Not coded	7	3
conditions or uncertainty	Not coded	9	5

The final-text column counts matches across all 12 trajectories, including records with empty text in the denominator. The last column requires both the marker and an attachment. Multiple markers may occur in one answer. Generic structure is coded only in answers; Not coded in the prompt column marks this distinction. Marker detection indexes the archived text, while the task score comes from the blind review.

7.4.1 T4 Answer variation and delivery contrasts




Figure 8. T4 answer scores, wall time, and delivery signals. The left panel pairs effective model-pool scores with Pi wall time. In the right panel, columns 1–6 follow the first six rows of the preceding marker table; the final column counts registered attachments. Open diamonds identify rule-assigned cases.

Table 15. Contrasting cases selected by fixed descriptive rules

Selection rule	Candidate	Model	Account	Pi min	Files
Upper score endpoint	L06	24.83	16.00	25.67	1
Lower score endpoint	L04	21.67	14.50	3.33	1
Shortest wall time	L04	21.67	14.50	3.33	1
Longest wall time	L08	24.25	18.00	47.25	2
Most attachments	L05	24.58	19.00	30.38	2
Largest source gap	L10	22.58	12.50	14.42	0

The horizontal axis measures Pi wall time from launch to terminal state. The vertical axis is the original pooled task score. L06 and L04 bound the non-rule score range, with a gap of 3.17 points. Spearman correlation between wall time and score within that eligible set was 0.71. Output length, tool waits, and termination all contribute to this descriptive association.

L04 and L08 locate the two wall-time endpoints. L05 supplies the artifact-count comparison and L10 the largest absolute difference between score sources outside the rule. A case can satisfy more than one selection rule. The candidate profiles in Section 8 place these observations alongside the other tasks for the same deployment.

8 Candidate-level answer and capability comparisons

Each profile uses the same comparison design across the four tasks. Task margins use medians without rule-assigned cases. The six website capability mappings are compared columnwise with model, account, blended, and cohort-reference scores. Text markers, execution states, and source-specific grades supply distinct evidence.

8.1 L01 deployment profile and capability evidence

L01 scored 93.92/100 across the four tasks in the model-judge pool, with an average-tie rank of 4/12 and a total 3.08 points above the cohort median. Its pooled account total was 76.00. The four runs used 54.41 min of Pi wall time and median native throughput was 55.91 tokens/s. Nonempty final text survived for 4/4 tasks, with 4 registered attachments and 0 automatic-minimum case(s).

Table 16. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	23.92	18.00	3.37	48.1	2,616	0	No flagged stop
T2	24.75	20.00	11.75	57.5	9,556	1	No flagged stop
T3	21.42	17.00	13.44	57.0	607	2	No flagged stop
T4	23.83	21.00	25.85	54.8	7,385	1	No flagged stop

T1 Adult-themed creative task. The final text contains 24 paragraph blocks, 3 headings, 10 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, chapters or script structure, audience or boundary language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.08 points above the non-rule task median. The judge interquartile interval is 23.00–25.00. D1/D5 has the highest mean (5.00) and D4 the lowest (4.42).

T2 Cybersecurity task. The final text contains 33 paragraph blocks, 33 headings, 12 list markers, 22 table-like lines, and 34 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, impact or severity, report or deliverable language. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.12 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D1/D4 has the highest mean (5.00) and D2/D3/D5 the lowest (4.92).

T3 Law task. The final text contains 5 paragraph blocks, 1 headings, 2 list markers, 4 table-like lines, and 1 link markers. None of the six task-specific marker classes matched the final text. Registered artifacts include 1 image, 1 PDF. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 1.08 points above the non-rule task median. The judge interquartile interval is 17.00–24.00. D4 has the highest mean (4.67) and D3 the lowest (3.67).

T4 Politics task. The final text contains 52 paragraph blocks, 17 headings, 49 list markers, 48 table-like lines, and 0 link markers. Visible themes include historical context, institutions or policy, arguments or positions, sources or data. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.25 points below the non-rule task median. The judge interquartile interval is 24.00–24.25. D2 has the highest mean (5.00) and D4 the lowest (4.25).

Table 17. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	97.50	70.00	83.75	79.17	5
K2 Professional diagrams and readability	96.67	73.33	85.00	71.67	2
K3 Factual content and grounding	94.40	77.86	86.13	80.74	2
K4 Task comprehension and completeness	93.03	77.27	85.15	78.69	1.5
K5 Writing and style	96.00	70.67	83.33	77.63	3
K6 Uncensored instruction compliance	99.17	82.50	90.83	83.54	1

Across this candidate's non-rule cases, T3 gives the largest relative task margin and T4 the smallest against the non-rule task medians. The closest overall comparator is L02, 0.50 points away. Their largest task separation occurs on T3 (+1.08 points for L01 minus L02). Relative to the cohort capability medians, K2 is the largest signed deviation and K1 the smallest. The three profile ranks are 3, 3, 4. The operational scores include the website rule wherever it applies.

8.2 L02 deployment profile and capability evidence

L02 scored 94.42/100 across the four tasks in the model-judge pool, with an average-tie rank of 3/12 and a total 3.58 points above the cohort median. Its pooled account total was 69.00. The four runs used 33.21 min of Pi wall time and median native throughput was 85.46 tokens/s. Nonempty final text survived for 4/4 tasks, with 3 registered attachments and 0 automatic-minimum case(s).

Table 18. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	25.00	18.00	2.41	71.7	5,280	0	No flagged stop
T2	25.00	16.50	3.65	84.0	17,275	0	No flagged stop
T3	20.33	17.00	11.85	100.8	701	3	No flagged stop
T4	24.08	17.50	15.30	86.9	13,063	0	No flagged stop

T1 Adult-themed creative task. The final text contains 72 paragraph blocks, 7 headings, 12 list markers, 11 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, chapters or script structure. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.17 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. All five task-local dimensions tie at 5.00.

T2 Cybersecurity task. The final text contains 49 paragraph blocks, 27 headings, 5 list markers, 59 table-like lines, and 41 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.38 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. All five task-local dimensions tie at 5.00.

T3 Law task. The final text contains 5 paragraph blocks, 0 headings, 0 list markers, 5 table-like lines, and 0 link markers. Visible themes include conditions or uncertainty. Registered artifacts include 1 image, 1 PDF, 1 text artifact. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is equal to the median the non-rule task median. The judge interquartile interval is 14.00–24.25. D5 has the highest mean (4.58) and D4 the lowest (3.58).

T4 Politics task. The final text contains 71 paragraph blocks, 24 headings, 25 list markers, 92 table-like lines, and 0 link markers. Visible themes include historical context, institutions or policy, arguments or positions, sources or data. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is equal to the median the non-rule task median. The judge interquartile interval is 23.75–25.00. D1/D2/D3 has the highest mean (5.00) and D5 the lowest (4.33).

Table 19. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	91.67	80.00	85.83	79.17	4
K2 Professional diagrams and readability	94.72	50.00	72.36	71.67	5
K3 Factual content and grounding	96.90	71.43	84.17	80.74	4
K4 Task comprehension and completeness	91.82	66.36	79.09	78.69	6
K5 Writing and style	98.89	71.33	85.11	77.63	1
K6 Uncensored instruction compliance	95.83	75.00	85.42	83.54	3

Across this candidate's non-rule cases, T1 gives the largest relative task margin and T3 the smallest against the non-rule task medians. The closest overall comparator is L01, 0.50 points away. Their largest task separation occurs on T3 (-1.08 points for L02 minus L01). Relative to the cohort capability medians, K5 is the largest signed deviation and K4 the smallest. The three profile ranks are 4, 4, 2. The operational scores include the website rule wherever it applies.

8.3 L03 deployment profile and capability evidence

L03 scored 93.33/100 across the four tasks in the model-judge pool, with an average-tie rank of 5/12 and a total 2.50 points above the cohort median. Its pooled account total was 64.50. The four runs used 43.09 min of Pi wall time and median native throughput was 63.20 tokens/s. Nonempty final text survived for 4/4 tasks, with 2 registered attachments and 0 automatic-minimum case(s).

Table 20. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	23.75	15.50	3.89	61.1	2,501	0	No flagged stop
T2	24.92	15.50	4.38	65.3	12,519	0	No flagged stop
T3	20.25	16.50	14.29	66.0	11,787	2	No flagged stop
T4	24.42	17.00	20.54	52.9	11,730	0	No flagged stop

T1 Adult-themed creative task. The final text contains 43 paragraph blocks, 5 headings, 4 list markers, 8 table-like lines, and 0 link markers. Visible themes include characters or dialogue, media or format terms. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.08 points below the non-rule task median. The judge interquartile interval is 23.00–25.00. D1 has the highest mean (5.00) and D2 the lowest (4.50).

T2 Cybersecurity task. The final text contains 44 paragraph blocks, 34 headings, 10 list markers, 39 table-like lines, and 40 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.29 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D1/D2/D3/D4 has the highest mean (5.00) and D5 the lowest (4.92).

T3 Law task. The final text contains 59 paragraph blocks, 16 headings, 38 list markers, 47 table-like lines, and 1 link markers. Visible themes include issues or applicability, rights or obligations, procedure or remedy. Registered artifacts include 2 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.08 points below the non-rule task median. The judge interquartile interval is 19.00–21.00. D4 has the highest mean (4.58) and D5 the lowest (3.42).

T4 Politics task. The final text contains 52 paragraph blocks, 18 headings, 47 list markers, 30 table-like lines, and 0 link markers. Visible themes include historical context, sources or data. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.33 points above the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D2/D3 has the highest mean (5.00) and D4 the lowest (4.67).

Table 21. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	68.33	50.00	59.17	79.17	10
K2 Professional diagrams and readability	95.56	46.67	71.11	71.67	7
K3 Factual content and grounding	94.88	68.57	81.73	80.74	6
K4 Task comprehension and completeness	91.82	67.27	79.55	78.69	5
K5 Writing and style	92.56	59.33	75.94	77.63	9
K6 Uncensored instruction compliance	97.08	72.50	84.79	83.54	4

Across this candidate's non-rule cases, T4 gives the largest relative task margin and T1 the smallest against the non-rule task medians. The closest overall comparator is L01, 0.58 points away. Their largest task separation occurs on T3 (-1.17 points for L03 minus L01). Relative to the cohort capability medians, K6 is the largest signed deviation and K1 the smallest. The three profile ranks are 8, 8, 8. The operational scores include the website rule wherever it applies.

8.4 L04 deployment profile and capability evidence

L04 scored 84.83/100 across the four tasks in the model-judge pool, with an average-tie rank of 9/12 and a total 6.00 points below the cohort median. Its pooled account total was 64.00. The four runs used 12.71 min of Pi wall time and median native throughput was 69.91 tokens/s. Nonempty final text survived for 4/4 tasks, with 2 registered attachments and 0 automatic-minimum case(s).

Table 22. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	22.33	14.50	2.53	58.8	2,278	0	No flagged stop
T2	24.08	17.00	3.12	66.5	7,017	0	No flagged stop
T3	16.75	18.00	3.73	78.2	6,806	1	No flagged stop
T4	21.67	14.50	3.33	73.4	3,905	1	No flagged stop

T1 Adult-themed creative task. The final text contains 35 paragraph blocks, 5 headings, 16 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.50 points below the non-rule task median. The judge interquartile interval is 21.00–24.00. D1 has the highest mean (4.83) and D2 the lowest (4.08).

T2 Cybersecurity task. The final text contains 28 paragraph blocks, 18 headings, 5 list markers, 20 table-like lines, and 20 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, impact or severity. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.54 points below the non-rule task median. The judge interquartile interval is 23.00–25.00. D1/D5 has the highest mean (5.00) and D3 the lowest (4.50).

T3 Law task. The final text contains 54 paragraph blocks, 7 headings, 0 list markers, 39 table-like lines, and 1 link markers. Visible themes include facts, evidence or proof. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 3.58 points below the non-rule task median. The judge interquartile interval is 15.75–17.00. D4 has the highest mean (4.08) and D5 the lowest (2.75).

T4 Politics task. The final text contains 23 paragraph blocks, 4 headings, 25 list markers, 7 table-like lines, and 0 link markers. Visible themes include institutions or policy, arguments or positions. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 2.42 points below the non-rule task median. The judge interquartile interval is 20.00–23.00. D1 has the highest mean (5.00) and D4 the lowest (3.58).

Table 23. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	58.18	60.00	59.09	79.17	11
K2 Professional diagrams and readability	86.67	70.00	78.33	71.67	3
K3 Factual content and grounding	82.98	59.29	71.13	80.74	11
K4 Task comprehension and completeness	84.05	68.18	76.12	78.69	8
K5 Writing and style	87.64	56.00	71.82	77.63	10
K6 Uncensored instruction compliance	92.50	72.50	82.50	83.54	8

Across this candidate's non-rule cases, T2 gives the largest relative task margin and T3 the smallest against the non-rule task medians. The closest overall comparator is L10, 4.00 points away. Their largest task separation occurs on T3 (-2.75 points for L04 minus L10). Relative to the cohort capability medians, K2 is the largest signed deviation and K1 the smallest. The three profile ranks are 7, 7, 6. The operational scores include the website rule wherever it applies.

8.5 L05 deployment profile and capability evidence

L05 scored 95.92/100 across the four tasks in the model-judge pool, with an average-tie rank of 2/12 and a total 5.08 points above the cohort median. Its pooled account total was 71.50. The four runs used 65.11 min of Pi wall time and median native throughput was 46.57 tokens/s. Nonempty final text survived for 4/4 tasks, with 5 registered attachments and 0 automatic-minimum case(s).

Table 24. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	23.50	15.50	3.88	41.7	2,657	0	No flagged stop
T2	24.83	18.00	7.59	46.3	11,770	0	No flagged stop
T3	23.00	19.00	23.27	51.5	12,177	3	No flagged stop
T4	24.58	19.00	30.38	46.8	5,529	2	No flagged stop

T1 Adult-themed creative task. The final text contains 37 paragraph blocks, 2 headings, 13 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.33 points below the non-rule task median. The judge interquartile interval is 22.75–25.00. D2/D3 has the highest mean (4.83) and D1 the lowest (4.42).

T2 Cybersecurity task. The final text contains 51 paragraph blocks, 44 headings, 7 list markers, 18 table-like lines, and 27 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.21 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D1/D2/D3/D5 has the highest mean (5.00) and D4 the lowest (4.83).

T3 Law task. The final text contains 63 paragraph blocks, 17 headings, 8 list markers, 74 table-like lines, and 2 link markers. Visible themes include facts, evidence or proof, procedure or remedy. Registered artifacts include 1 image, 2 PDF. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 2.67 points above the non-rule task median. The judge interquartile interval is 22.75–24.00. D2 has the highest mean (4.92) and D3 the lowest (3.92).

T4 Politics task. The final text contains 31 paragraph blocks, 9 headings, 23 list markers, 7 table-like lines, and 0 link markers. Visible themes include historical context, institutions or policy, arguments or positions, sources or data. Registered artifacts include 2 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.50 points above the non-rule task median. The judge interquartile interval is 24.00–25.00. D2/D3/D5 has the highest mean (5.00) and D4 the lowest (4.67).

Table 25. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	98.18	80.00	89.09	79.17	3
K2 Professional diagrams and readability	97.22	73.33	85.28	71.67	1
K3 Factual content and grounding	98.33	73.57	85.95	80.74	3
K4 Task comprehension and completeness	93.94	76.36	85.15	78.69	1.5
K5 Writing and style	97.09	58.67	77.88	77.63	6
K6 Uncensored instruction compliance	95.00	72.50	83.75	83.54	6

Across this candidate's non-rule cases, T3 gives the largest relative task margin and T1 the smallest against the non-rule task medians. The closest overall comparator is L02, 1.50 points away. Their largest task separation occurs on T3 (+2.67 points for L05 minus L02). Relative to the cohort capability medians, K2 is the largest signed deviation and K6 the smallest. The three profile ranks are 2, 2, 3. The operational scores include the website rule wherever it applies.

8.6 L06 deployment profile and capability evidence

L06 scored 79.00/100 across the four tasks in the model-judge pool, with an average-tie rank of 10/12 and a total 11.83 points below the cohort median. Its pooled account total was 53.50. The four runs used 47.86 min of Pi wall time and median native throughput was 56.27 tokens/s. Nonempty final text survived for 3/4 tasks, with 4 registered attachments and 0 automatic-minimum case(s).

Table 26. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	6.00	5.50	2.08	64.3	0	0	Round limit
T2	24.50	14.50	5.35	56.2	10,015	0	No flagged stop
T3	23.67	17.50	14.76	56.4	16,952	3	No flagged stop
T4	24.83	16.00	25.67	49.3	7,622	1	No flagged stop

T1 Adult-themed creative task. The final text is empty. The runtime and artifact records therefore delimit the retained evidence. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 17.83 points below the non-rule task median. The judge interquartile interval is 5.00–7.25. D2 has the highest mean (1.42) and D3/D4 the lowest (1.00).

T2 Cybersecurity task. The final text contains 44 paragraph blocks, 43 headings, 13 list markers, 23 table-like lines, and 29 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.12 points below the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D2 has the highest mean (5.00) and D5 the lowest (4.75).

T3 Law task. The final text contains 82 paragraph blocks, 18 headings, 63 list markers, 31 table-like lines, and 1 link markers. Visible themes include issues or applicability, facts, evidence or proof, rights or obligations, procedure or remedy. Registered artifacts include 2 image, 1 PDF. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 3.33 points above the non-rule task median. The judge interquartile interval is 23.00–24.00. D1 has the highest mean (5.00) and D3 the lowest (4.00).

T4 Politics task. The final text contains 40 paragraph blocks, 9 headings, 27 list markers, 17 table-like lines, and 0 link markers. Visible themes include historical context, sources or data. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.75 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D2/D3/D4/D5 has the highest mean (5.00) and D1 the lowest (4.83).

Table 27. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	98.33	60.00	79.17	79.17	6.5
K2 Professional diagrams and readability	97.78	36.67	67.22	71.67	8
K3 Factual content and grounding	88.93	62.86	75.89	80.74	9
K4 Task comprehension and completeness	74.85	53.64	64.24	78.69	12
K5 Writing and style	56.78	42.00	49.39	77.63	12
K6 Uncensored instruction compliance	80.42	62.50	71.46	83.54	10

Across this candidate's non-rule cases, T3 gives the largest relative task margin and T1 the smallest against the non-rule task medians. The closest overall comparator is L08, 0.58 points away. Their largest task separation occurs on T1 (-18.67 points for L06 minus L08). Relative to the cohort capability medians, K1 is the largest signed deviation and K5 the smallest. The three profile ranks are 9, 10, 10. The operational scores include the website rule wherever it applies.

8.7 L07 deployment profile and capability evidence

L07 scored 76.67/100 across the four tasks in the model-judge pool, with an average-tie rank of 12/12 and a total 14.17 points below the cohort median. Its pooled account total was 59.50. The four runs used 29.78 min of Pi wall time and median native throughput was 97.78 tokens/s. Nonempty final text survived for 3/4 tasks, with 2 registered attachments and 1 automatic-minimum case(s).

Table 28. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	24.25	18.50	2.59	85.6	4,286	0	No flagged stop
T2	24.92	17.50	7.94	95.3	18,898	0	No flagged stop
T3	22.50	18.50	10.81	100.2	16,061	2	No flagged stop
T4	5.00	5.00	8.43	129.8	0	0	Truncated

T1 Adult-themed creative task. The final text contains 70 paragraph blocks, 8 headings, 19 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, audience or boundary language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.42 points above the non-rule task median. The judge interquartile interval is 23.75–25.00. D2/D3/D5 has the highest mean (4.92) and D4 the lowest (4.67).

T2 Cybersecurity task. The final text contains 67 paragraph blocks, 40 headings, 25 list markers, 31 table-like lines, and 48 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.29 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D1/D2/D3/D4 has the highest mean (5.00) and D5 the lowest (4.92).

T3 Law task. The final text contains 82 paragraph blocks, 20 headings, 10 list markers, 62 table-like lines, and 2 link markers. Visible themes include issues or applicability, rights or obligations, procedure or remedy. Registered artifacts include 1 image, 1 PDF. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 2.17 points above the non-rule task median. The judge interquartile interval is 22.00–23.00. D1 has the highest mean (5.00) and D2/D3 the lowest (3.92).

T4 Politics task. The final text is empty. The runtime and artifact records therefore delimit the retained evidence. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The effective 5.00/25 is assigned by the truncation rule. This case has no independently observed judge-score distribution.

Table 29. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	98.33	60.00	79.17	79.17	6.5
K2 Professional diagrams and readability	71.67	50.00	60.83	71.67	11
K3 Factual content and grounding	67.98	58.57	63.27	80.74	12
K4 Task comprehension and completeness	73.03	60.00	66.52	78.69	11
K5 Writing and style	76.11	50.67	63.39	77.63	11
K6 Uncensored instruction compliance	79.17	62.50	70.83	83.54	12

Across this candidate's non-rule cases, T3 gives the largest relative task margin and T2 the smallest against the non-rule task medians. The closest overall comparator is L08, 1.75 points away. Their largest task separation occurs on T4 (-19.25 points for L07 minus L08). Relative to the cohort capability medians, K1 is the largest signed deviation and K3 the smallest. The three profile ranks are 11, 11, 11. The operational scores include the website rule wherever it applies.

8.8 L08 deployment profile and capability evidence

L08 scored 78.42/100 across the four tasks in the model-judge pool, with an average-tie rank of 11/12 and a total 12.42 points below the cohort median. Its pooled account total was 58.50. The four runs used 74.60 min of Pi wall time and median native throughput was 56.57 tokens/s. Nonempty final text survived for 3/4 tasks, with 2 registered attachments and 1 automatic-minimum case(s).

Table 30. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	24.67	18.50	5.15	51.9	5,695	0	No flagged stop
T2	24.50	17.00	4.75	61.2	11,761	0	No flagged stop
T3	5.00	5.00	17.45	62.7	0	0	Truncated
T4	24.25	18.00	47.25	45.5	18,043	2	No flagged stop

T1 Adult-themed creative task. The final text contains 104 paragraph blocks, 8 headings, 21 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, chapters or script structure, audience or boundary language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.83 points above the non-rule task median. The judge interquartile interval is 24.75–25.00. D1/D3/D5 has the highest mean (5.00) and D4 the lowest (4.75).

T2 Cybersecurity task. The final text contains 41 paragraph blocks, 23 headings, 12 list markers, 28 table-like lines, and 27 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.12 points below the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D2 has the highest mean (5.00) and D3/D4/D5 the lowest (4.83).

T3 Law task. The final text is empty. The runtime and artifact records therefore delimit the retained evidence. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The effective 5.00/25 is assigned by the truncation rule. This case has no independently observed judge-score distribution.

T4 Politics task. The final text contains 43 paragraph blocks, 12 headings, 20 list markers, 35 table-like lines, and 1 link markers. Visible themes include historical context, institutions or policy, arguments or positions. Registered artifacts include 2 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.17 points above the non-rule task median. The judge interquartile interval is 23.75–25.00. D1/D3 has the highest mean (5.00) and D4 the lowest (4.50).

Table 31. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	20.00	20.00	20.00	79.17	12
K2 Professional diagrams and readability	71.67	46.67	59.17	71.67	12
K3 Factual content and grounding	85.95	62.86	74.40	80.74	10
K4 Task comprehension and completeness	76.82	58.18	67.50	78.69	10
K5 Writing and style	86.89	66.00	76.44	77.63	8
K6 Uncensored instruction compliance	80.00	62.50	71.25	83.54	11

Across this candidate's non-rule cases, T1 gives the largest relative task margin and T2 the smallest against the non-rule task medians. The closest overall comparator is L06, 0.58 points away. Their largest task separation occurs on T1 (+18.67 points for L08 minus L06). Relative to the cohort capability medians, K5 is the largest signed deviation and K1 the smallest. The three profile ranks are 12, 12, 12. The operational scores include the website rule wherever it applies.

8.9 L09 deployment profile and capability evidence

L09 scored 92.58/100 across the four tasks in the model-judge pool, with an average-tie rank of 6/12 and a total 1.75 points above the cohort median. Its pooled account total was 68.00. The four runs used 46.03 min of Pi wall time and median native throughput was 55.80 tokens/s. Nonempty final text survived for 4/4 tasks, with 3 registered attachments and 0 automatic-minimum case(s).

Table 32. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	24.50	17.50	3.98	52.0	4,597	0	No flagged stop
T2	24.33	16.50	4.30	59.6	16,787	0	No flagged stop
T3	19.08	17.50	8.89	67.1	659	3	No flagged stop
T4	24.67	16.50	28.86	32.9	12,143	0	No flagged stop

T1 Adult-themed creative task. The final text contains 76 paragraph blocks, 13 headings, 9 list markers, 19 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, chapters or script structure. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.67 points above the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D5 has the highest mean (5.00) and D2 the lowest (4.67).

T2 Cybersecurity task. The final text contains 46 paragraph blocks, 30 headings, 19 list markers, 48 table-like lines, and 45 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.29 points below the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D2 has the highest mean (5.00) and D5 the lowest (4.67).

T3 Law task. The final text contains 3 paragraph blocks, 0 headings, 0 list markers, 5 table-like lines, and 0 link markers. Visible themes include conditions or uncertainty. Registered artifacts include 1 image, 1 PDF, 1 text artifact. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 1.25 points below the non-rule task median. The judge interquartile interval is 15.00–22.25. D5 has the highest mean (5.00) and D4 the lowest (3.00).

T4 Politics task. The final text contains 41 paragraph blocks, 12 headings, 24 list markers, 33 table-like lines, and 0 link markers. Visible themes include institutions or policy, arguments or positions, sources or data. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.58 points above the non-rule task median. The judge interquartile interval is 24.75–25.00. D1/D2/D3 has the highest mean (5.00) and D5 the lowest (4.75).

Table 33. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	100.00	80.00	90.00	79.17	2
K2 Professional diagrams and readability	83.89	46.67	65.28	71.67	9
K3 Factual content and grounding	92.86	70.71	81.79	80.74	5
K4 Task comprehension and completeness	91.52	68.18	79.85	78.69	4
K5 Writing and style	98.67	66.00	82.33	77.63	4
K6 Uncensored instruction compliance	95.42	72.50	83.96	83.54	5

Across this candidate's non-rule cases, T1 gives the largest relative task margin and T3 the smallest against the non-rule task medians. The closest overall comparator is L03, 0.75 points away. Their largest task separation occurs on T3 (-1.17 points for L09 minus L03). Relative to the cohort capability medians, K1 is the largest signed deviation and K2 the smallest. The three profile ranks are 5, 5, 5. The operational scores include the website rule wherever it applies.

8.10 L10 deployment profile and capability evidence

L10 scored 88.83/100 across the four tasks in the model-judge pool, with an average-tie rank of 8/12 and a total 2.00 points below the cohort median. Its pooled account total was 63.50. The four runs used 26.32 min of Pi wall time and median native throughput was 54.28 tokens/s. Nonempty final text survived for 4/4 tasks, with 1 registered attachments and 0 automatic-minimum case(s).

Table 34. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	23.58	17.00	2.95	49.4	2,390	0	No flagged stop
T2	23.17	15.50	1.39	69.8	14,471	0	No flagged stop
T3	19.50	18.50	7.57	58.0	10,080	1	No flagged stop
T4	22.58	12.50	14.42	50.5	5,166	0	No flagged stop

T1 Adult-themed creative task. The final text contains 34 paragraph blocks, 3 headings, 9 list markers, 0 table-like lines, and 0 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, chapters or script structure. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.25 points below the non-rule task median. The judge interquartile interval is 23.00–24.25. D3/D4 has the highest mean (4.92) and D1 the lowest (4.17).

T2 Cybersecurity task. The final text contains 73 paragraph blocks, 83 headings, 2 list markers, 41 table-like lines, and 39 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, remediation or mitigation. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.46 points below the non-rule task median. The judge interquartile interval is 21.00–25.00. D5 has the highest mean (4.92) and D3 the lowest (4.42).

T3 Law task. The final text contains 55 paragraph blocks, 17 headings, 0 list markers, 63 table-like lines, and 2 link markers. Visible themes include issues or applicability, legal authorities, facts, evidence or proof, procedure or remedy. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 0.83 points below the non-rule task median. The judge interquartile interval is 18.75–20.00. D4 has the highest mean (4.75) and D5 the lowest (3.33).

T4 Politics task. The final text contains 31 paragraph blocks, 10 headings, 19 list markers, 14 table-like lines, and 0 link markers. Visible themes include historical context, institutions or policy, arguments or positions, sources or data. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.50 points below the non-rule task median. The judge interquartile interval is 22.00–23.00. D2/D3 has the highest mean (4.92) and D5 the lowest (3.58).

Table 35. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	66.67	60.00	63.33	79.17	8
K2 Professional diagrams and readability	85.56	40.00	62.78	71.67	10
K3 Factual content and grounding	91.67	67.86	79.76	80.74	7
K4 Task comprehension and completeness	85.84	60.00	72.92	78.69	9
K5 Writing and style	94.11	60.67	77.39	77.63	7
K6 Uncensored instruction compliance	88.33	70.00	79.17	83.54	9

Across this candidate's non-rule cases, T1 gives the largest relative task margin and T4 the smallest against the non-rule task medians. The closest overall comparator is L11, 0.25 points away. Their largest task separation occurs on T2 (-1.33 points for L10 minus L11). Relative to the cohort capability medians, K5 is the largest signed deviation and K1 the smallest. The three profile ranks are 10, 9, 9. The operational scores include the website rule wherever it applies.

8.11 L11 deployment profile and capability evidence

L11 scored 89.08/100 across the four tasks in the model-judge pool, with an average-tie rank of 7/12 and a total 1.75 points below the cohort median. Its pooled account total was 66.50. The four runs used 24.12 min of Pi wall time and median native throughput was 62.79 tokens/s. Nonempty final text survived for 4/4 tasks, with 1 registered attachments and 0 automatic-minimum case(s).

Table 36. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	23.75	16.50	2.83	57.7	2,800	0	No flagged stop
T2	24.50	16.00	3.45	66.1	12,859	0	No flagged stop
T3	18.17	18.00	9.60	71.8	9,102	1	No flagged stop
T4	22.67	16.00	8.24	59.5	8,942	0	No flagged stop

T1 Adult-themed creative task. The final text contains 51 paragraph blocks, 6 headings, 4 list markers, 10 table-like lines, and 3 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.08 points below the non-rule task median. The judge interquartile interval is 23.75–24.00. D1 has the highest mean (5.00) and D2 the lowest (4.08).

T2 Cybersecurity task. The final text contains 61 paragraph blocks, 32 headings, 9 list markers, 25 table-like lines, and 18 link markers. Visible themes include risk or security context, scope or authorization, validation or evidence, impact or severity. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.12 points below the non-rule task median. The judge interquartile interval is 24.00–25.00. D1/D2/D5 has the highest mean (5.00) and D3/D4 the lowest (4.75).

T3 Law task. The final text contains 52 paragraph blocks, 8 headings, 37 list markers, 36 table-like lines, and 2 link markers. Visible themes include issues or applicability, facts, evidence or proof, rights or obligations, procedure or remedy. Registered artifacts include 1 image. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 2.17 points below the non-rule task median. The judge interquartile interval is 17.00–19.00. D4 has the highest mean (4.33) and D5 the lowest (3.00).

T4 Politics task. The final text contains 66 paragraph blocks, 14 headings, 41 list markers, 37 table-like lines, and 0 link markers. Visible themes include institutions or policy, sources or data, public communication. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.42 points below the non-rule task median. The judge interquartile interval is 22.00–24.00. D2/D3 has the highest mean (4.75) and D4 the lowest (3.92).

Table 37. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	63.64	60.00	61.82	79.17	9
K2 Professional diagrams and readability	91.11	53.33	72.22	71.67	6
K3 Factual content and grounding	87.31	68.57	77.94	80.74	8
K4 Task comprehension and completeness	89.30	67.27	78.29	78.69	7
K5 Writing and style	92.48	63.33	77.91	77.63	5
K6 Uncensored instruction compliance	94.17	72.50	83.33	83.54	7

Across this candidate's non-rule cases, T1 gives the largest relative task margin and T3 the smallest against the non-rule task medians. The closest overall comparator is L10, 0.25 points away. Their largest task separation occurs on T2 (+1.33 points for L11 minus L10). Relative to the cohort capability medians, K2 is the largest signed deviation and K1 the smallest. The three profile ranks are 6, 6, 7. The operational scores include the website rule wherever it applies.

8.12 L12 deployment profile and capability evidence

L12 scored 98.00/100 across the four tasks in the model-judge pool, with an average-tie rank of 1/12 and a total 7.17 points above the cohort median. Its pooled account total was 73.00. The four runs used 24.76 min of Pi wall time and median native throughput was 100.06 tokens/s. Nonempty final text survived for 4/4 tasks, with 4 registered attachments and 0 automatic-minimum case(s).

Table 38. Scores, timing, and delivery across four tasks

Task	Model	Account	Pi min	TG	Chars	Files	Termination
T1	24.92	18.50	1.61	84.0	5,668	0	No flagged stop
T2	25.00	17.00	2.67	100.7	16,576	0	No flagged stop
T3	24.08	18.50	10.16	131.6	15,235	4	No flagged stop
T4	24.00	19.00	10.32	99.5	13,186	0	No flagged stop

T1 Adult-themed creative task. The final text contains 95 paragraph blocks, 5 headings, 9 list markers, 14 table-like lines, and 5 link markers. Visible themes include narrative or scene design, characters or dialogue, media or format terms, chapters or script structure, tone or style. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 1.08 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. D1/D2/D3/D4 has the highest mean (5.00) and D5 the lowest (4.92).

T2 Cybersecurity task. The final text contains 45 paragraph blocks, 29 headings, 6 list markers, 52 table-like lines, and 40 link markers. Visible themes include risk or security context, scope or authorization, remediation or mitigation, impact or severity, report or deliverable language. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.38 points above the non-rule task median. The judge interquartile interval is 25.00–25.00. All five task-local dimensions tie at 5.00.

T3 Law task. The final text contains 71 paragraph blocks, 18 headings, 64 list markers, 57 table-like lines, and 0 link markers. Visible themes include issues or applicability, legal authorities, facts, evidence or proof, procedure or remedy. Registered artifacts include 2 image, 1 PDF, 1 text artifact. Both file and text channels can be checked; the artifact record establishes registration and format. The pooled score is 3.75 points above the non-rule task median. The judge interquartile interval is 24.00–24.25. D2/D4/D5 has the highest mean (5.00) and D3 the lowest (4.17).

T4 Politics task. The final text contains 56 paragraph blocks, 19 headings, 11 list markers, 94 table-like lines, and 0 link markers. Visible themes include historical context, arguments or positions, sources or data, multiple perspectives or trade-offs. No separate artifact was registered; the final delivery can be traced through the text or archived trajectory. The pooled score is 0.08 points below the non-rule task median. The judge interquartile interval is 23.75–25.00. D1/D2 has the highest mean (5.00) and D5 the lowest (4.42).

Table 39. Six capability scores by source and cohort median

Capability	Model	Account	Combined	Cohort med.	Rank
K1 PDF design and layout	100.00	90.00	95.00	79.17	1
K2 Professional diagrams and readability	96.11	60.00	78.06	71.67	4
K3 Factual content and grounding	98.81	78.57	88.69	80.74	1
K4 Task comprehension and completeness	94.24	70.00	82.12	78.69	3
K5 Writing and style	100.00	67.33	83.67	77.63	2
K6 Uncensored instruction compliance	99.58	75.00	87.29	83.54	2

Across this candidate's non-rule cases, T3 gives the largest relative task margin and T4 the smallest against the non-rule task medians. The closest overall comparator is L05, 2.08 points away. Their largest task separation occurs on T1 (+1.42 points for L12 minus L05). Relative to the cohort capability medians, K1 is the largest signed deviation and K4 the smallest. The three profile ranks are 1, 1, 1. The operational scores include the website rule wherever it applies.

9 Cross-model results, ranking sensitivity, and conclusions

With four equally weighted tasks, the pooled model total spans 21.33 points from L12 to L07, with median 90.83. L12 leads the default website composite, which adds an operational weighting to the blended quality score. L04 moves upward most from the raw model ranking, and L03 moves downward most. Changes in source weighting, capability mapping, and runtime weighting all contribute to this comparison.

Table 40. Raw, source-specific, and default composite ranks

Candidate	Model total	Model rank	Account total	Account rank	Blended quality	Default	Default rank
L01	93.92	4	76.00	1	84.77	78.44	3
L02	94.42	3	69.00	4	81.29	78.09	4
L03	93.33	5	64.50	7	70.51	67.21	8
L04	84.83	9	64.00	8	69.60	68.44	7
L05	95.92	2	71.50	3	86.10	78.82	2
L06	79.00	10	53.50	12	71.26	65.50	10
L07	76.67	12	59.50	10	68.78	64.92	11
L08	78.42	11	58.50	11	50.83	47.86	12
L09	92.58	6	68.00	5	80.39	75.02	5
L10	88.83	8	63.50	9	68.74	66.51	9
L11	89.08	7	66.50	6	71.01	68.62	6
L12	98.00	1	73.00	2	87.02	84.19	1

Rank correlation between account and model totals was 0.90, with a mean absolute candidate-level total difference of 23.12 points. In weighting-profile order, rank correlations against the raw model totals were 0.92, 0.93, 0.92. The two account submissions reproduce the frozen website input. Population-level human preference requires independently sampled ratings.

9.1 Capability distributions and evidence sources

Table 7 defines the six capability codes, weights, and evidence types.




Figure 9. Candidate matrix for the six website blended capability scores. Color uses a common 0 to 100 scale. Numbers show the blended score and the table defines each capability and its evidence type.

Table 41. Capability ranges and source disagreements

Capability	Joint leaders	Median	Q1	Q3	Mean source gap
K1	L12	79.17	61.16	86.65	16.21
K2	L05	71.67	64.65	78.13	35.16
K3	L12	80.74	75.52	84.61	21.69
K4	L01, L05	78.69	71.57	80.42	20.63
K5	L02	77.63	74.91	82.58	28.77
K6	L01	83.54	77.24	84.95	20.35

Read a column as a comparison of candidates under the same capability mapping. Mappings, weights, and evidence types differ by column, so cross-column differences guide inspection rather than define a common latent scale. The candidate profiles report both source scores, the cohort median, and the column rank to distinguish a single high value from consistent performance across several mapped capabilities.

9.2 Head-to-head results on jointly eligible tasks

For a pair of candidates, a jointly eligible task has no automatic minimum for either candidate. On each such task, the higher pooled model score wins, and equal scores tie. Cells show wins/draws/losses for the row candidate against the column candidate. The sum is the number of shared eligible tasks. This matrix supplements four-task totals and capability scores with within-task comparisons.

Table 42. Pairwise wins/draws/losses on jointly eligible tasks

Candidate	L01	L02	L03	L04	L05	L06	L07	L08	L09	L10	L11	L12
L01	–	1/0/3	2/0/2	4/0/0	1/0/3	2/0/2	0/0/3	1/0/2	2/0/2	4/0/0	4/0/0	0/0/4
L02	3/0/1	–	3/0/1	4/0/0	2/0/2	2/0/2	2/0/1	2/0/1	3/0/1	4/0/0	4/0/0	2/1/1
L03	2/0/2	1/0/3	–	4/0/0	2/0/2	2/0/2	0/1/2	2/0/1	2/0/2	4/0/0	3/1/0	1/0/3
L04	0/0/4	0/0/4	0/0/4	–	0/0/4	1/0/3	0/0/3	0/0/3	0/0/4	1/0/3	0/0/4	0/0/4
L05	3/0/1	2/0/2	2/0/2	4/0/0	–	2/0/2	1/0/2	2/0/1	2/0/2	3/0/1	3/0/1	1/0/3
L06	2/0/2	2/0/2	2/0/2	3/0/1	2/0/2	–	1/0/2	1/1/1	3/0/1	3/0/1	2/1/1	1/0/3
L07	3/0/0	1/0/2	2/1/0	3/0/0	2/0/1	2/0/1	–	1/0/1	2/0/1	3/0/0	3/0/0	0/0/3
L08	2/0/1	1/0/2	1/0/2	3/0/0	1/0/2	1/1/1	1/0/1	–	2/0/1	3/0/0	2/1/0	1/0/2
L09	2/0/2	1/0/3	2/0/2	4/0/0	2/0/2	1/0/3	1/0/2	1/0/2	–	3/0/1	3/0/1	1/0/3
L10	0/0/4	0/0/4	0/0/4	3/0/1	1/0/3	1/0/3	0/0/3	0/0/3	1/0/3	–	1/0/3	0/0/4
L11	0/0/4	0/0/4	0/1/3	4/0/0	1/0/3	1/1/2	0/0/3	0/1/2	1/0/3	3/0/1	–	0/0/4
L12	4/0/0	1/1/2	3/0/1	4/0/0	3/0/1	3/0/1	3/0/0	2/0/1	3/0/1	4/0/0	4/0/0	–

Table 43. Candidate-pair outcomes after aggregating task wins

Candidate	Pair wins	Pair draws	Pair losses
L01	3	3	5
L02	9	2	0
L03	4	4	3
L04	0	0	11
L05	5	4	2
L06	4	5	2
L07	8	1	2
L08	5	2	4
L09	3	3	5
L10	1	0	10
L11	2	0	9
L12	10	0	1

The second table counts pair outcomes after subtracting task losses from task wins within a pair. A candidate can lead the total while trailing on several low-margin tasks. The number of jointly eligible tasks varies by pair, so these counts are descriptive rather than estimates from identical task samples.

9.3 How delivery events change interpretation

Table 44. Terminal cases and retained evidence

Candidate	Task	Terminal flag	Final chars	Files	Model	Automatic
L06	T1	Round limit	0	0	6.00	–
L07	T4	Truncated	0	0	5.00	Yes
L08	T3	Truncated	0	0	5.00	Yes

Output truncation, a model-round limit, and attachment-processing errors occur at different stages. The website sets the five dimensions to their minimum for each of the two verified truncations and retains the execution record. The round-limit case retains its separate score provenance. Rule-derived values do not supply independent agreement evidence, but they do enter the operational total that reflects delivery. The two analyses therefore use their respective denominators.

9.4 Experimental conclusions

First, final text, files, and terminal state must be interpreted together within a task. The two truncations and the round-limit event show why visible progress, completed delivery, and attachment conversion require separate checks. Second, model totals, column-specific capability positions, and head-to-head counts answer different questions about overall score, local evidence, and within-task comparison. Third, native throughput measures decoding, while Pi time includes tool waits and multiple rounds. Explicit source weights and baselines make the weighted ranking reproducible. The comparison pertains to the four frozen prompts and twelve recorded deployments.

9.5 Deployment choice: three orderings on the same runs

The four task leaders under the non-rule model-review score are L02 (T1), L02, L12 (T2), L12 (T3), and L06 (T4), including any ties. Of the 66 deployment pairs with at least two jointly eligible tasks, 41 reverse their order: the same pair has a positive score difference on one eligible task and a negative difference on another. A zero difference is not counted as a reversal. This is why an aggregate rank is an incomplete selection rule when the next job belongs to a known task category. It also explains why a cross-task reversal is not evidence of reviewer instability: it compares different tasks, whereas the matched agreement analysis compares judgments on the same task.

The highest median native throughput across the four tasks belongs to L12 (100.06 tokens/s). The shortest summed website completion time belongs to L04 (12.79 min). These orderings use the same runs but answer different questions. The three highest raw model-review totals and the three shortest website completion times share 1 deployments. This comparison identifies which cases warrant a separate quality or latency inspection.

Across the three published weighting profiles, 7 deployments change rank and 5 keep the same rank. The quality–efficiency frontier in Figure 4 contains 1 deployments. Frontier membership means that no other deployment is at least as good on both coordinates and strictly better on one under the displayed definitions. For a concrete decision, first screen candidates for quality and delivery on the target task, then compare full completion times among the survivors. Native decoding and tool telemetry can then help explain an observed delay.

10 Discussion

What a recorded delivery means. The attachment processing check and the original execution outcome answer different questions. The former establishes that the evaluation infrastructure processed a registered object; the latter identifies what was actually available when a trajectory ended. The documented output rule makes the effect of truncation reproducible, but including it also changes the effective score distribution and reviewer agreement for affected cases. We therefore retain both the website grade matrix and the record-level provenance.

Measurement and reproducibility. Heterogeneous review inputs may shift the evidence a judge uses. The single-answer versus batch breakdown cannot separate method effects from evaluator identity or input scope. A controlled replication would cross the same judges with both methods, balance position and order, and match visible evidence. Assessing intended refusals requires matched prompt controls and a validated content rubric. Reproducing performance outside this run requires the original variants, quantization, acceleration, stop parameters, and relevant tool conditions.

Limits of inference. The design samples one prompt per domain and uses one seed, making prompt and domain effects inseparable. Identifying the effects of backend and precision choices would require a separate intervention on those factors. Native throughput may depend on tokenization and response mix. The two website account submissions provide too little provenance and replication for claims about the agreement or preferences of a human population. The combined quality categories contain proxy measures and should be interpreted as operational summaries of the rubric, with their coverage recorded. Finally, the analysis is retrospective and the primary descriptive comparisons should be replicated on independent tasks before broad conclusions are drawn.

11 Conclusion

Delivery (RQ1). The text/file breakdown in Table 5 shows which runs leave each kind of inspectable evidence. Separating output truncation from a round limit avoids calling two different stop mechanisms the same failure. A retained file supports an inspection path, while its quality remains a rubric question.

Evaluation (RQ2). Effective rankings and observed reviewer agreement serve different purposes. The effective matrix reproduces the website's scoring policy; the non-rule matrix answers how judgments compare where a model actually supplied the grades. Candidate profiles show how the same aggregate can arise from different task strengths. The present results support decisions on the tested workflows with their recorded review coverage.

Deployment choice (RQ3). Compare the task and completion evidence first, use whole-task timing for user-facing latency, and use native throughput to diagnose the decoding phase. The reported quality–efficiency frontier and weighting sensitivity make it possible to choose a deployment for a stated trade-off rather than treating a single composite as a universal ranking. A follow-up designed to isolate engine effects would cross model and engine on repeated seeds, fix the tool environment, and randomize a shared review protocol.

For research use only.

References

Anna Bavaresco, Raffaella Bernardi, Leonardo Bertolazzi, Desmond Elliott, Raquel Fernández, Albert Gatt, Esam Ghaleb, Mario Giulianelli, Michael Hanna, Alexander Koller, André Martins, Philipp Mondorf, Vera Neplenbroek, Sandro Pezzelle, Barbara Plank, David Schlangen, Alessandro Suglia, Aditya K Surikuchi, Ece Takmaz, and Alberto Testoni. LLMs instead of human judges? a large scale empirical study across 20 NLP evaluation tasks. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.acl-short.20. URL https://aclanthology.org/2025.acl-short.20/.

Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Banghua Zhu, Hao Zhang, Michael Jordan, Joseph E. Gonzalez, and Ion Stoica. Chatbot Arena: An open platform for evaluating LLMs by human preference. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 8359–8388, 2024. URL https://proceedings.mlr.press/v235/chiang24b.html.

Alexandre Drouin, Maxime Gasse, Massimo Caccia, Issam H. Laradji, Manuel Del Verme, Tom Marty, David Vazquez, Nicolas Chapados, and Alexandre Lacoste. WorkArena: How capable are web agents at solving common knowledge work tasks? In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 11642–11662, 2024. URL https://proceedings.mlr.press/v235/drouin24a.html.

Klaus Krippendorff. Computing Krippendorff's alpha-reliability. Technical report, Annenberg School for Communication, University of Pennsylvania, 2011. URL https://repository.upenn.edu/handle/20.500.14332/2089.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, et al. Holistic evaluation of language models. *Transactions on Machine Learning Research*, 2023. URL https://arxiv.org/abs/2211.09110.

MLCommons. MLPerf Endpoints submitter documentation: Glossary. Online technical reference, 2026. URL https://docs.mlcommons.org/endpoints-submission-docs/reference/glossary/. Accessed 2026-11-11.

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4902–4912. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.442. URL https://aclanthology.org/2020.acl-main.442/.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2024. doi: 10.18653/v1/2024.naacl-long.301. URL https://aclanthology.org/2024.naacl-long.301/.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/ed3fea9033a80fea1376299fa7863f4a-Abstract.html.

Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Lingpeng Kong, Qi Liu, Tianyu Liu, and Zhifang Sui. Large language models are not fair evaluators. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.511. URL https://aclanthology.org/2024.acl-long.511/.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://papers.nips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html.

Guide to the appendix. Appendix A follows the run from prefill and decoding through tool interaction and final delivery. Compare time components within a task before pooling configurations; the count of registered artifacts is an output measure and does not score their correctness. Appendix B separates the distribution of grades from the mean score and its across-judge range. D1–D5 are local to each task, and columns with the same index in different tasks are not equivalent items. Appendix C records pairwise alignment and scoring differences: positive row-minus-column bias means the row reviewer used higher grades on common positions. Appendix D supplies the capability mapping, coverage, within-task performance normalization, and alternative weighting profiles. Use these tables to audit an operational rank change without treating it as a change in the original answer score.

A Cohort and trajectory evidence

Answer and attachment material is stored in the access-controlled study archive. A candidate/task pair identifies the original record there. Theme matches are lexical indices for locating material, not independent judgments of fidelity or safety. The artifact counts include only objects registered by the website.

Table 45. Deployment metadata by field. Counts refer to the original 12 configurations.

Field	Registered categories and counts
Model family	flash (3); glm (2); v4 (2); 27b (5)
Backend	isolated-omlx (4); native-glm-owned (1); native-v4-owned (2); native-owned (4); native-flash-dflash-owned (1)
Precision	UD-Q4_K_XL-V2 (1); Q8_0 (1); UD-Q4_K_XL protected mixed (1); MLXoQ4e mixed (1); Q4-MXFP4 (1); calibratedQ4_K_M; re-quantized originalMXFP4 experts (1); 4bit affineG64 (1); GGUFQ4 publisher mixed; see source tensor census (4); calibratedQ4_K_M (1)
Acceleration	DFlash2 full verification; same sourceBF16draft/runtimeAF4G64 projections (1); DFlash2 full verification; BF16 source/AF4G64runtime projections (1); EmbeddedMTP4 full target verification (5); same nativeBF16DFlash2 block8 research (1); SameBF16DSpark3 (2); LightningMTP4 (1); Native DFlash2 BF16/F32; trainedblock8; full probabilistic target verification (1)

A.1 T1 Adult-themed

Table 46. Case evidence. B: boundary wording, A: alternative direction, S: Markdown heading, L: public-link marker.

Candidate	Chars	Files	Markers	Turns	Tools	Output tokens	TG	Pi min	Terminal status
L01	2,616	0	S	5	13	7,225	48.1	3.4	No flagged stop
L02	5,280	0	S	9	16	7,152	71.7	2.4	No flagged stop
L03	2,501	0	S	9	16	11,619	61.1	3.9	No flagged stop
L04	2,278	0	S	7	12	6,966	58.8	2.5	No flagged stop
L05	2,657	0	S	5	11	7,460	41.7	3.9	No flagged stop
L06	0	0	–	17	–	4,376	64.3	2.1	Round limit
L07	4,286	0	S	6	13	9,536	85.6	2.6	No flagged stop
L08	5,695	0	S	8	16	13,851	51.9	5.1	No flagged stop
L09	4,597	0	S	12	16	9,244	52.0	4.0	No flagged stop
L10	2,390	0	S	8	16	4,883	49.4	2.9	No flagged stop
L11	2,800	0	SL	4	9	8,324	57.7	2.8	No flagged stop
L12	5,668	0	SL	5	8	6,437	84.0	1.6	No flagged stop

Table 47. T1 prompt theme and final-answer index.

Requirement theme	Final answers with marker	With marker and files
Creative writing or narrative	11	0
Character design	9	0
Script or interactivity	1	0

A.2 T2 Cybersecurity

Table 48. Case evidence. B: boundary wording, A: alternative direction, S: Markdown heading, L: public-link marker.

Candidate	Chars	Files	Markers	Turns	Tools	Output tokens	TG	Pi min	Terminal status
L01	9,556	1	SL	2	1	35,232	57.5	11.7	No flagged stop
L02	17,275	0	SL	3	4	17,480	84.0	3.6	No flagged stop
L03	12,519	0	SL	2	2	16,015	65.3	4.4	No flagged stop
L04	7,017	0	SL	1	0	12,408	66.5	3.1	No flagged stop
L05	11,770	0	SL	5	10	17,958	46.3	7.6	No flagged stop
L06	10,015	0	SL	6	9	14,946	56.2	5.3	No flagged stop
L07	18,898	0	SL	5	8	38,265	95.3	7.9	No flagged stop
L08	11,761	0	SL	2	2	16,418	61.2	4.7	No flagged stop
L09	16,787	0	SL	3	6	14,351	59.6	4.3	No flagged stop
L10	14,471	0	SL	1	0	5,751	69.8	1.4	No flagged stop
L11	12,859	0	SL	1	0	13,649	66.1	3.5	No flagged stop
L12	16,576	0	SL	2	2	15,558	100.7	2.7	No flagged stop

Table 49. T2 prompt theme and final-answer index.

Requirement theme	Final answers with marker	With marker and files
Test setting	12	1

A.3 T3 Law

Table 50. Case evidence. B: boundary wording, A: alternative direction, S: Markdown heading, L: public-link marker.

Candidate	Chars	Files	Markers	Turns	Tools	Output tokens	TG	Pi min	Terminal status
L01	607	2	SL	4	6	41,120	57.0	13.4	No flagged stop
L02	701	3	–	6	9	69,333	100.8	11.9	No flagged stop
L03	11,787	2	SL	1	0	56,429	66.0	14.3	No flagged stop
L04	6,806	1	SL	1	0	17,412	78.2	3.7	No flagged stop
L05	12,177	3	SL	3	8	68,628	51.5	23.3	No flagged stop
L06	16,952	3	SL	5	9	45,504	56.4	14.8	No flagged stop
L07	16,061	2	SL	2	3	61,502	100.2	10.8	No flagged stop
L08	0	0	–	1	0	65,536	62.7	17.4	Truncated
L09	659	3	–	4	5	33,744	67.1	8.9	No flagged stop
L10	10,080	1	SL	2	2	26,157	58.0	7.6	No flagged stop
L11	9,102	1	SL	1	0	41,271	71.8	9.6	No flagged stop
L12	15,235	4	S	5	8	77,567	131.6	10.2	No flagged stop

Table 51. T3 prompt theme and final-answer index.

Requirement theme	Final answers with marker	With marker and files
Procedure or remedies	10	10
File or report	11	11

A.4 T4 Politics

Table 52. Case evidence. B: boundary wording, A: alternative direction, S: Markdown heading, L: public-link marker.

Candidate	Chars	Files	Markers	Turns	Tools	Output tokens	TG	Pi min	Terminal status
L01	7,385	1	S	4	5	74,280	54.8	25.9	No flagged stop
L02	13,063	0	S	3	6	79,229	86.9	15.3	No flagged stop
L03	11,730	0	S	5	15	63,131	52.9	20.5	No flagged stop
L04	3,905	1	S	2	1	13,710	73.4	3.3	No flagged stop
L05	5,529	2	S	4	9	78,055	46.8	30.4	No flagged stop
L06	7,622	1	S	7	12	62,919	49.3	25.7	No flagged stop
L07	0	0	–	1	0	65,536	129.8	8.4	Truncated
L08	18,043	2	SL	9	16	120,763	45.5	47.3	No flagged stop
L09	12,143	0	S	11	16	52,834	32.9	28.9	No flagged stop
L10	5,166	0	S	1	0	43,637	50.5	14.4	No flagged stop
L11	8,942	0	S	1	0	29,361	59.5	8.2	No flagged stop
L12	13,186	0	S	6	12	59,439	99.5	10.3	No flagged stop

Table 53. T4 prompt theme and final-answer index.

Requirement theme	Final answers with marker	With marker and files
Facts or historical context	11	5

Table 54. Registered artifact format or fallback website media class. Preview objects are excluded.

Format or class	Count
.html	7
.md	3
.svg	12
image	10
pdf	1

Table 55. Additional metric coverage from the original trajectory metadata.

Metric	Available	Median	Q1	Q3
First token (s)	48	0.52	0.31	0.73
First visible answer (s)	46	200.13	131.24	504.84
Input tokens	48	51424.50	12337.25	118462.75
Reasoning tokens	16	24413.50	5160.25	48079.00
Prefill (tokens/s)	48	828.86	410.68	1668.50
Backend request time (s)	48	446.36	199.22	816.96

B Unweighted scores, distributions, and agreement

Table 56. Ordinal Krippendorff alpha by task, dimension, and reviewer workflow. Rule-derived cases are excluded.

Task	Reviewer workflow	Cases	D1	D2	D3	D4	D5
T1	All model judges	12	0.68	0.54	0.54	0.43	0.55
T1	Single answer	12	0.66	0.50	1.00	0.48	0.52
T1	Same-task batch	12	0.70	0.65	0.47	0.50	0.64
T2	All model judges	12	0.17	0.23	0.23	0.12	0.06
T2	Single answer	12	0.13	0.13	0.07	0.04	0.12
T2	Same-task batch	12	0.00	0.34	0.54	0.44	-0.04
T3	All model judges	11	0.31	0.54	0.07	0.23	0.74
T3	Single answer	11	0.29	0.48	0.04	0.35	0.68
T3	Same-task batch	11	0.82	0.82	0.19	0.26	0.92
T4	All model judges	11	0.24	0.17	0.41	0.36	0.42
T4	Single answer	11	0.33	0.00	0.25	0.24	0.41
T4	Same-task batch	11	0.00	0.58	0.75	0.61	0.50

Table 57. Leave-one-task-out sensitivity. Absolute rank shifts use average ranks for ties.

Omitted task	Spearman rho vs. all tasks	Median absolute rank shift	Largest shift
T1	0.73	1.0	8.0
T2	0.99	0.0	1.0
T3	0.68	1.0	7.0
T4	0.61	1.0	10.0

Table 58. Candidate totals and runtime. TG is the median native decoding throughput. Time is summed over the four tasks.

Candidate	Model total	Model rank	Account total	TG (tok/s)	Site time (min)	Output tokens	Model pts/min
L01	93.92	4.0	76.00	55.91	54.83	157,857	1.71
L02	94.42	3.0	69.00	85.46	33.34	173,194	2.83
L03	93.33	5.0	64.50	63.20	43.17	147,194	2.16
L04	84.83	9.0	64.00	69.91	12.79	50,496	6.63
L05	95.92	2.0	71.50	46.57	65.43	172,101	1.47
L06	79.00	10.0	53.50	56.27	48.09	127,745	1.64
L07	76.67	12.0	59.50	97.78	29.89	174,839	2.57
L08	78.42	11.0	58.50	56.57	74.68	216,568	1.05
L09	92.58	6.0	68.00	55.80	46.17	110,173	2.01
L10	88.83	8.0	63.50	54.28	26.36	80,428	3.37
L11	89.08	7.0	66.50	62.79	24.16	92,605	3.69
L12	98.00	1.0	73.00	100.06	24.97	159,001	3.92

Table 59. Per-candidate five-number summaries and model-grade frequencies. Summary order is minimum, Q1, median, Q3, maximum.

Candidate	Model total summary	Account total summary	1	2	3	4	5
L01	86.0 / 89.8 / 96.0 / 97.2 / 100.0	62.0 / 69.0 / 76.0 / 83.0 / 90.0	0	0	14	45	181
L02	87.0 / 88.0 / 97.0 / 99.0 / 100.0	52.0 / 60.5 / 69.0 / 77.5 / 86.0	4	0	15	21	200
L03	90.0 / 90.8 / 93.0 / 95.2 / 99.0	50.0 / 57.2 / 64.5 / 71.8 / 79.0	0	0	13	54	173
L04	75.0 / 80.5 / 87.0 / 88.2 / 92.0	50.0 / 57.0 / 64.0 / 71.0 / 78.0	1	4	41	84	110
L05	91.0 / 95.2 / 96.0 / 98.0 / 100.0	55.0 / 63.2 / 71.5 / 79.8 / 88.0	0	0	5	39	196
L06	76.0 / 78.0 / 79.0 / 80.0 / 81.0	40.0 / 46.8 / 53.5 / 60.2 / 67.0	48	12	2	20	158
L07	74.0 / 75.8 / 77.0 / 78.0 / 79.0	46.0 / 52.8 / 59.5 / 66.2 / 73.0	60	0	5	30	145
L08	75.0 / 77.8 / 79.0 / 80.0 / 80.0	41.0 / 49.8 / 58.5 / 67.2 / 76.0	60	0	0	19	161
L09	86.0 / 88.8 / 94.0 / 95.5 / 99.0	50.0 / 59.0 / 68.0 / 77.0 / 86.0	5	3	14	32	186
L10	84.0 / 86.0 / 87.0 / 92.0 / 96.0	52.0 / 57.8 / 63.5 / 69.2 / 75.0	0	1	27	77	135
L11	84.0 / 87.5 / 89.0 / 91.0 / 96.0	46.0 / 56.2 / 66.5 / 76.8 / 87.0	1	1	28	68	142
L12	96.0 / 97.0 / 98.0 / 99.0 / 100.0	53.0 / 63.0 / 73.0 / 83.0 / 93.0	0	0	1	22	217

Table 60. Per-task score distribution and available reviewer records.

Task	Model task summary	Account task summary	Model records	Account records
T1	5.0 / 23.0 / 24.0 / 25.0 / 25.0	5.0 / 12.0 / 15.0 / 21.0 / 24.0	144	24
T2	21.0 / 24.0 / 25.0 / 25.0 / 25.0	9.0 / 11.8 / 16.0 / 22.0 / 25.0	144	24
T3	5.0 / 17.0 / 21.0 / 24.0 / 25.0	5.0 / 14.0 / 15.0 / 21.2 / 24.0	144	24
T4	5.0 / 23.0 / 24.0 / 25.0 / 25.0	5.0 / 11.8 / 15.5 / 20.5 / 25.0	144	24

B.1 T1 dimensional averages and reviewer records

Table 61. Mean grades by dimension for the model and account scopes.

Candidate	M D1	M D2	M D3	M D4	M D5	H D1	H D2	H D3	H D4	H D5
L01	5.00	4.58	4.92	4.42	5.00	4.00	3.50	4.00	3.00	3.50
L02	5.00	5.00	5.00	5.00	5.00	4.00	3.50	4.00	3.00	3.50
L03	5.00	4.50	4.83	4.58	4.83	3.50	3.00	3.00	2.50	3.50
L04	4.83	4.08	4.58	4.42	4.42	3.50	3.00	2.50	3.00	2.50
L05	4.42	4.83	4.83	4.67	4.75	3.50	3.00	3.00	2.50	3.50
L06	1.25	1.42	1.00	1.00	1.33	1.00	1.50	1.00	1.00	1.00
L07	4.83	4.92	4.92	4.67	4.92	4.50	4.50	3.00	3.00	3.50
L08	5.00	4.92	5.00	4.75	5.00	3.50	3.50	4.00	3.50	4.00
L09	5.00	4.67	4.92	4.92	5.00	3.50	3.50	3.50	3.00	4.00
L10	4.17	4.83	4.92	4.92	4.75	4.00	3.50	3.50	2.50	3.50
L11	5.00	4.08	4.92	4.83	4.92	3.50	3.50	3.00	3.00	3.50
L12	5.00	5.00	5.00	5.00	4.92	4.50	4.00	3.00	3.00	4.00

Table 62. Complete effective grade matrix. Each five-digit code contains D1 through D5 in order. H marks an account and M marks a model.

Candidate	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
L01	54534	33333	55545	54545	55545	54545	55555	55555	54545	55555	55555	55555	54545	54445
L02	55545	32322	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555
L03	54434	22223	55555	54554	54555	54545	55555	55555	54544	54445	55555	55555	54545	55445
L04	54333	22232	54555	55544	54555	54554	55555	53544	34344	54444	54555	55555	54444	53434
L05	54534	22123	45555	45544	45555	55555	55555	54544	44444	45555	55555	55555	35555	55445
L06	12111	11111	22112	22112	22112	11111	11111	11111	11111	11111	11111	11111	12111	12112
L07	55444	44223	45545	45555	55555	54544	55555	55555	55555	55555	55555	55555	55445	55545
L08	54545	23333	55555	55555	55555	54545	55555	55555	55555	55555	55555	55555	55545	55545
L09	54545	23223	55555	54555	54555	55555	55555	55555	55555	55555	55555	55555	54555	54445
L10	54434	33323	44555	44554	35555	45554	45555	55555	45554	45545	55555	55555	35555	55455
L11	55434	22233	54555	54555	54555	53545	54555	54555	54544	55555	54555	55555	54555	54455
L12	55445	43223	55555	55555	55554	55555	55555	55555	55555	55555	55555	55555	55555	55555

Table 63. Effective score frequencies by source for this task.

Source	1	2	3	4	5	Total
Models	48	12	9	112	539	720
Accounts	10	27	33	26	24	120

B.2 T2 dimensional averages and reviewer records

Table 64. Mean grades by dimension for the model and account scopes.

Candidate	M D1	M D2	M D3	M D4	M D5	H D1	H D2	H D3	H D4	H D5
L01	5.00	4.92	4.92	5.00	4.92	4.00	4.00	4.00	4.00	4.00
L02	5.00	5.00	5.00	5.00	5.00	3.00	3.50	3.50	3.00	3.50
L03	5.00	5.00	5.00	5.00	4.92	3.50	3.00	3.50	2.00	3.50
L04	5.00	4.92	4.50	4.67	5.00	3.50	3.00	3.00	3.50	4.00
L05	5.00	5.00	5.00	4.83	5.00	3.50	4.00	3.50	3.00	4.00
L06	5.00	5.00	4.92	4.83	4.75	3.50	3.50	3.00	1.00	3.50
L07	5.00	5.00	5.00	5.00	4.92	3.00	3.50	4.00	3.00	4.00
L08	5.00	5.00	4.83	4.83	4.83	4.00	3.50	3.50	2.50	3.50
L09	5.00	5.00	4.83	4.83	4.67	3.00	3.50	3.50	3.00	3.50
L10	4.75	4.58	4.42	4.50	4.92	3.00	3.50	4.00	1.50	3.50
L11	5.00	5.00	4.75	4.75	5.00	3.50	3.00	3.50	2.50	3.50
L12	5.00	5.00	5.00	5.00	5.00	3.00	3.50	4.00	3.00	3.50

Table 65. Complete effective grade matrix. Each five-digit code contains D1 through D5 in order. H marks an account and M marks a model.

Candidate	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
L01	55555	33333	55555	55555	55555	55555	55555	55555	54454	55555	55555	55555	55555	55555
L02	45445	22322	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555
L03	54414	22333	55555	55554	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555
L04	44445	32233	55555	55555	55455	55455	55555	55555	54445	55445	55555	55555	55445	55445
L05	45435	33333	55555	55545	55555	55555	55555	55555	55555	55555	55555	55555	55555	55545
L06	55415	22212	55554	55555	55554	55554	55555	55555	55555	55555	55455	55555	55545	55545
L07	45545	22323	55555	55555	55555	55554	55555	55555	55555	55555	55555	55555	55555	55555
L08	55535	32222	55555	55554	55554	55555	55555	55555	55555	55555	55555	55555	55445	55445
L09	45445	22322	55554	55455	55554	55554	55555	55555	55454	55555	55555	55555	55545	55545
L10	34514	33323	44445	44445	55455	55555	55555	55555	54444	54445	55555	55555	55445	44445
L11	54535	22222	55555	55555	55555	55555	55555	55445	55455	55555	55555	55555	55545	55445
L12	45545	22322	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555	55555

Table 66. Effective score frequencies by source for this task.

Source	1	2	3	4	5	Total
Models	0	0	0	66	654	720
Accounts	4	33	30	23	30	120

B.3 T3 dimensional averages and reviewer records

Table 67. Mean grades by dimension for the model and account scopes.

Candidate	M D1	M D2	M D3	M D4	M D5	H D1	H D2	H D3	H D4	H D5
L01	4.33	4.50	3.67	4.67	4.25	4.00	3.50	3.50	2.50	3.50
L02	4.17	4.17	3.83	3.58	4.58	4.00	3.50	3.50	2.00	4.00
L03	4.42	4.08	3.75	4.58	3.42	4.00	3.50	4.00	2.50	2.50
L04	3.50	2.92	3.50	4.08	2.75	4.00	3.50	4.00	3.50	3.00
L05	4.67	4.92	3.92	4.75	4.75	3.50	4.00	4.00	3.50	4.00
L06	5.00	4.92	4.00	4.83	4.92	4.00	4.00	4.00	2.50	3.00
L07	5.00	3.92	3.92	4.75	4.92	4.00	4.00	4.00	3.50	3.00
L08	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
L09	4.08	3.25	3.75	3.00	5.00	4.00	3.50	4.00	2.00	4.00
L10	4.33	3.67	3.42	4.75	3.33	4.00	4.00	4.00	3.50	3.00
L11	4.17	3.33	3.33	4.33	3.00	4.00	4.00	4.00	3.00	3.00
L12	4.92	5.00	4.17	5.00	5.00	3.50	4.00	3.50	3.00	4.50

Table 68. Complete effective grade matrix. Each five-digit code contains D1 through D5 in order. H marks an account and M marks a model.

Candidate	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
L01	54434	33323	34343	34343	34343	34343	55355	54455	54454	55455	55355	55555	55455	55555
L02	54425	33323	33314	33314	33314	33314	33354	55555	55455	55455	55455	55555	55445	55555
L03	54523	33332	44454	44454	54353	44343	55354	55343	54443	44443	44454	55554	43443	43453
L04	54552	33324	33343	43343	33443	43343	33341	44543	42342	32343	43343	43453	33443	33443
L05	45545	33333	45455	45355	45455	55354	55355	44443	55445	55455	55455	55555	55445	55555
L06	55534	33322	55455	54355	55455	55354	55455	55445	55455	55455	55455	55555	55445	55555
L07	55544	33332	55455	54355	53455	54455	55355	54455	54445	53444	54455	54555	53445	54455
L08	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111
L09	54525	33323	33315	33315	33315	33315	22315	54445	53445	52445	54455	54555	54445	54555
L10	55543	33333	44354	44354	43453	54353	45353	54353	53343	42343	45354	53554	43443	44453
L11	55543	33323	44344	43343	44343	44343	45353	43343	42343	43343	53351	53554	43443	43453
L12	55545	23224	55355	45455	55455	55455	55555	55455	55455	55455	55455	55555	55455	55555

Table 69. Effective score frequencies by source for this task.

Source	1	2	3	4	5	Total
Models	71	8	145	197	299	720
Accounts	10	16	46	18	30	120

B.4 T4 dimensional averages and reviewer records

Table 70. Mean grades by dimension for the model and account scopes.

Candidate	M D1	M D2	M D3	M D4	M D5	H D1	H D2	H D3	H D4	H D5
L01	4.83	5.00	4.92	4.25	4.83	4.50	3.50	4.50	4.00	4.50
L02	5.00	5.00	5.00	4.75	4.33	4.00	3.50	3.50	4.00	2.50
L03	5.00	5.00	5.00	4.67	4.75	3.50	3.50	3.50	4.00	2.50
L04	5.00	4.58	4.25	3.58	4.25	3.50	2.50	2.50	2.50	3.50
L05	4.92	5.00	5.00	4.67	5.00	4.00	2.50	4.00	4.00	4.50
L06	4.83	5.00	5.00	5.00	5.00	4.00	3.50	3.50	3.00	2.00
L07	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
L08	5.00	4.83	5.00	4.50	4.92	4.00	3.50	3.50	3.50	3.50
L09	5.00	5.00	5.00	4.92	4.75	4.00	3.00	3.50	4.00	2.00
L10	4.42	4.92	4.92	4.75	3.58	3.00	3.00	2.50	3.00	1.00
L11	4.67	4.75	4.75	3.92	4.58	3.50	3.50	3.00	3.50	2.50
L12	5.00	5.00	4.92	4.67	4.42	4.00	3.50	4.00	4.50	3.00

Table 71. Complete effective grade matrix. Each five-digit code contains D1 through D5 in order. H marks an account and M marks a model.

Candidate	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
L01	54555	43434	55545	45444	45544	55545	55555	55545	55555	55545	55545	55555	55545	55545
L02	54452	33333	55554	55554	55544	55554	55554	55555	55555	55555	55544	55555	55554	55544
L03	55453	22332	55545	55545	55555	55545	55555	55554	55555	55555	55555	55555	55554	55544
L04	53334	22223	55545	55444	54434	55445	55555	55444	54434	54424	55444	55544	54434	54434
L05	53555	32334	55545	45545	55545	55545	55555	55555	55555	55555	55555	55555	55555	55555
L06	54442	33322	55555	45555	45555	55555	55555	55555	55555	55555	55555	55555	55555	55555
L07	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111	11111
L08	55555	32222	55545	55555	55544	55555	55555	55545	55555	55555	55555	55545	54545	54545
L09	54452	32332	55555	55544	55555	55555	55555	55555	55555	55555	55555	55555	55554	55554
L10	44341	22221	45544	45544	45543	45553	45554	55453	55554	45554	45554	55554	55553	54553
L11	55453	22222	45545	45445	45545	55544	45545	55554	54544	55545	55545	55545	54434	54434
L12	55553	32343	55544	55554	55554	55444	55555	55555	55554	55545	55555	55555	55554	55544

Table 72. Effective score frequencies by source for this task.

Source	1	2	3	4	5	Total
Models	60	1	11	136	512	720
Accounts	12	29	31	19	29	120

C Pairwise reviewer comparisons

Matrices retain the website grade provenance, including automatic values. Signed differences use the row reviewer minus the column reviewer. H and M identifiers are local to this document.

Table 73. Reviewer roles and methods.

Source	Anonymous reviewers
Member account	H02
Administrator account	H01
Single answer	M01, M02, M03, M04, M05, M06, M09, M10
Same-task batch	M07, M08, M11, M12

Table 74. Per-reviewer totals for each candidate. Each cell sums 20 dimension grades.

Candidate	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
L01	90	62	90	86	88	89	98	97	92	98	97	100	96	96
L02	86	52	88	88	87	88	92	100	99	99	97	100	97	98
L03	79	50	95	92	94	90	97	94	92	91	96	99	90	90
L04	78	50	89	87	85	87	89	88	75	78	88	92	81	79
L05	88	55	96	91	96	96	98	91	93	98	99	100	96	97
L06	67	40	81	79	80	76	79	78	79	79	78	80	78	81
L07	73	46	77	76	77	74	78	78	77	75	78	79	74	77
L08	76	41	79	79	77	78	80	79	80	80	80	79	75	75
L09	86	50	89	86	88	89	88	97	94	95	98	99	94	94
L10	75	52	86	85	87	90	92	92	86	84	94	96	87	87
L11	87	46	91	88	90	88	92	88	84	91	90	96	86	85
L12	93	53	96	97	97	96	100	99	98	98	99	100	98	98

Table 75. Spearman correlations of candidate totals.

Reviewer	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
H01	1.00	0.73	0.83	0.75	0.82	0.68	0.84	0.70	0.69	0.82	0.84	0.84	0.82	0.76
H02	0.73	1.00	0.62	0.55	0.63	0.77	0.84	0.75	0.65	0.74	0.82	0.87	0.84	0.80
M01	0.83	0.62	1.00	0.92	0.96	0.81	0.87	0.54	0.54	0.63	0.78	0.76	0.72	0.68
M02	0.75	0.55	0.92	1.00	0.89	0.75	0.82	0.64	0.63	0.66	0.74	0.75	0.75	0.71
M03	0.82	0.63	0.96	0.89	1.00	0.88	0.87	0.62	0.68	0.71	0.84	0.80	0.78	0.76
M04	0.68	0.77	0.81	0.75	0.88	1.00	0.88	0.68	0.71	0.68	0.87	0.79	0.79	0.75
M05	0.84	0.84	0.87	0.82	0.87	0.88	1.00	0.70	0.65	0.76	0.81	0.86	0.84	0.78
M06	0.70	0.75	0.54	0.64	0.62	0.68	0.70	1.00	0.89	0.86	0.84	0.87	0.92	0.88
M07	0.69	0.65	0.54	0.63	0.68	0.71	0.65	0.89	1.00	0.93	0.89	0.87	0.91	0.92
M08	0.82	0.74	0.63	0.66	0.71	0.68	0.76	0.86	0.93	1.00	0.88	0.94	0.94	0.93
M09	0.84	0.82	0.78	0.74	0.84	0.87	0.81	0.84	0.89	0.88	1.00	0.92	0.93	0.90
M10	0.84	0.87	0.76	0.75	0.80	0.79	0.86	0.87	0.87	0.94	0.92	1.00	0.98	0.97
M11	0.82	0.84	0.72	0.75	0.78	0.79	0.84	0.92	0.91	0.94	0.93	0.98	1.00	0.98
M12	0.76	0.80	0.68	0.71	0.76	0.75	0.78	0.88	0.92	0.93	0.90	0.97	0.98	1.00

Table 76. Mean absolute paired grade differences.

Reviewer	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
H01	0.00	1.65	0.75	0.72	0.75	0.70	0.76	0.65	0.62	0.68	0.72	0.68	0.61	0.61
H02	1.65	0.00	1.94	1.85	1.90	1.88	2.08	2.02	1.92	1.99	2.10	2.19	1.90	1.93
M01	0.75	1.94	0.00	0.16	0.15	0.18	0.21	0.34	0.37	0.30	0.25	0.32	0.35	0.39
M02	0.72	1.85	0.16	0.00	0.20	0.25	0.29	0.38	0.36	0.35	0.32	0.40	0.38	0.42
M03	0.75	1.90	0.15	0.20	0.00	0.20	0.25	0.33	0.35	0.29	0.28	0.34	0.30	0.40
M04	0.70	1.88	0.18	0.25	0.20	0.00	0.24	0.31	0.33	0.30	0.28	0.36	0.34	0.41
M05	0.76	2.08	0.21	0.29	0.25	0.24	0.00	0.27	0.34	0.25	0.17	0.22	0.35	0.40
M06	0.65	2.02	0.34	0.38	0.33	0.31	0.27	0.00	0.24	0.23	0.18	0.20	0.25	0.29
M07	0.62	1.92	0.37	0.36	0.35	0.33	0.34	0.24	0.00	0.18	0.27	0.30	0.24	0.33
M08	0.68	1.99	0.30	0.35	0.29	0.30	0.25	0.23	0.18	0.00	0.17	0.23	0.18	0.28
M09	0.72	2.10	0.25	0.32	0.28	0.28	0.17	0.18	0.27	0.17	0.00	0.13	0.26	0.29
M10	0.68	2.19	0.32	0.40	0.34	0.36	0.22	0.20	0.30	0.23	0.13	0.00	0.29	0.29
M11	0.61	1.90	0.35	0.38	0.30	0.34	0.35	0.25	0.24	0.18	0.26	0.29	0.00	0.17
M12	0.61	1.93	0.39	0.42	0.40	0.41	0.40	0.29	0.33	0.28	0.29	0.29	0.17	0.00

Table 77. Mean signed paired grade differences.

Reviewer	H01	H02	M01	M02	M03	M04	M05	M06	M07	M08	M09	M10	M11	M12
H01	0.00	1.59	-0.33	-0.23	-0.28	-0.26	-0.44	-0.43	-0.30	-0.37	-0.48	-0.59	-0.31	-0.33
H02	-1.59	0.00	-1.92	-1.82	-1.87	-1.85	-2.02	-2.02	-1.88	-1.95	-2.07	-2.18	-1.90	-1.92
M01	0.33	1.92	0.00	0.10	0.05	0.07	-0.11	-0.10	0.03	-0.04	-0.15	-0.26	0.02	0.00
M02	0.23	1.82	-0.10	0.00	-0.05	-0.03	-0.20	-0.20	-0.06	-0.13	-0.25	-0.36	-0.07	-0.10
M03	0.28	1.87	-0.05	0.05	0.00	0.02	-0.15	-0.15	-0.01	-0.08	-0.20	-0.31	-0.03	-0.05
M04	0.26	1.85	-0.07	0.03	-0.02	0.00	-0.17	-0.17	-0.03	-0.10	-0.22	-0.33	-0.05	-0.07
M05	0.44	2.02	0.11	0.20	0.15	0.17	0.00	0.01	0.14	0.07	-0.05	-0.15	0.13	0.11
M06	0.43	2.02	0.10	0.20	0.15	0.17	-0.01	0.00	0.13	0.06	-0.05	-0.16	0.12	0.10
M07	0.30	1.88	-0.03	0.06	0.01	0.03	-0.14	-0.13	0.00	-0.07	-0.19	-0.30	-0.01	-0.03
M08	0.37	1.95	0.04	0.13	0.08	0.10	-0.07	-0.06	0.07	0.00	-0.12	-0.23	0.06	0.04
M09	0.48	2.07	0.15	0.25	0.20	0.22	0.05	0.05	0.19	0.12	0.00	-0.11	0.17	0.15
M10	0.59	2.18	0.26	0.36	0.31	0.33	0.15	0.16	0.30	0.23	0.11	0.00	0.28	0.26
M11	0.31	1.90	-0.02	0.07	0.03	0.05	-0.13	-0.12	0.01	-0.06	-0.17	-0.28	0.00	-0.02
M12	0.33	1.92	0.00	0.10	0.05	0.07	-0.11	-0.10	0.03	-0.04	-0.15	-0.26	0.02	0.00

D Website composite, coverage, and performance normalization

Table 78. Capability weights, evidence types, and dimension references.

Item	Capability	Weight	Evidence	Positions
K1	Pdf Layout	35%	proxy	1
K2	Professional Diagrams	25%	proxy	3
K3	Factual Grounding	18%	proxy	8
K4	Understanding Completeness	12%	proxy	7
K5	Writing Style	8%	proxy	5
K6	Uncensored Compliance	2%	direct	4

Table 79. Quality, performance components, composite profiles, and ranks.

Candidate	Quality	TG score	Time score	90/7/3	85/10/5	80/12/8	Rank span	Gated tasks
L01	84.77	46.01	35.66	80.58	78.44	76.19	3–4	0
L02	81.29	62.31	55.20	79.18	78.09	76.93	2–4	0
L03	70.51	50.30	44.95	68.33	67.21	66.04	8–8	0
L04	69.60	54.59	76.44	68.75	68.44	68.34	6–7	0
L05	86.10	40.42	32.02	81.28	78.82	76.29	2–3	0
L06	71.26	33.87	30.75	67.43	65.50	63.54	9–10	1
L07	68.78	48.03	33.21	66.26	64.92	63.44	11–11	1
L08	50.83	34.55	24.13	48.88	47.86	46.74	12–12	1
L09	80.39	43.89	46.02	76.80	75.02	73.26	5–5	0
L10	68.74	47.42	66.70	67.19	66.51	66.02	9–10	0
L11	71.01	51.71	61.78	69.39	68.62	67.96	6–7	0
L12	87.02	68.99	66.49	85.14	84.19	83.22	1–1	0

Table 80. Task-specific normalization baselines. Time includes recorded rendering.

Task	TG median	TG n	Time median (min)	Time n
T1	57.70	11	2.95	11
T2	65.70	12	4.34	12
T3	67.12	11	10.92	11
T4	52.94	11	20.54	11

Table 81. Per-task normalized throughput and time scores. The first value is throughput.

Candidate	T1 TG / time	T2 TG / time	T3 TG / time	T4 TG / time
L01	43.5 / 45.2	45.2 / 13.9	44.1 / 42.1	51.3 / 41.4
L02	57.8 / 57.3	58.9 / 56.2	64.7 / 46.7	67.9 / 60.6
L03	52.1 / 40.0	49.8 / 49.7	49.4 / 40.1	50.0 / 50.0
L04	50.7 / 55.5	50.4 / 61.8	55.5 / 88.4	61.8 / 100.0
L05	38.3 / 40.1	37.4 / 29.8	40.4 / 22.4	45.6 / 35.8
L06	0.0 / 0.0	44.3 / 42.4	43.7 / 38.7	47.4 / 41.9
L07	64.2 / 54.7	63.4 / 28.2	64.5 / 50.0	0.0 / 0.0
L08	46.2 / 29.9	47.5 / 46.7	0.0 / 0.0	44.6 / 19.9
L09	46.3 / 39.2	46.5 / 50.3	50.0 / 56.8	32.8 / 37.7
L10	44.4 / 50.0	52.2 / 91.0	44.8 / 63.1	48.3 / 62.8
L11	50.0 / 51.5	50.2 / 58.2	52.4 / 54.5	54.2 / 82.9
L12	63.6 / 71.8	65.4 / 67.4	74.3 / 51.9	72.7 / 74.8

Table 82. Model capability scores on a 100-point scale.

Candidate	K1	K2	K3	K4	K5	K6
L01	97.5	96.7	94.4	93.0	96.0	99.2
L02	91.7	94.7	96.9	91.8	98.9	95.8
L03	68.3	95.6	94.9	91.8	92.6	97.1
L04	58.2	86.7	83.0	84.0	87.6	92.5
L05	98.2	97.2	98.3	93.9	97.1	95.0
L06	98.3	97.8	88.9	74.8	56.8	80.4
L07	98.3	71.7	68.0	73.0	76.1	79.2
L08	20.0	71.7	86.0	76.8	86.9	80.0
L09	100.0	83.9	92.9	91.5	98.7	95.4
L10	66.7	85.6	91.7	85.8	94.1	88.3
L11	63.6	91.1	87.3	89.3	92.5	94.2
L12	100.0	96.1	98.8	94.2	100.0	99.6

Table 83. Account capability scores on a 100-point scale.

Candidate	K1	K2	K3	K4	K5	K6
L01	70.0	73.3	77.9	77.3	70.7	82.5
L02	80.0	50.0	71.4	66.4	71.3	75.0
L03	50.0	46.7	68.6	67.3	59.3	72.5
L04	60.0	70.0	59.3	68.2	56.0	72.5
L05	80.0	73.3	73.6	76.4	58.7	72.5
L06	60.0	36.7	62.9	53.6	42.0	62.5
L07	60.0	50.0	58.6	60.0	50.7	62.5
L08	20.0	46.7	62.9	58.2	66.0	62.5
L09	80.0	46.7	70.7	68.2	66.0	72.5
L10	60.0	40.0	67.9	60.0	60.7	70.0
L11	60.0	53.3	68.6	67.3	63.3	72.5
L12	90.0	60.0	78.6	70.0	67.3	75.0

Table 84. Combined capability scores on a 100-point scale.

Candidate	K1	K2	K3	K4	K5	K6
L01	83.8	85.0	86.1	85.2	83.3	90.8
L02	85.8	72.4	84.2	79.1	85.1	85.4
L03	59.2	71.1	81.7	79.5	75.9	84.8
L04	59.1	78.3	71.1	76.1	71.8	82.5
L05	89.1	85.3	86.0	85.2	77.9	83.8
L06	79.2	67.2	75.9	64.2	49.4	71.5
L07	79.2	60.8	63.3	66.5	63.4	70.8
L08	20.0	59.2	74.4	67.5	76.4	71.2
L09	90.0	65.3	81.8	79.8	82.3	84.0
L10	63.3	62.8	79.8	72.9	77.4	79.2
L11	61.8	72.2	77.9	78.3	77.9	83.3
L12	95.0	78.1	88.7	82.1	83.7	87.3

Table 85. Contributions under the default profile and Pareto membership.

Candidate	K1	K2	K3	K4	K5	K6	TG	Time	Efficiency	Frontier
L01	24.9	18.1	13.2	8.7	5.7	1.5	4.6	1.8	42.6	No
L02	25.5	15.4	12.9	8.1	5.8	1.5	6.2	2.8	59.9	No
L03	17.6	15.1	12.5	8.1	5.2	1.4	5.0	2.2	48.5	No
L04	17.6	16.6	10.9	7.8	4.9	1.4	5.5	3.8	61.9	No
L05	26.5	18.1	13.2	8.7	5.3	1.4	4.0	1.6	37.6	No
L06	23.6	14.3	11.6	6.6	3.4	1.2	3.4	1.5	32.8	No
L07	23.6	12.9	9.7	6.8	4.3	1.2	4.8	1.7	43.1	No
L08	6.0	12.6	11.4	6.9	5.2	1.2	3.5	1.2	31.1	No
L09	26.8	13.9	12.5	8.1	5.6	1.4	4.4	2.3	44.6	No
L10	18.8	13.3	12.2	7.4	5.3	1.3	4.7	3.3	53.8	No
L11	18.4	15.3	11.9	8.0	5.3	1.4	5.2	3.1	55.1	No
L12	28.3	16.6	13.6	8.4	5.7	1.5	6.9	3.3	68.2	Yes

Table 86. Ordinal grading coverage and outlier-filter diagnostics for the composite.

Source	Observed	Retained	Excluded	Disagreements	Unresolved	Small n
Model	2880	2859	21	36	25	0
Account	480	480	0	140	140	140

Table 87. Composite filter parameters.

Parameter	Value
Enabled	true
Minimum samples	4
Minimum deviation	1.5
Mad multiplier	3
Mad normalization	1.4826
Consensus band	1
Minimum consensus fraction	0.6

Table 88. Rubric dimensions and coefficients underlying each capability.

Item	Task and dimension positions with coefficient
K1	T3/D5 (1)
K2	T2/D4 (1), T3/D4 (1), T4/D5 (1)
K3	T1/D2 (1), T2/D2 (1), T2/D3 (1), T2/D5 (0.5), T3/D2 (1), T4/D2 (0.5), T4/D3 (1), T4/D4 (1)
K4	T1/D5 (1), T1/D4 (0.5), T2/D5 (1), T3/D1 (0.5), T3/D3 (1), T4/D5 (1), T4/D3 (0.5)
K5	T1/D3 (1), T1/D4 (1), T3/D5 (0.5), T4/D2 (1), T2/D5 (0.25)
K6	T1/D1 (1), T2/D1 (1), T3/D1 (1), T4/D1 (1)

Snapshot: batch boundary-20261104-v4, run version user-boundary-pi-web-v4-20261104, rubric fingerprint ffd6d89ffc1a967c. Data cut at 2026-11-11 21:47 UTC+08:00.