## Recall, Recall rate@k and precision in top-k recommendation

Asked 5 years, 4 months ago Active 12 months ago Viewed 23k times



12

According to authors in 1, 2, and 3, **Recall** is the percentage of relevant items selected out of all the relevant items in the repository, while **Precision** is the percentage of relevant items out of those items selected by the guery.



 $\star$ 

Therefore, assuming user U gets a top-k recommended list of items, they would be something like:



**Recall**= (Relevant\_Items\_Recommended in top-*k*) *I* (Relevant\_Items)

**Precision**= (Relevant\_Items\_Recommended in top-*k*) *I* (*k*\_Items\_Recommended)

Until that part everything is clear but I do not understand the difference between them and **Recall rate@k**. How would be the formula to compute **recall rate@k**?


recommendation-engine

evaluation

precision-recall

Share Improve this question Follow





You directly put @K in calculating simple Precision and Recall for rating prediction what may be confusing. The rule is simple - if You try to measure only RATING prediction - use simple Precision and Recall on the whole recommended result. If You are interested in measure RANKING prediction, then You are more interested how well let say top-5 performs (first recommendation carousel screen), then top-10 (second screen) and so on. Because in second case You are more interested in how well Your solution ordered the whole response - ranked results. – Bartłomiej Twardowski Nov 15 '15 at 10:26

Thank you so much @Bartłomiej Twardowski. So, just I was doing that rate@k already? – Luisa Hernández Nov 16 ¹15 at 11:25 ✓

Yes, if you are truncating to top k item and only calculating p/r on it. – Bartłomiej Twardowski Nov 16 '15 at 13:03

## 1 Answer

Active Oldest Votes

答えが見つからない?日本語で聞いてみましょう。





13

Finally, I received an explanation from Prof. Yuri Malheiros (<u>paper 1</u>). Although recall rate@*k* as cited in papers cited in the questions seemed to be the normal recall metrics but applied into a top-*k*, they are not the same. This metric is also used in paper 2, paper 3 and paper 3


**Join Stack Overflow** to learn, share knowledge, and build your career.





of items for each recommendation), to calculate the recall rate is necessary to look at each of the 50 recommendations. If, for each recommendation, at least one recommended item is correct, you can increment a value, in this case, let us call it *N*. In order to calculate the recall rate@*R*, it is necessary to make the *N/R*.

Share Improve this answer Follow



- I think you made a mistake there, you described the precision@k again. Recall@k means you count the relevant documents among the top-k and divide it by the total number of relevant documents in the repository. See <a href="mailto:ils.unc.edu/courses/2013\_spring/inls509\_001/lectures/...">ils.unc.edu/courses/2013\_spring/inls509\_001/lectures/...</a> Chris Jul 12 '17 at 16:58
- Agree with Chris. What you're describing sounds like mean precision@k. halflings Nov 8 '18 at 4:25

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up