
test_coordonees_perceptives

Laurent Perrinet (INT, UMR7289)

February 27, 2014

```
In [3]: import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

```
In [4]: from parametres import VPs, volume, p, d_x, d_y, d_z, calibration, DEBUG
from modele_dynamique import arcdistance, orientation, xyz2azel, rae2xyz
DEBUG parametres , position croix: [ 0.          3.76999998  1.37
]
```

```
In [5]: print xyz2azel.__doc__
renvoie le vecteur de coordonnées perceptuelles en fonction des
coordonnées physiques
```

xyz = 3 x N x ...

Le vecteur OV désigne le centre des coordonnées sphériques,
- O est la référence des coordonnées cartésiennes et
- V les coordonnées cartésiennes du centre (typiquement du
videoprojecteur).

cf. https://en.wikipedia.org/wiki/Spherical_coordinates

1 Testing spherical coordinates

Plotting function:

```
In [6]: def plot_xyz2azel(motion, vp=VPs[1], axes_perc=['t', 'r', 'az', 'el', 'rec'], axes_xy
"""
Let's define a function that displays for a particular motion
(a collection of poistions in the x, y, z space --- usually
continuous) the resulting spherical coordinates (wrt to vp).

"""
fig = plt.figure(figsize=(18,10))
t = np.linspace(0, 1, motion.shape[1])[:, np.newaxis]*np.ones((1, motion.shape[2]))
rae_VC = xyz2azel(motion, np.array([vp['x'], vp['y'], vp['z']]))
motion_rec = rae2xyz(rae_VC, np.array([vp['x'], vp['y'], vp['z']]))
#print rae_VC.shape
for i_ax, axe_perc in enumerate(axes_perc):
    for j_ax, axe_xyz in enumerate(axes_xyz):
        #print i_ax, j_ax, 3*i_ax + j_ax
        ax = fig.add_subplot(len(axes_perc), len(axes_xyz), 1 + len(axes_xyz)*i_ax
```

```

    if axe_perc == 't':
        #ax.plot(t, rae_VC[i_ax, :, :])
        #print motion_x[j_ax, :, :].shape, t.shape
        ax.plot(motion[j_ax, :, :], t)
    elif axe_perc == 'rec':
        ax.plot(motion_rec[j_ax, :, :], t)
    else:
        if axe_perc in ['az', 'el']: scale = 180./np.pi
        else: scale = 1.
        #print motion_x[j_ax, :, :].shape, rae_VC[i_ax-1, :, :].shape
        ax.plot(motion[j_ax, :, :], rae_VC[i_ax-1, :, :]*scale)
    ax.plot([vp[axe_xyz]], [0.], 'D')
    ax.set_xlabel(axe_xyz)
    ax.set_ylabel(axe_perc)
plt.show()
return rae_VC
print plot_xyz2azel.__doc__

```

Let's define a function that displays for a particular motion (a collection of positions in the x, y, z space --- usually continuous) the resulting spherical coordinates (wrt to vp).

```

In [22]: vp = VPs[1]
print vp
{'cz': 1.36, 'cy': 4.0, 'cx': 11.057115384615384, 'pc_min': 0.001,
'address': '10.42.0.52', 'y': 4.0, 'x': 0.9428846153846154, 'pc_max':
1000000.0, 'z': 1.36, 'foc': 21.802535306060136}

```

Pointing ahead:

```

print xyz2azel(np.array([vp['cx'], vp['cy'], vp['cz']]), np.array([vp['x'], vp['y'], v
In [24]: [ 10.11423077  0.          0.          ]

```

Pointing left (bigger y) should give positive azimuth, zero elevation:

```

print xyz2azel(np.array([vp['cx'], vp['cy']+1, vp['cz']]), np.array([vp['x'], vp['y'],
In [28]: [ 10.16354584  0.0985503  0.          ]

```

Pointing up (bigger z) should give positive elevation, zero azimuth:

```

print xyz2azel(np.array([vp['cx'], vp['cy'], vp['cz']+1]), np.array([vp['x'], vp['y'],
In [29]: [ 10.16354584  0.          0.09855029]

```

1.1 Motion in depth


Let's define N_{player} trajectories of N_{t} points, where players are distributed in the width (y) and move in the axis of the VP (x):

```

N_player, N_t = 10, 1000

In [8]: x = vp['x']*(np.linspace(0., 5., N_t)[np.newaxis, :, np.newaxis]*np.ones((1, 1, N_play
In [9]: y = vp['y']*np.ones((1, N_t, 1))*np.linspace(0, 2, N_player, endpoint=True)[np.newaxis
z = vp['z']*np.ones((1, N_t, N_player)) # constant
#print x.shape, y.shape, z.shape
motion_x = np.vstack((x, y, z))
motion_x += .01*np.random.randn(3, N_t, N_player)
motion_x.shape
rae_VC = plot_xyz2azel(motion_x, vp=vp)


```



the same but with a motion slightly higher than the VPnote : when azimuth is superior to 90° in absolute value, it means it is behind Note the small elevation:

```
In [10]: el = rae_VC[2,:,:]
print el.min(), el.max(), el.mean(), el.std()
-0.0694759707467 0.0607342907873 6.00750351743e-08 0.0061162178747
```


```
In [11]: z = 1.1*vp['z']*np.ones((1, N_t, N_player)) # constant
#print x.shape, y.shape, z.shape
motion_x = np.vstack((x, y, z))
motion_x += .01*np.random.randn(3, N_t, N_player)
rae_VC = plot_xyz2azel(motion_x, vp=vp)
```



being slightly up creates a small elevation, especially for a trajectory approaching the VP

1.2 Motion in width


```
In [12]: x = vp['x']*np.ones((1, N_t, 1))*np.linspace(0., 2., N_player, endpoint=True)[np.newaxis]
y = vp['y']*(np.linspace(0, 2, N_t)[np.newaxis, :, np.newaxis]*np.ones((1, 1, N_player)))
z = vp['z']*np.ones((1, N_t, N_player)) # constant
motion_y = np.vstack((x, y, z))
motion_y += .01*np.random.randn(3, N_t, N_player)
rae_VC = plot_xyz2azel(motion_y, vp=vp)
```



note that when the motion is behind the observer ($x < VP[x]$), the azimuth flips from -180° to 180° , everything is normal...

1.3 Motion in height

```
In [13]: x = vp['x']*np.ones((1, N_t, 1))*np.linspace(0, 5., N_player, endpoint=True)[np.newaxis]
y = vp['y']*np.ones((1, N_t, N_player)) # constant
z = vp['z']*(np.linspace(0, 2., N_t)[np.newaxis, :, np.newaxis]*np.ones((1, 1, N_player)))
motion_z = np.vstack((x, y, z))
motion_z += .01*np.random.randn(3, N_t, N_player)
rae_VC = plot_xyz2azel(motion_z, vp=vp)
```



2 Testing great circle navigation

Similar tests, but now looking at the `arcdistance` and `orientation` functions:

```
In [14]: print arcdistance.__doc__
renvoie l'angle sur le grand cercle (en radians)

# rae1 ---> rae2

r = distance depuis le centre des coordonnées sphériques (mètres)
a = azimuth = déclinaison = longitude (radians)
e = elevation = ascension droite = latitude (radians)

http://en.wikipedia.org/wiki/Great-circle_distance
http://en.wikipedia.org/wiki/Vincenty%27s_formulae
```

```
In [15]: print orientation.__doc__
renvoie le cap suivant le grand cercle (en radians)

r = distance depuis le centre des coordonnées sphériques (mètres)
a = azimuth = déclinaison = longitude (radians)
e = elevation = ascension droite = latitude (radians)

http://en.wikipedia.org/wiki/Great-circle_navigation
#http://en.wikipedia.org/wiki/Haversine_formula
```

```
In [16]: def plot_xyz2perceptif(motion, vp=VPs[i_vp], axes_xyz=['x', 'y', 'z']):
        """
        Let's define a function that displays for a particular motion
        (a collection of positions in the x, y, z space --- usually
        continuous) the resulting orientation and arcdistance.
```

```

"""
fig = plt.figure(figsize=(18,10))
t = np.linspace(0, 1, motion.shape[1])[:, np.newaxis]*np.ones((1, motion.shape[2]))
rae_VC = xyz2azel(motion, np.array([vp['x'], vp['y'], vp['z']]))
motion_rec = rae2xyz(rae_VC, np.array([vp['x'], vp['y'], vp['z']]))
#print rae_VC.shape
for i_ax, axe_perc in enumerate(axes_perc):
    for j_ax, axe_xyz in enumerate(axes_xyz):
        #print i_ax, j_ax, 3*i_ax + j_ax
        ax = fig.add_subplot(len(axes_perc), len(axes_xyz), 1 + len(axes_xyz)*i_ax)
        if axe_perc == 't':
            #ax.plot(t, rae_VC[i_ax, :, :])
            #print motion_x[j_ax, :, :].shape, t.shape
            ax.plot(motion[j_ax, :, :], t)
        elif axe_perc == 'rec':
            ax.plot(motion_rec[j_ax, :, :], t)
        else:
            if axe_perc in ['az', 'el']: scale = 180./np.pi
            else: scale = 1.
            #print motion_x[j_ax, :, :].shape, rae_VC[i_ax-1, :, :].shape
            ax.plot(motion[j_ax, :, :], rae_VC[i_ax-1, :, :]*scale)
            ax.plot([vp[axe_xyz]], [0.], 'D')
            ax.set_xlabel(axe_xyz)
            ax.set_ylabel(axe_perc)
plt.show()
return rae_VC
print plot_xyz2azel.__doc__

```

Let's define a function that displays for a particular motion (a collection of poistions in the x, y, z space --- usually continuous) the resulting spherical coordinates (wrt to vp).

```
plot_xyz2perceptif(motion_x)
```

In [18]:

NameError
call last)

Traceback (most recent

```

<ipython-input-18-c09b8f1ab8b2> in <module>()
----> 1 plot_xyz2perceptif(motion_x)

```

```

<ipython-input-16-ccc213330bd4> in plot_xyz2perceptif(motion,
vp, axes_xyz)
    11     motion_rec = rae2xyz(rae_VC, np.array([vp['x'],
vp['y'], vp['z']]))
    12     #print rae_VC.shape
--> 13     for i_ax, axe_perc in enumerate(axes_perc):
    14         for j_ax, axe_xyz in enumerate(axes_xyz):
    15             #print i_ax, j_ax, 3*i_ax + j_ax

```

```
NameError: global name 'axes_perc' is not defined  
<matplotlib.figure.Figure at 0x10b905410>
```

In [17]: