

Title:		
Sheet: /STM/		Rev:
Author:		
Date:	Size: A4	Id: 2/20
File: STM.kicad_sch		








Table 5. JTAG/SWD cable connections on STLINK-V2-ISOL

Pin no.	ST_LINKV2 connector (CN3)	ST_LINKV2 function	Target connection (JTAG)	Target connection (SWD)
1				
2	VAPP	Target VCC	MCU VDD ⁽¹⁾	MCU VDD ⁽¹⁾
3	TRST	JTAG TRST	NJTRST	GND ⁽²⁾
4	Not connected	Not connected	Not connected	Not connected
5	TDI	JTAG TDI	JTDO	GND ⁽²⁾
6	Not connected	Not connected	Not connected	Not connected
7	TMS_SWDIO	JTAG TMS, SWD IO	JTMS	SWDIO
8	Not connected	Not connected	Not connected	Not connected
9	TKC_SWCLK	JTAG TCK, BW CLK	JTCK	SWCLK
10	Not used ⁽⁵⁾	Not used ⁽⁵⁾	Not connected ⁽⁵⁾	Not connected ⁽⁵⁾
11	Not connected	Not connected	Not connected	Not connected
12	GND	GND	GND ⁽³⁾	GND ⁽³⁾
13	TDO_SWO	JTAG TDI, SWO	JTDO	TRACESWO ⁽⁴⁾
14	Not used ⁽⁵⁾	Not used ⁽⁵⁾	Not connected ⁽⁵⁾	Not connected ⁽⁵⁾
15	NRST	NRST	NRST	NRST
16	Not connected	Not connected	Not connected	Not connected
17	Not connected	Not connected	Not connected	Not connected
18	GND	GND	GND ⁽³⁾	GND ⁽³⁾
19	Not connected	Not connected	Not connected	Not connected
20	GND	GND	GND ⁽³⁾	GND ⁽³⁾

Table 4. JTAG/SWD cable connections on STLINK-V2

Pin no.	ST-LINK/V2 connector (CN3)	ST-LINK/V2 function	Target connection (JTAG)	Target connection (SWD)
1	VAPP	Target VCC	MCU VDD ⁽¹⁾	MCU VDD ⁽¹⁾
2	TRST	JTAG TRST	NJTRST	GND ⁽²⁾
4	GND	GND	GND ⁽³⁾	GND ⁽²⁾
5	TDI	JTAG TDO	JTDO	GND ⁽²⁾
6	GND	GND	GND ⁽³⁾	GND ⁽²⁾
7	TMS_SWIO	JTAG TMS, SW IO	JTMS	SWDIO
8	GND	GND	GND ⁽³⁾	GND ⁽²⁾
9	TCK_SWCLK	JTAG TCK, SW CLK	JTCK	SWCLK
10	GND	GND	GND ⁽³⁾	GND ⁽²⁾
11	Not connected	Not connected	Not connected	Not connected
12	GND	GND	GND ⁽³⁾	GND ⁽²⁾
13	TDO_SWO	JTAG TDI, SWO	JTDO	TRACESWO ⁽⁴⁾
14	GND	GND	GND ⁽³⁾	GND ⁽²⁾
15	NRST	NRST	NRST	NRST
16	GND	GND	GND ⁽³⁾	GND ⁽²⁾
17	Not connected	Not connected	Not connected	Not connected
18	GND	GND	GND ⁽³⁾	GND ⁽²⁾
19	VDD	VDD (3.3 V)	Not connected	Not connected
20	GND	GND	GND ⁽³⁾	GND ⁽²⁾

Figure 10. JTAG debugging flat ribbon layout



10-pin JTAG/SWD Connector


VCC	1	<input type="checkbox"/>	<input type="checkbox"/>	2	SDWIO / TMS
GND	3	<input type="checkbox"/>	<input type="checkbox"/>	4	SWDCLK / TCK
GND	5	<input type="checkbox"/>	<input type="checkbox"/>	6	SWO / TDO
KEY	7	<input type="checkbox"/>	<input type="checkbox"/>	8	NC / TDI
GNDetect	9	<input type="checkbox"/>	<input type="checkbox"/>	10	nRESET




Rev:


Id: 6/20

File: PinoutSTM.kicad_sch




Title:		
Sheet: /STM/CAN_Interface/		Rev:
Author:		
Date:	Size: A4	Id: 7/20
File: PowerSTM.kicad_sch		





Title:		
Sheet: /CM4/CM4_Module1A/CM4_LED1/		Rev:
Author:		
Date:	Size: A4	Id: 8/20
File: CM4_LED1.kicad_sch		



Title:

Sheet: /CM4/CM4_Module1A/CM4_LED2/

Rev:

Author:



Date:

Size: A4


Id: 9/20

File: CM4_LED2.kicad_sch

POE Protection



Optimal: Green: 325 Ohm (3.3–2.65)/0.002
Optimal: Yellow: 725 Ohm (3.3–1.85)/0.002



Title:

Sheet: /CM4/CM4_Module1A/CM4_Ethernet/

Rev:


Author:

Date:


Size: A4

Id: 10/20


File: CM4_Ethernet.kicad_sch



Title:		
Sheet: /CM4/CM4_Module1B/		Rev:
Author:		
Date:	Size: A4	Id: 11/20
File: CM4_Module1B.kicad_sch		



Not in the PCB yet as we dont know if we actually need it.



Title:

Sheet: /Piezzo/

Rev:


Author:

Date:




Size: A4

Id: 4/20


File: Piezzo.kicad_sch



Title:		
Sheet: /LPHS-connector/		Rev:
Author:		
Date:	Size: A4	Id: 14/20
File: LPHT-connector.kicad_sch		




Wont work... diodes are not perfect...



Title:		
Sheet: /Power_logic/		Rev:
Author:		
Date:	Size: A4	Id: 14/20
File: Power_logic.kicad_sch		

for questions about wiring etc please consult the datasheet...
<https://www.ti.com/lit/ds/symlink/tps2120.pdf?ts=1761678178328>




		Pins	MIN	MAX	UNIT
V _{IN1} , V _{IN2} , V _{OUT}	Maximum Power Pin Voltage	IN1, IN2, OUT	-0.3	24	V
V _{OV1} , V _{OV2}	Maximum Overvoltage Pin Voltage	OV1, OV2	-0.3	6	V
V _{PR1} , V _{SEL}	Maximum Control Pin Voltage	PR1, SEL	-0.3	6	V
V _{ST}	Maximum Control Pin Voltage	ST	-0.3	6	V
I _{OUT}	Maximum Output Current	OUT	Internally Limited		
T _{J, MAX}	Maximum Junction Temperature		Internally Limited		
T _{STG}	Storage temperature		-65	150	°C

Figure 6-2. TPS2121 (RUX) Package 12-Pin VQFN-HR Bottom View

PIN		TPS2121		TPS2121		IO		DESCRIPTION	
NAME		WCSP	VQFN-HR						
IN1	B1, B2, C1	7	1					Power Input for Source 1	
IN2	B3, B4, C4	2	1					Power Input for Source 2	
OUT	C2, C3, D1, D2, D3, D4	1, 8	1					Power Output	
ST	E1	9	0					Status output indicating which channel is selected. Connect to GND if not required.	
ILIM	E2	10	0					Output Current Limiting for both channels.	
ISL	E3	11	0					Adjusts Input Settling Delay Time and Output Soft Start Time	
GND	E4	12	—					Device Ground	
PR1	A1	6	1					Enables Priority Operation. Connect to IN1 to set switchover voltage. Connect to GND if not required.	
OV1	A2	5	1					Active Low Enable Supervisor for IN1 Overvoltage Protection. Connect to GND if not required.	
OV2	A3	4	1					Active Low Enable Supervisor for IN2 Overvoltage Protection. Connect to GND if not required.	
SEL	A4	—	1					Active Low Enable for IN1. Allows GPIO to override priority operation and manually select IN2. TPS2120 only.	
CP2	—	3	1					Enables Comparator Operation and is compared to PR1 to set switchover voltage. Connect to GND if not required. TPS2121 only.	




Title:		
Sheet: /Power_logic/5V_Logic/		Rev:
Author:		
Date:	Size: A4	Id: 15/20
File: 5V_Logic.kicad_sch		




[R] = [kOhm]	22 kΩ → -4.55 A
65.2 / R*0.861	39 kΩ → -2.78 A
	50 kΩ → -2.25 A
	56 kΩ → -2.04 A
	68 kΩ → -1.72 A
	100 kΩ → -1.24 A



Title:		
Sheet: /Power_logic/3.3V_Logic/		Rev:
Author:		
Date:	Size: A4	Id: 16/20
File: 3.3V_Logic.kicad_sch		




Title:		
Sheet: /Power_logic/GPIO_REF3.3V/		Rev:
Author:		
Date:	Size: A4	Id: 17/20
File: GPIO_REF3.3V.kicad_sch		



Title:		
Sheet: /IMU/		Rev:
Author:		
Date:	Size: A4	Id: 18/20
File: IMU.kicad_sch		

PS -> 3.3V IIC
CSB1 -> 3.3V NOT SPI

PB8 on STM
PB9 on STM



Accelerometer
SD01 pin pulled to GND (0x18)
SD01 pin pulled to VDDIO: (0x19)

Gyroscope:
SD02 pin pulled to GND: (0x68)
SD02 pin pulled to VDDIO: 0x69



Title:

Sheet: /IMU/IMU1/

Rev:

Author:

Date:

Size: A4

Id: 19/20

File: IMU1.kicad_sch

