

Technical Information

Valid since 16.01.2015 Texapon® N 70

Revision 12.2

PRD 30528345 Page 1 of 3

Care Chemicals ® = registered trademark of BASF in many countries ™ = Trademark of BASF

General characterisation

Chemical description

Sodium Laureth Sulfate + 2 EO

Mol weight 382 g/mol

Labeling information

INCI name(s)

Sodium Laureth Sulfate

Composition hints for finished product label

INCI Components

INCI Name (US/EU/CN) Content Sodium Laureth Sulfate 68 - 73 %

Active ingredient information

Ingredient CASR-No. Remark

Sodium Laureth Sulfate 68891-38-3





Technical Information

 Texapon® N 70
 Valid since Revision
 16.01.2015

 PRD 30528345
 Page
 2 of 3

 ® = registered trademark of BASF in many countries
 ™ = Trademark of BASF
 Care Chemicals

Product properties

Appearance

Flowable paste, transparent to yellowish

Example of use

Owing to its outstanding detergency and cleansing quality Texapon® N 70 is used for the manufacture of liquid dishwashing and technical cleaning agents as well as liquid light-duty detergents.

Because of its good foam characteristic and the easy thickening with salt, the product is also suited as a basic surfactant for cosmetic cleansing preparations such as shampoos, shower gels and foam baths.

Texapon® N 70 is a highly concentrated sodium lauryl ether sulphate derived from natural fatty alcohols. Due to its high content of washing active substance, Texapon® N 70 is particularly suited for highly concentrated endproducts, or if raw materials with a lower water content are required.

Processing

When diluted with water, Texapon® N 70 shows gel structures which are typical of ether sulphates. After the addition of water, the viscosity first increases rather rapidly, and after a reduction of the active substance to a level below 30 %, it decreases considerably. Liquid, stable solutions are obtained up to 28 % of the active substance. At higher concentrations the product becomes pasty.

Texapon® N 70 has an extremely low salt content, and when diluted with water to the normal use concentration, it shows a very low viscosity. When sodium chloride and alkanolamides (Comperlan® types) are added, the viscosity can be adjusted accordingly.

In this way, the viscosity of diluted solutions of Texapon® N 70 with approx. 5 - 28 % washing active substance can be easily increased to the desired value.

If sodium chloride is used as a thickening agent, Texapon® N 70 can be incorporated into the formulation in the cold state if the following incorporation sequence is adhered to:

The required amount of sodium chloride has to be diluted in the smallest quantity of water that is absolutely necessary for obtaining a solution (preparation of a saturated table salt solution). This salt solution is added to the undiluted Texapon® N 70 whilst stirring, and stirring is continued until the mixture has become more fluid.

Subsequently, the remaining water can be added without difficulty.

If incorporation cannot be effected in this way, it is recommended that Texapon® N 70 be dissolved with hot water of approx. 80 °C whilst stirring, and only then should other components be added.





Technical Information

Texapon® N 70		Valid since Revision	16.01.2015 12.2
PRD 30528345		Page	3 of 3
R – registered trademark of BASE in many countries	™ – Trademark of BASE	Care Chemicals	

As a general rule, sodium chloride should not be added in solid form, but in the form of an aqueous solution. Continous mixing of Texapon® N 70 with water is also possible without any difficulty, if the appropriate apparatus and equipment is available.

Stabilising additives / Auxiliaries

The Product is unpreserved

Disclaimer

This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation.NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

