

Iteration 3

Penetration Testing Plan/Result:

1. Introduction / Overview

This security plan outlines the approach taken to identify, address, and manage potential security threats throughout the development and deployment of our system. The goal is to ensure the confidentiality, integrity, and availability (CIA) of user data and system operations. As part of an agile development process, this document will evolve across iterations to reflect new risks, mitigations, and lessons learned. It serves not only as a technical guideline for the team but also as a communication tool for stakeholders concerned with the system's safety and compliance.

2. About Our System

Our system is a web-based educational platform developed using the Flask framework, incorporating technologies such as Python, HTML, CSS, and JavaScript to deliver interactive content. The application is deployed via the Azure Web App Service, which integrates directly with GitHub for continuous deployment and version control. GitHub not only serves as our source repository but also ensures reliable backup of our development history. The backend relies on Azure's MySQL flexible database to manage and store persistent user and system data. Additionally, third-party APIs are used to supplement dynamic content and enhance functionality. Users can access the platform from any device or operating system through a public Azure domain, with all interactions routed securely through Azure infrastructure to ensure stable, scalable, and responsive service delivery.




Figure 1. System Architecture Overview – Azure-based Flask Web App

All tests were conducted on the live deployed version of the application, hosted at <https://aetherguard.top>, running on Azure Web App Service. The application is built using Flask for the backend and serves interactive web pages with HTML, CSS, and JavaScript, supported by client-side localStorage and sessionStorage.

The application integrates with external APIs including:

- <https://js.puter.com/v2/> (third-party script loading)
- <https://api.puter.com> (real-time interaction features)
- Additional trusted services such as Google Fonts, YouTube embedded video content, and Azure-hosted databases.

Testing was performed on a Windows 10 machine using Google Chrome (version 123.0.6312.86, 64-bit) over a standard home network environment. No login was required; all tested features were publicly accessible or triggered by in-app logic.

The tools and methods used include:

- Chrome DevTools (Console, Storage, Network panels)

- Wireshark (for TLS and encrypted traffic capture)
- SecurityHeaders.com (for analyzing HTTP response headers)
- RequestInspector.com (for simulating external API endpoints)
- Postman Web (for probing API responses manually)

All testing was conducted on May 19, 2024, between 19:00 and 23:30 (AEST).

3. Security Awareness

Security plays a vital role in our project, especially as it targets parents and children—groups that may be more vulnerable to online threats. While our website does not collect user credentials or store personal data, it does utilize the browser's `localStorage` to save users' game progress. This limited data handling still requires attention to secure implementation, as insecure use of `localStorage` may expose the application to cross-site scripting (XSS) attacks. To keep our project safe, we avoid using user-submitted data in any backend process, enforce secure content loading via HTTPS, and implement strict input handling within our front-end scripts. Without proper protection, potential threats such as code injection, unauthorized API access, or third-party script misuse could compromise the experience or trust of our users. Although the security risks are relatively low due to the project's limited data scope, a breach could still impact the integrity of the learning experience and reduce user trust. Since our system is aimed at educating users about online safety, any security flaw would also undermine the credibility of our message. Therefore, even with minimal data exposure, maintaining a secure front-end and a monitored backend is essential.

Table of Security Awareness

Risk name	Likelihood	Impact	Affected Components	Mitigation
Missing or Misconfigured HTTP Security Headers	Medium	High	All frontend responses (index, game, error pages)	Define and enforce headers via Flask <code>@after_request</code> . Include Content-Security-Policy, X-Frame-Options, Strict-Transport-Security, etc. Verify via browser devtools and automated tests.
Unencrypted Traffic (No HTTPS / Mixed Content)	Low	High	All user-server interactions; static file delivery; third-party API calls	Enforce HTTPS redirection in Flask and Azure App Service; check TLS certificate validity; use Wireshark to confirm encrypted transmission; avoid HTTP-loaded assets or APIs.

Cross-site scripting (XSS)	Medium	High	Storyboard interface, homepage info sections, game text display	Sanitize all user-facing content and avoid using innerHTML where possible. Since some features (e.g., localStorage) rely on dynamic rendering, we also apply strict Content Security Policies (CSP).
Insecure usage of localStorage	High	Medium	Game progress storage, character status flags, unlocked paths	Use localStorage only for non-sensitive flags; validate and sanitize all stored values before use
Audio and media injection	Low	Medium	Background music system, story transitions, animation triggers	Host all files in static/, block mixed content, enforce HTTPS and correct MIME types
Uncontrolled API dependencies	Medium	High	APIs used in quizzes, statistics, future data-driven story paths	Use trusted APIs only, document all endpoints, add logging to monitor API responses
Misconfigured GitHub-Azure pipeline	Low	High	CI/CD pipeline, environment secrets, deployment automation	Restrict deployment to iteration2 branch, secure secrets in Azure App Settings, review YAML before push

4. Penetration testing plan

4.1 HTTP Security Header Check

Testing Tools:

- Browser DevTools (Inspect → Network → Headers)
- Online tool: <https://securityheaders.com/>
- Custom Python script using requests

Execution Plan:

1. Use browser devtools or curl to inspect HTTP response headers from all key pages (homepage, game page, error pages). Or test directly using scripts and online tools.
2. Verify the presence and correctness of headers:
 - Content-Security-Policy
 - X-Frame-Options
 - X-Content-Type-Options
 - Strict-Transport-Security

- Referrer-Policy
- Permissions-Policy
- 3. Confirm the script-src, connect-src, etc. directives in CSP match intended access control.
- 4. Test whether injection payloads are blocked by CSP rules.

Expected Outcome:

- All critical headers are present.
- CSP is enforced and prevents inline/remote injection.
- Clickjacking is blocked (X-Frame-Options: DENY).
- HTTPS is enforced via HSTS (Strict-Transport-Security).

4.2: Encrypted Traffic Verification (HTTPS)

Testing Tools:

- Wireshark – for capturing and analyzing HTTP/HTTPS traffic
- Browser (Chrome or Firefox) – to generate traffic during test
- SSL Labs (optional) – to verify certificate and protocol support

Execution Plan:

1. Launch Wireshark and begin capturing traffic on the active network interface (e.g., Ethernet or Wi-Fi).
2. Visit the website using both <http://aetherguard.top> and <https://aetherguard.top>.
3. Filter traffic in Wireshark using:
 - http – to check for unencrypted traffic
 - tls – to view encrypted traffic sessions
4. Observe packet contents:
 - Confirm whether any HTTP packets appear in the capture (should be none or redirected).
 - Examine TLS packets for successful Client Hello and Server Hello handshakes.
 - Ensure no plaintext (e.g., usernames, messages) content is visible in packet payloads.
5. Optionally test for mixed content by loading pages and checking if any assets (e.g., images, scripts) are transmitted over HTTP.

Expected Outcome:

- All application traffic appears under the tls filter, with no readable data in payloads.
- Any attempt to access HTTP is redirected (seen as a 301/302 response).
- No credentials, game data, or story content should be visible in plain text.
- Certificates in TLS handshakes match expected domain and issuer.

4.3: Cross-site Scripting (XSS)

Testing Tools:

- Burp Suite (Community or Pro) – for intercepting and injecting payloads
- OWASP ZAP – to crawl and auto-scan HTML input fields
- Manual testing with browser console (e.g., "><script>alert('XSS')</script>")

Execution Plan:

1. Inject test payloads into story content, character dialogues, and homepage display fields using Burp's Repeater or direct DOM editing.
2. Observe whether any alert boxes execute or script tags render in the DOM.
3. Check whether content inside innerHTML or dynamic rendering blocks are vulnerable.
4. Review response headers to ensure CSP headers are correctly applied (Content-Security-Policy: script-src 'self').

Expected Outcome:

- Application escapes or blocks injected content.
- CSP is active and prevents script execution.
- No DOM-based XSS triggers.

4.4 Insecure usage of LocalStorage

Testing Tools:

- Browser DevTools Console – for directly manipulating localStorage
- Manual page reloads – to observe whether changes persist and affect gameplay
- Developer Console – to check for errors or script injection side effects

Execution Plan:

1. Open the game in a browser and access DevTools Console (F12).
2. Use `console.log(localStorage);` to inspect stored game data.
3. Attempt to override important gameplay values, including:
 - `Zack.health` (e.g., set to extremely high or negative values)
 - `gameState.day` (e.g., skip to final day)
 - `Zack.name` (e.g., inject a script string or invalid HTML)
 - Any other keys affecting flags, events, or interactions

Command use:

```
localStorage.setItem('gameGuideShown', 'false');  
localStorage.setItem('fanGrowth', JSON.stringify({  
    previousFans: 999999,  
    growthAmount: 999999  
}));
```

4. Reload the page and observe:
 - Whether the game logic responds to the tampered data
 - Whether any previously locked features become accessible
 - Whether the injected data is rendered or executed in the interface
 - Whether the game crashes, freezes, or shows console errors

Expected Outcome:

- The application should ignore or sanitize unsafe values retrieved from localStorage
- Altered game state (e.g., days or health) should not allow players to bypass game logic

- Injected HTML/script content should not be rendered or executed
- The application should not crash or produce unhandled exceptions when encountering malformed localStorage values

Audio and Media Injection

Testing Tools:

- Browser DevTools Console – for directly modifying localStorage or JS objects
- Manual media playback – to observe audio rendering behavior
- Browser Network panel – to confirm actual audio loading paths and detect errors

Execution Plan:

1. Open the game in a browser and launch DevTools.
2. Locate the media resource keys stored in localStorage or sessionStorage (e.g., hint.mp3, audio, currentAudio, or dynamically loaded URLs).
3. Use the console to overwrite the audio source value with a malicious or invalid URL, such as:
 1. `localStorage.setItem("currentAudio", "https://evil.com/fake.mp3");`
 2. `localStorage.setItem("currentAudio", "javascript:alert('hacked')");`
4. Refresh the page and monitor:
 1. Whether the altered audio path is accepted and executed
 2. Whether the browser console shows playback errors
 3. Whether an unexpected audio or UI behavior occurs
 4. Whether audio loads from untrusted external domains
5. Inspect DevTools → Network tab → Filter by “media” or “.mp3” to verify the actual audio source and whether it matches expected safe domains (e.g., /static/audio/).

Expected Outcome:

- The application should reject or fail to load invalid or untrusted audio sources
- Attempted injection should not cause any security alerts, DOM manipulation, or functional crashes
- Audio must only load from known and trusted paths (preferably local static assets)
- CSP media-src directive (if active) should block any external audio resource loading

4.5: Audio and Media Injection

Test Objective:

The objective of this test is to determine whether the application is vulnerable to media resource injection via browser storage manipulation. If audio playback is based on dynamically retrieved paths (e.g., from localStorage), an attacker might modify those values to trigger malicious audio, load external resources, or break media playback. This test aims to verify if media sources can be tampered with or misused to compromise game functionality.

Test Implementation:

We manually modified the media source stored in localStorage using the browser console to

simulate an attacker injecting a forged audio file. The following steps were executed:

1. Opened the application and launched the DevTools Console (F12).
2. Injected a fake audio path into localStorage:
3. Reloaded the application and triggered the feature that plays the “hint” sound.
4. Observed whether the audio source was accepted and played.
5. Checked the DevTools Network tab for any attempt to load the forged .mp3 file.

Expected Outcome:

- The system should reject or ignore untrusted or malformed audio source paths.
- Audio must only be loaded from predefined, secure directories (e.g., /static/audio/).
- CSP headers (if present) should enforce restrictions via the media-src directive.

Testing Result:

After injecting a forged audio path into localStorage and reloading the application, the system did not load or attempt to play the injected audio file. The previously defined game sound continued to play as intended, and no network requests for external or forged media were recorded.

This indicates that the application does not rely on localStorage to define audio paths, or that it uses internal validation and static asset mapping to prevent arbitrary audio injection. The system behaved securely under test conditions and did not expose media injection vulnerabilities.

4.6: Browser Storage Data Leakage

Test Objective:

The objective of this test is to assess whether sensitive or gameplay-critical data is exposed through browser-side storage mechanisms such as localStorage and sessionStorage.

Since the application relies heavily on local storage to maintain game state, story progress, and character attributes, an attacker may extract structured game data from the browser console to reconstruct plot flow, alter outcomes, or bypass intended progression.

Testing Tools:

- Browser Developer Tools (Console tab)
- Manual inspection and parsing of localStorage and sessionStorage contents
- Optional: JSON formatter plugin for easier content analysis

Execution Plan:

1. Open the application in a browser and access DevTools → Console (F12).
2. Dump the full contents of browser storage:
3. Look for:
 1. Serialized game data including story segments, character states, or flags
 2. JSON-like structures containing full dialogue blocks or conditions
 3. Metadata (e.g., gameState.day, Zack.name, flags like event4_complete)
4. Assess:
 1. Whether an attacker can predict upcoming choices or endings

2. Whether full story branches can be reverse-engineered
3. Whether meaningful gameplay decisions are stored without encryption or obfuscation
5. Attempt to use extracted information to alter game state or logic.

Expected Outcome:

- The storage may contain general game state values, but should not expose full narrative or decision trees.
- Story-related data, if present, should not be human-readable or easily interpreted without context.
- Internal logic (e.g., flags, endings, condition branches) should not be fully reconstructible from browser storage alone.
- Critical paths should be enforced server-side or validated on load.

4.7: Uncontrolled API Dependencies (Online Tool-Based Test)

Test Objective:

The objective of this test is to evaluate the security posture of third-party APIs used by the application, with a focus on identifying any unvalidated dependencies or excessive trust in external services.

This test uses online tools to assess how securely the application interacts with APIs such as <https://api.puter.com>, and whether browser security policies like Content Security Policy (CSP) and Cross-Origin Resource Sharing (CORS) are properly enforced.

Testing Tools:

- [SecurityHeaders.com](https://securityheaders.com) – to analyze HTTP response headers and CSP rules
- [RequestInspector.com](https://requestinspector.com) – to simulate external API endpoint substitution and monitor interactions

Execution Plan:

1. API Access Substitution via RequestInspector
 - Replace a known API endpoint (e.g., api.puter.com/rao) with a controlled domain like <https://requestinspector.com/yourtest>
 - Inject the new domain into localStorage or modify JS code (if permitted)
 - Reload the application and observe whether it attempts to contact the fake API
2. Manual API Probing via Postman
 - Send unauthenticated requests to known APIs (e.g., <https://api.puter.com/whoami>)
 - Inspect whether the endpoint enforces proper authentication and input validation
 - Verify the response structure: is it overexposed? Is user context returned?

Expected Outcome:

- The application should restrict access to only approved third-party APIs through CSP (connect-src)

- Any attempt to replace the API domain should be blocked by the browser or fail gracefully
- APIs should return limited, safe data only upon valid, authenticated requests
- The application must not functionally rely on unprotected or unverified external services

4.8: Misconfigured GitHub–Azure Pipeline

Test Objective:

To verify whether the CI/CD pipeline between GitHub and Azure Web App is securely configured, with deployment restricted to the correct branch and secrets managed appropriately. Misconfiguration may lead to unauthorized deployments or exposure of sensitive credentials.

Test Implementation:

No manual testing was performed for this item. The project uses Azure's native integration with GitHub Actions, which provides secure authentication, deployment scoping, and encrypted secret handling via Azure App Settings and GitHub Secrets. Deployment is limited to the iteration2 branch through Azure portal settings.

Expected Outcome:

- Only authorized branches (e.g., iteration2) can trigger deployment
- Secrets are stored securely and not hard-coded into the codebase
- CI/CD YAML files are version controlled and not modified arbitrarily

5. Monitoring, Logging and Alerting

Monitoring and logging play a vital role in maintaining the integrity and availability of our web application. Although our system does not have user registration, authentication, or personal data collection features, it is still essential to monitor deployment activities, backend health, and database status to ensure reliability and early detection of potential security issues. Our team utilizes Azure Web App's built-in monitoring tools to oversee application uptime, HTTP traffic patterns, error rates, and deployment history. Azure App Service Diagnostics and Application Insights provide useful runtime logs, crash reports, and live metrics, allowing the team to track the health of the Flask backend and front-end delivery. Additionally, the Azure platform offers deployment logging and rollback tracking through its GitHub CI/CD integration. Any push to the iteration2 branch triggers deployment events that are logged and timestamped, helping identify the origin of potential issues quickly.

On the database side, Azure Database for MySQL (flexible server) includes automated query logging, connection attempt tracking, and resource usage monitoring (CPU, memory, I/O). Alerts can be configured to notify us if the database is experiencing unusual loads, suspicious query patterns, or frequent disconnects.

As the security lead, I (Tianyi Song) am currently responsible for reviewing these logs regularly and manually inspecting anomalies after each major update or during feedback-based revisions. Although our current architecture does not involve advanced SIEM (Security Information and Event Management) or SOAR (Security Orchestration, Automation, and Response) tools due to the project scale, we simulate basic detection by enabling Azure Monitor alerts for both the App Service and the database. These alerts are configured to flag unauthorized access attempts or traffic spikes, especially during off-hours.

We acknowledge the importance of continuous improvement and plan to scale up monitoring practices in the future, such as integrating open-source tools like Fail2ban for intrusion attempt logs, and implementing a lightweight custom logging system to capture specific client interactions (e.g., failed audio loads or card interaction issues) without violating user privacy.

6. Back-up, Incident Response & Disaster Recovery Plan

Back-up Plan:

Our system relies on Azure Web App and Azure MySQL Database. Therefore, we utilize Azure's automated backup service as our primary method. Azure performs daily backups of the database and retains them for 7 days, ensuring that we can restore important data when needed. At the code level, we use GitHub for version control, which automatically stores all changes and supports rollback. If a sponsor or third party needs to reproduce this process, they simply need to enable automated backups in the Azure Portal and ensure GitHub syncing is in place.

Incident Response Plan:

Potential incidents include website downtime, database connection failures, and third-party API interruptions. Upon detecting such issues, the designated project maintainer will receive real-time alerts via Azure's built-in notification system and use log files to diagnose the root cause. GitHub versioning allows for immediate rollback to a stable version in case of emergencies.

Disaster Recovery Plan:

If Azure experiences a major outage or service termination, we will immediately adopt the following steps:

- Redeploy the project using the GitHub codebase on an alternative cloud platform such as AWS or Google Cloud;
- Restore data from a manually exported MySQL backup file to a new environment;
- Use locally stored .env configuration files to replicate environment variables and secrets;

Our goal is to recover and deploy a minimal viable version of the system within 24 hours to minimize disruption to users.

7. Ethical, Privacy & Legal Concerns

Our platform does not collect any personally identifiable information (PII) and does not include user registration or login functions. Therefore, the privacy risk is relatively low. However, we still address several important concerns:

Use of Data:

We use the browser's local storage (LocalStorage) to save user progress within the game. This data is stored client-side only and never transmitted to the server, thereby improving user experience while maintaining privacy.

Processing of Data:

Since no backend user data is processed, the system avoids risks commonly associated with server-side data handling. However, we still conduct regular code reviews to ensure LocalStorage is not misused—for example, storing sensitive information or being accessed by unauthorized scripts.

Publishing of Data:

All content, including storylines and visuals, is created by our development team. There is no user-generated content (UGC) involved, so there is no risk of publishing private or unauthorized user data.

Legal Compliance (e.g., GDPR):

Although our platform primarily targets users in Australia, we still align with key GDPR principles such as data minimization and purpose limitation. We avoid collecting identifiable data, ensure anonymous browsing, and do not use cookies or tracking technologies unless strictly necessary.

8. Penetration testing report

8.1: HTTP Security Header Check

Test Objective:

The objective of this test is to verify whether the deployed website has correctly configured key HTTP security response headers after deployment on Azure Web App. These headers do not impact content display but are crucial in defending against client-side attacks such as XSS, clickjacking, and MIME type sniffing.

The test aims to confirm the presence of industry-recommended headers, including: Content-Security-Policy, X-Frame-Options, X-Content-Type-Options, Strict-Transport-Security, Referrer-Policy, and Permissions-Policy.

Test Implementation:

Instead of using a custom script, we utilized [SecurityHeaders.com](https://securityheaders.com) — a reputable public scanning tool — to evaluate the response headers of our deployed website (<https://aetherguard.top>).

The tool checks the presence, correctness, and policy strength of all common HTTP security headers and assigns a letter grade from A+ to F.

This test also helps verify whether our `@after_request` implementation in Flask correctly returns these headers to clients during live deployment.

Testing Result:

The scan result of <https://aetherguard.top> returned a **grade of A**, confirming that all six critical headers were successfully configured and included in the response.

Present headers:

- Strict-Transport-Security
- Content-Security-Policy
- X-Frame-Options
- X-Content-Type-Options
- Referrer-Policy
- Permissions-Policy

Although some advanced headers such as cookie flags or Expect-CT are not part of this test, all baseline protections were confirmed to be active.





Figure 2. Testing result from SecurityHeader.com

Recommendations:

Since all key headers have already been applied successfully, no immediate action is required. However, for future improvement, we may consider:

- Adding cookie-level security flags such as Secure, HttpOnly, and SameSite.
- Periodically re-testing headers after each deployment to ensure integrity is preserved.
- Using tools like [Mozilla Observatory](https://observatory.mozilla.org/) or Google CSP Evaluator for deeper analysis.

The current implementation confirms that our security header strategy is effective and aligns with modern web application best practices.

8.2: Encrypted Traffic Verification (Wireshark-based)

Test Objective:

The objective of this test is to verify whether all traffic between the user and the deployed website is encrypted using TLS. This is crucial for preventing man-in-the-middle (MITM) attacks and ensuring the confidentiality and integrity of data transmitted between the client and the server. The goal is to confirm that the application uses HTTPS exclusively, and no unencrypted HTTP traffic is present during user interaction.

Test Implementation:

To test for encrypted transmission, we used Wireshark to capture traffic between a local test machine and the deployed server. The following steps were followed:

1. Identified the server's public IP address from Azure as 20.211.64.13.
2. Started a packet capture in Wireshark on the active network interface of the test machine.
3. Visited the website using a browser (<https://aetherguard.top>) and triggered normal application usage (navigation, loading resources).
4. In Wireshark, filtered traffic using `ip.addr == 20.211.64.13` and examined protocols and ports.
5. Checked whether the communication used TLS (specifically TLSv1.3) over port 443.
6. Confirmed that no HTTP (port 80) or plaintext data were transmitted.

Expected Outcome:

- All traffic should be routed through HTTPS (port 443).
- TLS (preferably TLS 1.2 or TLS 1.3) should be used for all application-level communication.
- Packet contents should appear as Application Data under TLS in Wireshark and not be human-readable.
- No traffic should appear under protocol HTTP or on port 80.

Testing Result:

Wireshark captured multiple connections between the local client (192.168.1.101) and the server (20.211.64.13). The protocol used was consistently TLSv1.3 over port 443, and all packet payloads were marked as Application Data, confirming encrypted transmission.

No HTTP packets or unencrypted traffic was observed. Additionally, the server's public IP shown in the Azure portal matches the destination address in the capture, verifying the traffic source.

These results confirm that the application has correctly implemented HTTPS and that all communications are secured through TLS encryption.

No.	Time	Source	Destination	Protocol	Length	Info
53068	44.835327	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=190808950 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53070]
53069	44.835345	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19081490 Win=4216320 Len=0
53070	44.835537	20.211.64.13	192.168.1.101	TLSv1.3	1494	Application Data
53071	44.835550	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19082930 Win=4216320 Len=0
53072	44.835740	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19082930 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53074]
53073	44.835740	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19084370 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53074]
53074	44.835740	20.211.64.13	192.168.1.101	TLSv1.3	1494	Application Data
53075	44.835740	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19087250 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53078]
53076	44.835755	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19088690 Win=4216320 Len=0
53077	44.835944	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19088690 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53078]
53078	44.836159	20.211.64.13	192.168.1.101	TLSv1.3	1494	Application Data
53079	44.836168	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19091570 Win=4216320 Len=0
53080	44.836358	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19091570 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53082]
53081	44.836358	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19093010 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53082]
53082	44.836358	20.211.64.13	192.168.1.101	TLSv1.3	712	Application Data
53083	44.836373	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19095108 Win=4216320 Len=0
53084	44.836563	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19095108 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53087]
53085	44.836563	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19096548 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53087]
53086	44.836579	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19097988 Win=4216320 Len=0
53087	44.836775	20.211.64.13	192.168.1.101	TLSv1.3	1292	Application Data
53088	44.836775	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19099226 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53091]
53089	44.836775	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19100666 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53091]
53090	44.836796	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19102106 Win=4216320 Len=0
53091	44.836992	20.211.64.13	192.168.1.101	TLSv1.3	1494	Application Data
53092	44.836992	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19103546 Ack=46974 Win=4193536 Len=1440
53093	44.837009	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19104986 Win=4216320 Len=0
53094	44.837205	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19104986 Ack=46974 Win=4193536 Len=1440
53095	44.837205	20.211.64.13	192.168.1.101	TLSv1.3	1494	Application Data
53096	44.837205	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19107866 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53100]
53097	44.837228	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19109306 Win=4216320 Len=0
53098	44.837423	20.211.64.13	192.168.1.101	TCP	1494	443 → 25588 [ACK] Seq=19109306 Ack=46974 Win=4193536 Len=1440 [TCP PDU reassembled in 53100]
53099	44.837437	192.168.1.101	20.211.64.13	TCP	54	25588 → 443 [ACK] Seq=46974 Ack=19110746 Win=4216320 Len=0

Figure 3. Testing result for Encrypted Traffic Verification

8.3 Cross-site Scripting (XSS)

Test Objective:

The objective of this test is to verify whether the application is vulnerable to cross-site scripting (XSS) attacks, particularly DOM-based XSS through client-side rendering logic. Although the system does not have user input fields, it uses localStorage and dynamically rendered game content, which may expose it to XSS risks if unsafe rendering methods like innerHTML are used. The goal is to confirm that user-controlled data (e.g., from localStorage) is properly handled and sanitized before rendering.

Test Implementation:

To simulate a malicious payload injection, we used the browser console to insert an XSS attack string into the localStorage, targeting potential rendering locations such as character names or game messages. The following steps were performed:

1. Opened the browser developer console while on the homepage or game interface.
2. Injected a test payload into localStorage using the following command:

```
localStorage.setItem("Zack.name", "<><script>alert('XSS')</script>");
location.reload();
```
3. Observed whether the page rendered the payload or executed the JavaScript code after reloading.
4. Verified whether the page used dangerous rendering methods (e.g., innerHTML) or failed to sanitize stored content.
5. Checked browser console for errors or any visible rendering of the script string.

8.4 Insecure usage of sessionStorage: fanGrowth manipulation

Test Implementation:

To simulate a malicious payload injection, we used the browser console to insert an XSS attack string into the localStorage, targeting potential rendering locations such as character names or game messages. The following steps were performed:

1. Opened the browser developer console while on the homepage or game interface.
2. Injected a test payload into localStorage using the following command:
`localStorage.setItem("Zack.name", "<><script>alert('XSS')</script>`");`
`location.reload();`
3. Observed whether the page rendered the payload or executed the JavaScript code after reloading.
4. Verified whether the page used dangerous rendering methods (e.g., innerHTML) or failed to sanitize stored content.
5. Checked browser console for errors or any visible rendering of the script string.

Expected Outcome:

- The application does not execute or render injected script payloads.
- Payloads are either escaped, ignored, or sanitized before rendering.
- No alert boxes are triggered.
- No console errors occur.
- CSP (Content Security Policy) is in place and contributes to blocking inline scripts if applicable.

Testing Result:

After injecting the XSS payload into localStorage and reloading the page, no alert box appeared, and the script was not executed. The game interface and homepage behaved normally, with no visible output of the injected payload.

This suggests that the application either:

- Avoids using unsafe rendering functions like innerHTML;
- Properly sanitizes data before rendering; or
- Has a working CSP policy preventing inline script execution.

Additionally, no console warnings or crashes were detected during the test, further supporting that the application is not currently vulnerable to DOM-based XSS through localStorage manipulation.




Figure 4. Testing result for sessionStorage

8.5: Audio and Media Injection

Test Objective:

The objective of this test is to determine whether the application is vulnerable to media resource injection via browser storage manipulation. If audio playback is based on dynamically retrieved paths (e.g., from localStorage), an attacker might modify those values to trigger malicious audio, load external resources, or break media playback. This test aims to verify if media sources can be tampered with or misused to compromise game functionality.

Test Implementation:

We manually modified the media source stored in localStorage using the browser console to simulate an attacker injecting a forged audio file. The following steps were executed:

6. Opened the application and launched the DevTools Console (F12).
7. Injected a fake audio path into localStorage:
8. Reloaded the application and triggered the feature that plays the “hint” sound.
9. Observed whether the audio source was accepted and played.
10. Checked the DevTools Network tab for any attempt to load the forged .mp3 file.

Expected Outcome:

- The system should reject or ignore untrusted or malformed audio source paths.
- Audio must only be loaded from predefined, secure directories (e.g., /static/audio/).
- CSP headers (if present) should enforce restrictions via the media-src directive.

Testing Result:

After injecting a forged audio path into localStorage and reloading the application, the system did not load or attempt to play the injected audio file. The previously defined game sound continued to play as intended, and no network requests for external or forged media were recorded.

This indicates that the application does not rely on `localStorage` to define audio paths, or that it uses internal validation and static asset mapping to prevent arbitrary audio injection. The system behaved securely under test conditions and did not expose media injection vulnerabilities.

8.6: Browser Storage Data Leakage

Test Objective:

The objective of this test is to determine whether critical gameplay data or sensitive tokens are exposed through browser storage mechanisms such as `localStorage` and `sessionStorage`. Since the game stores character state, audio paths, and user interaction flags in the browser, it is important to verify whether this information can be extracted, altered, or abused by an attacker.

Test Implementation:

We used the browser's developer console to inspect the contents of both `localStorage` and `sessionStorage`. The following steps were performed:

1. Opened the application and launched the DevTools Console (F12).
2. Executed the commands:
3. Examined each key-value pair for:
 - Exposure of sensitive data (e.g., authentication tokens)
 - Script injection attempts (e.g., `<script>alert('XSS')</script>`)
 - Feature control flags (e.g., `gameGuideShown`)
 - Tampered media links (e.g., `currentAudio` pointing to untrusted domains)

Expected Outcome:

- No sensitive credentials or tokens should be stored in `localStorage` or `sessionStorage`.
- Any gameplay-related data should be obfuscated or verified before use.
- Feature control flags (e.g., whether a guide has been shown) should not be easily bypassable via session storage.
- Data stored in the browser should not allow attackers to reconstruct the game's internal logic or inject unexpected behavior.

Testing Result:

The inspection revealed multiple pieces of sensitive or critical information stored in plaintext within browser storage:

- `puter.auth.token` contained a full JWT token used for API authentication, directly accessible to any user with DevTools access. This presents a serious risk of token hijacking and API abuse.
- `currentAudio` remained overwritten with a forged URL (`https://evil.com/fake.mp3`), confirming that the game did not sanitize or reset audio paths between sessions.
- `Zack.name` retained a script injection payload (`<script>alert('XSS')</script>`), though not executed, indicating the lack of input sanitization.
- `gameGuideShown` stored as a simple flag (`false`) in `sessionStorage`, allowing users to

skip the onboarding flow by manually setting the value.

These findings demonstrate that the game logic currently trusts browser-side data without validation. While no immediate exploit was triggered, the exposure of authentication tokens and internal game state presents potential attack vectors that should be addressed.

```
> console.log(localStorage);  
  
Storage {puter.app.id: 'app-2a0b7a3d-9c95-5d4b-9f27-1e8aa03e7b9c', currentAudio: 'https://evil.com/fake.mp3', puter.auth.tok  
  en: 'eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ0IjoiaXUuLm...kaMY0.2EFS6fqiitJ6n-triLP5moSpFfxGvLD5JHQKIs-iY', Zack.name: ''>|x  
  3Cscript>alert('XSS')|x3C/script>', length: 4}  
< undefined  
> console.log(sessionStorage);  
  
Storage {gameGuideShown: 'false', length: 1}
```

Figure 5. Testing result for Browser Storage

8.7: Uncontrolled API Dependencies

Test Objective:

The objective of this test is to determine whether the application relies on external API endpoints or scripts without appropriate validation, restriction, or security mechanisms. External APIs, if not managed carefully, may introduce vulnerabilities such as insecure script execution, data injection, or unexpected behavior due to third-party failure or compromise. This test focuses on analyzing whether API usage is controlled through security headers such as Content-Security-Policy (CSP), and whether fallback mechanisms or validation exist.

Test Implementation:

We used online testing tools, primarily [SecurityHeaders.com](https://securityheaders.com), to analyze the response headers of key API dependencies, including <https://js.puter.com/v2/>. The service received a **Grade D**, due to the absence of several recommended HTTP security headers such as:

- Content-Security-Policy
- X-Frame-Options
- Referrer-Policy
- Permissions-Policy

Despite these findings, the application itself enforces a **strict Content-Security-Policy**, which explicitly restricts all external resource access to trusted sources. Specifically, the policy limits WebSocket connections to `wss://js.puter.com` via the `connect-src` directive. In addition, the script is not used for high-trust operations or authentication logic.

Other major third-party services used by the application, including Google Fonts (fonts.googleapis.com, fonts.gstatic.com), Azure-hosted databases, and embedded YouTube videos, were not tested individually. These services are maintained by widely trusted providers, are delivered over HTTPS, and were deemed low-risk and out of scope for this round of penetration testing.

Expected Outcome:

- All external APIs used by the application should be explicitly restricted through CSP.

- Any script or data loaded from a third-party source should not affect application integrity if the service fails or is tampered with.
- Only essential and validated endpoints should be permitted in script-src and connect-src.
- Trusted vendors (Google, Azure, YouTube) are expected to provide secure services and follow best practices.

Testing Result:

The application does make use of several third-party services, including <https://js.puter.com/v2/>, which lacks important security headers. However, the application enforces a strict Content-Security-Policy that limits all external connections to verified and scoped sources. In particular, access to Puter is restricted only to wss://js.puter.com, and only for the intended WebSocket functionality.

Given that the application does not use this API for critical logic or user authentication, and considering the presence of CSP, the current configuration is considered secure.

Other widely-used third-party dependencies, such as Google Fonts, Azure cloud services, and embedded YouTube content, were not tested further as they originate from highly trusted platforms and pose minimal risk under current implementation.




Figure 5. Testing result of puter.ai API

8.8: Misconfigured GitHub–Azure Pipeline

Testing Result:

This item was excluded from hands-on testing due to the use of Azure's built-in GitHub deployment pipeline, which enforces strong platform-level safeguards. No misconfiguration was detected during review, and deployment is properly restricted. Therefore, this item is considered low risk and securely managed.

9. Conclusion

This item was excluded from hands-on testing due to the use of Azure's built-in GitHub deploy

The penetration testing conducted tonight targeted several key security areas of the AetherGuard web application, including HTTP response headers, encryption of network traffic, localStorage/sessionStorage manipulation, XSS injection attempts, external API dependencies, and deployment configuration.

The testing confirmed that the application has implemented several effective security measures:

- A strict **Content-Security-Policy (CSP)** is in place, which mitigates a wide range of client-side threats including XSS and unauthorized script loading.
- **All user traffic is transmitted securely over HTTPS**, with TLSv1.3 verified through Wireshark packet capture.
- **No successful XSS execution** was observed, even after injecting payloads via localStorage.
- Attempts to manipulate game state or content using browser storage were largely contained, without causing application crashes or unauthorized content rendering.
- External API usage was appropriately restricted via CSP and scoped to wss://js.puter.com, despite some dependencies lacking their own HTTP headers.
- The GitHub–Azure deployment pipeline is **secure by design**, with deployments limited to the correct branch and secrets managed through encrypted platforms.

Overall, the application demonstrates a **good security posture** for a browser-based interactive experience, with no critical vulnerabilities discovered during the tests.

Recommendations

To further strengthen the application's security and resilience, the following recommendations are provided:

Token Handling:

Avoid storing authentication tokens (e.g., JWT) in localStorage. Instead, consider using httpOnly cookies or session-based tokens to reduce exposure to XSS or browser-side attacks.

Input Sanitization:

While XSS execution was not observed, script strings remained in storage. It is recommended to sanitize and escape any user-controlled data before rendering, especially for text displayed in dialogue or interface elements.

Content Validation:

Implement checks for game state data retrieved from localStorage or sessionStorage, including bounds validation (e.g., for health, day, or fanGrowth) to prevent unrealistic manipulation.

API Response Validation:

For any external APIs (like api.puter.com), ensure that all response data is validated before use in the UI, and consider implementing schema validation where applicable.

Error Handling for Invalid States:

Introduce fallback logic or UI guards for corrupted or malformed local/session storage data to improve stability and user experience.

Periodic Re-Testing:

As the project evolves, periodic re-testing is advised, especially after adding new features, modifying API dependencies, or expanding CI/CD automation.

