

JQuery Exersice


1. Console "Hello Word" in document.ready function

Sol:-

Program file – ques1.html

```
<html>
<head>
  <script src="https://code.jquery.com/jquery-1.9.1.min.js"></script>
  <script>
    $( document ).ready(function() {
      console.log( "Hello world" );
    });
  </script>
</head>
<body>
  <h2>Jquery</h2>
</body>
</html>
```

Output:



2. Select a ID name "#test" and add class "load" when DOM is loaded


Sol:-

Program file – ques2.html

```
<html>
<head>
  <script src="https://code.jquery.com/jquery-1.9.1.min.js"></script>
</head>
<body>
  <p id="test">Jquery</p>
</body>
<script>
  $(document ).ready(function() {
    $("#test").addClass("load");
  });
</script>
```

```
});  
</script>  
</html>
```

Output:-




3. Change the color of element which class name end with "-new"

Sol:-

Program file – ques3.html

```
<!DOCTYPE html>  
<html>  
<head>  
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>  
</head>  
<body>  
<p class="cls-new">I am Naveen Garg</p>  
<p class="cls-old">To The New</p>  
<span class="iam-new">Hello World</span>  
<script>  
$(document).ready(function() {  
  $(".[class$='-new']").css("color", "red")  
});  
</script>  
</body>  
</html>
```

OUTPUT:-



4. Disable submit button using jquery attr method

Sol:-

Program file – ques4.html

```
<!DOCTYPE html>
<html lang="en">
<body>
<h2>jQuery - How to disabled submit button after clicked</h2>

<form id="formABC" action="#" method="POST">
  <input type="submit" id="btnSubmit" value="Submit"></input>
</form>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/1.12.4/jquery.min.js"></script>

<script>
  $(document).ready(function () {

    $("#formABC").submit(function (e) {
      e.preventDefault();

      $("#btnSubmit").attr("disabled", true);

      return true;

    });
  });
</script>
</body>
</html>
```

Output:-

jQuery - How to disabled submit button after clicked

Submit

jQuery - How to disabled submit button after clicked

Submit

5. Change the font size of ".target" which has parent element with id name "#main"

Sol:-

Program file – ques5.html

```
<!DOCTYPE html>
<html>
<body>
<h3>jQuery - Change the font size </h3>
<button id="btn1">Click
</button>
<div id="div1" class="mydiv">
<p id="main" class="target" value="hw">
This is first <b>paragraph</b>
</p>
</div>
</body>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/1.12.4/jquery.min.js"></script>
<script >
$(document).ready(function () {
$("#btn1").click(function () {
alert($('#main').css("font-size", '+=20px'));
});
});
</script>
</html>
```

Output:

jQuery - Change the font size

Click

This is first paragraph

jQuery - Change the font size

Click

This is first paragraph

6. After page load change the HTML of div element with "p" element

Sol:-

Program file – ques6.html

```
<html>
  <head>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>
    <style>
      .test-new{
        font-size: 26px;
      }
      body{
        background-color: azure;
      }
    </style>
  </head>
  <body>
    <div>
      <h3>This is inside div tag.</h3>
    </div>
    <p class="test-new">Hello, Have a great day.</p>
  </body>
  <script>
    $(document).ready(function(){
      $("div").html("<p>")
    });
  </script>
```

</html>

Output:



7.Bind a click function to an "click" element and append next "click" next to it.

Sol:-

Program file – ques7.html

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<meta charset="utf-8">
```

```
<title>bind demo</title>
```

```
<script src="https://code.jquery.com/jquery-3.5.0.js"></script>
```

```
</head>
```

```
<body>
```

```
  <a id="load_list" href="#">Load the list</a>
```

```
  <ul></ul>
```

```
</body>
```

```
<script>
```

```
  $('#load_list').click(function() {
```


```
    $('ul').append('<li><a href="#">Click here</a></li>');
```

```

        return false;
    });
    $('ul').delegate('a','click',function() {
        alert("Thank you for clicking");
        return false;
    });
</script>
</html>

```

Output:



8.Click event not working on element which added dynamicly or via script, make it work using .on method

Sol:-

Program File – ques8.html

HTML

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="utf-8">
    <title></title>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.8.3/jquery.min.js"></script>
</h2></h2>
<button>generate new element</button>

</head>

```

```

<body>

<script>
var counter = 0;
$("#button").click(function() {
$("#h2").append("<p class='test'>click me " + (++counter) + "</p>")
});
// With on():
$("#h2").on("click", "p.test", function(){
alert($(this).text());
});
</script>
</body>
</html>

```

Output:

JQuery

generate new element

JQuery

click me 1

click me 2

generate new element

9. Get dropdown selected value on onchange event and append in div container

Sol:-

Program file – ques9.html

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title></title>
  <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.8.3/jquery.min.js"></script>
</h2> JQuery </h2> <br>
<div class=container> hello </div> <br>
<select>

```




```

<option value="1">One</option>
<option value="2">Two</option>
</select>
<body>
<script>
$('select').on('change', function() {
alert( this.value );
{
    $("div").append(" <b>Naveen Garg</b>.");
}
});
</script>
</body>
</html>

```

Output:



10. Create a dropdown menu using hover method in jquery

Sol:-

Program file – ques10.html

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="utf-8">
    <title></title>
    <style>
.dropdown{

```

```

display: none;
}
</style>
<h2>jQuery</h2><br><br>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/2.1.1/jquery.min.js"></script>
<div class="wrapper">
<div class="button">
<button value="Hover on me!" id="hover">Hover On Me!
</button>
</div>
<div class="dropdown">
<ul>
<li><a href="#">C++</a></li>
<li><a href="#">Java</a></li>
<li><a href="#">JavaScript Page</a></li>
<li><a href="#">HTML Page</a></li>
<li><a href="#">CSS Page</a></li>
</ul>
</div>
</div>
</head>
<body>
<script>
$(document).ready(function(){
$(".button").hover(function(){
$(".dropdown").slideToggle();
});
});
</script>
</body>
</html>

```

Output:

jQuery

Hover On Me!

JQuery

Hover On Me!

- [C++](#)
- [Java](#)
- [JavaScript Page](#)
- [HTML Page](#)
- [CSS Page](#)

11. On clicking on "google" tag. It is taking us to google home page. Stop it from happening

Sol:-

Program file – ques11.html

```
<html>
  <head>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>


    <style>
      div{
        background-color: azure;
        border-radius: 10px;
        margin: 30px;
        padding: 20px;
        text-align: center;
        font-size: 30px;
      }
      body{
        background-color: gray;
      }
    </style>
  </head>
  <body>
    <div class="container">
      <a href="https://www.google.com/">Google</a>
      <h5>.preventDefault() stops the default action of an element from happening.
    </h5>
    </div>
  </body>
  <script>
    $("a").click(function(event){
```

```

        event.preventDefault();
    });
</script>
</html>

```

Output:



12. We have bind a click funtion to parent div but we want stop it from performing when user clicks on its child li

Sol:-

Program file – ques12.html



```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title></title>
<script src="https://code.jquery.com/jquery-3.5.0.js"></script>
</head>
<body>
<div class="header">
  <a href="https://www.google.com/">parent link</a>
  <ul class="children">
    <li>click child list</li>
  </ul>
</div>
</body>
<script>
$(document).ready(function(){
  $(".header").click(function(){
    $(this).children(".children").toggle();
  });
  $(".header a").click(function(e) {
    e.stopPropagation();

```

```
});  
});  
</script>  
</html>
```

Output:



13. Get the max height of elements using jquery each method

Sol:-

Program file – ques13.html

```
<!DOCTYPE html>  
<html lang="en">  
<head>  
  <meta charset="utf-8">  
  <title></title>  
</head>  
<body>  
<div>  
  <div class="a">  
    Line number 1<br/>  
    Line number 2  
  </div>  
  <div class="a">  
    Line number 1<br/>  
    Line number 2<br/>
```

```
Line number 3<br/>
Line number 4<br/>
Line number 5<br/>
Line number 6<br/>
Line number 7
</div>
<div class="a">
  Line number 1
</div>
<div class="a">
  Line number 1<br/>
  Line number 2
</div>
</div>
<script src="https://code.jquery.com/jquery-3.5.0.js"></script>
<script>
var highest = null;
var hi = 0;
$(".a").each(function(){
  var h = $(this).height();
  if(h > hi){
    hi = h;
    highest = $(this);
  }
});
highest.css("background-color", "red");
</script>
</body>
</html>
```

Output:

Line number 1
Line number 2

Line number 1
Line number 2
Line number 3
Line number 4
Line number 5
Line number 6
Line number 7

Line number 1

Line number 1
Line number 2

14. Chagne color of every cell which has numberl larger than 10.

Sol:-

Program File – ques14.html

```
<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title></title>
  <script src="https://code.jquery.com/jquery-3.5.0.js"></script>
</head>
<body>
<table border="1">
  <tr><td>CELL #0</td><td>CELL #1</td><td>CELL #2</td></tr>
  <tr><td>CELL #3</td><td>CELL #4</td><td>CELL #5</td></tr>
  <tr><td>CELL #6</td><td>CELL #7</td><td>CELL #8</td></tr>
  <tr><td>CELL #9</td><td>CELL #10</td><td>CELL #11</td></tr>
  <tr><td>CELL #12</td><td>CELL #13</td><td>CELL #14</td></tr>
</table>
```

```

</body>
<script>
    $( "td:gt(10)" ).css( "backgroundColor", "yellow" );
</script>
</html>

```

Output:

CELL #0	CELL #1	CELL #2
CELL #3	CELL #4	CELL #5
CELL #6	CELL #7	CELL #8
CELL #9	CELL #10	CELL #11
CELL #12	CELL #13	CELL #14

15. Retrive the data from server using ajax get call

Sol:-

Program file – ques15.html


```

<!DOCTYPE html>
<html>
<head>
    <title></title>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.8.3/jquery.min.js"></script>
</head>
<body>
<button id="btn">Click</button>
<div>
<p id="result">
</div>
<script>
    $(document).ready(function(){
        $("#btn").click(function(){
            $.ajax({url: "https://jsonplaceholder.typicode.com/posts", success: function(result){
                console.log(result);
                $("#result").html(JSON.stringify(result));}});
        });
    });
</script>
</body>

```


</html>

Output:



16. Add cross button on row and bind click function which make a delete request to server, after success event remove the row from dom

Sol:-

Program file – ques16.html

<html>

<head>

<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>

</head>

<body>

<button id="btn">Click</button>

<div class="data">

</div>

<script>

\$(document).ready(function(){

\$(document).on('click', '.del', function(e){

let id =\$(this).attr('name')

\$.ajax({


url: 'https://jsonplaceholder.typicode.com/posts/'+id,

type: 'DELETE',

success: function(result) {

```
alert("successfully deleted")
$('#div#'+id).remove();
}
});
});
$("#btn").click(function(){
$.ajax({
url: 'https://jsonplaceholder.typicode.com/posts/',
success: function(result) {
for(var i in result)
{
$('.data').append(
'<div id='+result[i].id+'> <span id='+result[i].id+'>'+result[i].title+'</span> <button class="del"
name='+result[i].id+'>X</button></div>'
);
}
}
});
});
});
</script>
</body>
</html>
```

Ouput:



17. Create a image array and in div create a slide show to animate images of delay of 500ms.

Sol:-

Program file – ques17.html

```
<!DOCTYPE html>

<html>

<head>

<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>

</head>

<body>

<button id="start">Start slide</button>

<button id="stop">Stop slide</button><br><br><br><br>

<div id="images" border="1"></div>

<script>

$(document).ready(function(){

var interval;

$('#start').on("click",function()

{

var i=0;

var arr = new Array("https://picsum.photos/536/354", "https://picsum.photos/536/355",

"https://picsum.photos/536/356", "https://picsum.photos/536/357");
```

```

interval =setInterval(function()
{$('#images').html('');
i++;
if(i==4)
i=0;
}, 2000);
});
$('#stop').on("click",function()
{
clearInterval(interval);
});
});
</script>
</body>
</html>

```

Output:

