Export the report (Runs in the background)

API Endpoint

`POST /api/v2/report-export/`

Example Payloads

1. Using the complete payload with settings information (& Saving the settings)

```
{
    "name": "Last 7 Days Report",
    "description": "Seven days report",
    "report_type": "ticket_report_export",
    "date_range": "custom",
    "from_date": "2017-01-01",
    "to_date": "2018-01-01",
    "filter_date_by": "created_at",
    "settings": {
        "all_categories": true,
        "categories": [],
        "ticket_fields": ["ticket_subject"],
        "contact_fields": ["contact_name"],
        "ticket_custom_field": [1, 2],
        "contact_custom_fields": [3, 4],
        "contact_group_custom_fields": [5, 6],
        "strip_newlines": true,
        "filters": {
            "match_all": [],
            "match_any": [
                {
                    "field": "assignee_id",
                    "predicate": "in",
                    "value": [93]
                },
                {
                    "field": "status_id",
                    "predicate": "in",
                    "value": [1]
                }],
            "resource_type":"tickets"
        }
    },
    "save_settings": true,
    "export_as": "csv"
}
```

2. Using the complete payload with settings information (& Not saving the settings). In this case `name` & `description` are not needed unlike the previous case.

```json
{
    "report_type": "ticket_report_export",
    "date_range": "custom",
    "from_date": "2017-01-01",
    "to_date": "2018-01-01",
    "filter_date_by": "created_at",
    "settings": {
        "all_categories": true,
        "categories": [],
        "ticket_fields": ["ticket_subject"],
        "contact_fields": ["contact_name"],
        "ticket_custom_field": [1, 2],
        "contact_custom_fields": [3, 4],
        "contact_group_custom_fields": [5, 6],
        "strip_newlines": true,
        "filters": {
            "match_all": [],
            "match_any": [
                {
                    "field": "assignee_id",
                    "predicate": "in",
                    "value": [93]
                },
                {
                    "field": "status_id",
                    "predicate": "in",
                    "value": [1]
                }],
            "resource_type":"tickets"
        }
    },
    "save_settings": false,
    "export_as": "csv"
}
```

3. Using the complete payload with settings information (& Updating the settings)

```json
{
    "name": "Last 7 Days Report",
    "description": "Seven days report",
    "report_type": "ticket_report_export",
    "date_range": "custom",
    "from_date": "2017-01-01",
    "to_date": "2018-01-01",
    "filter_date_by": "created_at",
    "settings": {
        "all_categories": true,
        "categories": [],
        "ticket_fields": ["ticket_subject"],
        "contact_fields": ["contact_name"],
        "ticket_custom_field": [1, 2],
```

```json
        "contact_custom_fields": [3, 4],
        "contact_group_custom_fields": [5, 6],
        "strip_newlines": true,
        "filters": {
            "match_all": [],
            "match_any": [
                {
                    "field": "assignee_id",
                    "predicate": "in",
                    "value": [93]
                },
                {
                    "field": "status_id",
                    "predicate": "in",
                    "value": [1]
                }],
            "resource_type":"tickets"
        }
    },
    "save_settings": true,
    "export_as": "csv",
    "settings_id": 1
}
```