

# Rajalakshmi Engineering College

Name: Naveed Sheriff  
Email: 240701348@rajalakshmi.edu.in  
Roll no: 240701348  
Phone: 9025573780  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John and Mary are collaborating on a project that involves data analysis. They each have a set of age data, one sorted in ascending order and the other in descending order. However, their analysis requires the data to be in ascending order.

Write a program to help them merge the two sets of age data into a single sorted array in ascending order using merge sort.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of age values in each dataset.

The second line consists of N space-separated integers, representing the ages of participants in John's dataset (in ascending order).

The third line consists of N space-separated integers, representing the ages of participants in Mary's dataset (in descending order).

### **Output Format**

The output prints a single line containing space-separated integers, which represents the merged dataset of ages sorted in ascending order.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

1 3 5 7 9

10 8 6 4 2

Output: 1 2 3 4 5 6 7 8 9 10

### **Answer**

```
#include <stdio.h>
```

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int n;
```

```
    scanf("%d",&n);
```

```
    int m= n+n;
```

```
    int a[m];
```

```
    for(int i=0;i<m;i++)
```

```
    {
```

```
        scanf("%d",&a[i]);
```

```
    }
```

```
    for(int i=1;i<m;i++)
```

```
    {
```

```
        int temp = a[i];
```

```
        int j=i-1;
```

```
        while(j>=0 && a[j]>temp)
```

```
        {
```

```
            a[j+1] = a[j];
```

```
            j--;
```

```

    }
    a[j+1] = temp;
}
for(int i=0;i<m;i++)
{
    printf("%d ",a[i]);
}
}

int main() {
    int n, m;
    scanf("%d", &n);
    int arr1[n], arr2[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr1[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr2[i]);
    }
    int merged[n + n];
    mergeSort(arr1, n);
    mergeSort(arr2, n);
    merge(merged, arr1, arr2, n, n);
    for (int i = 0; i < n + n; i++) {
        printf("%d ", merged[i]);
    }
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10