Dispatch Service Setup Guide — CentOS 9

Dispatch is the service which dispatches the product after purchase. It is written in GoLang, so GoLang is required.

1. Install GoLang

Install GoLang on the CentOS 9 server.

```
dnf install golang -y
```

2. Add Application User

Create the roboshop application user.

```
useradd roboshop
```

3. Create Application Directory

Create the application directory.

```
mkdir /app
```

4. Download Application Code

Download the Dispatch application artifact to /tmp.

```
curl -L -o /tmp/dispatch.zip https://roboshop-builds.s3.amazonaws.com/dispatch.zip
```

5. Extract Application Code

Change to /app and extract the downloaded application.

```
cd /app
unzip /tmp/dispatch.zip
```

6. Initialize Go Module

Initialize the Go module for the Dispatch application.

```
cd /app
go mod init dispatch
```

7. Download Go Dependencies

Download the dependencies required by the Dispatch application.

```
go get
```

8. Build the Dispatch Application

Build the Dispatch application binary.

```
go build
```

9. Configure SystemD Dispatch Service

Create /etc/systemd/system/dispatch.service and replace the RabbitMQ placeholder with the actual RabbitMQ server IP address.

```
[Unit]
Description=Dispatch Service

[Service]
User=roboshop
Environment=AMQP_HOST=<RABBITMQ-SERVER-IPADDRESS>
Environment=AMQP_USER=roboshop
Environment=AMQP_PASS=roboshop123
ExecStart=/app/dispatch
SyslogIdentifier=dispatch

[Install]
WantedBy=multi-user.target
```

10. Reload SystemD

Reload systemd so it recognizes the newly created Dispatch service.

```
systemctl daemon-reload
```

11. Enable and Start Dispatch Service

Enable Dispatch to start automatically at boot and start the service.

```
systemctl enable dispatch
systemctl start dispatch
```

12. Verify Dispatch Service

Check the current status of the Dispatch service.

```
systemctl status dispatch
```

Final Command Sequence

```
dnf install golang -y
useradd roboshop
mkdir /app
curl -L -o /tmp/dispatch.zip https://roboshop-builds.s3.amazonaws.com/dispatch.zip
cd /app
unzip /tmp/dispatch.zip
go mod init dispatch
go get
go build

# Create /etc/systemd/system/dispatch.service
systemctl daemon-reload
systemctl enable dispatch
systemctl start dispatch

systemctl status dispatch
```

Important: Replace <RABBITMQ-SERVER-IPADDRESS> with the actual RabbitMQ server address. The RabbitMQ username and password must match the credentials configured on the RabbitMQ server.