MySQL Installation on CentOS Stream 9 (Roboshop)

Service Overview

MySQL is the relational database used by the Shipping service in Roboshop. CentOS Stream 9 supports MySQL 8.0. This guide explains installation and automation using shell scripts.

1. Disable Default Module

Disable the default MySQL module.

```
dnf module disable mysql -y
```

2. Configure Repository

Create /etc/yum.repos.d/mysql.repo

```
[mysql80-community]
name=MySQL 8.0 Community Server
baseurl=https://repo.mysql.com/yum/mysql-8.0-community/el/9/$basearch/
enabled=1
gpgcheck=0
```

3. Install MySQL

Install MySQL Community Server.

```
dnf install mysql-community-server -y
```

4. Enable and Start Service

Enable MySQL during boot and start it.

```
systemctl enable mysqld
systemctl start mysqld
systemctl status mysqld
```

5. Configure Root Password

For shell scripts, first check whether the password is already configured. If not, use the automated option when available, otherwise retrieve the temporary password and change it manually.

```
mysql -uroot -pRoboShop@1 -e "show databases;"

if [ $? -ne 0 ]
then
    if mysql_secure_installation --help | grep -q "set-root-pass"
    then
        mysql_secure_installation --set-root-pass RoboShop@1
    else
        TEMP_PASS=$(grep 'temporary password' /var/log/mysqld.log | awk '{print $NF}')
        mysql --connect-expired-password -u root -p"${TEMP_PASS}" -e "ALTER USER 'root'@'localhost' I
    fi
else
    echo "MySQL Root Password Already Set... SKIPPING"
fi
```

6. Verify Installation

Verify that the root password works.

```
mysql -uroot -pRoboShop@1 -e "show databases;"
```

Command Summary

Quick reference.

```
dnf module disable mysql -y
```

```
dnf install mysql-community-server -y
systemctl enable mysqld
systemctl start mysqld
mysql -uroot -pRoboShop@1 -e "show databases;"
```