RabbitMQ Setup Guide — CentOS 9

RabbitMQ is a messaging queue used by some components of the application.

1. Configure Erlang YUM Repository

Configure the Erlang repository using the repository script provided by the vendor.

```
curl -s https://packagecloud.io/install/repositories/rabbitmq/erlang/script.rpm.sh | bash
```

2. Configure RabbitMQ YUM Repository

Configure the RabbitMQ Server repository.

```
curl -s https://packagecloud.io/install/repositories/rabbitmq/rabbitmq-server/script.rpm.sh | bash
```

3. Install RabbitMQ

Install the RabbitMQ server package. On CentOS 9, dnf is preferred, although yum is also available.

```
dnf install rabbitmq-server -y
```

4. Enable RabbitMQ Service

Enable RabbitMQ to start automatically when the server boots.

```
systemctl enable rabbitmq-server
```

5. Start RabbitMQ Service

Start the RabbitMQ service.

```
systemctl start rabbitmq-server
```

6. Check RabbitMQ Service

Verify that RabbitMQ is running.

```
systemctl status rabbitmq-server
```

7. Create Application User

RabbitMQ comes with a default guest/guest user. The guest user cannot be used for remote application connections, so create a separate application user.

```
rabbitmqctl add_user roboshop roboshop123
```

8. Set Permissions for Application User

Give the roboshop user permissions on the default / virtual host.

```
rabbitmqctl set_permissions -p / roboshop ".*" ".*" ".*"
```

9. Verify RabbitMQ User

Verify that the roboshop user was created successfully.

```
rabbitmqctl list_users
```

Final Command Sequence

```
curl -s https://packagecloud.io/install/repositories/rabbitmq/erlang/script.rpm.sh | bash

curl -s https://packagecloud.io/install/repositories/rabbitmq/rabbitmq-server/script.rpm.sh | bash

dnf install rabbitmq-server -y

systemctl enable rabbitmq-server

systemctl start rabbitmq-server

rabbitmqctl add_user roboshop roboshop123

rabbitmqctl set_permissions -p / roboshop ".*" ".*" ".*"
```

Expected service status: Active: active (running)