2)
```java
//
    import java.sql.*;
    import java.util.*;
    public class Q2 {
        public static void main (String[] args) {
    // TODO Auto-generated method stub try {

    Class.forName ("Com.mysql.cj.dbc.Driver");

    Connection
    conn = DriverManager.getconnection ("jdbc.mysql://localhost:3306/
    mydb", "root", "1234");
    System.out.println ("Connected");
        PreparedStatement
        pst = conn.prepareStatement ("insert into book details values(?,?,?,?)");
    Scanner sc = new Scanner (System.in);
    System.out.println ("Enter book name");
        String bname = sc.nextline();
    System.out.println ("Enter author name");

    String name = sc.nextline();
    System.out.println ("Enter no. of pages");
    int nop = sc.nextInt();
    System.out.println ("Enter price");
    int price = sc.nextInt();
    pst.setString (1, bname);
    pst.setString (2, bname);
    pst.setInt (3, nop);
    pst.setInt (4, price);
    int x = pst.executedUpdate ();
    pst.close();
```

Hitesh

```java
if (x! = 0) {
System. out. println ("Data inserted");
}

else {
System. out. println ("Enter again");
}
pst = conn. prepareStatement ("select * from bookdetails");
ResultSet rs = pst. executeQuery ();
while (rs. next ()) {
System. out. println (" Book Name: " + rs. getString (1));
System. out. println (" Author Name: " + rs. getString (2));
System. out. println (" No. of pages: " + rs. getInt (3));
System. out. println (" Price: " + rs. getInt (4));
}

// create procedure
// rs. first ();
conn. close ();

}
cat (Exception e) {
e. printStackTrace ();
}
}
}
```

Hiteshi