Name Nipurn Khotni Rolling. 200		
Course. MCA-2A	T	*
		**
07		9
Inden . html	7006/	*
html		
< html>		e la
(head) (neta charset="150-8859-1")		- h
(title) livent title here (title)		
(/head)		
(body)	• 4	
< form action - "login jsp">	1.1	
(table)		
$\langle \mathcal{W} \rangle$	. 1	
Enter warname	F. 189.1	iyo.
(td) <input home="41&lt;/td" type="tent"/> <td></td> <td></td>		
(Ad) (Ar)	6	
(tv)		
<+d>Enter paraword		

(1/4) > "Login"> 1.1. 11: "1" </form> (/tody) 1 - Rigg - 191 - Parado 191 . " (/html) Jet Dunglade L. V. Suffer, The second second DBatil import java sql. X; public class DButil & static Connection con = hull; Static Prepared Statement pst=hull; · division which is static static ResultSet is milly The state of the Public static Connection get Comm() { try ? ass. For Name ("ovade. jdbc. driver. Ovadelhirer"); 3/2 1. 2. of x . 1 4

con = Driver Manager. get Connection ("jabe: oracle thin @ books."
1521: XE", "Soma", abod"). catch (Exception c) { A 10 10 , 1 10, System.out.println(e); Feturn con; public static Result Set Sgot Outa () throws Exception ? (on = get (om (); pst = con. prepare Statement ("select & from wers"); 15 = pst. eneasteQuery(); public static int add Data (UserBean 6) throws Exception & con = get (onn(); pst = con preparatotement ("insert into users values (?,???) pst setString (1, b, get Name ()); Pst. set String (2, b.getParsword());

pst. settit (3, b. get Age ()); pst. setInt (4, b.getPhone (1); 1 = pst. eneute Update (); i story package injert west hildler to here's it. give. Tv K public does the Bean ? private String name). private String parsword; prisonte int. age; poliste int phone of war tout and believe that I then they public String getName () ¿ Letur name: public voil settlame (String name) ? 2 this none = name; 

public String get Pousword OE Jehun paisword; Public void setParsword (String Str Parsword) ?

this parsword = parsword; to the week from public int. get Age () { the call for all is Letium age; public void setAge (int age) { this.age = age ; public int getPhone () { Leturn phone; public void set Phone (int phone) & this phone = phone ;

lagin.jap < 1. @ page language = "joura" content Type = tent/Lital; charset = 150-8859-1" page Encoding = "150-8889-1"/> <1.0 page import="co. --- "1.> (1.@ page import = " 1.> < 1.0 page import= "java.sql\*"/> < Html> <head > < mita charst="150-8859-1"> 11 3 41 . 3 <title > Insert title here <1title> - Allow to the (head) < body> <! !! The Beam v = null; Result Set is = hall; !! > Respect Orspotcher rd = regress, get Request Dispotcher ("Success. String id = lequest. getPorsoneter ("H"); String PSW = request. got Povamitur ("t2"); () atolding. Stude = c+1

boden status false; while (rs. nout)) { if ( (id equals (15 get String (1)) & (psw equals (15 get String (17))), 5 status = true; if (status) { rd. forward (request. response); Dise & privath ("Invalid id or parsuored"); </body>
</html>

< 1.6 page language = Java .... (head) < meta charset = "150-8859-1"> <title> hoser title have </title> (head) String user = lequest get Pairsmeter ("+1");
 out. pretty ("Welcome", + user + "?"); would be as helper I the (body) </Atml>