

SWEN221 Software Design and Engineering

6: Java Assert Keyword

Marco Servetto, David J. Pearce

VUW

Assert Keyword

- ▶ Added in Java 1.4
Basic use is extremely simple:

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

Assert Keyword

- ▶ Added in Java 1.4
Basic use is extremely simple:
 - ▶ **assert** *<condition>*;

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

Assert Keyword

- ▶ Added in Java 1.4

Basic use is extremely simple:

- ▶ **assert** *<condition>*;

Or

- ▶ **assert** *<condition>* : *<message>*;

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

Assert Keyword

- ▶ Added in Java 1.4

Basic use is extremely simple:

- ▶ **assert** *<condition>*;

Or

- ▶ **assert** *<condition>* : *<message>*;

- ▶ Disabled by default. Use `java -ea MyProgram`

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

```
assert x!=null;
```

```
assert x>=0;
```

Assert Keyword

- ▶ Added in Java 1.4

Basic use is extremely simple:

- ▶ **assert** *<condition>*;

Or

- ▶ **assert** *<condition>* : *<message>*;

- ▶ Disabled by default. Use `java -ea MyProgram`

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

```
assert x!=null;
```

```
assert x>=0;
```

```
assert x!=null: "x can not be not null";
```

```
assert x>=0: "x can not be negative";
```

Assert Keyword

- ▶ Added in Java 1.4

Basic use is extremely simple:

- ▶ **assert** *<condition>*;

Or

- ▶ **assert** *<condition>* : *<message>*;

- ▶ Disabled by default. Use `java -ea MyProgram`

```
void foo(A a) {  
    assert a!=null;  
    ...  
}
```

```
assert x!=null;
```

```
assert x>=0;
```

```
assert x!=null: "x can not be not null";
```

```
assert x>=0: "x can not be negative";
```

but also

```
assert isConsistent();
```

```
assert x!=null : ErrorHelpers.notNull("x", "Reason");
```

```
assert x!=null;
```

if `x` is `null` and assertions are enabled, then

```
throw new AssertionError(); //Unchecked Exception
```



```
assert x!=null;
```

if `x` is `null` and assertions are enabled, then

```
throw new AssertionError(); //Unchecked Exception
```

```
assert x!=null : "msg";
```

if `x` is `null` and assertions are enabled, then

```
throw new AssertionError("msg"); //Unchecked Exception
```

Enable Assertions

- ▶ Command line:
- ▶ Eclipse (stupid repetitive mode):
- ▶ Eclipse (smart but invasive mode):

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
- ▶ Eclipse (stupid repetitive mode):
- ▶ Eclipse (smart but invasive mode):

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
 - ▶ `java -ea -jar MyExecutable.jar`
- ▶ Eclipse (stupid repetitive mode):
- ▶ Eclipse (smart but invasive mode):

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
 - ▶ `java -ea -jar MyExecutable.jar`
- ▶ Eclipse (stupid repetitive mode):
 - ▶ Run → Run configurations → **select your configuration** → arguments → vm arguments → **write** “-ea”
- ▶ Eclipse (smart but invasive mode):

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
 - ▶ `java -ea -jar MyExecutable.jar`
- ▶ Eclipse (stupid repetitive mode):
 - ▶ Run → Run configurations → **select your configuration** → arguments → vm arguments → **write** “-ea”
- ▶ Eclipse (smart but invasive mode):
 - ▶ Window → Preferences → Java → Installed JREs
Select the JRE, press Edit button, inside “Default JRE Arguments” **write** “-ea”.

To enable assertions only in a package (and sub-packages)

`-ea:namePackage...` **No space before the three dots!!!**

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
 - ▶ `java -ea -jar MyExecutable.jar`
- ▶ Eclipse (stupid repetitive mode):
 - ▶ Run → Run configurations → **select your configuration** → arguments → vm arguments → **write** “-ea”
- ▶ Eclipse (smart but invasive mode):
 - ▶ Window → Preferences → Java → Installed JREs
Select the JRE, press Edit button, inside “Default JRE Arguments” **write** “-ea”.

To enable assertions only in a package (and sub-packages)

`-ea:namePackage...` **No space before the three dots!!!**

Even if Eclipse is in debug mode, even if you are using Junit or similar tools, assertions are not automatically enabled.

Enable Assertions

- ▶ Command line:
 - ▶ `java -ea MyMainClass`
 - ▶ `java -ea -jar MyExecutable.jar`
- ▶ Eclipse (stupid repetitive mode):
 - ▶ Run → Run configurations → **select your configuration** → arguments → vm arguments → **write** “-ea”
- ▶ Eclipse (smart but invasive mode):
 - ▶ Window → Preferences → Java → Installed JREs
Select the JRE, press Edit button, inside “Default JRE Arguments” **write** “-ea”.

To enable assertions only in a package (and sub-packages)

`-ea:namePackage...` **No space before the three dots!!!**

Even if Eclipse is in debug mode, even if you are using Junit or similar tools, assertions are not automatically enabled.

DEMO

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

X AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[] args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

C "b is false"

~~X~~ "b is null"

~~X~~ NullPointerException

~~X~~ *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

X AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

X AssertionError

X "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

☒ AssertionError

☒ "b is true"

☒ "b is false"

☒ "b is null"

☐ NullPointerException

☐ *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

~~X~~ "b is null"

~~X~~ NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac -ea A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

~~X~~ "b is null"

~~X~~ NullPointerException

F *invalid flag: -ea*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

A AssertionError

☒ "b is true"

☒ "b is false"

☒ "b is null"

☒ NullPointerException

☒ *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

X AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

D "b is null"

~~X~~ NullPointerException

~~X~~ *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

X AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

~~X~~ AssertionError

~~X~~ "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

~~X~~ AssertionError

~~X~~ "b is true"

~~X~~ "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

☒ AssertionError

☒ "b is true"

☒ "b is false"

☒ "b is null"

☐ NullPointerException

☐ *something else*

Quiz time

```
class A{  
    public static Boolean b;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

☒ AssertionError

☒ "b is true"

☒ "b is false"

☒ "b is null"

☐ NullPointerException

☒ *something else*

Quiz time

```
class A{  
    public static Boolean b=true;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

A AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b=true;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

X AssertionError

B "b is true"

C "b is false"

D "b is null"

E NullPointerException

F *something else*

Quiz time

```
class A{  
    public static Boolean b=true;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java -ea A

☒ AssertionError

☐ "b is true"

☒ "b is false"

☒ "b is null"

☒ NullPointerException

☒ *something else*

Quiz time

```
class A{  
    public static Boolean b=true;  
    public static void main(String[]args){  
        assert b;  
        System.out.println("b is "+b);  
    }  
}
```

>> javac A.java

>> java A

☒ AssertionError

☐ "b is true"

☒ "b is false"

☒ "b is null"

☒ NullPointerException

☒ *something else*

Contracts

Every method have,
implicitly or explicitly,
a contract.

```
int factorial(int n) {  
    if(n<1) return 1;  
    return n*factorial(n-1);  
}
```

If method is called
over acceptable parameters,
then a certain result
is produced.

Contracts

```
int factorial(int n) {  
    assert n>=0;  
    if(n<1) return 1;  
    return n*factorial(n-1);  
}
```

Modify the contract
of the method,
Make it simpler!

Pre/Post conditions

Checks at the end of method execution are called	Checks at the start of the method execution are called
postconditions	preconditions
Is a behavioural constraint: ensures your code behave as expected	Is a usage limitation: ensures your code is called as expected

```
void methodName(...) {  
    assert precondition();try{  
        ...DoSomething...  
    }finally{assert postcondition();}  
}
```

(p.s. doing useful checks in the middle of the method execution is a good idea, just there is no a special name)

How much code in assertions?

How much code in assertions?

- ▶ Verification code is very important
- ▶ As for regular code, you can factorize and modularize it with methods, classes, libraries..
- ▶ An equilibrate program with assertions can contain up to 50% of verification code

How much code in assertions?

- ▶ Verification code is very important
- ▶ As for regular code, you can factorize and modularize it with methods, classes, libraries..
- ▶ An equilibrate program with assertions can contain up to 50% of verification code
- ▶ In addition to testing

Assertions - Libraries

Assertions - Libraries

- ▶ great for debug

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state!

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)
- ▶ cooperate with documentation

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)
- ▶ cooperate with documentation (active documentation)

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)
- ▶ cooperate with documentation (active documentation)
 - ▶ make library usage safer

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)
- ▶ cooperate with documentation (active documentation)
 - ▶ make library usage safer
library used in unacceptable way

Assertions - Libraries

- ▶ great for debug (much better than `System.err.println(..)`)
- ▶ cooperate with private state! (preserve valid program state)
- ▶ cooperate with documentation (active documentation)
 - ▶ make library usage safer
library used in unacceptable way
→ `AssertionError` with an informative error message