

EuroEats

Data Dictionary

Relational Database Reference — 9 Tables • 14,967 Rows

Prepared by: EuroEats Data Team

Dataset Summary

The EuroEats database consists of 9 tables covering customers, restaurants, menu items, drivers, orders, order line items, deliveries, payments, and reviews. Exact row counts as of this extract are shown below.

Table	Row Count
customers	1,500
restaurants	120
menu_items	1,500
drivers	350
orders	4,500
order_items	4,697
deliveries	1,000
payments	800
reviews	500
TOTAL	14,967

How to read the table sections

Each of the following sections documents one table: its purpose, exact row count, and every column with its data type, key role, and description. **PK** marks a primary key; **FK** → **table.column** marks a foreign key and the table/column it references; **UQ** marks a uniqueness constraint (used where a table has at most one row per referenced order).

customers

Every person who has signed up to order on the EuroEats platform.

Row count: 1,500

Column	Data Type	Key	Description
customer_id	INTEGER	PK	Unique identifier for the customer.
first_name	VARCHAR(50)	—	Customer's first name.
last_name	VARCHAR(50)	—	Customer's last name.
age	INTEGER	—	Customer's age in years (18-75).
gender	VARCHAR(10)	—	Female / Male / Other.
country	VARCHAR(50)	—	One of the 15 EuroEats countries.
city	VARCHAR(50)	—	City within that country.
registration_date	DATE	—	Date the customer created their account.
customer_segment	VARCHAR(20)	—	Budget / Regular / Premium.
loyalty_status	VARCHAR(20)	—	Bronze / Silver / Gold / Platinum, derived from tenure and segment.

restaurants

Partner restaurants listed on the EuroEats platform.

Row count: 120

Column	Data Type	Key	Description
restaurant_id	INTEGER	PK	Unique identifier for the restaurant.
restaurant_name	VARCHAR(100)	—	Display name of the restaurant.
country	VARCHAR(50)	—	Restaurant's country.
city	VARCHAR(50)	—	Restaurant's city.
cuisine_type	VARCHAR(30)	—	One of 16 cuisines (Italian, Indian, Chinese, Japanese, Mexican, Greek, Turkish, French, Spanish, Burgers, Pizza, Vegan, Bakery, Thai, Mediterranean, Local cuisine).
price_level	INTEGER	—	1 (cheap) to 4 (expensive); skews higher in capitals and higher cost-of-living countries.
restaurant_rating	DECIMAL(2,1)	—	Average customer rating, 1-5.
average_preparation_time	INTEGER	—	Typical kitchen prep time in minutes; varies by cuisine.
restaurant_join_date	DATE	—	Date the restaurant joined the platform.
restaurant_size	VARCHAR(10)	—	Small / Medium / Large.
average_daily_orders	INTEGER	—	Typical daily order volume.

menu_items

The dishes and drinks each restaurant sells.

Row count: 1,500

Column	Data Type	Key	Description
item_id	INTEGER	PK	Unique identifier for the menu item.
restaurant_id	INTEGER	FK → restaurants.restaurant_id	Owning restaurant.
item_name	VARCHAR(100)	—	Dish or drink name.
category	VARCHAR(20)	—	Starter / Main / Dessert / Drink / Side.
price_eur	DECIMAL(6,2)	—	Price in EUR, scaled by country cost-of-living and restaurant price level.
preparation_time_minutes	INTEGER	—	Kitchen time for this specific item.
calories	INTEGER	—	Estimated calorie count.
vegetarian	INTEGER (0/1)	—	1 = vegetarian; probability depends on cuisine.
popularity_score	DECIMAL(5,1)	—	0-100 popularity index; anti-correlated with price.

drivers

The independent delivery workforce.

Row count: 350

Column	Data Type	Key	Description
driver_id	INTEGER	PK	Unique identifier for the driver.
first_name	VARCHAR(50)	—	Driver's first name.
last_name	VARCHAR(50)	—	Driver's last name.
country	VARCHAR(50)	—	Driver's home country.
city	VARCHAR(50)	—	Driver's home city.
vehicle_type	VARCHAR(20)	—	Bicycle / E-bike / Scooter / Motorcycle / Car.
years_experience	DECIMAL(4,1)	—	Years delivering on the platform (0-12).
driver_rating	DECIMAL(3,2)	—	1-5, correlated with experience.
completed_deliveries	INTEGER	—	Career delivery count, correlated with experience.
employment_type	VARCHAR(20)	—	Full-time / Part-time / Freelance.
average_speed_kmh	DECIMAL(5,1)	—	Typical travel speed; depends on vehicle type.

orders

Every order placed on the platform, with pricing and status.

Row count: 4,500

Column	Data Type	Key	Description
order_id	INTEGER	PK	Unique identifier for the order.
customer_id	INTEGER	FK → customers.customer_id	Ordering customer.
restaurant_id	INTEGER	FK → restaurants.restaurant_id	Restaurant fulfilling the order (mostly same city as customer).
order_datetime	DATETIME	—	Order timestamp, weighted toward lunch/dinner hours and Fri/Sat; always on or after the customer's registration date.
number_of_items	INTEGER	—	Total item quantity in the order.
subtotal_eur	DECIMAL(8,2)	—	Sum of order_items (unit price x qty minus item discount).
delivery_fee_eur	DECIMAL(6,2)	—	Fee, higher in high cost-of-living countries, slightly reduced for large orders.
discount_eur	DECIMAL(6,2)	—	Promo discount, present on roughly 18% of orders.
total_amount_eur	DECIMAL(8,2)	—	subtotal + delivery_fee - discount.
payment_method	VARCHAR(20)	—	Credit Card / Debit Card / PayPal / Apple Pay / Google Pay / Cash.
order_status	VARCHAR(20)	—	Delivered (90%) / Cancelled (6%) / Refunded (4%).

order_items

The individual line items within each order.

Row count: 4,697

Column	Data Type	Key	Description
order_item_id	INTEGER	PK	Unique identifier for the order line item.
order_id	INTEGER	FK → orders.order_id	Parent order.
item_id	INTEGER	FK → menu_items.item_id	Ordered menu item (from the order's restaurant).
quantity	INTEGER	—	Quantity ordered (1-3).
unit_price_eur	DECIMAL(6,2)	—	Menu price at time of order (small noise applied).
item_discount_eur	DECIMAL(6,2)	—	Occasional per-item discount (roughly 8% of lines).

deliveries

Trip-level detail for orders that were dispatched to a driver. Core table for delivery-time analysis.

Row count: 1,000

Column	Data Type	Key	Description
delivery_id	INTEGER	PK	Unique identifier for the delivery.
order_id	INTEGER	FK → orders.order_id , UQ	One delivery per order.
driver_id	INTEGER	FK → drivers.driver_id	Assigned driver (usually same city as restaurant).
distance_km	DECIMAL(5,2)	—	Restaurant-to-customer distance; shorter within the same city.
traffic_level	VARCHAR(10)	—	Low / Medium / High; higher at peak hours and in capitals.
weather_condition	VARCHAR(10)	—	Clear / Cloudy / Rain / Snow; driven by the row's own temperature.
temperature_c	DECIMAL(4,1)	—	Derived from country/season climate profile plus noise.
pickup_delay_minutes	DECIMAL(5,1)	—	Delay before the driver picks up the order; rises with traffic.
restaurant_wait_minutes	DECIMAL(5,1)	—	Kitchen wait; depends on restaurant's base prep time, order size, and workload at that hour.
estimated_delivery_minutes	DECIMAL(5,1)	—	Platform's ETA shown to the customer.
actual_delivery_minutes	DECIMAL(5,1)	—	Actual delivery duration in minutes (roughly 8-130).
delivery_status	VARCHAR(15)	—	Delivered / Delayed (>75 min) / Cancelled (rare).

payments

Payment transactions tied to orders.

Row count: 800

Column	Data Type	Key	Description
payment_id	INTEGER	PK	Unique identifier for the payment.
order_id	INTEGER	FK → orders.order_id, UQ	Paid order (cash orders excluded).
payment_datetime	DATETIME	—	Timestamp shortly after order_datetime.
payment_method	VARCHAR(20)	—	Matches the order's payment method.
amount_eur	DECIMAL(8,2)	—	Equals the order's total_amount_eur.
payment_status	VARCHAR(15)	—	Completed / Failed (roughly 2%) / Refunded (matches refunded orders).
currency	VARCHAR(3)	—	Always 'EUR' (analytical currency for the dataset).

reviews

Customer feedback left after an order.

Row count: 500

Column	Data Type	Key	Description
review_id	INTEGER	PK	Unique identifier for the review.
order_id	INTEGER	FK → orders.order_id, UQ	Reviewed order (delivered orders only).
customer_id	INTEGER	FK → customers.customer_id	Reviewing customer.
rating	INTEGER	—	1-5, weighted average of delivery_rating and food_rating.
review_datetime	DATETIME	—	Timestamp, 1-3 days after the order.
delivery_rating	INTEGER	—	1-5; lower for slower deliveries.
food_rating	INTEGER	—	1-5; correlated with the restaurant's overall rating.
review_sentiment	VARCHAR(10)	—	Positive (rating >=4) / Neutral (3) / Negative (<=2).