

# Cukeddoctor Documentation

Version 1.1.1-SNAPSHOT

# Table of Contents

|  |    |
|--|----|
| <b>1. Introduction</b>                                 | 1  |
| <b>2. Features</b>                                     | 2  |
| <b>2.1. Cukedoctor Converter</b>                       | 2  |
| 2.1.1. Convert features test output into documentation | 2  |
| <b>2.2. Ordering</b>                                   | 5  |
| 2.2.1. Default ordering                                | 5  |
| 2.2.2. Custom ordering                                 | 7  |
| <b>2.3. Enrich features</b>                            | 9  |
| 2.3.1. DocSting enrichment                             | 9  |
| 2.3.2. Comments enrichment                             | 12 |
| <b>2.4. Documentation introduction chapter</b>         | 14 |
| 2.4.1. Introduction chapter in classpath               | 15 |

# Chapter 1. Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and AsciiDoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

- Living documentation should be readable and highlight your software features;
  - Most bdd tools generate reports and not a truly documentation.
- Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of [cucumber json output](#) files;
  - In the 'worst case' to [enhance](#) your documentation you will need to know a bit of [asciidoc markup](#).

In the subsequent chapters you will see a documentation which is generated by the output of [Cukedoctor's BDD tests](#), **a real bdd living documentation**.

# Chapter 2. Features

## 2.1. Cukedoctor Converter

In order to have awesome *living documentation*

As a bdd developer

I want to use **Cukedoctor** to convert my cucumber test results into **readable** living documentation.

### 2.1.1. Convert features test output into documentation

## Given

The following two features: 🍌 (396ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

## When

I convert their json test output using cukedoctoer converter 🍌 (01s 082ms)

To generate cucumber .json output files just execute your *BDD* tests with **json** formatter, example:



```
@RunWith(Cucumber.class)
@CucumberOptions(plugin = {"json:target/cucumber.json"})
)
```



**plugin** option replaced **format** option which was deprecated in newer cucumber versions.

## Then

I should have awesome living documentation 👍 (001ms)

# Documentation

# Summary

| Scenarios                         |        |       | Steps  |        |         |         |           |         |       | Features: 2 |        |
|-----------------------------------|--------|-------|--------|--------|---------|---------|-----------|---------|-------|-------------|--------|
| Passed                            | Failed | Total | Passed | Failed | Skipped | Pending | Undefined | Missing | Total | Duration    | Status |
| Scenario 1: Feature 1 & Feature 2 |        |       |        |        |         |         |           |         |       |             |        |
| 1                                 | 0      | 1     | 1      | 0      | 0       | 0       | 0         | 0       | 1     | 647ms       | passed |
| Scenario 2: Feature 1 & Feature 2 |        |       |        |        |         |         |           |         |       |             |        |
| 1                                 | 0      | 1     | 1      | 0      | 0       | 0       | 0         | 0       | 1     | 000ms       | passed |
| Totals                            |        |       |        |        |         |         |           |         |       |             |        |
| 2                                 | 0      | 2     | 2      | 0      | 0       | 0       | 0         | 0       | 2     | 647ms       |        |

## Features

# Feature1

### Scenario: Scenario feature 1

**Given**

scenario step 👍 (647ms)

## Feature2

### Scenario: Scenario feature 2

**Given**

scenario step 👍 (000ms)

## 2.2. Ordering

In order to have features ordered in living documentation  
As a bdd developer  
I want to control the order of features in my documentation

### 2.2.1. Default ordering

## Given

The following two features: 🍌 (000ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

## When

I convert them using default order 🍌 (032ms)

## Then



Features should be ordered by name in resulting documentation 🍌 (000ms)

## Feature1

### Scenario: Scenario feature 1

#### Given

scenario step 🍌 (647ms)

## Feature2

### Scenario: Scenario feature 2

#### Given

scenario step 🍌 (000ms)

### 2.2.2. Custom ordering

## Given

The following two features: 🇮🇸 (000ms)

#order: 2

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

#order: 1

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step



Ordering is done using feature comment '**#order:**'

## When

I convert them using comment order 🇮🇸 (025ms)

## Then

Features should be ordered respecting order comment 🍌 (000ms)

## Feature2

### Scenario: Scenario feature 2

#### Given

scenario step 🍌 (000ms)

## Feature1

### Scenario: Scenario feature 1

#### Given

scenario step 🍌 (313ms)

## 2.3. Enrich features

In order to have awesome *living documentation*

As a bdd developer

I want to render asciidoc markup inside my features.

### 2.3.1. DocSting enrichment

Asciidoc markup can be used in feature **DocStrings**. To do so you need to enable it by using **[cukector-dicrete]** comment on the feature.

## Given

The following two features: 🍌 (000ms)

Feature: Enrich feature

Scenario: Render source code

```
# cukedocter-discrete
Given the following source code in docstrings
"""
[source, java]
-----
public int sum(int x, int y){
    int result = x + y;
    return result; (1)
}
-----
<1> We can have callouts in living documentation
"""
```

Scenario: Render table

```
# cukedocter-discrete
Given the following table
"""
|===

| Cell in column 1, row 1 | Cell in column 2, row 1
| Cell in column 1, row 2 | Cell in column 2, row 2
| Cell in column 1, row 3 | Cell in column 2, row 3

|===
"""
```

## When

I convert docstring enriched json output using cukedocter converter 🍌 (047ms)

## Then

## Discrete class feature

## Scenario: Render source code

**Given**

the following source code 👍 (267ms)

```
public int sum(int x, int y){
    int result = x + y;
    return result; ①
}
```

[illegible]

## Scenario: Render table

### Given

the following table 👍 (000ms)

|                         |                         |
|-------------------------|-------------------------|
| Cell in column 1, row 1 | Cell in column 2, row 1 |
| Cell in column 1, row 2 | Cell in column 2, row 2 |
| Cell in column 1, row 3 | Cell in column 2, row 3 |

### 2.3.2. Comments enrichment

AsciiDoc markup can be used in feature comments. To do so you need to surround asciidoc markup by **curly brackets**;

## Given

The following feature with asciidoc markup in comments: 🍌 (000ms)

Feature: Calculator

Scenario: Adding numbers

You can *\*asciidoc markup\** in *\_feature\_* *#description#*.

NOTE: This is a very important feature!

*#{IMPORTANT: AsciiDoc markup inside *\*steps\** must be surrounded by *\*curly brackets\*.*}*

Given I have numbers 1 and 2

*# {NOTE: Steps comments are placed *\*before\** each steps so this comment is for the *\*WHEN\** step.}*

When I sum the numbers

*# {\* this is a list of itens inside a feature step}*

*# {\* there is no multiline comment in gherkin}*

*# {\*\* second level list item}*

Then I should have 3 as result

## When

I convert enriched feature json output using cukedocto 🍌 (036ms)

## Then

## Calculator

### Scenario: Adding numbers

You can use **asciidoc markup** in *feature* description.



This is a very important feature!

#### Given

I have numbers 1 and 2 👍 (114ms)



AsciiDoc markup inside **steps** must be surrounded by curly brackets.

#### When

I sum the numbers 👍 (000ms)



Steps comments are placed **before** each steps so this comment is for the **WHEN** step.

#### Then

I should have 3 as result 👍 (001ms)

- this is a list of itens inside a feature step
- there is no multiline comment in gherkin
  - second level list item

## 2.4. Documentation introduction chapter



In order to have an introduction chapter in my documentation  
As a bdd developer  
I want to be able to provide an asciidoc based document which  
introduces my software.

#### **2.4.1. Introduction chapter in classpath**

## Given

The following two features: 🍌 (000ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

## And

The following asciidoc document is on your application classpath 👍 (040ms)

# Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and Asciidoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

- Living documentation should be readable and highlight your software features;
  - Most bdd tools generate reports and not a truly documentation.
- Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of [cucumber json output](#) files;
  - In the 'worst case' to  
&amp;&amp;&amp;&amp;&lt;&amp;&amp;&amp;&amp;&lt;Enrich-  
features,enhance&amp;&amp;&amp;&amp;&gt;&amp;&amp;&amp;&amp;&gt;  
; your documentation you will need to know a bit of [asciidoc markup](#).



The introduction file must be named **intro-chapter.adoc** and can be in any package of your application,



By default Cukedoctor will look into application folders but you can make Cukedoctor look into external folder by setting the following system property:

```
System.setProperty("INTRO_CHAPTER_DIR", "/home/some/external/folder");
```

## When

Bdd tests results are converted into documentation by Cukedoctor 👍 (000ms)

## Then

Resulting documentation should have the provided introduction chapter 👍 (000ms)

# Documentation

## Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and AsciiDoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

- Living documentation should be readable and highlight your software features;
  - Most bdd tools generate reports and not a truly documentation.
- Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of [cucumber json output](#) files;
  - In the 'worst case' to  
&amp;amp;amp;amp;lt;&amp;amp;amp;amp;lt;Enrich-  
features,enhance&amp;amp;amp;amp;gt;&amp;amp;amp;amp;gt;  
; your documentation you will need to know a bit of [asciidoc markup](#).

## Summary

| Scenarios  |        |       | Steps  |        |         |         |           |         |       | Features: 2 |        |
|--|--------|-------|--------|--------|---------|---------|-----------|---------|-------|-------------|--------|
| Passed   | Failed | Total | Passed | Failed | Skipped | Pending | Undefined | Missing | Total | Duration    | Status |
| &amp;amp;amp;amp;lt;&amp;amp;amp;amp;lt;Feature1&amp;amp;amp;amp;gt;&amp;amp;amp;amp;gt; |        |       |        |        |         |         |           |         |       |             |        |
| 1  | 0      | 1     | 1      | 0      | 0       | 0       | 0         | 0       | 1     | 647ms       | passed |
| &amp;amp;amp;amp;lt;&amp;amp;amp;amp;lt;Feature2&amp;amp;amp;amp;gt;&amp;amp;amp;amp;gt; |        |       |        |        |         |         |           |         |       |             |        |
| 1  | 0      | 1     | 1      | 0      | 0       | 0       | 0         | 0       | 1     | 000ms       | passed |
| Totals   |        |       |        |        |         |         |           |         |       |             |        |
| 2  | 0      | 2     | 2      | 0      | 0       | 0       | 0         | 0       | 2     | 647ms       |        |

## Features

### Feature1

## Scenario: Scenario feature 1

### Given

scenario step 🍌 (647ms)

## Feature2

## Scenario: Scenario feature 2

### Given

scenario step 🍌 (000ms)