



OOP using Java

Trainer: Mr. Rohan Paramane



Arrays

- Array is a sequential/linear container/collection which is used to store elements of same type in continuous memory location.
- If we want to access elements of array then we should use integer index.
- Array index always begins with 0.

- **Advantage Of Array**

1. We can access elements of array randomly.

- **Disadvantage Of Array**

1. We can not resize array at runtime.
2. It requires continuous memory.
3. Insertion and removal of element from array is a time consuming job
4. Using assignment operator, we can not copy array into another array.
5. Compiler do not check array bounds(min and max index).



Array In Java


- Array is a reference type in Java. In other words, to create instance of array, new operator is required. It means that array instance get space on heap.
- There are 3 types of array in Java:
 1. Single dimensional Array
 2. Multidimensional Array
 3. Ragged Array
- Using illegal index, if we try to access elements of array then JVM throws `ArrayIndexOutOfBoundsException`.
- If we try to store incorrect type of object into array then JVM throws `ArrayStoreException`.
- If we try to negative value for array size then JVM throws `NegativeArraySizeException`.




Single Dimensional Array

Reference declaration	Instantiation
<pre>int arr[]; //OK int [arr]; //NOT OK int[] arr; //OK</pre>	<pre>int[] arr1 = new int[3]; //or int size = 3; int[] arr2 = new int[size];</pre>
<pre>int[] arr1 = new int[-3]; //NegativeArraySizeException //or int size = -3; int[] arr2 = new int[size]; //NegativeArraySizeException</pre>	
Initialization	
<pre>int[] arr = new int[size]{ 10, 20, 30 }; //Not OK int[] arr = new int[]{ 10, 20, 30 }; //OK int[] arr = { 10, 20, 30 }; //OK</pre>	

```
int[] arr = new int[3];
```



```
int[] arr = new int[]{10,20,30};
```



Array Of Primitive Values

```
public class Program {
```

```
    public static void main(String[] args) {
```

```
        boolean[] arr = new boolean[ 3 ]; //contains all false
```

```
        int[] arr = new int[ 3 ]; //contains all 0
```

```
        double[] arr = new double[ 3 ]; //contains all 0.0
```




```
    }
```

```
}
```

```
boolean[] arr = new boolean[3];
```

```
int[] arr = new int[3];
```

```
double[] arr = new double[3];
```




If we create array of primitive values then it's default value depends of default value of data type.



Array Of References


```
public class Program {  
    public static void main(String[] args) {  
        Date[] arr = new Date[ 3 ]; //Contains all null  
    }  
}
```



If we create an array of references then by default it contains null.



Array of reference and instance



Array Of Instances


- Let us see how to create array of instances of non primitive type

```
public class Program {  
    public static void main(String[] args) {  
        Date[] arr = new Date[ 3 ];  
        arr[ 0 ] = new Date( );  
        arr[ 1 ] = new Date( );  
        arr[ 2 ] = new Date( );  
    }  
}
```

//or

```
public static void main(String[] args) {  
    Date[] arr = new Date[ 3 ];  
    for( int index = 0; index < arr.length; ++ index )  
        arr[ index ] = new Date( );  
}
```

```
Date[] arr = new Date[ 3 ];  
arr[ 0 ] = new Date( );  
arr[ 1 ] = new Date( );  
arr[ 2 ] = new Date( );
```



[Array Of Instances]




Multi Dimensional Array

- Array of elements where each element is array of same column size is called as multi dimensional array.

Reference declaration:	Array Creation:
<pre>int arr[][]; //OK int []arr[] //OK int[][] arr; //OK</pre>	<pre>int[][] arr = new int[2][3];</pre>
Initialization	
<pre>int[][] arr = new int[][]{{10,20,30},{40,50,60}}; //OK int[][] arr = { {10,20,30}, {40,50,60} }; //OK</pre>	

+ Multi Dimensional Array




Ragged Array

- A multidimensional array where column size of every array is different.

Reference declaration	Array creation
<pre>int arr[][]; int []arr[]; int[][] arr;</pre>	<pre>int[][] arr = new int[3][]; arr[0] = new int[2]; arr[1] = new int[3]; arr[2] = new int[5];</pre>
Array Initialization	
<pre>int[][] arr = new int[3][]; arr[0] = new int[]{ 10, 20 }; arr[1] = new int[]{ 10, 20, 30 }; arr[2] = new int[]{ 10, 20, 30, 40, 50 };</pre>	
<pre>int[][] arr = { { 1, 2 }, { 1, 2, 3 }, {1,2,3,4,5}};</pre>	

+ Ragged Array



Variable Arity/Argument Method

```
private static sum( int... arguments ){
    int result = 0;
    for( int element : arguments )
        result = result + element;
    return result;
}

public static void main(String[] args) {
    int result = 0;
    result = Program.sum( );           //OK
    result = Program.sum( 10, 20, 30 ); //OK
    result = Program.sum( 10, 20, 30, 40, 50 ); //OK
    result = Program.sum( 10, 20, 30, 40, 50, 60, 70, 80, 90, 100 ); //OK
}
```





Thank you!

Rohan Paramane

rohan.paramane@sunbeaminfo.com

