

Spring Framework

Servlet-API

MVC Architecture : Manual

Architecture is implemented strictly, disciplined way

remove lot of Boiler-plate code

abstract the low level complexity

Focus more on business logic

Most popular frameworks to develop java application

J2EE : Java 2 Enterprise Edition : Framework to develop web app using java

Complex in nature

- # lots of deployment descriptor

- # lots of interface, abstract classes needs to be created to expose a single service

- # productivity reduces, reduces efficiency

Rod Johnson


=> Object Factory : Responsible for creating and managing object


Increased the Productivity


Increased the efficiency

1. Object Factory
2. Highly Modular
3. POJOs

Spring Framework







Object Factory | Bean Factory | Application Context

Provided by Spring - Core Module

A Custom Configuration needs to be provided to define the behavior of Object Factory

XML Based Configuration (Legacy)

Annotation Based Configuration (Modern)

Pure Java Based Configuration (Modern)

Std Spring Framework :

bundle of few Modules

=> Core

=> Spring-web-mvc

=> Spring AOP (proxy)

Bean Factory works on two key principals

1. IoC : Inversion of Control
2. DI : Dependency Injection

IoC : Outsourcing the (control of) creation and management of Object

XML Based Config :


XML file + certain dependencies for support of additional spring tags


BEAN : Container(Object Factory) managed Object

Multiple classes provided for Bean Factory

way of config (XML or java)

env for which bean factory (simple java, web app)





Need the BEna factory to inject Fortune Service instance into EmailService

Constructor Based DI

Setter BAsed DI

```
<bean id="personal"
class="com.wf.training.spring.factory.service.PersonalFortune"></bean>
  <bean id="professional"
    <!-- Injecting Dependency -->

    <!-- Constructor Based -->
    <bean id="emailservice"
class="com.wf.training.spring.factory.service.EmailService">
  <constructor-arg ref="personal"/>
</bean>
```

A dashed arrow points from the `<bean id="personal">` line to the `<constructor-arg ref="personal"/>` line, indicating that the 'personal' bean is injected into the 'emailservice' bean via its constructor.

Injecting the literal values :

Delegate them to a text file (properties files)

literal values as key-value pair

need to specify property file in config

Bean Management :

1. Life cycle

2. Scope

=> Scope : Accessibility of bean

by default scope : Singleton : Single instance will be created

: Prototype : Diff each time

request

session : Web based

application

Life Cycle of Bean

Bean Container (Factory) is created

Instantiates the bean

Injects the dependency

Follows internal processing

Life cycle Hook (method)--init

Platform to prepare the bean logically before it is made available

Bean is exposed to be consumed

Container is terminated...

Life cycle Hook (method)--destroy

Platform to perform clean-up operations

Bean is destroyed

Prototype : BEan container does not maintain life cycle..

Annotation based config

xml file : path reference

Creating the bean

@Component :

Any class decorated with @Component will be initiated by bean factory

By default the class name itself becomes the id , first character being small case...

DI using annotation

1. Constructor
2. Setter
3. Field

@Autowired : search for bean, if found, inject it

Scope : @Scope

Life cycle hook methods : Annotations

Pure Java Based Config :

xml file will be replaced by Java class

Pure Java Config :

Programmatically configure Bean Factory

before 10 am or after 5 pm : personal fortune

else : professional fortune

Expose the bean

@Component

Class level


@Bean

Method level

Spring web-mvc module : MVC architecture
uses Servlet-API : in an abstract
POJO

Controller : Servlet
View : JSP
Model : Data Structure

Controller : POJOs (Servlet capabilities)
View : Spring supports multiple view templates
 default : JSP + JSTL
 Thymeleaf
 Mustache
 FreeMarker
 Velocity
 Tiles
Model : Data Structure/Data Container



1. Need to register the DispatcherServlet
2. COnfig to target all requests to DS

web.xml (servlet-api)

Spring Based Config : (XML)

- + Bean Factory Config
- + web mvc config

View Resolver :

eg : "index" (string) name of view page (controller)

prefix : location

suffix : View Template (extension)

<servlet-name>-servlet.xml


eg: dispatcher-servlet.xml

```
<property name="prefix" value="/WEB-INF/views/" />
<property name="suffix" value=".jsp" />
```

/WEB-INF/views/index.jsp

Custom Resources

1. Controller : POJO, registered with Handler Mapper



identifying the HTTP Verb

Mapping will take place using getter/setter only

Maven Project

1. archetype : web
2. Add the Server Runtime Library
3. convert java 1.5 to 1.8
4. Adding dependencies
 1. spring framework
 2. servlet for DS
 3. jsp+jstl

Pure Java Config

web.xml (servlet-api) ~ add a maven plugin
~ Java Class

dispatcher-servlet.xml (spring) ~ Java class

Java Class for web.xml

- # Registered DS (auto - inherit inbuilt class)

- # Mapped the url

Java Class for Spring config

- # component scanning path

- # exposed a bean of ViewResolver

Form handling spring-way : Forms are critical
Custom Tag Library : JSP

Need to add the reference of custom tag library

Spring forms : map the forms (UI) with java classes
control the form behavior (UI) through java classes

Validation : Validator API : Hibernate-Validator (dependency)

Client - Side Validation : submission takes place when all constraint are satisfied
HTML5 attribute + JS

Server-Side Validation :

Absolute URL : fetch the context path : predeclared variable in JSP to access the context path

Annotation : interface(skeleton) + implementation class (logic)

@EmployeeCode

Rule

1. Retention policy : compile/runtime

compile : @Override/@FunctionalInterface

runtime : validation

2. Target : where that annotation can be used


method, class, field...


Spring - Security Module
authentication(valid) + authorization (role based)

Dependency:

spring-security-web
spring-security-config
spring-security-taglibs

Spring Security Module





1. Add Dependency
2. a class to activate security filter
3. a class to add config

default security (all resources are secured) :

provide an inbuilt login form

3 authentication ways

1. httpBasic : not recommended
2. formLogin (inbuilt)
3. formLogin (custom)

form : spring-form


security over CSRF attack

spring security for every form , will pass a security token, while submission same token needed to sent back, checked by security filter

Every form must be spring-form

Custom login (spring-form)

```
# login : username
# password : password
# method : POST
```



taglib of security

1. get some info about logged in user