

Java 8

Classical : Imperative

How

Object mutability

Java 8 : Declarative Style

What we want

Object immutability

Interface:

default method (definition)

static method (definition)

collection api

interface (10 functionalities + 2)
stream

Object Oriented approach : interface

Functional Interface :

Contain only one abstract method

might have static , default method in any count

Lambda:

anonymous function

no method param type, return type

not be encapsulated in any class

can be assigned to a variable of functional interface

```
() -> <single line>
```

```
()->{  
    // multi line  
}
```

```
(msg)->{}
```

```
msg -> {}
```

```
(a,b) -> {}
```

```
(a,b)->{  
    int sum = a+b;  
    return sum;  
}
```

```
(a,b)-> a+b; // by default associated with return statement
```

the method signature of the only abstract method of Functional interface must match with method signature of lambda expression

java.util.function

functional interface containing some very common prototype method

4 categories

Consumer

Predicate

Function

Supplier

Consumer :

void accept(<T>)

Predicate

boolean test(<T>)

Function

<R> apply(<T>);

Supplier

<T> get()

Variants

Consumer : BiConsumer (Generic)

void accept(<T>,<M>)

Primitive type implementation

IntConsumer()

Predicate:


BiPredicate, Primitive type implementation

Function : BiFunction

Functional programming remove overhead of creating objects and loading class files





Conveyer belt



Parallel Processing not to be preferred

1. when an external mutable object is involved
2. when the stream activities involve some inherent complexity





Java EE

Servlet

Java Class

```
class MyServ extends GenericServlet/HttpServlet{
```

```
}
```

GenericServlet : Support only generic Http Verb (Form verbs) get/post

HttpServlet : identifies HTTP Verbs (get,post,put,delete)

identifies intention of http verb

```
class MyServ extends GenericServlet/HttpServlet{  
    <---- lifecycle ----->  
    init (load)  
    service(GenericServlet) (doPost,doGet,doPut,doDelete: HttpServlet) : request/response  
    destroy (unloaded)  
}  
  
service/(doPost,doGet,doPut,doDelete) (HttpServletRequest request,  
                                         HttpServletResponse response){  
  
}
```

Named Core Datatypes of TS

number -1/5.3/200 5~5.0

string 'Hello',"Hello",`Hello`

boolean true/false

Spring

Spring Core

Spring MVC (maven)

Spring Boot

Spring Framework : Servlet technology

CORE

Bean Factory

IoC

DI


AOP


IoC : Outsourcing the creation and management of object

Bean : Java Object managed by container

AOP : Aspect Oriented Programming (Proxy)

Clean, Loosly Coupled, reusable JAva Code






Scope : Singleton (Default)
Prototype

request : single request-response cycle
session : all request-response cycle for a particular user
global : all request-response cycle for all user(web context)

Spring Context does not maintains complete lifecycle of Prototype bean

Servlet Technology being used in Spring MVC framework



Maven:

Dependency Management

Standard folder/file system

build

test

documentation

pom : project object model

all config related to maven activity

web.xml : a must file for servlet config

web.xml : Servlet config

Custom spring servlet config (java):


inbuilt servlet : register that servlet (DispatcherServlet : config)

config code: as per more requirement

controller code (multiple support layers)

model : data structure

views : presentation purpose



View Resolver:

Single View File (jsp)

Modular View File (Tiles)


Multipart response (as downloadable file)

=>What type of responses you want

=>What type of responses your view templates

Spring Boot:

1. Dependency management 2.2



Configuration:

Auto/Easy

=> Curated clubbed up Annotation

=> Added new annotation for custom config

=> property files : add correct key-values pair

=> adding dependency : will activate that feature and auto configure

some default behavior

spring-security (

spring-actuator

spring-devtool

web application

- spring boot web application packaged as jar

- standalone : executed like a simple java

- Tomcat is embedded

Spring boot is self-sufficient for maven tool

- eg : mvn package/test/clean/install

spring boot tool:

- eg: mvnw package/test/clean/install

Spring boot application are by default


not configured to use jsp-jstl view templates

Spring boot is by default configured to use :

thymeleaf


```
> java -jar bootapp.jar server.port=9091
```

InternalResourceViewResolver (



REST-WS

REpresentational State Transfer



1. how to generate a request ?
2. what is format in which data will arrive?

Request, REST :

=>purely the URL

=>Conventions for URL

=>ALL HTTP VERBS (intention)

eg :POST : add some

PUT : edit

SOAP / WSDL : programmatic request

REceiving data:

standard, simple as possible

JSON,XML,HTML,TEXT

Allowed to explore the concept of micro-service architecture

JAX-RS (specification)

Jersey

Restlet

RESTEasy

Apache CXF

Spring :

not a JAX-RS implementation

@RestController

1. does auto : interconversion of JSON<->JAVA (jackson-databind project)
2. DEALS with Request /Response

Request Object



Response Object

header
content
status code

Jackson - databind project :

uses the getter/setter method for interconversion

lombok project

Convention:

Employee

/api/employees	GET	: asking for all employee records (/api/get-all-records)
/api/employees/{id}	GET	: asking for a single emp record with id : {id}
/api/employees	POST	: a record is submitted (add)
/api/employees	PUT	: a record is submitted (update)
/api/employees/{id}	DELETE	: delete a record with id : {id}
/api/employess	DELETE	: a array of id is submitted
/api/employees/{id1}/{id2}	DELETE	

spring-data-rest

Actuators

Microservice architecture

monolith :

Interdependency

Fragile in nature

deployment :

usage of resources


bound to specific technology


team division / management

new team member inclusion

1. does not easily integrate/comply agile

2. CI/CD implementation is a challenge







Spring boot :


Spring / Spring MVC


Most resonable default


Integrates Spring cloud out of the box

















12-factor guideline

Lightweight

Reactive

Stateless

Atomic


Externalized

Consistent

Resilient

Good Citizens

Versioned x.x.x




Spring-Data (persistent API)


: Mysql : JPA


: Mongo-DB impl

=> Lots of pre-built DB interaction

=> Add custom method : implementation provided on the fly
proper naming convention







HTML : STRUCTURE

CSS : PRESENTATION

Javascript : BEHAVIOR

HTML-5

- # backward compatibility
- # Standardized the error handing
- # New Semantics Elements
- # Built-in API
- # audio/video

Semantically correct Structural elements

traditional : <p>,,<div>

article,

section

aside,

header,


footer

OUTLINE ALGORITHM :

Smooth rendering

Assisstive technology

Search EO



Categorization
Metadata
Metadata
Interactive
HEading
Phrasing
Sectioning

API
DOM spec is part of HTML5
Built in APIs (internal activities)
A/V Api
Offline Application API
History API
WEb Protocol API
Drag n Drop API
Geolocation
2D Canvas
Local Storage
Session Storage
Messaging API
Local DB API

CSS

Cascade Style Sheet

SS : presentation rul

Cascading : rule for resolving conflicts with multiple SS applied on same elements

Browser SS

external

internal

inline

Location of style

Heirarchy of HTML

Assembly of properties

selector { property : value}
p{color: #FFFFFF}

element
(ID)
. Class

Cascading rule
Specificity

Bootstrap + JS

BootStrap : mobile first CSS library (device independent)

Grid System : use 5 grid breakpoint

extra small : <567 px : col (auto layout)

small 567-768 col-sm

medium 768-992 col-md

large 992-1200 col-lg

xl > 1200 col-xl

Vanilla JS (Ecma Script)

ES - 5

ES-5 > (external javascript file)

transpilers (babel, traceur)

ES-5

```
graph TD; A[ES-5 > (external javascript file)] -.->|transpilers (babel, traceur)| B[ES-5]
```

Javascript (rich set of library allowed to integrate)

Objects

=> HTML/CSS code (DOM Tree)

=> Browser window

=> history


=> navigation

ES6

JS : making HTML page more dynamic/responsive/interactive

Server based logic --> Client (Outsource)

New Programming constructs



Microsoft - Javascript superset (Typescript)

```
function add(num1, num2){  
    return num1 + num2;  
}
```

named Type
interface/generic

```
add(20,30); 50
```

```
add('20','30'); 2030
```



```
npm
```



```
npm install -g typescript
```

```
var button = document.querySelector("button");  
var input1 = document.getElementById("num1");  
var input2 = document.getElementById("num2");
```

```
function add(num1, num2){  
    return num1 + num2;  
}
```

```
button.addEventListener("click", function(){  
    console.log(add(+input1.value, +input2.value));  
});
```

=>Proper division
=>Management tools



Inter-microservice :

Discovery Server/Client

feign-client

load balancing

externalization :

 config

 security

 single point access

CQRS : Transaction

Event Driven - Messaging API

Fault Tolerance

Tracing

Documentation Swagger

Kubernetes


object : JavaScript objects, types of object


Tuple : fixed size, ordered array

```
class Base{                                enums
    constructor(name : string){
    }
}
```


```
class Derived extends Base{
}
```

```
const der = new Derived("");
```





Modules (Packages)



NodeJS (npm)

to download and install angular CLI

=>npm install -g @angular/cli

Create a new Angular Application

=>ng new <app-name>

All npm :

package.json

npm install

Component :

=> TS class : config

=> presentation : HTML

=> CSS

=> TS class : unit test code

Creating new component

ng generate component <component>

Entry Form : (Add New Product)

<Collection>

List of Product

- 1.. Single Component (New Data Entry, holding the collection, show the list)
2. Two Component (New Data Entry, holding the collection | show the list)
3. Three Component (New Data Entry | holding the collection | show the list)

show the list

show the detail of one product

-> show only image

-> show reviews

-> show purchase (cost + add to cart)

Directives : ngFor

Services : shared resources (functionality/algo/data)

Pipes | Customize/Transform the output

Angular directive :


helps to add simple programmatic constructs directly into HTML
majorly as attributes of existing HTML Components


eg : FOR LOOP Directive


```
{{<var>}}
```


Form

```
<form></form>
```









events : NO HTML EVENTS

events : synthetic events (custom events provided by ANGULAR)

event handling compatible to platform + TS