

Activity: Decrypt an encrypted message

Introduction

In this lab, you'll complete a series of tasks to obtain instructions for decrypting an encrypted file. Encryption of data in use, at rest, and in transit is critical to security functions. You'll use the Linux skills you have learned to uncover the clues needed to decode a classical cipher, restore a file, and reveal a hidden message.

What you'll do

You have multiple tasks in this lab:

- List the contents of a directory
- Read the contents of files
- Use Linux commands to revert a classical cipher back to plaintext
- Decrypt an encrypted file and restore the file to its original state

Activity: Decrypt an encrypted message

1 hourFree

Activity overview

Previously, you learned about cryptography and how encryption and decryption can be used to secure information online. You were also introduced to the Caesar cipher, one of the earliest cryptographic algorithms used to protect people's privacy.

As a security analyst, it's important that you understand the role of encryption to secure data online and that you're familiar with the right security controls to do so.

In this lab activity, you'll be guided through some basic cryptographic activities using Linux commands to decrypt files and reveal hidden messages.

Scenario

In this scenario, all of the files in your home directory have been encrypted. You'll need to use Linux commands to break the Caesar cipher and decrypt the files so that you can read the hidden messages they contain.

Here's how you'll do this task: **First**, you'll explore the contents of the home directory and read the contents of a file. **Next**, you'll find a hidden file and decrypt the Caesar cipher it contains. **Finally**, you'll decrypt the encrypted data file to recover your data and reveal the hidden message.

OK, it's time to decrypt some messages in Linux!

Note: *The lab starts with you logged in as user `analyst`, with your home directory, `/home/analyst`, as the current working directory.*

Start your lab

Before you begin, you can review the instructions for using the Qwiklabs platform under the **Resources** tab in Coursera.

If you haven't already done so, click **Start Lab**. This brings up the terminal so that you can begin completing the tasks!

When you have completed all the tasks, refer to the **End your Lab** section that follows the tasks for information on how to end your lab.

Task 1. Read the contents of a file

The lab starts in your home directory, `/home/analyst`, as the current working directory.

In this task, you need to explore the contents of your home directory and read the contents of a file to get further instructions.

1. Use the `ls` command to list the files in the current working directory.

Two files, `Q1.encrypted` and `README.txt`, and a subdirectory, `caesar`, are listed:

```
Q1.encrypted README.txt caesar
```

The README .txt file contains an important message with instructions you need to follow.

2. Use the cat command to list the contents of the README .txt file.

The message in the README .txt file advises that the caesar subdirectory contains a hidden file.

In the next task, you'll need to find the hidden file and solve the Caesar cipher that protects it. The file contains instructions on how to recover your data.

Click **Check my progress** to verify that you have completed this task correctly.

Read the contents of a file

Check my progress

Task 2. Find a hidden file

In this task, you need to find a hidden file in your home directory and decrypt the Caesar cipher it contains. This task will enable you to complete the next task.

1. First, use the cd command to change to the caesar subdirectory of your home directory:

```
cd caesar
```

Copied!

content_copy

2. Use the `ls -a` command to list all files, including hidden files, in your home directory.

This will display the following output:

```
. .. .leftShift3
```

Hidden files in Linux can be identified by their name starting with a period (.).

3. Use the `cat` command to list the contents of the `.leftShift3` file.

The message in the `.leftShift3` file appears to be scrambled. This is because the data has been encrypted using a Caesar cipher. This cipher can be solved by shifting each alphabet character to the left or right by a fixed number of spaces. In this example, the shift is three letters to the left. Thus "d" stands for "a", and "e" stands for "b".

4. You can decrypt the Caesar cipher in the `.leftshift3` file by using the following command:

```
cat .leftShift3 | tr "d-za-cD-ZA-C" "a-zA-Z"
```

Copied!

content_copy

Note: The `tr` command translates text from one set of characters to another, using a mapping. The first parameter to the `tr` command represents the input set of characters, and the second represents the output set of characters. Hence, if you provide parameters "abcd" and "pqrs", and the input string to the `tr` command is "ac", the output string will be "pr".

In this case, the command `tr "d-za-cD-ZA-C" "a-zA-Z"` translates all the lowercase and uppercase letters in the alphabet back to their original position. The first character set, indicated by "d-za-cD-ZA-C", is translated to the second character set, which is "a-zA-Z".

Note: The output provides you with the command you need to solve the next task! You don't need to copy the command revealed in the output. It will be provided in the next task.

5. Now, return to your home directory before completing the next task:

```
cd ~
```

Copied!

content_copy

Click **Check my progress** to verify that you have completed this task correctly.

Find a hidden file

Check my progress

Task 3. Decrypt a file

Now that you have solved the Caesar cipher, in this task you need to use the command revealed in `.leftshift3` to decrypt a file and recover your data so you can read the message it contains.

1. Use the exact command revealed in the previous task to decrypt the encrypted file:

```
openssl aes-256-cbc -pbkdf2 -a -d -in Q1.encrypted -out Q1.recovered -k ettubrute
```

Copied!

content_copy

Although you don't need to memorize this command, to help you better understand the syntax used, let's break it down.

In this instance, the `openssl` command reverses the encryption of the file with a secure symmetric cipher, as indicated by AES-256-CBC. The `-pbkdf2` option is used to add extra security to the key, and `-a` indicates the desired encoding for the output. The `-d` indicates decrypting, while `-in` specifies the input file and `-out` specifies the output file. The `-k` specifies the password, which in this example is `ettubrute`.

2. Use the `ls` command to list the contents of your current working directory again.

The new file `Q1 . recovered` in the directory listing is the decrypted file and contains a message.

3. Use the `cat` command to list the contents of the `Q1 . recovered` file.

Click **Check my progress** to verify that you have completed this task correctly.

Decrypt a file

Check my progress

Conclusion

Great work! You now have practical experience in using basic Linux Bash shell commands to

- list hidden files,
- decrypt a Caesar cipher, and
- decrypt an encrypted file.

This is an important milestone on your journey towards understanding encryption and decryption.

End your lab

Before you end the lab, make sure you're satisfied that you've completed all the tasks, and follow these steps:

1. Click **End Lab**. A pop-up box will appear. Click **Submit** to confirm that you're done. Ending the lab will remove your access to the Bash shell. You won't be able to access the work you've completed in it again.
2. Another pop-up box will ask you to rate the lab and provide feedback comments. You can complete this if you choose to.
3. Close the browser tab containing the lab to return to your course.
4. Refresh the browser tab for the course to mark the lab as complete.

Exemplar: Decrypt an encrypted message

1 hourFree

Activity overview

Previously, you learned about cryptography and how encryption and decryption can be used to secure information online. You were also introduced to the Caesar cipher, one of the earliest cryptographic algorithms used to protect people's privacy.

As a security analyst, it's important that you understand the role of encryption to secure data online and that you're familiar with the right security controls to do so.

In this lab activity, you'll be guided through some basic cryptographic activities using Linux commands to decrypt files and reveal hidden messages.

Scenario

In this scenario, all of the files in your home directory have been encrypted. You'll need to use Linux commands to break the Caesar cipher and decrypt the files so that you can read the hidden messages they contain.

Here's how you'll do this task: **First**, you'll explore the contents of the home directory and read the contents of a file. **Next**, you'll find a hidden file and decrypt the Caesar cipher it contains. **Finally**, you'll decrypt the encrypted data file to recover your data and reveal the hidden message.

OK, it's time to decrypt some messages in Linux!

Note: *The lab starts with you logged in as user `analyst`, with your home directory, `/home/analyst`, as the current working directory.*

Start your lab

Before you begin, you can review the instructions for using the Qwiklabs platform under the **Resources** tab in Coursera.

If you haven't already done so, click **Start Lab**. This brings up the terminal so that you can begin completing the tasks!

When you have completed all the tasks, refer to the **End your Lab** section that follows the tasks for information on how to end your lab.

Task 1. Read the contents of a file

The lab starts in your home directory, `/home/analyst`, as the current working directory.

In this task, you need to explore the contents of your home directory and read the contents of a file to get further instructions.

1. Use the `ls` command to list the files in the current working directory.

The command to complete this step:

```
ls /home/analyst
```

Copied!

content_copy

Two files, `Q1.encrypted` and `README.txt`, and a subdirectory, `caesar`, are listed:

```
Q1.encrypted README.txt caesar
```

The `README.txt` file contains an important message with instructions you need to follow.

2. Use the `cat` command to list the contents of the `README.txt` file.

The command to complete this step:

```
cat README.txt
```

Copied!

content_copy

This will display the following output:

```
Hello,  
All of your data has been encrypted. To recover your data, you will need  
to solve a cipher. To get started look for a hidden file in the caesar  
subdirectory.
```

The message in the README.txt file advises that the caesar subdirectory contains a hidden file.

In the next task, you'll need to find the hidden file and solve the Caesar cipher that protects it. The file contains instructions on how to recover your data.

Click **Check my progress** to verify that you have completed this task correctly.

Read the contents of a file

Check my progress

Task 2. Find a hidden file

In this task, you need to find a hidden file in your home directory and decrypt the Caesar cipher it contains. This task will enable you to complete the next task.

1. First, use the `cd` command to change to the `caesar` subdirectory of your home directory:

```
cd caesar
```

Copied!

content_copy

2. Use the `ls -a` command to list all files, including hidden files, in your home directory.

The command to complete this step:

```
ls -a
```

Copied!

content_copy

This will display the following output:

```
. .. .leftShift3
```

Hidden files in Linux can be identified by their name starting with a period (.).

3. Use the `cat` command to list the contents of the `.leftShift3` file.

The command to complete this step:

```
cat .leftShift3
```

Copied!

content_copy

The message in the `.leftShift3` file appears to be scrambled. This is because the data has been encrypted using a Caesar cipher. This cipher can be solved by shifting each alphabet character to the left or right by a fixed number of spaces. In this example, the shift is three letters to the left. Thus "d" stands for "a", and "e" stands for "b".

4. You can decrypt the Caesar cipher in the `.leftshift3` file by using the following command:

```
cat .leftShift3 | tr "d-za-cD-ZA-C" "a-zA-Z"
```

Copied!

content_copy

Note: The `tr` command translates text from one set of characters to another, using a mapping. The first parameter to the `tr` command represents the input set of characters, and the second represents the output set of characters. Hence, if you provide parameters "abcd" and "pqrs", and the input string to the `tr` command is "ac", the output string will be "pr".

This will display the following output:

In order to recover your files you will need to enter the following command:

```
openssl aes-256-cbc -pbkdf2 -a -d -in Q1.encrypted -out Q1.recovered -k  
ettubrute
```

In this case, the command `tr "d-za-cD-ZA-C" "a-zA-Z"` translates all the lowercase and uppercase letters in the alphabet back to their original position. The first character set, indicated by "d-za-cD-ZA-C", is translated to the second character set, which is "a-zA-Z".

Note: The output provides you with the command you need to solve the next task!

You don't need to copy the command revealed in the output. It will be provided in the next task.

5. Now, return to your home directory before completing the next task:

```
cd ~
```

Copied!

content_copy

Click **Check my progress** to verify that you have completed this task correctly.

Find a hidden file

Check my progress

Task 3. Decrypt a file

Now that you have solved the Caesar cipher, in this task you need to use the command revealed in `.leftshift3` to decrypt a file and recover your data so you can read the message it contains.

1. Use the exact command revealed in the previous task to decrypt the encrypted file:

```
openssl aes-256-cbc -pbkdf2 -a -d -in Q1.encrypted -out Q1.recovered -k  
ettubrute
```

Copied!

content_copy

Although you don't need to memorize this command, to help you better understand the syntax used, let's break it down.

In this instance, the `openssl` command reverses the encryption of the file with a secure symmetric cipher, as indicated by `AES-256-CBC`. The `-pbkdf2` option is used to add extra security to the key, and `-a` indicates the desired encoding for the output. The `-d` indicates decrypting, while `-in` specifies the input file and `-out` specifies the output file. The `-k` specifies the password, which in this example is `ettubrute`.

2. Use the `ls` command to list the contents of your current working directory again.

The command to complete this step:

`ls`

Copied!

content_copy

The new file `Q1.recovered` in the directory listing is the decrypted file and contains a message.

3. Use the `cat` command to list the contents of the `Q1.recovered` file.

The command to complete this step:

`cat Q1.recovered`

Copied!

content_copy

This will display the following output:

```
If you are able to read this, then you have successfully decrypted the
classic cipher text. You recovered the encryption key that was used to
encrypt this file. Great work!
```

Click **Check my progress** to verify that you have completed this task correctly.

Decrypt a file

Check my progress

Conclusion

Great work! You now have practical experience in using basic Linux Bash shell commands to

- list hidden files,
- decrypt a Caesar cipher, and
- decrypt an encrypted file.

This is an important milestone on your journey towards understanding encryption and decryption.

End your lab

Before you end the lab, make sure you're satisfied that you've completed all the tasks, and follow these steps:

1. Click **End Lab**. A pop-up box will appear. Click **Submit** to confirm that you're done.
Ending the lab will remove your access to the Bash shell. You won't be able to access the work you've completed in it again.
2. Another pop-up box will ask you to rate the lab and provide feedback comments.
You can complete this if you choose to.
3. Close the browser tab containing the lab to return to your course.
4. Refresh the browser tab for the course to mark the lab as complete.