IMPLEMENTATION OF BOOLEAN LOGIC IN ARM

Valmeekam Navya

FWC22039

January 9, 2023

Contents

1 BCD to GRAY Conversion 2 Implementation 3 Karnaugh Map 4 Setup 4.1 The steps for implementation: 2

Abstract

This manual explains BCD to GRAY code conversion by finding boolean equations.

1 BCD to GRAY Conversion

The BCD to GRAY code converter takes the numbers $0,\,1,\,\ldots$, 9 in binary as inputs and generates the converted number as output. Make connections as shown in table 1. Gray code – also known as Cyclic Code, Reflected Binary Code (RBC), Reflected Binary (RB) or Grey code.

Problem : - Implement BCD to GRAY conversion

2 Implementation

Connections :-	Arduino	2	3	4	5	6	7	8
	Display	а	b	С	d	е	f	g

3 Karnaugh Map

Using Boolean logic or kmaps, G0, G1, G2, G3 in the truth table can be expressed in terms of the inputs A,B,C,D

$\setminus CI$	D			·	
AB	00	01	11	10	
00	0	1	0	1	
01	0	1	0	1	
11	0	0	0	0	
10	0	1	0	0	

Kmap for G0

AB	00	01	11	10
00	0	0	1	1
01	1	1	0	0
11	0	0	0	0
10	0	0	0	0


kmap for G1

$$G1 = A'BC' + A'B'C \tag{2}$$

$\setminus CI$				
AB	00	01	11	10
00	0	0	0	0
01	1	1	1	1
11	0	0	0	0
10	1	1	0	0

kmap for G2

$$G2 = A'B + AB'C' \tag{3}$$



Kmap for G3

$$G3 = AB'C' \tag{4}$$


Using Boolean logic or kmaps, a,b,c,d,e,f,g in the truth table can be expressed in terms of G0,G1,G2,G3 as:

$$a = G0'G1'G2G3' + G0G1'G2'G3'$$
 (5)


$$b = G0'G1'G2G3 + G0'G1G2G3' + G0G1'G2G3'$$
 (6)

$$c = G0'G1G2'G3' + G0'G1'G2G3$$
 (7)


$$d = G0'G1'G2G3' + G0G1G2G3' + G0G1'G2'G3'$$
 (8)



e = G0G3' + G0G2G3' (9)



f = G0G2'G3' + G1G2'G3' + G0G1G3' (10)



Kmap for g

$$g = G1'G2'G3' + G1'G2G3 + G0G1G2G3'$$
 (11)

The code below realizes BCD to GRAY conversion using vaman board

https://github.com/NavyaValmeekam/FWC/tree/main/Arm/code

4 Setup

- 1. Connect the Vaman to the Laptop through USB.
- 2. There is a button and an LED to the left of the USB port on the Vaman. There is another button to the right of the LED.
- 3. Press the right button first and immediately press the left button. The LED will be blinking green. The Vaman is now in bootloader mode.

4.1 The steps for implementation:

1. Login to termux-ubuntu on the android device and execute the following commands:

Make sure that the required installation of pygmy-sdk had done prior executing below commands

proot—distro login debian
cd /data/data/com.termux/files/home/
mkdir arm
svn co https://github.com/NavyaValmeekam/FWC/
tree/main/Arm/code

cd code/GCC_Project
make
scp /data/data/com.termux/files/home/arm/code/
GCC_Project/output/bin/codes.bin
usernameofpc@IPaddress:/home/username

Make sure that the appropriate username, IP address of the Laptop is given in the above command.

2. Now execute the following commands on the Laptop terminal

Make sure that required installation of programmer application and modification of bash file had done prior executing below command

bash flash.sh codes.bin

3. After finishing the process of flashing with the programmer application press the button to the right of the USB port to reset. Vaman is now flashed with our source code