

No part of this publication may be reproduced or distributed in any form or any means, electronic, mechanical, photocopying, or otherwise without the prior permission of the author.

GATE SOLVED PAPER
Computer Science Engineering
Databases

Copyright © By NODIA & COMPANY

Information contained in this book has been obtained by authors, from sources believes to be reliable. However, neither Nodia nor its authors guarantee the accuracy or completeness of any information herein, and Nodia nor its authors shall be responsible for any error, omissions, or damages arising out of use of this information. This book is published with the understanding that Nodia and its authors are supplying information but are not attempting to render engineering or other professional services.

NODIA AND COMPANY

B-8, Dhanshree Tower Ist, Central Spine, Vidyadhar Nagar, Jaipur 302039

Ph : +91 - 141 - 2101150

www.nodia.co.in

email : enquiry@nodia.co.in

GATE SOLVED PAPER - CS

DATABASES

YEAR 2000

ONE MARK

- Q. 1 Given the relations
employee (name, salary, deptno), and
department (deptno, deptname, address)
Which of the following queries cannot be expressed using the basic relational algebra operations ($\sigma, \pi, \bowtie, \cup, \cap, -$) ?
(A) Department address of every employee
(B) Employee whose name is the same as their department name
(C) The sum of all employee salaries
(D) All employees of a given department

YEAR 2000

TWO MARKS

- Q. 2 Given the following relation instance.

X	Y	Z
1	4	2
1	5	3
1	6	3
3	2	2

Which of the following functional dependencies are satisfied by the instance ?

- (A) $XY \rightarrow Z$ and $Z \rightarrow Y$ (B) $YZ \rightarrow X$ and $Y \rightarrow Z$
(C) $YZ \rightarrow X$ and $X \rightarrow Z$ (D) $XZ \rightarrow Y$ and $Y \rightarrow X$

- Q. 3 Given relations $r(w, x)$ and $s(y, z)$, the result of select distinct w, x from r, s :

is guaranteed to be same as r , provided :

- (A) r has no duplicates and s is non empty
(B) r and s have no duplicates
(C) s has no duplicates and r is non empty
(D) r and s have the same number of tuples

YEAR 2001

ONE MARK

- Q. 4 Consider a schema $R(A, B, C, D)$ and functional dependencies $A \rightarrow B$ and $C \rightarrow D$. Then the decomposition of R into $R_1(AB)$ and $R_2(CD)$ is :
(A) Dependency preserving and lossless join
(B) Lossless join but not dependency preserving
(C) Dependency preserving but not lossless join
(D) Not dependency preserving and not lossless join

- Q. 5 Suppose the adjacency relation of vertices in a graph is represented in a table Adj (X, Y). Which of the following queries cannot be expressed by a relational algebra expression of constant length ?
- (A) List all vertices adjacent to a given vertex.
 - (B) List all vertices which have self loops
 - (C) List all vertices which belong to cycles of less than three vertices
 - (D) List all vertices reachable from a given vertex
- Q. 6 Let r and s be two relations over the relation schemes R and S respectively, and let A be an attribute in R . Then the relational algebra expression $\sigma_{A=a}(r \bowtie s)$ is always equal to :
- (A) $\sigma_{A=a}(r)$
 - (B) r
 - (C) $\sigma_{A=a}(r \bowtie s)$
 - (D) None of the above

YEAR 2001

TWO MARKS

- Q. 7 $R(A, B, C, D)$ is a relation. Which of the following does not have a lossless join, dependency preserving BCNF decomposition ?
- (A) $A \rightarrow B, B \rightarrow CD$
 - (B) $A \rightarrow B, B \rightarrow C, C \rightarrow D$
 - (C) $AB \rightarrow C, C \rightarrow AD$
 - (D) $A \rightarrow BCD$
- Q. 8 Which of the following relational calculus expressions is not safe ?
- (A) $\{r \mid \exists u \in R_1 (t[A] = u[A] \wedge \neg \exists s \in R_2 (t[A] = s[A]))\}$
 - (B) $\{r \mid \forall u \in R_1 (u[A] = "x" \Rightarrow \exists s \in R_2 (t[A] = s[A] \wedge s[A] = u[A]))\}$
 - (C) $\{t \mid \neg (t \in R_1)\}$
 - (D) $\{t \mid \exists u \in R_1 (t[A] = u[A]) \wedge \exists s \in R_2 (t[A] = s[A])\}$
- Q. 9 Consider a relation geq which represents "greater than or equal to", that is, $(x, y) \in geq$ only if $y \leq x$.
Create table geq
(
 lb integer not null
 ub integer not null
primary key lb
foreign key (ub) references geq on delete cascade):
Which of the following is possible if a tuple (x, y) is deleted ?
- (A) A tuple (z, w) with $z > y$ is deleted
 - (B) A tuple (z, w) with $z > x$ is deleted
 - (C) A tuple (z, w) with $w < x$ is deleted
 - (D) The deletion of (x, y) is prohibited

YEAR 2002

ONE MARK

- Q. 10 Relation R with an associated set of functional dependencies, F , is decomposed into $BCNF$. The redundancy (arising out of functional dependencies) in the resulting set of relations is.
- (A) Zero
 - (B) More than zero but less than that of an equivalent $3NF$ decomposition
 - (C) Proportional to the size of F^+
 - (D) Indeterminate.

- Q. 11 With regard to the expressive power of the formal relational query languages, which of the following statements is true ?
- (A) Relational algebra is more powerful than relational calculus.
 (B) Relational algebra has the same power as relational calculus.
 (C) Relational algebra has the same power as safe relational calculus.
 (D) None of the above.

- Q. 12 AB^+ -tree index is to be built on the Name attribute of the relation *STUDENT*. Assume that all student names are of length 8 bytes, disk blocks are of size 512 bytes, and index pointers are of size 4 bytes. Given this scenario, what would be the best choice of the degree (i.e. the number of pointers per node) of the B^+ -tree
- (A) 16 (B) 42
 (C) 43 (D) 44

- Q. 13 Relation R is decomposed using a set of functional dependencies, F , and relation S is decomposed using another set of functional dependencies, G . One decomposition is definitely $BCNF$, the other is definitely $3NF$, but it is not known which is which. To make a guaranteed identification, which one of the following tests should be used on the decompositions ? (Assume that the closures of F and G are available).
- (A) Dependency-preservation (B) Lossless-join
 (C) $BCNF$ definition (D) $3NF$ definition

- Q. 14 From the following instance of relation schema $R(A, B, C)$, we can conclude that :

A	B	C
1	1	1
1	1	0
2	3	2
2	3	2

- (A) A functionally determines B and B functionally determines C
 (B) A functionally determines B and B does not functionally determines C .
 (C) B does not functionally determines C
 (D) A does not functionally B and B does not functionally determines.

YEAR 2003

ONE MARK

- Q. 15 Which of the following scenarios may lead to an irrecoverable error in a database system?
- (A) A transaction writes a data item after it is read by an uncommitted transaction
 (B) A transaction read a data item after it is read by an uncommitted transaction
 (C) A transaction read a data item after it is written by an committed transaction
 (D) A transaction read a data item after it is written by an uncommitted transaction

Q. 16

Consider the following SQL query

```
select distinct  $a_1, a_2, \dots, a_n$ 
```

```
from  $r_1, r_2, \dots, r_m$ 
```

```
where  $P$ 
```

For an arbitrary predicate P , this query is equivalent to which of the following relational algebra expressions?

(A) $\Pi_{a_1, a_2, \dots, a_n} \sigma_P(r_1 \times r_2 \times \dots \times r_m)$

(B) $\Pi_{a_1, a_2, \dots, a_n} \sigma_P(r_1 \bowtie r_2 \bowtie \dots \bowtie r_m)$

(C) $\Pi_{a_1, a_2, \dots, a_n} \sigma_P(r_1 \cup r_2 \cup \dots \cup r_m)$

(D) $\Pi_{a_1, a_2, \dots, a_n} \sigma_P(r_1 \cap r_2 \cup \dots \cap r_m)$

YEAR 2003

TWO MARKS

Q. 17

Consider the following functional dependences in a database:

Data_of_Birth \rightarrow Age

Age \rightarrow Eligibility

Name \rightarrow Roll_number

Roll_number \rightarrow Name

Course_number \rightarrow Course_name

Course_number \rightarrow Instructor

(Roll_number, Course_number) \rightarrow Grade

The relation (Roll number, Name, Date_of_birth, Age) is

(A) in second normal form but not in third normal form

(B) in third normal form but not in BCNF

(C) in BCNF

(D) in none of the above

Q. 18

Consider the set of relations shown below and the SQL query that follow:

Students: (Roll_number, Name, Date_of_birth)

Courses: (Course_number, Course_name, Instructor)

Grades: (Roll_number, Course_number, Grade)

```
select distinct Name
```

```
from Students, Courses, Grades
```

```
Where Students.Roll_number=Grades.Roll_number
```

```
and Courses.Instructor=Korth
```

```
and Courses.Course_number=Grades.Course_number
```

```
and Grades.grade=A
```

Which of the following sets is computed by the above query?

(A) Names of students who have got an A grade in all courses taught by Korth

(B) Names of students who have got an A grade in all courses

(C) Name of students who have got an A grade in at least one of the courses taught by Korth

(D) None of the above

Q. 19

Consider three data items $D1, D2$ and $D3$ and the following execution schedule of transactions $T1, T2$ and $T3$. In the diagram, $R(D)$ and $W(D)$ denote the actions reading and writing the data item D respectively.

T1	T2	T3
	R(D3);	
	R(D2);	
	R(D2);	
		R(D2);
		R(D3);
R(D1);		
R(D1);		
		W(D2);
		W(D3);
	R(D1);	
R(D2);		
W(D2);		
	W(D1);	

- (A) The schedule is serializable as $T2; T3; T1$;
 (B) The schedule is serializable as $T2; T1; T3$;
 (C) The schedule is serializable as $T3; T2; T1$;
 (D) The schedule is not serializable

YEAR 2004

ONE MARK

Q. 20

Let $R_1(A, B, C)$ and $R_2(D, E)$ be two relation schema, where the primary keys are shown underlined, and let C be a foreign key in R_1 referring to R_2 . Suppose there is no violation of the above referential integrity constraint in the corresponding relation instances r_1 and r_2 . Which one of the following relational algebra expressions would necessarily produce an empty relation?

- (A) $\Pi_D(r_1) - \Pi_C(r_1)$ (B) $\Pi_C(r_1) - \Pi_D(r_1)$
 (C) $\Pi_D(r_1 \bowtie_{C \neq D} R_2) - \Pi_C(r_1)$ (D) $\Pi_C(r_1 \bowtie_{C=D} R_2)$

Q. 21

Consider the following relation schema pertaining to a students database:

Student(rollno, name, address)

Enroll(rollno, courseno, coursename)

where the primary keys are shown underlined. The number of tuples in the student and Enroll tables are 120 and 8 respectively. What are the maximum and minimum number of tuples that can be present in $(\text{Student} * \text{Enroll})$, where '*' denotes natural join?

- (A) 8,8 (B) 120,8
 (C) 960,8 (D) 960,120


YEAR 2004

TWO MARKS

Q. 22

It is desired to design an object-oriented employee record system for a company. Each employee has a name, unique id and salary. Employees belong to different categories and their salary is determined by their category. The functions get Name., getld and compute Salary are required. Given the class hierarchy below, possible locations for these functions are:

- (i) getld is implemented in the superclass
- (ii) getld is implemented in the subclass
- (iii) getName is an abstract function in the superclass
- (iv) getName is implemented in the superclass
- (v) getName is implemented in the subclass
- (vi) getSalary is an abstract function in the superclass
- (vii) getSalary is implemented in the superclass
- (viii) getSalary is implemented in the subclass



Choose the best design

- (A) (i), (iv), (vi), (viii)
- (B) (i), (iv), (vii)
- (C) (i), (iii), (v), (vi), (viii)
- (D) (ii), (v), (viii)

Q. 23

The relation scheme student Performance (name, courseNo, rollNo, grade) has the following functional dependencies:

- name, courseNo \rightarrow grade
- RollNo, courseNo \rightarrow grade
- name \rightarrow rollNo
- rollNo \rightarrow name

The highest normal form of this relation scheme is

- (A) 2 NF
- (B) 3NF
- (C) BCNF
- (D) 4 NF

Q. 24

Consider the relation Student (name, sex, marks), where the primary key is shown underlined, pertaining to students in a class that has at least one boy and one girl. What does the following relational algebra expression produce?

$$\Pi_{\text{name}} (\sigma_{\text{sex} = \text{female}} (\text{Student})) \bowtie_{\text{marks} \leq m} \rho_{\text{marks} \leq m} (\text{Student})$$

- (A) names of girl students with the highest marks
- (B) names of girl students with more marks than some boy student
- (C) names of girl students with marks not less than some boy student
- (D) names of girl students with more marks than all the boy students

- Q. 25 The order of an internal node in a B* tree index is the maximum number of children it can have. Suppose that a child pointer takes 6 bytes, the search field value takes 14 bytes., and the block size is 512 bytes. What is the order of the internal node?
- (A) 24 (B) 25
(C) 26 (D) 27
- Q. 26 The employee information in a company is stored in the relation
Employee (name, sex, salary, deptName)
Consider the following SQL query
- ```
select deptname
 from Employee
 where sex= 'M'
group by deptName
having avg (salary)>
 (select avg(salary)from Employee)
```
- It returns the names of the department in which
- (A) the average salary is more than the average salary in the company  
(B) the average salary of male employees is more than the average salary of all male employees in the company  
(C) the average salary of male employees is more than the average salary of employees in the same department  
(D) the average salary of made employees is more than the average salary in the company

YEAR 2005

ONE MARKS

- Q. 27 Which one of the following is a key factor for preferring  $B^+$ -trees to binary search trees for indexing database relation?
- (A) Database relations have a large number of record  
(B) Database relations are sorted on the primary key  
(C)  $B^+$ -trees require less memory than binary search trees  
(D) Data transfer from disks is in blocks
- Q. 28 Which-one of the following statements about normal forms is FALSE?
- (A) BCNF is stricter than 3 NF  
(B) Loss less, dependency-preserving decomposition into 3 NF is always possible  
(C) Loss less, dependency-preserving decomposition into BCNF is always possible  
(D) Any relation with two attributes is BCNF
- Q. 29 Let  $r$  be a relation instance with schema  $R = (A, B, C, D)$ . WE DEFINE  $R_1 = \Pi_{A,B,C}(r)$  and  $R_2 = \Pi_{AD}(r)$ . let  $S = r_1 * r_2$  where  $*$  denotes natural join. Given that the decomposition of  $r$  into  $r_1$  and  $r_2$  is lossy, which one of the following is TRUE?
- (A)  $s \subset r$  (B)  $r \subset s = r$   
(C)  $r \subset s$  (D)  $r^* s = s$



YEAR 2005

TWO MARKS

- Q. 30 Let  $E_1$  and  $E_2$  be two entities in an E/R diagram with simple single-valued attributes.  $R_1$  and  $R_2$  are two relationships between  $E_1$  and  $E_2$  where  $R_1$  is one-to-many and  $R_2$  is many-to-many.  $R_1$  and  $R_2$  do not have any attributes of their own. What is the minimum number of tables required to represent this situation in the relational model?
- (A) 2 (B) 3  
(C) 4 (D) 5

- Q. 31 The following table has two attributes  $A$  and  $C$  where  $A$  is the primary key and  $C$  is the foreign key referencing  $A$  with on-delete cascade.

| A | C |
|---|---|
| 2 | 4 |
| 3 | 4 |
| 4 | 3 |
| 5 | 2 |
| 7 | 2 |
| 9 | 5 |
| 6 | 4 |

The set of all tuples that must be additionally deleted to preserve referential integrity when the tuple (2,4) is deleted is:

- (A) (3,4) and (6,4)  
(B) (5,2) and (7,2)  
(C) (5,2) (7,2) and (9,5)  
(D) 1
- Q. 32 The relation book (title, price) contains the titles and prices of different books. Assuming that no two books have the same price, what does the following SQL select title  
from book as B  
where (select count(\*)  
from book as T  
where T. price > B.Price) < 5
- (A) Titles of the four most expensive books  
(B) Title of the fifth most inexpensive book  
(C) Title of the fifth most expensive book  
(D) Titles of the five most expensive books

- Q. 33 Consider a relation scheme  $R = (A, B, C, D, E, H)$  on which the following functional dependencies hold:  
 $\{A \rightarrow B, BC \rightarrow D, E \rightarrow C, D \rightarrow A\}$   
What are the candidate keys of  $R$ ?
- (A)  $AE, BE$   
(B)  $AE, BE, DE$   
(C)  $AEH, BEH, BCH$   
(D)  $AEH, BEH, DEH$

YEAR 2006

ONE MARK

Q. 34

Consider the following log sequence of two transactions on a bank account, with initial balance 12000, that transfer 2000 to a mortgage payment and, then apply a 5% interest.

1. T1 start
2. T1 B old = 12000 new = 10000
3. T1 M old = 0 new = 2000
4. T1 commit
5. T2 start
6. T2 B old = 10000 new = 10500
7. T2 commit

Suppose the database system crashed just before log record 7 is written. When the system is restarted, which one statement is true of the recovery procedure?

- (A) We must redo log record 6 to set B to 10500
- (B) We must undo log record 6 to set B to 10000 and then redo log records 2 and 3
- (C) We need not redo log records 2 and 3 because transaction T1 has committed
- (D) We can apply redo and undo operations in arbitrary order because they are idempotent

YEAR 2006

TWO MARKS

Q. 35

Consider the relation account (customer, balance) where customer is a primary key and there are no null values. We would like to rank customers according to decreasing balance. The customer with the largest balance gets rank 1. Ties are not broken but ranks are skipped: if exactly two customers have the largest balance they each get rank 1 and rank 2 is not assigned.

Query 1 : Select A. customer, count (B. customer) from account A, account B where A. customer

Query 2 : Select A. customer, 1+count(B. customer) from account A, account B where A. balance < B. balance group by A. customer

Consider these statements about Query 1 and Query 2.

1. Query 1 will produce the same row set as Query 2 for some but not all databases
2. Both Query 1 Query 2 are correct implementations of the specification
3. Query 1 is a correct implementation of the specification but Query 2 is not
4. Neither query 1 nor Query 2 is a correct implementation of the specification
5. Assigning rank with a pure relational Query takes less time than scanning in decreasing balance order the assigning ranks using ODBC

Which two of the above statements are correct?

- (A) 2 and 5
- (B) 1 and 3
- (C) 1 and 4
- (D) 3 and 5

Q. 36

Consider the relation enrolled (student, course) in which student, course) is the primary key, and the relation paid (student, amount) where student is the primary key. Assume no null values and no foreign keys or integrity constraints. Given the following four queries:


Query 1: Select from enrolled where student in (select student from paid)  
 Query 2: Select student from paid where student in (select student from enrolled)  
 Query 3: Select E. student from enrolled E, paid P where E. student= P student  
 Query 4: Select student from paid where exists (select \* from enrolled where enrolled student=paid.student)

Which one of the following statements is correct?

- (A) All queries return identical row sets for any database
- (B) Query 2 and Query 4 return identical row sets for all databases but there exist database for which Query 1 and Query 2 return different row sets
- (C) There exist databases for which Query 3 returns strictly fewer rows than Query 2
- (D) There exist databases for which Query 4 will encounter an integrity violation at runtime

Q. 37

Consider the relation enrolled (student, course) in which (student, course) is the primary key, and the relation paid (student, amount) where student is the primary key. Assume no null values and no foreign keys or integrity constraints. Assume that amounts 6000, 7000, 8000, 9000 and 10000 were each paid by 20% of the students. Consider these query plans (Plan 1 on left, Plan 2 on right) to “list all courses taken by students who have paid more than x.”



A disk seek takes 4 ms. disk data transfer bandwidth is 300 MB/s and checking a tuple to see if amount is greater x takes 10 μs. Which of the following statements

is correct?

- (A) Plan 1 and Plan 2 will not output identical row sets for all databases
- (B) A course may be listed more than once in the output of Plan 1 for some databases
- (C) For  $x = 5000$ , Plan 1 executes faster than Plan 2 for all databases
- (D) For  $x = 9000$ , Plan 1 executes slower than Plan 2 for all databases

Q. 38

The following functional dependencies are given:

$AB \rightarrow CF, AF \rightarrow D, DE \rightarrow F, C \rightarrow G, F \rightarrow E, G \rightarrow A.$

Which one of the following options is false?

- (A)  $\{CF\}^+ = \{ACFEFG\}$
- (B)  $\{BG\}^+ = \{ABCDG\}$
- (C)  $\{AF\}^+ = \{ACDEFG\}$
- (D)  $\{AB\}^+ = \{ACDFG\}$

YEAR 2007

TWO MARKS

- Q. 39 Information about a collection of students is given by the relation studInfo (studId, name, sex). The relation enroll (studId, CourseId) gives which student has enrolled for (or taken) what course(s). Assume that every course is taken by at least one male and at least one female student. What does the following relational algebra expression represent?  

$$\Pi_{\text{courseId}} ((\Pi_{\text{studId}} (\sigma_{\text{sex} = \text{"female"}} (\text{studInfo})) \times \Pi_{\text{courseId}} (\text{enroll})) - \text{enroll})$$
 (A) Courses in which all the female students are enrolled  
 (B) Courses in which a proper subset of female students are enrolled  
 (C) Courses in which only male students are enrolled  
 (D) None of the above.
- Q. 40 Consider the relation employee (name, sex, supervisorName (with name as the key, supervisor Name-gives the name of the supervisor of the employee under consideration. What does the following Tuple Relational Calculus query produce?  

$$\{e.\text{name} \mid \text{employee}(e) \wedge (\forall x) [\neg \text{employee}(x) \vee x.\text{supervisorName} \neq e.\text{name} \vee x.\text{sex} = \text{"male"}]\}$$
 (A) Names of employees with a male supervisor  
 (B) Names of employees with no immediate male subordinates  
 (C) Names of employees with no immediate female subordinates  
 (D) Names of employees with a female supervisor
- Q. 41 Consider the table employee (empId, name, department, salary) and the two queries  $Q_1, Q_2$  below. Assuming that department 5 has more than one employee, and we want to find the employees who get higher salary than anyone in the department 5, which one of the statements is TRUE for any arbitrary employee table?  
 $Q_1$  : Select e. empId  
       From employee e  
       Where not exists  
       (Select \* From employee s Where s. department = "5" and s.salary >= e.salary)  
 $Q_2$  : Select e. empId  
       From employee e  
       Where e.salary > Any  
       (Select distinct salary From employee s Where s. department = "5")  
 (A)  $Q_1$  is the correct query.  
 (B)  $Q_2$  is the correct query  
 (C) Both  $Q_1$  and  $Q_2$  produce the same answer  
 (D) Neither  $Q_1$  nor  $Q_2$  is the correct query
- Q. 42 Which one of the following statements is FALSE?  
 (A) Any relation with two attributes is in BCNF  
 (B) A relation in which every key has only one attribute is in 2NF  
 (C) A prime attribute can be transitively dependent on a key in 3NF relation  
 (D) A prime attribute can be transitively dependent on a key in a BCNF relation.

- Q. 43 The order of a leaf node in a  $B^+$ -tree is the maximum number of (value, data record pointer) pairs it can hold. Given that the block size is 1K bytes, data record pointer is 7 bytes long, the value field is 9 bytes long and a block pointer is 6 bytes long, what is the order of the leaf node?
- (A) 63 (B) 64  
(C) 67 (D) 68

- Q. 44 Consider the following schedules involving two transactions. Which one of the following statements is TRUE?
- $S_1: r_1(X); r_1(Y); r_2(X); r_2(Y); w_2(Y); w_1(X)$   
 $S_2: r_1(X); r_2(X); r_2(Y); w_2(Y); r_1(Y); w_1(X)$
- (A) Both  $S_1$  and  $S_2$  are conflict serializable  
 (B)  $S_1$  is conflict serializable and  $S_2$  is not conflict serializable  
 (C)  $S_1$  is not conflict serializable and  $S_2$  is conflict serializable  
 (D) Both  $S_1$  and  $S_2$  are not conflict serializable

YEAR 2008

ONE MARK

- Q. 45 A clustering index is defined on the fields which are of type
- (A) Non-key and ordering (B) Non-key and non-ordering  
 (C) key and ordering (D) Key and non-ordering

YEAR 2008

TWO MARKS

- Q. 46 Let  $R$  and  $S$  be two relations with the following schema
- $R(\underline{P}, \underline{Q}, R1, R2, R3)$   
 $S(\underline{P}, \underline{Q}, S1, S2)$
- Where  $\{P, Q\}$  is the key for both schemes. Which of the following queries are equivalent?
- I  $\Pi_P(\bowtie S)$   
 II  $\Pi_P(R) \bowtie \Pi_P(S)$   
 III  $\Pi_P(\Pi_{P,Q}(R) \cap \Pi_{P,Q}(S))$   
 IV  $\Pi_P(\Pi_{P,Q}(R) - (\Pi_{P,Q}(R) - \Pi_{P,Q}(S)))$
- (A) Only I and II (B) Only I and II  
 (C) Only I, II and III (D) Only I, II and IV


- Q. 47 Consider the following relational schemes for a library database:
- Book (Title, Author, Catalog\_no, Publisher, Year, price)  
 Collection (Title, Author, Catalog\_no)
- Which the following functional dependencies:
- I. Title Author  $\rightarrow$  Catalog\_no  
 II. Catalog\_no  $\rightarrow$  Title Author Publisher Year  
 III. Publisher Title Year  $\rightarrow$  price
- Assume  $\{\text{Author, Title}\}$  is the key for both schemes: which of the following statements is true?
- (A) Both Book and Collection are in BCNF  
 (B) Both Book and Collection are in 3NF only  
 (C) Book is in 2NF and Collection is in 3NF  
 (D) Both Book and Collection are in 2NF only

- Q. 48 Consider a file of 1684 records. Each record is 32 bytes long and its key field is of size 6 bytes. The file is ordered on a non-key field, and the file organization is unspanned. The file is stored in a file system with block size 1024 bytes, and the size of a block pointer is 10 bytes. If the secondary index is built on the key field of the file, and a multi-level index scheme is used to store the secondary index, the number of first-level and second-level blocks in the multi-level index are respectively
- (A) 8 and 0 (B) 128 and 6  
(C) 256 and 4 (D) 512 and 5

**Common Data For Q. 49 & 50 :**

Solve the problems and choose the correct answers.

Consider the following ER diagram



- Q. 49 The minimum number of tables needed to represent  $M, N, P, R1, R2$  is
- (A) 2 (B) 3  
(C) 4 (D) 5
- Q. 50 Which of the following is a correct attribute set for one of the tables for the correct answer to the above question?
- (A)  $\{M1, M2, M3, P1\}$  (B)  $\{M1, P1, N1, N2\}$   
(C)  $\{M1, P1, N1\}$  (D)  $\{M1, P1\}$

YEAR 2009

TWO MARKS

- Q. 51 Consider two transactions  $T_1$  and  $T_2$  and four schedules  $S_1, S_2, S_3, S_4$  of  $T_1$  and  $T_2$  as given below :

$T_1: R1[x] W1[x] W1[y]$

$T_2: R2[x] R2[y] W2[y]$

$S_1: R1[x] R2[x] R2[y] W1[x] W1[y] W2[y]$

$S_2: R1[x] R2[x] R2[y] W1[x] W2[y] W1[y]$

$S_3: R1[x] W1[x] R2[x] W1[y] R2[y] W2[y]$

$S_4: R2[x] R2[y] R1[x] W1[x] W1[y] W2[y]$

Which of the above schedules are conflict-serializable?

- (A)  $S_1$  and  $S_2$  (B)  $S_2$  and  $S_3$   
(C)  $S_3$  only (D)  $S_4$  only
- Q. 52 The following key values are inserted into a  $B+$  -tree in which order of the internal nodes is 3, and that of the leaf nodes is 2, in the sequence given below. The order of internal nodes is the maximum number of tree pointers in each node, and the order of leaf nodes is the maximum number of data items that can be stored in it. The  $B+$  -tree is initially empty.
- 10,3,6,8,4,2,1

The maximum number of times leaf nodes would get split up as a result of these insertions is

- (A) 2 (B) 3  
(C) 4 (D) 5

Q. 53

Let  $R$  and  $S$  be relation schemes such that  $R = \{a, b, c\}$  and  $S = \{c\}$ . Now consider the following queries on the database :

- I.  $\pi_{R-S}(r) - \pi_{R-S}(\pi_{R-S}(r) \times S - \pi_{R-S,S}(r))$   
 II.  $\{t \mid t \in \pi_{R-S}(r) \wedge \forall u \in s(\exists v \in r(u = v[s] \wedge t = v[R-S]))\}$   
 III.  $\{t \mid t \in \pi_{R-S}(r) \wedge \forall v \in r(\exists u \in s(u = v[s] \wedge t = v[R-S]))\}$   
 IV. Select  $R.a, R.b$

From  $R, S$

Where  $R.c = S.c$

Which of the above queries are equivalent?

- (A) I and II (B) I and III  
(C) II and IV (D) III and IV

### Common Data For Q. 54 & 55 :

Consider the following relational schema:

Suppliers(sid: integer, sname:string, city:string, street:string)

Parts(pid:integer, pname:string, color:string)

Catalog(sid:integer, pid:integer, cost:real)

Q. 54

Consider the following relational query on the above database :

```
SELECT S.sname
FROM Suppliers S
WHERE S.sid NOT IN (SELECT C.sid
 FROM Catalog C
 WHERE C.pid NOT IN (SELECT P.pid
 FROM Parts P
 WHERE P.color = 'blue'))
```

Assume that relations corresponding to the above schema are not empty. Which one of the following is the correct interpretation of the above query?

- (A) Find the names of all suppliers who have supplied a non-blue part.  
 (B) Find the names of all suppliers who have not supplied a non-blue part.  
 (C) Find the names of all suppliers who have supplied only blue parts.  
 (D) Find the names of all suppliers who have not supplied only blue parts.

Q. 55

Assume that, in the suppliers relation above, each supplier and each street within a city has a unique name, and (same, city) forms a candidate key. No other functional dependencies are implied other than those implied by primary and candidate keys. Which one of the following is TRUE about the above schema ?

- (A) The schema is in BCNF. (B) The schema is in 3NF but not in BCNF.  
 (C) The schema is in 2NF but not in 3NF.  
 (D) The schema is not in 2NF.

YEAR 2010

ONE MARK

Q. 56

Consider a  $B^+$ -tree in which the maximum number of keys in a node is 5. What is the minimum number of keys in any non-root node?

- (A) 1 (B) 2  
(C) 3 (D) 4

Q. 57

A relational schema for a train reservation database is given below.

Passenger (pid, pname, age)

Reservation (pid, class, tid)

Table : passenger

| pid | pname    | Age |
|-----|----------|-----|
| 0   | 'Sachin' | 65  |
| 1   | 'Rahul'  | 66  |
| 2   | Sourav'  | 67  |
| 3   | 'Anil'   | 69  |

Table : Reservation

| pid | class | tid  |
|-----|-------|------|
| 0   | 'AC'  | 8200 |
| 1   | 'AC'  | 8201 |
| 2   | 'SC'  | 8201 |
| 3   | 'AC'  | 8203 |
| 4   | 'SC'  | 8204 |
| 5   | 'AC'  | 8202 |

What pids are returned by the following SQL query for the above instance of the tables ?

```
SELECT pid
FROM Reservation
WHERE class= 'AC' AND
EXISTS (SELECT*
FROM Passenger
WHERE age>65 AND
Passenger.pid = Reservation.pid)
```

- (A) 1,0 (B) 1, 2  
(C) 1, 3 (D) 1, 5

Q. 58

Which of the following concurrency control protocols ensure both conflict serializability and freedom from deadlock?

I. 2-phase locking

II Time-stamp ordering

- (A) I only (B) II only  
(C) Both I and II (D) Neither I nor II



YEAR 2010

TWO MARKS

Q. 59

Consider the following schedule for transactions T1, T2, and T3 :

| T1        | T2        | T3        |
|-----------|-----------|-----------|
| Read (X)  |           |           |
|           | Read (Y)  |           |
|           |           | Read (Y)  |
| Write (X) |           |           |
|           |           | Write (X) |
|           | Read (X)  |           |
|           | Write (X) |           |

Which one of the schedules below is the correct serialization of the above ?

- (A)  $T1 \rightarrow T3 \rightarrow T2$
- (B)  $T2 \rightarrow T1 \rightarrow T3$
- (C)  $T2 \rightarrow T3 \rightarrow T1$
- (D)  $T3 \rightarrow T1 \rightarrow T2$

Q. 60

The following functional dependencies hold for relations R(A,B,C) and S(B,D,E):

$B \rightarrow A$

$A \rightarrow C$

The relation R contains 200 tuples and the relation S contains 100 tuples. What is the maximum number of tuples possible in the natural join  $R \bowtie S$  ?

- (A) 100
- (B) 200
- (C) 300
- (D) 2000

YEAR 2011

ONE MARK

Q. 61

Consider a relational table with a single record from each registered student with the following attributes.

1. Registration\_Num: Unique registration number of each registered student
2. UID: Unique identity number, unique at the national level for each citizen
3. BankAccount\_Num: Unique account number at the bank. A student can have multiple accounts or joint accounts. This attribute stores the primary account number.
4. Name: Name of the student
5. Hostel\_Room: Room number of the hostel

Which of the following options is INCORRECT?

- (A) BankAccount\_Num is a candidate key
- (B) Registration\_Num can be a primary key
- (C) UID is a candidate key if all students are from the same country
- (D) If S is a superkey such that  $S \cap \text{UID}$  is NULL the  $S \cup \text{UID}$  is also a superkey

YEAR 2011

TWO MARKS

Q. 62

Consider a database table T containing two columns X and Y each of type integer. After the creation of the table, one record ( $X=1$ ,  $Y=1$ ) is inserted in the table. Let MX and MY denote the respective maximum values of X and Y among all records in the table at any point in time. Using MX and MY, new records are inserted in the table 128 times with X and Y values being  $MX + 1$ ,  $2*MY + 1$  respectively. It may be noted that each time after the insertion, values of MX and MY change.

What will be the output of the following SQL query after the steps mentioned above are carried out?

```
SELECT Y FROM T WHERE X = 7;
```

- (A) 127
- (B) 255
- (C) 129
- (D) 257

Q. 63

Database table by name Loan\_records is given below:

| Borrower | Bank_Manager | Loan_Amount |
|----------|--------------|-------------|
| Ramesh   | Sunderajan   | 10000.00    |
| Suresh   | Ramgopal     | 5000.00     |
| Mahesh   | Sunderajan   | 7000.00     |

What is the output of the following SQL query?

```
SELECT count(*)
FROM (
 (SELECT Borrower, Bank_Manager FROM Loan_Records)
 AS S NATURAL JOIN
 (SELECT Bank_Manager, Loan_Amount FROM Loan_Records)
 AS T
);
```

- (A) 3
- (B) 9
- (C) 5
- (D) 6

YEAR 2012

ONE MARK

Q. 64

Which of the following is TRUE?

- (A) Every relation in 3NF is also in BCNF
- (B) A relation R is in 3NF if every non-prime attribute of R is fully functionally dependent on every key of R
- (C) Every relation in BCNF is also in 3NF
- (D) No relation can be in both BCNF and 3NF

Q. 65

Given the basic ER and relational models, which of the following is INCORRECT?

- (A) An attribute of an entity can have more than one value
- (B) An attribute of an entity can be composite
- (C) In a row of a relational table, an attribute can have more than one value
- (D) In a row of a relational table, an attribute can have exactly one value or a NULL value

Q. 66

Which of the following statements are TRUE about an SQL query?

- P: An SQL query can contain a HAVING clause even if it does not have a GROUP BY clause
- Q: An SQL query can contain a HAVING clause only if it has a GROUP BY clause
- R: All attributes used in the GROUP BY clause must appear in the SELECT clause
- S: Not all attributes used in the GROUP BY clause need to appear in the SELECT clause

- (A) P and R (B) P and S  
(C) Q and R (D) Q and S

YEAR 2012

TWO MARKS

Q. 67

Consider the following transactions with data items P and Q initialized to zero:

```

T1: Read (P);
 red (0);
 if P = 0 then Q := Q + 1;
 write (Q);
T2: read (0);
 read (P);
 if Q = 0 then P := P + 1;
 write (P);

```

Any non-serial interleaving of  $T_1$  and  $T_2$  for concurrent execution leads to

- (A) a serializable schedule
- (B) a schedule that is no conflict serializable
- (C) a conflict serializable schedule
- (D) a schedule for which a precedence graph cannot be drawn

Q. 68

Suppose  $R_1(A, B)$  and  $R_2(C, D)$  are two relation schemes. Let  $r_1$  and  $r_2$  be the corresponding relation instances. B is a foreign key that refers to C in  $R_2$ . If data in  $r_1$  and  $r_2$  satisfy referential integrity constraints, which of the following is ALWAYS TRUE?

- (A)  $\Pi_B(r_1) - \Pi_C(r_2) = \emptyset$  (B)  $\Pi_C(r_2) - \Pi_B(r_1) = \emptyset$   
(C)  $\Pi_B(r_1) = \Pi_C(r_2)$  (D)  $\Pi_B(r_1) - \Pi_C(r_2) \neq \emptyset$

### Common Data For Q. 69 and 70 :

Consider the following relations A, B and C:

A.

| Id | Name   | Age |
|----|--------|-----|
| 12 | Arun   | 60  |
| 15 | Shreya | 24  |
| 99 | Rohit  | 11  |

B.

| Id | Name   | Age |
|----|--------|-----|
| 15 | Shreya | 24  |
| 25 | Hari   | 40  |
| 98 | Rohit  | 20  |
| 99 | Rohit  | 11  |

C.

| Id | Phone | Age |
|----|-------|-----|
| 10 | 2200  | 02  |
| 99 | 2100  | 01  |

Q. 69

How many tuples does the result of the following relational algebra expression contain? Assume that the schema of  $A \cup B$  is the same as that of A.

$$(A \cup B) \bowtie_{A.Id > 40 \vee C.Id < 15} C$$

(A) 7

(B) 4

(C) 5

(D) 9

Q. 70

How many tuples does the result of the following SQL query contain?

```
SELECT A.Id
```

```
FROM A
```

```
WHERE A.Age >
```

```
ALL (SELECT B.Age
```

```
FROM B
```

```
WHERE B.Name = 'Arun')
```

(A) 4

(B) 3

(C) 0

(D) 1

\*\*\*\*\*

## ANSWER KEY

| Databases |     |     |     |     |     |     |     |     |     |
|-----------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1         | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | 10  |
| (C)       | (B) | (A) | (C) | (C) | (C) | (D) | (C) | (C) | (A) |
| 11        | 12  | 13  | 14  | 15  | 16  | 17  | 18  | 19  | 20  |
| (C)       | (D) | (C) | (B) | (D) | (A) | (D) | (C) | (D) | (A) |
| 21        | 22  | 23  | 24  | 25  | 26  | 27  | 28  | 29  | 30  |
| (A)       | (A) | (B) | (D) | (C) | (D) | (D) | (C) | (C) | (B) |
| 31        | 32  | 33  | 34  | 35  | 36  | 37  | 38  | 39  | 40  |
| (C)       | (D) | (D) | (C) | (C) | (A) | (C) | (C) | (D) | (C) |
| 41        | 42  | 43  | 44  | 45  | 46  | 47  | 48  | 49  | 50  |
| (B)       | (D) | (B) | (C) | (A) | (C) | (C) | (C) | (A) | (A) |
| 51        | 52  | 53  | 54  | 55  | 56  | 57  | 58  | 59  | 60  |
| (B)       | (C) | (C) | (A) | (A) | (B) | (C) | (B) | (A) | (A) |
| 61        | 62  | 63  | 64  | 65  | 66  | 67  | 68  | 69  | 70  |
| (A)       | (A) | (C) | (C) | (C) | (A) | (B) | (A) | (A) | (B) |