

No part of this publication may be reproduced or distributed in any form or any means, electronic, mechanical, photocopying, or otherwise without the prior permission of the author.

GATE SOLVED PAPER
Computer Science Engineering
Software Engineering & Web Technology

Copyright © By NODIA & COMPANY

Information contained in this book has been obtained by authors, from sources believes to be reliable. However, neither Nodia nor its authors guarantee the accuracy or completeness of any information herein, and Nodia nor its authors shall be responsible for any error, omissions, or damages arising out of use of this information. This book is published with the understanding that Nodia and its authors are supplying information but are not attempting to render engineering or other professional services.

NODIA AND COMPANY

B-8, Dhanshree Tower Ist, Central Spine, Vidyadhar Nagar, Jaipur 302039

Ph : +91 - 141 - 2101150

www.nodia.co.in

email : enquiry@nodia.co.in

GATE SOLVED PAPER - CS

SOFTWARE ENGINEERING & WEB TECHNOLOGY

YEAR 2011

ONE MARK

- Q. 1 A company needs to develop digital signal processing software for one of its newest inventions. The software is expected to have 40000 lines of code. The company needs to determine the effort in person-months needed to develop this software using the basic COCOMO model. The multiplicative factor for this model is given as 2.8 for the software development on embedded systems, while the exponentiation factor is given as 1.20. Which is the estimated effort in person months?

(A) 234.25 (B) 932.50
(C) 287.80 (D) 122.40

- Q. 2 A company needs to develop a strategy for software product development for which it has a choice of two programming languages L1 and L2. The number of Lines of Code (LOC) developed using L2 is estimated to be twice the LOC developed with L1. The product will have to be maintained for five years. Various parameters for the company are given in the table below.

Parameter	Languagey L1	Language L2
Man years needed for development	LOC/10000	LOC/10000
Development Cost per man year	1000000	750000
Maintenance time	5 years	5 years
Cost of maintenance per year	100000	50000

Total cost of the project includes cost of development and maintenance. What is the LOC for L1 for which the cost of the project using L1 is equal to the cost of the project using L2?

(A) 4000 (B) 5000
(C) 4333 (D) 4667

- Q. 3 HTML (Hyper Text Markup Language) has language elements which permit certain actions other than describing the structure of the web document. Which one of the following actions is NOT supported by pure HTML (without any server or client side scripting) page?

(A) Embed web objects from different sites into the same page
(B) Refresh the page automatically after a specified interval
(C) Automatically redirect to another page upon download
(D) Display the client time as part of the page

- Q. 4 Which one of the following is NOT desired in a good Software Requirement Specifications (SRS) document?
- (A) Functional Requirements
(B) Non-Functional Requirements
(C) Goals of Implementation
(D) Algorithms for Software Implementation

YEAR 2011

TWO MARKS

- Q. 5 Which of the given options provides the increasing order of asymptotic complexity of functions f_1, f_2, f_3 and f_4 ?

$$f_1(n) = 2^n$$

$$f_2(n) = n^{3/2}$$

$$f_3(n) = n \log_2 n$$

- (A) f_3, f_2, f_4, f_1 (B) f_3, f_2, f_1, f_4
(C) f_2, f_3, f_1, f_4 (D) f_2, f_3, f_4, f_1

- Q. 6 The following is the comment written for a C function.

* This function computes the roots of a quadratic equation $a.x^2+b.x+c=0$.

The function stores two real roots in *root1 and *root2 and returns the status of validity of roots. It handles four different kinds of cases.

(i) When coefficient a is zero irrespective of discriminant.

(ii) When discriminant is positive.

(iii) When discriminant is zero.

(iv) When discriminant is negative.

Only in case (ii) and (iii), the stored roots are valid.

Otherwise 0 is stored in the roots.

The function returns 0 when the roots are valid and - otherwise.

The function also ensures $\text{root1} \geq \text{root2}$.

```
int get_QuadRoots (float a, float b, float c, float *root1, float *root2);
```

A software test engineer is assigned the job of doing black box testing. He comes up with the following test cases, many of which are redundant.

Test Case	Input Set			Expected Output Set		
	a	b	c	root1	root2	Return Value
11	0.0	0.0	7.0	0.0	0.0	- 1
12	0.0	1.0	3.0	0.0	0.0	- 1
13	1.0	2.0	1.0	- 1.0	- 1.0	0
14	4.0	- 12.0	9.0	1.5	1.5	0
15	1.0	- 2.0	- 3.0	3.0	- 1.0	0
16	1.0	1.0	4.0	0.0	0.0	- 1

Which one of the following options provide the set of non-redundant tests using equivalence class partitioning approach from input perspective for black box testing?

(A) T1, T2, T3, T6

(B) T1, T3, T4, T5

(C) T2, T4, T5, T6

(D) T2, T3, T4, T5

ANSWER KEY

Software Engineering & Web Technology									
1	2	3	4	5	6				
(A)	(B)	(D)	(D)	(C)	(C)				