

Cloud Computing

Assignment 2

Name: Nayab Khazin

Registration number: 2023-BSE-046

Submitted to: Sir Waqas Saleem

Semester: 5-B

Contents

| | |
|---|----|
| 1. Summary | 3 |
| 2. Architecture Design | 3 |
| 2.1 Architecture Overview | 3 |
| 2.2 Architecture Diagram | 3 |
| 2.3 Component Descriptions | 4 |
| 2.4 Network Topology | 4 |
| 2.5 Security Design | 4 |
| 3. Implementation Details | 4 |
| Part 1: Infrastructure Setup | 4 |
| Part 2: Webserver Module | 11 |
| Part 3: Server Scripts | 16 |
| Part 4: Deployment | 22 |
| Part 5: Testing and Verification | 27 |
| Part 6: Cleanup | 40 |
| 4. Testing Results | 46 |
| 4.1 Load Balancing Tests | 46 |
| 4.2 Cache Performance Tests | 47 |
| 4.3 High Availability Tests | 47 |
| 4.4 Security Tests | 47 |
| 4.5 Performance Metrics | 48 |
| 4.6 Summary of Testing Results | 48 |
| 5. Challenges & Solutions | 48 |
| 5.1 SSH Connectivity and Access Control Issues | 49 |
| 5.2 Backend Server Communication Failure | 49 |
| 5.3 Cache Header Visibility and Validation Issues | 49 |
| 5.4 Lessons Learned | 50 |
| 6. Conclusion | 50 |
| 7. Appendices | 51 |

1. Summary

In the assignment, focus is placed on the design of the multi-tier web environment in the Amazon Web Services (AWS) with the best practices of Infrastructure as Code (IaC) implemented through Terraform. The objective was to create a scalable secure highly available web

The system design involved an architecture using an Nginx reverse proxy which acted as a load balancer and multiple web servers in the back end.

The cloud infrastructure that has been deployed incorporates Virtual Private Cloud infrastructure, public subnets, security groups, EC2 instance configurations for both Nginx and Apache servers, as well as scripts to automatically configure the servers. Reusability and ease of maintenance are achieved through the implementation of modules from the Terraform tool in these setups.


Some key achievements on this project include implementing load balancing, caching, availability with a backup server, secure access with security groups, automated provisioning with Terraform, and resource cleanup following testing.

2. Architecture Design

2.1 Architecture Overview

This system is developed on Amazon Web Services using Terraform. In this system, it uses a three-tier architecture. That is for providing security. The processing of requests from the clients on the internet takes place through an Nginx server that handles reverse proxying, load balancing, SSL/TLS terminating, and cache management.

The Nginx server receives the incoming traffic and handles the requests by forwarding the requests to several Apache backend servers. The two servers act as the master servers, while the remaining server is configured as the standby server. The method aids in optimizing the efficiency and preventing the backend servers from being routed to the internet.



Architecture Diagram

This is evident from the design diagram where traffic is coming from the Internet through HTTP (80) or HTTPS (443) to NginxLoadBalancer. NginxLoadBalancer will then split this traffic to several back-end Apache Web Servers.

Web-1 and Web-2 act as backup servers in this case, while Web-3 is the backup node in the system. There is an indication of redundancy in routing requests in the system.

Component Descriptions

Nginx Server: Serves as a reverse proxy and load balancer. It provides functionality to encrypt and decrypt data with SSL/TLS, handles cache, and supports load balancing.

Web-1 and Web-2 (Primary Servers): Apache servers managing and serving content from applications. A number can be provided to increase availability and scalability.

Web-3 (Backup Server): To be used in cases where primary servers are down or overloaded.

VPC & Subnets: Ensure an isolated networking environment in AWS for all resources.

Security Groups: Define and manage the flow of incoming and outgoing traffic among system components.

Network Topology

EC2 instances run on a dedicated customized VPC. The running server of Nginx is located in a public subnet and receives traffic from the internet. The Backend Apache servers are secure; the servers only receive traffic from the Nginx servers as defined in the security groups. Such architecture patterns improve the security of the networks.

Designing Security

Security implements the principle of least privilege principle. The Nginx web server enables both HTTPS as well as HTTP connections from the outside environment, but the remaining servers are not reachable from the outside environment. SSH connectivity is provided just by the authorized IP addresses. Security Groups determine the

Their design encompasses internal communication between the modules, as well as encryption in SSL/TLS to safeguard client information.

Implementation Details

Part 1: Infrastructure Setup

Terraform was used to define the complete AWS infrastructure. The project follows a modular structure with separate files for networking, compute resources, variables, outputs, and locals.

Variables allow flexible configuration without modifying core code.

1.1

```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> tree /F
Folder PATH listing
Volume serial number is 3E30-6A77
C:.\
  .gitignore
  locals.tf
  main.tf
  outputs.tf
  README.md
  readme.txt
  terraform.tfvars
  variables.tf
  modules
    -networking
      main.tf
      outputs.tf
      variables.tf
    -security
      main.tf
      outputs.tf
      variables.tf
    -webserver
      main.tf
      outputs.tf
      variables.tf
  scripts
    apache-setup.sh
    nginx-setup.sh
```

```
.gitignore X  README.md ●
.gitignore
1  # Terraform files
2  .terraform/
3  *.tfstate
4  *.tfstate.backup
5  terraform.tfvars
6
7  # Sensitive data
8  *.pem
9  *.key
10
11 # Logs
12 *.log
13
14 # OS files
15 .DS_Store
16 Thumbs.db
17 |
```

1.2

```
.gitignore variables.tf X  README.md ●
modules > networking > variables.tf
1  # VPC CIDR Block
2  variable "vpc_cidr_block" {
3    description = "CIDR block for the VPC"
4    type        = string
5
6    validation {
7      condition = can(cidrnetmask(var.vpc_cidr_block))
8      error_message = "The VPC CIDR block must be a valid CIDR notation (e.g., 10.0.0.0/16)."
```

```
variables.tf
24 variable "availability_zone" {
27 }
28
29 # Environment Prefix
30 variable "env_prefix" {
31   description = "Environment prefix for resource naming (e.g., dev, prod)"
32   type       = string
33   default    = "dev"
34 }
35
36 # EC2 Instance Type
37 variable "instance_type" {
38   description = "EC2 instance type for web servers"
39   type       = string
40   default    = "t3.micro"
41 }
42
43 # Public SSH Key Path
44 variable "public_key" {
45   description = "Path to the public SSH key"
46   type       = string
47 }
48
49 # Private SSH Key Path
50 variable "private_key" {
51   description = "Path to the private SSH key"
52   type       = string
53 }
54
55 # Backend Servers Configuration
56 variable "backend_servers" {
57   description = "List of backend servers with name and setup script path"
58   type       = list(object({
59     name       = string
60     script_path = string
61   }))
62   default = []
63 }
64
```

```
terraform.tfvars
1 vpc_cidr_block    = "10.0.0.0/16"
2 subnet_cidr_block = "10.0.10.0/24"
3 availability_zone  = "me-central-1a"
4 env_prefix        = "prod"
5 instance_type     = "t3.micro"
6
7 public_key = "~/.ssh/id_ed25519.pub"
8 private_key = "~/.ssh/id_ed25519"
9
10 backend_servers = [
11   {
12     name       = "nginx-server"
13     script_path = "scripts/nginx-setup.sh"
14   },
15   {
16     name       = "apache-server"
17     script_path = "scripts/apache-setup.sh"
18   }
19 ]
20
```

1.3

```
.gitignore × variables.tf ...networking main.tf × outputs.tf
modules > networking > main.tf
1  # Create VPC
2  resource "aws_vpc" "this" {
3    cidr_block = var.vpc_cidr_block
4
5    tags = {
6      Name = "${var.env_prefix}-vpc"
7    }
8  }
9
10 # Create Public Subnet
11 resource "aws_subnet" "this" {
12   vpc_id            = aws_vpc.this.id
13   cidr_block        = var.subnet_cidr_block
14   availability_zone  = var.availability_zone
15   map_public_ip_on_launch = true
16
17   tags = {
18     Name = "${var.env_prefix}-public-subnet"
19   }
20 }
21
22 # Create Internet Gateway
23 resource "aws_internet_gateway" "this" {
24   vpc_id = aws_vpc.this.id
25
26   tags = {
27     Name = "${var.env_prefix}-igw"
28   }
29 }
30
31 # Create Route Table
32 resource "aws_route_table" "this" {
```

```
① readme.md main.tf ×
modules > networking > main.tf
21
22 # Create Internet Gateway
23 resource "aws_internet_gateway" "this" {
24     vpc_id = aws_vpc.this.id
25
26     tags = {
27         Name = "${var.env_prefix}-igw"
28     }
29 }
30
31 # Create Route Table
32 resource "aws_route_table" "this" {
33     vpc_id = aws_vpc.this.id
34
35     route {
36         cidr_block = "0.0.0.0/0"
37         gateway_id = aws_internet_gateway.this.id
38     }
39
40     tags = {
41         Name = "${var.env_prefix}-route-table"
42     }
43 }
44
45 # Associate Route Table with Subnet
46 resource "aws_route_table_association" "this" {
47     subnet_id      = aws_subnet.this.id
48     route_table_id = aws_route_table.this.id
49 }
50
```

```
🔍 .gitignore variables.tf ...networking main.tf outputs.tf
modules > networking > outputs.tf
1  output "vpc_id" {
2      description = "ID of the created VPC"
3      value       = aws_vpc.this.id
4  }
5
6  output "subnet_id" {
7      description = "ID of the created public subnet"
8      value       = aws_subnet.this.id
9  }
10
11 output "igw_id" {
12     description = "ID of the Internet Gateway"
13     value       = aws_internet_gateway.this.id
14 }
15
16 output "route_table_id" {
17     description = "ID of the route table"
18     value       = aws_route_table.this.id
19 }
20
```


1.4

```
modules > security > main.tf
1  # Nginx Security Group (Reverse Proxy / Load Balancer)
2  resource "aws_security_group" "nginx_sg" {
3      name          = "${var.env_prefix}-nginx-sg"
4      description   = "Security group for Nginx reverse proxy"
5      vpc_id        = var.vpc_id
6
7      # SSH from your IP only
8      ingress {
9          description = "SSH access"
10         from_port   = 22
11         to_port     = 22
12         protocol    = "tcp"
13         cidr_blocks = [var.my_ip]
14     }
15
16     # HTTP from anywhere
17     ingress {
18         description = "HTTP access"
19         from_port   = 80
20         to_port     = 80
21         protocol    = "tcp"
22         cidr_blocks = ["0.0.0.0/0"]
23     }
24
25     # HTTPS from anywhere
26     ingress {
27         description = "HTTPS access"
28         from_port   = 443
29         to_port     = 443
30         protocol    = "tcp"
31         cidr_blocks = ["0.0.0.0/0"]
32     }
33 }
```

```
① readme.md  main.tf  X
modules > security > main.tf
2  resource "aws_security_group" "nginx_sg" {
23
24
25      # HTTPS from anywhere
26      ingress {
27          description = "HTTPS access"
28          from_port   = 443
29          to_port     = 443
30          protocol    = "tcp"
31          cidr_blocks = ["0.0.0.0/0"]
32      }
33
34      # Allow all outbound traffic
35      egress {
36          from_port   = 0
37          to_port     = 0
38          protocol    = "-1"
39          cidr_blocks = ["0.0.0.0/0"]
40      }
41
42      tags = {
43          Name = "${var.env_prefix}-nginx-sg"
44      }
45  }
46
47  # Backend Security Group (Web Servers)
48  resource "aws_security_group" "backend_sg" {
49      name           = "${var.env_prefix}-backend-sg"
50      description    = "Security group for backend web servers"
51      vpc_id         = var.vpc_id
52
53      # SSH from your IP only
54      ingress {
55          description = "SSH access"
56          from_port   = 22
57          to_port     = 22
58          protocol    = "tcp"
59          cidr_blocks = [var.my_ip]
60      }
61  }
```

1.5

```

locals.tf
1 # Get public IP dynamically
2 data "http" "my_ip" {
3   url = "https://icanhazip.com"
4 }
5
6 locals {
7   # My public IP with /32
8   my_ip = "${chomp(data.http.my_ip.response_body)}/32"
9
10  # Common tags for all resources
11  common_tags = {
12    Environment = var.env_prefix
13    Project     = "Assignment-2"
14    ManagedBy   = "Terraform"
15  }
16
17  # Backend server configuration
18  backend_servers = [
19    {
20      name       = "web"
21      suffix     = "1"
22      script_path = "./scripts/apache-setup.sh"
23    },
24    {
25      name       = "web"
26      suffix     = "2"
27      script_path = "./scripts/apache-setup.sh"
28    },
29    {
30      name       = "web"
31      suffix     = "3"
32      script_path = "./scripts/apache-setup.sh"
33    }
34  ]

```

Part 2: Webserver Module

Reusable Terraform modules were created for web servers. Each module provisions an EC2 instance, attaches security groups, assigns key pairs, and executes user-data scripts for automatic configuration.

2.1

```

modules > webserver > variables.tf
1 variable "env_prefix" {
2   description = "Environment prefix for naming"
3   type       = string
4 }
5
6 variable "instance_name" {
7   description = "Base name of the EC2 instance"
8   type       = string
9 }
10
11 variable "instance_suffix" {
12   description = "Unique suffix for instance"
13   type       = string
14 }
15
16 variable "instance_type" {
17   description = "EC2 instance type"
18   type       = string
19 }
20
21 variable "availability_zone" {
22   description = "Availability zone"
23   type       = string
24 }
25
26 variable "vpc_id" {
27   description = "VPC ID"
28   type       = string
29 }
30
31 variable "subnet_id" {
32   description = "Subnet ID"
33 }

```

```
① readme.md variables.tf ×
modules > webserver > variables.tf
21 variable "availability_zone" {
22     type      = string
23 }
24
25
26 variable "vpc_id" {
27     description = "VPC ID"
28     type        = string
29 }
30
31 variable "subnet_id" {
32     description = "Subnet ID"
33     type        = string
34 }
35
36 variable "security_group_id" {
37     description = "Security group ID"
38     type        = string
39 }
40
41 variable "public_key" {
42     description = "Public SSH key path"
43     type        = string
44 }
45
46 variable "script_path" {
47     description = "User data script path"
48     type        = string
49 }
50
51 variable "common_tags" {
52     description = "Common tags for resources"
53     type        = map(string)
54 }
55
```

```
modules > webserver > main.tf
1  # Get latest Amazon Linux 2023 AMI
2  data "aws_ami" "amazon_linux" {
3      most_recent = true
4      owners      = ["amazon"]
5
6      filter {
7          name     = "name"
8          values   = ["al2023-ami-*-x86_64"]
9      }
10 }
11
12 # Create Key Pair (unique per instance)
13 resource "aws_key_pair" "this" {
14     key_name     = "${var.env_prefix}-${var.instance_name}-${var.instance_suffix}-key"
15     public_key   = file(var.public_key)
16
17     tags = var.common_tags
18 }
19
20 # Create EC2 Instance
21 resource "aws_instance" "this" {
22     ami                = data.aws_ami.amazon_linux.id
23     instance_type      = var.instance_type
24     availability_zone   = var.availability_zone
25     subnet_id          = var.subnet_id
26     vpc_security_group_ids = [var.security_group_id]
27     associate_public_ip_address = true
28     key_name           = aws_key_pair.this.key_name
29
30     user_data = file(var.script_path)
31
32     tags = merge(
33         var.common_tags,
34         {
35             Name = "${var.env_prefix}-${var.instance_name}-${var.instance_suffix}"
36         }
37     )
38 }
39
```

```

modules > webserver > outputs.tf
1  output "instance_id" {
2      description = "EC2 instance ID"
3      value       = aws_instance.this.id
4  }
5
6  output "public_ip" {
7      description = "Public IP of the EC2 instance"
8      value       = aws_instance.this.public_ip
9  }
10
11 output "private_ip" {
12     description = "Private IP of the EC2 instance"
13     value       = aws_instance.this.private_ip
14 }
15 |

```

2.2

```

main.tf
1  # -----
2  # Networking Module
3  # -----
4  module "networking" {
5      source = "../modules/networking"
6
7      vpc_cidr_block    = var.vpc_cidr_block
8      subnet_cidr_block = var.subnet_cidr_block
9      availability_zone = var.availability_zone
10     env_prefix        = var.env_prefix
11 }
12
13 # -----
14 # Security Module
15 # -----
16 module "security" {
17     source = "../modules/security"
18
19     vpc_id      = module.networking.vpc_id
20     env_prefix  = var.env_prefix
21     my_ip       = local.my_ip
22 }
23
24 # -----
25 # NGINX SERVER (1 INSTANCE)
26 # -----
27 module "nginx_server" {
28     source = "../modules/webserver"
29
30     env_prefix      = var.env_prefix
31     instance_name   = "nginx-proxy"
32     instance_suffix = "nginx"
33 }

```

```
1  readme.md  main.tf  X
main.tf
23
24  # -----
25  # NGINX SERVER (1 INSTANCE)
26  # -----
27  module "nginx_server" {
28      source = "../modules/webserver"
29
30      env_prefix      = var.env_prefix
31      instance_name   = "nginx-proxy"
32      instance_suffix = "nginx"
33      instance_type   = var.instance_type
34      availability_zone = var.availability_zone
35
36      vpc_id          = module.networking.vpc_id
37      subnet_id       = module.networking.subnet_id
38      security_group_id = module.security.nginx_sg_id
39
40      public_key = var.public_key
41      script_path = "../scripts/nginx-setup.sh"
42      common_tags = local.common_tags
43  }
44
45  # -----
46  # BACKEND SERVERS (3 INSTANCES)
47  # -----
48  module "backend_servers" {
49      for_each = {
50          for server in local.backend_servers :
51              "${server.name}-${server.suffix}" => server
52      }
53
54      source = "../modules/webserver"
55
56      env_prefix      = var.env_prefix
57      instance_name   = each.value.name
58      instance_suffix = each.value.suffix
59      instance_type   = var.instance_type
60      availability_zone = var.availability_zone
61
62      vpc_id          = module.networking.vpc_id
63      subnet_id       = module.networking.subnet_id
64      security_group_id = module.security.backend_sg_id
65
66      public_key = var.public_key
67      script_path = each.value.script_path
68      common_tags = local.common_tags
69  }
70
```


Part 3: Server Scripts

Shell scripts were used to configure servers automatically:

- **Apache Setup Script** installs Apache, starts the service, and deploys a sample web page.
- **Nginx Setup Script** configures reverse proxy rules, caching, and load balancing across backend servers.

Code snippets were embedded in the scripts directory and executed during instance initialization.

3.1




```
scripts > $ apache-setup.sh
1  #!/bin/bash
2  set -e
3
4  # -----
5  # Update system
6  # -----
7  yum update -y
8
9  # -----
10 # Install Apache
11 # -----
12 yum install httpd -y
13
14 # -----
15 # Start and enable Apache
16 # -----
17 systemctl start httpd
18 systemctl enable httpd
19
20 # -----
21 # Get metadata token (IMDSv2)
22 # -----
23 TOKEN=$(curl -s -X PUT "http://169.254.169.254/latest/api/token" \
24   -H "X-aws-ec2-metadata-token-ttl-seconds: 21600")
25
26 # -----
27 # Get instance metadata
28 # -----
29 PRIVATE_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
30   http://169.254.169.254/latest/meta-data/local-ipv4)
31
32 PUBLIC_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
```



```

scripts > 0 apache-setup.sh
29 PRIVATE_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
30 http://169.254.169.254/latest/meta-data/local-ipv4)
31
32 PUBLIC_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
33 http://169.254.169.254/latest/meta-data/public-ipv4)
34
35 PUBLIC_DNS=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
36 http://169.254.169.254/latest/meta-data/public-hostname)
37
38 HOSTNAME=$(hostname)
39
40 DEPLOY_TIME=$(date)
41
42 # -----
43 # Create HTML page
44 # -----
45 cat > /var/www/html/index.html <<EOF
46 <!DOCTYPE html>
47 <html>
48 <head>
49     <title>Backend Server</title>
50     <style>
51         body {
52             font-family: Arial;
53             background: #f0f0f0;
54             color: white;
55             padding: 40px;
56         }
57         .box {
58             background: rgba(255,255,255,0.1);
59             padding: 25px;
60             border-radius: 10px;
61         }
62         h1 { color: #ffd700; }
63         p { margin: 8px 0; }
64     </style>
65 </head>
66 <body>
67     <div class="box">
68         <h1>Backend Web Server</h1>
69         <p><b>Hostname:</b> $HOSTNAME</p>
70         <p><b>Private IP:</b> $PRIVATE_IP</p>
71         <p><b>Public IP:</b> $PUBLIC_IP</p>
72         <p><b>Public DNS:</b> $PUBLIC_DNS</p>
73         <p><b>Deployed At:</b> $DEPLOY_TIME</p>
74         <p><b>Status:</b> Active Backend Server</p>
75         <p><b>Managed By:</b> Terraform</p>
76     </div>
77 </body>
78 </html>
79 EOF
80
81 # -----
82 # Set permissions
83 # -----
84 chmod 644 /var/www/html/index.html
85
86 echo "Apache backend setup completed"
87

```



3.2

```
$ apache-setup.sh X $ nginx-setup.sh X main.tf ...webserver main.tf \ provider.tf
scripts > $ nginx-setup.sh
1  #!/bin/bash
2  set -e
3
4  # Update and install Nginx
5  yum update -y
6  yum install -y nginx openssl
7  systemctl start nginx
8  systemctl enable nginx
9
10 # Create SSL directories
11 mkdir -p /etc/ssl/private
12 mkdir -p /etc/ssl/certs
13
14 # Get metadata token
15 TOKEN=$(curl -s -X PUT "http://169.254.169.254/latest/api/token" \
16   -H "X-aws-ec2-metadata-token-ttl-seconds: 21600")
17
18 # Get public IP
19 PUBLIC_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
20   http://169.254.169.254/latest/meta-data/public-ipv4)
21
22 # Generate self-signed certificate
23 openssl req -x509 -nodes -days 365 -newkey rsa:2048 \
24   -keyout /etc/ssl/private/selfsigned.key \
25   -out /etc/ssl/certs/selfsigned.crt \
26   -subj "/CN=$PUBLIC_IP" \
27   -addext "subjectAltName=IP:$PUBLIC_IP" \
28   -addext "basicConstraints=CA:FALSE" \
29   -addext "keyUsage=digitalSignature,keyEncipherment" \
30   -addext "extendedKeyUsage=serverAuth"
31
32 echo "Self-signed certificate created for IP: $PUBLIC_IP"
```

```
① readme.md ② nginx-setup.sh X
scripts > ② nginx-setup.sh
23
34 # Backup original config
35 cp /etc/nginx/nginx.conf /etc/nginx/nginx.conf.bak
36
37 # Create Nginx configuration
38 # Note: Backend IPs will be added manually after deployment
39 cat > /etc/nginx/nginx.conf <<'EOF'
40 user nginx;
41 worker_processes auto;
42 error_log /var/log/nginx/error.log notice;
43 pid /run/nginx.pid;
44
45 events {
46     worker_connections 1024;
47 }
48
49 http {
50     # Logging
51     log_format main '$remote_addr - $remote_user [$time_local] "$request" '
52                     '$status $body_bytes_sent "$http_referer" '
53                     '"$http_user_agent" "$http_x_forwarded_for" '
54                     'Cache: $upstream_cache_status';
55
56     access_log /var/log/nginx/access.log main;
57
58     # Basic settings
59     sendfile on;
60     tcp_nopush on;
61     keepalive_timeout 65;
62     types_hash_max_size 4096;
63
64     include /etc/nginx/mime.types;
65     default_type application/octet-stream;
66
67     # Gzip compression
68     gzip on;
69     gzip_vary on;
70     gzip_types text/plain text/css application/json application/javascript text/xml application/xml;
71
72     # Cache configuration
73     proxy_cache_path /var/cache/nginx
74                     levels=1:2
75                     keys_zone=my_cache:10m
76                     max_size=1g
77                     inactive=60m
78                     use_temp_path=off;
79
80     # Upstream backend servers
81     # PLACEHOLDER: Update these IPs after deployment
82     upstream backend_servers {
83         # Primary servers (active load balancing)
84         server BACKEND_IP_1:80;
85         server BACKEND_IP_2:80;
86
87         # Backup server (only used when primary servers are down)
88         server BACKEND_IP_3:80 backup;
89     }
90
91     # HTTPS Server
```

```
① readme.md  $ nginx-setup.sh X
scripts > $ nginx-setup.sh
49 http {
82     upstream backend_servers {
83         # Set the backend servers here
84     }
85
86     # HTTPS Server
87     server {
88         listen 443 ssl http2;
89         server_name _;
90
91         # SSL Configuration
92         ssl_certificate /etc/ssl/certs/selfsigned.crt;
93         ssl_certificate_key /etc/ssl/private/selfsigned.key;
94         ssl_protocols TLSv1.2 TLSv1.3;
95         ssl_ciphers HIGH:!aNULL:!MD5;
96         ssl_prefer_server_ciphers on;
97
98         # Security Headers
99         add_header Strict-Transport-Security "max-age=31536000; includeSubDomains" always;
100        add_header X-Frame-Options "SAMEORIGIN" always;
101        add_header X-Content-Type-Options "nosniff" always;
102        add_header X-XSS-Protection "1; mode=block" always;
103
104        # Proxy settings
105        location / {
106            proxy_pass http://backend_servers;
107
108            # Proxy headers
109            proxy_set_header Host $host;
110            proxy_set_header X-Real-IP $remote_addr;
111            proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
112            proxy_set_header X-Forwarded-Proto $scheme;
113
114            # Cache settings
115            proxy_cache my_cache;
116            proxy_cache_valid 200 60m;
117            proxy_cache_valid 404 10m;
118            proxy_cache_key "$scheme$request_method$host$request_uri";
119            proxy_cache_bypass $http_cache_control;
120            add_header X-Cache-Status $upstream_cache_status;
121
122            # Timeouts
123            proxy_connect_timeout 60s;
124            proxy_send_timeout 60s;
125            proxy_read_timeout 60s;
126        }
127
128        # Health check endpoint
129        location /health {
130            access_log off;
131            return 200 "Nginx is healthy\n";
132            add_header Content-Type text/plain;
133        }
134    }
135
136    # HTTP Server (redirect to HTTPS)
137    server {
138        listen 80;
139        server_name _;
140    }
141}
```

```

138     }
139 }
140
141 # HTTP Server (redirect to HTTPS)
142 server {
143     listen 80;
144     server_name _;
145
146     location / {
147         return 301 https://$host$request_uri;
148     }
149
150     # Allow health checks over HTTP
151     location /health {
152         access_log off;
153         return 200 "Nginx is healthy\n";
154         add_header Content-Type text/plain;
155     }
156 }
157 }
158 EOF
159
160 # Create cache directory
161 mkdir -p /var/cache/nginx
162 chown -R nginx:nginx /var/cache/nginx
163
164 # Test and restart Nginx
165 nginx -t && systemctl restart nginx
166
167 echo "Nginx setup completed successfully!"
168 echo "Remember to update backend server IPs in /etc/nginx/nginx.conf"

```

Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to nginx.org.
Commercial support is available at nginx.com.

Thank you for using nginx.

Part 4: Deployment

Infrastructure deployment was performed using standard Terraform commands:

- terraform init
- terraform validate
- terraform plan
- terraform apply

The deployment process successfully created all AWS resources, which were verified through the AWS Management Console.

4.1

```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> ssh-keygen -t ed25519 -f terraform-key -C "terraform"
Generating public/private ed25519 key pair.
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in terraform-key
Your public key has been saved in terraform-key.pub
The key fingerprint is:
SHA256:C6e9SY1C7nM2q0dLs3MyhsMtelGlf+N93JuR2aVWFHY terraform
The key's randomart image is:
+--[ED25519 256]--+
|                 oE|
|      .   .   o|
|      o   .  -|
|      o   .  -|
|     o.S.   o|
|    o.=++.. o o=|
|   .+*=+.o oo=o|
|  .Bo&o. ... *|
| .ooX+B   +. |
+-----[SHA256]-----+
PS C:\Users\tehre\OneDrive\Desktop\Assignment2>
```

```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> & "C:\Program Files\Terraform\terraform.exe" init
Initializing the backend...
Initializing modules...
Initializing provider plugins...
- Reusing previous version of hashicorp/aws from the dependency lock file
- Reusing previous version of hashicorp/http from the dependency lock file
- Using previously-installed hashicorp/aws v6.27.0
- Using previously-installed hashicorp/http v3.5.0

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
PS C:\Users\tehre\OneDrive\Desktop\Assignment2>
```

```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> & "C:\Program Files\Terraform\terraform.exe" validate
● Success! The configuration is valid.
```

```

PS C:\Users\tehre\OneDrive\Desktop\Assignment2> & "C:\Program Files\Terraform\terraform.exe" plan
data.http.my_ip: Reading...
data.http.my_ip: Read complete after 0s [id=https://icanhazip.com]
module.backend_servers["web-1"].data.aws_ami.amazon_linux: Reading...
module.backend_servers["web-3"].data.aws_ami.amazon_linux: Reading...
module.backend_servers["web-3"].aws_key_pair.this: Refreshing state... [id=prod-web-3-key]
module.nginx_server.data.aws_ami.amazon_linux: Reading...
module.backend_servers["web-1"].aws_key_pair.this: Refreshing state... [id=prod-web-1-key]
module.backend_servers["web-2"].data.aws_ami.amazon_linux: Reading...
module.backend_servers["web-2"].aws_key_pair.this: Refreshing state... [id=prod-web-2-key]
module.networking.aws_vpc.this: Refreshing state... [id=vpc-0d386fa295b017308]
module.nginx_server.aws_key_pair.this: Refreshing state... [id=prod-nginx-proxy-nginx-key]
module.backend_servers["web-3"].data.aws_ami.amazon_linux: Read complete after 2s [id=ami-005474a5a2e71202a]
module.nginx_server.data.aws_ami.amazon_linux: Read complete after 2s [id=ami-005474a5a2e71202a]
module.backend_servers["web-1"].data.aws_ami.amazon_linux: Read complete after 2s [id=ami-005474a5a2e71202a]
module.backend_servers["web-2"].data.aws_ami.amazon_linux: Read complete after 2s [id=ami-005474a5a2e71202a]
module.networking.aws_internet_gateway.this: Refreshing state... [id=igw-040a077e3c5dab955]
module.networking.aws_subnet.this: Refreshing state... [id=subnet-0d36175e32b2ad765]
module.security.aws_security_group.nginx_sg: Refreshing state... [id=sg-0620c6f4dc900a29e]
module.networking.aws_route_table.this: Refreshing state... [id=rtb-017fa5558e5e25b03]
module.security.aws_security_group.backend_sg: Refreshing state... [id=sg-01cf213ada86c4c3e]
module.networking.aws_instance.this: Refreshing state... [id=i-010c2dec0a4549cce]
module.networking.aws_route_table_association.this: Refreshing state... [id=rtbassoc-0f679574d1ce4c298]
module.backend_servers["web-3"].aws_instance.this: Refreshing state... [id=i-0f926aa7c23b4f18a]
module.backend_servers["web-1"].aws_instance.this: Refreshing state... [id=i-0f5dcc205f2354849]
module.backend_servers["web-2"].aws_instance.this: Refreshing state... [id=i-0be59f83fde56c21d]

```

Apply complete! Resources: 0 added, 2 changed, 0 destroyed.

Outputs:

```

backend_public_ips = {
  "web-1" = "51.20.116.132"
  "web-2" = "13.60.253.182"
  "web-3" = "51.20.189.98"
}

```

```

PS C:\Users\tehre\OneDrive\Desktop\Assignment2>

```

4.2

```

=====
DEPLOYMENT SUCCESSFUL!
=====
Next Steps:
1. SSH into Nginx server:
  ssh ec2-user@13.60.253.160

2. Edit Nginx config:
  sudo vim /etc/nginx/nginx.conf

3. Update backend IPs in upstream block:
  - BACKEND_IP_1: 10.0.10.241
  - BACKEND_IP_2: 10.0.10.47
  - BACKEND_IP_3: 10.0.10.173

4. Restart Nginx:
  sudo systemctl restart nginx

5. Test in browser:
  https://13.60.253.160

Backend Servers:
- web-1: 51.20.116.132 (private: 10.0.10.241)
- web-2: 13.60.253.182 (private: 10.0.10.47)
- web-3: 51.20.189.98 (private: 10.0.10.173)

=====

EOT
nginx_instance_id = "i-010c2dec0a4549cce"
nginx_public_ip = "13.60.253.160"
subnet_id = "subnet-0d36175e32b2ad765"
vpc_id = "vpc-0d386fa295b017308"

```



```

$ apache-setup.sh  $ nginx-setup.sh  outputs.tf  outputs.json  main.tf ...webserver
() outputs.json > {} backend_servers_info > {} type > {} 1 > {} web-1 > {} 1
1
2   {
3     "backend_public_ips": {
4       "sensitive": false,
5       "type": [
6         "object",
7         {
8           "web-1": "string",
9           "web-2": "string",
10          "web-3": "string"
11        }
12      ],
13      "value": {
14        "web-1": "51.20.116.132",
15        "web-2": "13.60.253.182",
16        "web-3": "51.20.189.98"
17      }
18    },
19    "backend_servers_info": {
20      "sensitive": false,
21      "type": [
22        "object",
23        {
24          "web-1": [
25            "object",
26            {
27              "instance_id": "string",
28              "private_ip": "string",
29              "public_ip": "string"
30            }
31          ],
32          "web-2": [
33            "object",
34            {
35              "instance_id": "string",
36              "private_ip": "string",
37              "public_ip": "string"
38            }
39          ],
40          "web-3": [
41            "object",

```

```

() outputs.json > {} backend_servers_info > {} type > {} 1 > {} web-3 > {} 1 > ** public_ip
18   "backend_servers_info": {
19     "type": [
20       "object",
21       {
22         "web-1": [
23           "object",
24           {
25             "instance_id": "string",
26             "private_ip": "string",
27             "public_ip": "string"
28           }
29         ],
30         "web-2": [
31           "object",
32           {
33             "instance_id": "string",
34             "private_ip": "string",
35             "public_ip": "string"
36           }
37         ],
38         "web-3": [
39           "object",
40           {
41             "instance_id": "string",
42             "private_ip": "string",
43             "public_ip": "string"
44           }
45         ]
46       }
47     ],
48     "value": {
49       "web-1": {
50         "instance_id": "i-0f5dccc205f2354849",
51         "private_ip": "10.0.10.241",
52         "public_ip": "51.20.116.132"
53       },
54       "web-2": {
55         "instance_id": "i-0be59f83fde56c21d",
56         "private_ip": "10.0.10.47",
57         "public_ip": "13.60.253.182"
58       },
59       "web-3": {
60         "instance_id": "i-0f926aa7c23b4f18a",
61         "private_ip": "10.0.10.173",
62         "public_ip": "51.20.189.98"
63       }
64     }
65   },
66 }

```

```
18 "backend_servers_info": {
20   "type": [
47   ],
48 },
49 "value": {
50   "web-1": {
51     "instance_id": "i-0f5dccc285f2354849",
52     "private_ip": "10.0.10.241",
53     "public_ip": "51.20.116.132"
54   },
55   "web-2": {
56     "instance_id": "i-0be59f83fde56c21d",
57     "private_ip": "10.0.10.47",
58     "public_ip": "13.60.253.182"
59   },
60   "web-3": {
61     "instance_id": "i-0f926aa7c23b4f18a",
62     "private_ip": "10.0.10.173",
63     "public_ip": "51.20.189.98"
64   }
65 },
66 },
67 "configuration_guide": {
68   "sensitive": false,
69   "type": "string",
70   "value": "\n\n===== \n\nDEPLOYMENT SUCCESSFUL \n\n===== \n\n\nNext Steps: \n\n1. SSH into Nginx server: \n\n  ssh e
71 },
72 "nginx_instance_id": {
73   "sensitive": false,
74   "type": "string",
75   "value": "i-018c2dec0a4549cce"
76 },
77 "nginx_public_ip": {
78   "sensitive": false,
79   "type": "string",
80   "value": "13.60.253.160"
81 },
82 "subnet_id": {
83   "sensitive": false,
84   "type": "string",
85   "value": "subnet-0d36175e32b2ad765"
86 },
87 "vpc_id": {
88   "sensitive": false,
89   "type": "string",
90   "value": "vpc-0d386fa295b017308"
91 }
92 }
```

4.3

Your VPCs (2) Info

Last updated 2 minutes ago

Actions

Create VPC

| <input type="checkbox"/> | Name | VPC ID | State | Encryption c... | Encryption control ... |
|--------------------------|----------|---------------------------------------|-----------|-----------------|------------------------|
| <input type="checkbox"/> | - | vpc-0a84b0a16b588656c | Available | - | - |
| <input type="checkbox"/> | prod-vpc | vpc-0d386fa295b017308 | Available | - | - |

VPC > Subnets

Last updated 3 minutes ago

Actions

Create subnet

| <input checked="" type="checkbox"/> | Name | Subnet ID | State | VPC | Block Public... | IPv4 CIDR |
|-------------------------------------|--------------------|--|-----------|--|---------------------------|----------------|
| <input checked="" type="checkbox"/> | prod-public-subnet | subnet-0d36175e32b2ad765 | Available | vpc-0d386fa295b017308 pro... | <input type="radio"/> Off | 10.0.10.0/24 |
| <input type="checkbox"/> | - | subnet-0b6af2e2371958306 | Available | vpc-0a84b0a16b588656c | <input type="radio"/> Off | 172.31.16.0/20 |
| <input type="checkbox"/> | - | subnet-09bc1ed999032d85d | Available | vpc-0a84b0a16b588656c | <input type="radio"/> Off | 172.31.0.0/20 |
| <input type="checkbox"/> | - | subnet-024ff5a4191126916 | Available | vpc-0a84b0a16b588656c | <input type="radio"/> Off | 172.31.32.0/20 |

subnet-0d36175e32b2ad765 / prod-public-subnet

Subnet ID

[subnet-0d36175e32b2ad765](#)

IPv4 CIDR

10.0.10.0/24

Availability Zone

[eu-n1-az1 \(eu-north-1a\)](#)

Subnet ARN

[arn:aws:ec2:eu-north-1:754080462526:subnet/subnet-0d36175e32b2ad765](#)

Available IPv4 addresses

247

Network border group

State

Available

IPv6 CIDR

-

VPC

[vpc-0d386fa295b017308](#) | prod-vpc

Block Public Access

☐ Off

IPv6 CIDR association ID

-

Route table

[rtb-017fa558e5e25b03](#) | prod-route-table

VPC > Security Groups

Security Groups (4) info

Find security groups by attribute or tag

Name

Security group ID

Security group name

VPC ID

Description

Owner

Inbound rules count

-

sg-056f139a245fbaef2

default

vpc-0d386fa295b017308

default VPC se...

754080462526

1 Permission entry

-

sg-0918018d0c7dbd857

default

vpc-0a84b0a16b588656c

default VPC se...

754080462526

1 Permission entry

prod-backend-sg

sg-01cf213ada86cd43e

prod-backend-sg

vpc-0d386fa295b017308

Security group...

754080462526

2 Permission entries

prod-nginx-sg

sg-0620c6f4dc900a29e

prod-nginx-sg

vpc-0d386fa295b017308

Security group...

754080462526

3 Permission entries

EC2 > Instances

Instances (4) info

Find Instance by attribute or tag (case-sensitive)

Instance state = running

Clear filters

All states

Connect

Instance state

Actions

Launch instances

Name

Instance ID

Instance state

Instance type

Status check

Alarm status

Availability Zone

Public IPv4

prod-nginx-proxy-nginx

i-010c2dec0a4549cce

Running

t3.micro

3/3 checks passce

View alarms +

eu-north-1a

-

prod-web-2

i-0be59f83fde56c21d

Running

t3.micro

3/3 checks passce

View alarms +

eu-north-1a

-

prod-web-1

i-0f5dcc205f2354849

Running

t3.micro

3/3 checks passce

View alarms +

eu-north-1a

-

prod-web-3

i-0f926aa7c23b4f18a

Running

t3.micro

3/3 checks passce

View alarms +

eu-north-1a

-

Part 5: Testing and Verification

Testing included verifying load balancing behaviour, cache functionality, backup server availability, and security rules. Browser developer tools were used to inspect HTTP headers and confirm caching behaviour.

5.1


```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> ssh ec2-user@13.60.253.160
The authenticity of host '13.60.253.160 (13.60.253.160)' can't be established.
ED25519 key fingerprint is SHA256:AwJVTMA+H0rBmtZkZ4T3GbnG15ykVZqwck0pjVGc18.
This host key is known by the following other names/addresses:
    C:\Users\tehre\.ssh\known_hosts:10: 13.60.220.48
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '13.60.253.160' (ED25519) to the list of known hosts.
#_
~\ ####_
~\ #####\
~\ ###|
~\#/ ___ Amazon Linux 2023 (ECS Optimized)
~\~' '->
~\
~\
~\
~\m/'
```


```
# =====
# BACKEND SERVERS
# =====
upstream backend_servers {
    server 10.0.10.241:80;
    server 10.0.10.47:80;
    server 10.0.10.173:80 backup;
}
```

```
[ec2-user@ip-10-0-10-135 ~]$ sudo nginx -t
nginx: [warn] could not build optimal types_hash, you should increase either types_hash_max_size: 1024 or types_hash_bucket_size: 64; ignoring types_hash_bucket_size
nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
nginx: configuration file /etc/nginx/nginx.conf test is successful
```


```
[ec2-user@ip-10-0-10-135 ~]$ sudo systemctl restart nginx
[ec2-user@ip-10-0-10-135 ~]$ sudo systemctl status nginx
● nginx.service - The nginx HTTP and reverse proxy server
   Loaded: loaded (/usr/lib/systemd/system/nginx.service; enabled; preset: disabled)
   Active: active (running) since Sat 2025-12-27 21:41:53 UTC; 4s ago
     Process: 43514 ExecStartPre=/usr/bin/rm -f /run/nginx.pid (code=exited, status=0/SUCCESS)
     Process: 43515 ExecStartPre=/usr/sbin/nginx -t (code=exited, status=0/SUCCESS)
     Process: 43516 ExecStart=/usr/sbin/nginx (code=exited, status=0/SUCCESS)
    Main PID: 43517 (nginx)
      Tasks: 3 (limit: 1067)
     Memory: 3.1M
        CPU: 42ms
    CGroup: /system.slice/nginx.service
            └─43517 "nginx: master process /usr/sbin/nginx"
              └─43518 "nginx: worker process"
                └─43519 "nginx: worker process"
```

5.2






Response from WEB-1



Response from WEB-2



5.3

| × | Headers | Preview | Response | Initiator | Timing |
|---|--------------------|---------|------------------------------|---------------------------------|--------|
| | Remote Address | | | 13.60.253.160:80 | |
| | Referrer Policy | | | strict-origin-when-cross-origin | |
| | ▼ Response Headers | | <input type="checkbox"/> Raw | | |
| | Accept-Ranges | | | bytes | |
| | Connection | | | keep-alive | |
| | Content-Length | | | 29 | |
| | Content-Type | | | text/html | |
| | Date | | | Sun, 28 Dec 2025 07:23:00 GMT | |
| | Etag | | | "695054e1-1d" | |
| | Last-Modified | | | Sat, 27 Dec 2025 21:51:29 GMT | |
| | Server | | | nginx/1.28.0 | |
| | X-Cache-Status | | | MISS | |

| × | Headers | Preview | Response | Initiator | Timing |
|---|------------------|---------|------------------------------|---------------------------------|--------|
| | Remote Address | | | 13.60.253.160:80 | |
| | Referrer Policy | | | strict-origin-when-cross-origin | |
| ▼ | Response Headers | | <input type="checkbox"/> Raw | | |
| | Accept-Ranges | | | bytes | |
| | Connection | | | keep-alive | |
| | Content-Length | | | 29 | |
| | Content-Type | | | text/html | |
| | Date | | | Sun, 28 Dec 2025 07:24:02 GMT | |
| | Etag | | | "695054e1-1d" | |
| | Last-Modified | | | Sat, 27 Dec 2025 21:51:29 GMT | |
| | Server | | | nginx/1.28.0 | |
| | X-Cache-Status | | | HIT | |

```
[ec2-user@ip-10-0-135 ~]$ sudo tail -n 20 /var/log/nginx/access.log
182.190.154.80 - [28/Dec/2025:58:52+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:56:59+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:00:32+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:08:46+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:11:53+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:03:42+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:06:09+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:06:39+0000] "GET / HTTP/1.1" 304 0 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:08:46+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:11:53+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:06:09+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:11:53+0000] "GET / HTTP/1.1" 304 0 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:13:30+0000] "HEAD / HTTP/1.1" 200 0 "-" curl/8.11.1"" Cache:MISS
curl/8.11.1"" Cache:HTT
182.190.154.80 - [28/Dec/2025:07:16:22+0000] "HEAD / HTTP/1.1" 200 0 "-" curl/8.11.1"" Cache:MSS
curl/8.11.1"" Cache:HTT
182.190.154.80 - [28/Dec/2025:07:16:35+0000] "HEAD / HTTP/1.1" 200 0 "-" curl/8.11.1"" Cache:HTT
curl/8.11.1"" Cache:MSS
182.190.154.80 - [28/Dec/2025:07:20:08+0000] "GET / HTTP/1.1" 200 29 "-" cypress.io/scanning/Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) Chrome/126.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:20:20+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:20:35+0000] "GET / HTTP/1.1" 200 29 "-" cypress.io/scanning/Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) Chrome/126.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:20:45+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:MSS
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:24:02+0000] "GET / HTTP/1.1" 200 29 "-" Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0 Safari/537.36 "" Cache:HTT
Cache:HTT
182.190.154.80 - [28/Dec/2025:07:24:17+0000] "xvdcbaabxlvdb8vxdb3ydvbfvAFVcfFjYdAyxvB8MvdU1xi7bzxyvDUQvcJfCdfVfcX14xf1wPdyf80vxbvs8j"wf5vf87vbxvD0vb0vxd1AvCbXvLcDbxvCh1x1vCBxvD07kvCx13vCBxvD09kvX
GVAkxvD09kvX [28/Dec/2025:07:25:14+0000] "" 400 0 "-" Cache:-
```

5.4


```
[ec2-user@ip-10-0-10-241 ~]$ sudo systemctl stop httpd
[ec2-user@ip-10-0-10-241 ~]$ sudo systemctl stop httpd
[ec2-user@ip-10-0-10-241 ~]$ sudo systemctl status httpd
o httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
   Active: inactive (dead) since Sat 2025-12-27 21:50:12 UTC; 9h ago
     Duration: 2h 46min 25.759s
       Docs: man:httpd.service(8)
    Main PID: 2095 (code=exited, status=0/SUCCESS)
      Status: "Total requests: 5; Idle/Busy workers 100/0;Requests/sec: 0.000501; Bytes served/sec: 0 B/sec"
        CPU: 8.570s

Dec 27 19:03:45 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: Starting httpd.service - The Apache HTTP Server...
Dec 27 19:03:45 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: Started httpd.service - The Apache HTTP Server.
Dec 27 19:03:45 ip-10-0-10-241.eu-north-1.compute.internal httpd[2095]: Server configured, listening on: port 80
Dec 27 21:50:11 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: Stopping httpd.service - The Apache HTTP Server...
Dec 27 21:50:12 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: httpd.service: Deactivated successfully.
Dec 27 21:50:12 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: Stopped httpd.service - The Apache HTTP Server.
Dec 27 21:50:12 ip-10-0-10-241.eu-north-1.compute.internal systemd[1]: httpd.service: Consumed 8.570s CPU time.
[ec2-user@ip-10-0-10-241 ~]$
```

← → ↻ ⚠ Not secure 13.60.253.160

🔍 | 🖥 User Account - Hac...

BACKUP SERVER - WEB-3

```
[ec2-user@ip-10-0-10-135 ~]$ sudo tail -20 /var/log/nginx/error.log
2025/12/28 07:36:12 [notice] 526817#526817: signal 17 (SIGCHLD) received from 560085
2025/12/28 07:36:12 [notice] 526817#526817: cache manager process 560085 exited with code 0
2025/12/28 07:36:12 [notice] 526817#526817: exit
2025/12/28 07:36:12 [notice] 572554#572554: using the "epoll" event method
2025/12/28 07:36:12 [notice] 572554#572554: nginx/1.28.0
2025/12/28 07:36:12 [notice] 572554#572554: OS: Linux 6.1.158-180.294.amzn2023.x86_64
2025/12/28 07:36:12 [notice] 572554#572554: getrlimit(RLIMIT_NOFILE): 65535:65535
2025/12/28 07:36:12 [notice] 572555#572555: start worker processes
2025/12/28 07:36:12 [notice] 572555#572555: start worker process 572556
2025/12/28 07:36:12 [notice] 572555#572555: start worker process 572557
2025/12/28 07:36:12 [notice] 572555#572555: start cache manager process 572558
2025/12/28 07:36:12 [notice] 572555#572555: start cache loader process 572559
2025/12/28 07:37:12 [notice] 572559#572559: http file cache: /var/cache/nginx 0.004M, bsize: 4096
2025/12/28 07:37:12 [notice] 572555#572555: signal 17 (SIGCHLD) received from 572559
2025/12/28 07:37:12 [notice] 572555#572555: cache loader process 572559 exited with code 0
2025/12/28 07:37:12 [notice] 572555#572555: signal 29 (SIGIO) received
2025/12/28 08:04:33 [error] 572557#572557: *15 connect() failed (111: Connection refused) while connecting to upstream, client: 182.190.154.89, server: _, request: "GET / HTTP/1.1"
, upstream: "http://10.0.10.241:80/", host: "13.60.253.160"
2025/12/28 08:04:33 [warn] 572557#572557: *15 upstream server temporarily disabled while connecting to upstream, client: 182.190.154.89, server: _, request: "GET / HTTP/1.1", upstr
eam: "http://10.0.10.241:80/", host: "13.60.253.160"
2025/12/28 08:43:30 [error] 572557#572557: *23 connect() failed (111: Connection refused) while connecting to upstream, client: 204.76.203.212, server: _, request: "GET / HTTP/1.1"
, upstream: "http://10.0.10.241:80/", host: "13.60.253.160:80"
2025/12/28 08:43:30 [warn] 572557#572557: *23 upstream server temporarily disabled while connecting to upstream, client: 204.76.203.212, server: _, request: "GET / HTTP/1.1", upstr
eam: "http://10.0.10.241:80/", host: "13.60.253.160:80"
[ec2-user@ip-10-0-10-135 ~]$
```



```

PS C:\Users\tehre\OneDrive\Desktop\Assignment2> ssh ec2-user@13.60.253.160
---
SSL handshake has read 1499 bytes and written 382 bytes
Verification error: self-signed certificate
---
New, TLSv1.3, Cipher is TLS_AES_256_GCM_SHA384
Server public key is 2048 bit
This TLS version forbids renegotiation.
Compression: NONE
Expansion: NONE
No ALPN negotiated
Early data was not sent
Verify return code: 18 (self-signed certificate)
---
---
Post-Handshake New Session Ticket arrived:
SSL-Session:
    Protocol : TLSv1.3
    Cipher : TLS_AES_256_GCM_SHA384
    Session-ID: 085289EDBEA9231C09E9931F6B3EE5EBAFE0CF864C6A38C70DFCDE07A1134957
    Session-ID-ctx:
    Resumption PSK: DAC5D384B853D43F834D4D33993411BA732D36B298412541AC425CBCB4ACFCA5F7E433AD243292DCB1B899AB65C11134
    PSK identity: None
    PSK identity hint: None
    SRP username: None
    TLS session ticket lifetime hint: 300 (seconds)
    TLS session ticket:
    0000 - 47 c0 4e 06 e7 00 aa 39-96 5f cc c8 55 f5 7d 3d G.N....9...U.)=
    0010 - 9c 86 62 24 f6 35 07 ed-5b d0 f6 a7 f2 63 46 88 ..b$.5..[....cF.
    0020 - 03 eb e5 f4 1e 20 2f 51-87 70 9b f5 c5 b8 77 b6 ...../Q.p....w.
    0030 - 33 a9 39 10 d3 64 60 f5-90 ac 7c 54 9c c1 1f 77 3.9..d'...|T...w
    0040 - ab 7f 65 0e 7c 69 73 09-7e b1 2a 2b b6 67 48 19 ..e.|is.~.*+.gH.
    0050 - d0 c4 25 0e da c9 c3 60-26 32 77 41 13 89 35 8a ..%....`82wA..S.
    0060 - af a2 bb a7 01 5f a4 74-c9 1f 16 fb 6b 1a 24 3a .....t....k.$:
    0070 - bb ef d7 b5 b3 52 8c f8-c1 fd 7a c3 7f 3c 2a 8a .....R.....z.<*.
    0080 - fe cb 6d f2 72 9e 1f 86-04 e0 9f 8e ff 37 22 57 ..m.r.....7"W
    0090 - a6 3e d6 b8 69 81 15 50-58 d6 54 c8 e2 2c 76 40 .>..i..PX.T...v@
    00a0 - 13 d3 14 ea 7e e6 6c 38-b9 e5 02 8b de e8 89 45 ....~.18.....E
    00b0 - 1a 75 a0 8c 59 0a 8e dd-d7 72 b9 ca 43 fe 35 be .u..Y....r..C.S.
    00c0 - f4 78 97 e4 bf a8 13 df-ff 17 4b 08 71 c5 d5 f2 .x.....K.q...
    00d0 - 0c 7b e1 6d cc 35 8a 07-83 ed 51 bf 92 53 18 54 .{.m.5....Q..S.T

    Start Time: 1766921631
    Timeout : 7200 (sec)
    Verify return code: 18 (self-signed certificate)
    Extended master secret: no
    Max Early Data: 0
---
read R BLOCK

```

```

PS C:\Users\tehre\OneDrive\Desktop\Assignment2> ssh ec2-user@13.60.253.160
Extended master secret: no
Max Early Data: 0
---
read R BLOCK
---
Post-Handshake New Session Ticket arrived:
SSL-Session:
    Protocol : TLSv1.3
    Cipher   : TLS_AES_256_GCM_SHA384
    Session-ID: C07FC7F3A0DD08D1ADA7094E849005C8231BA2B8AE162E33AFFE0841E1AE6007
    Session-ID-ctx:
    Resumption PSK: 8D178DD8EF61058FF44CEA0958F16FFD52C8D778DEC069C8A2BE15222576E5188C34BFD846376A23B2730714E835A5D3
    PSK identity: None
    PSK identity hint: None
    SRP username: None
    TLS session ticket lifetime hint: 300 (seconds)
    TLS session ticket:
0000 - 47 c0 4e 06 e7 00 aa 39-96 5f cc c8 55 f5 7d 3d   G.N....9...U.)=
0010 - be 8f 94 6a e0 03 99 84-fa 06 c5 c0 6a 49 03 d1   ...j.....jI..
0020 - 82 b6 8c 1e 79 30 f5 84-1e ee bd 7a 92 a2 d0 e3   ....y0.....z...
0030 - 72 67 dd 5d db 13 6f 8d-37 53 6c 57 89 5a 1f fd   rg.]...o.7S1W.Z..
0040 - b9 7c 53 b1 62 09 54 ff-f5 4b 73 8b 0a 92 dd 0b   .|S.b.T..Ks....
0050 - ef 85 10 69 ff d1 c8 41-25 a4 1e 16 0b 96 51 07   ...i...A%.....Q.
0060 - f1 1f 69 a9 f1 e4 86 6b-60 ce 86 95 11 ec 23 cc   ...i...k'.....#.
0070 - a5 e9 dc 4a d3 ea f5 25-21 17 67 82 62 6d 3f d0   ...J...%!.g.bm?.
0080 - 03 b7 08 d3 a9 a5 4a 16-dd f6 6f 25 e8 02 97 03   .....J...o%....
0090 - 24 f7 24 08 42 7c e4 b6-b1 bd 9f 06 be 67 61 ce   $.$.B|.....ga.
00a0 - 70 ec a1 4f 2b 7c 3d 38-aa a9 87 3a a3 fe 4b 2b   p..0+|=8.....K+
00b0 - cc 2f 36 78 07 d5 5d 52-9a d1 57 b2 e5 f9 df 45   ./6x..]R...W....E
00c0 - d3 97 1f 79 a8 d6 30 2d-05 0f a7 c6 40 a7 a4 14   ...y..0-....@...
00d0 - a0 f1 a3 97 fa 0f 6f 70-d5 e1 02 82 0b e3 e1 f0   .....op.....

    Start Time: 1766921631
    Timeout : 7200 (sec)
    Verify return code: 18 (self-signed certificate)
    Extended master secret: no
    Max Early Data: 0
---
read R BLOCK
closed
[ec2-user@ip-10-0-10-135 ~]$

```

```

[ec2-user@ip-10-0-10-135 ~]$ curl -I -k https://13.60.253.160
HTTP/1.1 200 OK
Server: nginx/1.28.0
Date: Sun, 28 Dec 2025 13:46:20 GMT
Content-Type: text/html
Content-Length: 31
Connection: keep-alive
Last-Modified: Sun, 28 Dec 2025 08:04:12 GMT
ETag: "6950e47c-1f"
X-Cache-Status: EXPIRED
Accept-Ranges: bytes

[ec2-user@ip-10-0-10-135 ~]$

```

```
[ec2-user@ip-10-0-10-135 ~]$ curl -I http://13.60.253.160
HTTP/1.1 301 Moved Permanently
Server: nginx/1.28.0
Date: Sun, 28 Dec 2025 13:48:59 GMT
Content-Type: text/html
Content-Length: 169
Connection: keep-alive
Location: https://13.60.253.160/

[ec2-user@ip-10-0-10-135 ~]$
```

```
PS C:\Users\tehre\OneDrive\Desktop\Assignment2> ssh ec2-user@13.60.253.160
2025/12/28 09:15:20 [notice] 572555#572555: signal 17 (SIGCHLD) received from 572557
2025/12/28 09:15:20 [notice] 572555#572555: worker process 572556 exited with code 0
2025/12/28 09:15:20 [notice] 572555#572555: worker process 572557 exited with code 0
2025/12/28 09:15:20 [notice] 572555#572555: signal 29 (SIGIO) received
2025/12/28 09:15:20 [notice] 572555#572555: signal 17 (SIGCHLD) received from 572558
2025/12/28 09:15:20 [notice] 572555#572555: cache manager process 572558 exited with code 0
2025/12/28 09:15:20 [notice] 572555#572555: exit
2025/12/28 09:15:20 [warn] 660615#660615: could not build optimal types_hash, you should increase either types_hash_max_size: 1024 or types_hash_bucket_size: 64; ignoring types_hash_bucket_size
2025/12/28 09:15:20 [emerg] 660615#660615: cannot load certificate "/etc/ssl/certs/selfsigned.crt": BIO_new_file() failed (SSL: error:80000002:system library::No such file or directory:calling fopen(/etc/ssl/certs/selfsigned.crt, r) error:10000080:BIO routines::no such file)
2025/12/28 09:15:49 [warn] 661095#661095: could not build optimal types_hash, you should increase either types_hash_max_size: 1024 or types_hash_bucket_size: 64; ignoring types_hash_bucket_size
2025/12/28 09:15:49 [emerg] 661095#661095: cannot load certificate "/etc/ssl/certs/selfsigned.crt": BIO_new_file() failed (SSL: error:80000002:system library::No such file or directory:calling fopen(/etc/ssl/certs/selfsigned.crt, r) error:10000080:BIO routines::no such file)
2025/12/28 09:20:22 [emerg] 665168#665168: cannot load certificate "/etc/ssl/certs/selfsigned.crt": BIO_new_file() failed (SSL: error:80000002:system library::No such file or directory:calling fopen(/etc/ssl/certs/selfsigned.crt, r) error:10000080:BIO routines::no such file)
2025/12/28 09:22:13 [emerg] 666833#666833: cannot load certificate "/etc/ssl/certs/selfsigned.crt": BIO_new_file() failed (SSL: error:80000002:system library::No such file or directory:calling fopen(/etc/ssl/certs/selfsigned.crt, r) error:10000080:BIO routines::no such file)
2025/12/28 11:32:55 [notice] 782464#782464: using the "epoll" event method
2025/12/28 11:32:55 [notice] 782464#782464: nginx/1.28.0
2025/12/28 11:32:55 [notice] 782464#782464: OS: Linux 6.1.158-180.294.amzn2023.x86_64
2025/12/28 11:32:55 [notice] 782464#782464: getrlimit(RLIMIT_NOFILE): 65535:65535
2025/12/28 11:32:55 [notice] 782493#782493: start worker processes
2025/12/28 11:32:55 [notice] 782493#782493: start worker process 782494
2025/12/28 11:32:55 [notice] 782493#782493: start worker process 782495
2025/12/28 11:32:55 [notice] 782493#782493: start cache manager process 782496
2025/12/28 11:32:55 [notice] 782493#782493: start cache loader process 782497
2025/12/28 11:33:55 [notice] 782497#782497: http file cache: /var/cache/nginx 0.004M, bsize: 4096
2025/12/28 11:33:55 [notice] 782493#782493: signal 17 (SIGCHLD) received from 782497
2025/12/28 11:33:55 [notice] 782493#782493: cache loader process 782497 exited with code 0
2025/12/28 11:33:55 [notice] 782493#782493: signal 29 (SIGIO) received
[ec2-user@ip-10-0-10-135 ~]$
```

```
[ec2-user@ip-10-0-10-135 ~]$ sudo tail -50 /var/log/nginx/access.log
182.190.154.89 - - [28/Dec/2025:07:53:35 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:53:35 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:53:35 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:56:29 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:59:12 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:59:13 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:59:14 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:07:59:14 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:08:04:33 +0000] "GET / HTTP/1.1" 200 31 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:EXPIRED
5.187.35.158 - - [28/Dec/2025:08:27:01 +0000] "GET /SDK/webLanguage HTTP/1.1" 404 3650 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.4430.85 Safari/537.36 Edg/90.0.818.46" "-" Cache:MISS
35.195.180.151 - - [28/Dec/2025:08:29:30 +0000] "GET / HTTP/1.1" 200 31 "-" "python-requests/2.32.5" "-" Cache:EXPIRED
204.76.203.212 - - [28/Dec/2025:08:43:30 +0000] "GET / HTTP/1.1" 200 31 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.4430.85 Safari/537.36 Edg/90.0.818.46" "-" Cache:EXPIRED
182.190.154.89 - - [28/Dec/2025:09:05:35 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:EXPIRED
182.190.154.89 - - [28/Dec/2025:09:05:36 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
182.190.154.89 - - [28/Dec/2025:09:09:37 +0000] "GET / HTTP/1.1" 304 0 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
```

Bonus tasks

Task 1

nginx error!

The page you are looking for is not found.

Website Administrator

Something has triggered missing webpage on your website. This is the default 404 error page for **nginx** that is distributed with Fedora. It is located
`/usr/share/nginx/html/404.html`

You should customize this error page for your own site or edit the `error_page` directive in the **nginx** configuration file `/etc/nginx/nginx.conf`.

NGINX NGINX

Task 2:

```
user nginx;
worker_processes auto;

error_log /var/log/nginx/error.log notice;
pid /run/nginx.pid;

events {
    worker_connections 1024;
}

http {
    include      /etc/nginx/mime.types;
    default_type application/octet-stream;

    sendfile      on;
    keepalive_timeout 65;

    # ----- Rate Limiting -----
    limit_req_zone $binary_remote_addr zone=mylimit:10m rate=2r/s;

    # ----- Proxy Cache -----
    proxy_cache_path /var/cache/nginx levels=1:2 keys_zone=mycache:10m
        max_size=100m inactive=10m use_temp_path=off;

    # ----- Upstream Backend -----
    upstream backend_servers {
        server 10.0.10.135:80;
    }

    server {
        listen 80;
        server_name _;

        # ----- Error Pages -----
        error_page 404 /errors/404.html;
        error_page 502 /errors/502.html;
        error_page 503 /errors/503.html;

        location = /errors/404.html {
            root /usr/share/nginx/html;
            internal;
        }
    }
}
```

```

server {
    listen 80;
    server_name _;

    # ----- Error Pages -----
    error_page 404 /errors/404.html;
    error_page 502 /errors/502.html;
    error_page 503 /errors/503.html;

    location = /errors/404.html {
        root /usr/share/nginx/html;
        internal;
    }

    location = /errors/502.html {
        root /usr/share/nginx/html;
        internal;
    }

    location = /errors/503.html {
        root /usr/share/nginx/html;
        internal;
    }

    # ----- Main Proxy -----
    location / {
        limit_req zone=mylimit burst=1 nodelay;
        limit_req_status 429;

        proxy_pass http://backend_servers;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;

        proxy_intercept_errors on;

        proxy_cache mycache;
        proxy_cache_valid 200 10m;
        add_header X-Cache-Status $upstream_cache_status always;
    }
}

```



```
HTTP/1.1 429 Too Many Requests
Server: nginx/1.28.0
Date: Sun, 28 Dec 2025 19:49:01 GMT
Content-Type: text/html
Content-Length: 169
Connection: keep-alive
X-Cache-Status: EXPIRED
X-Cache-Status: EXPIRED
```

```
HTTP/1.1 429 Too Many Requests
Server: nginx/1.28.0
Date: Sun, 28 Dec 2025 19:49:01 GMT
Content-Type: text/html
Content-Length: 169
Connection: keep-alive
X-Cache-Status: EXPIRED
X-Cache-Status: EXPIRED
```

```
HTTP/1.1 429 Too Many Requests
Server: nginx/1.28.0
Date: Sun, 28 Dec 2025 19:49:01 GMT
Content-Type: text/html
Content-Length: 169
Connection: keep-alive
```

```
HTTP/1.1 429 Too Many Requests
Server: nginx/1.28.0
```

Task 3

```
LOG_FILE="/var/log/backend_health.log"
TIMESTAMP=$(date "+%Y-%m-%d %H:%M:%S")

curl -s --max-time 5 http://localhost > /dev/null

if [ $? -eq 0 ]; then
    echo "$TIMESTAMP | Apache | UP" >> $LOG_FILE
else
    echo "$TIMESTAMP | Apache | DOWN" >> $LOG_FILE
    echo "$TIMESTAMP | ALERT: Apache is DOWN" >> $LOG_FILE

    systemctl restart httpd
    echo "$TIMESTAMP | ACTION: Apache restarted" >> $LOG_FILE
fi
```

```
[ec2-user@ip-10-0-10-47 ~]$ cat /var/log/backend_health.log
2025-12-28 19:57:01 | Apache | DOWN
2025-12-28 19:57:01 | ALERT: Apache is DOWN
2025-12-28 19:57:01 | ACTION: Apache restarted
2025-12-28 19:57:31 | Apache | UP
2025-12-28 19:58:02 | Apache | UP
[ec2-user@ip-10-0-10-47 ~]$
```

Part 6: Cleanup


All resources were destroyed using Terraform to avoid unnecessary AWS charges. The cleanup process removed EC2 instances, networking components, and security groups.

Command used:

```
terraform destroy
```

The Terraform state file confirmed that no resources remained.

6.1




```

① readme.md X
① readme.md > *# Assignment 2 -- Multi-Tier Web Infrastructure > *# Components Description > *# Backend Servers (Web-1, Web-2, Web-3)
1  # Assignment 2 -- Multi-Tier Web Infrastructure
44 ## Components Description
46 ### Nginx Server (Load Balancer)
47
48 - Entry point for all client traffic\
49 - Distributes requests to backend servers\
50 - Implements:
51   - Reverse proxy
52   - HTTP caching
53   - Rate limiting (429 responses)
54   - Custom error pages (404, 502, 503)
55
56 ### Backend Servers (Web-1, Web-2, Web-3)
57
58 - Run **Apache HTTP Server**
59 - Serve static web content
60 - Web-1 and Web-2 are **primary servers**
61 - Web-3 acts as a **backup server**
62
63 ### Terraform
64
65 - Infrastructure as Code (IaC) tool
66 - Automates provisioning of:
67   - EC2 instances
68   - Networking components
69   - Security groups
70
71 -----
72
73 ## Prerequisites
74
75 ### Required Tools
76
77 - Terraform
78 - AWS CLI
79 - SSH client
80 - Git
81
82 ### AWS Credentials Setup
83
84 Configure AWS credentials using:
85
86   aws configure
87
88 Provide AWS **Access Key**, **Secret Key**, **region**, and **output
89 format**.
90
91 ### SSH Key Setup
92

```

```

① readme.md X
① readme.md > ** # Assignment 2 -- Multi-Tier Web Infrastructure > ** ## Prerequisites
1  # Assignment 2 -- Multi-Tier Web Infrastructure
73 ## Prerequisites
82 ### AWS Credentials Setup
83
84 Configure AWS credentials using:
85
86     aws configure
87
88 Provide AWS **Access Key**, **Secret Key**, **region**, and **output
89 format**.
90
91 ### SSH Key Setup
92
93 Create or use an existing EC2 key pair:
94
95     chmod 400 key.pem
96
97 -----
98
99 ## Deployment Instructions
100
101 ### Step-by-Step Guide
102
103 Clone the repository:
104
105     git clone <repository-url>
106     cd Assignment2
107
108 Initialize Terraform:
109
110     terraform init
111
112 ### Variable Configuration
113
114 Edit 'terraform.tfvars':
115
116     region = "eu-north-1"
117     key_name = "my-key"
118
119 Validate configuration:
120
121     terraform validate
122
123 Deploy infrastructure:
124
125     terraform apply
126
127 Type **yes** when prompted.

```

```

1   # Assignment 2 -- Multi-Tier Web Infrastructure
99  ## Deployment Instructions
112 ### Variable Configuration
126
127 Type **yes** when prompted.
128
129 -----
130
131 ## Configuration Guide
132
133 ### How to Update Backend IPs
134
135 Edit Nginx upstream configuration:
136
137     upstream backend_servers {
138         server 10.0.10.135;
139         server 10.0.10.136;
140         server 10.0.10.137 backup;
141     }
142
143 Reload Nginx:
144
145     sudo systemctl reload nginx
146
147 ### Nginx Configuration Explanation
148
149 - 'proxy_pass' -- forwards requests to backend servers\
150 - 'proxy_cache' -- enables response caching\
151 - 'limit_req' -- enforces rate limiting\
152 - 'error_page' -- handles custom error responses
153
154 -----
155
156 ## Testing Procedures
157
158 ### Test Load Balancing
159
160     curl http://<nginx-public-ip>
161
162 ### Test Rate Limiting
163
164     seq 1 20 | xargs -n1 -P10 curl -I http://<nginx-public-ip>
165
166 ### Verify Cache
167
168 Check response headers for cache status.
169
170 -----

```

```

① readme.md X
① readme.md > ** # Assignment 2 -- Multi-Tier Web Infrastructure > ** ## Testing Procedures
1 # Assignment 2 -- Multi-Tier Web Infrastructure
156 ## Testing Procedures
166 ### Verify Cache
167
168 Check response headers for cache status.
169
170 -----
171
172 ## Architecture Details
173
174 ### Network Topology
175
176 - Single VPC
177 - Public subnet for Nginx
178 - Backend servers accessible only through Nginx
179
180 ### Security Groups Explanation
181
182 **Nginx Security Group** - Allow HTTP (80) - Allow SSH (22)
183
184 **Backend Security Group** - Allow HTTP from Nginx only - Allow SSH for
185 administration
186
187 ### Load Balancing Strategy
188
189 - Nginx round-robin load balancing
190 - Backup server activated if primary servers fail
191
192 -----
193
194 ## Troubleshooting
195
196 ### Common Issues and Solutions
197
198 **Backend not responding**
199 |
200 | sudo systemctl status httpd
201 |
202 **502 / 503 Errors** - Verify backend IP addresses - Ensure Apache is
203 running on backend servers
204
205 ### Log Locations
206
207 - Nginx access log: `/var/log/nginx/access.log`
208 - Nginx error log: `/var/log/nginx/error.log`
209 - Backend health log: `/var/log/backend_health.log`
210
211 ### Debug Commands
212

```

6.2

```

PS C:\Users\tehre\OneDrive\Desktop\Assignment2> & "C:\Program Files\Terraform\terraform.exe" destroy

```

```

module.networking.aws_internet_gateway.this: Still destroying... [id=igw-040a077e3c5dab955, 00m40s elapsed]
module.backend_servers["web-3"].aws_instance.this: Still destroying... [id=i-0f926aa7c23b4f18a, 00m50s elapsed]
module.backend_servers["web-2"].aws_instance.this: Still destroying... [id=i-0be59f83fde56c21d, 00m50s elapsed]
module.nginx_server.aws_instance.this: Still destroying... [id=i-010c2dec0a4549cce, 00m50s elapsed]
module.backend_servers["web-1"].aws_instance.this: Still destroying... [id=i-0f5dcc205f2354849, 00m50s elapsed]
module.networking.aws_internet_gateway.this: Still destroying... [id=igw-040a077e3c5dab955, 00m50s elapsed]
module.backend_servers["web-2"].aws_instance.this: Still destroying... [id=i-0be59f83fde56c21d, 01m00s elapsed]
module.backend_servers["web-3"].aws_instance.this: Still destroying... [id=i-0f926aa7c23b4f18a, 01m00s elapsed]
module.nginx_server.aws_instance.this: Still destroying... [id=i-010c2dec0a4549cce, 01m00s elapsed]
module.backend_servers["web-1"].aws_instance.this: Still destroying... [id=i-0f5dcc205f2354849, 01m00s elapsed]
module.networking.aws_internet_gateway.this: Still destroying... [id=igw-040a077e3c5dab955, 01m00s elapsed]
module.backend_servers["web-2"].aws_instance.this: Still destroying... [id=i-0be59f83fde56c21d, 01m10s elapsed]
module.backend_servers["web-3"].aws_instance.this: Still destroying... [id=i-0f926aa7c23b4f18a, 01m10s elapsed]
module.nginx_server.aws_instance.this: Still destroying... [id=i-010c2dec0a4549cce, 01m10s elapsed]
module.backend_servers["web-1"].aws_instance.this: Still destroying... [id=i-0f5dcc205f2354849, 01m10s elapsed]
module.networking.aws_internet_gateway.this: Still destroying... [id=igw-040a077e3c5dab955, 01m10s elapsed]
module.backend_servers["web-3"].aws_instance.this: Destruction complete after 1m13s
module.backend_servers["web-3"].aws_key_pair.this: Destroying... [id=prod-web-3-key]
module.backend_servers["web-2"].aws_instance.this: Destruction complete after 1m13s
module.backend_servers["web-2"].aws_key_pair.this: Destroying... [id=prod-web-2-key]
module.nginx_server.aws_instance.this: Destruction complete after 1m13s
module.nginx_server.aws_key_pair.this: Destroying... [id=prod-nginx-proxy-nginx-key]
module.backend_servers["web-3"].aws_key_pair.this: Destruction complete after 1s
module.backend_servers["web-2"].aws_key_pair.this: Destruction complete after 1s
module.nginx_server.aws_key_pair.this: Destruction complete after 1s
module.backend_servers["web-1"].aws_instance.this: Still destroying... [id=i-0f5dcc205f2354849, 01m20s elapsed]
module.networking.aws_internet_gateway.this: Still destroying... [id=igw-040a077e3c5dab955, 01m20s elapsed]
module.networking.aws_internet_gateway.this: Destruction complete after 1m20s
module.backend_servers["web-1"].aws_instance.this: Destruction complete after 1m24s
module.backend_servers["web-1"].aws_key_pair.this: Destroying... [id=prod-web-1-key]
module.security.aws_security_group.backend_sg: Destroying... [id=sg-01cf213ada86c4c3e]
module.networking.aws_subnet.this: Destroying... [id=subnet-0d36175e32b2ad765]
module.backend_servers["web-1"].aws_key_pair.this: Destruction complete after 0s
module.networking.aws_subnet.this: Destruction complete after 0s
module.security.aws_security_group.backend_sg: Destruction complete after 1s
module.security.aws_security_group.nginx_sg: Destroying... [id=sg-0620c6f4dc900a29e]
module.security.aws_security_group.nginx_sg: Destruction complete after 1s
module.networking.aws_vpc.this: Destroying... [id=vpc-0d386fa295b017308]
module.networking.aws_vpc.this: Destruction complete after 1s
Destroy complete! Resources: 15 destroyed.


```

```

PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS

PS C:\Users\tehre\OneDrive\Desktop\Assignment2> cat terraform.tfstate
{
  "version": 4,
  "terraform_version": "1.14.3",
  "serial": 51,
  "lineage": "e4ca0cbb-9b23-b3f0-a63d-f24593c5e21b",
  "outputs": {},
  "resources": [],
  "check_results": [
    {
      "object_kind": "var",
      "config_addr": "var.vpc_cidr_block",
      "status": "unknown",
      "objects": null
    },
    {
      "object_kind": "var",
      "config_addr": "var.subnet_cidr_block",
      "status": "unknown",
      "objects": null
    }
  ]
}
PS C:\Users\tehre\OneDrive\Desktop\Assignment2>

```



3. Testing Results

Testing was conducted to validate the correctness, reliability, performance, and security of the deployed cloud-based web architecture. The objective of this phase was to ensure that all core architectural goals—such as load balancing, caching efficiency, high availability, and secure access—were achieved successfully. Multiple functional and non-functional tests were performed on the deployed AWS infrastructure to evaluate real-world behavior under different conditions.

The testing process focused on five major areas: load balancing, cache performance, high availability, security, and performance metrics. Each test category is discussed in detail below, along with observations and outcomes.

3.1 Load Balancing Tests

The purpose of the load balancing tests was to verify that incoming client requests were distributed evenly across the available backend servers. The Nginx server was configured as a load balancer using a round-robin strategy, ensuring fair request distribution between Web-1 and Web-2.

To test this functionality, multiple HTTP requests were sent to the public IP address of the Nginx server using a web browser and command-line tools. Each backend Apache server was configured to display a unique identifier or hostname in the response message. This allowed easy identification of which backend server processed a particular request.

The results showed that consecutive requests were alternately handled by Web-1 and Web-2, confirming that the load balancer was functioning correctly. No single server was observed to receive a disproportionate number of requests under normal load conditions. This demonstrates that the system can efficiently distribute traffic and prevent overload on a single backend server.

Overall, the load balancing tests confirmed that the architecture supports horizontal scaling and improves fault tolerance by avoiding dependency on a single server.

3.2 Cache Performance Tests

Caching tests were performed to evaluate the effectiveness of the Nginx caching mechanism in improving response time and reducing backend server load. The cache was configured on the Nginx server to store frequently requested web content.

To verify caching behavior, browser developer tools were used to inspect HTTP response headers. The cache status was observed using the custom response header X-Cache-Status.

During the initial request to a web resource, the response header showed X-Cache-Status: MISS, indicating that the content was fetched from a backend Apache server and stored in the cache. Subsequent requests to the same resource returned X-Cache-Status: HIT, confirming that the response was served directly from the Nginx cache without contacting the backend servers.

This behavior demonstrates that caching was working as expected. The use of caching significantly reduced response times for repeated requests and decreased the processing load on backend servers. As a result, the system is more efficient and capable of handling higher traffic volumes.

3.3 High Availability Tests

High availability testing was conducted to ensure that the system remains operational even when one or more backend servers fail. This is a critical requirement for cloud-based systems where uninterrupted service is expected.

To test this scenario, one of the primary backend servers (Web-1 or Web-2) was manually stopped during active operation. While the server was offline, client requests were continuously sent to the Nginx server.

The results showed that traffic was automatically routed to the remaining available servers. When both primary servers were unavailable, the backup server (Web-3) successfully handled incoming requests. This confirms that the backup mechanism was correctly configured and that the Nginx server could dynamically route traffic based on server availability.

These results demonstrate that the architecture provides fault tolerance and ensures continuous service availability, even in the event of server failure.

3.4 Security Tests

Security testing focused on validating access control rules and ensuring that backend servers were protected from direct public access. AWS Security Groups were used as virtual firewalls to enforce network security policies.

Several security tests were performed, including attempting to directly access backend Apache servers using their public IP addresses. These attempts failed, confirming that

backend servers were not exposed to the internet and only accepted traffic from the Nginx server.

Additionally, SSH access was tested to verify that only authorized IP addresses could connect to EC2 instances. Unauthorized access attempts were blocked as expected. HTTP and HTTPS access were limited strictly to the Nginx server, reducing the overall attack surface.

The results confirm that the security configuration follows the principle of least privilege and effectively protects the infrastructure against unauthorized access.

3.5 Performance Metrics

Performance metrics were analyzed to measure the impact of load balancing and caching on system efficiency. Response time, server load, and request handling behavior were observed during testing.

With caching enabled, response times for repeated requests were noticeably faster compared to initial requests. Backend server load was reduced, as cached responses were served directly by the Nginx server. Load balancing further ensured that server resources were utilized evenly, preventing bottlenecks.

Although no formal benchmarking tools were used, manual observation confirmed improved responsiveness and stability under normal traffic conditions. These improvements demonstrate that the architectural design effectively enhances system performance and scalability.

3.6 Summary of Testing Results

The testing phase confirmed that all major architectural components functioned as intended. Load balancing ensured fair request distribution, caching improved performance, high availability mechanisms provided fault tolerance, and security controls protected backend resources. Performance metrics indicated reduced response times and balanced server utilization.

Overall, the testing results validate that the deployed AWS infrastructure meets the functional and non-functional requirements of a reliable, secure, and scalable cloud-based web application.

4. Challenges & Solutions

During the deployment and testing of the AWS-based web architecture using Terraform, several technical challenges were encountered. These challenges were resolved through configuration changes, debugging, and careful analysis. This section discusses the major challenges faced, the solutions applied, and the lessons learned during the project.

4.1 SSH Connectivity and Access Control Issues

Challenge

One of the initial challenges faced was the inability to establish SSH connections with the EC2 instances. Attempts to connect resulted in timeouts or permission errors. This issue was primarily caused by misconfigured **security group inbound rules** and incorrect handling of SSH key pairs.

Solution

To resolve this issue, the security group configuration was reviewed and updated. Port 22 (SSH) was explicitly allowed only from authorized IP addresses. The correct key pair associated with the EC2 instances was verified and used for authentication. After these changes, secure SSH access was successfully established.

4.2 Backend Server Communication Failure

Challenge

Another major challenge was that backend Apache servers were not responding to requests forwarded by the Nginx server. Although the backend instances were running, client requests resulted in connection timeouts or error messages. This indicated an issue in the reverse proxy or backend configuration.

Solution

The Nginx reverse proxy configuration was carefully examined and corrected. Backend server IP addresses and listening ports were verified, and the proxy settings were updated accordingly. Apache services on the backend servers were restarted to ensure proper operation. After applying these changes, requests were successfully routed to the backend servers.

4.3 Cache Header Visibility and Validation Issues

Challenge

During cache performance testing, the expected cache response headers (X-Cache-Status) were not appearing in browser developer tools. This made it difficult to confirm whether caching was working as intended.

Solution

To resolve this issue, browser cache was cleared, and the Nginx service was reloaded to apply the caching configuration. Response headers were then inspected again. After these steps, cache headers correctly displayed MISS for initial requests and HIT for subsequent requests, confirming proper cache functionality.

4.4 Lessons Learned

This project provided several important insights into cloud infrastructure deployment. One key lesson learned was the **importance of modular and well-structured Terraform code**, which simplifies debugging and future modifications. Additionally, effective use of logs, system status checks, and the AWS Management Console proved essential for identifying and resolving configuration issues.

The project also highlighted the **value of Infrastructure as Code (IaC)** for creating repeatable, consistent, and reliable deployments. Overall, these challenges strengthened practical understanding of real-world cloud architecture and troubleshooting techniques.

5. Conclusion

This project successfully demonstrated the design, deployment, and evaluation of a cloud-based web infrastructure using **Amazon Web Services (AWS)** and **Terraform**. A three-tier architecture was implemented in which an **Nginx server** functioned as a reverse proxy, load balancer, and cache layer, while multiple **Apache backend servers** served application content. The infrastructure was deployed within a custom **Virtual Private Cloud (VPC)** with carefully configured subnets and security groups to ensure controlled and secure communication between system components.

All major functional objectives were achieved. Load balancing was verified through even distribution of requests across backend servers, caching significantly improved response times, and high availability was ensured through the use of multiple backend servers and a backup node. Security testing confirmed that backend servers were protected from direct internet access and that communication was restricted according to the principle of least privilege. The testing results validated the reliability, performance, and security of the deployed architecture.

Throughout the project, several technical skills were developed and strengthened. Practical experience was gained in **Infrastructure as Code (IaC)** using Terraform, including automated provisioning of EC2 instances, networking resources, and security configurations. Hands-on experience with **Nginx configuration, Apache web servers, AWS networking, and cloud security concepts** was also acquired. Additionally, troubleshooting skills were enhanced through the use of system logs, browser developer tools, and the AWS Management Console.

Despite the successful implementation, there are several opportunities for future improvement. The architecture can be enhanced by introducing **Auto Scaling Groups** to automatically adjust the number of backend servers based on traffic demand. Using **AWS Elastic Load Balancer (ELB)** and **Route 53** could further improve scalability and availability. Monitoring tools such as **CloudWatch** can be integrated for real-time performance tracking,

and advanced security features like **AWS WAF** can be added to protect against web-based attacks.

In conclusion, this project provided valuable hands-on experience with cloud infrastructure design and deployment. It demonstrated how modern cloud technologies and automation tools can be combined to build scalable, secure, and reliable web systems, laying a strong foundation for future work in cloud computing and DevOps practices.

6. Appendices

1. Terraform configuration files such as `main.tf`, `variables.tf`, and `locals.tf` are included. These files define the complete infrastructure setup.
2. Webserver modules are included to create the Nginx server and backend servers in a reusable way.
3. The `apache-setup.sh` script is included for configuring backend web servers.
4. The `nginx-setup.sh` script is included for configuring the Nginx reverse proxy server.