# SELECT WITH VARIOUS CLAUSES

## Select with Group by Command

**Query:**
use exp;
select * from project group by P_Price;

| | S_No | P_Name | Coordinators | P_Price | Location |
|---|---|---|---|---|---|
| ▶ | 1 | Sai pavan | Komal | 1000 | Chennai |
| | 2 | Komal | Sai Pavan | 2000 | Kerela |
| | 3 | Akhil | Sai Pavan | 3000 | Hyderabad |
| * | NULL | NULL | NULL | NULL | NULL |

## Select with Having Command

**Query:**
use exp;
select * from project having P_Price=1000;

| | S_No | P_Name | Coordinators | P_Price | Location |
|---|---|---|---|---|---|
| ▶ | 1 | Sai pavan | Komal | 1000 | Chennai |
| * | NULL | NULL | NULL | NULL | NULL |

## Select with Order By Command

**Query:**
use exp;
select * from project order by P_Price;

| | S_No | P_Name | Coordinators | P_Price | Location |
|---|---|---|---|---|---|
| ▶ | 1 | Sai pavan | Komal | 1000 | Chennai |
| | 2 | Komal | Sai Pavan | 2000 | Kerela |
| | 3 | Akhil | Sai Pavan | 3000 | Hyderabad |
| * | NULL | NULL | NULL | NULL | NULL |