



## **LAB-REPORT**

Report no : 05

Report Name: Programming with Python Lab

Course code : ICT-3208

Course title : Network Planning and Designing Lab

Date of Submission : 15-Sept-2020

### **Submitted By**

Name: Md. Nayan Ali

ID: IT-16062

3<sup>rd</sup> year 2<sup>nd</sup> semester

Session: 2015-2016

Dept. of ICT

MBSTU.

### **Submitted To**

Mr. Nazrul Islam

Assistant Professor,

Dept. of ICT, MBSTU.

## Objectives:

- i. Understand how python function works
- ii. Understand the use of global and local variables
- iii. Understand how python modules works
- . Learning the basis of networking programming with
- iv. python

## Programming with Python Lab

### Exercises:

1. Python function (save as function.py).

#### Source Code:

```
def say_hello():  
    print('hello world')  
if __name__ == '__main__':  
    say_hello()
```

#### Output:

```
hello world
```

2. Python function (save as function\_2.py)

#### Source Code:

```
def print_max(a, b):  
    if a > b:  
        print(a, 'is maximum')  
    elif a == b:  
        print(a, 'is equal to', b)  
    else:  
        print(b, 'is maximum')  
if __name__ == '__main__':  
    print_max(3, 4)  
# directly pass literal values  
x = 5  
y = 7  
# pass variables as arguments  
print_max(x, y)
```

#### Output:

```
4 is maximum  
7 is maximum
```

3. Local variable (save as function\_local.py).

#### Source Code:

```
def x = 50  
def func():  
    global x  
    print('x is', x)  
x = 2
```

```
print('Changed global x to', x)
if __name__ == '__main__':
    func()
print('Value of x is', x)
```

**Output:**

```
x is 50
Changed global x to 2
Value of x is 2
```

4. Create python scrip using the syntax provided below (save as mymodule.py).

**Source Code:**

```
def say_hi():
    print('Hi, this is mymodule speaking.')
__version__ = '0.1'
```

5. Create python scrip using the syntax provided below (save as module\_demo.py).

**Source Code:**

```
import mymodule
if __name__ == '__main__':
    mymodule.say_hi()
print('Version', mymodule.__version__)
```

**Output:**

```
Hi, this is mymodule speaking.
Version 0.1
```

6. Create python scrip using the syntax provided below (save as module\_demo2.py).

**Source Code:**

```
from mymodule import say_hi, __version__
if __name__ == '__main__':
    say_hi()
print('Version', __version__)
```

**Output:**

```
Hi, this is mymodule speaking.
Version 0.1
```

7. Printing your machine's name and IPv4 address. Create python scrip using the syntax provided below (save as local\_machine\_info.py):

**Source Code:**

```
import socket
def print_machine_info():
    host_name = socket.gethostname()
    ip_address = socket.gethostbyname(host_name)
    print (" Host name: %s" % host_name)
    print (" IP address: %s" % ip_address)
if __name__ == '__main__':
    print_machine_info()
```

**Output:**

```
Host name: DESKTOP-8GD1EFD
IP address: 192.168.56.1
```

8. Retrieving a remote machine's IP address. Create python scrip using the syntax provided below (save as remote\_machine\_info.py):

**Source Code:**

```
import socket
def get_remote_machine_info():
    remote_host = 'www.python.org'
    try:
        print (" Remote host name: %s" % remote_host)
        print (" IP address: %s" %socket.gethostbyname(remote_host))
    except socket.error as err_msg:
        print ("Error accesing %s: error number and detail %s"
              %(remote_host, err_msg))
if __name__ == '__main__':
    get_remote_machine_info()
```

**Output:**

```
Remote host name: www.python.org
IP address: 151.101.8.223
```

9. Converting an IPv4 address to different formats. Create python scrip using the syntax below (save as ip4\_address\_conversion.py):

**Source Code:**

```
import socket
from binascii import hexlify
def convert_ip4_address():
    for ip_addr in ['127.0.0.1', '192.168.0.1']:
        packed_ip_addr = socket.inet_aton(ip_addr)
        unpacked_ip_addr = socket.inet_ntoa(packed_ip_addr)
        print (" IP Address: %s => Packed: %s, Unpacked: %s"
              %(ip_addr, hexlify(packed_ip_addr), unpacked_ip_addr))
if __name__ == '__main__':
    convert_ip4_address()
```

**Output:**

```
IP Address: 127.0.0.1 => Packed: b'7f000001', Unpacked: 127.0.0.1
IP Address: 192.168.0.1 => Packed: b'c0a80001', Unpacked: 192.168.0.1
```

10. Finding a service name, given the port and protocol. Create python scrip using the syntax below (save as finding\_service\_name.py):

**Source Code:**

```
import socket
def find_service_name():
    protocolname = 'tcp'
    for port in [80, 25]:
        print ("Port: %s => service name: %s" %(port,
            socket.getservbyport(port, protocolname)))
        print ("Port: %s => service name: %s" %(53,socket.getservbyport(53, 'udp')
        ))
if __name__ == '__main__':
```

```
find_service_name()
```

**Output:**

```
Port: 80 => service name: http
Port: 25 => service name: smtp
Port: 53 => service name: domain
```

11. Setting and getting the default socket timeout. Create python scrip using the syntax below (save as socket\_timeout.py):

**Source Code:**

```
import socket
def test_socket_timeout():
    s = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    print ("Default socket timeout: %s" %s.gettimeout())
    s.settimeout(100)
    print ("Current socket timeout: %s" %s.gettimeout())
if __name__ == '__main__':
    test_socket_timeout()
```

**Output:**

```
Default socket timeout: None
Current socket timeout: 100.0
```

12. Writing a simple echo client/server application (Tip: Use port 9900). Create python scrip using the syntax below (save as echo\_server.py):

**Source Code:**

```
import socket
import sys
import argparse
import codecs
from codecs import encode, decode
host = 'localhost'
data_payload = 8088
backlog = 5
def echo_server(port):
    """ A simple echo server """
    # Create a TCP socket
    sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    # Enable reuse address/port
    sock.setsockopt(socket.SOL_SOCKET, socket.SO_REUSEADDR, 1)
    # Bind the socket to the port
    server_address = (host, port)
    print ("Starting up echo server on %s port %s" %server_address)
    sock.bind(server_address)
    # Listen to clients, backlog argument specifies the max no. of queued
    # connections
    sock.listen(backlog)
    while True:
```

```

print ("Waiting to receive message from client")
client, address = sock.accept()
data = client.recv(data_payload)
if data:
    print ("Data: %s" %data)
    client.send(data)
    print ("sent %s bytes back to %s" % (data, address))
# end connection
client.close()
if __name__ == '__main__':
    parser = argparse.ArgumentParser(description='Socket Server Example')
    parser.add_argument('--
port', action="store", dest="port", type=int,required=True)
given_args = parser.parse_args()
port = given_args.port
echo_server(port)

```

**Output:** I can't fix the error.

13. Create python scrip using the syntax below (save as echo\_client.py):

**Source Code:**

```

#!/usr/bin/env python
import socket
import sys
import argparse
import codecs
from codecs import encode, decode
host = 'localhost'
def echo_client(port):
    """ A simple echo client """
    # Create a TCP/IP socket
    sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    # Connect the socket to the server
    server_address = (host, port)
    print ("Connecting to %s port %s" % server_address)
    sock.connect(server_address)
    # Send data
    try:
        # Send data
        message = "Test message: SDN course examples"
        print ("Sending %s" % message)
        sock.sendall(message.encode('utf_8'))
    # Look for the response
    amount_received = 0
    amount_expected = len(message)
    while amount_received < amount_expected:
        data = sock.recv(16)
        amount_received += len(data)

```

```
print ("Received: %s" % data)
except socket.errno as e:
print ("Socket error: %s" %str(e))
except Exception as e:
print ("Other exception: %s" %str(e))
finally:
print ("Closing connection to the server")
sock.close()
if __name__ == '__main__':
parser = argparse.ArgumentParser(description='Socket Server Example')
parser.add_argument('--
port', action="store", dest="port", type=int,required=True)
given_args = parser.parse_args()
port = given_args.port
echo_client(port)
```

**Output:** I can't fix the error.

**Conclusion:** From this lab, I've learned that the functionality of python. Also learn the use of Module that can be reused a number of functions in other programs. Networking background for socket and TCP, UDP with python are the most important part of the Lab.