

Lubrication Schedule

Preventive Maintenance · Lubrication Reference

Doc ID	PM-LUB-002
Version	1.6
Effective Date	2026-02-10
Owner	Maintenance Department
Scope	All plants, all machine types

1. Purpose

Specifies lubricant type, quantity, and interval for all rotating and sliding components to prevent premature bearing wear (DT-08) and reduce friction-related cycle time loss.

2. Lubrication Table

Machine Type	Component	Lubricant	Interval
CNC Milling	Spindle bearing	NLGI-2 lithium complex grease	500 operating hours
CNC Milling	Ball screw / linear guides	ISO VG 68 way oil	Weekly
Press Line	Hydraulic system	ISO VG 46 hydraulic oil	Monthly sample; change at 2000 hrs
Press Line	Ram guide gibs	NLGI-2 EP grease	Weekly
Assembly Line	Conveyor chain	Food-safe chain oil (if applicable) / ISO VG 100	Weekly
Assembly Line	Pneumatic torque tools	Air-tool oil, 1 drop per shift	Daily

3. Notes

- Over-greasing bearings is a leading cause of premature seal failure — follow the specified quantity only.
- Hydraulic oil samples showing particulate contamination or viscosity drift >10% require immediate change-out and root-cause check per Hydraulic_Maintenance_SOP.