

Contents

1 Build and Snippet	1	4.10 strongly connected component	14
1.1 Sublime Build	1	4.11 tree isomorphism	14
2 Data Structures	1	5 String	14
2.1 2D BIT	1	5.1 KMP	14
2.2 BIT	1	5.2 Manacher	14
2.3 Lazy Propagation	1	5.3 SuffixArray	14
2.4 MergeSortTree	2	5.4 Z	15
2.5 PST	3	5.5 double hashing	15
2.6 Segment Tree	3	6 Divide and Conquer	16
2.7 Sparse Table	4	6.1 maximum subarray sum	16
2.8 Trie	4	7 DP	16
2.9 sparse table 2D	4	7.1 CatalanDp	16
3 Number Theory	5	7.2 Coin Change	17
3.1 Big MOD	5	7.3 DearrangementDP	17
3.2 Bitwise Sieve	5	7.4 Knapsack	17
3.3 Chinese Remainder Theorem	5	7.5 SOS	17
3.4 Combinatorics	5	7.6 grundy	17
3.5 Divisor	5	8 Geometry	18
3.6 Eulars Totient Function	5	8.1 2D everything	18
3.7 FFT	6	8.2 3D	20
3.8 LargePrime	6	8.3 convex	21
3.9 Matrix	7	8.4 $\min_{i,j} d_{i,j}^2$	23
3.10 Mint	7	9 Misc	23
3.11 NOD and SOD	8	9.1 StressTest	23
3.12 Pollard rho	9	9.2 All Macros	23
3.13 Sieve	9	10 Equations and Formulas	24
3.14 nCr	9	10.1 Catalan Numbers	24
3.15 ntt	10	10.2 Stirling Numbers First Kind	24
4 Graph	10	10.3 Stirling Numbers Second Kind	24
4.1 Bellman Ford	10	10.4 Other Combinatorial Identities	24
4.2 BridgeTree	10	10.5 Different Math Formulas	24
4.3 DSU, MST	11	10.6 GCD and LCM	24
4.4 Dijkstra	11		
4.5 ETT, VT	11		
4.6 HLD	12		
4.7 K th shortest path	12		
4.8 LCA, CD	12		
4.9 block cut tree	13		

1 Build and Snippet

1.1 Sublime Build

```
#for linux
{
    "shell_cmd": "g++ $file -o $file_base_name && ./
        $file_base_name<input.txt> output.txt && rm
        $file_base_name",
    "working_dir": "$file_path",
    "selector": "source.c++"
}
#for windows
{
    "shell_cmd": "g++ -std=c++17 $file -o $file_base_name.
        exe && $file_base_name.exe <input.txt> output.txt
        && del $file_base_name.exe",
    "working_dir": "$file_path",
    "selector": "source.c++"
}
```

2 Data Structures

2.1 2D BIT

```
const int N = 1008;
int bit[N][N], a[N][N], n, m, q;
void update(int x, int y, int val) {
    for (; x < N; x += -x & x)
        for (int j = y; j < N; j += -j & j) bit[x][j] += val;
}
int get(int x, int y) {
    int ans = 0;
    for (; x; x -= x & -x)
        for (int j = y; j; j -= j & -j) ans += bit[x][j];
    return ans;
}
int get(int x1, int y1, int x2, int y2) {
    return get(x2, y2) - get(x1 - 1, y2) - get(x2, y1 - 1)
        + get(x1 - 1, y1 - 1);
}
```

2.2 BIT

```
class BIT {
    int *bin, N;

public:
    BIT(int N) : N(N) {
        bin = new int[N + 1];
```

```
        memset(bin, 0, (N + 1) * sizeof(int));
    }
    void update(int id, int val) {
        for (; id <= N; id += id & -id) bin[id] += val;
    }
    int helper(int id) {
        int sum = 0;
        for (; id > 0; id -= id & -id) sum += bin[id];
        return sum;
    }
    int query(int l, int r) { return helper(r) - helper(l - 1); }
    ~BIT() { delete[] bin; }
};
```

2.3 Lazy Propagation

```
template <typename node, typename change>
class SegmentTree {
public:
    int n;

    node *tree, identity;
    node (*merge)(node, node);

    change *lazy, noUpdate;
    void (*applyUpdate)(int, int, node &, change);
    void (*mergeUpdate)(int, int, change &, change);

    void build(vector<node> &input, int lo, int hi, int
        root = 0) {
        if (lo == hi) {
            tree[root] = input[lo];
            return;
        }

        int mid = lo + hi >> 1, leftChild = 2 * root + 1,
            rightChild = 2 * root + 2;
        build(input, lo, mid, leftChild);
        build(input, mid + 1, hi, rightChild);

        tree[root] = merge(tree[leftChild], tree[rightChild])
            ;
    }

    void propagate(int lo, int hi, int root) {
        applyUpdate(lo, hi, tree[root], lazy[root]);
```

```
        if (lo < hi) {
            int mid = lo + hi >> 1, leftChild = 2 * root + 1,
                rightChild = 2 * root + 2;

            mergeUpdate(lo, mid, lazy[leftChild], lazy[root]);
            mergeUpdate(mid + 1, hi, lazy[rightChild], lazy[
                root]);
        }

        lazy[root] = noUpdate;
    }

    void update(int from, int to, int lo, int hi, int root,
        change delta) {
        if (lo > hi) return;

        propagate(lo, hi, root);
        if (from > hi || to < lo) return;

        if (from <= lo && to >= hi) {
            mergeUpdate(lo, hi, lazy[root], delta);
            propagate(lo, hi, root);
            return;
        }

        int mid = lo + hi >> 1, leftChild = 2 * root + 1,
            rightChild = 2 * root + 2;
        update(from, to, lo, mid, leftChild, delta);
        update(from, to, mid + 1, hi, rightChild, delta);

        tree[root] = merge(tree[leftChild], tree[rightChild])
            ;
    }

    node query(int from, int to, int lo, int hi, int root)
        {
            if (lo > hi) return identity;

            propagate(lo, hi, root);
            if (from > hi || to < lo) return identity;

            if (from <= lo && to >= hi) return tree[root];

            int mid = lo + hi >> 1, leftChild = 2 * root + 1,
                rightChild = 2 * root + 2;
```

```

    node q1 = query(from, to, lo, mid, leftChild), q2 =
        query(from, to, mid + 1, hi, rightChild);
    return merge(q1, q2);
}

int lowerbound(int lo, int hi, int root, node val) {
    if (lo > hi) return -1;
    propagate(lo, hi, root);

    if (tree[root] < val) return -1;
    if (lo == hi) {
        if (tree[root] == val) return hi;
        return -1;
    }

    int mid = lo + hi >> 1, leftChild = 2 * root + 1,
        rightChild = 2 * root + 2;
    int leftSum = query(lo, mid, lo, mid, leftChild);

    if (leftSum >= val)
        return lowerbound(lo, mid, leftChild, val);
    else
        return lowerbound(mid + 1, hi, rightChild, val -
            leftSum);
    // val-leftsum works when merge function is sum
}

// leftmost position of a minsegtree
// that has value <= val
int walk(int lo, int hi, int root, int from, node val)
{
    if (lo > hi) return -1;

    propagate(lo, hi, root);
    if (from > hi) return -1;
    if (tree[root] > val) return hi;

    if (lo == hi) {
        return hi;
    }

    int mid = lo + hi >> 1, leftChild = 2 * root + 1,
        rightChild = 2 * root + 2;
    if (from > mid) return walk(mid + 1, hi, rightChild,
        from, val);

```

```

    node q1 = query(max(from, lo), mid, lo, mid,
        leftChild);

    if (q1 <= val) return walk(lo, mid, leftChild, from,
        val);
    return walk(mid + 1, hi, rightChild, from, val);
}

public:
SegmentTree(SegmentTree &st) : tree(st.tree), lazy(st.
    lazy), n(st.n), merge(st.merge), identity(st.
    identity), applyUpdate(st.applyUpdate), mergeUpdate(
    st.mergeUpdate), noUpdate(st.noUpdate) {}

SegmentTree(vector<node> &input, node (*merge)(node,
    node), node identity, void (*applyUpdate)(int, int,
    node &, change), void (*mergeUpdate)(int, int,
    change &, change), change noUpdate)
: n(input.size()), merge(merge), identity(identity)
, applyUpdate(applyUpdate), mergeUpdate(
    mergeUpdate), noUpdate(noUpdate) {
    tree = new node[n << 2];
    build(input, 0, n - 1);

    lazy = new change[n << 2];
    fill(lazy, lazy + (n << 2), noUpdate);
}

node query(int from, int to) {
    if (from > to || to > n) return identity;
    return query(from, to, 0, n - 1, 0);
}

void update(int from, int to, change delta) { update(
    from, to, 0, n - 1, 0, delta); }

int lowerbound(int val)
// Only works for non-decreasing function
{
    return lowerbound(0, n - 1, 0, val);
}

~SegmentTree() {
    delete[] tree;
    delete[] lazy;
}

```

```

};

int merge(int a, int b) { return a + b; }

void applyUpdate(int lo, int hi, int &val, int delta) {
    val += delta * (hi - lo + 1); }

void mergeUpdate(int lo, int hi, int &val, int delta) {
    val += delta; }

```

2.4 MergeSortTree

```

class MergeSortTree {
    int n;
    vector<vector<int>> tree;
    void build(int id, int le, int ri, vector<int> &a) {
        if (le == ri) {
            tree[id].push_back(a[le]);
            return;
        }
        int mid = (le + ri) >> 1;
        build(2 * id + 1, le, mid, a);
        build(2 * id + 2, mid + 1, ri, a);

        auto &left = tree[2 * id + 1], &right = tree[2 * id +
            2];
        int i = 0, j = 0, n = left.size(), m = right.size();
        while (i < n && j < m) {
            if (left[i] < right[j])
                tree[id].push_back(left[i]), i++;
            else
                tree[id].push_back(right[j]), j++;
        }
        while (i < n) tree[id].push_back(left[i]), i++;
        while (j < m) tree[id].push_back(right[j]), j++;
    }

    // number of element greater than val
    int queryL(int id, int le, int ri, int l, int r, int
        val) {
        if (le > r || ri < l) {
            return 0;
        }
        if (le >= l && ri <= r) {
            return ri - le + 1 - (upper_bound(tree[id].begin(),
                tree[id].end(), val) - tree[id].begin());
        }
    }
}

```

```

    }
    int mid = (le + ri) >> 1;
    return queryL(2 * id + 1, le, mid, l, r, val) +
           queryL(2 * id + 2, mid + 1, ri, l, r, val);
}

// number of element smaller than val
int queryS(int id, int le, int ri, int l, int r, int val) {
    if (le > r || ri < l) {
        return 0;
    }

    if (le >= l && ri <= r) {
        return (upper_bound(tree[id].begin(), tree[id].end()
            (), val - 1) - tree[id].begin());
    }

    int mid = (le + ri) >> 1;
    return queryS(2 * id + 1, le, mid, l, r, val) +
           queryS(2 * id + 2, mid + 1, ri, l, r, val);
}

public:
MergeSortTree(vector<int> &a) {
    n = a.size();
    tree.resize(n * 4);
    build(0, 0, n - 1, a);
}

int queryS(int l, int r, int val) { return queryS(0, 0,
    n - 1, l, r, val); }
int queryL(int l, int r, int val) { return queryL(0, 0,
    n - 1, l, r, val); }
};

```

2.5 PST

// this calculates xor/xor_hash of all the element less than 'x' in [0, i]. query is a walk function

```

class PST {
#define lc(u) tree[u].left
#define rc(u) tree[u].right;
    struct node {
        int left = 0, right = 0, val = 0;
    };
    node *tree;

```

```

    int N, LG, time = 0, I = 0;

    node create(int l, int r) { return {l, r, merge(tree[l]
        ].val, tree[r].val)}; }
    int merge(LL a, LL b) { return a ^ b; }
    int build(int le, int ri) {
        int id = ++time;
        if (le == ri) return tree[id] = node(), id;
        int m = (le + ri) / 2;
        return tree[id] = create(build(le, m), build(m + 1,
            ri)), id;
    }

    int update(int id, int le, int ri, int pos, int val) {
        int nid = ++time;
        if (le == ri) return tree[nid] = {0, 0, (tree[id].val
            ^ val)}, nid; // change here
        int m = (le + ri) / 2;
        if (pos <= m) {
            tree[nid] = create(update(tree[id].left, le, m, pos
                , val), tree[id].right);
        } else {
            tree[nid] = create(tree[id].left, update(tree[id].
                right, m + 1, ri, pos, val));
        }
        return nid;
    }

    int query(int id, int di, int le, int ri) {
        if (tree[id].val == tree[di].val) return 0;
        if (le == ri) return le;
        int m = (le + ri) >> 1;
        if (tree[tree[id].left].val != tree[tree[di].left].
            val) return query(tree[id].left, tree[di].left,
                le, m);
        return query(tree[id].right, tree[di].right, m + 1,
            ri);
    }
}

```

```

public:
PST(int N, int U) { // U --> number of expected updates
    this->N = N;
    LG = 33 - __builtin_clz(N);
    tree = new node[(N + U) * LG];
    build(0, N - 1);
}

int update(int id, int pos, int val) { return update(id
    , 0, N - 1, pos, val); }

```

```

    int query(int id, int di) { return query(id, di, 0, N -
        1); }
    ~PST() { delete[] tree; }
};

```

2.6 Segment Tree

```

template <typename DT>
class segmentTree {
    DT *seg, I;
    int n;
    DT (*merge)(DT, DT);

    void build(int idx, int le, int ri, vector<DT> &v) {
        if (le == ri) {
            seg[idx] = v[le];
            return;
        }
        int mid = (le + ri) >> 1;
        build(2 * idx + 1, le, mid, v);
        build(2 * idx + 2, mid + 1, ri, v);
        seg[idx] = merge(seg[2 * idx + 1], seg[2 * idx + 2]);
    }

    void update(int idx, int le, int ri, int pos, DT val) {
        if (le == ri) {
            seg[idx] = val;
            return;
        }
        int mid = (le + ri) >> 1;
        if (pos <= mid)
            update(2 * idx + 1, le, mid, pos, val);
        else
            update(2 * idx + 2, mid + 1, ri, pos, val);
        seg[idx] = merge(seg[2 * idx + 1], seg[2 * idx + 2]);
    }

    DT query(int idx, int le, int ri, int l, int r) {
        if (l <= le && r >= ri) {
            return seg[idx];
        }
        if (r < le || l > ri) {
            return I;
        }
        int mid = (le + ri) >> 1;
        return merge(query(2 * idx + 1, le, mid, l, r), query
            (2 * idx + 2, mid + 1, ri, l, r));
    }
}

```

```

}

// finding the leftmost appearance of value <= val in [
// 1....r] range
// need minimum segment tree
int walk(int idx, int le, int ri, int l, int r, DT val)
{
    if (r < le || l > ri) {
        return r;
    }
    if (le == ri) {
        if (seg[idx] <= val) return le;
        return r;
    }
    if (l <= le && r >= ri) {
        int mid = (le + ri) >> 1;
        if (seg[2 * idx + 1] <= val) return walk(2 * idx +
            1, le, mid, l, r, val);
        return walk(2 * idx + 2, mid + 1, ri, l, r, val);
    }
    int mid = (le + ri) >> 1;
    return merge(walk(2 * idx + 1, le, mid, l, r, val),
        walk(2 * idx + 2, mid + 1, ri, l, r, val));
}

public:
segmentTree(vector<DT> &v, DT (*fptr)(DT, DT), DT _I) {
    n = v.size();
    I = _I;
    merge = fptr;
    seg = new DT[4 * n];
    build(0, 0, n - 1, v);
}

void update(int pos, int val) { update(0, 0, n - 1, pos
    , val); }

int walk(int l, int r, DT val) {
    if (query(l, r) > val) return r;
    return walk(0, 0, n - 1, l, r, val);
}

DT query(int l, int r) { return query(0, 0, n - 1, l, r
    ); }

};

int fun(int a, int b) { return max(a, b); }

```

2.7 Sparse Table

```

class SparseTable {
private:
    vector<vector<int>> table;
    vector<int> log;
    int n;

public:
    SparseTable(const vector<int>& arr) {
        n = arr.size();
        log.resize(n + 1);
        buildLog();
        table = vector<vector<int>>(n, vector<int>(log[n] +
            1));
        for (int i = 0; i < n; i++) {
            table[i][0] = arr[i];
        }
        for (int j = 1; (1 << j) <= n; j++) {
            for (int i = 0; i + (1 << j) <= n; i++) {
                table[i][j] = merge(table[i][j - 1], table[i + (1
                    << (j - 1))][j - 1]);
            }
        }
    }

    int merge(int a, int b) { return max(a, b); }
    void buildLog() {
        log[1] = 0;
        for (int i = 2; i <= n; i++)
            log[i] = log[i / 2] + 1;
    }

    int Query(int L, int R) {
        int j = log[R - L + 1];
        return merge(table[L][j], table[R - (1 << j) + 1][j])
            ;
    }

    int query(int L, int R) {
        int sum = 0;
        for (int j = log[R - L + 1]; L <= R; j = log[R - L +
            1]) {
            sum = merge(sum, table[L][j]);
            L += (1 << j);
        }
        return sum;
    }
};

```

2.8 Trie

```

namespace tri {
const int k = 26;
struct trie_vertex {
    int next[k], cPrefix = 0;
    bool leaf = false;
    trie_vertex() { fill(begin(next), end(next), -1); }
};

struct Trie {
    vector<trie_vertex> trie;
    Trie() { trie.resize(1); }
    void insert(string const& s) {
        int v = 0;
        for (char ch : s) {
            int c = ch - 'a';
            if (trie[v].next[c] == -1) {
                trie[v].next[c] = trie.size();
                trie.emplace_back();
            }
            v = trie[v].next[c];
            trie[v].cPrefix++;
        }
        trie[v].leaf = true;
    }

    int search(string const& key, bool& isWord) {
        int v = 0, level = 0;
        for (char ch : key) {
            int c = ch - 'a';
            v = trie[v].next[c];
            if (v == -1) return -1;
            isWord = trie[v].leaf;
            level++;
        }
        return level;
    }
};

} // namespace tri

```

2.9 sparse table 2D

```

// rectangle query
namespace st2 {
const int N = 2e3 + 5, B = 12;
using Ti = long long;
Ti Id = LLONG_MAX;
Ti f(Ti a, Ti b) { return max(a, b); }
Ti tbl[N][N][B];
void init(int n, int m) {

```

```

for(int k = 1; k < B; k++) {
    for(int i = 0; i + (1 << k) - 1 < n; i++) {
        for(int j = 0; j + (1 << k) - 1 < m; j++) {
            tbl[i][j][k] = tbl[i][j][k - 1];
            tbl[i][j][k] = f(tbl[i][j][k], tbl[i][j + (1 << k - 1)][k - 1]);
            tbl[i][j][k] = f(tbl[i][j][k], tbl[i + (1 << k - 1)][j][k - 1]);
            tbl[i][j][k] = f(tbl[i][j][k], tbl[i + (1 << k - 1)][j + (1 << k - 1)][k - 1]);
        } } }
}

Ti query(int i, int j, int len) {
    int k = __lg(len);
    LL ret = tbl[i][j][k];
    ret = f(ret, tbl[i + len - (1 << k)][j][k]);
    ret = f(ret, tbl[i][j + len - (1 << k)][k]);
    ret = f(ret, tbl[i + len - (1 << k)][j + len - (1 << k)][k]);
    return ret;
}

}

int main() {
    for(int i = 0; i < n; i++)
        for(int j = 0; j < m; j++)
            cin >> st2 :: tbl[i][j][0];
    st2 :: init(n, m);
    cout << st2 :: query(x, y, s); // x, y, x + s - 1, y + s - 1
}

```

3 Number Theory

3.1 Big MOD

```

LL bigmod(LL x, LL n, LL mod) {
    if(n == -1) n = mod - 2;
    LL ans = 1;
    while(n) {
        if((n & 1)) ans = (ans * x) % mod;
        n >>= 1;
        x = (x * x) % mod;
    }
    return ans;
}

```

3.2 Bitwise Sieve

```
const int nmax = 1e8 + 1;
```

```

int mark[(nmax >> 6) + 1];
vector<int> primes;
#define isSet(n, pos) ((n) & (1LL << (pos)))
#define Set(n, pos) ((n) | (1LL << (pos)))
void sieve(int n) {
    for (int i = 3; i * i <= n; i += 2) {
        if (isSet(mark[i >> 6], (i >> 1) & 31) == 0) {
            for (int j = i * i; j <= n; j += (i << 1)) mark[j >> 6] = Set(mark[j >> 6], (j >> 1) & 31);
        }
    }
    primes.push_back(2);
    for (int i = 3; i <= n; i += 2) {
        if (isSet(mark[i >> 6], (i >> 1) & 31) == 0) primes.push_back(i);
    }
}

```

3.3 Chinese Remainder Theorem

```

using LL = long long;
using PLL = pair<LL, LL>;
// given a, b will find solutions for, ax + by = 1
tuple<LL, LL, LL> EGCD(LL a, LL b) {
    if (b == 0)
        return {1, 0, a};
    else {
        auto [x, y, g] = EGCD(b, a % b);
        return {y, x - a / b * y, g};
    }
}

```

```

// given modulo equations, will apply CRT
PLL CRT(vector<PLL> &v) {
    LL V = 0, M = 1;
    for (auto &[v, m] : v) { // value % mod
        auto [x, y, g] = EGCD(M, m);
        if ((v - V) % g != 0) return {-1, 0};
        V += x * (v - V) / g % (m / g) * M, M *= m / g;
        V = (V % M + M) % M;
    }
    return make_pair(V, M);
}

```

3.4 Combinatorics

```
/* Given n boxes, each box has cnt[i] different (
distinct) items,
```

```

you can take only 1 object from each box. how many
different combinations
of choices are there */
LL calL(LL box, LL take, vector<LL> &cnt) {
    vector<vector<int>> DP(box + 1, vector<int>(take + 2));
    dp[0][0] = 1, dp[0][1] = cnt[0];
    for (int s = 0; s <= take; s++) {
        for (int idx = 0; idx < box; idx++) {
            dp[idx + 1][s] = (dp[idx + 1][s] + dp[idx][s]);
            dp[idx + 1][s + 1] = (dp[idx + 1][s + 1] + dp[idx][s] * cnt[idx + 1][s]);
        }
    }
    return dp[box - 1][take];
}

```

3.5 Divisor

```

// calculate divisor in range[1,n]
LL sum_in_range(LL n) {
    return n * (n + 1) / 2;
}

LL sum_all_divisors(LL n) {
    LL ans = 0;
    for(LL i=1;i*i<=n;i++) {
        LL hello = i * (n / i - i + 1);
        LL world = sum_in_range(n / i) - sum_in_range(i);
        ans += hello + world;
    }
    return ans;
}

```

3.6 Eulers Totient Function

```

int phi(int n) {
    int ret = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0) n /= i;
            ret -= ret / i;
        }
    }
    if (n > 1) ret -= ret / n;
    return ret;
}

void phi_in_range() {
    int N = 1e6, phi[N + 1];
    for (int i = 0; i <= N; i++) phi[i] = i;
}

```

```

for (int i = 2; i <= N; i++) {
    if (phi[i] != i) continue;
    for (int j = i; j <= N; j += i) {
        phi[j] -= phi[j] / i;
    }
}

#some important properties of phi
phi(p) = p-1 ,where p is a prime number
phi(a*b) = phi(a)*phi(b) ,where a and b are co-prime
phi(a*b) = phi(a)*phi(b)*(gcd(a,b)/phi(gcd(a,b))) ,for
any number
phi(p^k) = p^k - p^(k-1) ,where p is a prime number, '^'
indicates power
Sum of values of totient functions of all divisors of n
is equal to n.

```

3.7 FFT

```

using CD = complex <double>;
typedef long long LL;
const double PI = acos(-1.0L);

int N;
vector<int> perm;
vector<CD> wp[2];
void precalculate(int n) {
    assert((n & (n - 1)) == 0), N = n;
    perm = vector<int>(N, 0);
    for (int k = 1; k < N; k <= 1) {
        for (int i = 0; i < k; i++) {
            perm[i] <= 1;
            perm[i + k] = 1 + perm[i];
        }
    }
    wp[0] = wp[1] = vector<CD>(N);
    for (int i = 0; i < N; i++) {
        wp[0][i] = CD(cos(2 * PI * i / N), sin(2 * PI * i / N));
        wp[1][i] = CD(cos(2 * PI * i / N), -sin(2 * PI * i / N));
    }
}

void fft(vector<CD> &v, bool invert = false) {
    if (v.size() != perm.size()) precalculate(v.size());
    for (int i = 0; i < N; i++)

```

```

        if (i < perm[i]) swap(v[i], v[perm[i]]);
    for (int len = 2; len <= N; len *= 2) {
        for (int i = 0, d = N / len; i < N; i += len) {
            for (int j = 0, idx = 0; j < len / 2; j++, idx += d) {
                CD x = v[i + j];
                CD y = wp[invert][idx] * v[i + j + len / 2];
                v[i + j] = x + y;
                v[i + j + len / 2] = x - y;
            }
        }
    }
    if (invert) {
        for (int i = 0; i < N; i++) v[i] /= N;
    }
}

void pairfft(vector<CD> &a, vector<CD> &b, bool invert = false) {
    int N = a.size();
    vector<CD> p(N);
    for (int i = 0; i < N; i++) p[i] = a[i] + b[i] * CD(0, 1);
    fft(p, invert);
    p.push_back(p[0]);
    for (int i = 0; i < N; i++) {
        if (invert) {
            a[i] = CD(p[i].real(), 0);
            b[i] = CD(p[i].imag(), 0);
        } else {
            a[i] = (p[i] + conj(p[N - i])) * CD(0.5, 0);
            b[i] = (p[i] - conj(p[N - i])) * CD(0, -0.5);
        }
    }
}

vector<LL> multiply(const vector<LL> &a, const vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    fa.resize(n);
    fb.resize(n);
    // fft(fa); fft(fb);
    pairfft(fa, fb);
    for (int i = 0; i < n; i++) fa[i] = fa[i] * fb[i];
    fft(fa, true);

```

```

    vector<LL> ans(n);
    for (int i = 0; i < n; i++) ans[i] = round(fa[i].real());
    return ans;
}

const int M = 1e9 + 7, B = sqrt(M) + 1;
vector<LL> anyMod(const vector<LL> &a, const vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> al(n), ar(n), bl(n), br(n);
    for (int i = 0; i < a.size(); i++) al[i] = a[i] % M / B, ar[i] = a[i] % M % B;
    for (int i = 0; i < b.size(); i++) bl[i] = b[i] % M / B, br[i] = b[i] % M % B;
    pairfft(al, ar);
    pairfft(bl, br);
    // fft(al); fft(ar); fft(bl); fft(br);
    for (int i = 0; i < n; i++) {
        CD ll = (al[i] * bl[i]), lr = (al[i] * br[i]);
        CD rl = (ar[i] * bl[i]), rr = (ar[i] * br[i]);
        al[i] = ll;
        ar[i] = lr;
        bl[i] = rl;
        br[i] = rr;
    }
    pairfft(al, ar, true);
    pairfft(bl, br, true);
    // fft(al, true); fft(ar, true); fft(bl, true); fft(br, true);
    vector<LL> ans(n);
    for (int i = 0; i < n; i++) {
        LL right = round(br[i].real()), left = round(al[i].real());
        ;
        LL mid = round(round(bl[i].real()) + round(ar[i].real()));
        ans[i] = ((left % M) * B * B + (mid % M) * B + right) % M;
    }
    return ans;
}

```

3.8 LargePrime

```

vector<int> sieve(const int N, const int Q = 17, const int L = 1 << 15) {

```

```
static const int rs[] = {1, 7, 11, 13, 17, 19, 23, 29};
struct P {
    P(int p) : p(p) {}
    int p; int pos[8];
};
auto approx_prime_count = [] (const int N) -> int {
    return N > 60184 ? N / (log(N) - 1.1)
        : max(1., N / (log(N) - 1.11)) + 1;
};

const int v = sqrt(N), vv = sqrt(v);
vector<bool> isp(v + 1, true);
for (int i = 2; i <= vv; ++i) if (isp[i]) {
    for (int j = i * i; j <= v; j += i) isp[j] = false;
}

const int rsize = approx_prime_count(N + 30);
vector<int> primes = {2, 3, 5}; int psize = 3;
primes.resize(rsize);

vector<P> sprimes; size_t pbeg = 0;
int prod = 1;
for (int p = 7; p <= v; ++p) {
    if (!isp[p]) continue;
    if (p <= Q) prod *= p, ++pbeg, primes[psize++] = p;
    auto pp = P(p);
    for (int t = 0; t < 8; ++t) {
        int j = (p <= Q) ? p : p * p;
        while (j % 30 != rs[t]) j += p << 1;
        pp.pos[t] = j / 30;
    }
    sprimes.push_back(pp);
}

vector<unsigned char> pre(prod, 0xFF);
for (size_t pi = 0; pi < pbeg; ++pi) {
    auto pp = sprimes[pi]; const int p = pp.p;
    for (int t = 0; t < 8; ++t) {
        const unsigned char m = ~(1 << t);
        for (int i = pp.pos[t]; i < prod; i += p) pre[i] &=
            m;
    }
}

const int block_size = (L + prod - 1) / prod * prod;
```

```
vector<unsigned char> block(block_size); unsigned char*
    pblock = block.data();
const int M = (N + 29) / 30;

for (int beg = 0; beg < M; beg += block_size, pblock -=
    block_size) {
    int end = min(M, beg + block_size);
    for (int i = beg; i < end; i += prod) {
        copy(pre.begin(), pre.end(), pblock + i);
    }
    if (beg == 0) pblock[0] &= 0xFE;
    for (size_t pi = pbeg; pi < sprimes.size(); ++pi) {
        auto& pp = sprimes[pi];
        const int p = pp.p;
        for (int t = 0; t < 8; ++t) {
            int i = pp.pos[t]; const unsigned char m = ~(1 <<
                t);
            for (; i < end; i += p) pblock[i] &= m;
            pp.pos[t] = i;
        }
    }
    for (int i = beg; i < end; ++i) {
        for (int m = pblock[i]; m > 0; m &= m - 1) {
            primes[psize++] = i * 30 + rs[__builtin_ctz(m)];
        }
    }
    assert(psize <= rsize);
    while (psize > 0 && primes[psize - 1] > N) --psize;
    primes.resize(psize);
    return primes;
}

3.9 Matrix
```

```
int n;
struct Matrix{
    vector<vector<LL>> Mat = vector<vector<LL>>(n, vector<
        LL>(n));
    // memset(Mat,0,sizeof(Mat));
    Matrix operator*(const Matrix &other){
        Matrix product;
        for (int i = 0; i < n; i++){
            for (int j = 0; j < n; j++){
                for (int k = 0; k < n; k++){
                    LL temp = ((Mat[i][k] % mod)*(other.Mat[k][j] %
                        mod))%mod;
```

```
product.Mat[i][j] = (product.Mat[i][j] % mod +
        temp % mod) % mod;
            }
        }
    }
    return product;
}
};
Matrix MatExpo(Matrix a, int p){
    Matrix product;
    for (int i = 0; i < n; i++)
        product.Mat[i][i] = 1;
    while (p > 0){
        if (p % 2) product = product * a;
        p /= 2;
        a = a * a;
    }
    return product;
}
```

3.10 Mint

```
int mint::M = 1e9 + 7;
class mint {
private:
    int value;
    static int M;

    void normalize() {
        value %= M;
        if (value < 0) value += M;
    }

    int mpow(int x, int n) const {
        if (n == -1) n = M - 2;
        int ans = 1;
        while (n) {
            if (n & 1) ans = (ans * x) % M;
            n >>= 1;
            x = (x * x) % M;
        }
        return ans;
    }

public:
    mint() : value(0){};
    mint(int value) : value(value) { normalize(); }
```



```

mint& operator=(int value) {
    this->value = value;
    normalize();
    return *this;
}

mint operator+(const mint& other) const { return mint(
    value + other.value); }
mint operator+(int other) const { return mint(value +
    other); }
mint operator-(const mint& other) const { return mint(
    value - other.value); }
mint operator-(int other) const { return mint(value -
    other); }
mint operator*(const mint& other) const { return mint(
    value * other.value); }
mint operator*(int other) const { return mint(value *
    other); }
mint operator/(const mint& other) const { return *this
    * mpow(other.value, -1); }
mint operator/(int other) const { return *this * mpow(
    other, -1); }

mint& operator+=(const mint& other) {
    value += other.value;
    normalize();
    return *this;
}
mint& operator+=(int other) {
    value += other;
    normalize();
    return *this;
}
mint& operator-=(const mint& other) {
    value -= other.value;
    normalize();
    return *this;
}
mint& operator-=(int other) {
    value -= other;
    normalize();
    return *this;
}
mint& operator*=(const mint& other) {
    value *= other.value;
    normalize();
    return *this;
}

```

```

    normalize();
    return *this;
}
mint& operator*=(int other) {
    value *= other;
    normalize();
    return *this;
}
mint& operator/=(const mint& other) {
    value = (value * mpow(other.value, -1));
    normalize();
    return *this;
}
mint& operator/=(int other) {
    value = (value * mpow(other, -1));
    normalize();
    return *this;
}

mint pow(int expo) const { return mint(mpow(value, expo
)); }
mint pow(const mint& expo) const { return mint(mpow(
    value, expo.value)); }

friend ostream& operator<<(ostream& os, const mint& var
) {
    os << var.value;
    return os;
}
friend istream& operator>>(istream& is, mint& var) {
    is >> var.value;
    var.normalize();
    return is;
}

int get() { return value; }
};

namespace com {
mint fact[N], inv[N], inv_fact[N];
void init() {
    fact[0] = inv_fact[0] = 1;
    for (int i = 1; i < N; i++) {
        inv[i] = i == 1 ? 1 : inv[i - mod % i] * (mod / i +
            1);
        fact[i] = fact[i - 1] * i;
    }
}

```

```

    inv_fact[i] = inv_fact[i - 1] * inv[i];
}
}

mint C(int n, int r) { return (r < 0 or r > n) ? mint(0)
    : fact[n] * inv_fact[r] * inv_fact[n - r]; }
mint P(int n, int r) { return (r < 0 or r > n) ? mint(0)
    : fact[n] * inv_fact[n - r]; }

mint C(mint& n, int r) { return C(n.get(), r); }
mint P(mint& n, int r) { return P(n.get(), r); }

mint C(int& n, mint& r) { return C(n, r.get()); }
mint P(int& n, mint& r) { return P(n, r.get()); }

mint C(mint& n, mint& r) { return C(n.get(), r.get()); }
mint P(mint& n, mint& r) { return P(n.get(), r.get()); }
} // namespace com
using namespace com;

```

3.11 NOD and SOD

```

// NUMBER = p_1^a_1 * p_2^a_2 .... p_n^a_n
LL NOD = 1, SOD = 1, POD = 1, POWER = 1;
for(int i = 0; i < n; i++) {
    LL p, a; cin >> p >> a;
    NOD = (NOD * (a + 1)) % MOD;
    SOD = ((SOD * (bigmod(p, a + 1, MOD) + MOD - 1)) % MOD
        * inv[p - 1]) % MOD;
    POD = bigmod(POD, a + 1, MOD) * bigmod(bigmod(x, a * (a
        + 1) / 2, MOD), POWER, MOD) % MOD;
    POWER = (POWER * (a + 1)) % (MOD - 1);
}
cout << NOD << ' ' << SOD << ' ' << POD << '\n';
// FULL TEMPLATE
using LL = long long;
using ULL = unsigned long long;
namespace sieve {
const int N = 1e7;
vector<int> primes;
int spf[N + 5], phi[N + 5], NOD[N + 5], cnt[N + 5], POW[N
    + 5];
bool prime[N + 5];
int SOD[N + 5];
void init() {
    fill(prime + 2, prime + N + 1, 1);
    SOD[1] = NOD[1] = phi[1] = spf[1] = 1;
}

```

```

for (LL i = 2; i <= N; i++) {
    if (prime[i]) {
        primes.push_back(i), spf[i] = i;
        phi[i] = i - 1;
        NOD[i] = 2, cnt[i] = 1;
        SOD[i] = i + 1, POW[i] = i;
    }
    for (auto p : primes) {
        if (p * i > N or p > spf[i]) break;
        prime[p * i] = false, spf[p * i] = p;
        if (i % p == 0) {
            phi[p * i] = p * phi[i];
            NOD[p * i] = NOD[i] / (cnt[i] + 1) * (cnt[i] + 2);
            cnt[p * i] = cnt[i] + 1;
            SOD[p * i] = SOD[i] / SOD[POW[i]] * (SOD[POW[i]] + p * POW[i]);
            POW[p * i] = p * POW[i];
            break;
        } else {
            phi[p * i] = phi[p] * phi[i];
            NOD[p * i] = NOD[p] * NOD[i], cnt[p * i] = 1;
            SOD[p * i] = SOD[p] * SOD[i], POW[p * i] = p;
        }
    }
}

// CSOD
LL csod(LL n) {
    LL ans = 0;
    for (LL i = 2; i * i <= n; ++i) {
        LL j = n / i;
        ans += (i + j) * (j - i + 1) / 2;
        ans += i * (j - i);
    }
    return ans;
}

summation of NOD(d)[d|n] = product of g(e_k + 1)[n=p_k^a_k]
g(x) = x * (x + 1) / 2

```

3.12 Pollard rho

```

namespace rho{
    inline LL mul(LL a, LL b, LL mod) {
        LL result = 0;

```

```

        while (b) {
            if (b & 1) result = (result + a) % mod;
            a = (a + a) % mod;
            b >>= 1;
        }
        return result;
    }
    inline LL bigmod(LL num, LL pow, LL mod){
        LL ans = 1;
        for( ; pow > 0; pow >>= 1, num = mul(num, num, mod)){
            if(pow&1) ans = mul(ans, num, mod);
            return ans;
        }
    }
    inline bool is_prime(LL n){
        if(n < 2 or n % 6 % 4 != 1) return (n|1) == 3;
        LL a[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022};
        LL s = __builtin_ctzll(n-1), d = n >> s;
        for(LL x: a){
            LL p = bigmod(x % n, d, n), i = s;
            for( ; p != 1 and p != n-1 and x % n and i--; p = mul(p, p, n));
            if(p != n-1 and i != s) return false;
        }
        return true;
    }
    LL f(LL x, LL n) {
        return mul(x, x, n) + 1;
    }
    LL get_factor(LL n) {
        LL x = 0, y = 0, t = 0, prod = 2, i = 2, q;
        for( ; t++ %40 or __gcd(prod, n) == 1; x = f(x, n), y = f(f(y, n), n) ){
            (x == y) ? x = i++, y = f(x, n) : 0;
            prod = (q = mul(prod, max(x,y) - min(x,y), n)) ? q : prod;
        }
        return __gcd(prod, n);
    }
    void _factor(LL n, map <LL, int> &res) {
        if(n == 1) return;
        if(is_prime(n)) res[n]++;
        else {
            LL x = get_factor(n);
            _factor(x, res);
            _factor(n / x, res);
        }
    }

```

```

    }
}
map <LL, int> factorize(LL n){
    map <LL, int> res;
    if(n < 2) return res;
    LL small_primes[] = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97 };
    for (LL p: small_primes)
        for( ; n % p == 0; n /= p, res[p]++);
    _factor(n, res);
    return res;
}
}

```

3.13 Sieve

```

const int N = 10000000;
vector <int> lp(N), pr;
for (int i = 2; i < N; i++) {
    if (lp[i] == 0) {
        lp[i] = i;
        pr.push_back (i);
    }
    for (int j = 0; i * pr[j] < N; j++) {
        lp[i * pr[j]] = pr[j];
        if (pr[j] == lp[i]) break;
    }
}

```

3.14 nCr

```

namespace com {
    LL fact[N], inv[N], inv_fact[N];
    void init() {
        fact[0] = inv_fact[0] = 1;
        for (int i = 1; i < N; i++) {
            inv[i] = i == 1 ? 1 : (LL)inv[i - mod % i] * (mod / i + 1) % mod;
            fact[i] = (LL)fact[i - 1] * i % mod;
            inv_fact[i] = (LL)inv_fact[i - 1] * inv[i] % mod;
        }
    }
    LL C(int n, int r) { return (r < 0 or r > n) ? 0 : fact[n] * inv_fact[r] % mod * inv_fact[n - r] % mod; }
} // namespace com

```

3.15 ntt

```

const LL N = 1 << 18;
const LL MOD = 786433;

vector<LL> P[N];
LL rev[N], w[N | 1], a[N], b[N], inv_n, g;
LL Pow(LL b, LL p) {
    LL ret = 1;
    while (p) {
        if (p & 1) ret = (ret * b) % MOD;
        b = (b * b) % MOD;
        p >>= 1;
    }
    return ret;
}
LL primitive_root(LL p) {
    vector<LL> factor;
    LL phi = p - 1, n = phi;
    for (LL i = 2; i * i <= n; i++) {
        if (n % i) continue;
        factor.emplace_back(i);
        while (n % i == 0) n /= i;
    }
    if (n > 1) factor.emplace_back(n);
    for (LL res = 2; res <= p; res++) {
        bool ok = true;
        for (LL i = 0; i < factor.size() && ok; i++)
            ok &= Pow(res, phi / factor[i]) != 1;
        if (ok) return res;
    }
    return -1;
}
void prepare(LL n) {
    LL sz = abs(31 - __builtin_clz(n));
    LL r = Pow(g, (MOD - 1) / n);
    inv_n = Pow(n, MOD - 2);
    w[0] = w[n] = 1;
    for (LL i = 1; i < n; i++) w[i] = (w[i - 1] * r) % MOD;
    for (LL i = 1; i < n; i++)
        rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (sz - 1));
}
void NTT(LL *a, LL n, LL dir = 0) {
    for (LL i = 1; i < n - 1; i++)
        if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (LL m = 2; m <= n; m <= 1) {
        for (LL i = 0; i < n; i += m) {

```

```

            for (LL j = 0; j < (m >> 1); j++) {
                LL &u = a[i + j], &v = a[i + j + (m >> 1)];
                LL t = v * w[dir ? n - n / m * j : n / m * j] %
                    MOD;
                v = u - t < 0 ? u - t + MOD : u - t;
                u = u + t >= MOD ? u + t - MOD : u + t;
            }
        }
    }
    if (dir)
        for (LL i = 0; i < n; i++) a[i] = (inv_n * a[i]) %
            MOD;
}
vector<LL> mul(vector<LL> p, vector<LL> q) {
    LL n = p.size(), m = q.size();
    LL t = n + m - 1, sz = 1;
    while (sz < t) sz <= 1;
    prepare(sz);

    for (LL i = 0; i < n; i++) a[i] = p[i];
    for (LL i = 0; i < m; i++) b[i] = q[i];
    for (LL i = n; i < sz; i++) a[i] = 0;
    for (LL i = m; i < sz; i++) b[i] = 0;

    NTT(a, sz);
    NTT(b, sz);
    for (LL i = 0; i < sz; i++) a[i] = (a[i] * b[i]) % MOD;
    NTT(a, sz, 1);

    vector<LL> c(a, a + sz);
    while (c.size() && c.back() == 0) c.pop_back();
    return c;
}

```

4 Graph

4.1 Bellman Ford

```

void bellmanford(int n, int m, vector<int> edge[], int
    dist[], int src){
    fill(dist, dist + n, INT_MAX);
    dist[src] = 0;
    int i, j, k;
    vector<int> v;
    for (i = 0; i < n; i++){
        for (j = 0; j < m; j++) {
            v = edge[j];
            if (dist[v[1]] > dist[v[0]] + v[2])

```

```

                dist[v[1]] = dist[v[0]] + v[2];
            }
        }
    }
    for (j = 0; j < m; j++){ // For checking negative loop
        v = edge[j];
        if (dist[v[1]] > dist[v[0]] + v[2]){
            fill(dist, dist + n, INT_MIN); // Negative loop
            detected
            return;
        }
    }
}

```

4.2 BridgeTree

```

vector<PLL> g[N];
vector<int> ng[N];
int disc[N], low[N], mark[N], vis[N], timer = 1;
;

void find_bridge(int u, int p) {
    disc[u] = low[u] = timer++;
    bool fl = 1;
    for (auto [v, id] : g[u]) {
        if (v == p && fl) {
            fl = 0;
            continue;
        }
        if (disc[v]) {
            low[u] = min(low[u], disc[v]);
        } else {
            find_bridge(v, u);
            low[u] = min(low[u], low[v]);
            if (disc[u] < low[v]) {
                mark[id] = 1;
            }
        }
    }
}

void colorComponents(int u, int color) {
    if (vis[u]) return;
    vis[u] = color;
    for (auto [v, id] : g[u]) {
        if (mark[id]) continue;
        colorComponents(v, color);
    }
}

```

```

}

void solve() {
    int n, m;
    cin >> n >> m;
    vector<PLL> edges;
    for (int i = 0; i < m; i++) {
        int u, v;
        cin >> u >> v;
        edges.push_back({u, v});
        g[u].push_back({v, i});
        g[v].push_back({u, i});
    }
    find_bridge(1, 0);
    int color = 1;
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) colorComponents(i, color++);
    }
    for (int i = 0; i < m; i++) {
        if (mark[i]) {
            ng[vis[edges[i].first]].push_back(vis[edges[i].second]);
            ng[vis[edges[i].second]].push_back(vis[edges[i].first]);
        }
    }
}

```

4.3 DSU, MST

```

class DSU {
    vector<int> parent, size;

public:
    DSU(int n) : parent(n + 1), size(n + 1, 1) { iota(
        parent.begin(), parent.end(), 0); }
    int root(int u) {
        if (parent[u] == u) return u;
        return parent[u] = root(parent[u]);
    }
    bool same(int u, int v) { return root(u) == root(v); }
    void merge(int u, int v) {
        u = root(u), v = root(v);
        if (u == v) return;
        if (size[u] < size[v]) swap(u, v);
        parent[v] = u, size[u] += size[v];
    }
}

```

```

};

int kruskal(vector<tuple<int, int, int>> edges, int n) {
    sort(edges.begin(), edges.end());
    DSU mst(n);
    int cost = 0;
    for (auto &[w, u, v] : edges) {
        if (mst.same(u, v)) continue;
        mst.merge(u, v);
        cost += w;
    }
    return cost;
}

// PRIM'S SPANNING TREE (MST)
DIJKSTRA code...
start from a node, and push nodes which are not marked
popped edges weight are taken

```

4.4 Dijkstra

```

struct node {
    int to;
    LL weight;
    bool operator<(const node &a) const {
        return weight > a.weight;
    }
};

vector<node> adj[N];
void dijkstra(int src, vector<LL> &dist, vector<int> &parent) {
    parent.assign(n + 1, -1);
    priority_queue<node> pq;
    pq.push({src, 0});
    dist[src] = 0;
    parent[src] = -1;
    while(!pq.empty()) {
        auto cur = pq.top(); pq.pop();
        for(auto next : adj[cur.to]) {
            if(dist[next.to] > dist[cur.to] + next.weight) {
                dist[next.to] = dist[cur.to] + next.weight;
                pq.push({next.to, dist[next.to]});
                parent[next.to] = cur.to;
            }
        }
    }
}

```

4.5 ETT, VT

```

struct euler_tour {
    int time = 0;
    tree &T;
    int n;
    vector<int> start, finish, level, par;
    euler_tour(tree &T, int root = 0)
        : T(T), n(T.n), start(n), finish(n), level(n), par(n) {
        time = 0;
        call(root);
    }
    void call(int node, int p = -1) {
        if (p != -1) level[node] = level[p] + 1;
        start[node] = time++;
        for (int e : T[node])
            if (e != p) call(e, node);
        par[node] = p;
        finish[node] = time++;
    }
    bool isAncestor(int node, int par) {
        return start[par] <= start[node] and finish[par] >= finish[node];
    }
    int subtreeSize(int node) { return finish[node] - start[node] + 1 >> 1; }
};

tree virtual_tree(vector<int> &nodes, lca_table &table,
    euler_tour &tour) {
    sort(nodes.begin(), nodes.end(),
        [&](int x, int y) { return tour.start[x] < tour.start[y]; });
    int n = nodes.size();
    for (int i = 0; i + 1 < n; i++)
        nodes.push_back(table.lca(nodes[i], nodes[i + 1]));
    sort(nodes.begin(), nodes.end());
    nodes.erase(unique(nodes.begin(), nodes.end()), nodes.end());
    sort(nodes.begin(), nodes.end(),
        [&](int x, int y) { return tour.start[x] < tour.start[y]; });
    n = nodes.size();
    stack<int> st;
    st.push(0);
    tree ans(n);
    for (int i = 1; i < n; i++) {

```

```

    while (!tour.isAncestor(nodes[i], nodes[st.top()]))
        st.pop();
    ans.addEdge(st.top(), i);
    st.push(i);
}
return ans;
}

set<int> getCenters(tree &T) {
    int n = T.n;
    vector<int> deg(n), q;
    set<int> s;
    for (int i = 0; i < n; i++) {
        deg[i] = T[i].size();
        if (deg[i] == 1) q.push_back(i);
        s.insert(i);
    }
    for (vector<int> t; s.size() > 2; q = t) {
        for (auto x : q) {
            for (auto e : T[x])
                if (--deg[e] == 1) t.push_back(e);
            s.erase(x);
        }
    }
    return s;
}

```

4.6 HLD

```

int sub[nmax], par[nmax], depth[nmax];
vector<int> adj[nmax];

void dfs_sz(int u, int p) {
    sub[u] = 1, par[u] = p;
    depth[u] = (p == -1) ? 0 : depth[p] + 1;
    int mx = 0; /// HLD
    for (auto &v : adj[u]) {
        if (v == p) continue;
        dfs_sz(v, u);
        sub[u] += sub[v];
        if (sub[v] > mx) mx = sub[v], swap(v, adj[u][0]); ///
        HLD
    }
}

int head[nmax];
int st[nmax], en[nmax], clk;
int dfsarr[nmax]; /// segtree will be built on this

```

```

void dfs_hld(int u, int p) {
    st[u] = ++clk;
    /// put stuff in dfarr here
    dfsarr[clk] = val[u]; /// node specific value

    head[u] = (p != -1 && adj[p][0] == u) ? head[p] : u; ///
    / HLD
    for (auto &v : adj[u]) {
        if (v == p) continue;
        dfs_hld(v, u);
    }
    en[u] = clk;
}

int lca(int a, int b) {
    for (; head[a] != head[b]; b = par[head[b]])
        if (depth[head[a]] > depth[head[b]]) swap(a, b);
    if (depth[a] > depth[b]) swap(a, b);
    return a;
}

/// process node u upto it's ancestor a
/// if excl is true, a will not be processed
int chainProcess(int a, int u, bool excl = false) {
    for (; head[u] != head[a]; u = par[head[u]]) {
        func(st[head[u]], st[u]); /// processing
        /// query(1, 1, n, st[head[u]
        ], st[u])
    }
    func(st[a] + excl, st[u]); /// processing
}

/// process path from node u to node v, if order matters
/// will be tough
/// if excl is true lca will not be processed
int pathProcess(int a, int b, bool excl) {
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (depth[head[a]] > depth[head[b]]) swap(a, b);
        func(st[head[b]], st[b]);
    }
    if (depth[a] > depth[b]) swap(a, b);
    func(st[a] + excl, st[b]);
}

```

4.7 K th shortest path

```

void K_shortest(int n, int m) {
    int st, des, k, u, v;
    LL w;
    scanf("%d%d%d", &st, &des, &k);
    st--, des--;
    vector<vector<pii>> edges(n);
    for (int i = 0; i < m; i++) {
        scanf("%d%d%lld", &u, &v, &w);
        u--, v--;
        edges[u].push_back({v, w});
    }
    vector<vector<LL>> dis(n, vector<LL>(k + 1, 1e8));
    vector<int> vis(n);
    priority_queue<pii, vector<pii>, greater<pii>> q;

    q.emplace(0LL, st);
    while (!q.empty()) {
        v = q.top().second, w = q.top().first;
        q.pop();
        if (vis[v] >= k) continue;
        /// for the variant, check if this path is greater
        /// than previous, if not, continue
        /// if(vis[v]>0 && w == dis[v][vis[v]-1]) continue;
        dis[v][vis[v]] = w;
        vis[v]++;
        for (auto nd : edges[v]) {
            q.emplace(w + nd.first, nd.second);
        }
    }
    LL ans = dis[des][k - 1];
    if (ans == 1e8) ans = -1;
    printf("%lld\n", ans);
}

```

4.8 LCA, CD

```

struct Tree {
    vector<vector<int>> adj;
    Tree(int N) : adj(N + 1) {}
    void addEdges(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
};

class LCA {
    int N, K;

```

```

vector<vector<int>> &adj, anc;
vector<int> level;

public:
LCA(Tree &tree) : adj(tree.adj) {
    N = tree.adj.size() - 1;
    K = 33 - __builtin_clz(N);
    anc.assign(N + 1, vector<int>(K));
    level.assign(N + 1, 0);
    initLCA(1);
}

void initLCA(int u, int p = 0) {
    anc[u][0] = p;
    level[u] = level[p] + 1;
    for (int i = 1; i < K; i++) {
        anc[u][i] = anc[anc[u][i - 1]][i - 1];
    }
    for (auto v : adj[u])
        if (v != p) {
            initLCA(v, u);
        }
}

int getAnc(int u, int k) {
    for (int i = K - 1; i >= 0; i--)
        if (k & (1 << i)) u = anc[u][i];
    return u;
}

int lca(int u, int v) {
    if (level[u] > level[v]) swap(u, v);
    v = getAnc(v, level[v] - level[u]);

    if (u == v) return u;
    for (int i = K - 1; i >= 0; i--) {
        if (anc[u][i] != anc[v][i]) u = anc[u][i], v = anc[v][i];
    }
    return anc[u][0];
}

int dis(int u, int v) { return level[u] + level[v] - 2
    * level[lca(u, v)]; }

};

class CD {
    vector<vector<int>> adj;
    vector<int> sub;

```

```

    vector<bool> blocked;
    int N;

public:
CD(Tree &tree) : adj(tree.adj) {
    N = tree.adj.size() - 1;
    blocked.assign(N + 1, 0);
    sub.assign(N + 1, 0);
    compute();
}

void compute(int u = 1, int p = 0) {
    sub[u] = 1;
    for (auto v : adj[u])
        if (v != p) {
            compute(v, u);
            sub[u] += sub[v];
        }
}

int centroid(int u, int p = 0) {
    int tot = sub[u];
    for (auto v : adj[u]) {
        if (v == p || blocked[v]) continue;
        if (2 * sub[v] > tot) {
            sub[u] = tot - sub[v];
            sub[v] = tot;
            return centroid(v, u);
        }
    }
    return u;
}

int count(int u, int p) { // calculate ans
}

void update(int u, int p) { // update
}

int decompose(int u = 1) {
    u = centroid(u);
    blocked[u] = 1;
    int ans = 0;

    // Do something here // count() update()
    for (auto v : adj[u])
        if (!blocked[v]) {
            ans += count(v, u);
            update(v, u);
        }
}

```

```

    }
    /// reset updates here

    for (auto v : adj[u])
        if (!blocked[v]) {
            decompose(v);
        }
    return ans;
}
};

```

4.9 block cut tree

```

#include <bits/stdc++.h>

using namespace std;

const int N = 200010;

bitset<N> art, good;
vector<int> g[N], tree[N], st, comp[N];
int n, m, ptr, cur, in[N], low[N], id[N];

void dfs(int u, int from = -1) {
    in[u] = low[u] = ++ptr;
    st.emplace_back(u);
    for (int v : g[u]) if (v ^ from) {
        if (!in[v]) {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] >= in[u]) {
                art[u] = in[u] > 1 || in[v] > 2;
                comp[++cur].emplace_back(u);
                while (comp[cur].back() ^ v) {
                    comp[cur].emplace_back(st.back());
                    st.pop_back();
                }
            }
        } else {
            low[u] = min(low[u], in[v]);
        }
    }
}

void buildTree() {
    ptr = 0;
    for (int i = 1; i <= n; ++i) {

```

```

    if (art[i]) id[i] = ++ptr;
}
for (int i = 1; i <= cur; ++i) {
    int x = ++ptr;
    for (int u : comp[i]) {
        if (art[u]) {
            tree[x].emplace_back(id[u]);
            tree[id[u]].emplace_back(x);
        } else {
            id[u] = x;
        }
    }
}
}

int main() {
    cin >> n >> m;
    while (m--) {
        int u, v;
        scanf("%d %d", &u, &v);
        g[u].emplace_back(v);
        g[v].emplace_back(u);
    }
    for (int i = 1; i <= n; ++i) {
        if (!in[i]) dfs(i);
    }
    buildTree();
    for (int i = 1; i <= ptr; ++i) {
        cout << i << " --> ";
        for (int j : tree[i]) cout << j << " "; cout << '\n';
    }
    return 0;
}

```

4.10 strongly connected component

```

bool vis[N];
vector<int> adj[N], adjr[N];
vector<int> order, component;
// tp = 0, finding topo order,
// tp = 1, reverse edge traversal
void dfs(int u, int tp = 0) {
    vis[u] = true;
    if (tp) component.push_back(u);
    auto& ad = (tp ? adjr : adj);
    for (int v : ad[u])
        if (!vis[v]) dfs(v, tp);
}

```

```

    if (!tp) order.push_back(u);
}

int main() {
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) dfs(i);
    }
    memset(vis, 0, sizeof vis);
    reverse(order.begin(), order.end());
    for (int i : order) {
        if (!vis[i]) {
            // one component is found
            dfs(i, 1), component.clear();
        }
    }
}

```

4.11 tree isomorphism

```

// has to include bigmod
LL Hash(int u, int p) {
    vector<LL> childrenHash;
    for (auto v : adj[u]) if (v != p)
        childrenHash.add(Hash(v, u));
    sort(all(childrenHash));
    LL nodeHash = 0;
    for (int i = 0; i < childrenHash.size(); i++)
        nodeHash = (nodeHash + childrenHash[i] * bigmod(SEED,
            i, MOD)) % MOD;
    return nodeHash;
}

```

5 String

5.1 KMP

```

int KMP(vector<int> &a, vector<int> &b) { // number of
    occurrence of a in b
    vector<int> pi(n);
    for (int i = 1, j = 0; i < n; i++) {
        while (j && a[i] != a[j]) j = pi[j - 1];
        if (a[i] == a[j]) j++;
        pi[i] = j;
    }
    int ans = 0;
    for (int i = 0, j = 0; i < m; i++) {
        while (j && b[i] != a[j]) j = pi[j - 1];
        if (a[j] == b[i]) j++;
        if (j == n) ans++, j = pi[j - 1];
    }
}

```

```

return ans;
}

```

5.2 Manacher

```

void Manacher() {
    vector<int> d1(n);
    // d[i] = number of palindromes taking s[i] as center
    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);
        while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
        d1[i] = k--;
        if (i + k > r) l = i - k, r = i + k;
    }
}

```

```

vector<int> d2(n);
// d[i] = number of palindromes taking s[i-1] and s[i]
// as center
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
    while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) k++;
    d2[i] = k--;
    if (i + k > r) l = i - k - 1, r = i + k;
}
}

```

5.3 SuffixArray

```

void inducedSort (const vector<int> &vec, int val_range,
    vector<int> &SA, const vector<int> &sl, const
    vector<int> &lms_idx) {
    vector<int> l(val_range, 0), r(val_range, 0);
    for (int c : vec) {
        ++r[c]; if (c + 1 < val_range) ++l[c + 1];
    }
    partial_sum(l.begin(), l.end(), l.begin());
    partial_sum(r.begin(), r.end(), r.begin());
    fill(SA.begin(), SA.end(), -1);
    for (int i = lms_idx.size() - 1; i >= 0; --i) SA[--r[
        vec[lms_idx[i]]]] = lms_idx[i];
    for (int i : SA) if (i > 0 and sl[i - 1]) SA[l[vec[i -
        1]]++] = i - 1;
    fill(r.begin(), r.end(), 0);
    for (int c : vec) ++r[c];
    partial_sum(r.begin(), r.end(), r.begin());
}

```



```

for (int k = SA.size() - 1, i = SA[k]; k; --k, i = SA[k]) {
    if (i and !sl[i - 1]) SA[--r[vec[i - 1]]] = i - 1;
}
}

vector<int> suffixArray (const vector<int> &vec, int val_range) {
    const int n = vec.size();
    vector<int> sl(n), SA(n), lms_idx;
    for (int i = n - 2; i >= 0; --i) {
        sl[i] = vec[i] > vec[i + 1] or (vec[i] == vec[i + 1] and sl[i + 1]);
        if (sl[i] and !sl[i + 1]) lms_idx.emplace_back(i + 1);
    }
    reverse(lms_idx.begin(), lms_idx.end());
    inducedSort(vec, val_range, SA, sl, lms_idx);
    vector<int> new_lms_idx(lms_idx.size()), lms_vec(lms_idx.size());
    for (int i = 0, k = 0; i < n; ++i) {
        if (SA[i] > 0 and !sl[SA[i]] and sl[SA[i] - 1])
            new_lms_idx[k++] = SA[i];
    }
    int cur = 0; SA[n - 1] = 0;
    for (int k = 1; k < new_lms_idx.size(); ++k) {
        int i = new_lms_idx[k - 1], j = new_lms_idx[k];
        if (vec[i] ^ vec[j]) {
            SA[j] = ++cur; continue;
        }
        bool flag = 0;
        for (int a = i + 1, b = j + 1; ; ++a, ++b) {
            if (vec[a] ^ vec[b]) {
                flag = 1; break;
            }
            if ((!sl[a] and sl[a - 1]) or (!sl[b] and sl[b - 1])) {
                flag = !(sl[a] and sl[a - 1] and !sl[b] and sl[b - 1]); break;
            }
        }
        SA[j] = flag ? ++cur : cur;
    }
    for (int i = 0; i < lms_idx.size(); ++i) lms_vec[i] = SA[lms_idx[i]];
    if (cur + 1 < lms_idx.size()) {

```

```

        auto lms_SA = suffixArray(lms_vec, cur + 1);
        for (int i = 0; i < lms_idx.size(); ++i) new_lms_idx[i] = lms_idx[lms_SA[i]];
    }
    inducedSort(vec, val_range, SA, sl, new_lms_idx);
    return SA;
}

vector<int> getSuffixArray (const string &s, const int LIM = 128) {
    vector<int> vec(s.size() + 1);
    copy(begin(s), end(s), begin(vec)); vec.back() = '#';
    auto ret = suffixArray(vec, LIM);
    ret.erase(ret.begin()); return ret;
}

// build RMQ on it to get LCP of any two suffix
vector<int> getLCParray (const string &s, const vector<int> &SA) {
    int n = s.size(), k = 0;
    vector<int> lcp(n), rank(n);
    for (int i = 0; i < n; ++i) rank[SA[i]] = i;
    for (int i = 0; i < n; ++i, k ? --k : 0) {
        if (rank[i] == n - 1) {
            k = 0; continue;
        }
        int j = SA[rank[i] + 1];
        while (i + k < n and j + k < n and s[i + k] == s[j + k]) ++k;
        lcp[rank[i]] = k;
    }
    lcp[n - 1] = 0; return lcp;
}

5.4 Z
vector<int> z(string const& s) {
    int n = size(s);
    vector<int> z(n);
    int x = 0, y = 0;
    for (int i = 1; i < n; i++) {
        z[i] = max(0, min(z[i - x], y - i + 1));
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            x = i, y = i + z[i], z[i]++;
        }
    }
    return z;
}

```

}

5.5 double hashing

/*

Simple Library for String Hashing, Uses Double Hash.
 $\text{Hash}(\text{abc} \dots \text{z}) = a \cdot p^n + b \cdot p^{(n-1)} + \dots + z$

In order to convert to Single Hash -

- o Delete operator overloads and fix reduce()
- o Replace all PLL with LL
- o Change mp pairs to appropriate value

Or set M2 = 1, which should be nearly as fast.

Some Primes:

1000000007, 1000000009, 1000000861, 1000099999 (< 2^{30})
 1088888881, 1111211111, 1500000001, 1481481481 (< 2^{31})
 2147483647 ($2^{31}-1$),

Author: anachor

 */

typedef pair<LL, LL> PLL;

namespace Hashing {

#define ff first

#define ss second

const PLL M = {1e9+7, 1e9+9}; //Should be large primes

const LL base = 1259; //Should be larger than alphabet size

const int N = 1e6+7; //Highest length of string

PLL operator+ (const PLL& a, LL x) {return {a.ff + x, a.ss + x};}

PLL operator- (const PLL& a, LL x) {return {a.ff - x, a.ss - x};}

PLL operator* (const PLL& a, LL x) {return {a.ff * x, a.ss * x};}

PLL operator+ (const PLL& a, PLL x) {return {a.ff + x.ff, a.ss + x.ss};}

PLL operator- (const PLL& a, PLL x) {return {a.ff - x.ff, a.ss - x.ss};}

PLL operator* (const PLL& a, PLL x) {return {a.ff * x.ff, a.ss * x.ss};}


```

PLL operator% (const PLL& a, PLL m) {return {a.ff % m
    .ff, a.ss % m.ss};}
ostream& operator<<(ostream& os, PLL hash) {
    return os<<("<<hash.ff<<", "<<hash.ss<<");
}
PLL pb[N];    //powers of base mod M
//Call pre before everything
void hashPre() {
    pb[0] = {1,1};
    for (int i=1; i<N; i++) pb[i] = (pb[i-1] * base)
        %M;
}
//Calculates hashes of all prefixes of s including
//empty prefix
vector<PLL> hashList(string s) {
    int n = s.size();
    vector<PLL> ans(n+1);
    ans[0] = {0,0};
    for (int i=1; i<=n; i++) ans[i] = (ans[i-1] *
        base + s[i-1])%M;
    return ans;
}
//Calculates hash of substring s[l..r] (1 indexed)
PLL substringHash(const vector<PLL> &hashlist, int l,
    int r) {
    return (hashlist[r]+(M-hashlist[l-1])*pb[r-l+1])%
        M;
}
//Calculates Hash of a string
PLL Hash (string s) {
    PLL ans = {0,0};
    for (int i=0; i<s.size(); i++) ans=(ans*base + s[
        i])%M;
    return ans;
}
//Tested on https://toph.co/p/palindromist
//appends c to string
PLL append(PLL cur, char c) {
    return (cur*base + c)%M;
}
//Tested on https://toph.co/p/palindromist
//prepends c to string with size k
PLL prepend(PLL cur, int k, char c) {
    return (pb[k]*c + cur)%M;
}
//Tested on https://toph.co/p/chikongunia

```

```

//replaces the i-th (0-indexed) character from right
//from a to b;
PLL replace(PLL cur, int i, char a, char b) {
    return cur + pb[i] * (M+b-a)%M;
}
//Erases c from front of the string with size len
PLL pop_front(PLL hash, int len, char c) {
    return (hash + pb[len-1]*(M-c))%M;
}
//Tested on https://toph.co/p/palindromist
//concatenates two strings where length of the right
//is k
PLL concat(PLL left, PLL right, int k) {
    return (left*pb[k] + right)%M;
}
PLL power (const PLL& a, LL p) {
    if (p==0) return {1,1};
    PLL ans = power(a, p/2);
    ans = (ans * ans)%M;
    if (p%2) ans = (ans*a)%M;
    return ans;
}
PLL inverse(PLL a) {
    if (M.ss == 1) return power(a, M.ff-2);
    return power(a, (M.ff-1)*(M.ss-1)-1);
}
//Erases c from the back of the string
PLL invb = inverse({base, base});
PLL pop_back(PLL hash, char c) {
    return ((hash-c*M)*invb)%M;
}
//Tested on https://toph.co/p/palindromist
//Calculates hash of string with size len repeated
//cnt times
//This is O(log n). For O(1), pre-calculate inverses
PLL repeat(PLL hash, int len, LL cnt) {
    PLL mul = ((pb[len*cnt]-1+M) * inverse(pb[len]-1+
        M))%M;
    PLL ans = (hash*mul);
    if (pb[len].ff == 1) ans.ff = hash.ff*cnt;
    if (pb[len].ss == 1) ans.ss = hash.ss*cnt;
    return ans%M;
}
// Solves https://judge.yosupo.jp/problem/
//enumerate_palindromes

```

```

using namespace Hashing;
vector<PLL> forwardHash, backwardHash;
int n;
bool check(int l, int r) {
    return substringHash(forwardHash, l, r) ==
        substringHash(backwardHash, n+1-r, n+1-l);
}

```

6 Divide and Conquer

6.1 maximum subarray sum

```

array<LL, 3> maxSubArraySum(std::vector<LL> &v, LL n) {
    LL max_so_far = -INF, max_ending_here = 0, start = 0,
        end = 0, s = 0;
    for(int i = 0; i < n; i++) {
        max_ending_here += v[i];
        if(max_so_far < max_ending_here) {
            max_so_far = max_ending_here;
            start = s, end = i;
        }
        if(max_ending_here < 0) {
            max_ending_here = 0;
            s = i + 1;
        }
    }
    return {max_so_far, start, end};
}

```

7 DP

7.1 CatalanDp

```

const int nmax = 1e4 + 1;
const int mod = 1000000007;
int catalan[nmax + 1];
// comb formula: ((2n)Cn)-((2n)C(n-1)) = (1/(n+1))*((2n)
// Cn)
void genCatalan(int n) {
    catalan[0] = catalan[1] = 1;
    for (int i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (int j = 0; j < i; j++) {
            catalan[i] += (catalan[j] * catalan[i - j - 1]) %
                mod;
            if (catalan[i] >= mod) {
                catalan[i] -= mod;
            }
        }
    }
}

```

```

}
}

7.2 Coin Change

void coin(){ //given different types of coin how many way
number x can be formed?
int n,x,mod=1e9+7; cin>>n>>x;
int a[n], dp[x+1]={};
for(int i=0;i<n;i++){
    cin>>a[i];
    if(a[i]<=x) dp[a[i]]=1;
}
for(int i=1;i<=x;i++){
    for(int j=0;j<n;j++){
        if(i>= a[j]){
            dp[i] += dp[i-a[j]];
            dp[i] %= mod;
        }
    }
}
cout<<dp[x]<<ln;
}

```

7.3 DearrangementDP

```

const int nmax = 2e5 + 1;
int drng[nmax + 1];

void gen_drng(int n) {
    drng[2] = 1;
    for (int i = 3; i <= n; i++) {
        drng[i] = ((i - 1ll) * ((drng[i - 2] + drng[i - 1]) %
            mod)) % mod;
    }
}

```

7.4 Knapsack

```

/*
for 1 ---->
1<=N<=100
1<=W<=105
1<=wi<=W
1<=vi<=1e9
for 2 ---->
1<=N<=100
1<=W<=1e9
1<=wi<=W

```

```

1<=vi<=1e3
*/
int n,W,v[101],w[101],dp[101][N];

int ks(int i,int W){
    if(i>=n) return 0;
    if(dp[i][W]!=-1) return dp[i][W];
    if(W<w[i]) return dp[i][W]=ks(i+1,W);
    else return dp[i][W]=max(ks(i+1,W),ks(i+1,W-w[i])+v[i]);
}

void solve(){
    cin>>n>>W;
    for(int i=0;i<n;i++){
        cin>>w[i]>>v[i];
    }
    cout<<ks(0,W)<<ln;
}

int knpsk2(int i,int val){
    if(val==0) return 0;
    if(i>=n) return INT_MAX;
    if(dp[i][val]!=-1) return dp[i][val];
    int b = ks(i+1,val);
    if(val-v[i]>=0) b = min(b,ks(i+1,val-v[i]) + w[i]);
    return dp[i][val] = b;
}

void solve(){
    cin>>n>>W;
    for(int i=0;i<n;i++){
        cin>>w[i]>>v[i];
    }
    int ans=0, sm=accumulate(v,v+n,0LL);;
    for(int j=sm;j>=0;j--){
        if(ks(0,j)<=W){
            cout<<j<<ln;
            break;
        }
    }
}

```

7.5 SOS

```

/*
Given a fixed array A of 2^N integers, we need to
calculate for all x function F(x) = Sum of all A[i]
such that x&i = i, i.e., i is a subset of x.

```

```

/*
//iterative version
for(int mask = 0; mask < (1<<N); ++mask){
    dp[mask][0] = A[mask]; //handle base case separately (
        leaf states)
    for(int i = 0; i < N; ++i){
        if(mask & (1<<i))
            dp[mask][i] = dp[mask][i-1] + dp[mask^(1<<i)][i-1];
        else
            dp[mask][i] = dp[mask][i-1];
    }
    F[mask] = dp[mask][N-1];
}

//memory optimized, super easy to code.
for(int i = 0; i < (1<<N); ++i)
    F[i] = A[i];
for(int i = 0; i < N; ++i) for(int mask = 0; mask < (1<<N); ++mask){
    if(mask & (1<<i))
        F[mask] += F[mask^(1<<i)];
}

```

7.6 Grundy

```

/* single pile game-> greedy or game dp multiple pile
game and disjunctive(before playing, choose 1 pile)
-> NIM game
else-> Grundy(converts n any game piles to n NIM piles)

```

grundy(x)->the smallest nonreachable Grundy value

there are n pile of games and k type of moves.
if XOR(grundy(games)) == 0: losing state else winning state */

```

vector<int> moves, dp;
int mex(vector<int> &a) {
    set<int> b(a.begin(), a.end());
    for (int i = 0; ; ++i)
        if (!b.count(i)) return i;
}

```

```

int Grundy(int x) {
    if (dp[x] != -1) return dp[x];
    vector<int> reachable;
    for (auto m : moves) {
        if (x - m < 0) continue;
    }
}

```

```

int val = grundys(x - m);
reachable.push_back(val);
}
return dp[x] = mex(reachable);
}

```

8 Geometry

8.1 2D everything

```

using LL = long long;
using ULL = unsigned long long;

```

```

const double PI = acos(-1), EPS = 1e-10;
template <typename DT> DT sq(DT x) {return x * x; }
template <typename DT> int dcmp(DT x) { return fabs(x) <
    EPS ? 0 : (x<0 ? -1 : 1);}

```

```

template <typename DT>
class point{
public:
    DT x,y;
    point() = default;
    point(DT x, DT y): x(x), y(y) {};
    template <typename X> point(point <X> p): x(p.x), y(p.y)
        {} ;
    point operator + (const point &rhs) const { return
        point(x + rhs.x, y + rhs.y); }
    point operator - (const point &rhs) const { return
        point(x - rhs.x, y - rhs.y); }
    point operator * (const point &rhs) const { return
        point(x * rhs.x - y * rhs.y, x * rhs.y + y * rhs.x)
        ;}
    point operator / (const point &rhs) const { return *
        this * point(rhs.x, - rhs.y) / ~(rhs);}

    point operator * (DT M) const { return point(M * x, M
        * y); }
    point operator / (DT M) const { return point(x / M, y
        / M); }
    bool operator < (point rhs) const { return x < rhs.x
        or (x == rhs.x and y < rhs.y); }
    bool operator == (const point &rhs) const { return x ==
        rhs.x and y == rhs.y; }
    bool operator <= (const point &rhs) const { return *
        this < rhs or *this == rhs; }
    bool operator != (const point &rhs) const { return x !=
        rhs.x or y != rhs.y; }

```

```

DT operator & (const point &rhs) const { return x *
    rhs.y - y * rhs.x; } // cross product
DT operator ^ (const point &rhs) const { return x *
    rhs.x + y * rhs.y; } // dot product
DT operator ~() const {return sq(x) + sq(y); }
    //square of norm
    point operator - () const {return *this * -1; }
    friend istream& operator >> (istream &is, point &p) {
        return is >> p.x >> p.y; }
    friend ostream& operator << (ostream &os, const point &
        p) { return os << p.x << " " << p.y; }

    friend DT DisSq(const point &a, const point &b){ return
        sq(a.x-b.x) + sq(a.y-b.y); }
    friend DT TriArea(const point &a, const point &b, const
        point &c) { return (b-a) & (c-a); }
    friend DT UTriArea(const point &a, const point &b,
        const point &c) { return abs(TriArea(a, b, c)); }
    friend bool Collinear(const point &a, const point &b,
        const point &c) { return UTriArea(a, b, c) < EPS; }
    friend double Angle(const point &u) { return atan2(u.y,
        u.x); }
    friend double Angle(const point &a, const point &b) {
        double ans = Angle(b) - Angle(a);
        return ans <= -PI ? ans + 2*PI : (ans > PI ? ans - 2*
            PI : ans);
    }
    point Perp(const point &a){ return point(-a.y, a.x); }
    point Conj(const point &a){ return point(a.x, -a.y); }
};
template <typename DT> using polygon = vector <point <DT>
    >>;
template <typename DT>
class polarComp {
    point <DT> O, dir;
    bool half(point <DT> p) {
        return dcmp(dir & p) < 0 || (dcmp(dir & p) == 0 &&
            dcmp(dir ^ p) > 0);
    }
public:
    polarComp(point <DT> O = point(0, 0), point <DT> dir =
        point(1, 0)) : O(O), dir(dir) {}
    bool operator() (point <DT> p, point <DT> q) {
        return make_tuple(half(p), 0) < make_tuple(half(q), (
            p & q));
    }
}

```

```

}; // given a pivot point and an initial direction, sorts
    by Angle with the given direction

```

```

template <typename DT>
class line{
public:
    point <DT> dir, O; // direction of vector and starting
        point
    line(point <DT> p, point <DT> q): dir(q - p), O(p) {};

    bool Contains(const point <double> &p){
        return fabs(p - O & dir) < EPS;
    } // checks whether the line Contains a certain point
    template <typename XT> point <XT> At(XT t){
        return point <XT> (dir) * t + O;
    } // inserts value of t in the vector representation,
        finds the point which is O + Dir*t
    double AtInv(const point <double> &p){
        return abs(dir.x) > 0 ? (p - O).x / dir.x : (p - O).y
            / dir.y;
    } // if the line Contains a point, gives the value t
        such that, p = O+Dir*t
    line Perp(point <DT> p){
        return line(p, p + (-dir.y, dir.x));
    }
    point <DT> ProjOfPoint(const point <DT> &P) {
        return O + dir * ((P - O) ^ dir) / (~dir);
    }
    double DisOfPoint(const point <DT> &P) {
        return fabs(dir & (P - O))/sqrt(~(dir));
    }
    friend bool Parallel(line& L, line& R){
        return fabs(R.dir & L.dir) < EPS;
    }
    friend int Intersects(line& L, line& R){
        return Parallel(L, R) ? R.Contains(L.O) ? -1 : 0 : 1;
    }
    friend pair <double, double> IntersectionAt(line &L,
        line &R){
        double r = double((L.O - R.O) & L.dir)/(R.dir & L.dir
            );
        double l = double((R.O - L.O) & R.dir)/(L.dir & R.dir
            );
        return {l, r};
    }
}

```

```

friend pair <int, point<double>> IntersectionPoint(line
    L, line R, int _L = 0, int _R = 0){
    // _L and _R can be 0 to 3, 0 is a normal line, 3 is
    // a segment, 1 and 2 are rays (considered bitwise)
    int ok = Intersects(L, R);
    if(ok == 0) return {0, {0, 0}};
    if(ok == 1){
        auto [l,r] = IntersectionAt(L, R);
        if(l < (0-EPS) and _L & 2 ) return {0, {0, 0}};
        if(l > (1+EPS) and _L & 1) return {0, {0, 0}};
        if(r < (0-EPS) and _R & 2 ) return {0, {0, 0}};
        if(r > (1+EPS) and _R & 1) return {0, {0, 0}};
        return {1, L.At(1)};
    }
    return {-1, {0,0}}; // they are the same line
};

template <typename DT>
class circle {
public:
    point <DT> O; DT R;
    circle(const point <DT> &O = {0, 0}, DT R = 0) : O(O),
        R(R) {}
    // the next two make sense only on circle <double>
    circle(const point <DT> &A, const point <DT> &B, const
        point <DT> &C){
        point <DT> X = (A + B) / 2, Y = (B + C) / 2, d1 = Perp(
            A - B), d2 = Perp(B - C);
        O = IntersectionPoint(line(X, d1), line(Y, d2)).
            second;
        R = sqrt(~(O - A));
    }
    circle(const point <DT> &A, const point <DT> &B, DT R){
        point <DT> X = (A + B) / 2, d = Perp(A - B);
        d = d * (R / sqrt(~(d)));
        O = X + d;
        R = sqrt(~(O - A));
    }
    double SectorArea(double ang) {
        // Area of a sector of circle
        return ang * R * R * .5;
    }
    double SectorArea(const point <DT> &a, const point <
        DT> &b) {
        return SectorArea(Angle(a - O, b - O));
    }
};

```

```

double ChordArea(const point <DT> &a, const point <DT>
    &b) {
    // Area between sector and its chord
    return SectorArea(a, b) - 0.5 * TriArea(O, a, b);
}

int Contains(const point <DT> &p){
    // 0 for outside, 1 for inside, -1 for on the
    // circle
    DT d = DisSq(O, p);
    return d > R * R ? 0 : (d == R * R ? -1 : 1);
}

friend tuple <int, point <DT>, point <DT>>
    IntersectionPoint(const circle &a, const circle &b)
    {
        if(a.R == b.R and a.O == b.O) return {-1, {0, 0}, {0,
            0}};
        double d = sqrt(DisSq(a.O, b.O));
        if(d > a.R + b.R or d < fabs(a.R - b.R)) return {0,
            {0, 0}, {0, 0}};
        double z = (sq(a.R) + sq(d) - sq(b.R)) / (2 * d);
        double y = sqrt(sq(a.R) - sq(z));
        point <DT> O = b.O - a.O, h = Perp(O) * (y / sqrt(~O)
            );
        O = a.O + O * (z / sqrt(~O));
        return make_tuple(1 + (~h) > EPS), O - h, O + h);
    }

friend tuple <int, point <DT>, point <DT>>
    IntersectionPoint(const circle &C, line <DT> L) {
        point <DT> P = L.ProjOfPoint(C.O);
        double D = DisSq(C.O, P);
        if(D > C.R * C.R) return {0, {0, 0}, {0, 0}};
        double x = sqrt(C.R * C.R - D);
        point <DT> h = L.dir * (x / sqrt(~L.dir));
        return {1 + (x > EPS), P - h, P + h};
    }

double SegmentedArea(point <DT> &a, point <DT> &b) {
    // signed area of the intersection between the circle
    // and triangle OAB
    double ans = SectorArea(a, b);
    line <DT> L(a, b);
    auto [cnt, p1, p2] = IntersectionPoint(*this, L);
    if(cnt < 2) return ans;
    double t1 = L.AtInv(p1), t2 = L.AtInv(p2);
    if(t2 < 0 or t1 > 1) return ans;
    if(t1 < 0) p1 = a;
    if(t2 > 1) p2 = b;
}

```

```

    return ans - ChordArea(p1, p2);
}

};

namespace polygon_algo{
    template <typename DT> polygon <DT> ConvexHull(polygon
        <DT> &PT){
        sort(PT.begin(), PT.end());
        int m = 0, n = PT.size();
        polygon <DT> hull(n + n + 2);
        for(int i = 0; i < n; i++){
            for( ; m > 1 and TriArea(hull[m-2], hull[m-1], PT[i]
                ]) <= 0; m-- );
            hull[m++] = PT[i];
        }
        for(int i = n - 2, k = m; i >= 0; i--){
            for( ; m > k and TriArea(hull[m - 2], hull[m - 1],
                PT[i]) <= 0; m--);
            hull[m++] = PT[i];
        }
        if(n > 1) m--;
        while(hull.size() > m) hull.pop_back();
        return hull;
    }

    template <typename DT> double MinimumBoundingBox(
        polygon <DT> P){
        auto p = ConvexHull(P);
        int n = p.size();
        double area = 1e20 + 5;
        for(int i = 0, l = 1, r = 1, u = 1 ; i < n ; i++){
            point <DT> edge = (p[(i+1)%n] - p[i]) / sqrt(DisSq(p[i]
                ], p[(i+1)%n]));
            for( ; (edge ^ p[r%n] - p[i]) < (edge ^ p[(r+1)%n] -
                p[i]); r++);
            for( ; u < r || (edge & p[u%n] - p[i]) < (edge & p[(u
                +1)%n] - p[i]); u++);
            for( ; l < u || (edge ^ p[l%n] - p[i]) > (edge ^ p[(l
                +1)%n] - p[i]); l++);
            double w = (edge ^ p[r%n] - p[i]) - (edge ^ p[l%n] -
                p[i]);
            double h = UTriArea(p[u%n], p[i], p[(i+1)%n]) / sqrt(
                DisSq(p[i], p[(i+1)%n]));
            area = min(area, w*h);
        }
        if(area > 1e19) area = 0;
        return area;
    }
}

```

```

template <typename DT> DT FarthestPairOfPoints(polygon
<DT> p){
    p = ConvexHull(p);
    int n = p.size();
    DT ans = -1e9;
    for(int i = 0, j = 1; i < n; i++) {
        for( ; UTriArea(p[i], p[(i + 1) % n], p[(j + 1) % n
            ]) > UTriArea(p[i], p[(i + 1) % n], p[j]) ; j =
                (j + 1) % n ) ;
        ans = max(ans, DisSq(p[i], p[j]));
        ans = max(ans, DisSq(p[(i + 1) % n], p[j]));
    }
    return ans; // will return square of the answer.
}

template <typename DT> int PointInConvexPolygon(polygon
<int> :: iterator b, polygon<int> :: iterator e,
const point<DT> &O){
    polygon<int> :: iterator lo = b + 2, hi = e - 1, ans
    = e;
    while(lo <= hi) {
        auto mid = lo + (hi - lo) / 2;
        if(TriArea(*b, O, *mid) >= 0) ans = mid, hi = mid -
            1;
        else lo = mid + 1;
    }
    if (ans == e or abs(UTriArea(*b, *(ans - 1), *ans) -
        UTriArea(*b, *(ans - 1), O) - UTriArea(*b, *ans,
            O) - UTriArea(*(ans - 1), *ans, O)) > EPS) return
        0;
    else return (Collinear(*b, *(b + 1), O) or Collinear
        (*(e - 1), *b, O) or Collinear(*ans, *(ans - 1)
            , O)) ? -1 : 1;
} // 0 for outside, -1 for on border, 1 for inside
template <typename DT> int PointInPolygon(polygon<DT>
&P, point<DT> pt) {
    int n = P.size();
    int cnt = 0;
    for(int i = 0, j = 1; i < n; i++, j = (j + 1) % n) {
        if(TriArea(pt, P[i], P[j]) == 0 and min(P[i], P[j])
            <= pt and pt <= max(P[i], P[j])) return -1;
        cnt += ((P[j].y >= pt.y) - (P[i].y >= pt.y)) *
            TriArea(pt, P[i], P[j]) > 0;
    }
    return cnt & 1;
}
}

```

```

using namespace polygon_algo;

// CLOSEST PAIR OF POINTS
template <typename DT> Dis(point<DT> a, point<DT> b){
    return ~(a - b);
}

template <typename DT>
DT Closest_Distance(vector<point<DT>> &v) {
    int n = v.size();
    sort(v.begin(), v.end());
    auto cmp = [] (point<DT> a, point<DT> b) {return (a.y
        < b.y || (a.y == b.y && a.x < b.x));};
    set<point<DT>, decltype(cmp)> s(cmp);
    DT best = 1e18;
    int j = 0;
    for (int i = 0; i < n; i++) {
        while (sq(v[i].x - v[j].x) >= best) {
            s.erase(v[j]);
            j = (j + 1) % n;
        }
        DT d = best;
        auto it1 = s.lower_bound( point<DT>(v[i].x, v[i].y -
            d) );
        auto it2 = s.upper_bound( point<DT>(v[i].x, v[i].y +
            d) );
        for (auto it = it1; it != it2; it++) best = min(best,
            Dis(v[i], *it));
        s.insert(v[i]);
    }
    return best;
}

```

8.2 3D

```

template <typename DT>
class Point {
public:
    DT x, y, z;
    Point(){};
    Point(DT x, DT y, DT z) : x(x), y(y), z(z) {}
    template <typename X> Point(Point<X> p) : x(p.x), y(p.y
        ), z(p.z) {}
    Point operator + (const Point &rhs) const { return
        Point(x + rhs.x, y + rhs.y, z + rhs.z); }
    Point operator - (const Point &rhs) const { return
        Point(x - rhs.x, y - rhs.y, z - rhs.z); }
}

```

```

Point operator * (DT M) const { return Point(M * x, M *
    y, M * z); }
Point operator / (DT M) const { return Point(x / M, y /
    M, z / M); }
// cross product
Point operator & (const Point &rhs) const { return
    Point(y * rhs.z - z * rhs.y, z * rhs.x - x * rhs.z, x
        * rhs.y - y * rhs.x); }
// dot product
DT operator ^ (const Point &rhs) const { return x * rhs
    .x + y * rhs.y + z * rhs.z; }
bool operator == (const Point &rhs) const { return x ==
    rhs.x && y == rhs.y && z == rhs.z; }
bool operator != (const Point &rhs) const { return !(*
    this == rhs); }
friend std::istream& operator >> (std::istream &is,
    Point &p) { return is >> p.x >> p.y >> p.z; }
friend std::ostream& operator << (std::ostream &os,
    const Point &p) { return os << p.x << " " << p.y <<
    " " << p.z; }
friend DT DisSq(const Point &a, const Point &b) {
    return (a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y -
        b.y) + (a.z - b.z)*(a.z - b.z); }

optional< Point<double> > ray_intersects_triangle(const
    Point<double> &origin, const Point<double> &
    ray_vector, const array< Point<double>, 3> &triangle)
{
    constexpr double epsilon = std::numeric_limits<double>
        >::epsilon();
    auto [A, B, C] = triangle;
    Point<double> edge1 = B - A;
    Point<double> edge2 = C - A;
    Point<double> ray_cross_e2 = ray_vector & edge2;
    double det = edge1 ^ ray_cross_e2;
    if (det > -epsilon && det < epsilon) return {}; // Ray
        is parallel to this triangle.
    double inv_det = 1.0 / det;
    Point<double> s = ray_origin - A;
    double u = inv_det * (s ^ ray_cross_e2);
    if (u < 0 || u > 1) return {};
    Point<double> s_cross_e1 = s & edge1;
    double v = inv_det * (ray_vector ^ s_cross_e1);
    if (v < 0 || u + v > 1) return {};
    // Compute t to find the intersection Point
}

```

```
double t = inv_det * (edge2 ^ s_cross_e1);
if (t > epsilon) return ray_origin + ray_vector * t; //
    ray intersection
else return {}; // Line intersection but not ray
    intersection
}
// HOW TO IMPLEMENT
// auto tmp = ray_intersects_triangle (origin, ray, v[i])
    ;
// if (tmp.has_value ()) Point <double>
    intersection_point = tmp.value ();
```

8.3 convex

```
// minkowski sum of two polygons in O(n)
Polygon minkowskiSum(Polygon A, Polygon B) {
    int n = A.size(), m = B.size();
    rotate(A.begin(), min_element(A.begin(), A.end()), A.
        end());
    rotate(B.begin(), min_element(B.begin(), B.end()), B.
        end());

    A.push_back(A[0]);
    B.push_back(B[0]);
    for (int i = 0; i < n; i++) A[i] = A[i + 1] - A[i];
    for (int i = 0; i < m; i++) B[i] = B[i + 1] - B[i];

    Polygon C(n + m + 1);
    C[0] = A.back() + B.back();
    merge(A.begin(), A.end() - 1, B.begin(), B.end() - 1, C.
        .begin() + 1,
        polarComp(Point(0, 0), Point(0, -1)));
    for (int i = 1; i < C.size(); i++) C[i] = C[i] + C[i -
        1];
    C.pop_back();
    return C;
}
// finds the rectangle with minimum area enclosing a
    convex polygon and
// the rectangle with minimum perimeter enclosing a
    convex polygon
// Tf Ti Same
pair<Tf, Tf> rotatingCalipersBoundingBox(const Polygon &p
    ) {
    using Linear::distancePointLine;
    int n = p.size();
    int l = 1, r = 1, j = 1;
```

```
Tf area = 1e100;
Tf perimeter = 1e100;
for (int i = 0; i < n; i++) {
    Point v = (p[(i + 1) % n] - p[i]) / length(p[(i + 1)
        % n] - p[i]);
    while (dcmp(dot(v, p[r % n] - p[i]) - dot(v, p[(r +
        1) % n] - p[i])) < 0)
        r++;
    while (j < r || dcmp(cross(v, p[j % n] - p[i]) -
        cross(v, p[(j + 1) % n] - p[i])) <
        0)
        j++;
    while (l < j ||
        dcmp(dot(v, p[l % n] - p[i]) - dot(v, p[(l + 1)
        % n] - p[i])) > 0)
        l++;
    Tf w = dot(v, p[r % n] - p[i]) - dot(v, p[l % n] - p[
        i]);
    Tf h = distancePointLine(p[j % n], Line(p[i], p[(i +
        1) % n]));
    area = min(area, w * h);
    perimeter = min(perimeter, 2 * w + 2 * h);
}
return make_pair(area, perimeter);
}
// returns the left side of polygon u after cutting it by
    ray a->b
Polygon cutPolygon(Polygon u, Point a, Point b) {
    using Linear::lineLineIntersection;
    using Linear::onSegment;

    Polygon ret;
    int n = u.size();
    for (int i = 0; i < n; i++) {
        Point c = u[i], d = u[(i + 1) % n];
        if (dcmp(cross(b - a, c - a)) >= 0) ret.push_back(c);
        if (dcmp(cross(b - a, d - c)) != 0) {
            Point t;
            lineLineIntersection(a, b - a, c, d - c, t);
            if (onSegment(t, Segment(c, d))) ret.push_back(t);
        }
    }
    return ret;
}
// returns true if point p is in or on triangle abc
```

```
bool pointInTriangle(Point a, Point b, Point c, Point p)
    {
        return dcmp(cross(b - a, p - a)) >= 0 && dcmp(cross(c -
            b, p - b)) >= 0 &&
            dcmp(cross(a - c, p - c)) >= 0;
    }
// pt must be in ccw order with no three collinear points
// returns inside = -1, on = 0, outside = 1
int pointInConvexPolygon(const Polygon &pt, Point p) {
    int n = pt.size();
    assert(n >= 3);

    int lo = 1, hi = n - 1;
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        if (dcmp(cross(pt[mid] - pt[0], p - pt[0])) > 0)
            lo = mid;
        else
            hi = mid;
    }

    bool in = pointInTriangle(pt[0], pt[lo], pt[hi], p);
    if (!in) return 1;

    if (dcmp(cross(pt[lo] - pt[lo - 1], p - pt[lo - 1])) ==
        0) return 0;
    if (dcmp(cross(pt[hi] - pt[lo], p - pt[lo])) == 0)
        return 0;
    if (dcmp(cross(pt[hi] - pt[(hi + 1) % n], p - pt[(hi +
        1) % n])) == 0)
        return 0;
    return -1;
}
// Extreme Point for a direction is the farthest point in
    that direction
// u is the direction for extremeness
int extremePoint(const Polygon &poly, Point u) {
    int n = (int)poly.size();
    int a = 0, b = n;
    while (b - a > 1) {
        int c = (a + b) / 2;
        if (dcmp(dot(poly[c] - poly[(c + 1) % n], u)) >= 0 &&
            dcmp(dot(poly[c] - poly[(c - 1 + n) % n], u)) >=
                0) {
            return c;
        }
    }
}
```



```

bool a_up = dcmp(dot(poly[(a + 1) % n] - poly[a], u))
    >= 0;
bool c_up = dcmp(dot(poly[(c + 1) % n] - poly[c], u))
    >= 0;
bool a_above_c = dcmp(dot(poly[a] - poly[c], u)) > 0;

if (a_up && !c_up)
    b = c;
else if (!a_up && c_up)
    a = c;
else if (a_up && c_up) {
    if (a_above_c)
        b = c;
    else
        a = c;
} else {
    if (!a_above_c)
        b = c;
    else
        a = c;
}

if (dcmp(dot(poly[a] - poly[(a + 1) % n], u)) > 0 &&
    dcmp(dot(poly[a] - poly[(a - 1 + n) % n], u)) > 0)
    return a;
return b % n;
}

// For a convex polygon p and a line l, returns a list of
// segments
// of p that touch or intersect line l.
// the i'th segment is considered (p[i], p[(i + 1) modulo
// |p|])
// #1 If a segment is collinear with the line, only that
// is returned
// #2 Else if l goes through i'th point, the i'th segment
// is added
// Complexity: O(lg |p|)
vector<int> lineConvexPolyIntersection(const Polygon &p,
    Line l) {
    assert((int)p.size() >= 3);
    assert(l.a != l.b);

    int n = p.size();
    vector<int> ret;

```

```

    Point v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);

    if (!olf || !ort) {
        int idx = (!olf ? lf : rt);
        if (orient(l.a, l.b, p[(idx - 1 + n) % n]) == 0)
            ret.push_back((idx - 1 + n) % n);
        else
            ret.push_back(idx);
        return ret;
    }
    if (olf == ort) return ret;

    for (int i = 0; i < 2; ++i) {
        int lo = i ? rt : lf;
        int hi = i ? lf : rt;
        int olo = i ? ort : olf;

        while (true) {
            int gap = (hi - lo + n) % n;
            if (gap < 2) break;

            int mid = (lo + gap / 2) % n;
            int omid = orient(l.a, l.b, p[mid]);
            if (!omid) {
                lo = mid;
                break;
            }
            if (omid == olo)
                lo = mid;
            else
                hi = mid;
        }
        ret.push_back(lo);
    }
    return ret;
}

// Calculate [ACW, CW] tangent pair from an external
// point
constexpr int CW = -1, ACW = 1;
bool isGood(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) != -dir;

```

```

}
Point better(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) == dir ? u : v;
}
Point pointPolyTangent(const Polygon &pt, Point Q, int
    dir, int lo, int hi) {
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid - 1], Q, dir);
        bool nxt = isGood(pt[mid], pt[mid + 1], Q, dir);

        if (pvs && nxt) return pt[mid];
        if (!pvs || !nxt) {
            Point p1 = pointPolyTangent(pt, Q, dir, mid + 1, hi
                );
            Point p2 = pointPolyTangent(pt, Q, dir, lo, mid -
                1);
            return better(p1, p2, Q, dir);
        }

        if (!pvs) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                hi = mid - 1;
            else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
        if (!nxt) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                lo = mid + 1;
            else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
    }

    Point ret = pt[lo];
    for (int i = lo + 1; i <= hi; i++) ret = better(ret, pt
        [i], Q, dir);
    return ret;
}

// [ACW, CW] Tangent
pair<Point, Point> pointPolyTangents(const Polygon &pt,
    Point Q) {

```

```

int n = pt.size();
Point acw_tan = pointPolyTangent(pt, Q, ACW, 0, n - 1);
Point cw_tan = pointPolyTangent(pt, Q, CW, 0, n - 1);
return make_pair(acw_tan, cw_tan);
}

```

8.4 $\min_{dis} squares$

```

typedef long double ld;
const ld eps = 1e-12;
int cmp(ld x, ld y = 0, ld tol = eps) {
    return (x <= y + tol) ? (x + tol < y) ? -1 : 0 : 1;
}

struct point{
    ld x, y;
    point(ld a, ld b) : x(a), y(b) {}
    point() {}
};

struct square{
    ld x1, x2, y1, y2, a, b, c;
    point edges[4];
    square(ld _a, ld _b, ld _c) {
        a = _a, b = _b, c = _c;
        x1 = a - c * 0.5;
        x2 = a + c * 0.5;
        y1 = b - c * 0.5;
        y2 = b + c * 0.5;
        edges[0] = point(x1, y1);
        edges[1] = point(x2, y1);
        edges[2] = point(x2, y2);
        edges[3] = point(x1, y2);
    }
};

ld min_dist(point &a, point &b) {
    ld x = a.x - b.x, y = a.y - b.y;
    return sqrt(x * x + y * y);
}

bool point_in_box(square s1, point p) {
    if (cmp(s1.x1, p.x) != 1 && cmp(s1.x2, p.x) != -1 &&
        cmp(s1.y1, p.y) != 1 && cmp(s1.y2, p.y) != -1)
        return true;
    return false;
}

bool inside(square &s1, square &s2) {
    for(int i = 0; i < 4; ++i) if(point_in_box(s2, s1.edges
        [i])) return true;
    return false;
}

```

```

}

bool inside_vert(square &s1, square &s2) {
    if((cmp(s1.y1, s2.y1) != -1 && cmp(s1.y1, s2.y2) != 1)
        || (cmp(s1.y2, s2.y1) != -1 && cmp(s1.y2, s2.y2) !=
            1)) return true;
    return false;
}

bool inside_hori(square &s1, square &s2) {
    if ((cmp(s1.x1, s2.x1) != -1 && cmp(s1.x1, s2.x2) != 1)
        || (cmp(s1.x2, s2.x1) != -1 && cmp(s1.x2, s2.x2)
            != 1)) return true;
    return false;
}

ld min_dist(square &s1, square &s2) {
    if (inside(s1, s2) || inside(s2, s1)) return 0;
    ld ans = 1e100;
    for (int i = 0; i < 4; ++i)
        for (int j = 0; j < 4; ++j)
            ans = min(ans, min_dist(s1.edges[i], s2.edges[j]));
    if (inside_hori(s1, s2) || inside_hori(s2, s1)) {
        if (cmp(s1.y1, s2.y2) != -1) ans = min(ans, s1.y1 -
            s2.y2);
        else if (cmp(s2.y1, s1.y2) != -1) ans = min(ans, s2.
            y1 - s1.y2);
    }
    if (inside_vert(s1, s2) || inside_vert(s2, s1)) {
        if (cmp(s1.x1, s2.x2) != -1) ans = min(ans, s1.x1 -
            s2.x2);
        else if (cmp(s2.x1, s1.x2) != -1) ans = min(ans, s2.x1
            - s1.x2);
    }
    return ans;
}

```

9 Misc

9.1 StressTest

9.2 All Macros

```

// #pragma GCC optimize("Ofast")
// #pragma GCC optimization ("O3")
// #pragma comment(linker, "/stack:200000000")
// #pragma GCC optimize("unroll-loops")
// #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,abm
    ,mmx,avx,tune=native")

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

```

```

using namespace __gnu_pbds;
// find_by_order(k) --> returns iterator to the kth
// largest element counting from 0
// order_of_key(val) --> returns the number of items
// in a set that are strictly smaller than our item
os.erase(os.find_by_order(os.order_of_key(v[i])))
==> to erase i-th element from ordered multiset

template <typename DT>
using ordered_set = tree<DT, null_type, less<DT>,
    rb_tree_tag, tree_order_statistics_node_update>;

mod = {1500000007, 1500000013, 1500000023, 1500000057,
    1500000077};

struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator () (uint64_t x) const {
        static const uint64_t FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count
            ();
        return splitmix64(x + FIXED_RANDOM);
    }
} Rng;

typedef gp_hash_table<int, int, custom_hash> gp;
gp table;

int leap_years(int y) { return y / 4 - y / 100 + y / 400;
    }

bool is_leap(int y) { return y % 400 == 0 || (y % 4 == 0
    && y % 100 != 0); }

bool __builtin_mul_overflow (type1 a, type2 b, type3 &res
    )
cin.tie(0)->ios_base::sync_with_stdio(0);

```


10 Equations and Formulas

10.1 Catalan Numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} \quad C_0 = 1, C_1 = 1 \text{ and } C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

The number of ways to completely parenthesize $n+1$ factors.

The number of triangulations of a convex polygon with $n+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

The number of rooted full binary trees with $n+1$ leaves (vertices are not numbered). A rooted binary tree is full if every vertex has either two children or no children.

Number of permutations of $1, \dots, n$ that avoid the pattern 123 (or any of the other patterns of length 3); that is, the number of permutations with no three-term increasing sub-sequence. For $n = 3$, these permutations are 132, 213, 231, 312 and 321.

10.2 Stirling Numbers First Kind

The Stirling numbers of the first kind count permutations according to their number of cycles (counting fixed points as cycles of length one).

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1)$, where, $S(0, 0) = 1$.

$$1, S(n, 0) = S(0, n) = 0 \quad \sum_{k=0}^n S(n, k) = n!$$

The unsigned Stirling numbers may also be defined algebraically, as the coefficient of the rising factorial:

$$x^{\bar{n}} = x(x+1)\dots(x+n-1) = \sum_{k=0}^n S(n, k) x^k$$

Lets $[n, k]$ be the stirling number of the first kind, then

$$[n \quad k] = \sum_{0 \leq i_1 < i_2 < \dots < i_k < n} i_1 i_2 \dots i_k.$$

10.3 Stirling Numbers Second Kind

Stirling number of the second kind is the number of ways to partition a set of n objects into k non-empty subsets.

$S(n, k) = k \cdot S(n-1, k) + S(n-1, k-1)$, where $S(0, 0) = 1$.

$1, S(n, 0) = S(0, n) = 0 \quad S(n, 2) = 2^{n-1} - 1 \quad S(n, k) \cdot k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation. $S_r(n+1, k) = k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1)$

Denote the n objects to partition by the integers $1, 2, \dots, n$. Define the reduced Stirling numbers of the second kind, denoted $S^d(n, k)$, to be the number of ways to partition the integers $1, 2, \dots, n$ into k nonempty subsets such that all elements in each subset have pairwise distance at least d . That is, for any integers i and j in a given subset, it is required that $|i - j| \geq d$. It has been shown that these numbers satisfy, $S^d(n, k) = S(n-d+1, k-d+1)$, $n \geq k \geq d$

10.4 Other Combinatorial Identities

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}$$

$$\sum_{i=0}^k \binom{n+i}{i} = \sum_{i=0}^k \binom{n+i}{n} = \binom{n+k+1}{k}$$

$$n, r \in \mathbb{N}, n > r, \sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$$

If $P(n) = \sum_{k=0}^n \binom{n}{k} \cdot Q(k)$, then,

$$Q(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot P(k)$$

If $P(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot Q(k)$, then,

$$Q(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot P(k)$$

10.5 Different Math Formulas

Picks Theorem : $A = i + b/2 - 1$

Derangements : $d(i) = (i-1) \times (d(i-1) + d(i-2))$

$$\frac{n}{ab} - \left\{ \frac{b/n}{a} \right\} - \left\{ \frac{a/n}{b} \right\} + 1$$

10.6 GCD and LCM

if m is any integer, then $\gcd(a + m \cdot b, b) = \gcd(a, b)$

The gcd is a multiplicative function in the following sense: if a_1 and a_2 are relatively prime, then $\gcd(a_1 \cdot a_2, b) = \gcd(a_1, b) \cdot \gcd(a_2, b)$.

$$\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c)).$$

$$\text{lcm}(a, \gcd(b, c)) = \gcd(\text{lcm}(a, b), \text{lcm}(a, c)).$$

For non-negative integers a and b , where a and b are not both zero, $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

$$\gcd(a, b) = \sum_{k|a \text{ and } k|b} \phi(k)$$

$$\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$$

$$\sum_{k=1}^n \gcd(k, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n x^{\gcd(k, n)} = \sum_{d|n} x^d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2$$

$$F(n) = \sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{(1 + \lfloor \frac{n}{l} \rfloor) (\lfloor \frac{n}{l} \rfloor)}{2} \right)^2 \sum_{d|l} \mu(d) l d$$