

Contents			
1 Build and Snippet	1	4 Graph	7
1.1 Sublime Build	1	4.1 Bellman Ford	7
2 Data Structures	1	4.2 BridgeTree	7
2.1 2D BIT	1	4.3 DSU, MST	7
2.2 BIT	1	4.4 ETT, VT	7
2.3 Lazy Propagation	1	4.5 HLD	8
2.4 MO	1	4.6 Hungarian	8
2.5 MergeSortTree	1	4.7 K th shortest path	8
2.6 PST	1	4.8 LCA, CD	8
2.7 SegmentTree	1	4.9 block cut tree	9
2.8 SegmentTreeBeats	2	4.10 maximum bipartite matching hopcroft	9
2.9 Sparse Table	2	4.11 strongly connected component	9
2.10 Trie	2	5 String	9
2.11 sparse table 2D	3	5.1 KMP	9
3 Number Theory	3	5.2 Manacher	9
3.1 2D FFT	3	5.3 SuffixArray	9
3.2 Bitwise Sieve	3	5.4 Z	10
3.3 Chinese Remainder Theorem	3	5.5 double hashing	10
3.4 Divisor	3	6 DP	10
3.5 Eulers Totient Function	3	6.1 CHT	10
3.6 FFT	3	6.2 CatalanDp	10
3.7 FWHT	4	6.3 DearrangementDP	10
3.8 GCD convolution	4	6.4 Li Chao Tree	10
3.9 LCM cnvolution	4	6.5 SOS	11
3.10 LargePrime	4	6.6 grundy	11
3.11 Linear Recurance	5	7 Geometry	11
3.12 Lucas	5	7.1 2D Shohag	11
3.13 Matrix	6	7.2 3D Shohag	17
3.14 NOD and SOD	6	7.3 3D	20
3.15 Pollard rho	6	7.4 3d hull	21
3.16 Sieve	6	7.5 ClosestPairOfPoints	21
3.17 XOR Basis	6	7.6 MinDisSquares	21
3.18 mobius function	6	7.7 Pick _s Theorem	22
3.19 nCr	6	7.8 convex	22
3.20 ntt	6	8 Misc	23
3.21 primality test	7	8.1 All Macros	23
3.22 prime counting function	7	8.2 StressTest	23
		9 Equations and Formulas	24
		9.1 Catalan Numbers, convolution and super	24
		9.2 Stirling Numbers First Kind	24
		9.3 Stirling Numbers Second Kind	24
		9.4 Other Combinatorial Identities	24
		9.5 Different Math Formulas	24
		9.6 GCD and LCM	24

1 Build and Snippet

1.1 Sublime Build

```
#for linux
{
    "shell_cmd": "g++ $file -o $file_base_name && ./\n    $file_base_name<input.txt> output.txt && rm\n    $file_base_name",\n    "working_dir": "$file_path",\n    "selector": "source.c++"\n}
```

2 Data Structures

2.1 2D BIT

```
const int N = 1008; int bit[N][N], a[N][N], n, m, q;\nvoid update(int x, int y, int val) { for (; x < N; x +=\n-x & x) for (int j = y; j < N; j += -j & j) bit[x][j] +=\nval; } int get(int x, int y) { int ans = 0; for (; x;\n-x & -x) for (int j = y; j; j -= j & -j) ans += bit[x\n][j]; return ans; } int get(int x1, int y1, int x2, int\ny2) { return get(x2, y2) - get(x1 - 1, y2) - get(x2, y1\n- 1) + get(x1 - 1, y1 - 1); }
```

2.2 BIT

```
class BIT { int *bin, N; public: BIT(int N) : N(N) { bin\n= new int[N + 1]; memset(bin, 0, (N + 1) * sizeof(int))\n; } void update(int id, int val) { for (; id <= N; id +=\nid & -id) bin[id] += val; } int helper(int id) { int\nsum = 0; for (; id > 0; id -= id & -id) sum += bin[id];\nreturn sum; } int query(int l, int r) { return helper(r)\n- helper(l - 1); } ~BIT() { delete[] bin; } };
```

2.3 Lazy Propagation

```
class LazySegmentTree { vector<int> tree; vector<int>\nlazy; int n, I; int merge(int a, int b) { return a + b;\n} void propagate(int node, int le, int ri) { if (lazy[\nnode] != 0) { tree[node] += (ri - le + 1) * lazy[node];\nif (le != ri) { lazy[2 * node + 1] += lazy[node]; lazy[2\n* node + 2] += lazy[node]; } lazy[node] = 0; } } void\nbuild(int node, int le, int ri, vector<int> &arr) { if (\nle == ri) { tree[node] = arr[le]; return; } int mid = (\nle + ri) / 2; build(2 * node + 1, le, mid, arr); build(2\n* node + 2, mid + 1, ri, arr); tree[node] = merge(tree\n[2 * node + 1], tree[2 * node + 2]); } void update(int\nnode, int le, int ri, int l, int r, int val) { propagate\n(node, le, ri); if (r < le || l > ri) { return; } if (le
```

```
>= l && ri <= r) { tree[node] += (ri - le + 1) * val;\nif (le != ri) { lazy[2 * node + 1] += val; lazy[2 * node\n+ 2] += val; } return; } int mid = (le + ri) / 2;\nupdate(2 * node + 1, le, mid, l, r, val); update(2 * \nnode + 2, mid + 1, ri, l, r, val); tree[node] = merge(\ntree[2 * node + 1], tree[2 * node + 2]); } int query(\nint node, int le, int ri, int l, int r) { propagate(node\n, le, ri); if (l <= le && r >= ri) { return tree[node];\n} if (r < le || l > ri) { return I; } int mid = (le + ri\n) / 2; return merge(query(2 * node + 1, le, mid, l, r), \nquery(2 * node + 2, mid + 1, ri, l, r)); } public:\nLazySegmentTree(vector<int> &arr, int I) { n = arr.size\n(); this->I = I; tree.resize(4 * n, 0); lazy.resize(4 * \nn, 0); build(0, 0, n - 1, arr); } void update(int l, int\nr, int val) { update(0, 0, n - 1, l, r, val); } int\nquery(int l, int r) { return query(0, 0, n - 1, l, r); }\n};
```

2.4 MO

```
struct Query { int l, r, idx; bool operator<(const Query\n&other) const { if (l / BLOCK != other.l / BLOCK) {\nreturn l / BLOCK < other.l / BLOCK; } return r < other.r\n; } }; vector<bool> mo_algorithm(vector<Query> &queries,\nint n, int q) { sort(queries.begin(), queries.end());\nint currl = 0, curr_r = -1; vector<bool> result(q); for\n(auto &query : queries) { int l = query.l, r = query.r,\nidx = query.idx; while (curr_r < r) { add(++curr_r); }\nwhile (curr_r > r) { remove(curr_r--); } while (currl <\nl) { remove(currl++); } while (currl > l) { add(--currl)\n; } } return result; }
```

2.5 MergeSortTree

```
class MergeSortTree { int n; vector<vector<int>> tree;\nvoid build(int id, int le, int ri, vector<int> &a) { if\n(le == ri) { tree[id].push_back(a[le]); return; } int\nmid = (le + ri) >> 1; build(2 * id + 1, le, mid, a);\nbuild(2 * id + 2, mid + 1, ri, a); auto &left = tree[2 * \nid + 1], &right = tree[2 * id + 2]; int i = 0, j = 0, n\n= left.size(), m = right.size(); while (i < n && j < m)\n{ if (left[i] < right[j]) tree[id].push_back(left[i]),\ni++; else tree[id].push_back(right[j]), j++; } while (i\n< n) tree[id].push_back(left[i]), i++; while (j < m)\ntree[id].push_back(right[j]), j++; } /* number of\nelement greater than val */ int queryL(int id, int le,\nint ri, int l, int r, int val) { if (le > r || ri < l) {\nreturn 0; } if (le >= l && ri <= r) { return ri - le +
```

```
1 - (upper_bound(tree[id].begin(), tree[id].end(), val)\n- tree[id].begin()); } int mid = (le + ri) >> 1; return\nqueryL(2 * id + 1, le, mid, l, r, val) + queryL(2 * id +\n2, mid + 1, ri, l, r, val); } /* number of element\nsmaller than val */ int queryS(int id, int le, int ri,\nint l, int r, int val) { if (le > r || ri < l) { return\n0; } if (le >= l && ri <= r) { return (upper_bound(tree[\nid].begin(), tree[id].end(), val - 1) - tree[id].begin()\n); } int mid = (le + ri) >> 1; return queryS(2 * id + 1,\nle, mid, l, r, val) + queryS(2 * id + 2, mid + 1, ri, l\n, r, val); } public: MergeSortTree(vector<int> &a) { n =\na.size(); tree.resize(n * 4); build(0, 0, n - 1, a); }\nint queryS(int l, int r, int val) { return queryS(0, 0,\nn - 1, l, r, val); } int queryL(int l, int r, int val) {\nreturn queryL(0, 0, n - 1, l, r, val); } };
```

2.6 PST

```
class PST{ #define lc(u) tree[u].left #define rc(u) tree\n[u].right; struct node{ int left = 0, right = 0, val =\n0; }; node *tree; int N, LG, time = 0, I = 0; node\ncreate(int l, int r){ return {l, r, merge(tree[l].val,\ntree[r].val)}; } int merge(LL a, LL b){ return a + b; }\nint build(int le, int ri){ int id = ++time; if(le == ri)\nreturn tree[id] = node(), id; int m = (le + ri) / 2;\nreturn tree[id] = create(build(le, m), build(m + 1, ri))\n, id; } int update(int id, int le, int ri, int pos, int\nval){ int nid = ++time; if(le == ri) return tree[nid] =\n{0, 0, (tree[id].val + val)}, nid; /* // change here */\nint m = (le + ri) / 2; if(pos <= m){ tree[nid] = create(\nupdate(tree[id].left, le, m, pos, val), tree[id].right);\n}else{ tree[nid] = create(tree[id].left, update(tree[id\n].right, m + 1, ri, pos, val)); } return nid; } int\nquery(int id, int le, int ri, int l, int r){ if(r < le\n|| ri < l) return 0; if(l <= le && ri <= r) return tree[\nid].val; int m = (le + ri) >> 1; return query(tree[id].\nleft, le, m, l, r) + query(tree[id].right, m + 1, ri, l,\nr); } public: PST(int N, int U){ /*U --> number of\nexpected updates */ this->N = N; LG = 33 - __builtin_clz\n(N); tree = new node[N * 4 + U * LG]; build(0, N - 1); }\nint update(int id, int pos, int val){ return update(id,\n0, N - 1, pos, val); } int query(int id, int l, int r){\nif(l > r) return 0; return query(id, 0, N - 1, l, r); }\n~PST(){ delete[] tree; } };
```

2.7 SegmentTree

```

template <typename DT> class segmentTree { DT *seg, I;
int n; DT (*merge)(DT, DT); void build(int idx, int le,
int ri, vector<DT> &v) { if (le == ri) { seg[idx] = v[le];
return; } int mid = (le + ri) >> 1; build(2 * idx + 1, le, mid, v);
build(2 * idx + 2, mid + 1, ri, v); seg[idx] = merge(seg[2 * idx + 1],
seg[2 * idx + 2]); } void update(int idx, int le, int ri, int pos, DT val) {
if (le == ri) { seg[idx] = val; return; } int mid = (le + ri) >> 1;
if (pos <= mid) update(2 * idx + 1, le, mid, pos, val);
else update(2 * idx + 2, mid + 1, ri, pos, val); seg[idx] = merge(seg[2 * idx + 1],
seg[2 * idx + 2]); } DT query(int idx, int le, int ri, int l, int r) {
if (l <= le && r >= ri) { return seg[idx]; } if (r < le || l > ri) {
return I; } int mid = (le + ri) >> 1; return merge(query(2 * idx + 1, le, mid, l, r),
query(2 * idx + 2, mid + 1, ri, l, r)); } /* // finding the leftmost
appearance of value <= val in [l...r] range // need
minimum segment tree */ int walk(int idx, int le, int ri,
int l, int r, DT val) { if (r < le || l > ri) { return
r; } if (le == ri) { if (seg[idx] <= val) return le;
return r; } if (l <= le && r >= ri) { int mid = (le + ri) >> 1;
if (seg[2 * idx + 1] <= val) return walk(2 * idx + 1, le, mid, l, r, val);
return walk(2 * idx + 2, mid + 1, ri, l, r, val); } int mid = (le + ri) >> 1;
return merge(walk(2 * idx + 1, le, mid, l, r, val), walk(2 * idx + 2, mid + 1, ri, l, r, val)); }
public: segmentTree() {} segmentTree(vector<DT> &v, DT (*fptr)(DT, DT), DT _I) {
n = v.size(); I = _I; merge = fptr; seg = new DT[4 * n]; build(0, 0, n - 1, v); }
void update(int pos, DT val) { update(0, 0, n - 1, pos, val); } int walk(int l,
int r, DT val) { if (query(l, r) > val) return r; return walk(0, 0, n - 1, l, r, val); }
DT query(int l, int r) { return query(0, 0, n - 1, l, r); } ~segmentTree(){
delete[] seg; } }; int fun(int a, int b) { return max(a, b); }

```

2.8 SegmentTreeBeats

```

class SegTreeBeats { const int INF = INT_MAX; const LL
NEG_INF = LLONG_MIN; vector<LL> mx, mn, smx, smn, sum,
add; vector<int> mxcnt, mncnt; int L, R; void applyMax(int u, LL x) {
sum[u] += mncnt[u] * (x - mn[u]); if (mx[u] == mn[u]) mx[u] = x;
if (smx[u] == mn[u]) smx[u] = x; } void applyMin(int u, LL x) {
sum[u] -= mxcnt[u] * (mx[u] - x); if (mn[u] == mx[u]) mn[u] = x;
if (smn[u] == mx[u]) smn[u] = x; mx[u] = x; } void applyAdd(int u, LL x,
int tl, int tr) { sum[u] += (tr -

```

```

tl + 1) * x; add[u] += x; mx[u] += x, mn[u] += x; if (smx[u] != NEG_INF)
smx[u] += x; if (smn[u] != INF) smn[u] += x; } void push(int u, int tl,
int tr) { int lft = u << 1, ryt = lft | 1, mid = (tl + tr) >> 1; if (add[u]
!= 0) { applyAdd(lft, add[u], tl, mid); applyAdd(ryt, add[u], mid + 1, tr);
add[u] = 0; } if (mx[u] < mx[lft]) applyMin(lft, mx[u]); if (mx[u] < mx[ryt])
applyMin(ryt, mx[u]); if (mn[u] > mn[lft]) applyMax(lft, mn[u]); if (mn[u] > mn[ryt])
applyMax(ryt, mn[u]); } void merge(int u) { int lft = u << 1, ryt = lft | 1;
sum[u] = sum[lft] + sum[ryt]; mx[u] = max(mx[lft], mx[ryt]); smx[u] = max(smx[lft],
smx[ryt]); if (mx[lft] != mx[ryt]) smx[u] = max(smx[u], min(mx[lft], mx[ryt]));
mxcnt[u] = (mx[u] == mx[lft]) * mxcnt[lft] + (mx[u] == mx[ryt]) * mxcnt[ryt];
mn[u] = min(mn[lft], mn[ryt]); smn[u] = min(smn[lft], smn[ryt]); if (mn[lft]
!= mn[ryt]) smn[u] = min(smn[u], max(mn[lft], mn[ryt])); mncnt[u] = (mn[u] == mn[lft]) *
mncnt[lft] + (mn[u] == mn[ryt]) * mncnt[ryt]; } void build(const vector<int> &a,
int tl, int tr, int u) { if (tl == tr) { sum[u] = mn[u] = mx[u] = a[tl];
mxcnt[u] = mncnt[u] = 1; smx[u] = NEG_INF; smn[u] = INF; return; } int mid =
(tl + tr) >> 1, lft = u << 1, ryt = lft | 1; build(a, tl, mid, lft); build(a, mid + 1, tr, ryt);
merge(u); } public: SegTreeBeats(const vector<int> &a) { int n = a.size(); L = 0;
R = n - 1; mx.resize(4 * n, 0); mn.resize(4 * n, 0); smx.resize(4 * n, NEG_INF);
smn.resize(4 * n, INF); sum.resize(4 * n, 0); add.resize(4 * n, 0); mxcnt.resize(4 * n, 0);
mncnt.resize(4 * n, 0); build(a, L, R, 1); } /* // a[i] = min(x, a[i]); */ void
minimize(int l, int r, LL x) { minimize(l, r, x, L, R, 1); } /* // a[i] = max(x, a[i]); */ void
maximize(int l, int r, LL x) { maximize(l, r, x, L, R, 1); } /* // a[i] = a[i] + x; */ void
increase(int l, int r, LL x) { increase(l, r, x, L, R, 1); } LL getSum(int l, int r) {
return getSum(l, r, L, R, 1); } private: void minimize(int l, int r, LL x, int tl,
int tr, int u) { if (l > tr || tl > r || mx[u] <= x) return; if (l <= tl && tr <= r
&& smx[u] < x) { applyMin(u, x); return; } push(u, tl, tr); int mid = (tl + tr) >> 1,
lft = u << 1, ryt = lft | 1; minimize(l, r, x, tl, mid, lft); minimize(l, r, x, mid + 1, tr, ryt);
merge(u); } void maximize(int l, int r, LL x, int tl, int tr, int u) { if (l > tr || tl > r
|| mn[u] >= x) return; if (l <= tl && tr <= r && smn[u] > x) { applyMax(u, x); return; }
push(u, tl, tr); int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1; maximize(l, r, x, tl,
mid, lft); maximize(l, r, x, mid + 1, tr, ryt); merge(u); } void increase(int l, int r, LL
x, int tl, int tr, int u) { if (l > tr || tl > r || mn[u] >= x) return; if (l <= tl && tr <= r
&& smn[u] > x) { applyMin(u, x); return; } push(u, tl, tr); int mid = (tl + tr) >> 1,
lft = u << 1, ryt = lft | 1; increase(l, r, x, tl, mid, lft); increase(l, r, x, mid + 1, tr, ryt);
merge(u); } void decrease(int l, int r, LL x, int tl, int tr, int u) { if (l > tr || tl > r
|| mx[u] <= x) return; if (l <= tl && tr <= r && smx[u] < x) { applyMax(u, x); return; }
push(u, tl, tr); int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1; decrease(l, r, x, tl,
mid, lft); decrease(l, r, x, mid + 1, tr, ryt); merge(u); }

```

```

1, tr, ryt); merge(u); } void increase(int l, int r, LL x, int tl, int tr, int u) {
if (l > tr || tl > r) return; if (l <= tl && tr <= r) { applyAdd(u, x, tl, tr);
return; } push(u, tl, tr); int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
increase(l, r, x, tl, mid, lft); increase(l, r, x, mid + 1, tr, ryt); merge(u); }
LL getSum(int l, int r, int tl, int tr, int u) { if (l > tr || tl > r) return 0;
if (l <= tl && tr <= r) return sum[u]; push(u, tl, tr); int mid = (tl + tr) >> 1,
lft = (u << 1), ryt = (lft | 1); LL x = getSum(l, r, tl, mid, lft), y = getSum(l, r, mid + 1, tr, ryt);
return x + y; } }

```

2.9 Sparse Table

```

class SparseTable { private: vector<vector<int>> table;
vector<int> log; int n; public: SparseTable(const vector<int> &arr) {
n = arr.size(); log.resize(n + 1); buildLog(); table = vector<vector<int>>(n, vector<int>(
log[n] + 1)); for (int i = 0; i < n; i++) { table[i][0] = arr[i]; } for (int j = 1; (1 << j) <= n; j++) {
for (int i = 0; i + (1 << j) <= n; i++) { table[i][j] = merge(table[i][j - 1], table[i + (1 << j) - 1][j - 1]); } }
int merge(int a, int b) { return max(a, b); } void buildLog() { log[1] = 0; for (int i = 2; i <= n; i++)
log[i] = log[i / 2] + 1; } int Query(int L, int R) { int j = log[R - L + 1]; return merge(table[L][j], table[R - (1 << j) + 1][j]); }
int query(int L, int R) { int sum = 0; for (int j = log[R - L + 1]; L <= R; j = log[R - L + 1]) { sum = merge(sum, table[L][j]); L += (1 << j); }
return sum; } }

```

2.10 Trie

```

struct node { int path, leaf; vector<int> child; node(int n = 0) : child(n, -1), path(0), leaf(0) {} }; class
Trie { int n, ptr; vector<node> tree; public: Trie(int n) : n(n), ptr(0) { tree.emplace_back(node(n)); } void
insert(string &s) { int cur = 0; for (auto u : s) { int &next = tree[cur].child[u - '0']; if (next == -1) { tree.emplace_back(node(n));
next = ++ptr; } tree[cur].path++; cur = next; } tree[cur].path++; tree[cur].leaf++; } void erase(string &s) { int cur = 0; for (auto u : s) { tree[cur].path--;
cur = tree[cur].child[u - '0']; } tree[cur].path--; tree[cur].leaf--; } bool find(string &s) { int cur = 0; for (auto u : s) { cur = tree[cur].child[u - '0'];
if (cur == -1 || !tree[cur].path) return 0; } return tree[cur].leaf > 0; } }

```

2.11 sparse table 2D

```
/* // rectangle query */ namespace st2 { const int N = 2
e3 + 5, B = 12; using Ti = long long; Ti Id = LLONG_MAX;
Ti f(Ti a, Ti b) { return max(a, b); } Ti tbl[N][N][B];
void init(int n, int m) { for(int k = 1; k < B; k++) {
for(int i = 0; i + (1 << k) - 1 < n; i++) { for(int j =
0; j + (1 << k) - 1 < m; j++) { tbl[i][j][k] = tbl[i][j
][k - 1]; tbl[i][j][k] = f(tbl[i][j][k], tbl[i][j + (1
<< k - 1)][k - 1]); tbl[i][j][k] = f(tbl[i][j][k], tbl[i
+ (1 << k - 1)][j][k - 1]); tbl[i][j][k] = f(tbl[i][j][
k], tbl[i + (1 << k - 1)][j + (1 << k - 1)][k - 1]); } }
} } Ti query(int i, int j, int len) { int k = __lg(len)
; LL ret = tbl[i][j][k]; ret = f(ret, tbl[i + len - (1
<< k)][j][k]); ret = f(ret, tbl[i][j + len - (1 << k)][k
]); ret = f(ret, tbl[i + len - (1 << k)][j + len - (1 <<
k)][k]); return ret; } } int main() { for(int i = 0; i
< n; i++) for(int j = 0; j < m; j++) cin >> st2 :: tbl[i
][j][0]; st2 :: init(n, m); cout << st2 :: query(x, y, s
); // x, y, x + s - 1, y + s - 1 }
```

3 Number Theory

3.1 2D FFT

```
const int N = 1 << 13; const int mod = 998244353; const
int root = 3; using Mat = vector<vector<int>>>; int lim,
rev[N], w[N], wn[N], inv_lim; void reduce(int &x) { x =
(x + mod) % mod; } int POW(int x, int y, int ans = 1) {
for (; y >= 1, x = (long long) x * x % mod) if (y &
1) ans = (long long) ans * x % mod; return ans; } void
precompute(int len) { lim = wn[0] = 1; int s = -1; while
(lim < len) lim <= 1, ++s; for (int i = 0; i < lim; ++
i) rev[i] = rev[i >> 1] >> 1 | (i & 1) << s; const int g
= POW(root, (mod - 1) / lim); inv_lim = POW(lim, mod -
2); for (int i = 1; i < lim; ++i) wn[i] = (long long) wn
[i - 1] * g % mod; } void ntt(vector<int> &a, int typ) {
for (int i = 0; i < lim; ++i) if (i < rev[i]) swap(a[i
], a[rev[i]]); for (int i = 1; i < lim; i <= 1) { for (
int j = 0, t = lim / i / 2; j < i; ++j) w[j] = wn[j * t
]; for (int j = 0; j < lim; j += i << 1) { for (int k =
0; k < i; ++k) { const int x = a[k + j], y = (long long)
a[k + j + i] * w[k] % mod; reduce(a[k + j] += y - mod),
reduce(a[k + j + i] = x - y); } } } if (!typ) { reverse
(a.begin() + 1, a.begin() + lim); for (int i = 0; i <
lim; ++i) a[i] = (long long) a[i] * inv_lim % mod; } }
/* // a is of size n * n // b is of size m * m // max(n,
m)^2 * log(max(n, m)); */ Mat multiply(Mat a, Mat b) {
```

```
int n = a.size(), m = b.size(); int len = n + m - 1;
precompute(len); a.resize(lim); for (int i = 0; i < lim;
i++) { a[i].resize(lim, 0); } b.resize(lim); for (int i
= 0; i < lim; i++) { b[i].resize(lim, 0); } /* //
convert rows to point value form */ for (int i = 0; i <
lim; i++) { ntt(a[i], 1); ntt(b[i], 1); } Mat ans(lim,
vector<int> (lim, 0)); for (int j = 0; j < lim; j++) {
vector<int> col_a(lim), col_b(lim); for (int i = 0; i <
lim; i++) { col_a[i] = a[i][j]; col_b[i] = b[i][j]; } /*
// convert columns to point value form */ ntt(col_a, 1)
; ntt(col_b, 1); /* // so everything is in point value
form, // so compute the product easily */ for (int i =
0; i < lim; i++) { col_a[i] = 1LL * col_a[i] * col_b[i]
% mod; } /* // inverse fft on columns */ ntt(col_a, 0);
for (int i = 0; i < lim; i++) { a[i][j] = col_a[i]; } }
/* // inverse fft on rows */ for (int i = 0; i < lim; i
++) { ntt(a[i], 0); } a.resize(n + m - 1); for (int i =
0; i < n + m - 1; i++) { a[i].resize(n + m - 1); }
return a; } Mat multiply_brute(Mat a, Mat b) { int n = a
.size(), m = b.size(); Mat ans(n + m - 1, vector<int> (n
+ m - 1, 0)); for (int i = 0; i < n; i++) { for (int j
= 0; j < n; j++) { for (int r = 0; r < m; r++) { for (
int c = 0; c < m; c++) { ans[i + r][j + c] += 1LL * a[i
][j] * b[r][c] % mod; ans[i + r][j + c] %= mod; } } } }
return ans; }
```

3.2 Bitwise Sieve

```
const int nmax = 1e8 + 1; int mark[(nmax >> 6) + 1];
vector<int> primes; #define isSet(n, pos) (bool)((n &
(1LL << (pos))) #define Set(n, pos) ((n) | (1LL << (pos)
)) void sieve(int n) { for (int i = 3; i * i <= n; i +=
2) { if (isSet(mark[i >> 6], (i >> 1) & 31) == 0) { for
(int j = i * i; j <= n; j += (i << 1)) mark[j >> 6] =
Set(mark[j >> 6], (j >> 1) & 31); } } primes.push_back
(2); for (int i = 3; i <= n; i += 2) { if (isSet(mark[i
>> 6], (i >> 1) & 31) == 0) primes.push_back(i); } }
```

3.3 Chinese Remainder Theorem

```
/* // given a, b will find solutions for, ax + by = 1 */
tuple<LL, LL, LL> EGCD(LL a, LL b) { if (b == 0) return
{1, 0, a}; else { auto [x, y, g] = EGCD(b, a % b);
return {y, x - a / b * y, g}; } } /* // given modulo
equations, will apply CRT */ PLL CRT(vector<PLL> &v) {
LL V = 0, M = 1; for (auto &[v, m] : v) { /* // value %
mod */ auto [x, y, g] = EGCD(M, m); if ((v - V) % g !=
0) return {-1, 0}; V += x * (v - V) / g % (m / g) * M, M
```

```
*= m / g; V = (V % M + M) % M; } return make_pair(V, M)
; }
```

3.4 Divisor

```
/* // calculate divisor in range[1,n] */ LL sum_in_range
(LL n) { return n * (n + 1) / 2; } LL sum_all_divisors(
LL n) { LL ans = 0; for(LL i=1; i*i<=n; i++) { LL hello =
i * (n / i - i + 1); LL world = sum_in_range(n / i) -
sum_in_range(i); ans += hello + world; } return ans; }
```

3.5 Eulers Totient Function

```
void phi_in_range() { int N = 1e6, phi[N + 1]; for (int
i = 0; i <= N; i++) phi[i] = i; for (int i = 2; i <= N;
i++) { if (phi[i] != i) continue; for (int j = i; j <= N
; j += i) { phi[j] -= phi[j] / i; } } } #some important
properties of phi phi(a*b) = phi(a)*phi(b)*(gcd(a,b)/phi
(gcd(a,b))) phi(p^k) = p^k - p^(k-1), where p is a prime
number SUM{phi(d)} = n, d|n
```

3.6 FFT

```
using CD = complex<double>; typedef long long LL; const
double PI = acos(-1.0L); int N; vector<int> perm;
vector<CD> wp[2]; void precalculate(int n) { assert((n &
(n - 1)) == 0), N = n; perm = vector<int>(N, 0); for (
int k = 1; k < N; k <= 1) { for (int i = 0; i < k; i++)
{ perm[i] <= 1; perm[i + k] = 1 + perm[i]; } } wp[0] =
wp[1] = vector<CD>(N); for (int i = 0; i < N; i++) { wp
[0][i] = CD(cos(2 * PI * i / N), sin(2 * PI * i / N));
wp[1][i] = CD(cos(2 * PI * i / N), -sin(2 * PI * i / N))
; } } void fft(vector<CD> &v, bool invert = false) { if
(v.size() != perm.size()) precalculate(v.size()); for (
int i = 0; i < N; i++) if (i < perm[i]) swap(v[i], v[
perm[i]]); for (int len = 2; len <= N; len *= 2) { for (
int i = 0, d = N / len; i < N; i += len) { for (int j =
0, idx = 0; j < len / 2; j++, idx += d) { CD x = v[i + j
]; CD y = wp[invert][idx] * v[i + j + len / 2]; v[i + j]
= x + y; v[i + j + len / 2] = x - y; } } } if (invert)
{ for (int i = 0; i < N; i++) v[i] /= N; } } void
pairfft(vector<CD> &a, vector<CD> &b, bool invert =
false) { int N = a.size(); vector<CD> p(N); for (int i =
0; i < N; i++) p[i] = a[i] + b[i] * CD(0, 1); fft(p,
invert); p.push_back(p[0]); for (int i = 0; i < N; i++)
{ if (invert) { a[i] = CD(p[i].real(), 0); b[i] = CD(p[i
].imag(), 0); } else { a[i] = (p[i] + conj(p[N - i])) *
CD(0.5, 0); b[i] = (p[i] - conj(p[N - i])) * CD(0, -0.5)
; } } } vector<LL> multiply(const vector<LL> &a, const
```



```
vector<LL> &b) { int n = 1; while (n < a.size() + b.size()
()) n <= 1; vector<CD> fa(a.begin(), a.end()), fb(b.
begin(), b.end()); fa.resize(n); fb.resize(n); /* // fft
(fa); fft(fb); */ pairfft(fa, fb); for (int i = 0; i < n
; i++) fa[i] = fa[i] * fb[i]; fft(fa, true); vector<LL>
ans(n); for (int i = 0; i < n; i++) ans[i] = round(fa[i
].real()); return ans; } const int M = 1e9 + 7, B = sqrt
(M) + 1; vector<LL> anyMod(const vector<LL> &a, const
vector<LL> &b) { int n = 1; while (n < a.size() + b.size
()) n <= 1; vector<CD> al(n), ar(n), bl(n), br(n); for
(int i = 0; i < a.size(); i++) al[i] = a[i] % M / B, ar[
i] = a[i] % M % B; for (int i = 0; i < b.size(); i++) bl
[i] = b[i] % M / B, br[i] = b[i] % M % B; pairfft(al, ar
); pairfft(bl, br); /* // fft(al); fft(ar); fft(bl); fft
(br); */ for (int i = 0; i < n; i++) { CD ll = (al[i] *
bl[i]), lr = (al[i] * br[i]); CD rl = (ar[i] * bl[i]),
rr = (ar[i] * br[i]); al[i] = ll; ar[i] = lr; bl[i] = rl
; br[i] = rr; } pairfft(al, ar, true); pairfft(bl, br,
true); /* // fft(al, true); fft(ar, true); fft(bl, true)
; fft(br, true); */ vector<LL> ans(n); for (int i = 0; i
< n; i++) { LL right = round(br[i].real()), left =
round(al[i].real()); ; LL mid = round(round(bl[i].real()
) + round(ar[i].real())); ans[i] = ((left % M) * B * B +
(mid % M) * B + right) % M; } return ans; }
```

3.7 FWHT

```
#include<bits/stdc++.h> using namespace std; const int N
= 3e5 + 9, mod = 1e9 + 7; int POW(long long n, long
long k) { int ans = 1 % mod; n %= mod; if (n < 0) n +=
mod; while (k) { if (k & 1) ans = (long long) ans * n %
mod; n = (long long) n * n % mod; k >>= 1; } return ans;
} const int inv2 = (mod + 1) >> 1; #define M (1 << 20)
#define OR 0 #define AND 1 #define XOR 2 struct FWHT{
int P1[M], P2[M]; void wt(int *a, int n, int flag = XOR)
{ if (n == 0) return; int m = n / 2; wt(a, m, flag); wt
(a + m, m, flag); for (int i = 0; i < m; i++){ int x = a
[i], y = a[i + m]; if (flag == OR) a[i] = x, a[i + m] =
(x + y) % mod; if (flag == AND) a[i] = (x + y) % mod, a[
i + m] = y; if (flag == XOR) a[i] = (x + y) % mod, a[i +
m] = (x - y + mod) % mod; } } void iwt(int* a, int n,
int flag = XOR) { if (n == 0) return; int m = n / 2; iwt
(a, m, flag); iwt(a + m, m, flag); for (int i = 0; i < m
; i++){ int x = a[i], y = a[i + m]; if (flag == OR) a[i]
= x, a[i + m] = (y - x + mod) % mod; if (flag == AND) a
[i] = (x - y + mod) % mod, a[i + m] = y; if (flag == XOR
) a[i] = 1LL * (x + y) * inv2 % mod, a[i + m] = 1LL * (x
```

```
- y + mod) * inv2 % mod; /* // replace inv2 by >>1 if
not required */ } } vector<int> multiply(int n, vector<
int> A, vector<int> B, int flag = XOR) { assert(
__builtin_popcount(n) == 1); A.resize(n); B.resize(n);
for (int i = 0; i < n; i++) P1[i] = A[i]; for (int i =
0; i < n; i++) P2[i] = B[i]; wt(P1, n, flag); wt(P2, n,
flag); for (int i = 0; i < n; i++) P1[i] = 1LL * P1[i] *
P2[i] % mod; iwt(P1, n, flag); return vector<int> (P1,
P1 + n); } vector<int> pow(int n, vector<int> A, long
long k, int flag = XOR) { assert(__builtin_popcount(n)
== 1); A.resize(n); for (int i = 0; i < n; i++) P1[i] =
A[i]; wt(P1, n, flag); for(int i = 0; i < n; i++) P1[i]
= POW(P1[i], k); iwt(P1, n, flag); return vector<int> (
P1, P1 + n); } };
```

3.8 GCD convolution

```
template<int MOD> struct ModInt { private: int r; static
ModInt Pow(ModInt x, size_t n) { ModInt ret = 1; for (;
n >= 1, x *= x) if (n & 1) ret *= x; return ret; }
public: constexpr ModInt() : r(0) {} constexpr ModInt(
int x) : r(x % MOD) { if (r < 0) r += MOD; } constexpr
ModInt(i64 x) : r(x % MOD) { if (r < 0) r += MOD; }
ModInt Inv() const { return Pow(*this, MOD - 2); }
ModInt operator- () const { return r ? MOD - r : 0; }
ModInt operator+ (const ModInt& x) const { return ModInt
(*this) += x; } ModInt operator- (const ModInt& x) const
{ return ModInt(*this) -= x; } ModInt operator* (const
ModInt& x) const { return ModInt(*this) *= x; } ModInt
operator/ (const ModInt& x) const { return ModInt(*this)
/= x; } ModInt operator+= (const ModInt& x) { r += x.r;
if (r >= MOD) r -= MOD; return *this; } ModInt operator
-= (const ModInt& x) { r -= x.r; if (r < 0) r += MOD;
return *this; } ModInt operator*= (const ModInt& x) { r
= (i64)r * x.r % MOD; return *this; } ModInt operator/=
(const ModInt& x) { return *this *= x.Inv(); } bool
operator== (const ModInt& x) const { return r == x.r; }
bool operator!= (const ModInt& x) const { return r != x.
r; } operator int() const { return r; } operator i64()
const { return r; } friend istream& operator>> (istream&
in, ModInt& x) { i64 t; cin >> t; x = ModInt(t); return
in; } friend ostream& operator<< (ostream& out, const
ModInt& x) { return out << x.r; } }; using mint = ModInt
<998'244'353>; /* Linear Sieve, O(n) */ vector<int>
PrimeEnumerate(int n) { vector<int> P; vector<bool> B(n
+ 1, 1); for (int i = 2; i <= n; i++) { if (B[i]) P.
push_back(i); for (int j : P) { if (i * j > n) break; B[
i * j] = 0; if (i % j == 0) break; } } return P; }
template<typename T> void DivisorZetaTransform(vector<T
>& v) { const int n = (int)v.size() - 1; for (int p :
PrimeEnumerate(n)) { for (int i = 1; i * p <= n; i++) v[
i * p] += v[i]; } } template<typename T> void
DivisorMobiusTransform(vector<T>& v) { const int n = (
int)v.size() - 1; for (int p : PrimeEnumerate(n)) { for
(int i = n / p; i > 0; i--) v[i * p] -= v[i]; } } template<
typename T> vector<T> LCMConvolution(vector<T> A, vector
<T> B) { DivisorZetaTransform(A); DivisorZetaTransform(B
); for (int i = 0; i < A.size(); i++) A[i] *= B[i];
DivisorMobiusTransform(A); return A; } int main() {
fastio; int n; cin >> n; vector A(n + 1, mint(0)), B(n +
1, mint(0)); for (int i = 1; i <= n; i++) cin >> A[i];
for (int i = 1; i <= n; i++) cin >> B[i]; auto C =
LCMConvolution(A, B); for (int i = 1; i <= n; i++) cout
<< C[i] << ' '; }
```

```
i * j] = 0; if (i % j == 0) break; } } return P; }
template<typename T> void MultipleZetaTransform(vector<T
>& v) { const int n = (int)v.size() - 1; for (int p :
PrimeEnumerate(n)) { for (int i = n / p; i > 0; i--) v[i] +=
v[i * p]; } } template<typename T> void
MultipleMobiusTransform(vector<T>& v) { const int n = (
int)v.size() - 1; for (int p : PrimeEnumerate(n)) { for
(int i = 1; i * p <= n; i++) v[i] -= v[i * p]; } }
template<typename T> vector<T> GCDConvolution(vector<T>
A, vector<T> B) { MultipleZetaTransform(A);
MultipleZetaTransform(B); for (int i = 0; i < A.size();
i++) A[i] *= B[i]; MultipleMobiusTransform(A); return A;
} }
```

3.9 LCM cnvolution

```
/* See GCD for MODint */ using mint = ModInt<998'244'
353>; /* Linear Sieve, O(n) */ vector<int>
PrimeEnumerate(int n) { vector<int> P; vector<bool> B(n
+ 1, 1); for (int i = 2; i <= n; i++) { if (B[i]) P.
push_back(i); for (int j : P) { if (i * j > n) break; B[
i * j] = 0; if (i % j == 0) break; } } return P; }
template<typename T> void DivisorZetaTransform(vector<T
>& v) { const int n = (int)v.size() - 1; for (int p :
PrimeEnumerate(n)) { for (int i = 1; i * p <= n; i++) v[
i * p] += v[i]; } } template<typename T> void
DivisorMobiusTransform(vector<T>& v) { const int n = (
int)v.size() - 1; for (int p : PrimeEnumerate(n)) { for
(int i = n / p; i > 0; i--) v[i * p] -= v[i]; } } template<
typename T> vector<T> LCMConvolution(vector<T> A, vector
<T> B) { DivisorZetaTransform(A); DivisorZetaTransform(B
); for (int i = 0; i < A.size(); i++) A[i] *= B[i];
DivisorMobiusTransform(A); return A; } int main() {
fastio; int n; cin >> n; vector A(n + 1, mint(0)), B(n +
1, mint(0)); for (int i = 1; i <= n; i++) cin >> A[i];
for (int i = 1; i <= n; i++) cin >> B[i]; auto C =
LCMConvolution(A, B); for (int i = 1; i <= n; i++) cout
<< C[i] << ' '; }
```

3.10 LargePrime

```
vector<int> sieve(const int N, const int Q = 17, const
int L = 1 << 15) { static const int rs[] = {1, 7, 11,
13, 17, 19, 23, 29}; struct P { P(int p) : p(p) {} int p
; int pos[8]; }; auto approx_prime_count = [] (const int
N) -> int { return N > 60184 ? N / (log(N) - 1.1) : max
(1., N / (log(N) - 1.11)) + 1; }; const int v = sqrt(N),
vv = sqrt(v); vector<bool> isp(v + 1, true); for (int i
```

```

= 2; i <= vv; ++i) if (isp[i]) { for (int j = i * i; j
<= v; j += i) isp[j] = false; } const int rsize =
approx_prime_count(N + 30); vector<int> primes = {2, 3,
5}; int psize = 3; primes.resize(rsize); vector<P>
sprimes; size_t pbeg = 0; int prod = 1; for (int p = 7;
p <= v; ++p) { if (!isp[p]) continue; if (p <= Q) prod
*= p, ++pbeg, primes[psize++] = p; auto pp = P(p); for (
int t = 0; t < 8; ++t) { int j = (p <= Q) ? p : p * p;
while (j % 30 != rs[t]) j += p << 1; pp.pos[t] = j / 30;
} sprimes.push_back(pp); } vector<unsigned char> pre(
prod, 0xFF); for (size_t pi = 0; pi < pbeg; ++pi) { auto
pp = sprimes[pi]; const int p = pp.p; for (int t = 0; t
< 8; ++t) { const unsigned char m = ~(1 << t); for (int
i = pp.pos[t]; i < prod; i += p) pre[i] &= m; } } const
int block_size = (L + prod - 1) / prod * prod; vector<
unsigned char> block(block_size); unsigned char* pblock
= block.data(); const int M = (N + 29) / 30; for (int
beg = 0; beg < M; beg += block_size, pblock +=
block_size) { int end = min(M, beg + block_size); for (
int i = beg; i < end; i += prod) { copy(pre.begin(), pre
.end(), pblock + i); } if (beg == 0) pblock[0] &= 0xFE;
for (size_t pi = pbeg; pi < sprimes.size(); ++pi) { auto
& pp = sprimes[pi]; const int p = pp.p; for (int t = 0;
t < 8; ++t) { int i = pp.pos[t]; const unsigned char m =
~(1 << t); for (; i < end; i += p) pblock[i] &= m; pp.
pos[t] = i; } } for (int i = beg; i < end; ++i) { for (
int m = pblock[i]; m > 0; m &= m - 1) { primes[psize++]
= i * 30 + rs[_builtin_ctz(m)]; } } } assert(psize <=
rsize); while (psize > 0 && primes[psize - 1] > N) --
psize; primes.resize(psize); return primes; }

```

3.11 Linear Recurrence

```

const int N = 3e5 + 9, mod = 1e9 + 7; template <int32_t
MOD> struct modint { int32_t value; modint() = default;
modint(int32_t value_) : value(value_) {} inline modint<
MOD> operator + (modint<MOD> other) const { int32_t c =
this->value + other.value; return modint<MOD>(c >= MOD ?
c - MOD : c); } inline modint<MOD> operator - (modint<
MOD> other) const { int32_t c = this->value - other.
value; return modint<MOD>(c < 0 ? c + MOD : c); } inline
modint<MOD> operator * (modint<MOD> other) const {
int32_t c = (int64_t)this->value * other.value % MOD;
return modint<MOD>(c < 0 ? c + MOD : c); } inline modint
<MOD> & operator += (modint<MOD> other) { this->value +=
other.value; if (this->value >= MOD) this->value -= MOD
; return *this; } inline modint<MOD> & operator -= (

```

```

modint<MOD> other) { this->value -= other.value; if (
this->value < 0) this->value += MOD; return *this; }
inline modint<MOD> & operator *= (modint<MOD> other) {
this->value = (int64_t)this->value * other.value % MOD;
if (this->value < 0) this->value += MOD; return *this; }
inline modint<MOD> operator - () const { return modint<
MOD>(this->value ? MOD - this->value : 0); } modint<MOD>
pow(uint64_t k) const { modint<MOD> x = *this, y = 1;
for (; k; k >>= 1) { if (k & 1) y *= x; x *= x; } return
y; } modint<MOD> inv() const { return pow(MOD - 2); }
/* MOD must be a prime */ inline modint<MOD> operator /
(modint<MOD> other) const { return *this * other.inv(); }
inline modint<MOD> operator /= (modint<MOD> other) {
return *this *= other.inv(); } inline bool operator == (
modint<MOD> other) const { return value == other.value; }
inline bool operator != (modint<MOD> other) const {
return value != other.value; } inline bool operator < (
modint<MOD> other) const { return value < other.value; }
inline bool operator > (modint<MOD> other) const {
return value > other.value; } }; template <int32_t MOD>
modint<MOD> operator * (int64_t value, modint<MOD> n) {
return modint<MOD>(value) * n; } template <int32_t MOD>
modint<MOD> operator * (int32_t value, modint<MOD> n) {
return modint<MOD>(value % MOD) * n; } template <int32_t
MOD> istream & operator >> (istream & in, modint<MOD> &
n) { return in >> n.value; } template <int32_t MOD>
ostream & operator << (ostream & out, modint<MOD> n) {
return out << n.value; } using mint = modint<mod>;
vector<mint> combine (int n, vector<mint> &a, vector<
mint> &b, vector<mint> &tr) { vector<mint> res(n * 2 +
1, 0); for (int i = 0; i < n + 1; i++) { for (int j = 0;
j < n + 1; j++) res[i + j] += a[i] * b[j]; } for (int i
= 2 * n; i > n; --i) { for (int j = 0; j < n; j++) res[
i - 1 - j] += res[i] * tr[j]; } res.resize(n + 1);
return res; }; // transition -> for(i = 0; i < x; i++) f
[n] += tr[i] * f[n-i-1] // S contains initial values, k
is 0 indexed mint LinearRecurrence(vector<mint> &S,
vector<mint> &tr, long long k) { int n = S.size();
assert(n == (int)tr.size()); if (n == 0) return 0; if (k
< n) return S[k]; vector<mint> pol(n + 1), e(pol); pol
[0] = e[1] = 1; for (++k; k; k /= 2) { if (k % 2) pol =
combine(n, pol, e, tr); e = combine(n, e, e, tr); } mint
res = 0; for (int i = 0; i < n; i++) res += pol[i + 1]
* S[i]; return res; }

```

3.12 Lucas

```

const int N = 1e6 + 3, mod = 1e6 + 3; using ll = long
long; template <const int32_t MOD> struct modint {
int32_t value; modint() = default; modint(int32_t value_
) : value(value_) {} inline modint<MOD> operator + (
modint<MOD> other) const { int32_t c = this->value +
other.value; return modint<MOD>(c >= MOD ? c - MOD : c); }
inline modint<MOD> operator - (modint<MOD> other)
const { int32_t c = this->value - other.value; return
modint<MOD>(c < 0 ? c + MOD : c); } inline modint<MOD>
operator * (modint<MOD> other) const { int32_t c = (
int64_t)this->value * other.value % MOD; return modint<
MOD>(c < 0 ? c + MOD : c); } inline modint<MOD> &
operator += (modint<MOD> other) { this->value += other.
value; if (this->value >= MOD) this->value -= MOD;
return *this; } inline modint<MOD> & operator -= (modint
<MOD> other) { this->value -= other.value; if (this->
value < 0) this->value += MOD; return *this; } inline
modint<MOD> & operator *= (modint<MOD> other) { this->
value = (int64_t)this->value * other.value % MOD; if (
this->value < 0) this->value += MOD; return *this; }
inline modint<MOD> operator - () const { return modint<
MOD>(this->value ? MOD - this->value : 0); } modint<MOD>
pow(uint64_t k) const { modint<MOD> x = *this, y = 1;
for (; k; k >>= 1) { if (k & 1) y *= x; x *= x; } return
y; } modint<MOD> inv() const { return pow(MOD - 2); }
/* // MOD must be a prime */ inline modint<MOD> operator
/ (modint<MOD> other) const { return *this * other.inv
(); } inline modint<MOD> operator /= (modint<MOD> other)
{ return *this *= other.inv(); } inline bool operator
== (modint<MOD> other) const { return value == other.
value; } inline bool operator != (modint<MOD> other)
const { return value != other.value; } inline bool
operator < (modint<MOD> other) const { return value <
other.value; } inline bool operator > (modint<MOD> other
) const { return value > other.value; } }; template <
int32_t MOD> modint<MOD> operator * (int32_t value,
modint<MOD> n) { return modint<MOD>(value) * n; }
template <int32_t MOD> modint<MOD> operator * (int64_t
value, modint<MOD> n) { return modint<MOD>(value % MOD)
* n; } template <int32_t MOD> istream & operator >> (
istream & in, modint<MOD> &n) { return in >> n.value; }
template <int32_t MOD> ostream & operator << (ostream &
out, modint<MOD> n) { return out << n.value; } using
mint = modint<mod>; struct combi { int n; vector<mint>
facts, finvs, invs; combi(int _n): n(_n), facts(_n),
finvs(_n), invs(_n) { facts[0] = finvs[0] = 1; invs[1] =

```

```
1; for (int i = 2; i < n; i++) invs[i] = invs[mod % i] *
(-mod / i); for(int i = 1; i < n; i++){ facts[i] =
facts[i - 1] * i; finvs[i] = finvs[i - 1] * invs[i]; } }
inline mint fact(int n) { return facts[n]; } inline
mint finv(int n) { return finvs[n]; } inline mint inv(
int n) { return invs[n]; } inline mint ncr(int n, int k)
{ return n < k or k < 0 ? 0 : facts[n] * finvs[k] *
finvs[n-k]; } }; combi C(N); /* // returns nCr modulo
mod where mod is a prime // Complexity: log(n) */ mint
lucas(ll n, ll r) { if (r > n) return 0; if (n < mod)
return C.ncr(n, r); return lucas(n / mod, r / mod) *
lucas(n % mod, r % mod); }
```

3.13 Matrix

```
template<typename DT> struct Matrix{ vector<vector<DT>>
mat; Matrix(vector<vector<DT>> &mat) : mat(mat) {}
Matrix(int n) : mat(n, vector<DT> (n)){ for(int i = 0; i
< n; i++){ mat[i][i] = 1; } } Matrix(int n, int m) :
mat(n, vector<DT> (m)) {} Matrix operator*(Matrix &other
){ auto &a = mat, &b = other.mat; assert(a[0].size() ==
b.size()); int n = a.size(), m = b[0].size(), s = a[0].
size(); Matrix<DT> ret(n, m); for(int i = 0; i < n; i++)
{ for(int j = 0; j < m; j++){ DT temp = 0; for(int k =
0; k < s; k++){ temp = (temp + 1LL * a[i][k] * b[k][j] %
MOD) % MOD; } ret.mat[i][j] = temp; } } return ret; }
}; Matrix<int> pow(Matrix<int> a, LL p){ int n = a.mat.
size(); Matrix<int> ret(n); while(p){ if(p & 1) ret =
ret * a; a = a * a; p >>= 1; } return ret; }
```

3.14 NOD and SOD

```
/* // NUMBER = p_1^a_1 * p_2^a_2 .... p_n^a_n */ LL NOD
= 1, SOD = 1, POD = 1, POWER = 1; for(int i = 0; i < n;
i++) { LL p, a; cin >> p >> a; NOD = (NOD * (a + 1)) %
MOD; SOD = ((SOD * (bigmod(p, a + 1, MOD) + MOD - 1)) %
MOD * inv[p - 1]) % MOD; POD = bigmod(POD, a + 1, MOD) *
bigmod(bigmod(x, a * (a + 1) / 2, MOD), POWER, MOD) %
MOD; POWER = (POWER * (a + 1)) % (MOD - 1); } cout <<
NOD << ' ' << SOD << ' ' << POD << '\n'; /* // CSOD */
LL csod(LL n) { LL ans = 0; for(LL i = 2; i * i <= n; ++
i) { LL j = n / i; ans += (i + j) * (j - i + 1) / 2; ans
+= i * (j - i); } return ans; } summation of NOD(d)[d|n
] = product of g(e_k + 1)[n=p_k^a_k] g(x) = x * (x + 1)
/ 2
```

3.15 Pollard rho

```
namespace rho{ inline LL mul(LL a, LL b, LL mod) { LL
result = 0; while (b) { if (b & 1) result = (result + a)
% mod; a = (a + a) % mod; b >>= 1; } return result; }
inline LL bigmod(LL num, LL pow, LL mod){ LL ans = 1; for(
; pow > 0; pow >>= 1, num = mul(num, num, mod)) if(pow
& 1) ans = mul(ans, num, mod); return ans; } inline bool
is_prime(LL n){ if(n < 2 or n % 6 % 4 != 1) return (n|1)
== 3; LL a[] = {2, 325, 9375, 28178, 450775, 9780504,
1795265022}; LL s = __builtin_ctzll(n-1), d = n >> s;
for(LL x: a){ LL p = bigmod(x % n, d, n), i = s; for( ;
p != 1 and p != n-1 and x % n and i--; p = mul(p, p, n))
; if(p != n-1 and i != s) return false; } return true; }
LL f(LL x, LL n) { return mul(x, x, n) + 1; } LL
get_factor(LL n) { LL x = 0, y = 0, t = 0, prod = 2, i =
2, q; for( ; t++ %40 or __gcd(prod, n) == 1; x = f(x, n
), y = f(f(y, n), n) ){ (x == y) ? x = i++, y = f(x, n)
: 0; prod = (q = mul(prod, max(x,y) - min(x,y), n)) ? q
: prod; } return __gcd(prod, n); } void _factor(LL n,
map<LL, int> &res) { if(n == 1) return; if(is_prime(n))
res[n]++; else { LL x = get_factor(n); _factor(x, res);
_factor(n / x, res); } } map<LL, int> factorize(LL n){
map<LL, int> res; if(n < 2) return res; LL
small_primes[] = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29,
31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89,
97 }; for (LL p: small_primes) for( ; n % p == 0; n /= p
, res[p]++); _factor(n, res); return res; }
```

3.16 Sieve

```
const int N = 10000000; vector<int> lp(N), pr; for (int
i = 2; i < N; i++) { if (lp[i] == 0) { lp[i] = i; pr.
push_back(i); } for (int j = 0; i * pr[j] < N; j++) {
lp[i * pr[j]] = pr[j]; if (pr[j] == lp[i]) break; } }
```

3.17 XOR Basis

```
template<typename T = int, int B = 31> struct Basis { T
a[B]; Basis() { memset(a, 0, sizeof a); } void insert(T
x){ for (int i = B - 1; i >= 0; i--) { if (x >> i & 1) {
if (a[i]) x ^= a[i]; else { a[i] = x; break; } } } }
bool can(T x) { for(int i = B - 1; i >= 0; i--) { x =
min(x, x ^ a[i]); } return x == 0; } T max_xor(T ans =
0) { for(int i = B - 1; i >= 0; i--) { ans = max(ans,
ans ^ a[i]); } return ans; } };
```

3.18 mobius function

```
const int N = 1e6 + 5; int mob[N]; void mobius() {
memset(mob, -1, sizeof mob); mob[1] = 1; for (int i = 2;
```

```
i < N; i++) if (mob[i]) { for (int j = i + i; j < N; j
+= i) mob[j] -= mob[i]; } }
```

3.19 nCr

```
namespace com { LL fact[N], inv[N], inv_fact[N]; void
init() { fact[0] = inv_fact[0] = 1; for (LL i = 1; i < N
; i++) { inv[i] = i == 1 ? 1 : (LL)inv[i - mod % i] * (
mod / i + 1) % mod; fact[i] = (LL)fact[i - 1] * i % mod;
inv_fact[i] = (LL)inv_fact[i - 1] * inv[i] % mod; } }
LL C(int n, int r) { return (r < 0 or r > n) ? 0 : fact[
n] * inv_fact[r] % mod * inv_fact[n - r] % mod; } }
```

3.20 ntt

```
const LL N = 1 << 18; const LL MOD = 786433; vector<LL>
P[N]; LL rev[N], w[N | 1], a[N], b[N], inv_n, g; LL Pow(
LL b, LL p) { LL ret = 1; while (p) { if (p & 1) ret = (
ret * b) % MOD; b = (b * b) % MOD; p >>= 1; } return ret
; } LL primitive_root(LL p) { vector<LL> factor; LL phi
= p - 1, n = phi; for (LL i = 2; i * i <= n; i++) { if (
n % i) continue; factor.emplace_back(i); while (n % i ==
0) n /= i; } if (n > 1) factor.emplace_back(n); for (LL
res = 2; res <= p; res++) { bool ok = true; for (LL i =
0; i < factor.size() && ok; i++) ok &= Pow(res, phi /
factor[i]) != 1; if (ok) return res; } return -1; } void
prepare(LL n) { LL sz = abs(31 - __builtin_clz(n)); LL
r = Pow(g, (MOD - 1) / n); inv_n = Pow(n, MOD - 2); w[0]
= w[n] = 1; for (LL i = 1; i < n; i++) w[i] = (w[i - 1]
* r) % MOD; for (LL i = 1; i < n; i++) rev[i] = (rev[i
>> 1] >> 1) | ((i & 1) << (sz - 1)); } void NTT(LL *a,
LL n, LL dir = 0) { for (LL i = 1; i < n - 1; i++) if (i
< rev[i]) swap(a[i], a[rev[i]]); for (LL m = 2; m <= n;
m <= 1) { for (LL i = 0; i < n; i += m) { for (LL j =
0; j < (m >> 1); j++) { LL &u = a[i + j], &v = a[i + j +
(m >> 1)]; LL t = v * w[dir ? n - n / m * j : n / m * j
] % MOD; v = u - t < 0 ? u - t + MOD : u - t; u = u + t
>= MOD ? u + t - MOD : u + t; } } } if (dir) for (LL i =
0; i < n; i++) a[i] = (inv_n * a[i]) % MOD; } vector<LL
> mul(vector<LL> p, vector<LL> q) { LL n = p.size(), m =
q.size(); LL t = n + m - 1, sz = 1; while (sz < t) sz
<= 1; prepare(sz); for (LL i = 0; i < n; i++) a[i] = p[
i]; for (LL i = 0; i < m; i++) b[i] = q[i]; for (LL i =
n; i < sz; i++) a[i] = 0; for (LL i = m; i < sz; i++) b[
i] = 0; NTT(a, sz); NTT(b, sz); for (LL i = 0; i < sz; i
++) a[i] = (a[i] * b[i]) % MOD; NTT(a, sz, 1); vector<LL
> c(a, a + sz); while (c.size() && c.back() == 0) c.
pop_back(); return c; }
```


3.21 primality test

```
using ULL = unsigned long long; /* // 5472940991761
worst carmichael number */ inline ULL mul(ULL a, ULL b,
ULL mod){ LL ans = a * b - mod * (ULL) (1.L / mod * a *
b); return ans + mod * (ans < 0) - mod * (ans >= (LL)
mod); } inline ULL bigmod(ULL num, ULL pow, ULL mod){ ULL
ans = 1; for( ; pow > 0; pow >>= 1, num = mul(num, num,
mod)) if(pow&1) ans = mul(ans, num, mod); return ans; }
inline bool is_prime(ULL n){ if(n < 2 or n % 6 % 4 != 1)
return (n|1) == 3; ULL a[] = {2, 325, 9375, 28178,
450775, 9780504, 1795265022}; ULL s = __builtin_ctzll(n
-1), d = n >> s; for(ULL x: a){ ULL p = bigmod(x % n, d,
n), i = s; for( ; p != 1 and p != n-1 and x % n and i
--; p = mul(p, p, n)); if(p != n-1 and i != s) return
false; } return true; } /* // handle bigmod overflow */
vector<int> primes; vector<bool> prime(200, true); bool
check_primality(LL p){ if(p<2) return false; if(primes.
empty()){ for(int i=2; i<100; i++){ for(int j=i+i; j<200; j
+=i) prime[j] = false; } for(int i=2; i<200; i++){ if(
prime[i]) primes.push_back(i); } } for(auto a: primes){
if(p!=a and bigmod(a, p-1, p) != 1) return false; } return
true; }
```

3.22 prime counting function

```
namespace PCF {
const LL MAX = 1E13;
const int N = 7E6; /// around MAX^(2/3)/15
const int M = 7, PM = 2 * 3 * 5 * 7 * 11 * 13 * 17;

bool isp[N];
int prime[N], pi[N];
int phi[M + 1][PM + 1], sz[M + 1];

auto div = [](LL a, LL b) -> LL { return double(a) / b
; };
auto rt2 = [](LL x) -> int { return sqrtl(x); };
auto rt3 = [](LL x) -> int { return cbrtl(x); };

void init() {
int cnt = 0;
for (int i = 2; i < N; i++) isp[i] = true;
pi[0] = pi[1] = 0;
for (int i = 2; i < N; i++) {
if (isp[i]) prime[++cnt] = i;
pi[i] = cnt;
}
```

```
for (int j = 1; j <= cnt && i * prime[j] < N; j++)
{
isp[i * prime[j]] = false;
if (i % prime[j] == 0) break;
}
}
sz[0] = 1;
for (int i = 0; i <= PM; ++i) phi[0][i] = i;
for (int i = 1; i <= M; ++i) {
sz[i] = prime[i] * sz[i - 1];
for (int j = 1; j <= PM; ++j) phi[i][j] = phi[i -
1][j] - phi[i - 1][div(j, prime[i])];
}
}
LL getphi(LL x, int s) {
if (s == 0) return x;
if (s <= M) return phi[s][x % sz[s]] + (x / sz[s]) *
phi[s][sz[s]];
if (x <= 1LL * prime[s] * prime[s]) return pi[x] - s
+ 1;
if (x <= 1LL * prime[s] * prime[s] * prime[s] && x <
N) {
int s2x = pi[rt2(x)];
LL ans = pi[x] - (s2x + s - 2) * (s2x - s + 1) / 2;
for (int i = s + 1; i <= s2x; ++i) ans += pi[div(x,
prime[i])];
return ans;
}
}
return getphi(x, s - 1) - getphi(div(x, prime[s]), s
- 1);
}
LL getpi(LL x) {
if (x < N) return pi[x];
LL ans = getphi(x, pi[rt3(x)]) + pi[rt3(x)] - 1;
for (int i = pi[rt3(x)] + 1, ed = pi[rt2(x)]; i <=
ed; ++i) ans -= getpi(div(x, prime[i])) - i + 1;
return ans;
}
} // namespace PCF
```

4 Graph

4.1 Bellman Ford

```
void bellmanford(int n, int m, vector<int> edge[], int
dist[], int src){ fill(dist, dist + n, INT_MAX); dist[
src] = 0; int i, j, k; vector<int> v; for (i = 0; i < n;
i++){ for (j = 0; j < m; j++) { v = edge[j]; if (dist[v
```

```
[1]] > dist[v[0]] + v[2]) dist[v[1]] = dist[v[0]] + v
[2]; } } for (j = 0; j < m; j++){ /* // For checking
negative loop */ v = edge[j]; if (dist[v[1]] > dist[v
[0]] + v[2]){ fill(dist, dist + n, INT_MIN); /* //
Negative loop detected */ return; } } }
```

4.2 BridgeTree

```
vector<PLL> g[N]; vector<int> ng[N]; int disc[N], low[N
], mark[N], vis[N], timer = 1; void find_bridge(int u,
int p) { disc[u] = low[u] = timer++; bool fl = 1; for (
auto [v, id] : g[u]) { if (v == p && fl) { fl = 0;
continue; } if (disc[v]) { low[u] = min(low[u], disc[v])
; } else { find_bridge(v, u); low[u] = min(low[u], low[v
]); if (disc[u] < low[v]) { mark[id] = 1; } } } } void
colorComponents(int u, int color) { if (vis[u]) return;
vis[u] = color; for (auto [v, id] : g[u]) { if (mark[id
]) continue; colorComponents(v, color); } } void solve()
{ int n, m; cin >> n >> m; vector<PLL> edges; for (int
i = 0; i < m; i++) { int u, v; cin >> u >> v; edges.
push_back({u, v}); g[u].push_back({v, i}); g[v].
push_back({u, i}); } find_bridge(1, 0); int color = 1;
for (int i = 1; i <= n; i++) { if (!vis[i])
colorComponents(i, color++); } for (int i = 0; i < m; i
++) { if (mark[i]) { ng[vis[edges[i].first]].push_back(
vis[edges[i].second]); ng[vis[edges[i].second]].
push_back(vis[edges[i].first]); } } }
```

4.3 DSU, MST

```
class DSU { vector<int> parent, size; public: DSU(int n)
: parent(n + 1), size(n + 1, 1) { iota(parent.begin(),
parent.end(), 0); } int root(int u) { if (parent[u] == u
) return u; return parent[u] = root(parent[u]); } bool
same(int u, int v) { return root(u) == root(v); } void
merge(int u, int v) { u = root(u), v = root(v); if (u ==
v) return; if (size[u] < size[v]) swap(u, v); parent[v]
= u, size[u] += size[v]; } }; int kruskal(vector<tuple<
int, int, int>> edges, int n) { sort(edges.begin(),
edges.end()); DSU mst(n); int cost = 0; for (auto [w, u
, v] : edges) { if (mst.same(u, v)) continue; mst.merge(
u, v); cost += w; } return cost; } /* // PRIM'S SPANNING
TREE (MST) */ DIJKSTRA code... start from a node, and
push nodes which are not marked popped edges weight are
taken
```

4.4 ETT, VT


```

struct euler_tour { int time = 0; tree &T; int n; vector
<int> start, finish, level, par; euler_tour(tree &T, int
root = 0) : T(T), n(T.n), start(n), finish(n), level(n)
, par(n) { time = 0; call(root); } void call(int node,
int p = -1) { if (p != -1) level[node] = level[p] + 1;
start[node] = time++; for (int e : T[node]) if (e != p)
call(e, node); par[node] = p; finish[node] = time++; }
bool isAncestor(int node, int par) { return start[par]
<= start[node] and finish[par] >= finish[node]; } int
subtreeSize(int node) { return finish[node] - start[node]
+ 1 >> 1; } }; tree virtual_tree(vector<int> &nodes,
lca_table &table, euler_tour &tour) { sort(nodes.begin()
, nodes.end(), [&](int x, int y) { return tour.start[x]
< tour.start[y]; }); int n = nodes.size(); for (int i =
0; i + 1 < n; i++) nodes.push_back(table.lca(nodes[i],
nodes[i + 1])); sort(nodes.begin(), nodes.end()); nodes.
erase(unique(nodes.begin(), nodes.end()), nodes.end());
sort(nodes.begin(), nodes.end(), [&](int x, int y) {
return tour.start[x] < tour.start[y]; }); n = nodes.size
(); stack<int> st; st.push(0); tree ans(n); for (int i =
1; i < n; i++) { while (!tour.isAncestor(nodes[i],
nodes[st.top()]))) st.pop(); ans.addEdge(st.top(), i); st
.push(i); } return ans; } set<int> getCenters(tree &T) {
int n = T.n; vector<int> deg(n), q; set<int> s; for (
int i = 0; i < n; i++) { deg[i] = T[i].size(); if (deg[i]
== 1) q.push_back(i); s.insert(i); } for (vector<int>
t; s.size() > 2; q = t) { for (auto x : q) { for (auto e
: T[x]) if (--deg[e] == 1) t.push_back(e); s.erase(x);
} } return s; }

```

4.5 HLD

```

class HLD { vector<int> parent, depth, heavy, head, pos,
euler, start, end; int n, cur_pos; LazySegmentTree
segTree; int dfs(int v, const vector<vector<int>>> &adj)
{ int size = 1, max_c_size = 0; for (int c : adj[v]) {
if (c != parent[v]) { parent[c] = v; depth[c] = depth[v]
+ 1; int c_size = dfs(c, adj); size += c_size; if (
c_size > max_c_size) { max_c_size = c_size; heavy[v] = c
; } } } return size; } void decompose(int v, int h,
const vector<vector<int>>> &adj) { head[v] = h; pos[v] =
cur_pos++; euler.push_back(v); start[v] = euler.size() -
1; if (heavy[v] != -1) decompose(heavy[v], h, adj); for
(int c : adj[v]) { if (c != parent[v] && c != heavy[v])
decompose(c, c, adj); } end[v] = euler.size() - 1; }
public: HLD(int n, const vector<vector<int>>> &adj,
vector<LL> &v) : n(n), parent(n), depth(n), heavy(n, -1)

```

```

, head(n), pos(n), start(n), end(n), cur_pos(0), segTree
(v, 0) { parent[0] = -1; depth[0] = 0; dfs(0, adj);
decompose(0, 0, adj); for (int i = 0; i < n; i++)
segTree.update(pos[i], pos[i], v[i]); } void update_path
(int a, int b, LL val) { while (head[a] != head[b]) {
if (depth[head[a]] < depth[head[b]]) swap(a, b); segTree
.update(pos[head[a]], pos[a], val); a = parent[head[a]];
} if (depth[a] > depth[b]) swap(a, b); segTree.update(
pos[a], pos[b], val); } LL query_path (int a, int b) {
LL res = 0; while (head[a] != head[b]) { if (depth[head[
a]] < depth[head[b]]) swap(a, b); res = max (res,
segTree.query(pos[head[a]], pos[a])); a = parent[head[a
]]; } if (depth[a] > depth[b]) swap(a, b); res = max (
res, segTree.query(pos[a], pos[b])); return res; } void
update_subtree (int v, LL val) { segTree.update(start[v]
, end[v], val); } LL query_subtree (int v) { return
segTree.query(start[v], end[v]); } };

```

4.6 Hungarian

```

/* Complexity:  $O(n^3)$  but optimized It finds minimum
cost maximum matching. For finding maximum cost maximum
matching add -cost and return -matching() 1-indexed */
struct Hungarian { long long c[N][N], fx[N], fy[N], d[N]
; int l[N], r[N], arg[N], trace[N]; queue<int> q; int
start, finish, n; const long long inf = 1e18; Hungarian
() {} Hungarian(int n1, int n2): n(max(n1, n2)) { for (
int i = 1; i <= n; ++i) { fy[i] = l[i] = r[i] = 0; for (
int j = 1; j <= n; ++j) c[i][j] = inf; /* // make it 0
for maximum cost matching (not necessarily with max
count of matching) */ } } void add_edge(int u, int v,
long long cost) { c[u][v] = min(c[u][v], cost); } inline
long long getC(int u, int v) { return c[u][v] - fx[u] -
fy[v]; } void initBFS() { while (!q.empty()) q.pop(); q
.push(start); for (int i = 0; i <= n; ++i) trace[i] = 0;
for (int v = 1; v <= n; ++v) { d[v] = getC(start, v);
arg[v] = start; } finish = 0; } void findAugPath() {
while (!q.empty()) { int u = q.front(); q.pop(); for (
int v = 1; v <= n; ++v) if (!trace[v]) { long long w =
getC(u, v); if (!w) { trace[v] = u; if (!r[v]) { finish
= v; return; } q.push(r[v]); } if (d[v] > w) { d[v] = w;
arg[v] = u; } } } } void subX_addY() { long long delta
= inf; for (int v = 1; v <= n; ++v) if (trace[v] == 0 &&
d[v] < delta) { delta = d[v]; } /* Rotate */ fx[start]
+= delta; for (int v = 1; v <= n; ++v) if (trace[v]) {
int u = r[v]; fy[v] -= delta; fx[u] += delta; } else d[v]
-= delta; for (int v = 1; v <= n; ++v) if (!trace[v]

```

```

&& !d[v]) { trace[v] = arg[v]; if (!r[v]) { finish = v;
return; } q.push(r[v]); } } void Enlarge() { do { int u
= trace[finish]; int nxt = l[u]; l[u] = finish; r[finish]
= u; finish = nxt; } while (finish); } long long
maximum_matching() { for (int u = 1; u <= n; ++u) { fx[u]
= c[u][1]; for (int v = 1; v <= n; ++v) { fx[u] = min(
fx[u], c[u][v]); } } for (int v = 1; v <= n; ++v) { fy[v]
= c[1][v] - fx[1]; for (int u = 1; u <= n; ++u) { fy[v]
= min(fy[v], c[u][v] - fx[u]); } } for (int u = 1; u
<= n; ++u) { start = u; initBFS(); while (!finish) {
findAugPath(); if (!finish) subX_addY(); } Enlarge(); }
long long ans = 0; for (int i = 1; i <= n; ++i) { if (c[
i][l[i]] != inf) ans += c[i][l[i]]; else l[i] = 0; }
return ans; } }; int32_t main() { ios_base::
sync_with_stdio(0); cin.tie(0); int n1, n2, m; cin >> n1
>> n2 >> m; Hungarian M(n1, n2); for (int i = 1; i <= m
; i++) { int u, v, w; cin >> u >> v >> w; M.add_edge(u,
v, -w); } cout << -M.maximum_matching() << '\n'; for (
int i = 1; i <= n1; i++) cout << M.l[i] << ' '; return
0; }

```

4.7 K th shortest path

```

void K_shortest(int n, int m) { int st, des, k, u, v; LL
w; scanf("%d%d%d", &st, &des, &k); st--, des--; vector<
vector<pii>> > edges(n); for (int i = 0; i < m; i++) {
scanf("%d%d%d", &u, &v, &w); u--, v--; edges[u].
push_back({w, v}); } vector<vector<LL>> > dis(n, vector<
LL>(k + 1, 1e8)); vector<int> vis(n); priority_queue<pii
, vector<pii>, greater<pii>> > q; q.emplace(0LL, st);
while (!q.empty()) { v = q.top().second, w = q.top().
first; q.pop(); if (vis[v] >= k) continue; /* // for the
variant, check if this path is greater than previous,
if not, continue // if(vis[v]>0 && w == dis[v][vis[v]
-1]) continue; */ dis[v][vis[v]] = w; vis[v]++; for (
auto nd : edges[v]) { q.emplace(w + nd.first, nd.second)
; } } LL ans = dis[des][k - 1]; if (ans == 1e8) ans =
-1; printf("%lld\n", ans); }

```

4.8 LCA, CD

```

struct Tree { vector<vector<int>> adj; Tree(int N) : adj
(N + 1) {} void addEdges(int u, int v) { adj[u].
push_back(v); adj[v].push_back(u); } }; class LCA { int
N, K; vector<vector<int>> &adj, anc; vector<int> level;
public: LCA(Tree &tree) : adj(tree.adj) { N = tree.adj.
size() - 1; K = 33 - __builtin_clz(N); anc.assign(N + 1,
vector<int>(K)); level.assign(N + 1, 0); initLCA(1); }

```

```

void initLCA(int u, int p = 0) { anc[u][0] = p; level[u]
= level[p] + 1; for (int i = 1; i < K; i++) { anc[u][i]
= anc[anc[u][i - 1]][i - 1]; } for (auto v : adj[u]) if
(v != p) { initLCA(v, u); } } int getAnc(int u, int k)
{ for (int i = K - 1; i >= 0; i--) if (k & (1 << i)) u =
anc[u][i]; return u; } int lca(int u, int v) { if (
level[u] > level[v]) swap(u, v); v = getAnc(v, level[v]
- level[u]); if (u == v) return u; for (int i = K - 1; i
>= 0; i--) { if (anc[u][i] != anc[v][i]) u = anc[u][i],
v = anc[v][i]; } return anc[u][0]; } int dis(int u, int
v) { return level[u] + level[v] - 2 * level[lca(u, v)];
} }; class CD { vector<vector<int>> adj; vector<int>
sub; vector<bool> blocked; int N; public: CD(Tree &tree)
: adj(tree.adj) { N = tree.adj.size() - 1; blocked.
assign(N + 1, 0); sub.assign(N + 1, 0); compute(); }
void compute(int u = 1, int p = 0) { sub[u] = 1; for (
auto v : adj[u]) if (v != p) { compute(v, u); sub[u] +=
sub[v]; } } int centroid(int u, int p = 0) { int tot =
sub[u]; for (auto v : adj[u]) { if (v == p || blocked[v]
) continue; if (2 * sub[v] > tot) { sub[u] = tot - sub[
v]; sub[v] = tot; return centroid(v, u); } } return u; }
int count(int u, int p) { /* // calculate ans */ } void
update(int u, int p) { /* // update */ } int decompose(
int u = 1) { u = centroid(u); blocked[u] = 1; int ans =
0; /* // Do something here */ count() update() */
for (auto v : adj[u]) if (!blocked[v]) { ans += count(v,
u); update(v, u); } /* // reset updates here */ for (
auto v : adj[u]) if (!blocked[v]) { decompose(v); }
return ans; } };

```

4.9 block cut tree

```

const int N = 200010; bitset<N> art, good; vector<int>
g[N], tree[N], st, comp[N]; int n, m, ptr, cur, in[N],
low[N], id[N]; void dfs (int u, int from = -1) { in[u] =
low[u] = ++ptr; st.emplace_back(u); for (int v : g[u])
if (v ^ from) { if (!in[v]) { dfs(v, u); low[u] = min(
low[u], low[v]); if (low[v] >= in[u]) { art[u] = in[u] >
1 or in[v] > 2; comp[++cur].emplace_back(u); while (
comp[cur].back() ^ v) { comp[cur].emplace_back(st.back()
); st.pop_back(); } } } else { low[u] = min(low[u], in[
v]); } } } void buildTree() { ptr = 0; for (int i = 1; i
<= n; ++i) { if (art[i]) id[i] = ++ptr; } for (int i =
1; i <= cur; ++i) { int x = ++ptr; for (int u : comp[i])
{ if (art[u]) { tree[x].emplace_back(id[u]); tree[id[u]
].emplace_back(x); } else { id[u] = x; } } } } int main
() { cin >> n >> m; while (m--) { int u, v; scanf("%d %d

```

```

", &u, &v); g[u].emplace_back(v); g[v].emplace_back(u);
} for (int i = 1; i <= n; ++i) { if (!in[i]) dfs(i); }
buildTree(); for (int i = 1; i <= ptr; ++i) { cout << i
<< " --> "; for (int j : tree[i]) cout << j << " "; cout
<< '\n'; } return 0; }

```

4.10 maximum bipartite matching hopcroft

```

/* // do everything 1-based */ class BipartiteMatcher {
private: int n, m; /* // Number of vertices in left and
right sets */ vector<vector<int>> adj; /* // Adjacency
list for the bipartite graph */ vector<int> dist; /* //
Distance array for BFS */ vector<int> matchL, matchR; /*
// matchL[u] is the right vertex matched with u; */ /*
// matchR[v] is the left vertex matched with v */ public
: BipartiteMatcher(int n, int m) : n(n), m(m) { adj.
resize(n + 1); matchL.resize(n + 1, 0); matchR.resize(m
+ 1, 0); dist.resize(n + 1); } void addEdge(int u, int v
) { adj[u].push_back(v); } bool bfs() { queue<int> q;
for (int u = 1; u <= n; u++) { if (matchL[u] == 0) {
dist[u] = 0; q.push(u); } else { dist[u] = INT_MAX; } }
dist[0] = INT_MAX; while (!q.empty()) { int u = q.front
(); q.pop(); if (dist[u] < dist[0]) { for (int v : adj[u]
) { if (dist[matchR[v]] == INT_MAX) { dist[matchR[v]] =
dist[u] + 1; q.push(matchR[v]); } } } } return dist[0]
!= INT_MAX; } bool dfs(int u) { if (u != 0) { for (int v
: adj[u]) { if (dist[matchR[v]] == dist[u] + 1) { if (
dfs(matchR[v])) { matchL[u] = v; matchR[v] = u; return
true; } } } dist[u] = INT_MAX; return false; } return
true; } int hopcroftKarp() { int matching = 0; while (
bfs()) { for (int u = 1; u <= n; u++) { if (matchL[u] ==
0 && dfs(u)) { matching++; } } } return matching; } };

```

4.11 strongly connected component

```

bool vis[N]; vector<int> adj[N], adjr[N]; vector<int>
order, component; /* // tp = 0, finding topo order, //
tp = 1, reverse edge traversal */ void dfs(int u, int tp
= 0) { vis[u] = true; if (tp) component.push_back(u);
auto& ad = (tp ? adjr : adj); for (int v : ad[u]) if (!
vis[v]) dfs(v, tp); if (!tp) order.push_back(u); } int
main() { for (int i = 1; i <= n; i++) { if (!vis[i]) dfs
(i); } memset(vis, 0, sizeof vis); reverse(order.begin()
, order.end()); for (int i : order) { if (!vis[i]) { /*
// one component is found */ dfs(i, 1), component.clear
(); } } }

```

5 String

5.1 KMP

```

int KMP(vector<int> &a, vector<int> &b) { /* // number
of occurrence of a in b */ vector<int> pi(n); for (int i
= 1, j = 0; i < n; i++) { while (j && a[i] != a[j]) j =
pi[j - 1]; if (a[i] == a[j]) j++; pi[i] = j; } int ans =
0; for (int i = 0, j = 0; i < m; i++) { while (j && b[i]
) != a[j]) j = pi[j - 1]; if (a[j] == b[i]) j++; if (j
== n) ans++, j = pi[j - 1]; } return ans; }

```

5.2 Manacher

```

void Manacher() { vector<int> d1(n); /* // d[i] = number
of palindromes taking s[i] as center */ for (int i = 0,
l = 0, r = -1; i < n; i++) { int k = (i > r) ? 1 : min(
d1[l + r - i], r - i + 1); while (0 <= i - k && i + k <
n && s[i - k] == s[i + k]) k++; d1[i] = k--; if (i + k >
r) l = i - k, r = i + k; } vector<int> d2(n); /* // d[i]
= number of palindromes taking s[i-1] and s[i] as
center */ for (int i = 0, l = 0, r = -1; i < n; i++) {
int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s
[i + k]) k++; d2[i] = k--; if (i + k > r) l = i - k - 1,
r = i + k; } }

```

5.3 SuffixArray

```

void inducedSort (const vector<int> &vec, int val_range
, vector<int> &SA, const vector<int> &sl, const vector
<int> &lms_idx) { vector<int> l(val_range, 0), r(
val_range, 0); for (int c : vec) { ++r[c]; if (c + 1 <
val_range) ++l[c + 1]; } partial_sum(l.begin(), l.end(),
l.begin()); partial_sum(r.begin(), r.end(), r.begin());
fill(SA.begin(), SA.end(), -1); for (int i = lms_idx.
size() - 1; i >= 0; --i) SA[--r[vec[lms_idx[i]]]] =
lms_idx[i]; for (int i : SA) if (i > 0 and sl[i - 1]) SA
[l[vec[i - 1]]++] = i - 1; fill(r.begin(), r.end(), 0);
for (int c : vec) ++r[c]; partial_sum(r.begin(), r.end()
, r.begin()); for (int k = SA.size() - 1, i = SA[k]; k;
--k, i = SA[k]) { if (i and !sl[i - 1]) SA[--r[vec[i -
1]]] = i - 1; } } vector<int> suffixArray (const vector
<int> &vec, int val_range) { const int n = vec.size();
vector<int> sl(n), SA(n), lms_idx; for (int i = n - 2;
i >= 0; --i) { sl[i] = vec[i] > vec[i + 1] or (vec[i] ==
vec[i + 1] and sl[i + 1]); if (sl[i] and !sl[i + 1])
lms_idx.emplace_back(i + 1); } reverse(lms_idx.begin(),
lms_idx.end()); inducedSort(vec, val_range, SA, sl,
lms_idx); vector<int> new_lms_idx(lms_idx.size()),

```

```

lms_vec(lms_idx.size()); for (int i = 0, k = 0; i < n; ++i) { if (SA[i] > 0 and !sl[SA[i]] and sl[SA[i] - 1]) new_lms_idx[k++] = SA[i]; } int cur = 0; SA[n - 1] = 0; for (int k = 1; k < new_lms_idx.size(); ++k) { int i = new_lms_idx[k - 1], j = new_lms_idx[k]; if (vec[i] ^ vec[j]) { SA[j] = ++cur; continue; } bool flag = 0; for (int a = i + 1, b = j + 1; ; ++a, ++b) { if (vec[a] ^ vec[b]) { flag = 1; break; } if ((!sl[a] and sl[a - 1]) or (!sl[b] and sl[b - 1])) { flag = !(sl[a] and sl[a - 1] and !sl[b] and sl[b - 1]); break; } } SA[j] = flag ? ++cur : cur; } for (int i = 0; i < lms_idx.size(); ++i) lms_vec[i] = SA[lms_idx[i]]; if (cur + 1 < lms_idx.size()) { auto lms_SA = suffixArray(lms_vec, cur + 1); for (int i = 0; i < lms_idx.size(); ++i) new_lms_idx[i] = lms_idx[lms_SA[i]]; } inducedSort(vec, val_range, SA, sl, new_lms_idx); return SA; } vector<int> getSuffixArray(const string &s, const int LIM = 128) { vector<int> vec(s.size() + 1); copy(begin(s), end(s), begin(vec)); vec.back() = '#'; auto ret = suffixArray(vec, LIM); ret.erase(ret.begin()); return ret; } /* // build RMQ on it to get LCP of any two suffix */ vector<int> getLCParray(const string &s, const vector<int> &SA) { int n = s.size(), k = 0; vector<int> lcp(n), rank(n); for (int i = 0; i < n; ++i) rank[SA[i]] = i; for (int i = 0; i < n; ++i, k ? --k : 0) { if (rank[i] == n - 1) { k = 0; continue; } int j = SA[rank[i] + 1]; while (i + k < n and j + k < n and s[i + k] == s[j + k]) ++k; lcp[rank[i]] = k; } lcp[n - 1] = 0; return lcp; }

```

5.4 Z

```

vector<int> z(string const& s) { int n = size(s); vector<int> z(n); int x = 0, y = 0; for (int i = 1; i < n; ++i) { z[i] = max(0, min(z[i - x], y - i + 1)); while (i + z[i] < n && s[z[i]] == s[i + z[i]]) { x = i, y = i + z[i], z[i]++; } } return z; }

```

5.5 double hashing

Some Primes: 1000000007, 1000000009, 1000000861, 1000099999 (< 2³⁰) 1088888881, 1111211111, 1500000001, 1481481481 (< 2³¹) namespace Hashing { #define ff first #define ss second const PLL M = {1e9+7, 1e9+9}; const LL base = 1259; const int N = 1e6+7; PLL operator+ (const PLL& a, LL x) {return {a.ff + x, a.ss + x};} PLL operator- (const PLL& a, LL x) {return {a.ff - x, a.ss - x};} PLL operator* (const PLL& a, LL x) {return {a.ff * x, a.ss * x};} PLL operator+ (const PLL&

```

a, PLL x) {return {a.ff + x.ff, a.ss + x.ss};} PLL operator- (const PLL& a, PLL x) {return {a.ff - x.ff, a.ss - x.ss};} PLL operator* (const PLL& a, PLL x) {return {a.ff * x.ff, a.ss * x.ss};} PLL operator% (const PLL& a, PLL m) {return {a.ff % m.ff, a.ss % m.ss};} ostream& operator<<(ostream& os, PLL hash) { return os<<("<hash.ff<<", "<hash.ss<<"); } PLL pb[N]; /* ///powers of base mod M ///Call pre before everything */ void hashPre() { pb[0] = {1,1}; for (int i=1; i<N; i++) pb[i] = (pb[i-1] * base)%M; } /* ///Calculates hashes of all prefixes of s including empty prefix */ vector<PLL> hashList(string s) { int n = s.size(); vector<PLL> ans(n+1); ans[0] = {0,0}; for (int i=1; i<=n; i++) ans[i] = (ans[i-1] * base + s[i-1])%M; return ans; } /* ///Calculates hash of substring s[l..r] (1 indexed) */ PLL substringHash(const vector<PLL> &hashlist, int l, int r) { return (hashlist[r]+(M-hashlist[l-1])*pb[r-l+1])%M; } /* ///Calculates Hash of a string */ PLL Hash (string s) { PLL ans = {0,0}; for (int i=0; i<s.size(); i++) ans =(ans*base + s[i])%M; return ans; } /* ///appends c to string */ PLL append(PLL cur, char c) { return (cur*base + c)%M; } /* ///prepends c to string with size k */ PLL prepend(PLL cur, int k, char c) { return (pb[k]*c + cur)%M; } /* ///replaces the i-th (0-indexed) character from right from a to b; */ PLL replace(PLL cur, int i, char a, char b) { return (cur + pb[i] * (M+b-a))%M; } /* ///Erases c from front of the string with size len */ PLL pop_front(PLL hash, int len, char c) { return (hash + pb[len-1]*(M-c))%M; } /* ///concatenates two strings where length of the right is k */ PLL concat(PLL left, PLL right, int k) { return (left*pb[k] + right)%M; } PLL power (const PLL& a, LL p) { if (p==0) return {1,1}; PLL ans = power(a, p/2); ans = (ans * ans)%M; if (p%2) ans = (ans*a)%M; return ans; } PLL inverse(PLL a) { if (M.ss == 1) return power(a, M.ff-2); return power(a, (M.ff-1)*(M.ss-1)-1); } /* ///Erases c from the back of the string */ PLL invb = inverse({base, base}); PLL pop_back(PLL hash, char c) { return ((hash-c*M)*invb)%M; } /* ///Calculates hash of string with size len repeated cnt times ///This is O(log n). For O(1), pre-calculate inverses */ PLL repeat(PLL hash, int len, LL cnt) { PLL mul = ((pb[len*cnt]-1*M) * inverse(pb[len]-1*M))%M; PLL ans = (hash*mul); if (pb[len].ff == 1) ans.ff = hash.ff*cnt; if (pb[len].ss == 1) ans.ss = hash.ss*cnt; return ans%M; } } using namespace Hashing; vector<PLL> forwardHash, backwardHash; int n; bool check(int l,

```

```

int r) { return substringHash(forwardHash, l, r) == substringHash(backwardHash, n+1-r, n+1-l); }

```

6 DP

6.1 CHT

```

struct Line { mutable LL m, c, p; bool operator<(const Line& o) const { return m < o.m; } bool operator<(LL x) const { return p < x; } }; /* // this calculates maximum value of m * x + c over all lines // to get minimum value use m = -m , c = -c , query(x) = -query(x) */ struct LineContainer : multiset<Line, less<>> { /* // ( for doubles, use inf = 1/.0, div(a,b) = a/b) */ static const LL inf = LLONG_MAX; LL div(LL a, LL b) { /* // floored division */ return a / b - ((a ^ b) < 0 && a % b); } bool isect(iterator x, iterator y) { if (y == end()) return x->p = inf, 0; if (x->m == y->m) x->p = x->c > y->c ? inf : -inf; else x->p = div(y->c - x->c, x->m - y->m); return x->p >= y->p; } void add(LL m, LL c) { auto z = insert({m, c, 0}), y = z++, x = y; while (isect(y, z)) z = erase(z); if (x != begin() && isect(--x, y)) isect(x, y = erase(y)); while ((y = x) != begin() && (--x)->p >= y->p) isect(x, erase(y)); } LL query(LL x) { assert(!empty()); auto l = *lower_bound(x); return l.m * x + l.c; } };

```

6.2 CatalanDp

```

const int nmax = 1e4 + 1; const int mod = 1000000007; int catalan[nmax + 1]; /* // comb formula: ((2n)Cn)-((2n)C(n-1)) = (1/(n+1))*((2n)Cn) */ void genCatalan(int n) { catalan[0] = catalan[1] = 1; for (int i = 2; i <= n; i++) { catalan[i] = 0; for (int j = 0; j < i; j++) { catalan[i] += (catalan[j] * catalan[i - j - 1]) % mod; if (catalan[i] >= mod) { catalan[i] -= mod; } } } }

```

6.3 DearrangementDP

```

const int nmax = 2e5 + 1; int drng[nmax + 1]; void gen_drng(int n) { drng[2] = 1; for (int i = 3; i <= n; i++) { drng[i] = ((i - 1ll) * ((drng[i - 2] + drng[i - 1]) % mod)) % mod; } }

```

6.4 Li Chao Tree

```

const ll inf = 2e18; struct Line { ll m, c; ll eval(ll x) { return m * x + c; } }; struct node { Line line; node * left = nullptr; node * right = nullptr; node(Line line) : line(line) {} void add_segment(Line nw, int l, int r, int L, int R) { if (l > r || r < L || l > R) return;

```



```

int m = (l + 1 == r ? l : (l + r) / 2); if (l >= L and r
<= R) { bool lef = nw.eval(l) < line.eval(l); bool mid
= nw.eval(m) < line.eval(m); if (mid) swap(line, nw); if
(l == r) return; if (lef != mid) { if (left == nullptr)
left = new node(nw); else left -> add_segment(nw, l, m,
L, R); } else { if (right == nullptr) right = new node(
nw); else right -> add_segment(nw, m + 1, r, L, R); }
return; } if (max(l, L) <= min(m, R)) { if (left ==
nullptr) left = new node({0, inf}); left -> add_segment(
nw, l, m, L, R); } if (max(m + 1, L) <= min(r, R)) { if
(right == nullptr) right = new node({0, inf}); right ->
add_segment(nw, m + 1, r, L, R); } } ll query_segment(
ll x, int l, int r, int L, int R) { if (l > r || r < L
|| l > R) return inf; int m = (l + 1 == r ? l : (l + r)
/ 2); if (l >= L and r <= R) { ll ans = line.eval(x); if
(l < r) { if (x <= m && left != nullptr) ans = min(ans,
left -> query_segment(x, l, m, L, R)); if (x > m &&
right != nullptr) ans = min(ans, right -> query_segment(
x, m + 1, r, L, R)); } return ans; } ll ans = inf; if (
max(l, L) <= min(m, R)) { if (left == nullptr) left =
new node({0, inf}); ans = min(ans, left -> query_segment
(x, l, m, L, R)); } if (max(m + 1, L) <= min(r, R)) { if
(right == nullptr) right = new node({0, inf}); ans =
min(ans, right -> query_segment(x, m + 1, r, L, R)); }
return ans; } }; struct LiChaoTree { int L, R; node*
root; LiChaoTree() : L(numeric_limits<int>::min() / 2),
R(numeric_limits<int>::max() / 2), root(nullptr) {}
LiChaoTree(int L, int R) : L(L), R(R) { root = new node
({0, inf}); } void add_line(Line line) { root ->
add_segment(line, L, R, L, R); } /* y = mx + b: x in [l,
r] */ void add_segment(Line line, int l, int r) { root
-> add_segment(line, L, R, l, r); } ll query(ll x) {
return root -> query_segment(x, L, R, L, R); } ll
query_segment(ll x, int l, int r) { return root ->
query_segment(x, l, r, L, R); } }; int32_t main() {
ios_base::sync_with_stdio(0); cin.tie(0); LiChaoTree t =
LiChaoTree((int)-1e9, (int) 1e9); int n, q; cin >> n >>
q; for (int i = 0; i < n; i++) { ll l, r, a, b; cin >>
l >> r >> a >> b; r--; t.add_segment({a, b}, l, r); }
while (q--) { int ty; cin >> ty; if (ty == 0) { ll l, r,
a, b; cin >> l >> r >> a >> b; r--; t.add_segment({a, b
}, l, r); } else { ll x; cin >> x; ll ans = t.query(x);
if (ans >= inf) cout << "INFINITY\n"; else cout << ans
<< '\n'; } } }

```

6.5 SOS

/* Given a fixed array A of 2^N integers, we need to calculate for all x function $F(x) = \text{Sum of all } A[i] \text{ such that } x \& i = i$, i.e., i is a subset of x. */ /* // iterative version */ for(int mask = 0; mask < (1<<N); ++mask){ dp[mask][1] = A[mask]; /* //handle base case separately (leaf states) */ for(int i = 0; i < N; ++i){ if(mask & (1<<i)) dp[mask][i] = dp[mask][i-1] + dp[mask ^ (1<<i)][i-1]; else dp[mask][i] = dp[mask][i-1]; } F[mask] = dp[mask][N-1]; } /* //memory optimized, super easy to code. */ for(int i = 0; i < (1<<N); ++i) F[i] = A[i]; for(int i = 0; i < N; ++i) for(int mask = 0; mask < (1<<N); ++mask){ if(mask & (1<<i)) F[mask] += F[mask ^ (1<<i)]; }

6.6 Grundy

/* single pile game-> greedy or game dp multiple pile game and disjunctive(before playing, choose 1 pile) -> NIM game else-> Grundy(converts n any game piles to n NIM piles) Grundy(x)->the smallest nonreachable Grundy value there are n pile of games and k type of moves. if XOR(Grundy(games)) == 0: losing state else winning state */ vector<int> moves, dp; int mex(vector<int> &a) { set<int> b(a.begin(), a.end()); for (int i = 0; ; ++i) if (!b.count(i)) return i; } int Grundy(int x) { if (dp[x] != -1) return dp[x]; vector<int> reachable; for (auto m : moves) { if (x - m < 0) continue; int val = Grundy(x - m); reachable.push_back(val); } return dp[x] = mex(reachable); }

7 Geometry

7.1 2D Shohag

```

const int N = 3e5 + 9; const double inf = 1e100; const
double eps = 1e-9; const double PI = acos((double)-1.0);
int sign(double x) { return (x > eps) - (x < -eps); }
struct PT { double x, y; PT() { x = 0, y = 0; } PT(
double x, double y) : x(x), y(y) {} PT(const PT &p) : x(
p.x), y(p.y) {} PT operator + (const PT &a) const {
return PT(x + a.x, y + a.y); } PT operator - (const PT &a)
const { return PT(x - a.x, y - a.y); } PT operator *
(const double a) const { return PT(x * a, y * a); }
friend PT operator * (const double &a, const PT &b) {
return PT(a * b.x, a * b.y); } PT operator / (const
double a) const { return PT(x / a, y / a); } bool
operator == (PT a) const { return sign(a.x - x) == 0 &&
sign(a.y - y) == 0; } bool operator != (PT a) const {
return !(*this == a); } bool operator < (PT a) const {

```

```

return sign(a.x - x) == 0 ? y < a.y : x < a.x; } bool
operator > (PT a) const { return sign(a.x - x) == 0 ? y
> a.y : x > a.x; } double norm() { return sqrt(x * x + y
* y); } double norm2() { return x * x + y * y; } PT
perp() { return PT(-y, x); } double arg() { return atan2
(y, x); } PT truncate(double r) { /* returns a vector
with norm r and having same direction */ double k = norm
(); if (!sign(k)) return *this; r /= k; return PT(x * r,
y * r); } }; istream &operator >> (istream &in, PT &p)
{ return in >> p.x >> p.y; } ostream &operator << (
ostream &out, PT &p) { return out << "(" << p.x << ", "
<< p.y << ")"; } inline double dot(PT a, PT b) { return
a.x * b.x + a.y * b.y; } inline double dist2(PT a, PT b)
{ return dot(a - b, a - b); } inline double dist(PT a,
PT b) { return sqrt(dot(a - b, a - b)); } inline double
cross(PT a, PT b) { return a.x * b.y - a.y * b.x; }
inline double cross2(PT a, PT b, PT c) { return cross(b
- a, c - a); } inline int orientation(PT a, PT b, PT c)
{ return sign(cross(b - a, c - a)); } PT perp(PT a) {
return PT(-a.y, a.x); } PT rotatecw90(PT a) { return PT
(-a.y, a.x); } PT rotateccw90(PT a) { return PT(a.y, -a.x
); } PT rotateccw(PT a, double t) { return PT(a.x * cos(
t) - a.y * sin(t), a.x * sin(t) + a.y * cos(t)); } PT
rotatecw(PT a, double t) { return PT(a.x * cos(t) + a.y
* sin(t), -a.x * sin(t) + a.y * cos(t)); } double SQ(
double x) { return x * x; } double rad_to_deg(double r)
{ return (r * 180.0 / PI); } double deg_to_rad(double d)
{ return (d * PI / 180.0); } double get_angle(PT a, PT
b) { double costheta = dot(a, b) / a.norm() / b.norm();
return acos(max((double)-1.0, min((double)1.0, costheta)
)); } bool is_point_in_angle(PT b, PT a, PT c, PT p) {
/* does point p lie in angle <bac */ assert(orientation(
a, b, c) != 0); if (orientation(a, c, b) < 0) swap(b, c)
; return orientation(a, c, p) >= 0 && orientation(a, b,
p) <= 0; } bool half(PT p) { return p.y > 0.0 || (p.y ==
0.0 && p.x < 0.0); } void polar_sort(vector<PT> &v) {
/* sort points in counterclockwise */ sort(v.begin(), v.
end(), [](PT a, PT b) { return make_tuple(half(a), 0.0, a
.norm2()) < make_tuple(half(b), cross(a, b), b.norm2());
}); } void polar_sort(vector<PT> &v, PT o) { /* sort
points in counterclockwise with respect to point o */
sort(v.begin(), v.end(), [&](PT a, PT b) { return
make_tuple(half(a - o), 0.0, (a - o).norm2()) <
make_tuple(half(b - o), cross(a - o, b - o), (b - o).
norm2()); }); }

```



```

struct line { PT a, b; /* goes through points a and b */
  PT v; double c; /* line form: direction vec [cross] (x,
  y) = c */ line() {} /* direction vector v and offset c
  */ line(PT v, double c) : v(v), c(c) { auto p =
  get_points(); a = p.first; b = p.second; } /* equation
  ax + by + c = 0 */ line(double _a, double _b, double _c)
  : v({_b, -_a}), c(-_c) { auto p = get_points(); a = p.
  first; b = p.second; } /* goes through points p and q */
  line(PT p, PT q) : v(q - p), c(cross(v, p)), a(p), b(q)
  {} pair<PT, PT> get_points() { /* extract any two
  points from this line */ PT p, q; double a = -v.y, b = v
  .x; /* ax + by = c */ if (sign(a) == 0) { p = PT(0, c /
  b); q = PT(1, c / b); } else if (sign(b) == 0) { p = PT(
  c / a, 0); q = PT(c / a, 1); } else { p = PT(0, c / b);
  q = PT(1, (c - a) / b); } return {p, q}; } /* ax + by +
  c = 0 */ array<double, 3> get_abc() { double a = -v.y, b
  = v.x; return {a, b, -c}; } /* 1 if on the left, -1 if
  on the right, 0 if on the line */ int side(PT p) {
  return sign(cross(v, p) - c); } /* line that is
  perpendicular to this and goes through point p */ line
  perpendicular_through(PT p) { return {p, p + perp(v)}; }
  /* translate the line by vector t i.e. shifting it by
  vector t */ line translate(PT t) { return {v, c + cross(
  v, t)}; } /* compare two points by their orthogonal
  projection on this line */ /* a projection point comes
  before another if it comes first according to vector v
  */ bool cmp_by_projection(PT p, PT q) { return dot(v, p)
  < dot(v, q); } line shift_left(double d) { PT z = v.
  perp().truncate(d); return line(a + z, b + z); } }; /*
  find a point from a through b with distance d */ PT
  point_along_line(PT a, PT b, double d) { assert(a != b);
  return a + (((b - a) / (b - a).norm()) * d); } /*
  projection point c onto line through a and b assuming a
  != b */ PT project_from_point_to_line(PT a, PT b, PT c)
  { return a + (b - a) * dot(c - a, b - a) / (b - a).norm2
  (); } /* reflection point c onto line through a and b
  assuming a != b */ PT reflection_from_point_to_line(PT a
  , PT b, PT c) { PT p = project_from_point_to_line(a, b, c)
  ; return p + p - c; } /* minimum distance from point c
  to line through a and b */ double
  dist_from_point_to_line(PT a, PT b, PT c) { return fabs(
  cross(b - a, c - a) / (b - a).norm()); } /* returns true
  if point p is on line segment ab */ bool
  is_point_on_seg(PT a, PT b, PT p) { if (fabs(cross(p - b
  , a - b)) < eps) { if (p.x < min(a.x, b.x) - eps || p.x
  > max(a.x, b.x) + eps) return false; if (p.y < min(a.y,

```

```

b.y) - eps || p.y > max(a.y, b.y) + eps) return false;
return true; } return false; } /* minimum distance point
from point c to segment ab that lies on segment ab */
PT project_from_point_to_seg(PT a, PT b, PT c) { double
r = dist2(a, b); if (sign(r) == 0) return a; r = dot(c -
a, b - a) / r; if (r < 0) return a; if (r > 1) return b
; return a + (b - a) * r; } /* minimum distance from
point c to segment ab */ double dist_from_point_to_seg(
PT a, PT b, PT c) { return dist(c,
project_from_point_to_seg(a, b, c)); } /* 0 if not
parallel, 1 if parallel, 2 if collinear */ int
is_parallel(PT a, PT b, PT c, PT d) { double k = fabs(
cross(b - a, d - c)); if (k < eps){ if (fabs(cross(a - b
, a - c)) < eps && fabs(cross(c - d, c - a)) < eps)
return 2; else return 1; } else return 0; } /* check if
two lines are same */ bool are_lines_same(PT a, PT b, PT
c, PT d) { if (fabs(cross(a - c, c - d)) < eps && fabs(
cross(b - c, c - d)) < eps) return true; return false; }
/* bisector vector of <abc */ PT angle_bisector(PT &a,
PT &b, PT &c){ PT p = a - b, q = c - b; return p + q *
sqrt(dot(p, p) / dot(q, q)); } /* 1 if point is ccw to
the line, 2 if point is cw to the line, 3 if point is on
the line */ int point_line_relation(PT a, PT b, PT p) {
int c = sign(cross(p - a, b - a)); if (c < 0) return 1;
if (c > 0) return 2; return 3; } /* intersection point
between ab and cd assuming unique intersection exists */
bool line_line_intersection(PT a, PT b, PT c, PT d, PT
&ans) { double a1 = a.y - b.y, b1 = b.x - a.x, c1 =
cross(a, b); double a2 = c.y - d.y, b2 = d.x - c.x, c2 =
cross(c, d); double det = a1 * b2 - a2 * b1; if (det ==
0) return 0; ans = PT((b1 * c2 - b2 * c1) / det, (c1 *
a2 - a1 * c2) / det); return 1; } /* intersection point
between segment ab and segment cd assuming unique
intersection exists */ bool seg_seg_intersection(PT a,
PT b, PT c, PT d, PT &ans) { double oa = cross2(c, d, a)
, ob = cross2(c, d, b); double oc = cross2(a, b, c), od
= cross2(a, b, d); if (oa * ob < 0 && oc * od < 0){ ans
= (a * ob - b * oa) / (ob - oa); return 1; } else return
0; } /* intersection point between segment ab and
segment cd assuming unique intersection may not exists
*/ /* se.size()==0 means no intersection */ /* se.size()
==1 means one intersection */ /* se.size()==2 means
range intersection */ set<PT>
seg_seg_intersection_inside(PT a, PT b, PT c, PT d) { PT
ans; if (seg_seg_intersection(a, b, c, d, ans)) return
{ans}; set<PT> se; if (is_point_on_seg(c, d, a)) se.

```

```

insert(a); if (is_point_on_seg(c, d, b)) se.insert(b);
if (is_point_on_seg(a, b, c)) se.insert(c); if (
is_point_on_seg(a, b, d)) se.insert(d); return se; } /*
intersection between segment ab and line cd */ /* 0 if
do not intersect, 1 if proper intersect, 2 if segment
intersect */ int seg_line_relation(PT a, PT b, PT c, PT
d) { double p = cross2(c, d, a); double q = cross2(c, d,
b); if (sign(p) == 0 && sign(q) == 0) return 2; else if
(p * q < 0) return 1; else return 0; } /* intersection
between segment ab and line cd assuming unique
intersection exists */ bool seg_line_intersection(PT a,
PT b, PT c, PT d, PT &ans) { bool k = seg_line_relation(
a, b, c, d); assert(k != 2); if (k)
line_line_intersection(a, b, c, d, ans); return k; } /*
minimum distance from segment ab to segment cd */ double
dist_from_seg_to_seg(PT a, PT b, PT c, PT d) { PT dummy
; if (seg_seg_intersection(a, b, c, d, dummy)) return
0.0; else return min({dist_from_point_to_seg(a, b, c),
dist_from_point_to_seg(a, b, d), dist_from_point_to_seg(
c, d, a), dist_from_point_to_seg(c, d, b)}); } /*
minimum distance from point c to ray (starting point a
and direction vector b) */ double dist_from_point_to_ray
(PT a, PT b, PT c) { b = a + b; double r = dot(c - a, b
- a); if (r < 0.0) return dist(c, a); return
dist_from_point_to_line(a, b, c); } /* starting point as
and direction vector ad */ bool ray_ray_intersection(PT
as, PT ad, PT bs, PT bd) { double dx = bs.x - as.x, dy
= bs.y - as.y; double det = bd.x * ad.y - bd.y * ad.x;
if (fabs(det) < eps) return 0; double u = (dy * bd.x -
dx * bd.y) / det; double v = (dy * ad.x - dx * ad.y) /
det; if (sign(u) >= 0 && sign(v) >= 0) return 1; else
return 0; } double ray_ray_distance(PT as, PT ad, PT bs,
PT bd) { if (ray_ray_intersection(as, ad, bs, bd))
return 0.0; double ans = dist_from_point_to_ray(as, ad,
bs); ans = min(ans, dist_from_point_to_ray(bs, bd, as));
return ans; }
struct circle { PT p; double r; circle() {} circle(PT _p
, double _r): p(_p), r(_r) {}; /* center (x, y) and
radius r */ circle(double x, double y, double _r): p(PT(
x, y)), r(_r) {}; /* circumcircle of a triangle */ /*
the three points must be unique */ circle(PT a, PT b, PT
c) { b = (a + b) * 0.5; c = (a + c) * 0.5;
line_line_intersection(b, b + rotatecw90(a - b), c, c +
rotatecw90(a - c), p); r = dist(a, p); } /* inscribed
circle of a triangle */ /* pass a bool just to
differentiate from circumcircle */ circle(PT a, PT b, PT

```

```

c, bool t) { line u, v; double m = atan2(b.y - a.y, b.x - a.x), n = atan2(c.y - a.y, c.x - a.x); u.a = a; u.b = u.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0))); v.a = b; m = atan2(a.y - b.y, a.x - b.x), n = atan2(c.y - b.y, c.x - b.x); v.b = v.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0))); line_line_intersection(u.a, u.b, v.a, v.b, p); r = dist_from_point_to_seg(a, b, p); } bool operator == (circle v) { return p == v.p && sign(r - v.r) == 0; } double area() { return PI * r * r; } double circumference() { return 2.0 * PI * r; } }; /* 0 if outside, 1 if on circumference, 2 if inside circle */ int circle_point_relation(PT p, double r, PT b) { double d = dist(p, b); if (sign(d - r) < 0) return 2; if (sign(d - r) == 0) return 1; return 0; } /* 0 if outside, 1 if on circumference, 2 if inside circle */ int circle_line_relation(PT p, double r, PT a, PT b) { double d = dist_from_point_to_line(a, b, p); if (sign(d - r) < 0) return 2; if (sign(d - r) == 0) return 1; return 0; } /* compute intersection of line through points a and b with */ /* circle centered at c with radius r > 0 */ vector<PT> circle_line_intersection(PT c, double r, PT a, PT b) { vector<PT> ret; b = b - a; a = a - c; double A = dot(b, b), B = dot(a, b); double C = dot(a, a) - r * r, D = B * B - A * C; if (D < -eps) return ret; ret.push_back(c + a + b * (-B + sqrt(D + eps)) / A); if (D > eps) ret.push_back(c + a + b * (-B - sqrt(D)) / A); return ret; } /* 5 - outside and do not intersect */ /* 4 - intersect outside in one point */ /* 3 - intersect in 2 points */ /* 2 - intersect inside in one point */ /* 1 - inside and do not intersect */ int circle_circle_relation(PT a, double r, PT b, double R) { double d = dist(a, b); if (sign(d - r - R) > 0) return 5; if (sign(d - r - R) == 0) return 4; double l = fabs(r - R); if (sign(d - r - R) < 0 && sign(d - l) > 0) return 3; if (sign(d - l) == 0) return 2; if (sign(d - l) < 0) return 1; assert(0); return -1; } vector<PT> circle_circle_intersection(PT a, double r, PT b, double R) { if (a == b && sign(r - R) == 0) return {PT(1e18, 1e18)}; vector<PT> ret; double d = sqrt(dist2(a, b)); if (d > r + R || d + min(r, R) < max(r, R)) return ret; double x = (d * d - R * R + r * r) / (2 * d); double y = sqrt(r * r - x * x); PT v = (b - a) / d; ret.push_back(a + v * x + rotateccw90(v) * y); if (y > 0) ret.push_back(a + v * x - rotateccw90(v) * y); return ret; } /* returns two circle c1, c2 through points a, b and of radius r */ /* 0 if there is no such circle, 1 if one

```

```

circle, 2 if two circle */ int get_circle(PT a, PT b, double r, circle &c1, circle &c2) { vector<PT> v = circle_circle_intersection(a, r, b, r); int t = v.size(); if (!t) return 0; c1.p = v[0], c1.r = r; if (t == 2) c2.p = v[1], c2.r = r; return t; } /* returns two circle c1, c2 which is tangent to line u, goes through */ /* point q and has radius r1; 0 for no circle, 1 if c1 = c2, 2 if c1 != c2 */ int get_circle(line u, PT q, double r1, circle &c1, circle &c2) { double d = dist_from_point_to_line(u.a, u.b, q); if (sign(d - r1 * 2.0) > 0) return 0; if (sign(d) == 0) { cout << u.v.x << ' ' << u.v.y << '\n'; c1.p = q + rotateccw90(u.v).truncate(r1); c2.p = q + rotatecw90(u.v).truncate(r1); c1.r = c2.r = r1; return 2; } line u1 = line(u.a + rotateccw90(u.v).truncate(r1), u.b + rotateccw90(u.v).truncate(r1)); line u2 = line(u.a + rotatecw90(u.v).truncate(r1), u.b + rotatecw90(u.v).truncate(r1)); circle cc = circle(q, r1); PT p1, p2; vector<PT> v; v = circle_line_intersection(q, r1, u1.a, u1.b); if (!v.size()) v = circle_line_intersection(q, r1, u2.a, u2.b); v.push_back(v[0]); p1 = v[0], p2 = v[1]; c1 = circle(p1, r1); if (p1 == p2) { c2 = c1; return 1; } c2 = circle(p2, r1); return 2; } /* returns the circle such that for all points w on the circumference of the circle */ /* dist(w, a) : dist(w, b) = rp : rq */ /* rp != rq */ /* https://en.wikipedia.org/wiki/Circles_of_Apollonius */ circle get_apollonius_circle(PT p, PT q, double rp, double rq) { rq == rq; rp == rp; double a = rq - rp; assert(sign(a)); double g = rq * p.x - rp * q.x; g /= a; double h = rq * p.y - rp * q.y; h /= a; double c = rq * p.x * p.x - rp * q.x * q.x + rq * p.y * p.y - rp * q.y * q.y; c /= a; PT o(g, h); double r = g * g + h * h - c; r = sqrt(r); return circle(o, r); } /* returns area of intersection between two circles */ double circle_circle_area(PT a, double r1, PT b, double r2) { double d = (a - b).norm(); if (r1 + r2 < d + eps) return 0; if (r1 + d < r2 + eps) return PI * r1 * r1; if (r2 + d < r1 + eps) return PI * r2 * r2; double theta_1 = acos((r1 * r1 + d * d - r2 * r2) / (2 * r1 * d)), theta_2 = acos((r2 * r2 + d * d - r1 * r1) / (2 * r2 * d)); return r1 * r1 * (theta_1 - sin(2 * theta_1) / 2.) + r2 * r2 * (theta_2 - sin(2 * theta_2) / 2.); } /* tangent lines from point q to the circle */ int tangent_lines_from_point(PT p, double r, PT q, line &u, line &v) { int x = sign(dist2(p, q) - r * r); if (x < 0) return 0; /* point in circle */ if (x == 0) { /* point on circle */ u = line(q

```

```

, q + rotateccw90(q - p)); v = u; return 1; } double d = dist(p, q); double l = r * r / d; double h = sqrt(r * r - l * l); u = line(q, p + ((q - p).truncate(l) + (rotateccw90(q - p).truncate(h))))); v = line(q, p + ((q - p).truncate(l) + (rotatecw90(q - p).truncate(h))))); return 2; } /* returns outer tangents line of two circles */ /* if inner == 1 it returns inner tangent lines */ int tangents_lines_from_circle(PT c1, double r1, PT c2, double r2, bool inner, line &u, line &v) { if (inner) r2 = -r2; PT d = c2 - c1; double dr = r1 - r2, d2 = d.norm2(), h2 = d2 - dr * dr; if (d2 == 0 || h2 < 0) { assert(h2 != 0); return 0; } vector<pair<PT, PT>>out; for (int tmp: {-1, 1}) { PT v = (d * dr + rotateccw90(d) * sqrt(h2) * tmp) / d2; out.push_back({c1 + v * r1, c2 + v * r2}); } u = line(out[0].first, out[0].second); if (out.size() == 2) v = line(out[1].first, out[1].second); return 1 + (h2 > 0); } /* O(n^2 log n) */ /* https://vjudge.net/problem/UVA-12056 */ struct CircleUnion { int n; double x[2020], y[2020], r[2020]; int covered[2020]; vector<pair<double, double>> seg, cover; double arc, pol; inline int sign(double x) {return x < -eps ? -1 : x > eps; } inline int sign(double x, double y) {return sign(x - y); } inline double SQ(const double x) {return x * x; } inline double dist(double x1, double y1, double x2, double y2) {return sqrt(SQ(x1 - x2) + SQ(y1 - y2)); } inline double angle(double A, double B, double C) { double val = (SQ(A) + SQ(B) - SQ(C)) / (2 * A * B); if (val < -1) val = -1; if (val > +1) val = +1; return acos(val); } CircleUnion() { n = 0; seg.clear(), cover.clear(); } void init() { n = 0; seg.clear(), cover.clear(); arc = pol = 0; } void add(double xx, double yy, double rr) { x[n] = xx, y[n] = yy, r[n] = rr, covered[n] = 0, n++; } void getarea(int i, double lef, double rig) { arc += 0.5 * r[i] * r[i] * (rig - lef - sin(rig - lef)); double x1 = x[i] + r[i] * cos(lef), y1 = y[i] + r[i] * sin(lef); double x2 = x[i] + r[i] * cos(rig), y2 = y[i] + r[i] * sin(rig); pol += x1 * y2 - x2 * y1; } double solve() { for (int i = 0; i < n; i++) { for (int j = 0; j < i; j++) { if (!sign(x[i] - x[j]) && !sign(y[i] - y[j]) && !sign(r[i] - r[j])) { r[i] = 0.0; break; } } } for (int i = 0; i < n; i++) { for (int j = 0; j < n; j++) { if (i != j && sign(r[j] - r[i]) >= 0 && sign(dist(x[i], y[i], x[j], y[j]) - (r[j] - r[i])) <= 0) { covered[i] = 1; break; } } } for (int i = 0; i < n; i++) { if (sign(r[i]) && !covered[i]) { seg.clear(); for (int j = 0; j < n; j++) { if (i != j) { double d =

```

```

dist(x[i], y[i], x[j], y[j]); if (sign(d - (r[j] + r[i]))
) >= 0 || sign(d - abs(r[j] - r[i])) <= 0) { continue; }
double alpha = atan2(y[j] - y[i], x[j] - x[i]); double
beta = angle(r[i], d, r[j]); pair<double, double> tmp(
alpha - beta, alpha + beta); if (sign(tmp.first) <= 0 &&
sign(tmp.second) <= 0) { seg.push_back(pair<double,
double>(2 * PI + tmp.first, 2 * PI + tmp.second)); }
else if (sign(tmp.first) < 0) { seg.push_back(pair<
double, double>(2 * PI + tmp.first, 2 * PI)); seg.
push_back(pair<double, double>(0, tmp.second)); } else {
seg.push_back(tmp); } } sort(seg.begin(), seg.end());
double rig = 0; for (vector<pair<double, double>>::
iterator iter = seg.begin(); iter != seg.end(); iter++)
{ if (sign(rig - iter->first) >= 0) { rig = max(rig,
iter->second); } else { getarea(i, rig, iter->first);
rig = iter->second; } } if (!sign(rig)) { arc += r[i] *
r[i] * PI; } else { getarea(i, rig, 2 * PI); } } }
return pol / 2.0 + arc; } } CU; double area_of_triangle(
PT a, PT b, PT c) { return fabs(cross(b - a, c - a) *
0.5); } /* -1 if strictly inside, 0 if on the polygon, 1
if strictly outside */ int is_point_in_triangle(PT a,
PT b, PT c, PT p) { if (sign(cross(b - a, c - a)) < 0)
swap(b, c); int c1 = sign(cross(b - a, p - a)); int c2 =
sign(cross(c - b, p - b)); int c3 = sign(cross(a - c, p -
c)); if (c1 < 0 || c2 < 0 || c3 < 0) return 1; if (c1 + c2 +
c3 != 3) return 0; return -1; } double perimeter(vector
<PT> &p) { double ans=0; int n = p.size(); for (int i =
0; i < n; i++) ans += dist(p[i], p[(i + 1) % n]); return
ans; } double area(vector<PT> &p) { double ans = 0; int
n = p.size(); for (int i = 0; i < n; i++) ans += cross(
p[i], p[(i + 1) % n]); return fabs(ans) * 0.5; } /*
centroid of a (possibly non-convex) polygon, */ /*
assuming that the coordinates are listed in a clockwise
or */ /* counterclockwise fashion. Note that the
centroid is often known as */ /* the "center of gravity"
or "center of mass". */ PT centroid(vector<PT> &p) {
int n = p.size(); PT c(0, 0); double sum = 0; for (int i
= 0; i < n; i++) sum += cross(p[i], p[(i + 1) % n]);
double scale = 3.0 * sum; for (int i = 0; i < n; i++) {
int j = (i + 1) % n; c = c + (p[i] + p[j]) * cross(p[i],
p[j]); } return c / scale; } /* 0 if cw, 1 if ccw */
bool get_direction(vector<PT> &p) { double ans = 0; int
n = p.size(); for (int i = 0; i < n; i++) ans += cross(
p[i], p[(i + 1) % n]); if (sign(ans) > 0) return 1;
return 0; } /* it returns a point such that the sum of
distances */ /* from that point to all points in p is

```

```

minimum */ /* O(n log^2 MX) */ PT geometric_median(
vector<PT> p) { auto tot_dist = [&](PT z) { double res =
0; for (int i = 0; i < p.size(); i++) res += dist(p[i],
z); return res; }; auto findY = [&](double x) { double
yl = -1e5, yr = 1e5; for (int i = 0; i < 60; i++) {
double ym1 = yl + (yr - yl) / 3; double ym2 = yr - (yr -
yl) / 3; double d1 = tot_dist(PT(x, ym1)); double d2 =
tot_dist(PT(x, ym2)); if (d1 < d2) yr = ym2; else yl =
ym1; } return pair<double, double>(yl, tot_dist(PT(x,
yl))); }; double xl = -1e5, xr = 1e5; for (int i = 0; i
< 60; i++) { double xm1 = xl + (xr - xl) / 3; double xm2
= xr - (xr - xl) / 3; double y1, d1, y2, d2; auto z =
findY(xm1); y1 = z.first; d1 = z.second; z = findY(xm2);
y2 = z.first; d2 = z.second; if (d1 < d2) xr = xm2;
else xl = xm1; } return {xl, findY(xl).first }; }
vector<PT> convex_hull(vector<PT> &p) { if (p.size() <=
1) return p; vector<PT> v = p; sort(v.begin(), v.end());
vector<PT> up, dn; for (auto& p : v) { while (up.size()
> 1 && orientation(up[up.size() - 2], up.back(), p) >=
0) { up.pop_back(); } while (dn.size() > 1 &&
orientation(dn[dn.size() - 2], dn.back(), p) <= 0) { dn.
pop_back(); } up.push_back(p); dn.push_back(p); } v = dn
; if (v.size() > 1) v.pop_back(); reverse(up.begin(), up
.end()); up.pop_back(); for (auto& p : up) { v.push_back
(p); } if (v.size() == 2 && v[0] == v[1]) v.pop_back();
return v; } /* checks if convex or not */ bool is_convex
(vector<PT> &p) { bool s[3]; s[0] = s[1] = s[2] = 0; int
n = p.size(); for (int i = 0; i < n; i++) { int j = (i
+ 1) % n; int k = (j + 1) % n; s[sign(cross(p[j] - p[i],
p[k] - p[i])) + 1] = 1; if (s[0] && s[2]) return 0; }
return 1; } /* -1 if strictly inside, 0 if on the
polygon, 1 if strictly outside */ /* it must be strictly
convex, otherwise make it strictly convex first */ int
is_point_in_convex(vector<PT> &p, const PT& x) { /* O(
log n) */ int n = p.size(); assert(n >= 3); int a =
orientation(p[0], p[1], x), b = orientation(p[0], p[n -
1], x); if (a < 0 || b > 0) return 1; int l = 1, r = n -
1; while (l + 1 < r) { int mid = l + r >> 1; if (
orientation(p[0], p[mid], x) >= 0) l = mid; else r = mid
; } int k = orientation(p[l], p[r], x); if (k <= 0)
return -k; if (l == 1 && a == 0) return 0; if (r == n -
1 && b == 0) return 0; return -1; } bool
is_point_on_polygon(vector<PT> &p, const PT& z) { int n
= p.size(); for (int i = 0; i < n; i++) { if (
is_point_on_seg(p[i], p[(i + 1) % n], z)) return 1; }
return 0; } /* returns 1e9 if the point is on the

```

```

polygon */ int winding_number(vector<PT> &p, const PT& z
) { /* O(n) */ if (is_point_on_polygon(p, z)) return 1e9
; int n = p.size(), ans = 0; for (int i = 0; i < n; ++i)
{ int j = (i + 1) % n; bool below = p[i].y < z.y; if (
below != (p[j].y < z.y)) { auto orient = orientation(z,
p[j], p[i]); if (orient == 0) return 0; if (below == (
orient > 0)) ans += below ? 1 : -1; } } return ans; } /*
-1 if strictly inside, 0 if on the polygon, 1 if
strictly outside */ int is_point_in_polygon(vector<PT> &
p, const PT& z) { /* O(n) */ int k = winding_number(p, z
); return k == 1e9 ? 0 : k == 0 ? 1 : -1; } /* id of the
vertex having maximum dot product with z */ /* polygon
must need to be convex */ /* top - upper right vertex */
/* for minimum dot product negate z and return -dot(z,
p[id]) */ int extreme_vertex(vector<PT> &p, const PT &z,
const int top) { /* O(log n) */ int n = p.size(); if (n
== 1) return 0; double ans = dot(p[0], z); int id = 0;
if (dot(p[top], z) > ans) ans = dot(p[top], z), id = top
; int l = 1, r = top - 1; while (l < r) { int mid = l +
r >> 1; if (dot(p[mid + 1], z) >= dot(p[mid], z)) l =
mid + 1; else r = mid; } if (dot(p[l], z) > ans) ans =
dot(p[l], z), id = l; l = top + 1, r = n - 1; while (l <
r) { int mid = l + r >> 1; if (dot(p[(mid + 1) % n], z)
>= dot(p[mid], z)) l = mid + 1; else r = mid; } l %= n;
if (dot(p[l], z) > ans) ans = dot(p[l], z), id = l;
return id; } /* maximum distance from any point on the
perimeter to another point on the perimeter */ double
diameter(vector<PT> &p) { int n = (int)p.size(); if (n
== 1) return 0; if (n == 2) return dist(p[0], p[1]);
double ans = 0; int i = 0, j = 1; while (i < n) { while
(cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] - p[j]) >=
0) { ans = max(ans, dist2(p[i], p[j])); j = (j + 1) % n;
} ans = max(ans, dist2(p[i], p[j])); i++; } return sqrt(
ans); } /* minimum distance between two parallel lines
(non necessarily axis parallel) */ /* such that the
polygon can be put between the lines */ double width(
vector<PT> &p) { int n = (int)p.size(); if (n <= 2)
return 0; double ans = inf; int i = 0, j = 1; while (i <
n) { while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n]
- p[j]) >= 0) j = (j + 1) % n; ans = min(ans,
dist_from_point_to_line(p[i], p[(i + 1) % n], p[j])); i
++; } return ans; } /* minimum perimeter */ double
minimum_enclosing_rectangle(vector<PT> &p) { int n = p.
size(); if (n <= 2) return perimeter(p); int mndot = 0;
double tmp = dot(p[1] - p[0], p[0]); for (int i = 1; i <
n; i++) { if (dot(p[i] - p[0], p[i]) <= tmp) { tmp =

```



```

dot(p[1] - p[0], p[i]); mndot = i; } } double ans = inf;
int i = 0, j = 1, mxdot = 1; while (i < n) { PT cur = p
[(i + 1) % n] - p[i]; while (cross(cur, p[(j + 1) % n] -
p[j]) >= 0) j = (j + 1) % n; while (dot(p[(mxdot + 1) %
n], cur) >= dot(p[mxdot], cur)) mxdot = (mxdot + 1) % n
; while (dot(p[(mndot + 1) % n], cur) <= dot(p[mndot],
cur)) mndot = (mndot + 1) % n; ans = min(ans, 2.0 * ((
dot(p[mxdot], cur) / cur.norm() - dot(p[mndot], cur) /
cur.norm()) + dist_from_point_to_line(p[i], p[(i + 1) %
n], p[j]))); i++; } return ans; } /* given n points,
find the minimum enclosing circle of the points */ /*
call convex_hull() before this for faster solution */ /*
expected O(n) */ random_device rd; mt19937 g(rd());
circle minimum_enclosing_circle(vector<PT> &p) { shuffle
(p.begin(), p.end(), g); int n = p.size(); circle c(p
[0], 0); for (int i = 1; i < n; i++) { if (sign(dist(c.p
, p[i]) - c.r) > 0) { c = circle(p[i], 0); for (int j =
0; j < i; j++) { if (sign(dist(c.p, p[j]) - c.r) > 0) {
c = circle((p[i] + p[j]) / 2, dist(p[i], p[j]) / 2); for
(int k = 0; k < j; k++) { if (sign(dist(c.p, p[k]) - c.
r) > 0) { c = circle(p[i], p[j], p[k]); } } } } } }
return c; } /* returns a vector with the vertices of a
polygon with everything */ /* to the left of the line
going from a to b cut away. */ vector<PT> cut(vector<PT>
&p, PT a, PT b) { vector<PT> ans; int n = (int)p.size()
; for (int i = 0; i < n; i++) { double c1 = cross(b - a,
p[i] - a); double c2 = cross(b - a, p[(i + 1) % n] - a)
; if (sign(c1) >= 0) ans.push_back(p[i]); if (sign(c1 *
c2) < 0) { if (!is_parallel(p[i], p[(i + 1) % n], a, b))
{ PT tmp; line_line_intersection(p[i], p[(i + 1) % n],
a, b, tmp); ans.push_back(tmp); } } } return ans; } /*
not necessarily convex, boundary is included in the
intersection */ /* returns total intersected length */
/* it returns the sum of the lengths of the portions of
the line that are inside the polygon */ double
polygon_line_intersection(vector<PT> p, PT a, PT b) {
int n = p.size(); p.push_back(p[0]); line l = line(a, b)
; double ans = 0.0; vector< pair<double, int> > vec; for
(int i = 0; i < n; i++) { int s1 = orientation(a, b, p[
i]); int s2 = orientation(a, b, p[i + 1]); if (s1 == s2)
continue; line t = line(p[i], p[i + 1]); PT inter = (t.
v * l.c - l.v * t.c) / cross(l.v, t.v); double tmp = dot
(inter, l.v); int f; if (s1 > s2) f = s1 && s2 ? 2 : 1;
else f = s1 && s2 ? -2 : -1; vec.push_back(make_pair((f
> 0 ? tmp - eps : tmp + eps), f)); /* keep eps very
small like 1e-12 */ } sort(vec.begin(), vec.end()); for

```

```

(int i = 0, j = 0; i + 1 < (int)vec.size(); i++){ j +=
vec[i].second; if (j) ans += vec[i + 1].first - vec[i].
first; /* if this portion is inside the polygon */ /*
else ans = 0; if we want the maximum intersected length
which is totally inside the polygon, uncomment this and
take the maximum of ans */ } ans = ans / sqrt(dot(l.v, l
.v)); p.pop_back(); return ans; } /* given a convex
polygon p, and a line ab and the top vertex of the
polygon */ /* returns the intersection of the line with
the polygon */ /* it returns the indices of the edges of
the polygon that are intersected by the line */ /* so
if it returns i, then the line intersects the edge (p[i
], p[(i + 1) % n]) */ array<int, 2>
convex_line_intersection(vector<PT> &p, PT a, PT b, int
top) { int end_a = extreme_vertex(p, (a - b).perp(), top
); int end_b = extreme_vertex(p, (b - a).perp(), top);
auto cmp_l = [&](int i) { return orientation(a, p[i], b)
; }; if (cmp_l(end_a) < 0 || cmp_l(end_b) > 0) return
{-1, -1}; /* no intersection */ array<int, 2> res; for (
int i = 0; i < 2; i++) { int lo = end_b, hi = end_a, n =
p.size(); while ((lo + 1) % n != hi) { int m = ((lo +
hi + (lo < hi ? 0 : n)) / 2) % n; (cmp_l(m) == cmp_l(
end_b) ? lo : hi) = m; } res[i] = (lo + !cmp_l(hi)) % n;
swap(end_a, end_b); } if (res[0] == res[1]) return {res
[0], -1}; /* touches the vertex res[0] */ if (!cmp_l(res
[0]) && !cmp_l(res[1])) switch ((res[0] - res[1] + (int)
p.size() + 1) % p.size()) { case 0: return {res[0], res
[0]}; /* touches the edge (res[0], res[0] + 1) */ case
2: return {res[1], res[1]}; /* touches the edge (res[1],
res[1] + 1) */ } return res; /* intersects the edges (
res[0], res[0] + 1) and (res[1], res[1] + 1) */ } pair<
PT, int> point_poly_tangent(vector<PT> &p, PT Q, int dir
, int l, int r) { while (r - l > 1) { int mid = (l + r)
>> 1; bool pvs = orientation(Q, p[mid], p[mid - 1]) != -
dir; bool nxt = orientation(Q, p[mid], p[mid + 1]) != -
dir; if (pvs && nxt) return {p[mid], mid}; if (!(pvs ||
nxt)) { auto p1 = point_poly_tangent(p, Q, dir, mid + 1,
r); auto p2 = point_poly_tangent(p, Q, dir, l, mid - 1)
; return orientation(Q, p1.first, p2.first) == dir ? p1
: p2; } if (!pvs) { if (orientation(Q, p[mid], p[l]) ==
dir) r = mid - 1; else if (orientation(Q, p[l], p[r]) ==
dir) r = mid - 1; else l = mid + 1; } if (!nxt) { if (
orientation(Q, p[mid], p[l]) == dir) l = mid + 1; else
if (orientation(Q, p[l], p[r]) == dir) r = mid - 1; else
l = mid + 1; } } pair<PT, int> ret = {p[l], l}; for (
int i = l + 1; i <= r; i++) ret = orientation(Q, ret.

```

```

first, p[i]) != dir ? make_pair(p[i], i) : ret; return
ret; } /* (ccw, cw) tangents from a point that is
outside this convex polygon */ /* returns indexes of the
points */ /* ccw means the tangent from Q to that point
is in the same direction as the polygon ccw direction
*/ pair<int, int> tangents_from_point_to_polygon(vector<
PT> &p, PT Q) { int ccw = point_poly_tangent(p, Q, 1, 0,
(int)p.size() - 1).second; int cw = point_poly_tangent(p
, Q, -1, 0, (int)p.size() - 1).second; return make_pair(
ccw, cw); } /* minimum distance from a point to a convex
polygon */ /* it assumes point lie strictly outside the
polygon */ double dist_from_point_to_polygon(vector<PT>
&p, PT z) { double ans = inf; int n = p.size(); if (n
<= 3) { for (int i = 0; i < n; i++) ans = min(ans,
dist_from_point_to_seg(p[i], p[(i + 1) % n], z)); return
ans; } auto [r, l] = tangents_from_point_to_polygon(p,
z); if (l > r) r += n; while (l < r) { int mid = (l + r)
>> 1; double left = dist2(p[mid % n], z), right = dist2(p
[(mid + 1) % n], z); ans = min({ans, left, right}); if (
left < right) r = mid; else l = mid + 1; } ans = sqrt(
ans); ans = min(ans, dist_from_point_to_seg(p[l % n], p
[(l + 1) % n], z)); ans = min(ans,
dist_from_point_to_seg(p[l % n], p[(l - 1 + n) % n], z))
; return ans; } /* minimum distance from convex polygon
p to line ab */ /* returns 0 is it intersects with the
polygon */ /* top - upper right vertex */ double
dist_from_polygon_to_line(vector<PT> &p, PT a, PT b, int
top) { /* O(log n) */ PT orth = (b - a).perp(); if (
orientation(a, b, p[0]) > 0) orth = (a - b).perp(); int
id = extreme_vertex(p, orth, top); if (dot(p[id] - a,
orth) > 0) return 0.0; /* if orth and a are in the same
half of the line, then poly and line intersects */
return dist_from_point_to_line(a, b, p[id]); /* does not
intersect */ } /* minimum distance from a convex
polygon to another convex polygon */ /* the polygon
doesnot overlap or touch */ /* tested in https://toph.co/p
/the-wall */ double dist_from_polygon_to_polygon(vector<
PT> &p1, vector<PT> &p2) { /* O(n log n) */ double ans =
inf; for (int i = 0; i < p1.size(); i++) { ans = min(
ans, dist_from_point_to_polygon(p2, p1[i])); } for (int
i = 0; i < p2.size(); i++) { ans = min(ans,
dist_from_point_to_polygon(p1, p2[i])); } return ans; }
/* maximum distance from a convex polygon to another
convex polygon */ double
maximum_dist_from_polygon_to_polygon(vector<PT> &u,
vector<PT> &v) { /* O(n) */ int n = (int)u.size(), m = (

```



```

int)v.size(); double ans = 0; if (n < 3 || m < 3) { for
(int i = 0; i < n; i++) { for (int j = 0; j < m; j++)
ans = max(ans, dist2(u[i], v[j])); } return sqrt(ans); }
if (u[0].x > v[0].x) swap(n, m), swap(u, v); int i = 0,
j = 0, step = n + m + 10; while (j + 1 < m && v[j].x <
v[j + 1].x) j++; while (step-- > 0) { if (cross(u[(i + 1) % n]
- u[i], v[(j + 1) % m] - v[j]) >= 0) j = (j + 1) % m;
else i = (i + 1) % n; ans = max(ans, dist2(u[i], v[j]));
} return sqrt(ans); } /* calculates the area of the
union of n polygons (not necessarily convex). */ /* the
points within each polygon must be given in CCW order.
*/ /* complexity: O(N^2), where N is the total number of
points */ double rat(PT a, PT b, PT p) { return !sign(a
.x - b.x) ? (p.y - a.y) / (b.y - a.y) : (p.x - a.x) / (b
.x - a.x); }; double polygon_union(vector<vector<PT>> &p
) { int n = p.size(); double ans=0; for(int i = 0; i < n
; ++i) { for (int v = 0; v < (int)p[i].size(); ++v) { PT
a = p[i][v], b = p[i][(v + 1) % p[i].size()]; vector<
pair<double, int>> segs; segs.emplace_back(0, 0), segs.
emplace_back(1, 0); for(int j = 0; j < n; ++j) { if(i !=
j) { for(size_t u = 0; u < p[j].size(); ++u) { PT c = p
[j][u], d = p[j][(u + 1) % p[j].size()]; int sc = sign(
cross(b - a, c - a)), sd = sign(cross(b - a, d - a)); if
(!sc && !sd) { if(sign(dot(b - a, d - c)) > 0 && i > j)
{ segs.emplace_back(rat(a, b, c), 1), segs.emplace_back(
rat(a, b, d), -1); } } else { double sa = cross(d - c, a
- c), sb = cross(d - c, b - c); if(sc >= 0 && sd < 0)
segs.emplace_back(sa / (sa - sb), 1); else if(sc < 0 &&
sd >= 0) segs.emplace_back(sa / (sa - sb), -1); } } }
sort(segs.begin(), segs.end()); double pre = min(max(
segs[0].first, 0.0), 1.0), now, sum = 0; int cnt = segs
[0].second; for(int j = 1; j < segs.size(); ++j) { now =
min(max(segs[j].first, 0.0), 1.0); if (!cnt) sum += now
- pre; cnt += segs[j].second; pre = now; } ans += cross
(a, b) * sum; } } return ans * 0.5; }
/* contains all points p such that: cross(b - a, p - a)
>= 0 */
struct HP { PT a, b; HP() {} HP(PT a, PT b) : a(a), b(b)
{} HP(const HP& rhs) : a(rhs.a), b(rhs.b) {} int
operator < (const HP& rhs) const { PT p = b - a; PT q =
rhs.b - rhs.a; int fp = (p.y < 0 || (p.y == 0 && p.x <
0)); int fq = (q.y < 0 || (q.y == 0 && q.x < 0)); if (fp
!= fq) return fp == 0; if (cross(p, q)) return cross(p,
q) > 0; return cross(p, rhs.b - a) < 0; } PT
line_line_intersection(PT a, PT b, PT c, PT d) { b = b -
a; d = c - d; c = c - a; return a + b * cross(c, d) /

```

```

cross(b, d); } PT intersection(const HP &v) { return
line_line_intersection(a, b, v.a, v.b); } }; int check(
HP a, HP b, HP c) { return cross(a.b - a.a, b.
intersection(c) - a.a) > -eps; /* -eps to include
polygons of zero area (straight lines, points) */ /*
consider half-plane of counter-clockwise side of each
line */ /* if lines are not bounded add infinity
rectangle */ /* returns a convex polygon, a point can
occur multiple times though */ /* complexity: O(n log(n)
) */ vector<PT> half_plane_intersection(vector<HP> h) {
sort(h.begin(), h.end()); vector<HP> tmp; for (int i =
0; i < h.size(); i++) { if (!i || cross(h[i].b - h[i].a,
h[i - 1].b - h[i - 1].a)) { tmp.push_back(h[i]); } } h
= tmp; vector<HP> q(h.size() + 10); int qh = 0, qe = 0;
for (int i = 0; i < h.size(); i++) { while (qe - qh > 1
&& !check(h[i], q[qe - 2], q[qe - 1])) qe--; while (qe -
qh > 1 && !check(h[i], q[qh], q[qh + 1])) qh++; q[qe++]
= h[i]; } while (qe - qh > 2 && !check(q[qh], q[qe -
2], q[qe - 1])) qe--; while (qe - qh > 2 && !check(q[qe
- 1], q[qh], q[qh + 1])) qh++; vector<HP> res; for (int
i = qh; i < qe; i++) res.push_back(q[i]); vector<PT>
hull; if (res.size() > 2) { for (int i = 0; i < res.size
(); i++) { hull.push_back(res[i].intersection(res[(i +
1) % ((int)res.size())])); } } return hull; } /* rotate
the polygon such that the (bottom, left)-most point is
at the first position */ void reorder_polygon(vector<PT>
&p) { int pos = 0; for (int i = 1; i < p.size(); i++) {
if (p[i].y < p[pos].y || (sign(p[i].y - p[pos].y) == 0
&& p[i].x < p[pos].x)) pos = i; } rotate(p.begin(), p.
begin() + pos, p.end()); } /* a and b are convex
polygons */ /* returns a convex hull of their minkowski
sum */ /* min(a.size(), b.size()) >= 2 */ /* https://cp-algorithms.com/geometry/minkowski.html */ vector<PT>
minkowski_sum(vector<PT> a, vector<PT> b) {
reorder_polygon(a); reorder_polygon(b); int n = a.size()
, m = b.size(); int i = 0, j = 0; a.push_back(a[0]); a.
push_back(a[1]); b.push_back(b[0]); b.push_back(b[1]);
vector<PT> c; while (i < n || j < m) { c.push_back(a[i]
+ b[j]); double p = cross(a[i + 1] - a[i], b[j + 1] - b[
j]); if (sign(p) >= 0) ++i; if (sign(p) <= 0) ++j; }
return c; } /* returns the area of the intersection of
the circle with center c and radius r */ /* and the
triangle formed by the points c, a, b */ double
_triangle_circle_intersection(PT c, double r, PT a, PT b
) { double sd1 = dist2(c, a), sd2 = dist2(c, b); if(sd1
> sd2) swap(a, b), swap(sd1, sd2); double sd = dist2(a,

```

```

b); double d1 = sqrt1(sd1), d2 = sqrt1(sd2), d = sqrt(sd
); double x = abs(sd2 - sd - sd1) / (2 * d); double h =
sqrt1(sd1 - x * x); if(r >= d2) return h * d / 2; double
area = 0; if(sd + sd1 < sd2) { if(r < d1) area = r * r
* (acos(h / d2) - acos(h / d1)) / 2; else { area = r * r
* (acos(h / d2) - acos(h / r)) / 2; double y = sqrt1(r
* r - h * h); area += h * (y - x) / 2; } } else { if(r
< h) area = r * r * (acos(h / d2) + acos(h / d1)) / 2;
else { area += r * r * (acos(h / d2) - acos(h / r)) / 2;
double y = sqrt1(r * r - h * h); area += h * y / 2; if(
r < d1) { area += r * r * (acos(h / d1) - acos(h / r)) /
2; area += h * y / 2; } else area += h * x / 2; } }
return area; } /* intersection between a simple polygon
and a circle */ double polygon_circle_intersection(
vector<PT> &v, PT p, double r) { int n = v.size();
double ans = 0.00; PT org = {0, 0}; for(int i = 0; i < n
; i++) { int x = orientation(p, v[i], v[(i + 1) % n]);
if(x == 0) continue; double area =
_triangle_circle_intersection(org, r, v[i] - p, v[(i +
1) % n] - p); if (x < 0) ans -= area; else ans += area;
} return abs(ans); } /* find a circle of radius r that
contains as many points as possible */ /* O(n^2 log n);
*/ double maximum_circle_cover(vector<PT> p, double r,
circle &c) { int n = p.size(); int ans = 0; int id = 0;
double th = 0; for (int i = 0; i < n; ++i) { /* maximum
circle cover when the circle goes through this point */
vector<pair<double, int>> events = {{-PI, +1}, {PI,
-1}}; for (int j = 0; j < n; ++j) { if (j == i) continue
; double d = dist(p[i], p[j]); if (d > r * 2) continue;
double dir = (p[j] - p[i]).arg(); double ang = acos(d /
2 / r); double st = dir - ang, ed = dir + ang; if (st >
PI) st -= PI * 2; if (st <= -PI) st += PI * 2; if (ed >
PI) ed -= PI * 2; if (ed <= -PI) ed += PI * 2; events.
push_back({st - eps, +1}); /* take care of precisions!
*/ events.push_back({ed, -1}); if (st > ed) { events.
push_back({-PI, +1}); events.push_back({+PI, -1}); } }
sort(events.begin(), events.end()); int cnt = 0; for (
auto &e: events) { cnt += e.second; if (cnt > ans) {
ans = cnt; id = i; th = e.first; } } } PT w = PT(p[id].x
+ r * cos(th), p[id].y + r * sin(th)); c = circle(w, r)
; /* best_circle */ return ans; } /* radius of the
maximum inscribed circle in a convex polygon */ double
maximum_inscribed_circle(vector<PT> p) { int n = p.size
(); if (n <= 2) return 0; double l = 0, r = 20000; while
(r - l > eps) { double mid = (l + r) * 0.5; vector<HP>
h; const int L = 1e9; h.push_back(HP(PT(-L, -L), PT(L, -

```

```

L)); h.push_back(HP(PT(L, -L), PT(L, L))); h.push_back(
HP(PT(L, L), PT(-L, L))); h.push_back(HP(PT(-L, L), PT(-
L, -L))); for (int i = 0; i < n; i++) { PT z = (p[(i +
1) % n] - p[i]).perp(); z = z.truncate(mid); PT y = p[i]
+ z, q = p[(i + 1) % n] + z; h.push_back(HP(p[i] + z, p
[(i + 1) % n] + z)); } vector<PT> nw =
half_plane_intersection(h); if (!nw.empty()) l = mid;
else r = mid; } return l; } /* ear decomposition, O(n^3)
but faster */ vector<vector<PT>> triangulate(vector<PT>
p) { vector<vector<PT>> v; while (p.size() >= 3) { for
(int i = 0, n = p.size(); i < n; i++) { int pre = i == 0
? n - 1 : i - 1; int nxt = i == n - 1 ? 0 : i + 1;
int ori = orientation(p[i], p[pre], p[nxt]); if (ori <
0) { int ok = 1; for (int j = 0; j < n; j++) { if (j ==
i || j == pre || j == nxt) continue; if (
is_point_in_triangle(p[i], p[pre], p[nxt], p[j]) < 1) {
ok = 0; break; } } if (ok) { v.push_back({p[pre], p[i],
p[nxt]}); p.erase(p.begin() + i); break; } } } } return
v; }

```

```

struct star { int n; /* number of sides of the star */
double r; /* radius of the circumcircle */ star(int _n,
double _r) { n = _n; r = _r; } double area() { double
theta = PI / n; double s = 2 * r * sin(theta); double R
= 0.5 * s / tan(theta); double a = 0.5 * n * s * R;
double a2 = 0.25 * s * s / tan(1.5 * theta); return a -
n * a2; } }; /* given a list of lengths of the sides of
a polygon in counterclockwise order */ /* returns the
maximum area of a non-degenerate polygon that can be
formed using those lengths */ double
get_maximum_polygon_area_for_given_lengths(vector<double>
> v) { if (v.size() < 3) { return 0; } int m = 0; double
sum = 0; for (int i = 0; i < v.size(); i++) { if (v[i]
> v[m]) { m = i; } sum += v[i]; } if (sign(v[m] - (sum -
v[m])) >= 0) { return 0; /* no non-degenerate polygon
is possible */ } /* the polygon should be a circular
polygon */ /* that is all points are on the
circumference of a circle */ double l = v[m] / 2, r = 1
e6; /* fix it correctly */ int it = 60; auto ang = [] (
double x, double r) { /* x = length of the chord, r =
radius of the circle */ return 2 * asin((x / 2) / r); };
auto calc = [=] (double r) { double sum = 0; for (auto x
: v) { sum += ang(x, r); } return sum; }; /* compute the
radius of the circle */ while (it--) { double mid = (l
+ r) / 2; if (calc(mid) <= 2 * PI) { r = mid; } else { l
= mid; } } if (calc(r) <= 2 * PI - eps) { /* the center

```

```

of the circle is outside the polygon */ auto calc2 =
[&] (double r) { double sum = 0; for (int i = 0; i < v.
size(); i++) { double x = v[i]; double th = ang(x, r);
if (i != m) { sum += th; } else { sum += 2 * PI - th; }
} return sum; }; l = v[m] / 2; r = 1e6; it = 60; while (
it--) { double mid = (l + r) / 2; if (calc2(mid) > 2 *
PI) { r = mid; } else { l = mid; } } auto get_area =
[=] (double r) { double ans = 0; for (int i = 0; i < v.
size(); i++) { double x = v[i]; double area = r * r *
sin(ang(x, r)) / 2; if (i != m) { ans += area; } else {
ans -= area; } } return ans; }; return get_area(r); }
else { /* the center of the circle is inside the polygon
*/ auto get_area = [=] (double r) { double ans = 0; for
(auto x: v) { ans += r * r * sin(ang(x, r)) / 2; }
return ans; }; return get_area(r); } }

```

7.2 3D Shohag

```

const double inf = 1e100; const double eps = 1e-9; const
double PI = acos((double)-1.0); int sign(double x) {
return (x > eps) - (x < -eps); } struct PT { double x, y
; PT() { x = 0, y = 0; } PT(double x, double y) : x(x),
y(y) {} PT(const PT &p) : x(p.x), y(p.y) {} void scan()
{ cin >> x >> y; } PT operator + (const PT &a) const {
return PT(x + a.x, y + a.y); } PT operator - (const PT &
a) const { return PT(x - a.x, y - a.y); } PT operator *
(const double a) const { return PT(x * a, y * a); }
friend PT operator * (const double &a, const PT &b) {
return PT(a * b.x, a * b.y); } PT operator / (const
double a) const { return PT(x / a, y / a); } bool
operator == (PT a) const { return sign(a.x - x) == 0 &&
sign(a.y - y) == 0; } bool operator != (PT a) const {
return !(*this == a); } bool operator < (PT a) const {
return sign(a.x - x) == 0 ? y < a.y : x < a.x; } bool
operator > (PT a) const { return sign(a.x - x) == 0 ? y
> a.y : x > a.x; } double norm() { return sqrt(x * x + y
* y); } double norm2() { return x * x + y * y; } PT
perp() { return PT(-y, x); } double arg() { return atan2
(y, x); } PT truncate(double r) { /* // returns a vector
with norm r and having same direction */ double k =
norm(); if (!sign(k)) return *this; r /= k; return PT(x
* r, y * r); } }; inline double dot(PT a, PT b) { return
a.x * b.x + a.y * b.y; } inline double dist2(PT a, PT b)
{ return dot(a - b, a - b); } inline double dist(PT a,
PT b) { return sqrt(dot(a - b, a - b)); } inline double
cross(PT a, PT b) { return a.x * b.y - a.y * b.x; }
inline int orientation(PT a, PT b, PT c) { return sign(

```

```

cross(b - a, c - a)); } PT perp(PT a) { return PT(-a.y,
a.x); } PT rotateccw90(PT a) { return PT(-a.y, a.x); }
PT rotatecw90(PT a) { return PT(a.y, -a.x); } PT
rotateccw(PT a, double t) { return PT(a.x * cos(t) - a.y
* sin(t), a.x * sin(t) + a.y * cos(t)); } PT rotatecw(
PT a, double t) { return PT(a.x * cos(t) + a.y * sin(t),
-a.x * sin(t) + a.y * cos(t)); } double SQ(double x) {
return x * x; } double rad_to_deg(double r) { return (r
* 180.0 / PI); } double deg_to_rad(double d) { return (d
* PI / 180.0); } double get_angle(PT a, PT b) { double
costheta = dot(a, b) / a.norm() / b.norm(); return acos(
max((double)-1.0, min((double)1.0, costheta))); } struct
p3 { double x, y, z; p3() { x = 0, y = 0; z = 0; } p3(
double x, double y, double z) : x(x), y(y), z(z) {} p3(
const p3 &p) : x(p.x), y(p.y), z(p.z) {} void scan() {
cin >> x >> y >> z; } p3 operator + (const p3 &a) const
{ return p3(x + a.x, y + a.y, z + a.z); } p3 operator -
(const p3 &a) const { return p3(x - a.x, y - a.y, z - a.
z); } p3 operator * (const double a) const { return p3(x
* a, y * a, z * a); } friend p3 operator * (const
double &a, const p3 &b) { return p3(a * b.x, a * b.y, a
* b.z); } p3 operator / (const double a) const { return
p3(x / a, y / a, z / a); } bool operator == (p3 a) const
{ return sign(a.x - x) == 0 && sign(a.y - y) == 0 &&
sign(a.z - z) == 0; } bool operator != (p3 a) const {
return !(*this == a); } double abs() { return sqrt(x * x
+ y * y + z * z); } double sq() { return x * x + y * y
+ z * z; } p3 unit() { return *this / abs(); } } zero(0,
0, 0); double operator | (p3 v, p3 w) { /* //dot product
*/ return v.x * w.x + v.y * w.y + v.z * w.z; } p3
operator * (p3 v, p3 w) { /* //cross product */ return {
v.y * w.z - v.z * w.y, v.z * w.x - v.x * w.z, v.x * w.y
- v.y * w.x; }; } double sq(p3 v) { return v | v; } double
abs(p3 v) { return sqrt(sq(v)); } p3 unit(p3 v) {
return v / abs(v); } inline double dot(p3 a, p3 b) {
return a.x * b.x + a.y * b.y + a.z * b.z; } inline
double dist2(p3 a, p3 b) { return dot(a - b, a - b); }
inline double dist(p3 a, p3 b) { return sqrt(dot(a - b,
a - b)); } inline p3 cross(p3 a, p3 b) { return p3(a.y *
b.z - a.z * b.y, a.z * b.x - a.x * b.z, a.x * b.y - a.y
* b.x); } /* // if s is on the same side of the plane
pqr as the vector pq * pr then it will be positive //
otherwise negative or 0 if on the plane */ double orient
(p3 p, p3 q, p3 r, p3 s) { return (q - p) * (r - p) | (s
- p); } /* // returns orientation of p to q to r on the
plane perpendicular to n // assuming p, q, r are on the

```

```

plane /* double orient_by_normal(p3 p, p3 q, p3 r, p3 n
) { return (q - p) * (r - p) | n; } double get_angle(p3
a, p3 b) { double costheta = dot(a, b) / a.abs() / b.abs
(); return acos(max((double)-1.0, min((double)1.0,
costheta))); } double small_angle(p3 v, p3 w) { return
acos(min(fabs(v | w) / abs(v) / abs(w), (double)1.0)); }
struct plane { /* // n is the perpendicular normal
vector to the plane */ p3 n; double d; /* // (n | p) = d
*/ /* // From normal n and offset d */ plane(p3 n,
double d) : n(n), d(d) {} /* // From normal n and point
P */ plane(p3 n, p3 p) : n(n), d(n | p) {} /* // From
three non-collinear points P,Q,R */ plane(p3 p, p3 q, p3
r) : plane((q - p) * (r - p), p) {} /* // positive if
on the same side as the normal, negative if on the
opposite side, 0 if on the plane */ double side(p3 p) {
return (n | p) - d; } /* // distance from point p to
plane */ double dist(p3 p) { return fabs(side(p)) / abs(
n); } /* // translate the plane by vector t */ plane
translate(p3 t) { return {n, d + (n | t)}; } /* // shift
the plane perpendicular to n by distance dist */ plane
shiftUp(double dist) { return {n, d + dist * abs(n)}; }
/* // orthogonal projection of point p onto plane */ p3
proj(p3 p) { return p - n * side(p) / sq(n); } /* //
orthogonal reflection of point p onto plane */ p3 refl(
p3 p) { return p - n * 2 * side(p) / sq(n); } pair<p3,
p3> get_two_points_on_plane() { assert(sign(n.x) != 0 ||
sign(n.y) != 0 || sign(n.z) != 0); if (sign(n.x) == 0
&& sign(n.y) == 0) return {p3(1, 0, d/n.z), p3(0, 1, d/n
.z)}; if (sign(n.y) == 0 && sign(n.z) == 0) return {p3(d
/n.x, 1, 0), p3(d/n.x, 0, 1)}; if (sign(n.z) == 0 &&
sign(n.x) == 0) return {p3(1, d/n.y, 0), p3(0, d/n.y, 1)
}; if (sign(n.x) == 0) return {p3(1, d/n.y, 0), p3(0, 0,
d/n.z)}; if (sign(n.y) == 0) return {p3(0, 1, d/n.z),
p3(d/n.x, 0, 0)}; if (sign(n.z) == 0) return {p3(d/n.x,
0, 1), p3(0, d/n.y, 0)}; if (sign(d)!=0) return {p3(d/n
.x, 0, 0), p3(0, d/n.y, 0)}; return {p3(n.y, -n.x, 0), p3
(-n.y, n.x, 0)}; } }; struct coords { /* // coordinate
system for coplanar points // o is the origin, dx, dy,
dz are unit vectors similar to normal 3D system // but
dx and dy are on the plane */ p3 o, dx, dy, dz; /* //
From three points P, Q, R on the plane */ coords(p3 p,
p3 q, p3 r) : o(p) { dx = unit(q - p); dz = unit(dx * (r
- p)); dy = dz * dx; } /* // From four points P,Q,R,S:
take directions PQ, PR, PS as is // it allows us to keep
using integer coordinates but has some pitfalls // e.g.
distances and angles are not preserved but relative

```

```

positions are (convex hull works) */ coords(p3 p, p3 q,
p3 r, p3 s) : o(p), dx(q - p), dy(r - p), dz(s - p) {}
/* // 2D position vector of point p in this coordinate
system centered at o // p must be on the plane */ PT
pos2d(p3 p) { return {(p - o) | dx, (p - o) | dy}; } /*
// returns the 3D position vector of point p in this new
coordinate system // p can be outside the plane */ p3
pos3d(p3 p) { return {(p - o) | dx, (p - o) | dy, (p - o
) | dz}; } /* // given 2D position vector p centered at
o, return the original 3D position vector */ p3 pos3d(PT
p){ return o + dx * p.x + dy * p.y; } }; struct line3d
{ /* // d is the direction vector of the line */ p3 d, o
; /* // p = o + k * d (k is a real parameter) */ line3d
() {} /* // From two points P, Q */ line3d(p3 p, p3 q) :
d(q - p), o(p) {} /* // From two planes p1, p2 //
assuming they are not parallel */ line3d(plane p1, plane
p2) { d = p1.n * p2.n; o = (p2.n * p1.d - p1.n * p2.d)
* d / sq(d); /* // o is actually the closest point on
the line to the origin */ } double dist2(p3 p) { return
sq(d * (p - o)) / sq(d); } double dist(p3 p) { return
sqrt(dist2(p)); } /* // compare points by their
projection on the line // so you can sort points on the
line using this */ bool cmp_proj(p3 p, p3 q) { return (d
| p) < (d | q); } /* // orthogonal projection of point
p onto line */ p3 proj(p3 p) { return o + d * (d | (p - o
) / sq(d); } /* // orthogonal reflection of point p onto
line */ p3 refl(p3 p) { return proj(p) * 2 - p; } /* //
returns the intersection point of the line with plane p
// assuming plane and line are not parallel */ p3 inter
(plane p) { /* // assert((d | p.n) != 0); // no
intersection if parallel */ return o - d * p.side(o) / (
d | p.n); } }; /* // smallest distance between two lines
*/ double dist(line3d l1, line3d l2) { p3 n = l1.d * l2
.d; if (n == zero) return l1.dist(l2.o); /* // parallel
*/ return fabs((l2.o - l1.o) | n) / abs(n); } /* //
closest point from line l2 to line l1 */ p3
closest_on_l1(line3d l1, line3d l2) { p3 n2 = l2.d * (l1
.d * l2.d); return l1.o + l1.d * ((l2.o - l1.o) | n2) /
(l1.d | n2); } /* // small angle between direction
vectors of two lines */ double get_angle(line3d l1,
line3d l2) { return small_angle(l1.d, l2.d); } bool
is_parallel(line3d l1, line3d l2) { return l1.d * l2.d
== zero; } bool is_perpendicular(line3d l1, line3d l2) {
return sign((l1.d | l2.d)) == 0; } /* // small angle
between normal vectors of two planes */ double get_angle
(plane p1, plane p2) { return small_angle(p1.n, p2.n); }

```

```

bool is_parallel(plane p1, plane p2) { return p1.n * p2
.n == zero; } bool is_perpendicular(plane p1, plane p2)
{ return sign((p1.n | p2.n)) == 0; } double get_angle(
plane p, line3d l) { return PI / 2 - small_angle(p.n, l
.d); } bool is_parallel(plane p, line3d l) { return sign
((p.n | l.d)) == 0; } bool is_perpendicular(plane p,
line3d l) { return p.n * l.d == zero; } /* // returns
the line perpendicular to plane p and passing through
point o */ line3d perp_through(plane p, p3 o) {return
line3d(o, o + p.n);} /* // returns the plane
perpendicular to line l and passing through point o */
plane perp_through(line3d l, p3 o) {return plane(l.d, o)
; } /* // returns two points on intesection line of two
planes formed by points // a1, b1, c1 and a2, b2, c2
respectively */ pair<p3, p3> plane_plane_intersection(p3
a1, p3 b1, p3 c1, p3 a2, p3 b2, p3 c2) { p3 n1 = (b1 -
a1) * (c1 - a1); p3 n2 = (b2 - a2) * (c2 - a2); double
d1 = n1 | a1, d2 = n2 | a2; p3 d = n1 * n2; if (d ==
zero) return make_pair(zero, zero); p3 o = (n2 * d1 - n1
* d2) * d / (d | d); return make_pair(o, o + d); } /*
// returns center of circle passing through three // non
-collinear and co-planer points a, b and c */ p3
circle_center(p3 a, p3 b, p3 c) { p3 v1 = b - a, v2 = c
- a; double v1v1 = v1 | v1, v2v2 = v2 | v2, v1v2 = v1 |
v2; double base = 0.5 / (v1v1 * v2v2 - v1v2 * v1v2);
double k1 = base * v2v2 * (v1v1 - v1v2); double k2 =
base * v1v1 * (v2v2 - v1v2); return a + v1 * k1 + v2 *
k2; } /* // segment ab to point c */ double
distance_from_segment_to_point(p3 a, p3 b, p3 c) { if (
sign(dot(b - a, c - a)) < 0) return dist(a, c); if (sign
(dot(a - b, c - b)) < 0) return dist(b, c); return fabs(
cross((b - a).unit(), c - a).abs()); } double
distance_from_triangle_to_point(p3 a, p3 b, p3 c, p3 d)
{ plane P(a, b, c); p3 proj = P.proj(d); double dis =
min(distance_from_segment_to_point(a, b, d), min(
distance_from_segment_to_point(b, c, d),
distance_from_segment_to_point(c, a, d))); int o = sign(
orient_by_normal(a, b, proj, P.n)); int inside = o ==
sign(orient_by_normal(b, c, proj, P.n)); inside &= o ==
sign(orient_by_normal(c, a, proj, P.n)); if (inside)
return (d - proj).abs(); return dis; } double
distance_from_triangle_to_segment(p3 a, p3 b, p3 c, p3 d
, p3 e) { double l = 0.0, r = 1.0; int cnt = 100; double
ret = inf; while (cnt--) { double mid1 = l + (r - l) /
3.0, mid2 = r - (r - l) / 3.0; double x =
distance_from_triangle_to_point(a, b, c, d + (e - d) *

```



```

mid1); double y = distance_from_triangle_to_point(a, b,
c, d + (e - d) * mid2); if (x < y) { r = mid2; ret = x;
} else { ret = y; l = mid1; } } return ret; } /* //
triangles are solid */ double
distance_from_triangle_to_triangle(p3 a, p3 b, p3 c, p3
d, p3 e, p3 f) { double ret = inf; ret = min(ret,
distance_from_triangle_to_segment(a, b, c, d, e)); ret =
min(ret, distance_from_triangle_to_segment(a, b, c, e,
f)); ret = min(ret, distance_from_triangle_to_segment(a,
b, c, f, d)); ret = min(ret,
distance_from_triangle_to_segment(d, e, f, a, b)); ret =
min(ret, distance_from_triangle_to_segment(d, e, f, b,
c)); ret = min(ret, distance_from_triangle_to_segment(d,
e, f, c, a)); return ret; } bool operator < (p3 p, p3 q
) { return tie(p.x, p.y, p.z) < tie(q.x, q.y, q.z); }
struct edge { int v; bool same; /* // is the common edge
between two faces in the same order? */ }; /* // Given
a series of faces (lists of points) of a polyhedron,
reverse some of them // so that their orientations are
consistent (all area vectors of the faces either
pointing outwards or inwards) // just compute the area
vector of one face to see if its pointing outwards or
inwards */ vector<vector<p3>> reorient(vector<vector<p3
>> fs) { int n = fs.size(); /* // Find the common edges
and create the resulting graph */ vector<vector<edge>> g
(n); map<pair<p3,p3>, int> es; for (int u = 0; u < n; u
++) { for (int i = 0, m = fs[u].size(); i < m; i++) { p3
a = fs[u][i], b = fs[u][(i + 1) % m]; /* // Lets look
at edge a-b */ if (es.count({a, b})) { /* // seen in
same order */ int v = es[{a, b}]; g[u].push_back({v,
true}); g[v].push_back({u, true}); } else if (es.count({
b, a})) { /* // seen in different order */ int v = es[{
b, a}]; g[u].push_back({v, false}); g[v].push_back({u,
false}); } else { /* // not seen yet */ es[{a,b}] = u; }
} } /* // Perform BFS to find which faces should be
flipped */ vector<bool> vis(n, false), flip(n); flip[0] =
false; queue<int> q; q.push(0); while (!q.empty()) {
int u = q.front(); q.pop(); for (edge e : g[u]) { if (!
vis[e.v]) { vis[e.v] = true; /* // If the edge was in
the same order, // exactly one of the two should be
flipped */ flip[e.v] = (flip[u] ^ e.same); q.push(e.v);
} } } /* Actually perform the flips */ for (int u = 0; u
< n; u++) if (flip[u]) { reverse(fs[u].begin(), fs[u].
end()); } return fs; } /* // O(n^2), O(n) faces in the
hull */ struct CH3D { struct face { int a, b, c; /* //
the number of three points on one face of the convex

```

```

hull */ bool ok; /* // whether the face belongs to the
face on the final convex hull */ }; int n; /* // initial
vertex number */ vector<p3> P; int num; /* // convex
hull surface triangle number */ vector<face> F; /* //
convex surface triangles */ vector<vector<int>> g; void
init(vector<p3> p) { P = p; n = p.size(); F.resize(8 * n
+ 1); g.resize(n + 1, vector<int> (n + 1)); } double
len(p3 a) { return sqrt(a | a); } p3 cross(const p3 &a,
const p3 &b, const p3 &c) { return (b - a) * (c - a); }
double area(p3 a, p3 b, p3 c) { return len((b - a) * (c
- a)); } double volume(p3 a, p3 b, p3 c, p3 d) { return
(b - a) * (c - a) | (d - a); } /* // positive: p3 in the
same direction */ double dblcmp(p3 &p, face &f) { p3 m
= P[f.b] - P[f.a]; p3 n = P[f.c] - P[f.a]; p3 t = p - P[
f.a]; return (m * n) | t; } void deal(int p, int a, int
b) { int f = g[a][b]; /* // search for another plane
adjacent to the edge */ face add; if (F[f].ok) { if (
dblcmp(P[p], F[f]) > eps) dfs(p, f); else { add.a = b;
add.b = a; add.c = p; /* // pay attention to the order
here, to be right-handed */ add.ok = true; g[p][b] = g[a
][p] = g[b][a] = num; F[num++] = add; } } } /* //
recursively search all faces that should be removed from
the convex hull */ void dfs(int p, int now) { F[now].ok
= 0; deal(p, F[now].b, F[now].a); deal(p, F[now].c, F[
now].b); deal(p, F[now].a, F[now].c); } bool same(int s,
int t) { p3 &a = P[F[s].a]; p3 &b = P[F[s].b]; p3 &c =
P[F[s].c]; return fabs(volume(a, b, c, P[F[t].a])) < eps
&& fabs(volume(a, b, c, P[F[t].b])) < eps && fabs(
volume(a, b, c, P[F[t].c])) < eps; } /* // building a 3D
convex hull */ void create_hull() { int i, j, tmp; face
add; num = 0; if (n < 4) return; /* // ensure that the
first four points are not coplanar */ bool flag = true;
for (i = 1; i < n; i++) { if (len(P[0] - P[i]) > eps) {
swap(P[1], P[i]); flag = false; break; } } if (flag)
return; flag = true; /* // make the first three points
not collinear */ for (i = 2; i < n; i++) { if (len((P[0]
- P[1]) * (P[1] - P[i])) > eps) { swap(P[2], P[i]);
flag = false; break; } } if (flag) return; flag = true;
/* // make the first four points not coplanar */ for (
int i = 3; i < n; i++) { if (fabs((P[0] - P[1]) * (P[1]
- P[2]) | (P[0] - P[i])) > eps) { swap(P[3], P[i]); flag
= false; break; } } if (flag) return; for (i = 0; i <
4; i++) { add.a = (i + 1) % 4; add.b = (i + 2) % 4; add.
c = (i + 3) % 4; add.ok = true; if (dblcmp(P[i], add) >
0) swap(add.b, add.c); g[add.a][add.b] = g[add.b][add.c]
= g[add.c][add.a] = num; F[num++] = add; } for (i = 4; i

```

```

< n; i++) { for (j = 0; j < num; j++) { if (F[j].ok &&
dblcmp(P[i], F[j]) > eps) { dfs(i, j); break; } } } tmp
= num; for (i = num = 0; i < tmp; i++) if (F[i].ok) F[
num++] = F[i]; } double surface_area() { double res = 0;
if (n == 3) { p3 p = cross(P[0], P[1], P[2]); res = len
(p) / 2.0; return res; } for (int i = 0; i < num; i++) {
res += area(P[F[i].a], P[F[i].b], P[F[i].c]); } return
res / 2.0; } double volume() { double res = 0; p3 tmp(0,
0, 0); for (int i = 0; i < num; i++) { res += volume(tmp
, P[F[i].a], P[F[i].b], P[F[i].c]); } return fabs(res /
6.0); } int number_of_triangles() { /* // number of
surface triangles */ return num; } int
number_of_polygons() { /* // number of surface polygons
*/ int i, j, res, flag; for (i = res = 0; i < num; i++)
{ flag = 1; for (j = 0; j < i; j++) { if (same(i, j)) {
flag = 0; break; } } res += flag; } return res; } p3
centroid() { /* // center of gravity */ p3 ans(0, 0, 0),
o(0, 0, 0); double all = 0; for (int i = 0; i < num; i
++) { double vol = volume(o, P[F[i].a], P[F[i].b], P[F[i
].c]); ans = ans + (o + P[F[i].a] + P[F[i].b] + P[F[i].c
]) / 4.0 * vol; all += vol; } ans = ans / all; return
ans; } double point_to_face_distance(p3 p, int i) {
return fabs(volume(P[F[i].a], P[F[i].b], P[F[i].c], p) /
len((P[F[i].b] - P[F[i].a]) * (P[F[i].c] - P[F[i].a])))
; } } /* // given the radius of the sphere, latitude
and longitude of a point in degrees // return the 3D
coordinates of the point on the sphere assuming the
sphere is centered at the origin */ p3 get_sphere(double
r, double lat, double lon) { lat *= PI / 180, lon *= PI
/ 180; return {r * cos(lat) * cos(lon), r * cos(lat) *
sin(lon), r * sin(lat)}; } int sphere_line_intersection(
p3 o, double r, line3d l, pair<p3,p3> &out) { double h2
= r * r - l.dist2(o); if (h2 < 0) return 0; /* // the
line doesnt touch the sphere */ p3 p = l.proj(o); p3 h =
l.d * sqrt(h2) / abs(l.d); /* // vector parallel to l, of
length h */ out = {p - h, p + h}; return 1 + (h2 > 0);
} /* // The shortest distance between two points A and B
on a sphere (0, r) is // given by travelling along
plane OAB and on the surface of the sphere. It is called
the great-circle distance // if a and b are outside the
sphere, then it will give the distance between their
projections on the sphere */ double great_circle_dist(p3
o, double r, p3 a, p3 b) { /* // s = r * theta */
return r * get_angle(a - o, b - o); } /* // Assume that
the sphere is centered at the origin // We will call a
segment [AB] valid if A and B are not // opposite each

```



```

other on the sphere */ bool validSegment(p3 a, p3 b) {
return a * b != zero || (a | b) > 0; } bool
proper_intersection(p3 a, p3 b, p3 c, p3 d, p3 &out) {
p3 ab = a * b, cd = c * d; /* // normals of planes OAB
and OCD */ int oa = sign(cd | a), ob = sign(cd | b), oc
= sign(ab | c), od = sign(ab | d); out = ab * cd * od;
/* // four multiplications => careful with overflow! */
return (oa != ob && oc != od && oa != oc); } /* //
Assume that the sphere is centered at the origin */ bool
point_on_sphere_segment(p3 a, p3 b, p3 p) { p3 n = a*b;
if (n == zero) return a * p == zero && (a | p) > 0;
return (n | p) == 0 && (n | a * p) >= 0 && (n | b * p)
<= 0; } struct DirectionSet : vector<p3> { using vector
::vector; /* // import constructors */ void insert(p3 p)
{ for (p3 q : *this) if (p*q == zero) return; push_back(
p); } }; /* // Assume that the sphere is centered at the
origin // it returns the direction vectors of the
intersection points // to get the actual points, scale
the direction vectors to the radius of the sphere */
DirectionSet segment_intersection_on_sphere(p3 a
, p3 b, p3 c, p3 d) { assert(validSegment(a, b) &&
validSegment(c, d)); p3 out; if (proper_intersection(a,
b, c, d, out)) return {out}; DirectionSet s; if (
point_on_sphere_segment(c, d, a)) s.insert(a); if (
point_on_sphere_segment(c, d, b)) s.insert(b); if (
point_on_sphere_segment(a, b, c)) s.insert(c); if (
point_on_sphere_segment(a, b, d)) s.insert(d); return s;
} /* // small angle between spherical segments ab and
ac // assume that the sphere is centered at the origin
// all points a, b, c are on the sphere */ double
angle_on_sphere(p3 a, p3 b, p3 c) { return get_angle(a *
b, a * c); } /* // oriented angle between spherical
segments ab and ac // that is how much we rotate
counterclockwise to get from ab to ac // assume that the
sphere is centered at the origin // all points a, b, c
are on the sphere */ double oriented_angle_on_sphere(p3
a, p3 b, p3 c) { if ((a * b | c) >= 0) return
angle_on_sphere(a, b, c); else return 2 * PI -
angle_on_sphere(a, b, c); } /* // Assume that the sphere
is centered at the origin // the polygon is simple and
given in counterclockwise order // for each consecutive
pair of points, the counterclockwise left // part of the
segment is considered to be inside the surface area
that the polygon encloses // if the polygon is outside
the sphere, the projection of the polygon on the sphere
will be considered */ double

```

```

area_on_the_surface_of_the_sphere(double r, vector<p3> p
) { int n = p.size(); double sum = -(n - 2) * PI; for (
int i = 0; i < n; i++) { sum += oriented_angle_on_sphere
(p[(i + 1) % n], p[(i + 2) % n], p[i]); } return r * r *
sum; } /* // Assume that 0 is the origin // it returns
0 if 0 is outside the polyhedron // 1 if 0 is inside the
polyhedron, and the vector areas of the faces are
oriented towards the outside; // 1 if 0 is inside the
polyhedron, and the vector areas of the faces are
oriented towards the inside. */ int winding_number_3D(
vector<vector<p3>> fs) { double sum = 0; for (vector<p3>
f : fs) { sum += remainder(
area_on_the_surface_of_the_sphere(1, f), 4 * PI); }
return round(sum / (4 * PI)); } struct sphere { p3 c;
double r; sphere() {} sphere(p3 c, double r) : c(c), r(r
) {} }; /* // spherical cap is a portion of a sphere cut
off by a plane */ struct spherical_cap { p3 c; double r
; spherical_cap() {} spherical_cap(p3 c, double r) : c(c
), r(r) {} /* // angle th is the polar angle between the
rays from the center of the sphere to one edge of the
cap // and orthogonal line from the center of the sphere
to the plane of the cap // height of the cap (just like
real world cap) */ double height(double th) { return r
* (1 - cos(th)); } /* // radius of the base of the cap
*/ double base_radius(double th) { return r * sin(th); }
/* // volume of the cap */ double volume(double th) {
double h = height(th); return PI * h * h * (3 * r - h) /
3.0; } /* // surface area of the cap */ double
surface_area(double th) { double h = height(th); return
2 * PI * r * h; } }; /* // returns the sphere passing
through four points */ sphere circumscribed_sphere(p3 a,
p3 b, p3 c, p3 d) { assert( sign(plane(a, b, c).side(d)
) != 0); plane u = plane(a - b, (a + b) / 2); plane v =
plane(b - c, (b + c) / 2); plane w = plane(c - d, (c + d
) / 2); assert(!is_parallel(u, v)); assert(!is_parallel(
v, w)); line3d l1(u, v), l2(v, w); assert( sign(dist(l1,
l2)) == 0); p3 C = closest_on_l1(l1, l2); return sphere
(C, abs(C - a)); } /* // it won't work if one sphere is
totally inside the other sphere // handle that case
separately // returns the surface area and volume of the
intersection */ pair<double, double>
sphere_sphere_intersection(sphere s1, sphere s2) {
double d = abs(s1.c - s2.c); if(sign(d - s1.r - s2.r) >=
0) return {0, 0}; /* // not intersecting */ /* // only
the distance matters, so we will now consider the
centers // of the big sphere to be (0, 0, 0) and (d, 0,

```

```

0) for the small sphere // we can transform the results
back to w.r.t the real centers if we want */ double R =
max(s1.r, s2.r); double r = min(s1.r, s2.r); double y =
R + r - d; double x = (R * R - r * r + d * d) / (2 * d);
/* // the intersecting plane is parallel to the yz
plane // with the above x value as its x coordinate */
double w = d * d - r * r + R * R; double a = sqrt(4 * d
* d * R * R - w * w) / (2.0 * d); /* // a is the radius
of the intersecting circle on the intersecting plane //
with center (x, 0) */ double h1 = R - x; double h2 = y -
h1; /* // h1 is the height of the intersecting
spherical cap of the big sphere // h2 is for the small
sphere // total volume of the whole intersection = sum
of the volumes of the spherical caps */ double volume =
PI * h1 * h1 * (3 * R - h1) / 3.0 + PI * h2 * h2 * (3 *
r - h2) / 3.0; /* // total surface area of the
intersecting spherical caps */ double surface_area = 2 *
PI * R * h1 + 2 * PI * r * h2; return make_pair(
surface_area, volume); } sphere
smallest_enclosing_sphere(vector<p3> p) { int n = p.size
(); p3 c(0, 0, 0); for(int i = 0; i < n; i++) c = c + p[
i]; c = c / n; double ratio = 0.1; int pos = 0; int it =
100000; while (it--) { pos = 0; for (int i = 1; i < n;
i++) { if(sq(c - p[i]) > sq(c - p[pos])) pos = i; } c =
c + (p[pos] - c) * ratio; ratio *= 0.998; } return
sphere(c, abs(c - p[pos])); } /* // it returns the angle
of the spherical cap that is formed by the intersection
of all tangents */ double tangent_from_point_to_sphere(
p3 p, sphere s) { double d = abs(p - s.c); if (sign(d -
s.r) < 0) return -1; /* // inside the sphere, so no
tangent */ if (sign(d - s.r) == 0) return -2; /* // on
the sphere, handle separately */ double tangent_length =
sqrt(d * d - s.r * s.r); double th = acos(s.r / d);
return th; }

```

7.3 3D

```

template <typename DT> class Point { public: DT x, y, z;
Point(){}; Point(DT x, DT y, DT z) : x(x), y(y), z(z)
{} template <typename X> Point(Point<X> p) : x(p.x), y(p
.y), z(p.z) {} Point operator + (const Point &rhs) const
{ return Point(x + rhs.x, y + rhs.y, z + rhs.z); }
Point operator - (const Point &rhs) const { return Point
(x - rhs.x, y - rhs.y, z - rhs.z); } Point operator * (
DT M) const { return Point(M * x, M * y, M * z); } Point
operator / (DT M) const { return Point(x / M, y / M, z
/ M); } /* // cross product */ Point operator & (const

```

```
Point &rhs) const { return Point(y * rhs.z - z * rhs.y, z *
    rhs.x - x * rhs.z, x * rhs.y - y * rhs.x); } /* // dot
    product */ DT operator ^ (const Point &rhs) const {
    return x * rhs.x + y * rhs.y + z * rhs.z; } bool
    operator == (const Point &rhs) const { return x == rhs.x
    && y == rhs.y && z == rhs.z; } bool operator != (const
    Point &rhs) const { return !(*this == rhs); } friend std
    ::istream& operator >> (std::istream &is, Point &p) {
    return is >> p.x >> p.y >> p.z; } friend std::ostream&
    operator << (std::ostream &os, const Point &p) { return
    os << p.x << " " << p.y << " " << p.z; } friend DT DisSq
    (const Point &a, const Point &b) { return (a.x - b.x)*(a
    .x - b.x) + (a.y - b.y)*(a.y - b.y) + (a.z - b.z)*(a.z -
    b.z); } };
```

```
optional < Point <double> > ray_intersects_triangle(
    const Point<double> &origin, const Point<double> &
    ray_vector, const array <Point<double>, 3> &triangle) {
    constexpr double epsilon = std::numeric_limits<double>::
    epsilon(); auto [A, B, C] = triangle; Point<double>
    edge1 = B - A; Point<double> edge2 = C - A; Point<double>
    > ray_cross_e2 = ray_vector & edge2; double det = edge1
    ^ ray_cross_e2; if (det > -epsilon && det < epsilon)
    return {}; /* // Ray is parallel to this triangle. */
    double inv_det = 1.0 / det; Point<double> s = ray_origin
    - A; double u = inv_det * (s ^ ray_cross_e2); if (u < 0
    || u > 1) return {}; Point<double> s_cross_e1 = s &
    edge1; double v = inv_det * (ray_vector ^ s_cross_e1);
    if (v < 0 || u + v > 1) return {}; /* // Compute t to
    find the intersection Point */ double t = inv_det * (
    edge2 ^ s_cross_e1); if (t > epsilon) return ray_origin
    + ray_vector * t; /* // ray intersection */ else return
    {}; /* // Line intersection but not ray intersection */
    } /* // HOW TO IMPLEMENT */ auto tmp =
    ray_intersects_triangle (origin, ray, v[i]); // if (tmp.
    has_value ()) Point <double> intersection_point = tmp.
    value (); */
```

7.4 3d hull

```
#define LD long double const LD EPS = 1e-9; const LD PI
= acos(-1); LD Sq(LD x) {return x * x;} LD Acos(LD x){
return acos(min(1.0L,max(-1.0L,x)));} LD Asin(LD x){
return asin(min(1.0L,max(-1.0L,x)));} LD Sqrt(LD x) {
return sqrt(max(0.0L, x));} int dcmp(LD x) { if(fabs(x)
< EPS) return 0; return (x > 0.0 ? +1 : -1); } struct
Point3 { LD x, y, z; Point3() {} Point3(LD a, LD b, LD c
```

```
) : x(a), y(b), z(c){} void operator=(const Point3& a) {
x=a.x,y=a.y,z=a.z; } Point3 operator+(Point3 a) {
Point3 p{x + a.x, y + a.y, z + a.z}; return p; } Point3
operator-(Point3 a) { Point3 p{x - a.x, y - a.y, z - a.z
}; return p; } Point3 operator*(LD a) { return Point3(x*
a,y*a,z*a); } Point3 operator/(LD a) { assert(a > EPS);
Point3 p{x/a, y/a, z/a}; return p; } LD& operator[](int
a) { if (a == 0) return x; if (a == 1) return y; if (a
== 2) return z; assert(false); } bool IsZero() { return
abs(x)<EPS&& abs(y)<EPS && abs(z) < EPS; } bool operator
==(Point3 a) { return (*this - a).IsZero(); } LD dot(
Point3 a) { return x * a.x + y * a.y + z * a.z; } LD
Norm() { return Sqrt(x * x + y * y + z * z); } LD SqNorm
() { return x * x + y * y + z * z; } void NormalizeSelf
() { *this = *this/Norm(); } Point3 Normalize() { Point3
res(*this); res.NormalizeSelf(); return res; } LD Dis(
Point3 a) { return (*this - a).Norm(); } pair<LD, LD>
SphericalAngles() { return {atan2(z, Sqrt(x*x+y*y)), atan2
(y,x)}; } LD Area(Point3 p) { return Norm() * p.Norm() *
sin(Angle(p)) / 2; } /* LD Angle(Point3 p) { LD a =
Norm(), b = p.Norm(), c = Dis(p); return Acos((a*a+b*b-c
*c)/(2*a*b)); } */ LD Angle(Point3 b) { Point3 a(*this);
return Acos(abs(a.dot(b))/a.Norm()/b.Norm()); } LD
Angle(Point3 p, Point3 q){return p.Angle(q);} Point3
cross(Point3 p) { Point3 q(*this); return {q[1]*p[2] - q
[2]*p[1], q[2]*p[0] - q[0] * p[2], q[0] * p[1] - q[1] *
p[0]}; } bool LexCmp(Point3& a, const Point3& b) { if (
abs(a.x - b.x) > EPS) { return a.x < b.x;} if (abs(a.y -
b.y) > EPS) { return a.y < b.y;} return a.z < b.z; } };
typedef vector<Point3> face; typedef vector<Point3>
edge; typedef vector<face> hull; #define INSIDE (-1) #
define ON (0) #define OUTSIDE (1) int side(Point3 a,
Point3 b, Point3 c, Point3 p){ Point3 norm = (b-a).cross
(c-a); Point3 me = p-a; return dcmp(me.dot(norm)); }
hull find_hull(vector<Point3> P) { random_shuffle(P.
begin(), P.end()); int n = P.size(); for(int j = 2; j <
n; j++) { Point3 n = (P[1]-P[0]).cross(P[j]-P[0]); if(n.
Norm() > EPS) {swap(P[j], P[2]);break;} } for(int j = 3;
j < n; j++) { if(side(P[0],P[1],P[2],P[j])) { swap(P[j
], P[3]); break; } } if(side(P[0],P[1],P[2],P[3]) ==
OUTSIDE) swap(P[0], P[1]); hull H{ {P[0],P[1],P[2]}, {P
[0],P[3],P[1]}, {P[0],P[2],P[3]}, {P[3],P[2],P[1]}}; auto
make_degrees = [&](const hull& H) { map<edge,int> ans;
for(const auto & f : H) { for(int i = 0; i < 3; i++){
Point3 a = f[i], b = f[(i+1)%3]; ans[{a,b}]++; } }
return ans; }; for(int j = 4; j < n; j++) { hull H2; H2.
```

```
reserve((int)H.size()); vector<face> plane; for(const
auto & f : H) { int s = side(f[0],f[1],f[2],P[j]); if (s
== INSIDE || s == ON) H2.push_back(f); } /* //For any
edge that now only has 1 incident //face (it's other
face deleted) add a new //face with this vertex and that
edge. */ map<edge, int> D = make_degrees(H2); const
auto tmp = H2; for (const auto & f : tmp) { for(int i =
0; i < 3; i++) { Point3 a = f[i], b = f[(i+1)%3]; int d
= D[{a,b}] + D[{b,a}]; if (d==1) H2.push_back({a, P[j],
b}); } } H = H2; } return H; }
```

7.5 ClosestPairOfPoints

```
/* ///Gives squared Distance /// O(n log n) */ long long
ClosestPair(vector<pair<int, int>> pts) { int n = pts.
size(); sort(pts.begin(), pts.end()); set<pair<int, int
>> s; long long best_dist = 1e18; int j = 0; for (int i
= 0; i < n; ++i) { int d = ceil(sqrt(best_dist)); while
(pts[i].first - pts[j].first >= best_dist) { s.erase({
pts[j].second, pts[j].first}); j += 1; } auto it1 = s.
lower_bound({pts[i].second - d, pts[i].first}); auto it2
= s.upper_bound({pts[i].second + d, pts[i].first}); for
(auto it = it1; it != it2; ++it) { int dx = pts[i].
first - it->second; int dy = pts[i].second - it->first;
best_dist = min(best_dist, 1LL * dx * dx + 1LL * dy * dy
); } s.insert({pts[i].second, pts[i].first}); } return
best_dist; }
```

7.6 MinDisSquares

```
typedef long double ld; const ld eps = 1e-12; int cmp(ld
x, ld y = 0, ld tol = eps) { return (x <= y + tol) ? (
x + tol < y) ? -1 : 0 : 1; } struct point{ ld x, y;
point(ld a, ld b) : x(a), y(b) {} point() {} }; struct
square{ ld x1, x2, y1, y2, a, b, c; point edges[4];
square(ld _a, ld _b, ld _c) { a = _a, b = _b, c = _c; x1
= a - c * 0.5; x2 = a + c * 0.5; y1 = b - c * 0.5; y2 =
b + c * 0.5; edges[0] = point(x1, y1); edges[1] = point
(x2, y1); edges[2] = point(x2, y2); edges[3] = point(x1,
y2); } }; ld min_dist(point &a, point &b){ ld x = a.x
- b.x, y = a.y - b.y; return sqrt(x * x + y * y); } bool
point_in_box(square s1, point p) { if (cmp(s1.x1, p.x)
!= 1 && cmp(s1.x2, p.x) != -1 && cmp(s1.y1, p.y) != 1 &&
cmp(s1.y2, p.y) != -1) return true; return false; }
bool inside(square &s1, square &s2) { for(int i = 0; i <
4; ++i) if(point_in_box(s2, s1.edges[i])) return true;
return false; } bool inside_vert(square &s1, square &s2)
{ if((cmp(s1.y1, s2.y1) != -1 && cmp(s1.y1, s2.y2) !=
```

```

1) || (cmp(s1.y2, s2.y1) != -1 && cmp(s1.y2, s2.y2) !=
1)) return true; return false; } bool inside_hori(square
&s1, square &s2) { if ((cmp(s1.x1, s2.x1) != -1 && cmp(
s1.x1, s2.x2) != 1) || (cmp(s1.x2, s2.x1) != -1 && cmp(
s1.x2, s2.x2) != 1)) return true; return false; } ld
min_dist(square &s1, square &s2) { if (inside(s1, s2) ||
inside(s2, s1)) return 0; ld ans = 1e100; for (int i =
0; i < 4; ++i) for (int j = 0; j < 4; ++j) ans = min(ans
, min_dist(s1.edges[i], s2.edges[j])); if (inside_hori(
s1, s2) || inside_hori(s2, s1)) { if (cmp(s1.y1, s2.y2)
!= -1) ans = min(ans, s1.y1 - s2.y2); else if (cmp(s2.y1
, s1.y2) != -1) ans = min(ans, s2.y1 - s1.y2); } if (
inside_vert(s1, s2) || inside_vert(s2, s1)) { if (cmp(s1
.x1, s2.x2) != -1) ans = min(ans, s1.x1 - s2.x2); else
if(cmp(s2.x1, s1.x2) != -1) ans = min(ans, s2.x1 - s1.x2
); } return ans; }

```

7.7 Pick's Theorem

```

struct Point{ long long x, y; Point(){ } Point(long long
x, long long y) : x(x), y(y){ } }; /* /// twice the area
of polygon */ long long double_area(Point poly[], int n)
{ long long res = 0; for (int i = 0, j = n - 1; i < n; j
= i++){ res += ((poly[j].x + poly[i].x) * (poly[j].y -
poly[i].y)); } return abs(res); } /* /// number of
lattice points strictly on polygon border */ long long
on_border(Point poly[], int n){ long long res = 0; for (
int i = 0, j = n - 1; i < n; j = i++){ res += __gcd(abs(
poly[i].x - poly[j].x), abs(poly[i].y - poly[j].y)); }
return res; } /* /// number of lattice points strictly
inside polygon */ long long interior(Point poly[], int n
){ long long res = 2 + double_area(poly, n) - on_border(
poly, n); return res / 2; }

```

7.8 convex

```

/* /// minkowski sum of two polygons in O(n) */ Polygon
minkowskiSum(Polygon A, Polygon B) { int n = A.size(), m
= B.size(); rotate(A.begin(), min_element(A.begin(), A.
end()), A.end()); rotate(B.begin(), min_element(B.begin
(), B.end()), B.end()); A.push_back(A[0]); B.push_back(B
[0]); for (int i = 0; i < n; i++) A[i] = A[i + 1] - A[i
]; for (int i = 0; i < m; i++) B[i] = B[i + 1] - B[i];
Polygon C(n + m + 1); C[0] = A.back() + B.back(); merge(
A.begin(), A.end() - 1, B.begin(), B.end() - 1, C.begin
() + 1, polarComp(Point(0, 0), Point(0, -1))); for (int
i = 1; i < C.size(); i++) C[i] = C[i] + C[i - 1]; C.
pop_back(); return C; } /* /// finds the rectangle with

```

```

minimum area enclosing a convex polygon and // the
rectangle with minimum perimeter enclosing a convex
polygon // Tf Ti Same */
pair<Tf, Tf> rotatingCalipersBoundingBox(const Polygon &
p) { using Linear::distancePointLine; int n = p.size();
int l = 1, r = 1, j = 1; Tf area = 1e100; Tf perimeter =
1e100; for (int i = 0; i < n; i++) { Point v = (p[(i +
1) % n] - p[i]) / length(p[(i + 1) % n] - p[i]); while (
dcmp(dot(v, p[r % n] - p[i]) - dot(v, p[(r + 1) % n] - p
[i])) < 0) r++; while (j < r || dcmp(cross(v, p[j % n] -
p[i]) - cross(v, p[(j + 1) % n] - p[i])) < 0) j++;
while (1 < j || dcmp(dot(v, p[l % n] - p[i]) - dot(v, p
[(l + 1) % n] - p[i])) > 0) l++; Tf w = dot(v, p[r % n]
- p[i]) - dot(v, p[l % n] - p[i]); Tf h =
distancePointLine(p[j % n], Line(p[i], p[(i + 1) % n]));
area = min(area, w * h); perimeter = min(perimeter, 2 *
w + 2 * h); } return make_pair(area, perimeter); } /*
// returns the left side of polygon u after cutting it
by ray a->b */
Polygon cutPolygon(Polygon u, Point a, Point b) { using
Linear::lineLineIntersection; using Linear::onSegment;
Polygon ret; int n = u.size(); for (int i = 0; i < n; i
++) { Point c = u[i], d = u[(i + 1) % n]; if (dcmp(cross
(b - a, c - a)) >= 0) ret.push_back(c); if (dcmp(cross(b
- a, d - c)) != 0) { Point t; lineLineIntersection(a, b
- a, c, d - c, t); if (onSegment(t, Segment(c, d))) ret
.push_back(t); } } return ret; } /* // returns true if
point p is in or on triangle abc */
bool pointInTriangle(Point a, Point b, Point c, Point p)
{ return dcmp(cross(b - a, p - a)) >= 0 && dcmp(cross(c
- b, p - b)) >= 0 && dcmp(cross(a - c, p - c)) >= 0; }
/* // pt must be in ccw order with no three collinear
points // returns inside = -1, on = 0, outside = 1 */
int pointInConvexPolygon(const Polygon &pt, Point p) {
int n = pt.size(); assert(n >= 3); int lo = 1, hi = n -
1; while (hi - lo > 1) { int mid = (lo + hi) / 2; if (
dcmp(cross(pt[mid] - pt[0], p - pt[0])) > 0) lo = mid;
else hi = mid; } bool in = pointInTriangle(pt[0], pt[lo
], pt[hi], p); if (!in) return 1; if (dcmp(cross(pt[lo]
- pt[lo - 1], p - pt[lo - 1])) == 0) return 0; if (dcmp(
cross(pt[hi] - pt[lo], p - pt[lo])) == 0) return 0; if (
dcmp(cross(pt[hi] - pt[(hi + 1) % n], p - pt[(hi + 1) %
n])) == 0) return 0; return -1; } /* // Extreme Point
for a direction is the farthest point in that direction
// u is the direction for extremeness */

```

```

int extremePoint(const Polygon &poly, Point u) { int n =
(int)poly.size(); int a = 0, b = n; while (b - a > 1) {
int c = (a + b) / 2; if (dcmp(dot(poly[c] - poly[(c +
1) % n], u)) >= 0 && dcmp(dot(poly[c] - poly[(c - 1 + n)
% n], u)) >= 0) { return c; } bool a_up = dcmp(dot(poly
[(a + 1) % n] - poly[a], u)) >= 0; bool c_up = dcmp(dot(
poly[(c + 1) % n] - poly[c], u)) >= 0; bool a_above_c =
dcmp(dot(poly[a] - poly[c], u)) > 0; if (a_up && !c_up)
b = c; else if (!a_up && c_up) a = c; else if (a_up &&
c_up) { if (a_above_c) b = c; else a = c; } else { if (!
a_above_c) b = c; else a = c; } } if (dcmp(dot(poly[a] -
poly[(a + 1) % n], u)) > 0 && dcmp(dot(poly[a] - poly[(
a - 1 + n) % n], u)) > 0) return a; return b % n; } /*
// For a convex polygon p and a line l, returns a list
of segments // of p that touch or intersect line l. //
the i'th segment is considered (p[i], p[(i + 1) modulo |
p|]) // #1 If a segment is collinear with the line, only
that is returned // #2 Else if l goes through i'th
point, the i'th segment is added // Complexity: O(lg |p
|) */
vector<int> lineConvexPolyIntersection(const Polygon &p,
Line l) { assert((int)p.size() >= 3); assert(l.a != l.b
); int n = p.size(); vector<int> ret; Point v = l.b - l.
a; int lf = extremePoint(p, rotate90(v)); int rt =
extremePoint(p, rotate90(v) * Ti(-1)); int olf = orient(
l.a, l.b, p[lf]); int ort = orient(l.a, l.b, p[rt]); if
(!olf || !ort) { int idx = (!olf ? lf : rt); if (orient(
l.a, l.b, p[(idx - 1 + n) % n]) == 0) ret.push_back((idx
- 1 + n) % n); else ret.push_back(idx); return ret; }
if (olf == ort) return ret; for (int i = 0; i < 2; ++i)
{ int lo = i ? rt : lf; int hi = i ? lf : rt; int olo =
i ? ort : olf; while (true) { int gap = (hi - lo + n) %
n; if (gap < 2) break; int mid = (lo + gap / 2) % n; int
omid = orient(l.a, l.b, p[mid]); if (!omid) { lo = mid;
break; } if (omid == olo) lo = mid; else hi = mid; }
ret.push_back(lo); } return ret; } /* // Calculate [ACW,
CW] tangent pair from an external point */
constexpr int CW = -1, ACW = 1; bool isGood(Point u,
Point v, Point Q, int dir) { return orient(Q, u, v) != -
dir; }
Point better(Point u, Point v, Point Q, int dir) {
return orient(Q, u, v) == dir ? u : v; }
Point pointPolyTangent(const Polygon &pt, Point Q, int
dir, int lo, int hi) { while (hi - lo > 1) { int mid = (
lo + hi) / 2; bool pvs = isGood(pt[mid], pt[mid - 1], Q,
dir); bool nxt = isGood(pt[mid], pt[mid + 1], Q, dir);

```

```

if (pvs && nxt) return pt[mid]; if (!(pvs || nxt)) {
Point p1 = pointPolyTangent(pt, Q, dir, mid + 1, hi);
Point p2 = pointPolyTangent(pt, Q, dir, lo, mid - 1);
return better(p1, p2, Q, dir); } if (!pvs) { if (orient(
Q, pt[mid], pt[lo]) == dir) hi = mid - 1; else if (
better(pt[lo], pt[hi], Q, dir) == pt[lo]) hi = mid - 1;
else lo = mid + 1; } if (!nxt) { if (orient(Q, pt[mid],
pt[lo]) == dir) lo = mid + 1; else if (better(pt[lo], pt
[hi], Q, dir) == pt[lo]) hi = mid - 1; else lo = mid +
1; } } Point ret = pt[lo]; for (int i = lo + 1; i <= hi;
i++) ret = better(ret, pt[i], Q, dir); return ret; } /*
// [ACW, CW] Tangent */
pair<Point, Point> pointPolyTangents(const Polygon &pt,
Point Q) { int n = pt.size(); Point acw_tan =
pointPolyTangent(pt, Q, ACW, 0, n - 1); Point cw_tan =
pointPolyTangent(pt, Q, CW, 0, n - 1); return make_pair(
acw_tan, cw_tan); }

```

8 Misc

8.1 All Macros

```

//#pragma GCC optimize("Ofast")
//#pragma GCC optimization ("O3")
//#pragma comment(linker, "/stack:200000000")
//#pragma GCC optimize("unroll-loops")
//#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,
abm,mmx,avx,tune=native")
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//find_by_order(k) --> returns iterator to the kth
largest element counting from 0
//order_of_key(val) --> returns the number of items
in a set that are strictly smaller than our item
os.erase(os.find_by_order(os.order_of_key(v[i])))
==> to erase i-th element from ordered multiset
template <typename DT>
using ordered_set = tree<DT, null_type, less<DT>,
rb_tree_tag,tree_order_statistics_node_update>;
mod = {1500000007, 1500000013, 1500000023, 1500000057,
1500000077};
struct custom_hash {
static uint64_t splitmix64 (uint64_t x) {
x += 0x9e3779b97f4a7c15;
x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
return x ^ (x >> 31);
}

```

```

}
size_t operator () (uint64_t x) const {
static const uint64_t FIXED_RANDOM = chrono::
steady_clock::now().time_since_epoch().count();
return splitmix64 (x + FIXED_RANDOM);
}
} Rng;
/* for StressTesting
mt19937 rng(random_device{}()); int randomInt(int low,
int high) { uniform_int_distribution<int> dist(low, high
); return dist(rng); } vector<int> permutation(int n){
vector<int> p(n); iota(p.begin(), p.end(), 1); shuffle(p
.begin(), p.end(), rng); return p; }
*/
typedef gp_hash_table<int, int, custom_hash> gp;
int leap_years(int y) { return y / 4 - y / 100 + y /
400; }
bool is_leap(int y) { return y % 400 == 0 || (y % 4 == 0
&& y % 100 != 0); }
bool __builtin_mul_overflow (type1 a, type2 b, type3 &
res)
cin.tie(0)->ios_base::sync_with_stdio(0);
int getWeekday (int day, int month, int year) {
if (month <= 2) {
month += 12;
year -= 1;
}
int f = (day + (13 * (month + 1)) / 5 + year + year /
4 - year / 100 + year / 400) % 7;
return f;
}

```

8.2 StressTest

```

#!/bin/bash
# Call as sh stress.sh ITERATIONS
g++ candidate.cpp -o candidate # candidate solution
g++ bruteforce.cpp -o bruteforce # bruteforce solution
g++ generator.cpp -o generator # test case generator
> all.txt
for i in $(seq 1 "$1") ; do
echo "Attempt $i/$1"
./generator > in.txt
echo "Attempt $i/$1" >> all.txt
cat < in.txt >> all.txt
./bruteforce < in.txt > out1.txt
./candidate < in.txt > out2.txt

```

```

diff -y out1.txt out2.txt > diff.txt
if [ $? -ne 0 ] ; then
echo -e "\nTest case:"
cat in.txt
echo -e "\nOutputs:"
cat diff.txt
break
fi
done
files=("in.txt" "out1.txt" "out2.txt" "diff.txt" "
candidate" "bruteforce" "generator")
for file in "${files[@]}"; do
rm "$file"
done

```


9 Equations and Formulas

9.1 Catalan Numbers, convolution and super

$$C_n = \frac{1}{n+1} \binom{2n}{n} \quad C_0 = 1, C_1 = 1 \text{ and } C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

The number of ways to completely parenthesize $n+1$ factors. The number of triangulations of a convex polygon with $n+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

Number of permutations of $1, \dots, n$ that avoid the pattern 123 (or any of the other patterns of length 3); that is, the number of permutations with no three-term increasing sub-sequence.

For $n = 3$, these permutations are 132, 213, 231, 312 and 321. $C_n^{(k)} = \frac{k+1}{n+k+1} \binom{2n+k}{n} S(m, n) = \frac{(2m)!(2n)!}{m!n!(m+n)!}$

$$C_n^{(k)} = \frac{(2n+k-1)(2n+k)}{n(n+k+1)} C_{n-1}^{(k)}$$

9.2 Stirling Numbers First Kind

The Stirling numbers of the first kind count permutations according to their number of cycles (counting fixed points as cycles of length one).

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1)$, where, $S(0, 0) = 1, S(n, 0) = S(0, n) = 0 \sum_{k=0}^n S(n, k) = n!$

The unsigned Stirling numbers may also be defined algebraically, as the coefficient of the rising factorial:

$$x^{\bar{n}} = x(x+1)\dots(x+n-1) = \sum_{k=0}^n S(n, k) x^k$$

Lets $[n, k]$ be the stirling number of the first kind, then

$$\left[n \atop k \right] = \sum_{0 \leq i_1 < i_2 < \dots < i_k < n} i_1 i_2 \dots i_k.$$

9.3 Stirling Numbers Second Kind

Stirling number of the second kind is the number of ways to partition a set of n objects into k non-empty subsets.

$S(n, k) = k \cdot S(n-1, k) + S(n-1, k-1)$, where $S(0, 0) = 1, S(n, 0) = S(0, n) = 0, S(n, 2) = 2^{n-1} - 1, S(n, k) \cdot k!$ = number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation.

$$S_r(n+1, k) = k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1)$$

Denote the n objects to partition by the integers $1, 2, \dots, n$. Define the reduced Stirling numbers of the second kind, denoted $S^d(n, k)$, to be the number of ways to partition the integers $1, 2, \dots, n$ into k nonempty subsets such that all elements in each subset have pairwise distance at least d . That is, for any integers i and j in a given subset, it is required that $|i - j| \geq d$. It has been shown that these numbers satisfy, $S^d(n, k) = S(n-d+1, k-d+1), n \geq k \geq d$

9.4 Other Combinatorial Identities

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}$$

$$\sum_{i=0}^k \binom{n+i}{i} = \sum_{i=0}^k \binom{n+i}{n} = \binom{n+k+1}{k}$$

$$n, r \in \mathbb{N}, n > r, \sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$$

$$\text{If } P(n) = \sum_{k=0}^n \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot P(k)$$

$$\text{If } P(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot P(k)$$

9.5 Different Math Formulas

Picks Theorem : $A = i + b/2 - 1$

Derangements : $d(i) = (i-1) \times (d(i-1) + d(i-2))$

9.6 GCD and LCM

if m is any integer, then $\gcd(a + m \cdot b, b) = \gcd(a, b)$

The gcd is a multiplicative function in the following sense: if a_1 and a_2 are relatively prime, then $\gcd(a_1 \cdot a_2, b) = \gcd(a_1, b) \cdot \gcd(a_2, b)$.

$$\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c)).$$

$$\text{lcm}(a, \gcd(b, c)) = \gcd(\text{lcm}(a, b), \text{lcm}(a, c)).$$

For non-negative integers a and b , where a and b are not both zero, $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

$$\gcd(a, b) = \sum_{k|a \text{ and } k|b} \phi(k)$$

$$\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$$

$$\sum_{k=1}^n \gcd(k, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n x^{\gcd(k, n)} = \sum_{d|n} x^d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2 = GPS(n-1) + 2 \cdot \sum_{d|n} \phi(d) \cdot \frac{n}{d}$$

$$\frac{n}{d} - n$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2$$

$$F(n) = \sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{(1 + \lfloor \frac{n}{l} \rfloor) (\lfloor \frac{n}{l} \rfloor)}{2} \right)^2 \sum_{d|l} \mu(d) l d$$