

Contents

	4.10 strongly connected component	14
1 Build and Snippet	1	5 String
1.1 Sublime Build	1	5.1 Aho
		5.2 KMP
2 Data Structures	1	5.3 Manacher
2.1 2D BIT	1	5.4 String Match FFT
2.2 BIT	1	5.5 Z
2.3 Beats	1	5.6 double hashing
2.4 Lazy Propagation	2	5.7 suffix array
2.5 MergeSortTree	3	
2.6 Mo With Update	4	6 DP
2.7 PST	4	6.1 CHT
2.8 Sparse Table	5	6.2 CatalanDp
2.9 Trie	5	6.3 DearrangementDP
2.10 segtree iterative	5	6.4 Li Chao Tree
2.11 sparse table 2D	6	6.5 SOS
		6.6 Grundy
3 Number Theory	6	7 Geometry
3.1 Chinese Remainder Theorem	6	7.1 2D everything
3.2 Eulers Totient Function	6	7.2 3D
3.3 FFT	6	7.3 MinDisSquares
3.4 Matrix	7	7.4 Picks Theorem
3.5 NOD and SOD	8	7.5 convex hull
3.6 Pollard rho	8	7.6 convex
3.7 Sieve	8	
3.8 XOR Basis	9	8 Misc
3.9 mobius function	9	8.1 All Macros
3.10 nCr	9	8.2 StressTest
3.11 ntt	9	8.3 gen
3.12 primality test	10	
3.13 prime counting function	10	9 Equations and Formulas
		9.1 Catalan Numbers
4 Graph	10	9.2 Stirling Numbers First Kind
4.1 BridgeTree	10	9.3 Stirling Numbers Second Kind
4.2 CD	11	9.4 Other Combinatorial Identities
4.3 DSU, MST	11	9.5 Different Math Formulas
4.4 Dinic	11	9.6 GCD and LCM
4.5 HLD	12	
4.6 LCA O(1)	13	
4.7 LCA O(n)	13	
4.8 block cut tree	13	
4.9 maximum bipartite matching hopcroft	14	

1 Build and Snippet

1.1 Sublime Build

```
{
"cmd" : ["g++ -std=c++20 -DLOCAL -Wall $file_name -o
$file_base_name && timeout 5s ./ $file_base_name<input.
txt> output.txt && rm $file_base_name"],
"selector" : "source.cpp",
"file_regex": "(\\. [ :]*):([0-9]+)?([0-9]+)??.*$",
"shell": true,
"working_dir" : "$file_path"
}
{
"shell_cmd": "g++ -std=c++23 \"$file\" -o \"
$file_base_name.exe\" && \"$file_base_name.exe\" <
input.txt > output.txt && del \"$file_base_name.exe
\\",
"working_dir": "$file_path",
"selector": "source.c++"
}
}
// interactive
"shell_cmd": "g++ -std=c++23 \"$file\" -o \"
$file_base_name.exe\" && start cmd /k \"$file_base_name.
exe\"",
```

2 Data Structures

2.1 2D BIT

```
const int N = 1008;
int bit[N][N], a[N][N], n, m, q;
void update(int x, int y, int val) {
    for (; x < N; x += -x & x)
        for (int j = y; j < N; j += -j & j) bit[x][j] += val;
}
int get(int x, int y) {
    int ans = 0;
    for (; x; x -= x & -x)
        for (int j = y; j; j -= j & -j) ans += bit[x][j];
    return ans;
}
int get(int x1, int y1, int x2, int y2) {
    return get(x2, y2) - get(x1 - 1, y2) - get(x2, y1 - 1)
        + get(x1 - 1, y1 - 1);
}
```

2.2 BIT

```
class BIT {
```

```
int *bin, N;

public:
    BIT(int n) : N(n + 1) {
        bin = new int[N + 1];
        memset(bin, 0, (N + 1) * sizeof(int));
    }
    void update(int id, int val) {
        id++;
        for (; id <= N; id += id & -id) bin[id] += val;
    }
    int helper(int id) {
        id++;
        int sum = 0;
        for (; id > 0; id -= id & -id) sum += bin[id];
        return sum;
    }
    int query(int l, int r) { return helper(r) - helper(l
        - 1); }
    ~BIT() { delete[] bin; }
};
```

2.3 Beats

```
class SegTreeBeats {
    const int INF = INT_MAX;
    const LL NEG_INF = LLONG_MIN;

    vector<LL> mx, mn, smx, smn, sum, add;
    vector<int> mxcnt, mncnt;
    int L, R;

    void applyMax(int u, LL x) {
        sum[u] += mncnt[u] * (x - mn[u]);
        if (mx[u] == mn[u]) mx[u] = x;
        if (smx[u] == mn[u]) smx[u] = x;
        mn[u] = x;
    }

    void applyMin(int u, LL x) {
        sum[u] -= mxcnt[u] * (mx[u] - x);
        if (mn[u] == mx[u]) mn[u] = x;
        if (smn[u] == mx[u]) smn[u] = x;
        mx[u] = x;
    }

    void applyAdd(int u, LL x, int tl, int tr) {
```

```
sum[u] += (tr - tl + 1) * x;
add[u] += x;
mx[u] += x, mn[u] += x;
if (smx[u] != NEG_INF) smx[u] += x;
if (smn[u] != INF) smn[u] += x;
}

void push(int u, int tl, int tr) {
    int lft = u << 1, ryt = lft | 1, mid = (tl + tr) >>
        1;
    if (add[u] != 0) {
        applyAdd(lft, add[u], tl, mid);
        applyAdd(ryt, add[u], mid + 1, tr);
        add[u] = 0;
    }
    if (mx[u] < mx[lft]) applyMin(lft, mx[u]);
    if (mx[u] < mx[ryt]) applyMin(ryt, mx[u]);

    if (mn[u] > mn[lft]) applyMax(lft, mn[u]);
    if (mn[u] > mn[ryt]) applyMax(ryt, mn[u]);
}

void merge(int u) {
    int lft = u << 1, ryt = lft | 1;
    sum[u] = sum[lft] + sum[ryt];

    mx[u] = max(mx[lft], mx[ryt]);
    smx[u] = max(smx[lft], smx[ryt]);
    if (mx[lft] != mx[ryt]) smx[u] = max(smx[u], min(mx[lft],
        mx[ryt]));
    mxcnt[u] =
        (mx[u] == mx[lft]) * mxcnt[lft] + (mx[u] == mx[ryt]) * mxcnt[ryt];

    mn[u] = min(mn[lft], mn[ryt]);
    smn[u] = min(smn[lft], smn[ryt]);
    if (mn[lft] != mn[ryt]) smn[u] = min(smn[u], max(mn[lft],
        mn[ryt]));
    mncnt[u] =
        (mn[u] == mn[lft]) * mncnt[lft] + (mn[u] == mn[ryt]) * mncnt[ryt];
}

void build(const vector<int>& a, int tl, int tr, int u) {
    if (tl == tr) {
```

```

    sum[u] = mn[u] = mx[u] = a[tl];
    mxcnt[u] = mncnt[u] = 1;
    smx[u] = NEG_INF;
    smn[u] = INF;
    return;
}
int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
build(a, tl, mid, lft);
build(a, mid + 1, tr, ryt);
merge(u);
}

public:
SegTreeBeats(const vector<int>& a) {
    int n = a.size();
    L = 0;
    R = n - 1;

    mx.resize(4 * n, 0);
    mn.resize(4 * n, 0);
    smx.resize(4 * n, NEG_INF);
    smn.resize(4 * n, INF);
    sum.resize(4 * n, 0);
    add.resize(4 * n, 0);
    mxcnt.resize(4 * n, 0);
    mncnt.resize(4 * n, 0);

    build(a, L, R, 1);
}
// a[i] = min(x, a[i]);
void minimize(int l, int r, LL x) { minimize(l, r, x, L, R, 1); }
// a[i] = max(x, a[i]);
void maximize(int l, int r, LL x) { maximize(l, r, x, L, R, 1); }
// a[i] = a[i] + x;
void increase(int l, int r, LL x) { increase(l, r, x, L, R, 1); }

LL getSum(int l, int r) { return getSum(l, r, L, R, 1); }
};

LL getMax(int l, int r) { return getMax(l, r, L, R, 1); }
};

```

```

private:
void minimize(int l, int r, LL x, int tl, int tr, int u) {
    if (l > tr || tl > r || mx[u] <= x) return;
    if (l <= tl && tr <= r && smx[u] < x) {
        applyMin(u, x);
        return;
    }
    push(u, tl, tr);
    int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
    minimize(l, r, x, tl, mid, lft);
    minimize(l, r, x, mid + 1, tr, ryt);
    merge(u);
}

void maximize(int l, int r, LL x, int tl, int tr, int u) {
    if (l > tr || tl > r || mn[u] >= x) return;
    if (l <= tl && tr <= r && smn[u] > x) {
        applyMax(u, x);
        return;
    }
    push(u, tl, tr);
    int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
    maximize(l, r, x, tl, mid, lft);
    maximize(l, r, x, mid + 1, tr, ryt);
    merge(u);
}

void increase(int l, int r, LL x, int tl, int tr, int u) {
    if (l > tr || tl > r) return;
    if (l <= tl && tr <= r) {
        applyAdd(u, x, tl, tr);
        return;
    }
    push(u, tl, tr);
    int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
    increase(l, r, x, tl, mid, lft);
    increase(l, r, x, mid + 1, tr, ryt);
    merge(u);
}
}

```

```

LL getSum(int l, int r, int tl, int tr, int u) {
    if (l > tr || tl > r) return 0;
    if (l <= tl && tr <= r) return sum[u];
    push(u, tl, tr);
    int mid = (tl + tr) >> 1, lft = u << 1, ryt = lft | 1;
    return getSum(l, r, tl, mid, lft) + getSum(l, r, mid + 1, tr, ryt);
}

LL getMax(int l, int r, int tl, int tr, int u) {
    if (l > tr || tl > r) return NEG_INF;
    if (l <= tl && tr <= r) return mx[u];
    push(u, tl, tr);
    int mid = (tl + tr) >> 1;
    return max(getMax(l, r, tl, mid, u << 1),
               getMax(l, r, mid + 1, tr, (u << 1) | 1));
}
};

```

2.4 Lazy Propagation

```

template <typename T, typename U>
struct LazySegmentTree {
    vector<T> tree;
    vector<U> lazy;
    int n;
    T I;
    function<T(T, T)> merge;
    void updateLazy(int id, U val) { lazy[id] += val; }

    void push(int id, int le, int ri) {
        tree[id] += (ri - le + 1) * lazy[id];
        if (le != ri) {
            updateLazy(2 * id + 1, lazy[id]);
            updateLazy(2 * id + 2, lazy[id]);
        }
        lazy[id] = 0;
    }

    void fix(int id) { tree[id] = merge(tree[2 * id + 1], tree[2 * id + 2]); }

    void build(int id, int le, int ri, vector<T>& arr) {
        if (le == ri) {
            tree[id] = arr[le];
            return;
        }
    }
}

```

```

    }
    int mid = (le + ri) / 2;
    build(2 * id + 1, le, mid, arr);
    build(2 * id + 2, mid + 1, ri, arr);
    fix(id);
}

void update(int id, int le, int ri, int l, int r, U
val) {
    push(id, le, ri);
    if (r < le || l > ri) return;
    if (le >= l && ri <= r) {
        updateLazy(id, val), push(id, le, ri);
        return;
    }
    int mid = (le + ri) / 2;
    update(2 * id + 1, le, mid, l, r, val);
    update(2 * id + 2, mid + 1, ri, l, r, val);
    fix(id);
}

T query(int id, int le, int ri, int l, int r) {
    push(id, le, ri);
    if (r < le || l > ri) return I;
    if (l <= le && ri <= r) return tree[id];
    int mid = (le + ri) / 2;
    return merge(query(2 * id + 1, le, mid, l, r),
        query(2 * id + 2, mid + 1, ri, l, r));
}

int findL(int id, int le, int ri, int l, int r, T val)
{
    push(id, le, ri);
    if (r < le || l > ri) return r + 1;
    if (l <= le && ri <= r && tree[id] > val) return r +
        1;
    if (le == ri) return le;

    int mid = (le + ri) / 2;
    int left = findL(2 * id + 1, le, mid, l, r, val);
    if (left <= r) return left;
    return findL(2 * id + 2, mid + 1, ri, l, r, val);
}

public:

```

```

LazySegmentTree(vector<T>& arr, T I, function<T(T, T)>
merge)
    : n(arr.size()), I(I), merge(merge) {
    tree.assign(4 * n, I);
    lazy.assign(4 * n, 0);
    build(0, 0, n - 1, arr);
}

LazySegmentTree(int n, T I, function<T(T, T)> merge)
    : n(n), I(I), merge(merge) {
    tree.assign(4 * n, I);
    lazy.assign(4 * n, 0);
}

void update(int l, int r, U val) { update(0, 0, n - 1,
    l, r, val); }

T query(int l, int r) { return query(0, 0, n - 1, l, r
); }

int findL(int l, int r, T val) { return findL(0, 0, n
- 1, l, r, val); }
};

```

2.5 MergeSortTree

```

class MergeSortTree {
    int n;
    vector<vector<int>> tree;
    void build(int id, int le, int ri, vector<int>& a) {
        if (le == ri) {
            tree[id].push_back(a[le]);
            return;
        }
        int mid = (le + ri) >> 1;
        build(2 * id + 1, le, mid, a);
        build(2 * id + 2, mid + 1, ri, a);

        auto &left = tree[2 * id + 1], &right = tree[2 * id
+ 2];
        int i = 0, j = 0, n = left.size(), m = right.size();
        while (i < n && j < m) {
            if (left[i] < right[j])
                tree[id].push_back(left[i]), i++;
            else
                tree[id].push_back(right[j]), j++;
        }
        while (i < n) tree[id].push_back(left[i]), i++;
        while (j < m) tree[id].push_back(right[j]), j++;
    }
};

```

```

// number of element greater than val
int queryL(int id, int le, int ri, int l, int r, int
val) {
    if (le > r || ri < l) {
        return 0;
    }
    if (le >= l && ri <= r) {
        return ri - le + 1 -
            (upper_bound(tree[id].begin(), tree[id].end
(), val) -
                tree[id].begin());
    }
    int mid = (le + ri) >> 1;
    return queryL(2 * id + 1, le, mid, l, r, val) +
        queryL(2 * id + 2, mid + 1, ri, l, r, val);
}

// number of element smaller than val
int queryS(int id, int le, int ri, int l, int r, int
val) {
    if (le > r || ri < l) {
        return 0;
    }
    if (le >= l && ri <= r) {
        return (upper_bound(tree[id].begin(), tree[id].end
(), val - 1) -
                tree[id].begin());
    }
    int mid = (le + ri) >> 1;
    return queryS(2 * id + 1, le, mid, l, r, val) +
        queryS(2 * id + 2, mid + 1, ri, l, r, val);
}

public:
MergeSortTree(vector<int>& a) {
    n = a.size();
    tree.resize(n * 4);
    build(0, 0, n - 1, a);
}

int queryS(int l, int r, int val) { return queryS(0,
0, n - 1, l, r, val); }
int queryL(int l, int r, int val) { return queryL(0,
0, n - 1, l, r, val); }

```

};

2.6 Mo With Update

```
const int N = 1e5 + 5, sz = 2700, bs = 25;
int arr[N], freq[2 * N], cnt[2 * N], id[N], ans[N];
struct query {
    int l, r, t, L, R;
    query(int l = 1, int r = 0, int t = 1, int id = -1)
        : l(l), r(r), t(t), L(l / sz), R(r / sz) {}
    bool operator<(const query& rhs) const {
        return (L < rhs.L) or (L == rhs.L and R < rhs.R) or
            (L == rhs.L and R == rhs.R and t < rhs.t);
    }
} Q[N];
struct update {
    int idx, val, last;
} Up[N];
int qi = 0, ui = 0;
int l = 1, r = 0, t = 0;
void add(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]++;
    cnt[freq[arr[idx]]]++;
}
void remove(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]--;
    cnt[freq[arr[idx]]]++;
}
void apply(int t) {
    const bool f = 1 <= Up[t].idx and Up[t].idx <= r;
    if (f) remove(Up[t].idx);
    arr[Up[t].idx] = Up[t].val;
    if (f) add(Up[t].idx);
}
void undo(int t) {
    const bool f = 1 <= Up[t].idx and Up[t].idx <= r;
    if (f) remove(Up[t].idx);
    arr[Up[t].idx] = Up[t].last;
    if (f) add(Up[t].idx);
}
int mex() {
    for (int i = 1; i <= N; i++)
        if (!cnt[i]) return i;
    assert(0);
}
```

```
int main() {
    int n, q;
    cin >> n >> q;
    int counter = 0;
    map<int, int> M;
    for (int i = 1; i <= n; i++) {
        cin >> arr[i];
        if (!M[arr[i]]) M[arr[i]] = ++counter;
        arr[i] = M[arr[i]];
    }
    iota(id, id + N, 0);
    while (q--) {
        int tp, x, y;
        cin >> tp >> x >> y;
        if (tp == 1)
            Q[++qi] = query(x, y, ui);
        else {
            if (!M[y]) M[y] = ++counter;
            y = M[y];
            Up[++ui] = {x, y, arr[x]};
            arr[x] = y;
        }
    }
    t = ui;
    cnt[0] = 3 * n;
    sort(id + 1, id + qi + 1, [&](int x, int y) { return Q[x] < Q[y]; });
    for (int i = 1; i <= qi; i++) {
        int x = id[i];
        while (Q[x].t > t) apply(++t);
        while (Q[x].t < t) undo(t--);
        while (Q[x].l < 1) add(--l);
        while (Q[x].r > r) add(++r);
        while (Q[x].l > 1) remove(l--);
        while (Q[x].r < r) remove(r--);
        ans[x] = mex();
    }
    for (int i = 1; i <= qi; i++) cout << ans[i] << '\n';
}
```

2.7 PST

```
// this calculates xor/xor_hash of all the element less
// than 'x' in [0, i].
// query is a walk function
class PST {
#define lc(u) tree[u].left
```

```
#define rc(u) tree[u].right;
struct node {
    int left = 0, right = 0, val = 0;
};
node* tree;
int N, LG, time = 0, I = 0;

node create(int l, int r) { return {l, r, merge(tree[l].val, tree[r].val)}; }
int merge(LL a, LL b) { return a ^ b; }
int build(int le, int ri) {
    int id = ++time;
    if (le == ri) return tree[id] = node(), id;
    int m = (le + ri) / 2;
    return tree[id] = create(build(le, m), build(m + 1, ri)), id;
}
int update(int id, int le, int ri, int pos, int val) {
    int nid = ++time;
    if (le == ri)
        return tree[nid] = {0, 0, (tree[id].val ^ val)},
            nid; // change here
    int m = (le + ri) / 2;
    if (pos <= m) {
        tree[nid] =
            create(update(tree[id].left, le, m, pos, val),
                tree[id].right);
    } else {
        tree[nid] =
            create(tree[id].left, update(tree[id].right, m + 1, ri, pos, val));
    }
    return nid;
}
int query(int id, int di, int le, int ri) {
    if (tree[id].val == tree[di].val) return 0;
    if (le == ri) return le;
    int m = (le + ri) >> 1;
    if (tree[tree[id].left].val != tree[tree[di].left].val)
        return query(tree[id].left, tree[di].left, le, m);
    return query(tree[id].right, tree[di].right, m + 1, ri);
}

public:
```

```

PST(int N, int U) { // U --> number of expected
updates
    this->N = N;
    LG = 33 - __builtin_clz(N);
    tree = new node[N * 4 + U * LG];
    build(0, N - 1);
}
int update(int id, int pos, int val) {
    return update(id, 0, N - 1, pos, val);
}
int query(int id, int di) { return query(id, di, 0, N
- 1); }
~PST() { delete[] tree; }
};

```

2.8 Sparse Table

```

class SparsedTable {
private:
    vector<vector<int>>> table;
    vector<int> log;
    int n;

public:
    SparsedTable(const vector<int>& arr) {
        n = arr.size();
        log.resize(n + 1);
        buildLog();

        table = vector<vector<int>>>(log[n] + 1, vector<int>(
n));

        for (int i = 0; i < n; i++) {
            table[0][i] = arr[i];
        }

        for (int j = 1; j <= log[n]; j++) {
            for (int i = 0; i + (1 << j) <= n; i++) {
                table[j][i] = merge(table[j - 1][i], table[j -
1][i + (1 << (j - 1))]);
            }
        }
    }

    int merge(int a, int b) { return a | b; }

    void buildLog() {

```

```

        log[1] = 0;
        for (int i = 2; i <= n; i++) {
            log[i] = log[i / 2] + 1;
        }
    }

    int Query(int L, int R) {
        int j = log[R - L + 1];
        return merge(table[j][L], table[j][R - (1 << j) +
1]);
    }

    int query(int L, int R) {
        int sum = 0;
        for (int j = log[R - L + 1]; L <= R; j = log[R - L +
1]) {
            sum = merge(sum, table[j][L]);
            L += (1 << j);
        }
        return sum;
    }

    void update(int L, int R, int val) {
        int j = log[R - L + 1];
        table[j][L] = min(table[j][L], val);
        table[j][R - (1 << j) + 1] = min(table[j][R - (1 <<
j) + 1], val);
    }

    void finalize() {
        for (int j = log[n]; j > 0; j--) {
            for (int i = 0; i + (1 << j) <= n; i++) {
                table[j - 1][i] = min(table[j - 1][i], table[j][i
]);
                table[j - 1][i + (1 << (j - 1))] =
                    min(table[j - 1][i + (1 << (j - 1))], table[j
][i]);
            }
        }
    }
};

```

2.9 Trie

```

struct node {
    int path, leaf;
    vector<int> child;

```

```

    node(int n = 0) : child(n, -1), path(0), leaf(0) {}
};

class Trie {
    int n, ptr;
    vector<node> tree;

public:
    Trie(int n) : n(n), ptr(0) { tree.emplace_back(node(n)
); }
    void insert(string& s) {
        int cur = 0;
        for (auto u : s) {
            int& next = tree[cur].child[u - '0'];
            if (next == -1) {
                tree.emplace_back(node(n));
                next = ++ptr;
            }
            tree[cur].path++;
            cur = next;
        }
        tree[cur].path++;
        tree[cur].leaf++;
    }
    void erase(string& s) {
        int cur = 0;
        for (auto u : s) {
            tree[cur].path--;
            cur = tree[cur].child[u - '0'];
        }
        tree[cur].path--;
        tree[cur].leaf--;
    }
    bool find(string& s) {
        int cur = 0;
        for (auto u : s) {
            cur = tree[cur].child[u - '0'];
            if (cur == -1 || !tree[cur].path) return 0;
        }
        return tree[cur].leaf > 0;
    }
};

```

2.10 segtree iterative

```

template <class T, class L, T it, T (*mergeT)(T, T), T
(*applyL)(T, L)>
struct SegTree {

```

```

int n;
vector<T> tree;
void update(int pos, L val) {
    pos += n;
    tree[pos] = applyL(tree[pos], val);
    while (pos > 1) {
        pos >>= 1;
        tree[pos] = mergeT(tree[pos << 1], tree[pos << 1 | 1]);
    }
}
T query(int l, int r) {
    l += n, r += n + 1;
    T lft = it, ryt = it;
    while (l < r) {
        if (l & 1) lft = mergeT(lft, tree[l++]);
        if (r & 1) ryt = mergeT(tree[--r], ryt);
        l >>= 1;
        r >>= 1;
    }
    return mergeT(lft, ryt);
}
SegTree(vector<T>& v) : n(v.size()) {
    tree.assign(2 * n, it);

    for (int i = 0; i < n; i++) tree[i + n] = v[i];
    for (int i = n - 1; i > 0; i--)
        tree[i] = mergeT(tree[i << 1], tree[i << 1 | 1]);
}
};

```

2.11 sparse table 2D

```

// rectangle query
namespace st2 {
    const int N = 2e3 + 5, B = 12;
    using Ti = long long;
    Ti Id = LLONG_MAX;
    Ti f(Ti a, Ti b) { return max(a, b); }
    Ti tbl[N][N][B];
    void init(int n, int m) {
        for (int k = 1; k < B; k++) {
            for (int i = 0; i + (1 << k) - 1 < n; i++) {
                for (int j = 0; j + (1 << k) - 1 < m; j++) {
                    tbl[i][j][k] = tbl[i][j][k - 1];
                    tbl[i][j][k] = f(tbl[i][j][k], tbl[i][j + (1 << k - 1)][k - 1]);
                }
            }
        }
    }
}

```

```

tbl[i][j][k] = f(tbl[i][j][k], tbl[i + (1 << k - 1)][j][k - 1]);
tbl[i][j][k] = f(tbl[i][j][k], tbl[i + (1 << k - 1)][j + (1 << k - 1)][k - 1]);
} } }
}
Ti query(int i, int j, int len) {
    int k = __lg(len);
    LL ret = tbl[i][j][k];
    ret = f(ret, tbl[i + len - (1 << k)][j][k]);
    ret = f(ret, tbl[i][j + len - (1 << k)][k]);
    ret = f(ret, tbl[i + len - (1 << k)][j + len - (1 << k)][k]);
    return ret;
}
}
int main() {
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            cin >> st2 :: tbl[i][j][0];
    st2 :: init(n, m);
    cout << st2 :: query(x, y, s); // x, y, x + s - 1, y + s - 1
}

```

3 Number Theory

3.1 Chinese Remainder Theorem

```

// given a, b will find solutions for, ax + by = 1
tuple<LL, LL, LL> EGCD(
    LL a, LL b) {
    if (b == 0)
        return {1, 0, a};
    else {
        auto [x, y, g] = EGCD(b, a % b);
        return {y, x - a / b * y, g};
    }
} // given modulo equations, will apply CRT
PLL CRT(vector<PLL>& v) {
    LL V = 0, M = 1;
    for (auto& [v, m] : v) { // value % mod
        auto [x, y, g] = EGCD(M, m);
        if ((v - V) % g != 0) return {-1, 0};
        V += x * (v - V) / g % (m / g) * M, M *= m / g;
        V = (V % M + M) % M;
    }
    return make_pair(V, M);
}

```

```

}

```

3.2 Eulers Totient Function

```

void phi_in_range() {
    int N = 1e6, phi[N + 1];
    for (int i = 0; i <= N; i++) phi[i] = i;
    for (int i = 2; i <= N; i++) {
        if (phi[i] != i) continue;
        for (int j = i; j <= N; j += i) {
            phi[j] -= phi[j] / i;
        }
    }
}
/* some important properties of phi
phi(a * b) = phi(a) * phi(b) * (gcd(a, b) / phi(gcd(a, b)))
phi(p ^ k) = p ^ k - p ^ (k - 1), where p is a prime number
SUM{phi(d)} = n, d | n */

```

3.3 FFT

```

// typedef complex<double> CD;
struct CD {
    double x, y;
    CD(double x = 0, double y = 0) : x(x), y(y) {}
    CD operator+(const CD &o) { return {x + o.x, y + o.y}; }
    CD operator-(const CD &o) { return {x - o.x, y - o.y}; }
    CD operator*(const CD &o) { return {x * o.x - y * o.y, x * o.y + o.x * y}; }
    void operator/=(double d) {
        x /= d;
        y /= d;
    }
    double real() { return x; }
    double imag() { return y; }
};
CD conj(const CD &c) { return CD(c.x, -c.y); }

typedef long long LL;
const double PI = acos(-1.0L);

namespace FFT {
    int N;
    vector<int> perm;
}

```

```
vector<CD> wp[2];

void precalculate(int n) {
    assert((n & (n - 1)) == 0);
    N = n;
    perm = vector<int>(N, 0);
    for (int k = 1; k < N; k <= 1) {
        for (int i = 0; i < k; i++) {
            perm[i] <= 1;
            perm[i + k] = 1 + perm[i];
        }
    }

    wp[0] = wp[1] = vector<CD>(N);
    for (int i = 0; i < N; i++) {
        wp[0][i] = CD(cos(2 * PI * i / N), sin(2 * PI * i / N));
        wp[1][i] = CD(cos(2 * PI * i / N), -sin(2 * PI * i / N));
    }
}

void fft(vector<CD> &v, bool invert = false) {
    if (v.size() != perm.size()) precalculate(v.size());

    for (int i = 0; i < N; i++)
        if (i < perm[i]) swap(v[i], v[perm[i]]);

    for (int len = 2; len <= N; len *= 2) {
        for (int i = 0, d = N / len; i < N; i += len) {
            for (int j = 0, idx = 0; j < len / 2; j++, idx += d) {
                CD x = v[i + j];
                CD y = wp[invert][idx] * v[i + j + len / 2];
                v[i + j] = x + y;
                v[i + j + len / 2] = x - y;
            }
        }
    }

    if (invert) {
        for (int i = 0; i < N; i++) v[i] /= N;
    }
}
```

```
void pairfft(vector<CD> &a, vector<CD> &b, bool invert = false) {
    int N = a.size();
    vector<CD> p(N);
    for (int i = 0; i < N; i++) p[i] = a[i] + b[i] * CD(0, 1);
    fft(p, invert);
    p.push_back(p[0]);

    for (int i = 0; i < N; i++) {
        if (invert) {
            a[i] = CD(p[i].real(), 0);
            b[i] = CD(p[i].imag(), 0);
        } else {
            a[i] = (p[i] + conj(p[N - i])) * CD(0.5, 0);
            b[i] = (p[i] - conj(p[N - i])) * CD(0, -0.5);
        }
    }
}

vector<bool> multiply(const vector<bool> &a, const vector<bool> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;

    vector<CD> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    fa.resize(n);
    fb.resize(n);

    //      fft(fa); fft(fb);
    pairfft(fa, fb);
    for (int i = 0; i < n; i++) fa[i] = fa[i] * fb[i];
    fft(fa, true);

    vector<bool> ans(n);
    for (int i = 0; i < n; i++) ans[i] = round(fa[i].real());
    while (ans.size() > 1 && !ans.back()) ans.pop_back();
    return ans;
}

const int M = 1e9 + 7, B = sqrt(M) + 1;
vector<LL> anyMod(const vector<LL> &a, const vector<LL> &b) {
```

```
int n = 1;
while (n < a.size() + b.size()) n <= 1;
vector<CD> al(n), ar(n), bl(n), br(n);

for (int i = 0; i < a.size(); i++)
    al[i] = a[i] % M / B, ar[i] = a[i] % M % B;
for (int i = 0; i < b.size(); i++)
    bl[i] = b[i] % M / B, br[i] = b[i] % M % B;

pairfft(al, ar);
pairfft(bl, br);
//      fft(al); fft(ar); fft(bl); fft(br);

for (int i = 0; i < n; i++) {
    CD ll = (al[i] * bl[i]), lr = (al[i] * br[i]);
    CD rl = (ar[i] * bl[i]), rr = (ar[i] * br[i]);
    al[i] = ll;
    ar[i] = lr;
    bl[i] = rl;
    br[i] = rr;
}

pairfft(al, ar, true);
pairfft(bl, br, true);
//      fft(al, true); fft(ar, true); fft(bl, true);
//      fft(br, true);

vector<LL> ans(n);
for (int i = 0; i < n; i++) {
    LL right = round(br[i].real()), left = round(al[i].real());
    LL mid = round(round(bl[i].real()) + round(ar[i].real()));
    ans[i] = ((left % M) * B * B + (mid % M) * B + right) % M;
}
return ans;
}
// namespace FFT
```

3.4 Matrix

```
template <typename DT>
struct Matrix {
    vector<vector<DT>> mat;
    Matrix(vector<vector<DT>>& mat) : mat(mat) {}
    Matrix(int n) : mat(n, vector<DT>(n)) {}
```



```

    for (int i = 0; i < n; i++) {
        mat[i][i] = 1;
    }
}
Matrix(int n, int m) : mat(n, vector<DT>(m)) {}
Matrix operator*(Matrix& other) {
    auto &a = mat, &b = other.mat;
    assert(a[0].size() == b.size());
    int n = a.size(), m = b[0].size(), s = a[0].size();
    Matrix<DT> ret(n, m);
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            DT temp = 0;
            for (int k = 0; k < s; k++) {
                temp = (temp + 1LL * a[i][k] * b[k][j] % MOD) % MOD;
            }
            ret.mat[i][j] = temp;
        }
    }
    return ret;
};
Matrix<int> pow(Matrix<int> a, LL p) {
    int n = a.mat.size();
    Matrix<int> ret(n);
    while (p) {
        if (p & 1) ret = ret * a;
        a = a * a;
        p >>= 1;
    }
    return ret;
}

```

3.5 NOD and SOD

```

// NUMBER = p1a1 * p2a2 .... pnan
LL NOD = 1, SOD = 1, POD = 1, POWER = 1;
for (int i = 0; i < n; i++) {
    LL p, a;
    cin >> p >> a;
    NOD = (NOD * (a + 1)) % MOD;
    SOD = ((SOD * (bigmod(p, a + 1, MOD) + MOD - 1)) % MOD
        * inv[p - 1]) % MOD;
    POD = bigmod(POD, a + 1, MOD) *
        bigmod(bigmod(x, a * (a + 1) / 2, MOD), POWER,
            MOD) % MOD;
}

```

```

    POWER = (POWER * (a + 1)) % (MOD - 1);
}
LL csod(LL n) {
    LL ans = 0;
    for (LL i = 2; i * i <= n; ++i) {
        LL j = n / i;
        ans += (i + j) * (j - i + 1) / 2;
        ans += i * (j - i);
    }
    return ans;
}
// summation of NOD(d)[d | n] = product of g(ek + 1)[n
= pkak g(x) = x * (x + 1) / 2

```

3.6 Pollard rho

```

namespace rho {
inline LL mul(LL a, LL b, LL mod) {
    LL result = 0;
    while (b) {
        if (b & 1) result = (result + a) % mod;
        a = (a + a) % mod;
        b >>= 1;
    }
    return result;
}
inline LL bigmod(LL num, LL pow, LL mod) {
    LL ans = 1;
    for (; pow > 0; pow >>= 1, num = mul(num, num, mod))
        if (pow & 1) ans = mul(ans, num, mod);
    return ans;
}
inline bool is_prime(LL n) {
    if (n < 2 or n % 6 % 4 != 1) return (n | 1) == 3;
    LL a[] = {2, 325, 9375, 28178, 450775, 9780504,
        1795265022};
    LL s = __builtin_ctzll(n - 1), d = n >> s;
    for (LL x : a) {
        LL p = bigmod(x % n, d, n), i = s;
        for (; p != 1 and p != n - 1 and x % n and i--; p =
            mul(p, p, n));
        if (p != n - 1 and i != s) return false;
    }
    return true;
}
LL f(LL x, LL n) { return mul(x, x, n) + 1; }
LL get_factor(LL n) {

```

```

    LL x = 0, y = 0, t = 0, prod = 2, i = 2, q;
    for (; t++ % 40 or __gcd(prod, n) == 1; x = f(x, n), y
        = f(f(y, n), n)) {
        (x == y) ? x = i++, y = f(x, n) : 0;
        prod = (q = mul(prod, max(x, y) - min(x, y), n)) ? q
            : prod;
    }
    return __gcd(prod, n);
}
void _factor(LL n, map<LL, int>& res) {
    if (n == 1) return;
    if (is_prime(n))
        res[n]++;
    else {
        LL x = get_factor(n);
        _factor(x, res);
        _factor(n / x, res);
    }
}
map<LL, int> factorize(LL n) {
    map<LL, int> res;
    if (n < 2) return res;
    LL small_primes[] = {2, 3, 5, 7, 11, 13, 17, 19, 23,
        29, 31, 37, 41,
        43, 47, 53, 59, 61, 67, 71, 73, 79,
        83, 89, 97};
    for (LL p : small_primes)
        for (; n % p == 0; n /= p, res[p]++);
    _factor(n, res);
    return res;
}
} // namespace rho

```

3.7 Sieve

```

const int N = 10000000;
vector<int> lp(N), pr;
for (int i = 2; i < N; i++) {
    if (lp[i] == 0) {
        lp[i] = i;
        pr.push_back(i);
    }
    for (int j = 0; i * pr[j] < N; j++) {
        lp[i * pr[j]] = pr[j];
        if (pr[j] == lp[i]) break;
    }
}

```

3.8 XOR Basis

```
template <typename T = int, int B = 31>
struct Basis {
    T a[B];
    Basis() { memset(a, 0, sizeof a); }
    void insert(T x) {
        for (int i = B - 1; i >= 0; i--) {
            if (x >> i & 1) {
                if (a[i] ^ x == a[i])
                    a[i] = x; break;
            }
        }
    }
    bool can(T x) {
        for (int i = B - 1; i >= 0; i--) {
            x = min(x, x ^ a[i]);
        }
        return x == 0;
    }
    T max_xor(T ans = 0) {
        for (int i = B - 1; i >= 0; i--) {
            ans = max(ans, ans ^ a[i]);
        }
        return ans;
    }
};
```

3.9 mobius function

```
const int N = 1e6 + 5;
int mob[N];
void mobius() {
    memset(mob, -1, sizeof mob);
    mob[1] = 1;
    for (int i = 2; i < N; i++)
        if (mob[i]) {
            for (int j = i + i; j < N; j += i) mob[j] -= mob[i];
        }
}
```

3.10 nCr

```
namespace com {
LL fact[N], inv[N], inv_fact[N];
void init() {
```

```
    fact[0] = inv_fact[0] = 1;
    for (LL i = 1; i < N; i++) {
        inv[i] = i == 1 ? 1 : (LL)inv[i - 1] * (mod / i + 1) % mod;
        fact[i] = (LL)fact[i - 1] * i % mod;
        inv_fact[i] = (LL)inv_fact[i - 1] * inv[i] % mod;
    }
}
LL C(int n, int r) {
    return (r < 0 || r > n) ? 0
        : fact[n] * inv_fact[r] % mod * inv_fact[n - r] % mod;
}
} // namespace com
```

3.11 ntt

```
const LL N = 1 << 18;
const LL MOD = 786433;

vector<LL> P[N];
LL rev[N], w[N | 1], a[N], b[N], inv_n, g =
    primitive_root(MOD);
LL Pow(LL b, LL p) {
    LL ret = 1;
    while (p) {
        if (p & 1) ret = (ret * b) % MOD;
        b = (b * b) % MOD;
        p >>= 1;
    }
    return ret;
}
LL primitive_root(LL p) {
    vector<LL> factor;
    LL phi = p - 1, n = phi;
    for (LL i = 2; i * i <= n; i++) {
        if (n % i) continue;
        factor.emplace_back(i);
        while (n % i == 0) n /= i;
    }
    if (n > 1) factor.emplace_back(n);
    for (LL res = 2; res <= p; res++) {
        bool ok = true;
        for (LL i = 0; i < factor.size() && ok; i++)
            ok &= Pow(res, phi / factor[i]) != 1;
        if (ok) return res;
    }
}
```

```
    return -1;
}
void prepare(LL n) {
    LL sz = abs(31 - __builtin_clz(n));
    LL r = Pow(g, (MOD - 1) / n);
    inv_n = Pow(n, MOD - 2);
    w[0] = w[n] = 1;
    for (LL i = 1; i < n; i++) w[i] = (w[i - 1] * r) % MOD;
    for (LL i = 1; i < n; i++)
        rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (sz - 1));
}
void NTT(LL *a, LL n, LL dir = 0) {
    for (LL i = 1; i < n - 1; i++)
        if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (LL m = 2; m <= n; m <= 1) {
        for (LL i = 0; i < n; i += m) {
            for (LL j = 0; j < (m >> 1); j++) {
                LL &u = a[i + j], &v = a[i + j + (m >> 1)];
                LL t = v * w[dir ? n - n / m * j : n / m * j] % MOD;
                v = u - t < 0 ? u - t + MOD : u - t;
                u = u + t >= MOD ? u + t - MOD : u + t;
            }
        }
        if (dir)
            for (LL i = 0; i < n; i++) a[i] = (inv_n * a[i]) % MOD;
    }
}
vector<LL> multiply(vector<LL> p, vector<LL> q) {
    LL n = p.size(), m = q.size();
    LL t = n + m - 1, sz = 1;
    while (sz < t) sz <= 1;
    prepare(sz);

    for (LL i = 0; i < n; i++) a[i] = p[i];
    for (LL i = 0; i < m; i++) b[i] = q[i];
    for (LL i = n; i < sz; i++) a[i] = 0;
    for (LL i = m; i < sz; i++) b[i] = 0;

    NTT(a, sz);
    NTT(b, sz);
    for (LL i = 0; i < sz; i++) a[i] = (a[i] * b[i]) % MOD;
    ;
    NTT(a, sz, 1);
```

```
vector<LL> c(a, a + sz);
while (c.size() && c.back() == 0) c.pop_back();
return c;
}
```

3.12 primality test

```
using u64 = uint64_t;
using u128 = __uint128_t;
u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1;
    base %= mod;
    while (e) {
        if (e & 1) result = (u128)result * base % mod;
        base = (u128)base * base % mod;
        e >>= 1;
    }
    return result;
}
bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1) return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
        if (x == n - 1) return false;
    }
    return true;
};
bool MillerRabin(u64 n, int iter = 5) { // returns true
if n is probably prime, else returns false.
    if (n < 4) return n == 2 || n == 3;
    int s = 0;
    u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1;
        s++;
    }
    for (int i = 0; i < iter; i++) {
        int a = 2 + rand() % (n - 3);
        if (check_composite(n, a, d, s)) return false;
    }
    return true;
}
```

3.13 prime counting function

```
namespace PCF {
```

```
const LL MAX = 1E13;
const int N = 7E6;
/// around MAX^(2/3)/15
const int M = 7, PM = 2 * 3 * 5 * 7 * 11 * 13 * 17;
bool isp[N];
int prime[N], pi[N];
int phi[M + 1][PM + 1], sz[M + 1];
auto div = [](LL a, LL b) -> LL { return double(a) / b; };
};
auto rt2 = [](LL x) -> int { return sqrtl(x); };
auto rt3 = [](LL x) -> int { return cbrtl(x); };
void init() {
    int cnt = 0;
    for (int i = 2; i < N; i++) isp[i] = true;
    pi[0] = pi[1] = 0;
    for (int i = 2; i < N; i++) {
        if (isp[i]) prime[++cnt] = i;
        pi[i] = cnt;
        for (int j = 1; j <= cnt && i * prime[j] < N; j++) {
            isp[i * prime[j]] = false;
            if (i % prime[j] == 0) break;
        }
    }
    sz[0] = 1;
    for (int i = 0; i <= PM; ++i) phi[0][i] = i;
    for (int i = 1; i <= M; ++i) {
        sz[i] = prime[i] * sz[i - 1];
        for (int j = 1; j <= PM; ++j)
            phi[i][j] = phi[i - 1][j] - phi[i - 1][div(j, prime[i])];
    }
}
LL getphi(LL x, int s) {
    if (s == 0) return x;
    if (s <= M) return phi[s][x % sz[s]] + (x / sz[s]) *
        phi[s][sz[s]];
    if (x <= 1LL * prime[s] * prime[s]) return pi[x] - s + 1;
    if (x <= 1LL * prime[s] * prime[s] * prime[s] && x < N) {
        int s2x = pi[rt2(x)];
        LL ans = pi[x] - (s2x + s - 2) * (s2x - s + 1) / 2;
        for (int i = s + 1; i <= s2x; ++i) ans += pi[div(x, prime[i])];
        return ans;
    }
}
```

```
return getphi(x, s - 1) - getphi(div(x, prime[s]), s - 1);
}
LL getpi(LL x) {
    if (x < N) return pi[x];
    LL ans = getphi(x, pi[rt3(x)]) + pi[rt3(x)] - 1;
    for (int i = pi[rt3(x)] + 1, ed = pi[rt2(x)]; i <= ed; ++i)
        ans -= getpi(div(x, prime[i])) - i + 1;
    return ans;
}
} // namespace PCF
```

4 Graph

4.1 BridgeTree

```
vector<PLL> g[N];
vector<int> ng[N];
int disc[N], low[N], mark[N], vis[N], timer = 1;
void find_bridge(int u, int p) {
    disc[u] = low[u] = timer++;
    bool fl = 1;
    for (auto [v, id] : g[u]) {
        if (v == p && fl) {
            fl = 0;
            continue;
        }
        if (disc[v]) {
            low[u] = min(low[u], disc[v]);
        } else {
            find_bridge(v, u);
            low[u] = min(low[u], low[v]);
            if (disc[u] < low[v]) {
                mark[id] = 1;
            }
        }
    }
}
void colorComponents(int u, int color) {
    if (vis[u]) return;
    vis[u] = color;
    for (auto [v, id] : g[u]) {
        if (mark[id]) continue;
        colorComponents(v, color);
    }
}
void solve() {
```

```

int n, m;
cin >> n >> m;
vector<PLL> edges;
for (int i = 0; i < m; i++) {
    int u, v;
    cin >> u >> v;
    edges.push_back({u, v});
    g[u].push_back({v, i});
    g[v].push_back({u, i});
}
find_bridge(1, 0);
int color = 1;
for (int i = 1; i <= n; i++) {
    if (!vis[i]) colorComponents(i, color++);
}
for (int i = 0; i < m; i++) {
    if (mark[i]) {
        ng[vis[edges[i].first]].push_back(vis[edges[i].second]);
        ng[vis[edges[i].second]].push_back(vis[edges[i].first]);
    }
}
}
}

```

4.2 CD

```

class CD {
    vector<vector<int>>> adj;
    vector<int> sub;
    vector<bool> blocked;
    int N;
public:
    CD(vector<vector<int>>> adj) : adj(adj) {
        N = tree.adj.size() - 1;
        blocked.assign(N + 1, 0);
        sub.assign(N + 1, 0);
        compute();
    }
    void compute(int u = 1, int p = 0) {
        sub[u] = 1;
        for (auto v : adj[u])
            if (v != p) {
                compute(v, u);
                sub[u] += sub[v];
            }
    }
}

```

```

int centroid(int u, int p = 0) {
    int tot = sub[u];
    for (auto v : adj[u]) {
        if (v == p || blocked[v]) continue;
        if (2 * sub[v] > tot) {
            sub[u] = tot - sub[v];
            sub[v] = tot;
            return centroid(v, u);
        }
    }
    return u;
}

int count(int u, int p) { /* calculate ans */ }
void update(int u, int p) { /* update */ }
int decompose(int u = 1) {
    u = centroid(u);
    blocked[u] = 1;
    int ans = 0;
    ///// Do something here ///// count() update()
    for (auto v : adj[u])
        if (!blocked[v]) {
            ans += count(v, u);
            update(v, u);
        }
    /// reset updates here
    for (auto v : adj[u])
        if (!blocked[v])
            decompose(v);
    return ans;
}
};

```

4.3 DSU, MST

```

class DSU {
    vector<int> parent, size;
public:
    DSU(int n) : parent(n + 1), size(n + 1, 1) {
        iota(parent.begin(), parent.end(), 0);
    }
    int root(int u) {
        if (parent[u] == u) return u;
        return parent[u] = root(parent[u]);
    }
    bool same(int u, int v) { return root(u) == root(v); }
    void merge(int u, int v) {

```

```

        u = root(u), v = root(v);
        if (u == v) return;
        if (size[u] < size[v]) swap(u, v);
        parent[v] = u, size[u] += size[v];
    }
};

int kruskal(vector<tuple<int, int, int>> edges, int n) {
    sort(edges.begin(), edges.end());
    DSU mst(n);
    int cost = 0;
    for (auto& [w, u, v] : edges) {
        if (mst.same(u, v)) continue;
        mst.merge(u, v);
        cost += w;
    }
    return cost;
} /* // PRIM'S SPANNING TREE (MST) */

DIJKSTRA code... start from a node,
and push nodes which are not marked popped edges
weight are taken

```

4.4 Dinic

```

struct Dinic {
    struct edge {
        int to, rid, isRev;
        LL cap, flow;
    };
    int n, s, t;
    vector<vector<edge>> g;
    vector<int> level, ptr;
    Dinic(int _n) : n(_n + 5) { g.resize(n); }
    void addEdge(int u, int v, LL cap) {
        g[u].push_back({v, (int)g[v].size(), 0, cap, 0LL});
        g[v].push_back({u, (int)g[u].size() - 1, 1, 0LL, 0LL});
    }
    bool bfs() {
        level.assign(n, -1);
        queue<int> q;
        q.push(s);
        level[s] = 0;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (auto& e : g[u]) {
                int v = e.to;

```

```

        if (level[v] == -1 and e.cap > e.flow)
            level[v] = level[u] + 1, q.push(v);
    }
}
return level[t] != -1;
}
LL dfs(int u, LL flow) {
    if (u == t) return flow;
    for (int& i = ptr[u]; i < (int)g[u].size(); i++) {
        edge& e = g[u][i];
        int v = e.to;
        if (level[v] != level[u] + 1 or e.cap <= e.flow)
            continue;
        LL cflow = dfs(v, min(flow, e.cap - e.flow));
        if (cflow) {
            e.flow += cflow, g[v][e.rid].flow -= cflow;
            return cflow;
        }
    }
    return 0;
}
LL maxFlow(int s, int t) {
    this->s = s, this->t = t;
    LL flow = 0;
    while (bfs()) {
        ptr.assign(n, 0);
        while (LL cflow = dfs(s, INF)) flow += cflow;
    }
    return flow;
}
};

```

4.5 HLD

```

const int N = 2E5 + 69;
int n;
// seg tree here
vector<int> adj[N];
int cur_pos;
bool WEIGHT_IN_EDGE = false;
int Parent[N], Depth[N], Heavy[N], Head[N], Pos[N];
int Start[N], End[N]; vector<int> Euler; /// ONLY
NEEDED FOR SUBTREE QUERIES
void reset (bool WIE = false) {
    cur_pos = 0;
    WEIGHT_IN_EDGE = WIE;
    fill (Heavy, Heavy + n, -1);

```

```

    // build (vector<T> (n, I));
}
int dfs (int v = 0) {
    int size = 1, max_c_size = 0;
    for (int c : adj[v]) {
        if (c != Parent[v]) {
            Parent[c] = v;
            Depth[c] = Depth[v] + 1;
            int c_size = dfs(c);
            size += c_size;
            if (c_size > max_c_size) {
                max_c_size = c_size;
                Heavy[v] = c;
            }
        }
    }
    return size;
}
void decompose (int v = 0, int h = 0) {
    Head[v] = h;
    Pos[v] = cur_pos++;
    Euler.push_back(v);
    Start[v] = (int)Euler.size() - 1;

    if (Heavy[v] != -1) decompose(Heavy[v], h);

    for (int c : adj[v]) {
        if (c != Parent[v] && c != Heavy[v]) decompose(c, c);
    }

    End[v] = Euler.size() - 1;
}
void update_path (int a, int b, LL val) {
    while (Head[a] != Head[b]) {
        if (Depth[Head[a]] < Depth[Head[b]]) swap(a, b);
        update(Pos[Head[a]], Pos[a], val);
        a = Parent[Head[a]];
    }
    if (Depth[a] > Depth[b]) swap(a, b);
    update(Pos[a] + WEIGHT_IN_EDGE, Pos[b], val);
}
// LL query_path (int a, int b) {
//     LL res = 0;
//     while (Head[a] != Head[b]) {
//         if (Depth[Head[a]] < Depth[Head[b]]) swap(a, b);

```

```

        //     res = merge (res, query(Pos[Head[a]], Pos[a]));
        //     a = Parent[Head[a]];
        // }
        // if (Depth[a] > Depth[b]) swap(a, b);
        // res = merge (res, query(Pos[a] + WEIGHT_IN_EDGE, Pos
        // [b]));
        // return res;
        // }
vector<T> query_up(int u, int anc) {
    vector<T> res;
    while (Head[u] != Head[anc]) {
        res.emplace_back (query(Pos[Head[u]], Pos[u]));
        u = Parent[Head[u]];
    }
    res.emplace_back (query(Pos[anc] + 1, Pos[u]));
    return res;
}
LL query_path(int u, int v) {
    int w = LCA::lca(u, v);
    auto left = query_up(u, w);
    auto right = query_up(v, w);
    node res = I;
    for (auto e : left) {
        res = merge (e, res);
    }
    if (not WEIGHT_IN_EDGE) {
        res = merge(query(Pos[w], Pos[w]), res);
    }
    swap (res.AP, res.PA);
    auto res2 = I;
    for (auto e : right) {
        res2 = merge (e, res2);
    }
    res = merge (res, res2);
    return max ({res.PP, res.PA, res.AP, res.AA});
}
void update_subtree (int v, LL val) { update(Start[v],
End[v], val); }
LL query_subtree (int v) { return query(Start[v], End[v
]); }
void HLD_initialize (vector<LL> &weight) {
    reset (true);
    Parent[0] = -1;
    dfs(); decompose();
    for (int i = 0; i < n; i++) update(Pos[i], Pos[i],
weight[i]);

```

```

}
vector < pair <int, LL> > adj_weight[N];
void early_dfs (vector<LL> &weight, int u = 0, int p =
-1) {
    for (auto [v, w] : adj_weight[u]) if (v ^ p) {
        weight[v] = w;
        early_dfs (weight, v, u);
    }
}

```

4.6 LCA O(1)

```

void dfs(int u, int p, int d, vector<int> g[], vector<
pair<int, int>> &order, vector<int> &mp){
    for(auto v: g[u]){
        if(v == p) continue;
        order.push_back({d, u});
        dfs(v, u, d + 1, g, order, mp);
    }
    order.push_back({d, u});
    mp[u] = (int) order.size() - 1;
}

```

```

void solve(int tc) {
    vector<int> g[n + 1], mp(n + 1);
    vector<pair<int, int>> order;
    dfs(1, 0, 0, g, order, mp);
    SparsedTable<pair<int, int>> sp(order);
    auto lca = [&](int u, int v){
        if(mp[u] > mp[v]) swap(u, v);

        return sp.query(mp[u], mp[v]).second;
    };
    auto dis = [&](int u, int v){
        int w = lca(u, v);
        u = mp[u], v = mp[v], w = mp[w];
        return order[u].first + order[v].first - 2 *
            order[w].first;
    };
}

```

4.7 LCA O(n)

```

struct LCA {
    int n;
    vector<int> lvl, par, jmp;
    LCA(vector<vector<int>> const& g, int u, int p)
        : n(g.size()), lvl(n, -1), par(n, -1), jmp(n, p) {

```

```

        lvl[u] = 0, par[u] = p;
        queue<int> q;
        for (q.push(u); q.size(); q.pop()) {
            int u = q.front();
            for (int v : g[u])
                if (lvl[v] < 0) {
                    q.push(v);
                    lvl[v] = lvl[u] + 1, par[v] = u;
                    if (lvl[jmp[u]] << 1 == lvl[u] + lvl[jmp[jmp[u]]])
                        jmp[v] = jmp[jmp[u]];
                    else
                        jmp[v] = u;
                }
            }
        }
        int getAnc(int u, int d) {
            d = max(0, lvl[u] - d);
            while (lvl[u] > d) {
                if (lvl[jmp[u]] < d)
                    u = par[u];
                else
                    u = jmp[u];
            }
            return u;
        }
        int lca(int u, int v) {
            if (lvl[u] < lvl[v]) swap(u, v);
            u = getAnc(u, lvl[u] - lvl[v]);
            while (u != v) {
                if (jmp[u] == jmp[v])
                    u = par[u], v = par[v];
                else
                    u = jmp[u], v = jmp[v];
            }
            return u;
        }
        int dist(int u, int v) { return lvl[u] + lvl[v] - 2 *
            lvl[lca(u, v)]; }
};

```

4.8 block cut tree

```

const int N = 4e5 + 1;
bitset<N> art;
vector<int> g[N], tree[N], st, comp[N];
int n, ptr, cur, in[N], low[N], id[N];

```

```

void memclear() {
    for (int i = 1; i <= n; i++) {
        g[i].clear();
        in[i] = low[i] = art[i] = 0;
    }
    for (int i = 1; i <= ptr; i++) {
        tree[i].clear();
        comp[i].clear();
    }
    st.clear();
    ptr = cur = 0;
}
void dfs(int u, int from = -1) {
    in[u] = low[u] = ++ptr;
    st.emplace_back(u);
    for (int v : g[u])
        if (v ^ from) {
            if (!in[v]) {
                dfs(v, u);
                low[u] = min(low[u], low[v]);
                if (low[v] >= in[u]) {
                    art[u] = ~from or in[v] > in[u] + 1;
                    comp[++cur].emplace_back(u);
                    while (comp[cur].back() ^ v) {
                        comp[cur].emplace_back(st.back());
                        st.pop_back();
                    }
                }
            } else
                low[u] = min(low[u], in[v]);
        }
}
void build_tree() {
    ptr = 0;
    for (int i = 1; i <= n; ++i)
        if (art[i]) id[i] = ++ptr;
    for (int i = 1; i <= cur; ++i) {
        int x = ++ptr;
        for (int u : comp[i]) {
            if (art[u]) {
                tree[x].emplace_back(id[u]);
                tree[id[u]].emplace_back(x);
            } else
                id[u] = x;
        }
    }
}

```

}

4.9 maximum bipartite matching hopcroft

```
// do everything 1-based
class BipartiteMatcher {
private:
    int n, m;           // Number of vertices in left
                        // and right sets
    vector<vector<int>> adj; // Adjacency list for the
                        // bipartite graph
    vector<int> dist;     // Distance array for BFS
    vector<int> matchL, matchR;
    // matchL[u] is the right vertex matched with u;
    // matchR[v] is the left vertex matched with v
public:
    BipartiteMatcher(int n, int m) : n(n), m(m) {
        adj.resize(n + 1);
        matchL.resize(n + 1, 0);
        matchR.resize(m + 1, 0);
        dist.resize(n + 1);
    }
    void addEdge(int u, int v) { adj[u].push_back(v); }
    bool bfs() {
        queue<int> q;
        for (int u = 1; u <= n; u++) {
            if (matchL[u] == 0) {
                dist[u] = 0;
                q.push(u);
            } else {
                dist[u] = INT_MAX;
            }
        }
        dist[0] = INT_MAX;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            if (dist[u] < dist[0]) {
                for (int v : adj[u]) {
                    if (dist[matchR[v]] == INT_MAX) {
                        dist[matchR[v]] = dist[u] + 1;
                        q.push(matchR[v]);
                    }
                }
            }
        }
        return dist[0] != INT_MAX;
    }
};
```

```
}
bool dfs(int u) {
    if (u != 0) {
        for (int v : adj[u]) {
            if (dist[matchR[v]] == dist[u] + 1) {
                if (dfs(matchR[v])) {
                    matchL[u] = v;
                    matchR[v] = u;
                    return true;
                }
            }
        }
        dist[u] = INT_MAX;
        return false;
    }
    return true;
}

int hopcroftKarp() {
    int matching = 0;
    while (bfs()) {
        for (int u = 1; u <= n; u++) {
            if (matchL[u] == 0 && dfs(u)) {
                matching++;
            }
        }
    }
    return matching;
}
};
```

4.10 strongly connected component

```
bool vis[N];
vector<int> adj[N], adjr[N];
vector<int> order, component;
void dfs(int u, int tp = 0) {
    vis[u] = true;
    if (tp) component.push_back(u);
    auto& ad = (tp ? adjr : adj);
    for (int v : ad[u])
        if (!vis[v]) dfs(v, tp);
    if (!tp) order.push_back(u);
}

int main() {
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) dfs(i);
    }
}
```

```
memset(vis, 0, sizeof vis);
reverse(order.begin(), order.end());
for (int i : order) {
    if (!vis[i]) { // one component is found
        dfs(i, 1), component.clear();
    }
}
}
```

5 String

5.1 Aho

```
const int N = 2000, L = 105;
struct AhoCorasick {
    int N, P;
    const int A = 256;
    vector<vector<int>> next;
    vector<int> link, out_link, end_in_pattern;
    vector<vector<int>> out;
    AhoCorasick() : N(0), P(0) { node(); }
    int node() {
        next.emplace_back(A, 0);
        link.emplace_back(0);
        out_link.emplace_back(0);
        out.emplace_back(0);
        end_in_pattern.emplace_back(0);
        return N++;
    }
    inline int get(char c) { return c; }
    int addPattern(const string T) {
        int u = 0;
        for (auto c : T) {
            if (!next[u][get(c)]) next[u][get(c)] = node();
            u = next[u][get(c)];
        }
        out[u].push_back(P);
        end_in_pattern[u] = 1;
        return P++;
    }
    void pushLinks() {
        queue<int> q;
        for (q.push(0); !q.empty(); ) {
            int u = q.front();
            q.pop();
            for (int c = 0; c < A; ++c) {
                int v = next[u][c];
                if (!v)
```



```

    next[u][c] = next[link[u]][c];
else {
    link[v] = u ? next[link[u]][c] : 0;
    out_link[v] = out[link[v]].empty() ? out_link[
    link[v]] : link[v];
    q.push(v);
}
end_in_pattern[v] |= end_in_pattern[out_link[v]];
}
}
int advance(int u, char c) {
    while (u && !next[u][get(c)]) u = link[u];
    u = next[u][get(c)];
    return u;
}
};

```

5.2 KMP

```

template <typename T>
vector<int> getLPSarray(T& b) {
    int m = b.size();
    vector<int> phi(m);
    for (int i = 1, j = 0; i < m; i++) {
        while (j && b[i] != b[j]) j = phi[j - 1];
        if (b[i] == b[j]) j++;
        phi[i] = j;
    }
    return phi;
}

template <typename T>
int KMP_match(T& a, T& b) {
    int n = a.size(), m = b.size();
    vector<int> lps = getLPSarray(b);
    int i = 0, j = 0, cnt = 0;
    while (n - i >= m - j) {
        if (a[i] == b[j]) { i++, j++; }
        if (j == m) {
            cnt++, j = lps[j - 1];
        } else if (i < n && a[i] != b[j]) {
            if (j) j = lps[j - 1];
            else i++;
        }
    }
    return cnt;
}

```

5.3 Manacher

```

void Manacher() {
    vector<int> d1(n);
    // d[i] = number of palindromes taking s[i] as center
    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);
        while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
        d1[i] = k--;
        if (i + k > r) l = i - k, r = i + k;
    }
    vector<int> d2(n);
    // d[i] = number of palindromes taking s[i-1] and s[i]
    as center
    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
        while (0 <= i - k - 1 && i + k < n && s[i - k - 1]
        == s[i + k]) k++;
        d2[i] = k--;
        if (i + k > r) l = i - k - 1, r = i + k;
    }
}

```

5.4 String Match FFT

```

/*find occurrences of t in s where '?'s are
automatically matched with any
* character res[i + m - 1] = sum_j=0 to m - 1 {s[i + j]
* t[j] * (s[i + j] -
* t[j]) */
vector<int> string_matching(string& s, string& t) {
    int n = s.size(), m = t.size();
    vector<int> s1(n), s2(n), s3(n);
    for (int i = 0; i < n; i++)
        s1[i] = s[i] == '?' ? 0 : s[i] - 'a' + 1; /*assign
        any non zero number for non '?'s */
    for (int i = 0; i < n; i++) s2[i] = s1[i] * s1[i];
    for (int i = 0; i < n; i++) s3[i] = s1[i] * s2[i];
    vector<int> t1(m), t2(m), t3(m);
    for (int i = 0; i < m; i++) t1[i] = t[i] == '?' ? 0 :
    t[i] - 'a' + 1;
    for (int i = 0; i < m; i++) t2[i] = t1[i] * t1[i];
    for (int i = 0; i < m; i++) t3[i] = t1[i] * t2[i];
    reverse(t1.begin(), t1.end());
    reverse(t2.begin(), t2.end());
    reverse(t3.begin(), t3.end());
}

```

```

vector<int> s1t3 = multiply(s1, t3);
vector<int> s2t2 = multiply(s2, t2);
vector<int> s3t1 = multiply(s3, t1);
vector<int> res(n);
for (int i = 0; i < n; i++) res[i] = s1t3[i] - s2t2[i]
* 2 + s3t1[i];
vector<int> oc;
for (int i = m - 1; i < n; i++)
    if (res[i] == 0) oc.push_back(i - m + 1);
return oc;
}

```

5.5 Z

```

vector<int> z(string const& s) {
    int n = size(s);
    vector<int> z(n);
    int x = 0, y = 0;
    for (int i = 1; i < n; i++) {
        z[i] = max(0, min(z[i - x], y - i + 1));
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            x = i, y = i + z[i], z[i]++;
        }
    }
    return z;
}

```

5.6 double hashing

```

// Some Primes : 1000000007, 1000000009, 1000000861,
1000099999(< 2 ^ 30)1088888881, 1111211111, 1500000001,
1481481481(< 2 ^ 31)
namespace Hashing {
#define ff first
#define ss second
const PLL M = {1e9 + 7, 1e9 + 9};
const LL base = 1259;
const int N = 1e6 + 7;
PLL operator+(const PLL& a, LL x) { return {a.ff + x, a.
ss + x}; }
PLL operator-(const PLL& a, LL x) { return {a.ff - x, a.
ss - x}; }
PLL operator*(const PLL& a, LL x) { return {a.ff * x, a.
ss * x}; }
PLL operator+(const PLL& a, PLL x) { return {a.ff + x.ff
, a.ss + x.ss}; }
PLL operator-(const PLL& a, PLL x) { return {a.ff - x.ff
, a.ss - x.ss}; }
}

```



```

PLL operator*(const PLL& a, PLL x) { return {a.ff * x.ff
, a.ss * x.ss}; }
PLL operator%(const PLL& a, PLL m) { return {a.ff % m.ff
, a.ss % m.ss}; }
ostream& operator<<(ostream& os, PLL hash) {
    return os << "(" << hash.ff << ", " << hash.ss << ")";
}
PLL pb[N];
void hashPre() {
    pb[0] = {1, 1};
    for (int i = 1; i < N; i++) pb[i] = (pb[i - 1] * base)
    % M;
}
vector<PLL> hashList(string s) {
    int n = s.size();
    vector<PLL> ans(n + 1);
    ans[0] = {0, 0};
    for (int i = 1; i <= n; i++) ans[i] = (ans[i - 1] *
    base + s[i - 1]) % M;
    return ans;
}
PLL substringHash(const vector<PLL>& hashlist, int l,
int r) {
    return (hashlist[r] + (M - hashlist[l - 1]) * pb[r - l
    + 1]) % M;
}
PLL Hash(string s) {
    PLL ans = {0, 0};
    for (int i = 0; i < s.size(); i++) ans = (ans * base +
    s[i]) % M;
    return ans;
}
PLL append(PLL cur, char c) {
    return (cur * base + c) % M;
}
PLL prepend(PLL cur, int k, char c) {
    return (pb[k] * c + cur) % M;
}
//replaces the i-th (0-indexed) character from right
from a to b;
PLL replace(PLL cur, int i, char a, char b) {
    return (cur + pb[i] * (M + b - a)) % M;
}
//Erases c from front of the string with size len
PLL pop_front(PLL hash, int len, char c) {
    return (hash + pb[len - 1] * (M - c)) % M;
}
//concatenates two strings where length of the right
is k

```

```

PLL concat(PLL left, PLL right, int k) { return (left *
pb[k] + right) % M; }
PLL power(const PLL& a, LL p) {
    if (p == 0) return {1, 1};
    PLL ans = power(a, p / 2);
    ans = (ans * ans) % M;
    if (p % 2) ans = (ans * a) % M;
    return ans;
}
PLL inverse(PLL a) {
    if (M.ss == 1) return power(a, M.ff - 2);
    return power(a, (M.ff - 1) * (M.ss - 1) - 1);
}
//Erases c from the back of the string
PLL invb = inverse({base, base});
PLL pop_back(PLL hash, char c) {
    return ((hash - c + M) * invb) % M;
}
//Calculates hash of string with size len repeated
cnt times
//This is O(log n). For O(1), pre-calculate inverses
PLL repeat(PLL hash, int len, LL cnt) {
    PLL mul = ((pb[len * cnt] - 1 + M) * inverse(pb[len] -
    1 + M)) % M;
    PLL ans = (hash * mul);
    if (pb[len].ff == 1) ans.ff = hash.ff * cnt;
    if (pb[len].ss == 1) ans.ss = hash.ss * cnt;
    return ans % M;
}

```

5.7 suffix array

```

const int N = 3e5 + 9;
const int LG = 18;

void induced_sort(const vector<int> &vec, int val_range,
vector<int> &SA, const vector<bool> &sl, const vector<
int> &lms_idx) {
    vector<int> l(val_range, 0), r(val_range, 0);
    for (int c : vec) {
        if (c + 1 < val_range) ++l[c + 1];
        ++r[c];
    }
    partial_sum(l.begin(), l.end(), l.begin());
    partial_sum(r.begin(), r.end(), r.begin());
    fill(SA.begin(), SA.end(), -1);
    for (int i = lms_idx.size() - 1; i >= 0; --i)
        SA[--r[vec[lms_idx[i]]]] = lms_idx[i];
}

```

```

for (int i : SA)
    if (i >= 1 && sl[i - 1]) {
        SA[l[vec[i - 1]]++] = i - 1;
    }
fill(r.begin(), r.end(), 0);
for (int c : vec)
    ++r[c];
partial_sum(r.begin(), r.end(), r.begin());
for (int k = SA.size() - 1, i = SA[k]; k >= 1; --k, i
= SA[k])
    if (i >= 1 && !sl[i - 1]) {
        SA[--r[vec[i - 1]]] = i - 1;
    }
}

vector<int> SA_IS(const vector<int> &vec, int val_range)
{
    const int n = vec.size();
    vector<int> SA(n), lms_idx;
    vector<bool> sl(n);
    sl[n - 1] = false;
    for (int i = n - 2; i >= 0; --i) {
        sl[i] = (vec[i] > vec[i + 1] || (vec[i] == vec[i +
        1] && sl[i + 1]));
        if (sl[i] && !sl[i + 1]) lms_idx.push_back(i + 1);
    }
    reverse(lms_idx.begin(), lms_idx.end());
    induced_sort(vec, val_range, SA, sl, lms_idx);
    vector<int> new_lms_idx(lms_idx.size()), lms_vec(
lms_idx.size());
    for (int i = 0, k = 0; i < n; ++i)
        if (!sl[SA[i]] && SA[i] >= 1 && sl[SA[i] - 1]) {
            new_lms_idx[k++] = SA[i];
        }
    int cur = 0;
    SA[n - 1] = cur;
    for (size_t k = 1; k < new_lms_idx.size(); ++k) {
        int i = new_lms_idx[k - 1], j = new_lms_idx[k];
        if (vec[i] != vec[j]) {
            SA[j] = ++cur;
            continue;
        }
        bool flag = false;
        for (int a = i + 1, b = j + 1; ++a, ++b) {
            if (vec[a] != vec[b]) {
                flag = true;
            }
        }
    }
}

```

```

        break;
    }
    if ((!sl[a] && sl[a - 1]) || (!sl[b] && sl[b - 1]))
    {
        flag = !((!sl[a] && sl[a - 1]) && (!sl[b] && sl[b - 1]));
        break;
    }
    SA[j] = (flag ? ++cur : cur);
}
for (size_t i = 0; i < lms_idx.size(); ++i)
    lms_vec[i] = SA[lms_idx[i]];
if (cur + 1 < (int)lms_idx.size()) {
    auto lms_SA = SA_IS(lms_vec, cur + 1);
    for (size_t i = 0; i < lms_idx.size(); ++i) {
        new_lms_idx[i] = lms_idx[lms_SA[i]];
    }
}
induced_sort(vec, val_range, SA, sl, new_lms_idx);
return SA;
}

vector<int> suffix_array(const string &s, const int LIM
= 128) {
    vector<int> vec(s.size() + 1);
    copy(begin(s), end(s), begin(vec));
    vec.back() = '$';
    auto ret = SA_IS(vec, LIM);
    ret.erase(ret.begin());
    return ret;
}

struct SuffixArray {
    int n;
    string s;
    vector<int> sa, rank, lcp;
    vector<vector<int>> t;
    vector<int> lg;
    SuffixArray() {}
    SuffixArray(string _s) {
        n = _s.size();
        s = _s;
        sa = suffix_array(s);
        rank.resize(n);
        for (int i = 0; i < n; i++) rank[sa[i]] = i;
        construct_lcp();
        prec();
    }
};

```

```

        build();
    }
    void construct_lcp() {
        int k = 0;
        lcp.resize(n - 1, 0);
        for (int i = 0; i < n; i++) {
            if (rank[i] == n - 1) {
                k = 0;
                continue;
            }
            int j = sa[rank[i] + 1];
            while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
            lcp[rank[i]] = k;
            if (k) k--;
        }
    }
    void prec() {
        lg.resize(n, 0);
        for (int i = 2; i < n; i++) lg[i] = lg[i / 2] + 1;
    }
    void build() {
        int sz = n - 1;
        t.resize(sz);
        for (int i = 0; i < sz; i++) {
            t[i].resize(LG);
            t[i][0] = lcp[i];
        }
        for (int k = 1; k < LG; ++k) {
            for (int i = 0; i + (1 << k) - 1 < sz; ++i) {
                t[i][k] = min(t[i][k - 1], t[i + (1 << (k - 1))][k - 1]);
            }
        }
    }
    int query(int l, int r) { // minimum of lcp[l], ..., lcp[r]
        int k = lg[r - l + 1];
        return min(t[l][k], t[r - (1 << k) + 1][k]);
    }
    int get_lcp(int i, int j) { // lcp of suffix starting from i and j
        if (i == j) return n - i;
        int l = rank[i], r = rank[j];
        if (l > r) swap(l, r);
        return query(l, r - 1);
    }
};

```

```

    }
    int lower_bound(string &t) {
        int l = 0, r = n - 1, k = t.size(), ans = n;
        while (l <= r) {
            int mid = l + r >> 1;
            if (s.substr(sa[mid], min(n - sa[mid], k)) >= t)
                ans = mid, r = mid - 1;
            else l = mid + 1;
        }
        return ans;
    }
    int upper_bound(string &t) {
        int l = 0, r = n - 1, k = t.size(), ans = n;
        while (l <= r) {
            int mid = l + r >> 1;
            if (s.substr(sa[mid], min(n - sa[mid], k)) > t) ans
                = mid, r = mid - 1;
            else l = mid + 1;
        }
        return ans;
    }
    // occurrences of s[p, ..., p + len - 1]
    pair<int, int> find_occurrence(int p, int len) {
        p = rank[p];
        pair<int, int> ans = {p, p};
        int l = 0, r = p - 1;
        while (l <= r) {
            int mid = l + r >> 1;
            if (query(mid, p - 1) >= len) ans.first = mid, r = mid - 1;
            else l = mid + 1;
        }
        l = p + 1, r = n - 1;
        while (l <= r) {
            int mid = l + r >> 1;
            if (query(p, mid - 1) >= len) ans.second = mid, l = mid + 1;
            else r = mid - 1;
        }
        return ans;
    }
};

```

6 DP

6.1 CHT

```
struct Line {
```

```

mutable LL m, c, p;
bool operator<(const Line& o) const { return m < o.m; }
bool operator<(LL x) const { return p < x; }
};
/* this calculates maximum value of m * x + c over all
lines */
/* to get minimum value use m = -m , c = -c , query(x) =
-query(x) */
struct LineContainer : multiset<Line, less<>> {
    /* (for doubles, use inf = 1/.0, div(a,b) = a/b) */
    static const LL inf = LLONG_MAX;
    LL div(LL a, LL b) { /* floored division */
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->m == y->m)
            x->p = x->c > y->c ? inf : -inf;
        else
            x->p = div(y->c - x->c, x->m - y->m);
        return x->p >= y->p;
    }
    void add(LL m, LL c) {
        auto z = insert({m, c, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y =
erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p) isect
(x, erase(y));
    }
    LL query(LL x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.m * x + l.c;
    }
};

```

6.2 CatalanDp

```

const int nmax = 1e4 + 1;
const int mod = 1000000007;
int catalan[nmax + 1]; /* // comb formula: ((2n)Cn)-((2n)
C(n-1)) =
(1/(n+1))*((2n)Cn) */
void genCatalan(int n) {
    catalan[0] = catalan[1] = 1;

```

```

    for (int i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (int j = 0; j < i; j++) {
            catalan[i] += (catalan[j] * catalan[i - j - 1]) %
mod;
            if (catalan[i] >= mod) {
                catalan[i] -= mod;
            }
        }
    }
}

```

6.3 DearrangementDP

```

const int nmax = 2e5 + 1;
int drng[nmax + 1];
void gen_drng(int n) {
    drng[2] = 1;
    for (int i = 3; i <= n; i++) {
        drng[i] = ((i - 1) * ((drng[i - 2] + drng[i - 1])
% mod)) % mod;
    }
}

```

6.4 Li Chao Tree

```

using ll = long long;
const ll inf = 2e18;

struct Line {
    ll m, c;
    ll eval(ll x) {
        return m * x + c;
    }
};

struct node {
    Line line;
    node* left = nullptr;
    node* right = nullptr;
    node(Line line) : line(line) {}
    void add_segment(Line nw, int l, int r, int L, int R)
    {
        if (l > r || r < L || l > R) return;
        int m = (l + 1 == r ? l : (l + r) / 2);
        if (l >= L and r <= R) {
            bool lef = nw.eval(l) < line.eval(l);
            bool mid = nw.eval(m) < line.eval(m);
            if (mid) swap(line, nw);

```

```

            if (l == r) return;
            if (lef != mid) {
                if (left == nullptr) left = new node(nw);
                else left -> add_segment(nw, l, m, L, R);
            }
            else {
                if (right == nullptr) right = new node(nw);
                else right -> add_segment(nw, m + 1, r, L, R);
            }
            return;
        }
        if (max(l, L) <= min(m, R)) {
            if (left == nullptr) left = new node({0, inf});
            left -> add_segment(nw, l, m, L, R);
        }
        if (max(m + 1, L) <= min(r, R)) {
            if (right == nullptr) right = new node({0, inf});
            right -> add_segment(nw, m + 1, r, L, R);
        }
    }
}

ll query_segment(ll x, int l, int r, int L, int R) {
    if (l > r || r < L || l > R) return inf;
    int m = (l + 1 == r ? l : (l + r) / 2);
    if (l >= L and r <= R) {
        ll ans = line.eval(x);
        if (l < r) {
            if (x <= m && left != nullptr) ans = min(ans,
left -> query_segment(x, l, m, L, R));
            if (x > m && right != nullptr) ans = min(ans,
right -> query_segment(x, m + 1, r, L, R));
        }
        return ans;
    }
    ll ans = inf;
    if (max(l, L) <= min(m, R)) {
        if (left == nullptr) left = new node({0, inf});
        ans = min(ans, left -> query_segment(x, l, m, L, R)
);
    }
    if (max(m + 1, L) <= min(r, R)) {
        if (right == nullptr) right = new node({0, inf});
        ans = min(ans, right -> query_segment(x, m + 1, r,
L, R));
    }
    return ans;
}

```

```
};

struct LiChaoTree {
    int L, R;
    node* root;
    LiChaoTree() : L(numeric_limits<int>::min() / 2), R(
        numeric_limits<int>::max() / 2), root(nullptr) {}
    LiChaoTree(int L, int R) : L(L), R(R) {
        root = new node({0, inf});
    }
    void add_line(Line line) {
        root -> add_segment(line, L, R, L, R);
    }
    // y = mx + b: x in [l, r]
    void add_segment(Line line, int l, int r) {
        root -> add_segment(line, L, R, l, r);
    }
    ll query(ll x) {
        return root -> query_segment(x, L, R, L, R);
    }
    ll query_segment(ll x, int l, int r) {
        return root -> query_segment(x, l, r, L, R);
    }
};
```

6.5 SOS

```
for (int mask = 0; mask < (1 << N); ++mask) {
    dp[mask][0] = A[mask];
    for (int i = 0; i < N; ++i) {
        if (mask & (1 << i))
            dp[mask][i] = dp[mask][i - 1] + dp[mask ^ (1 << i)
                ][i - 1];
        else
            dp[mask][i] = dp[mask][i - 1];
    }
    F[mask] = dp[mask][N - 1];
}
// good for inc-exc
for (int i = 0; i < (1 << N); ++i) F[i] = A[i];
for (int i = 0; i < N; ++i)
    for (int mask = 0; mask < (1 << N); ++mask)
        if (mask & (1 << i)) F[mask] += F[mask ^ (1 << i)];
```

6.6 Grundy

/* single pile game -> greedy or game dp multiple pile game and

```
* disjunctive(before playing, choose 1 pile) -> NIM
game else -> Grundy(converts
* n any game piles to n NIM piles) Grundy(x) -> the
smallest nonreachable Grundy
* value there are n pile of games and k type of moves.
if XOR(Grundy(games)) ==
* 0: losing state else winning state */
vector<int> moves, dp;
int mex(vector<int>& a) {
    set<int> b(a.begin(), a.end());
    for (int i = 0; ++i)
        if (!b.count(i)) return i;
}
int Grundy(int x) {
    if (dp[x] != -1) return dp[x];
    vector<int> reachable;
    for (auto m : moves) {
        if (x - m < 0) continue;
        int val = Grundy(x - m);
        reachable.push_back(val);
    }
    return dp[x] = mex(reachable);
}
```

7 Geometry

7.1 2D everything

```
using LL = long long; using ULL = unsigned long long;
const double PI = acos(-1), EPS = 1e-10; template <
typename DT> DT sq(DT x) {return x * x;} template <
typename DT> int dcmp(DT x) {return fabs(x) < EPS ? 0 :
(x < 0 ? -1 : 1);} template <typename DT> class point {
public: DT x, y; point() = default; point(DT x, DT y): x(
x), y(y) {}; template <typename X> point(point<X> p): x(
p.x), y(p.y) {}; point operator + (const point& rhs)
const { return point(x + rhs.x, y + rhs.y); } point
operator - (const point& rhs) const { return point(x -
rhs.x, y - rhs.y); } point operator * (const point& rhs)
const { return point(x * rhs.x - y * rhs.y, x * rhs.y +
y * rhs.x); } point operator / (const point& rhs) const
{ return *this * point(rhs.x, -rhs.y) / ~(rhs); } point
operator * (DT M) const { return point(M * x, M * y); }
point operator / (DT M) const { return point(x / M, y /
M); } bool operator < (point rhs) const { return x < rhs
.x or (x == rhs.x and y < rhs.y); } bool operator == (
const point& rhs) const { return x == rhs.x and y == rhs
.y; } bool operator <= (const point& rhs) const { return
```

```
*this < rhs or *this == rhs; } bool operator != (const
point& rhs) const { return x != rhs.x or y != rhs.y; }
DT operator & (const point& rhs) const { return x * rhs.
y - y * rhs.x; } /* cross product */ DT operator ^ (
const point& rhs) const { return x * rhs.x + y * rhs.y;
} /* dot product */ DT operator ~(const point& rhs) const {return sq(x)
+ sq(y); } /* square of norm */ point operator - (const
point& rhs) const { return *this - rhs; } friend ostream& operator >>
(ostream& is, point& p) { return is >> p.x >> p.y; }
friend ostream& operator << (ostream& os, const point& p)
{ return os << p.x << " " << p.y; } friend DT DisSq(
const point& a, const point& b) { return sq(a.x - b.x) + sq
(a.y - b.y); } friend DT TriArea(const point& a, const
point& b, const point& c) { return (b - a) & (c - a); }
friend DT UTriArea(const point& a, const point& b, const
point& c) { return abs(TriArea(a, b, c)); } friend bool
Collinear(const point& a, const point& b, const point&
c) { return UTriArea(a, b, c) < EPS; } friend double
Angle(const point& u) { return atan2(u.y, u.x); } friend
double Angle(const point& a, const point& b) { double
ans = Angle(b) - Angle(a); return ans <= -PI ? ans + 2*
PI : (ans > PI ? ans - 2*PI : ans); } friend double
Angle(const point& A, const point& B, const point& C) {
point BA = A - B; point BC = C - B; double dot = BA ^ BC
; double magBA = sqrt(~BA); double magBC = sqrt(~BC);
double cosTheta = dot / (magBA * magBC); cosTheta = std
::max(-1.0, std::min(1.0, cosTheta)); return acos(
cosTheta); } point Perp(const point& a) { return point(-a
.y, a.x); } point Conj(const point& a) { return point(a.x
, -a.y); } }; template <typename DT> using polygon =
vector<point<DT>>; template <typename DT> class
polarComp { point<DT> 0, dir; bool half(point<DT> p) {
return dcmp(dir & p) < 0 || (dcmp(dir & p) == 0 && dcmp
(dir ^ p) > 0); } public: polarComp(point<DT> 0 = point
(0, 0), point<DT> dir = point(1, 0)) : 0(0), dir(dir)
{} bool operator() (point<DT> p, point<DT> q) { return
make_tuple(half(p), 0) < make_tuple(half(q), (p & q));
} }; /* given a pivot point and an initial direction,
sorts by Angle with the given direction */
```

```
template <typename DT> class line { public: point<DT>
dir, 0; /* direction of vector and starting point */
line(point<DT> p, point<DT> q): dir(q - p), 0(p) {};
bool Contains(const point<double>& p) { return fabs(p -
0 & dir) < EPS; } /* checks whether the line Contains a
certain point */ template <typename XT> point<XT> At(
```

```

XT t){ return point <XT> (dir) * t + 0; } /* inserts
value of t in the vector representation, finds the point
which is 0 + Dir*t */ double AtInv(const point <double>
&p){ return abs(dir.x) > 0 ? (p - 0).x / dir.x : (p - 0)
.y / dir.y; } /* if the line Contains a point, gives
the value t such that, p = 0+Dir*t */ line Perp(point <
DT> p){ return line(p, p + (-dir.y,dir.x)); } point <DT>
ProjOfPoint(const point <DT> &P) { return 0 + dir * ((P
- 0) ^ dir) / (~dir); } double DisOfPoint(const point <
DT> &P) { return fabs(dir & (P - 0))/sqrt(~(dir)); }
friend bool Parallel(line& L, line& R){ return fabs(R.
dir & L.dir) < EPS; } friend int Intersects(line& L,
line& R){ return Parallel(L, R) ? R.Contains(L.0) ? -1 :
0 : 1; } friend pair <double, double> IntersectionAt(
line &L, line &R){ double r = double((L.0 - R.0) & L.dir
)/(R.dir & L.dir); double l = double((R.0 - L.0) & R.dir
)/(L.dir & R.dir); return {l, r}; } friend pair <int,
point<double>> IntersectionPoint(line L, line R,int _L =
0, int _R = 0){ /* _L and _R can be 0 to 3, 0 is a
normal line, 3 is a segment, 1 and 2 are rays (
considered bitwise) */ int ok = Intersects(L, R); if(ok
== 0) return {0, {0, 0}}; if(ok == 1){ auto [l,r] =
IntersectionAt(L, R); if(l < (0-EPS) and _L & 2 ) return
{0, {0, 0}}; if(l > (1+EPS) and _L & 1) return {0, {0,
0}}; if(r < (0-EPS) and _R & 2 ) return {0, {0, 0}}; if(
r > (1+EPS) and _R & 1) return {0, {0, 0}}; return {1, L
.At(1)}; } return {-1, {0,0}}; /* they are the same line
*/ } };
```

```

template <typename DT> class circle { public: point <DT>
0; DT R; circle(const point <DT> &0 = {0, 0}, DT R = 0)
: 0(0), R(R) {} /* the next two make sense only on
circle <double> */ circle(const point <DT> &A, const
point <DT> &B, const point <DT> &C){ point <DT> X = (A +
B) / 2, Y = (B + C) / 2, d1 = Perp(A - B), d2 = Perp(B
- C); 0 = IntersectionPoint(line(X, d1), line(Y, d2)).
second; R = sqrt(~(0 - A)); } circle(const point <DT> &A
, const point <DT> &B, DT R){ point <DT> X = (A + B) /
2, d = Perp(A - B); d = d * (R / sqrt(~(d))); 0 = X + d;
R = sqrt(~(0 - A)); } double SectorArea(double ang) {
/* Area of a sector of circle */ return ang* R * R * .5;
} double SectorArea(const point <DT> &a, const point <DT>
&b) { return SectorArea(Angle(a - 0, b - 0)); } double
ChordArea(const point <DT> &a, const point <DT> &b) {
/* Area between sector and its chord */ return
SectorArea(a, b) - 0.5 * TriArea(0, a, b); } int
```

```

Contains(const point <DT> &p){ /* 0 for outside, 1 for
inside, -1 for on the circle */ DT d = DisSq(0, p);
return d > R * R ? 0 : (d == R * R ? -1 : 1); } friend
tuple <int, point <DT>, point <DT>> IntersectionPoint(
const circle &a,const circle &b) { if(a.R == b.R and a.0
== b.0) return {-1, {0, 0}, {0, 0}}; double d = sqrt(
DisSq(a.0, b.0)); if(d > a.R + b.R or d < fabs(a.R - b.R
)) return {0, {0, 0}, {0, 0}}; double z = (sq(a.R) + sq(
d) - sq(b.R)) / (2 * d); double y = sqrt(sq(a.R) - sq(z)
); point <DT> 0 = b.0 - a.0, h = Perp(0) * (y / sqrt(~0)
); 0 = a.0 + 0 * (z / sqrt(~0)); return make_tuple(1 +
(~h) > EPS), 0 - h, 0 + h); } friend tuple <int, point
<DT>, point <DT>> IntersectionPoint(const circle &C,
line <DT> L) { point <DT> P = L.ProjOfPoint(C.0); double
D = DisSq(C.0, P); if(D > C.R * C.R) return {0, {0, 0},
{0, 0}}; double x = sqrt(C.R * C.R - D); point <DT> h =
L.dir * (x / sqrt(~L.dir)); return {1 + (x > EPS), P -
h, P + h}; } double SegmentedArea(point <DT> &a, point <
DT> &b) { /* signed area of the intersection between the
circle and triangle OAB */ double ans = SectorArea(a, b
); line <DT> L(a, b); auto [cnt, p1, p2] =
IntersectionPoint(*this, L); if(cnt < 2) return ans;
double t1 = L.AtInv(p1), t2 = L.AtInv(p2); if(t2 < 0 or
t1 > 1) return ans; if(t1 < 0) p1 = a; if(t2 > 1) p2 = b
; return ans - ChordArea(p1, p2); } };
```

```

namespace polygon_algo{ template <typename DT> polygon <
DT> ConvexHull(polygon <DT> &PT){ sort(PT.begin(), PT.
end()); int m = 0, n = PT.size(); polygon <DT> hull(n +
n + 2); for(int i = 0; i < n; i++){ for( ; m > 1 and
TriArea(hull[m-2], hull[m-1], PT[i]) <= 0; m-- ); hull[m
++] = PT[i];} for(int i = n - 2, k = m; i >= 0; i--){
for( ; m > k and TriArea(hull[m - 2], hull[m - 1], PT[i
]) <= 0; m--); hull[m++] = PT[i]; } if(n > 1) m--; while
(hull.size() > m) hull.pop_back(); return hull; }
template <typename DT> double MinimumBoundingBox(polygon
<DT> P){ auto p = ConvexHull(P); int n = p.size();
double area = 1e20 + 5; for(int i = 0, l = 1, r = 1, u =
1 ; i < n ; i++){ point <DT> edge = (p[(i+1)%n]-p[i])/
sqrt(DisSq(p[i], p[(i+1)%n])); for( ; (edge ^ p[r%n]-p[i
]) < (edge ^ p[(r+1)%n] - p[i]); r++); for( ; u < r || (
edge & p[u%n] - p[i]) < (edge & p[(u+1)%n] - p[i]); u++)
; for( ; l < u || (edge ^ p[l%n] - p[i]) > (edge ^ p[(l
+1)%n] - p[i]); l++); double w = (edge ^ p[r%n]-p[i]) -
(edge ^ p[l%n] - p[i]); double h = UTriArea(p[u%n], p[i
], p[(i+1)%n])/sqrt(DisSq(p[i], p[(i+1)%n])); area = min
```

```

(area,w*h); } if(area>1e19) area = 0; return area; }
template <typename DT> DT FarthestPairOfPoints(polygon <
DT> p){ p = ConvexHull(p); int n = p.size(); DT ans = -1
e9; for(int i = 0, j = 1; i < n; i++) { for( ; UTriArea(
p[i], p[(i + 1) % n], p[(j + 1) % n]) > UTriArea(p[i], p
[(i + 1) % n], p[j]) ; j = (j + 1) % n ) ; ans = max(ans
, DisSq(p[i], p[j])); ans = max(ans, DisSq(p[(i + 1) % n
], p[j])); } return ans; /* will return square of the
answer. */ } template <typename DT> int
PointInConvexPolygon(polygon <int> :: iterator b,
polygon <int> :: iterator e, const point <DT> &0){
polygon <int> :: iterator lo = b + 2, hi = e - 1, ans =
e; while(lo <= hi) { auto mid = lo + (hi - lo) / 2; if(
TriArea(*b, 0, *mid) >= 0) ans = mid, hi = mid - 1; else
lo = mid + 1; } if (ans == e or abs(UTriArea(*b, *(ans
- 1), *ans) - UTriArea(*b, *(ans - 1), 0) - UTriArea(*b,
*ans, 0) - UTriArea(*(ans - 1), *ans, 0)) > EPS) return
0; else return (Collinear(*b, *(b + 1), 0) or Collinear
(*(e - 1), *b, 0) or Collinear(*(ans), *(ans - 1), 0)) ?
-1 : 1; } /* 0 for outside, -1 for on border, 1 for
inside */ template <typename DT> int PointInPolygon(
polygon <DT> &P, point <DT> pt) { int n = P.size(); int
cnt = 0; for(int i = 0, j = 1; i < n; i++, j = (j + 1) %
n) { if(TriArea(pt, P[i], P[j]) == 0 and min(P[i], P[j
]) <= pt and pt <= max(P[i], P[j])) return -1; cnt += ((
P[j].y >= pt.y) - (P[i].y >= pt.y)) * TriArea(pt, P[i],
P[j]) > 0; } return cnt & 1; } } using namespace
polygon_algo;
```

```

/* CLOSEST PAIR OF POINTS */
template <typename DT> Dis(point <DT> a, point <DT> b){
return ~(a - b); } template <typename DT> DT
Closest_Distance(vector <point <DT>> &v) { int n = v.
size(); sort(v.begin(), v.end()); auto cmp = [](point <
DT> a, point <DT> b) {return (a.y < b.y || (a.y == b.y
&& a.x < b.x));}; set <point <DT>, decltype(cmp)> s(cmp)
; DT best = 1e18; int j = 0; for (int i = 0; i < n; i++)
{ while (sq(v[i].x - v[j].x) >= best) { s.erase(v[j]);
j = (j + 1) % n; } DT d = best; auto it1 = s.lower_bound
( point <DT>(v[i].x, v[i].y - d )); auto it2 = s.
upper_bound( point <DT>(v[i].x, v[i].y + d )); for (auto
it = it1; it != it2; it++) best = min(best, Dis(v[i], *
it)); s.insert(v[i]); } return best; }
```

7.2 3D


```
template <typename DT> class Point { public: DT x, y, z;
    Point() {}; Point(DT x, DT y, DT z) : x(x), y(y), z(z)
{} template <typename X> Point(Point<X> p) : x(p.x), y(p
.y), z(p.z) {} Point operator+(const Point& rhs) const {
    return Point(x + rhs.x, y + rhs.y, z + rhs.z); } Point
operator-(const Point& rhs) const { return Point(x - rhs
.x, y - rhs.y, z - rhs.z); } Point operator*(DT M) const
{ return Point(M * x, M * y, M * z); } Point operator/(
DT M) const { return Point(x / M, y / M, z / M); } /*
cross product */ Point operator&(const Point& rhs) const
{ return Point(y * rhs.z - z * rhs.y, z * rhs.x - x *
rhs.z, x * rhs.y - y * rhs.x); } /* dot product */ DT
operator^(const Point& rhs) const { return x * rhs.x + y
* rhs.y + z * rhs.z; } bool operator==(const Point& rhs
) const { return x == rhs.x && y == rhs.y && z == rhs.z;
} bool operator!=(const Point& rhs) const { return !(*
this == rhs); } friend std::istream& operator>>(std::
istream& is, Point& p) { return is >> p.x >> p.y >> p.z;
} friend std::ostream& operator<<(std::ostream& os,
const Point& p) { return os << p.x << " " << p.y << " "
<< p.z; } friend DT DisSq(const Point& a, const Point& b
) { return (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.
y - b.y) + (a.z - b.z) * (a.z - b.z); } };
```

```
optional<Point<double>> ray_intersects_triangle( const
Point<double>& origin, const Point<double>& ray_vector,
const array<Point<double>, 3>& triangle) { constexpr
double epsilon = std::numeric_limits<double>::epsilon();
auto [A, B, C] = triangle; Point<double> edge1 = B - A;
Point<double> edge2 = C - A; Point<double> ray_cross_e2
= ray_vector & edge2; double det = edge1 ^ ray_cross_e2
; if (det > -epsilon && det < epsilon) return {}; /* Ray
is parallel to this triangle. */ double inv_det = 1.0 /
det; Point<double> s = ray_origin - A; double u =
inv_det * (s ^ ray_cross_e2); if (u < 0 || u > 1) return
{}; Point<double> s_cross_e1 = s & edge1; double v =
inv_det * (ray_vector ^ s_cross_e1); if (v < 0 || u + v
> 1) return {}; /* Compute t to find the intersection
Point */ double t = inv_det * (edge2 ^ s_cross_e1); if (
t > epsilon) return ray_origin + ray_vector * t; /* ray
intersection */ else return {}; /* Line intersection but
not ray intersection */ }
```

```
/* HOW TO IMPLEMENT auto tmp = ray_intersects_triangle (
origin, ray, v[i]); if (tmp.has_value ()) Point <double>
intersection_point = tmp.value (); */
```

7.3 MinDisSquares

```
typedef long double ld;
const ld eps = 1e-12;
int cmp(ld x, ld y = 0, ld tol = eps) {
    return (x <= y + tol) ? (x + tol < y) ? -1 : 0 : 1;
}
struct point {
    ld x, y;
    point(ld a, ld b) : x(a), y(b) {}
    point() {}
};
struct square {
    ld x1, x2, y1, y2, a, b, c;
    point edges[4];
    square(ld _a, ld _b, ld _c) {
        a = _a, b = _b, c = _c;
        x1 = a - c * 0.5;
        x2 = a + c * 0.5;
        y1 = b - c * 0.5;
        y2 = b + c * 0.5;
        edges[0] = point(x1, y1);
        edges[1] = point(x2, y1);
        edges[2] = point(x2, y2);
        edges[3] = point(x1, y2);
    }
};
ld min_dist(point& a, point& b) {
    ld x = a.x - b.x, y = a.y - b.y;
    return sqrt(x * x + y * y);
}
bool point_in_box(square s1, point p) {
    if (cmp(s1.x1, p.x) != 1 && cmp(s1.x2, p.x) != -1 &&
        cmp(s1.y1, p.y) != 1 &&
            cmp(s1.y2, p.y) != -1)
        return true;
    return false;
}
bool inside(square& s1, square& s2) {
    for (int i = 0; i < 4; ++i)
        if (point_in_box(s2, s1.edges[i])) return true;
    return false;
}
bool inside_vert(square& s1, square& s2) {
    if ((cmp(s1.y1, s2.y1) != -1 && cmp(s1.y1, s2.y2) !=
1) ||
```

```
(cmp(s1.y2, s2.y1) != -1 && cmp(s1.y2, s2.y2) != 1)
)
    return true;
    return false;
}
bool inside_hori(square& s1, square& s2) {
    if ((cmp(s1.x1, s2.x1) != -1 && cmp(s1.x1, s2.x2) !=
1) ||
        (cmp(s1.x2, s2.x1) != -1 && cmp(s1.x2, s2.x2) != 1)
)
        return true;
    return false;
}
ld min_dist(square& s1, square& s2) {
    if (inside(s1, s2) || inside(s2, s1)) return 0;
    ld ans = 1e100;
    for (int i = 0; i < 4; ++i)
        for (int j = 0; j < 4; ++j)
            ans = min(ans, min_dist(s1.edges[i], s2.edges[j]));
    if (inside_hori(s1, s2) || inside_hori(s2, s1)) {
        if (cmp(s1.y1, s2.y2) != -1)
            ans = min(ans, s1.y1 - s2.y2);
        else if (cmp(s2.y1, s1.y2) != -1)
            ans = min(ans, s2.y1 - s1.y2);
    }
    if (inside_vert(s1, s2) || inside_vert(s2, s1)) {
        if (cmp(s1.x1, s2.x2) != -1)
            ans = min(ans, s1.x1 - s2.x2);
        else if (cmp(s2.x1, s1.x2) != -1)
            ans = min(ans, s2.x1 - s1.x2);
    }
    return ans;
}
```

7.4 Picks Theorem

```
struct Point {
    long long x, y;
    Point() {}
    Point(long long x, long long y) : x(x), y(y) {}
}; // twice the area of polygon
long long double_area(Point poly[], int n) {
    long long res = 0;
    for (int i = 0, j = n - 1; i < n; j = i++) {
        res += (poly[j].x + poly[i].x) * (poly[j].y - poly[
i].y));
    }
}
```

```

    return abs(res);
} /// number of lattice points strictly on polygon
border
long long on_border(Point poly[], int n) {
    long long res = 0;
    for (int i = 0, j = n - 1; i < n; j = i++) {
        res += __gcd(abs(poly[i].x - poly[j].x), abs(poly[i].y - poly[j].y));
    }
    return res;
} /// number of lattice points strictly inside polygon
long long interior(Point poly[], int n) {
    long long res = 2 + double_area(poly, n) - on_border(poly, n);
    return res / 2;
}

```

7.5 convex hull

```

template <typename DT>
class point {
public:
    DT x, y;
    point() = default;
    point(DT x, DT y): x(x), y(y) {}
    bool operator < (point rhs) const { return x < rhs.x
        || (x == rhs.x && y < rhs.y); }
    bool operator == (const point &rhs) const { return x
        == rhs.x && y == rhs.y; }
    point operator - (const point &rhs) const { return
        point(x - rhs.x, y - rhs.y); }
    DT operator & (const point &rhs) const { return x *
        rhs.y - y * rhs.x; } // cross product
    friend DT orientation (const point &a, const point &b,
        const point &c) { return (b - a) & (c - a); }
};

```

```

template <typename DT>
using polygon = vector<point<DT>>;

```

```

template <typename DT>
polygon<DT> ConvexHull(polygon<DT> &PT) {
    sort(PT.begin(), PT.end());
    int m = 0, n = PT.size();
    polygon<DT> hull(n + n + 2);
    for (int i = 0; i < n; i++) {

```

```

        for (; m > 1 && orientation (hull[m - 2], hull[m -
            1], PT[i]) < 0; m--);
        hull[m++] = PT[i];
    }
    for (int i = n - 2, k = m; i >= 0; i--) {
        for (; m > k && orientation (hull[m - 2], hull[m -
            1], PT[i]) < 0; m--);
        hull[m++] = PT[i];
    }
    if (n > 1) m--;
    hull.resize(m);
    return hull;
}
// Andrews monotone chain algorithm

```

7.6 convex

```

/* /// minkowski sum of two polygons in O(n) */ Polygon
minkowskiSum(
    Polygon A, Polygon B) {
    int n = A.size(), m = B.size();
    rotate(A.begin(), min_element(A.begin(), A.end()), A.
        end());
    rotate(B.begin(), min_element(B.begin(), B.end()), B.
        end());
    A.push_back(A[0]);
    B.push_back(B[0]);
    for (int i = 0; i < n; i++) A[i] = A[i + 1] - A[i];
    for (int i = 0; i < m; i++) B[i] = B[i + 1] - B[i];
    Polygon C(n + m + 1);
    C[0] = A.back() + B.back();
    merge(A.begin(), A.end() - 1, B.begin(), B.end() - 1,
        C.begin() + 1,
        polarComp(Point(0, 0), Point(0, -1)));
    for (int i = 1; i < C.size(); i++) C[i] = C[i] + C[i -
        1];
    C.pop_back();
    return C;
} /* // finds the rectangle with minimum area enclosing
a convex polygon and //
    the rectangle with minimum perimeter enclosing a
    convex polygon // Tf Ti
    Same */
pair<Tf, Tf> rotatingCalipersBoundingBox(const Polygon&
p) {
    using Linear::distancePointLine;
    int n = p.size();

```

```

    int l = 1, r = 1, j = 1;
    Tf area = 1e100;
    Tf perimeter = 1e100;
    for (int i = 0; i < n; i++) {
        Point v = (p[(i + 1) % n] - p[i]) / length(p[(i + 1)
            % n] - p[i]);
        while (dcmp(dot(v, p[r % n] - p[i]) - dot(v, p[(r +
            1) % n] - p[i])) < 0)
            r++;
        while (j < r || dcmp(cross(v, p[j % n] - p[i]) -
            cross(v, p[(j + 1) % n] - p[i])) <
            0)
            j++;
        while (l < j ||
            dcmp(dot(v, p[l % n] - p[i]) - dot(v, p[(l +
            1) % n] - p[i])) > 0)
            l++;
        Tf w = dot(v, p[r % n] - p[i]) - dot(v, p[l % n] - p
            [i]);
        Tf h = distancePointLine(p[j % n], Line(p[i], p[(i +
            1) % n]));
        area = min(area, w * h);
        perimeter = min(perimeter, 2 * w + 2 * h);
    }
    return make_pair(area, perimeter);
} /* // returns the left side of polygon u after cutting
it by ray a->b */
Polygon cutPolygon(Polygon u, Point a, Point b) {
    using Linear::lineLineIntersection;
    using Linear::onSegment;
    Polygon ret;
    int n = u.size();
    for (int i = 0; i < n; i++) {
        Point c = u[i], d = u[(i + 1) % n];
        if (dcmp(cross(b - a, c - a)) >= 0) ret.push_back(c);
        ;
        if (dcmp(cross(b - a, d - c)) != 0) {
            Point t;
            lineLineIntersection(a, b - a, c, d - c, t);
            if (onSegment(t, Segment(c, d))) ret.push_back(t);
        }
    }
    return ret;
} /* // returns true if point p is in or on triangle abc
*/

```

```

bool pointInTriangle(Point a, Point b, Point c, Point p)
{
    return dcmp(cross(b - a, p - a)) >= 0 && dcmp(cross(c - b, p - b)) >= 0 &&
           dcmp(cross(a - c, p - c)) >= 0;
} /* // pt must be in ccw order with no three collinear
points // returns inside
    = -1, on = 0, outside = 1 */
int pointInConvexPolygon(const Polygon& pt, Point p) {
    int n = pt.size();
    assert(n >= 3);
    int lo = 1, hi = n - 1;
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        if (dcmp(cross(pt[mid] - pt[0], p - pt[0])) > 0)
            lo = mid;
        else
            hi = mid;
    }
    bool in = pointInTriangle(pt[0], pt[lo], pt[hi], p);
    if (!in) return 1;
    if (dcmp(cross(pt[lo] - pt[lo - 1], p - pt[lo - 1]))
        == 0) return 0;
    if (dcmp(cross(pt[hi] - pt[lo], p - pt[lo])) == 0)
        return 0;
    if (dcmp(cross(pt[hi] - pt[(hi + 1) % n], p - pt[(hi + 1) % n])) == 0)
        return 0;
    return -1;
} /* // Extreme Point for a direction is the farthest
point in that direction //
    u is the direction for extremeness */
int extremePoint(const Polygon& poly, Point u) {
    int n = (int)poly.size();
    int a = 0, b = n;
    while (b - a > 1) {
        int c = (a + b) / 2;
        if (dcmp(dot(poly[c] - poly[(c + 1) % n], u)) >= 0
            &&
            dcmp(dot(poly[c] - poly[(c - 1 + n) % n], u)) >= 0) {
            return c;
        }
    }
    bool a_up = dcmp(dot(poly[(a + 1) % n] - poly[a], u))
        >= 0;

```

```

    bool c_up = dcmp(dot(poly[(c + 1) % n] - poly[c], u))
        >= 0;
    bool a_above_c = dcmp(dot(poly[a] - poly[c], u)) > 0;
    if (a_up && !c_up)
        b = c;
    else if (!a_up && c_up)
        a = c;
    else if (a_up && c_up) {
        if (a_above_c)
            b = c;
        else
            a = c;
    } else {
        if (!a_above_c)
            b = c;
        else
            a = c;
    }
}
if (dcmp(dot(poly[a] - poly[(a + 1) % n], u)) > 0 &&
    dcmp(dot(poly[a] - poly[(a - 1 + n) % n], u)) > 0)
    return a;
return b % n;
} /* // For a convex polygon p and a line l, returns a
list of segments // of p
    that touch or intersect line l. // the i'th segment
    is considered (p[i],
    p[(i + 1) modulo |p|]) // #1 If a segment is
    collinear with the line, only
    that is returned // #2 Else if l goes through i'th
    point, the i'th segment
    is added // Complexity: O(lg |p|) */
vector<int> lineConvexPolyIntersection(const Polygon& p,
Line l) {
    assert((int)p.size() >= 3);
    assert(l.a != l.b);
    int n = p.size();
    vector<int> ret;
    Point v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);
    if (!olf || !ort) {
        int idx = (!olf ? lf : rt);

```

```

        if (orient(l.a, l.b, p[(idx - 1 + n) % n]) == 0)
            ret.push_back((idx - 1 + n) % n);
        else
            ret.push_back(idx);
        return ret;
    }
    if (olf == ort) return ret;
    for (int i = 0; i < 2; ++i) {
        int lo = i ? rt : lf;
        int hi = i ? lf : rt;
        int olo = i ? ort : olf;
        while (true) {
            int gap = (hi - lo + n) % n;
            if (gap < 2) break;
            int mid = (lo + gap / 2) % n;
            int omid = orient(l.a, l.b, p[mid]);
            if (!omid) {
                lo = mid;
                break;
            }
            if (omid == olo)
                lo = mid;
            else
                hi = mid;
        }
        ret.push_back(lo);
    }
    return ret;
} /* // Calculate [ACW, CW] tangent pair from an
external point */
constexpr int CW = -1, ACW = 1;
bool isGood(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) != -dir;
}
Point better(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) == dir ? u : v;
}
Point pointPolyTangent(const Polygon& pt, Point Q, int
dir, int lo, int hi) {
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid - 1], Q, dir);
        bool nxt = isGood(pt[mid], pt[mid + 1], Q, dir);
        if (pvs && nxt) return pt[mid];
        if (!(pvs || nxt)) {

```



```

Point p1 = pointPolyTangent(pt, Q, dir, mid + 1, hi
);
Point p2 = pointPolyTangent(pt, Q, dir, lo, mid -
1);
return better(p1, p2, Q, dir);
}
if (!pvs) {
    if (orient(Q, pt[mid], pt[lo]) == dir)
        hi = mid - 1;
    else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
        hi = mid - 1;
    else
        lo = mid + 1;
}
if (!nxt) {
    if (orient(Q, pt[mid], pt[lo]) == dir)
        lo = mid + 1;
    else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
        hi = mid - 1;
    else
        lo = mid + 1;
}
}
Point ret = pt[lo];
for (int i = lo + 1; i <= hi; i++) ret = better(ret,
pt[i], Q, dir);
return ret;
} /* // [ACW, CW] Tangent */
pair<Point, Point> pointPolyTangents(const Polygon& pt,
Point Q) {
    int n = pt.size();
    Point acw_tan = pointPolyTangent(pt, Q, ACW, 0, n - 1)
;
    Point cw_tan = pointPolyTangent(pt, Q, CW, 0, n - 1);
    return make_pair(acw_tan, cw_tan);
}

```

8 Misc

8.1 All Macros

```

//#pragma GCC optimize("Ofast")
//#pragma GCC optimization ("O3")
//#pragma comment(linker, "/stack:200000000")
//#pragma GCC optimize("unroll-loops")
//#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,
abm,mmx,avx,tune=native")
#include <ext/pb_ds/assoc_container.hpp>

```

```

#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//find_by_order(k) --> returns iterator to the kth
largest element counting from 0
//order_of_key(val) --> returns the number of items
in a set that are strictly smaller than our item
os.erase (os.find_by_order (os.order_of_key(v[i]))) //to
erase i-th element from ordered multiset
template <typename DT>
using ordered_set = tree <DT, null_type, less<DT>,
rb_tree_tag,tree_order_statistics_node_update>;
struct custom_hash { static uint64_t splitmix64 (
uint64_t x) { x += 0x9e3779b97f4a7c15; x = (x ^ (x >>
30)) * 0xbf58476d1ce4e5b9; x = (x ^ (x >> 27)) * 0
x94d049b133111eb; return x ^ (x >> 31); } size_t
operator () (uint64_t x) const { static const uint64_t
FIXED_RANDOM = chrono::steady_clock::now ().
time_since_epoch ().count (); return splitmix64 (x +
FIXED_RANDOM); } } Rng;
typedef gp_hash_table<int, int, custom_hash> gp;

int leap_years(int y) { return y / 4 - y / 100 + y /
400; } bool is_leap(int y) { return y % 400 == 0 || (y %
4 == 0 && y % 100 != 0); } bool __builtin_mul_overflow (
type1 a, type2 b, type3 &res) cin.tie(0)->ios_base::
sync_with_stdio(0); int getWeekday (int day, int month,
int year) { if (month <= 2) { month += 12; year -= 1; }
int f = (day + (13 * (month + 1)) / 5 + year + year / 4
- year / 100 + year / 400) % 7; return f; }

```

8.2 StressTest

```

#!/bin/bash
# Call as sh stress.sh ITERATIONS
g++ brute.cpp -o brute # brute solution
g++ cand.cpp -o cand # cand solution
g++ gen.cpp -o gen # test case gen
> all.txt
for i in $(seq 1 "$1") ; do
    echo "Attempt $i/$1"
    ./gen > in.txt
    echo "Attempt $i/$1" >> all.txt
    cat < in.txt >> all.txt
    ./brute < in.txt > out1.txt
    ./cand < in.txt > out2.txt
    diff -y out1.txt out2.txt > diff.txt
    if [ $? -ne 0 ] ; then

```

```

        echo -e "\nTest case:"
        cat in.txt
        echo -e "\nOutputs:"
        cat diff.txt
        break
    fi
done
files=("in.txt" "out1.txt" "out2.txt" "diff.txt" "cand"
"brute" "gen")
for file in "${files[@]}"; do
    rm "$file"
done

```

8.3 gen

```

mt19937 rng(random_device{}());
LL randomInt(LL low, LL high) {
    uniform_int_distribution<LL> dist(low, high);
    return dist(rng);
}
vector<pair<int, int>> generate_random_tree(int n) {
    vector<int> prufer(n - 2);
    for (int i = 0; i < n - 2; ++i) prufer[i] = randomInt
(1, n);
    vector<int> degree(n + 1, 1);
    for (int x : prufer) degree[x]++;
    priority_queue<int, vector<int>, greater<int>> pq;
    for (int i = 1; i <= n; ++i)
        if (degree[i] == 1) pq.push(i);
    vector<pair<int, int>> edges;
    for (int x : prufer) {
        int leaf = pq.top();
        pq.pop();
        edges.emplace_back(leaf, x);
        degree[leaf]--, degree[x]--;
        if (degree[x] == 1) pq.push(x);
    }
    int u = pq.top(); pq.pop();
    int v = pq.top(); pq.pop();
    edges.emplace_back(u, v);
    return edges;
}
vector<int> permutation(int n) {
    vector<int> p(n); iota(p.begin(), p.end(), 1);
    shuffle(p.begin(), p.end(), rng);
    return p;
}

```

9 Equations and Formulas

9.1 Catalan Numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} \quad C_0 = 1, C_1 = 1 \text{ and } C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

The number of ways to completely parenthesize $n+1$ factors.
The number of triangulations of a convex polygon with $n+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

The number of rooted full binary trees with $n+1$ leaves (vertices are not numbered). A rooted binary tree is full if every vertex has either two children or no children.

Number of permutations of $1, \dots, n$ that avoid the pattern 123 (or any of the other patterns of length 3); that is, the number of permutations with no three-term increasing sub-sequence. For $n = 3$, these permutations are 132, 213, 231, 312 and 321.

9.2 Stirling Numbers First Kind

The Stirling numbers of the first kind count permutations according to their number of cycles (counting fixed points as cycles of length one).

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1), \text{ where, } S(0, 0) = 1, S(n, 0) = S(0, n) = 0 \sum_{k=0}^n S(n, k) = n!$$

The unsigned Stirling numbers may also be defined algebraically, as the coefficient of the rising factorial:

$$x^{\bar{n}} = x(x+1)\dots(x+n-1) = \sum_{k=0}^n S(n, k) x^k$$

Lets $[n, k]$ be the stirling number of the first kind, then

$$\left[n \atop k \right] = \sum_{0 \leq i_1 < i_2 < \dots < i_k < n} i_1 i_2 \dots i_k.$$

9.3 Stirling Numbers Second Kind

Stirling number of the second kind is the number of ways to partition a set of n objects into k non-empty subsets.

$$S(n, k) = k \cdot S(n-1, k) + S(n-1, k-1), \text{ where } S(0, 0) =$$

$1, S(n, 0) = S(0, n) = 0 \quad S(n, 2) = 2^{n-1} - 1 \quad S(n, k) \cdot k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation.

$$S_r(n+1, k) = k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1)$$

Denote the n objects to partition by the integers $1, 2, \dots, n$. Define the reduced Stirling numbers of the second kind, denoted $S^d(n, k)$, to be the number of ways to partition the integers $1, 2, \dots, n$ into k nonempty subsets such that all elements in each subset have pairwise distance at least d . That is, for any integers i and j in a given subset, it is required that $|i - j| \geq d$. It has been shown that these numbers satisfy, $S^d(n, k) = S(n-d+1, k-d+1), n \geq k \geq d$

9.4 Other Combinatorial Identities

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1} \quad \sum_{i=0}^k \binom{n+i}{i} = \sum_{i=0}^k \binom{n+i}{n} = \binom{n+k+1}{k}$$

$$n, r \in \mathbb{N}, n > r, \sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$$

$$\text{If } P(n) = \sum_{k=0}^n \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot P(k)$$

$$\text{If } P(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot P(k)$$

9.5 Different Math Formulas

Picks Theorem : $A = i + b/2 - 1$

Derangements : $d(i) = (i-1) \times (d(i-1) + d(i-2))$

$$\frac{n}{ab} - \left\{ \frac{bn}{a} \right\} - \left\{ \frac{an}{b} \right\} + 1$$

9.6 GCD and LCM

if m is any integer, then $\gcd(a + m \cdot b, b) = \gcd(a, b)$

The gcd is a multiplicative function in the following sense: if a_1 and a_2 are relatively prime, then $\gcd(a_1 \cdot a_2, b) = \gcd(a_1, b) \cdot \gcd(a_2, b)$.

$$\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c)).$$

$$\text{lcm}(a, \gcd(b, c)) = \gcd(\text{lcm}(a, b), \text{lcm}(a, c)).$$

For non-negative integers a and b , where a and b are not both zero, $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

$$\gcd(a, b) = \sum_{k|a \text{ and } k|b} \phi(k)$$

$$\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$$

$$\sum_{k=1}^n \gcd(k, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n x^{\gcd(k, n)} = \sum_{d|n} x^d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2$$

$$F(n) = \sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{(1 + \lfloor \frac{n}{l} \rfloor) (\lfloor \frac{n}{l} \rfloor)}{2} \right)^2 \sum_{d|l} \mu(d) l d$$