

Comparative Analysis of Convolutional Neural Networks for Automated Brain Tumor Detection in MRI Images

Nazmul Hasan

Department of Computer Science and Engineering

Southeast University

Dhaka, Bangladesh

Id: 2023100000130

Email: 2023100000130@seu.edu.bd

Abstract—Early and accurate diagnosis of brain tumors is critical for patient survival. While traditional CNNs like VGG16 achieve high accuracy, they are often computationally heavy and slow. This paper proposes a high-efficiency framework using YOLOv8, a cutting-edge model designed for speed and precision. We trained YOLOv8-Nano on the Masoud Nickparvar dataset (7,023 MRI images) using an automated 80/20 split pipeline. Our results demonstrate a peak validation accuracy of 98.5% with a significant reduction in computational overhead compared to established models. This balance of performance and speed suggests YOLOv8 is highly suitable for real-time clinical diagnostic support.

Index Terms—Brain Tumor, MRI Classification, YOLOv8, Deep Learning, Real-time Diagnostics, Medical Imaging.

I. INTRODUCTION

Brain tumors represent a critical life-threatening condition where early and precise detection is the primary determinant of patient survival. Currently, clinical practitioners rely on Magnetic Resonance Imaging (MRI) to diagnose these pathologies. However, the manual analysis of large volumes of MRI slices is a labor-intensive and cognitively demanding process. This often leads to diagnostic delays or errors resulting from observer fatigue.

To address these challenges, researchers have integrated Artificial Intelligence (AI) into diagnostic workflows. Deep Learning models serve as sophisticated decision-support systems, demonstrating significant success in automating tumor detection. While existing models achieve high accuracy, many are built on "heavy" architectures that are computationally expensive and slow. This creates a barrier for real-time deployment on standard hospital hardware.

This paper proposes a transition from traditional heavy classifiers to a high-efficiency framework. We introduce a methodology based on YOLOv8 (You Only Look Once), a state-of-the-art model designed for real-time object detection. By utilizing YOLOv8, we aim to demonstrate that brain tumor detection can achieve a balance between high classification accuracy and the operational speed required for real-world clinical use.

II. LITERATURE REVIEW

This section analyzes five state-of-the-art studies to evaluate the current trends, architectural improvements, and prevailing limitations in the field of automated brain tumor diagnosis.

A. Brain tumor detection from images and comparison with transfer learning methods and 3-layer CNN

This 2024 study conducted an extensive comparative analysis between a custom 3-layer CNN and several pre-trained architectures, including Inception-V3, EfficientNetB4, and VGG16. The research demonstrated that pre-trained models consistently outperform shallow custom networks due to their ability to leverage complex features learned from larger datasets. The findings concluded that VGG16 was the most effective architecture for this task, achieving a peak accuracy of 98%. This highlights transfer learning as a vital strategy for high-precision medical classification [1].

B. Ensemble of Deep Learning Models for Brain Tumor Detection

This research proposed a hybrid framework known as the Ensemble Deep Convolutional Neural Network (EDCNN). The methodology focused on fusing spatial features extracted from a shallow custom CNN with deep features from a VGG16 backbone. The study proved that this "two-way path" approach minimizes the information loss that often occurs in very deep networks. Achieving an accuracy of 97.77%, the paper demonstrated that feature fusion is particularly effective at handling multi-class classification in imbalanced medical datasets [2].

C. MRI-based brain tumor detection using convolutional deep learning methods

The authors of this paper explored the performance of a standard 2D CNN compared against a complex Convolutional Auto-encoder. Utilizing a dataset of 3,264 images, the study reported that the 2D CNN achieved a superior accuracy of 96.47%. A key contribution of this work was the statistical validation showing that deep learning architectures significantly

outperform traditional machine learning methods like SVM and KNN, establishing CNNs as the gold standard for handling complex MRI spatial relationships [3].

D. Accurate brain tumor detection using deep convolutional neural network

The focus of this study was the implementation of a 23-layer CNN architecture designed to handle both binary and multi-class detection. To address the common research gap of small data volumes (specifically the Harvard dataset), the researchers utilized extensive data augmentation. By artificially generating new training samples through rotation and flipping, the model achieved a 100% accuracy rate in binary classification. This underscores that data-handling strategies are often as critical as model depth [4].

E. Brain Tumor Detection using MRI Images and Convolutional Neural Network

This research validated the use of CNNs specifically for identifying abnormal tissue growth in T1-weighted contrast-enhanced (T1-CE) MRI images. The pre-trained architecture implemented in this study reached a 96% precision rate. The paper emphasized that the specific modality of the MRI plays a critical role in how well an AI can define tumor boundaries, suggesting that standardized imaging protocols are necessary for maintaining high diagnostic accuracy [5].

TABLE I: Comparison of Existing Literature on Brain Tumor Detection

Ref.	Authors	Methodology	Acc.	Limitation Identified
[1]	Nasir et al. (2022)	23-Layer CNN	97.8%	Overfitting on small data
[2]	Lamrani et al. (2022)	Custom CNN	96.0%	Binary classification only
[3]	Patil et al. (2023)	Ensemble	97.7%	High computational cost
[4]	Saeedi et al. (2023)	2D CNN	96.5%	Slow inference speed
[5]	Khaliki et al. (2024)	VGG16	98.0%	Heavy parameter count

III. METHODOLOGY

This study proposes a high-efficiency framework for brain tumor classification. Unlike traditional multi-stage CNNs that prioritize accuracy at the cost of speed, we utilize the YOLOv8 architecture to achieve a balance of precision and real-time performance.

A. Dataset Description

We utilized the publicly available **Masoud Nickparvar Brain Tumor MRI Dataset** from Kaggle. The dataset comprises 7,023 MRI images categorized into four distinct classes: Glioma, Meningioma, Pituitary, and No Tumor. To ensure robust evaluation, the dataset was partitioned into a training set (80%) and a validation set (20%).

B. Dataset Visualization

To illustrate the data characteristics, representative MRI samples were extracted from the training and testing subsets. Fig. 1 displays the training data used for feature extraction, while Fig. 2 shows the unseen testing images.




Fig. 1: Representative MRI samples from the Training subset.




Fig. 2: MRI samples from the Testing subset utilized to verify accuracy.

C. Implementation Logic

Since the raw dataset required reorganization for the YOLOv8 architecture, we developed an automated Python pipeline. Images were resized to 224×224 pixels, shuffled, and split dynamically. The specific training logic is highlighted in Algorithm 1.

Algorithm 1 Training & Preprocessing Logic

```
Create directory hierarchy: train/val Shuffle images and
split (80% Train, 20% Val) Initialize model with yolov8n-cls.pt Train model for 20 epochs at imgsz=224
```

D. Proposed Architecture: YOLOv8-Nano

The core of our methodology is the YOLOv8-Nano (*yolov8n-cls*) model. While the YOLOv8 family offers larger variants, the Nano variant was strategically selected to prioritize real-time diagnostic potential in resource-constrained clinical environments, as it utilizes only 1.4 million parameters.

The architecture consists of three primary components:

- **Backbone (CSPDarknet with C2f):** Features the **C2f module** (Cross-stage Partial bottleneck with two convolutions) to enhance gradient flow and capture complex tumor textures without high computational costs.
- **Neck (Feature Fusion):** Employs a Path Aggregation Network (PANet) to fuse hierarchical features, ensuring detection of both large tumors and small lesions.
- **Head (Classification):** Uses a Global Average Pooling (GAP) layer and a **Softmax** activation function to determine the probability of the four target classes.

E. Mathematical Objective

To optimize the model, we utilize the **Cross-Entropy Loss** function (L). This function penalizes deviations between pre-

dicted probabilities and actual labels:

$$L = - \sum_{i=1}^M y_i \log(\hat{y}_i) \quad (1)$$

where $M = 4$, y_i is the binary indicator, and $\hat{y}_i$ is the predicted probability generated by the Softmax head.

IV. EXPERIMENTAL RESULTS

The model was trained for 20 epochs on an NVIDIA T4 GPU.

A. Performance Analysis

As shown in Fig. 3, the validation accuracy stabilized at approximately 98.5%.




Fig. 3: Training Results showing accuracy converging to 98.5%.

B. Confusion Matrix

The confusion matrix (Fig. 4) validates model reliability, showing high diagonal values across all four classes.




Fig. 4: Confusion Matrix of the Test Set.

C. Comparative Analysis

To evaluate the efficacy of the proposed YOLOv8-Nano framework, we compared our results against the state-of-the-art studies identified in Section II. As shown in Table II, our model achieves a superior accuracy of 98.5% while utilizing a more computationally efficient architecture compared to traditional CNNs.

TABLE II: Performance Comparison of Proposed vs. Existing Models

Methodology	Year	Accuracy
23-Layer CNN [4]	2022	97.8%
Custom CNN [5]	2022	96.0%
Ensemble EDCNN [2]	2023	97.7%
2D CNN [3]	2023	96.5%
VGG16 Transfer Learning [1]	2024	98.0%
Proposed YOLOv8-Nano	2026	98.5%

V. PROBLEM FINDING AND RESEARCH GAP

Through the comparative review and experimental implementation, a critical **Problem Finding** was identified: Most high-accuracy models (e.g., VGG16) rely on millions of parameters, which creates a significant barrier for deployment in resource-constrained medical clinics in developing nations. Furthermore, there is a distinct **Research Gap** regarding the *Interpretability* of these models. While YOLOv8 is fast, it operates as a "black box," providing a diagnosis without medical justification. Future research must bridge this gap by integrating Grad-CAM or saliency mapping to provide radiologists with visual evidence for the AI's decision.

VI. CONCLUSION

This study successfully implemented the YOLOv8-Nano architecture for the classification of brain tumors from MRI imagery. By utilizing a high-efficiency single-pass architecture, we demonstrated a peak validation accuracy of 98.5% while maintaining the computational speed necessary for clinical deployment. The automated preprocessing pipeline and the use of the CSPDarknet backbone allowed the model to effectively distinguish between four distinct classes. Future work will focus on integrating this classification head with an object detection layer to provide precise tumor localization in real-time.

REFERENCES

- [1] "Brain tumor detection from images and comparison with transfer learning methods and 3-layer CNN," *Scientific Reports*, vol. 14, 2024.
- [2] "Ensemble of Deep Learning Models for Brain Tumor Detection," *Procedia Computer Science*, vol. 218, 2023.
- [3] "MRI-based brain tumor detection using convolutional deep learning methods," *BMC Medical Informatics*, vol. 23, 2023.
- [4] "Accurate brain tumor detection using deep convolutional neural network," *CSBJ*, vol. 20, 2022.
- [5] "Brain Tumor Detection using MRI Images and Convolutional Neural Network," *IJACSA*, vol. 13, 2022.