Risk-Controlled Spatio-Temporal Graph Learning for Anti-Money Laundering Under Extreme Imbalance and Topological Camouflage

Anonymized for Double-Blind Review

Department and Institution Withheld for Double-Blind Peer Review,

ARTICLE INFO

Keywords:
Anti-money laundering
Applied artificial intelligence
Spatio-temporal graph learning
Class imbalance
Conformal prediction
Financial surveillance

ABSTRACT

In enterprise financial surveillance, detecting money laundering across payment rails requires processing streaming transactions under statutory auditability and sub-millisecond service-level agreements. Existing systems suffer from velocity evasion, topological camouflage, extreme class imbalance ($\pi < 0.05\%$), cold-start sparsity, and uncalibrated uncertainty yielding up to 95% false positives. To address these challenges, this paper develops C-STGB (Conformal Spatio-Temporal GraphBoost), an applied neuro-symbolic system integrating: (1) a continuous-time harmonic temporal graph neural network with Hawkes intensity and learnable edge-trust gating; (2) a typology-clustered latent GraphSMOTE preserving 12-dimensional mass-flow conservation invariants; and (3) class-conditional conformal prediction with streaming Adaptive Conformal Inference guaranteeing distribution-free coverage ($1-\alpha \geq 99\%$) under non-stationary drift. Evaluated across 14 financial transaction networks spanning 9,534,980 entities and transactions, C-STGB achieves an unweighted macro-average minority F1-score of 68.05% (0.6974 PR-AUC), outperforming deep graph networks (+44.27 percentage points over GCN, Wilcoxon $W^+ = 105.0, W^- = 0.0, p_{\text{adj}} < 0.001$) and competitive gradient boosting (+3.29 percentage points over XGBoost, $W^+ = 99.5, W^- = 5.5, p_{\text{adj}} = 0.0032$). For core-banking operations, C-STGB routes 99.32% of streaming transactions into an automated straight-through processing tier with selective risk (illicit leakage) strictly below 0.22% (macro-average 0.13%), while restricting human review queues to 0.50% of borderline transactions (with decisive singletons totaling 99.50%). The streaming inference engine achieves a single-event Fast-Path latency of 0.45 milliseconds (P99: 0.82 ms, 31,200 tx/s multi-partition throughput), satisfying real-time authorization SLAs.

1. Introduction

Financial crime surveillance represents a vital, high-stakes application of intelligent expert systems within global financial infrastructure. According to the United Nations Office on Drugs and Crime (United Nations Office on Drugs and Crime, 2011), illicit syndicates launder between $800 billion and $2 trillion annually (representing 2% to 5% of global Gross Domestic Product) across inter-bank wire rails, mobile financial service (MFS) e-wallets, and distributed crypto-asset ledgers. Operational Financial Intelligence Units (FIUs) within commercial banking institutions traditionally rely on rule-based alert systems. However, these legacy architectures generate excessive false positive alert rates exceeding 90% to 95% (ACAMS and PwC, 2020; Financial Crimes Enforcement Network, 2019), imposing severe investigative backlogs and substantial operational expenses on compliance examiners.

To modernize financial surveillance, recent research has explored Graph Neural Networks (GNNs) to model the relational topologies of transaction graphs (Kipf and Welling, 2017; Hamilton et al., 2017; Weber et al., 2019; Hu et al., 2020). Nevertheless, deploying automated graph intelligence in mission-critical Anti-Money Laundering (AML) production pipelines reveals five severe operational challenges:

1. **Continuous-Time Velocity Evasion:** Laundering networks alternate between sub-second structuring bursts and multi-week dormant holding intervals, dynamics that cannot be captured simultaneously by discrete snapshot windowing (Pareja et al., 2020) or single-rate exponential decay kernels.
2. **Adversarial Topological Camouflage:** Illicit entities deliberately route high-degree synthetic transaction chaff to legitimate commercial hubs (e.g., merchant gateways and centralized exchanges), inducing severe feature over-smoothing during neighborhood message aggregation (Dou et al., 2020).
3. **Extreme Class Imbalance:** Operational financial streams exhibit severe minority class skew ($\pi < 0.05\%$ on inter-bank wire rails and retail payment networks, compared to 2.23% total and 9.76% labeled evaluation prevalence on `elliptic_v1`), inducing severe posterior score attenuation that triggers near-complete recall collapse under default decision cutoffs ($\tau = 0.50$).
4. **Cold-Start Graph Isolation ($d(u) \leq 2$):** Newly activated accounts possess sparse connectivity, receiving uninformative or noisy neighborhood aggregation vectors under pure spatial message passing.
5. **Uncalibrated Decision Uncertainty:** Black-box anomaly scores lack distribution-free statistical risk guarantees under non-stationary temporal distribution drift, exposing financial institutions to regulatory non-compliance under statutory model risk management audits (e.g., Federal Reserve SR 26-2 / OCC Bulletin 2011-12 supervisory guidance (Board of Governors of the Federal Reserve System, 2026; Office of the Comptroller of the Currency, 2011)).

ORCID(s):

To overcome these foundational hurdles, this study investigates the operational boundaries and synergy between graph learning and tree ensembles under production surveillance constraints.

A critical empirical finding of this work is that graph neural networks do not uniformly surpass optimized gradient-boosted decision trees across all financial transaction streams. Rather, their performance advantage is heavily concentrated in graph-rich, multi-hop relational laundering environments, whereas tree ensembles remain highly competitive or superior on predominantly flat, single-hop transactional ledgers.

Grounded in this operational reality, we propose **C-STGB** (Conformal Spatio-Temporal GraphBoost), an end-to-end intelligent surveillance and decision-support system. The principal scientific and systems contributions of this paper are organized around three foundational theoretical pillars and an enterprise-scale empirical validation:

1. **Theoretical Pillar 1 (Continuous-Time Spatiotemporal Graph Dynamics with Tri-Band Harmonic Attention & Hawkes Intensity):** We develop a camouflage-resilient spatio-temporal graph neural architecture combining multi-scale harmonic temporal projections (Φ_{time}) across burst, diurnal, and seasonal bands with Hawkes point-process arrival velocity descriptors ($\lambda_u(t)$) and a context-aware edge-trust gate ($\hat{g}_{ij}$) that suppresses synthetic camouflage chaff (65.9% pruning) and prevents feature over-smoothing around high-degree banking hubs.
2. **Theoretical Pillar 2 (Typology-Clustered Latent GraphSMOTE with Bilinear Edge Reconstruction):** We formulate a topology-preserving oversampling mechanism that clusters minority illicit embeddings into latent typological regimes (C_k) and synthesizes synthetic node representations paired with bilinear edge link prediction. We formally prove that synthetic node interpolation preserves point-level flow-conservation invariants ($\mathbf{z}_{\text{inv}}$) while overcoming extreme posterior score attenuation ($\pi < 0.05\%$).
3. **Theoretical Pillar 3 (Finite-Sample Class-Conditional Conformal Risk Control with ACI Drift Tracking):** We establish distribution-free Class-Conditional Conformal Risk Control for streaming financial ledgers, guaranteeing finite-sample coverage ($\geq 99.0\%$) simultaneously across both classes under exchangeability, non-asymptotic drift bounds under total variation shifts, and online Martingale tracking via Adaptive Conformal Inference (ACI) to handle delayed ground-truth feedback.
4. **Comprehensive Empirical Demarcation & Production Systems Profiling:** Across 14 financial transaction networks comprising 9.53M entities, 9.53M transactions, and 182 evaluation pairs over five locked random seeds, we demonstrate statistically significant superiority over deep GNNs (+44.27 pp mean uplift over GCN, $p_{\text{adj}} < 0.001$), define rigorous empirical boundaries where tabular learners remain competitive, and validate a streaming Fast-Path inference pipeline operating at 0.45 ms latency per transaction event.

Paper Organization: The remainder of this paper is structured as follows: Section 2 reviews related literature; Section 3 formalizes the threat model and the C-STGB expert system architecture; Section 4 presents the empirical evaluation across 14 benchmark networks; Section 5 analyzes operational implications and domain boundaries; Section 6 details qualitative forensic attributions and compliance decision-support case studies; Section 7 discusses limitations and ethical considerations; and Section 8 concludes the paper with future research directions.

2. Related Work

2.1. Graph Representation Learning for Anti-Money Laundering & Financial Fraud

The application of Graph Neural Networks (GNNs) to financial forensic analysis was pioneered by Weber et al. (2019) on the Elliptic Bitcoin benchmark, demonstrating that spatial architectures such as Graph Convolutional Networks (GCN) (Kipf and Welling, 2017) and GraphSAGE (Hamilton et al., 2017) capture localized topological connectivity patterns beyond isolated tabular classifiers. Subsequent research by Bellei et al. (2024) introduced the Elliptic2 multi-asset benchmark, highlighting higher-order relational subgraphs. In banking networks, Cheng et al. (2023) introduced group-aware deep graph learning to capture collective community-level transaction behavior, while Fu et al. (2025) developed H^2IDE to untangle fraudulent camouflage on multi-relational graphs via disentangled homophily and heterophily identification. More broadly, Qiao et al. (2025) surveyed modern deep graph anomaly detection paradigms, highlighting the persistent challenges of structural camouflage, degree skew, and non-uniform relation topologies.

Graph representations have also been deployed for Ethereum blockchain forensics (Zheng et al., 2020), multi-bank synthetic wire simulations (Suzumura et al., 2019; Lorenz et al., 2020), streaming credit card fraud detection (Dal Pozzolo et al., 2018), and cross-institutional federated learning architectures (Wang et al., 2023). However, prior AML graph frameworks largely operate over static topological snapshots. Consequently, they remain insensitive to continuous multi-scale temporal velocity patterns and vulnerable to severe feature over-smoothing when money launderers attach synthetic chaff edges to high-degree commercial hubs (Dou et al., 2020).

2.2. Continuous-Time Dynamic Temporal Graphs

Financial transaction networks evolve through asynchronous, continuous-time transaction events. Discrete snapshot dynamic GNNs, such as EvolveGCN (Pareja et al., 2020), discretize event streams into regular time slices, discarding intra-slice temporal ordering and obscuring sub-second velocity bursts. While continuous frameworks including Temporal Graph Networks (TGN) (Rossi et al., 2020), TGAT (Xu et al., 2020), and continuous anomaly

detectors (Wang et al., 2024) preserve exact event order, standard single exponential decay kernels ($\exp(-\lambda\Delta t)$) rapidly attenuate to zero over multi-week dormant holding periods. In operational financial crime surveillance, single-decay dynamic GNNs struggle to simultaneously model sub-second structuring bursts alongside multi-week holding intervals characteristic of layering chains. Furthermore, recent advances in edge-feature GNNs and expressive dynamic message passing (Egressy et al., 2024) demonstrate the necessity of modeling continuous edge transaction attributes for robust temporal surveillance.

2.3. Adversarial Graph Learning & Topological Camouflage Defense

Adversarial attacks on graph neural networks manipulate connectivity or node attributes to induce misclassification (Zügner et al., 2018). In financial forensics, adversaries employ topological camouflage: laundering entities deliberately attach transactional chaff edges to high-degree, reputable commercial hubs (e.g., payment gateways, exchanges, utility merchants) to blend into background traffic (Dou et al., 2020). Because standard graph convolutional aggregation treats incident edges with uniform or degree-normalized weights, camouflage connections drag illicit node embeddings toward majority benign centroids.

To counter camouflage, CARE-GNN (Dou et al., 2020) introduced reinforcement learning to select informative neighbors on multi-relational graphs, while Ou et al. (2026) developed CamFD to detect temporal behavioral inconsistencies of camouflaged fraudsters on dynamic graphs. However, existing camouflage defenses either rely on static relation heuristics or assume homophilic interactions, lacking continuous-time soft-gating that dynamically prunes high-degree banking chaff while providing provable finite-sample risk coverage.

2.4. Imbalanced Graph Representation Learning & Latent Oversampling

Real-world financial transaction graphs exhibit extreme class imbalance, often with illicit prevalence $\pi < 0.05\%$. Traditional Euclidean oversampling techniques such as SMOTE (Chawla et al., 2002) operate strictly on tabular feature vectors, generating synthetic instances without topologically valid relational edges. To bridge topological oversampling, Zhao et al. (2021) proposed GraphSMOTE, performing feature interpolation in the intermediate latent embedding space and decoding synthetic edges via an auxiliary link generator. However, standard GraphSMOTE executes unconstrained latent interpolation across the global minority class pool, neglecting distinct structural laundering typologies (cyclic wash trading vs. smurfing fan-out vs. pass-through layering), risking synthetic instances that violate domain-level flow-balance regularity.

2.5. Conformal Risk Control, Selective Classification & Temporal Drift

Conformal prediction, formalized by Vovk et al. (2005) and extended by Bates et al. (2021) and Angelopoulos and Bates (2023), provides distribution-free, finite-sample uncertainty quantification. Recent research has investigated conformal prediction on GNNs (Huang et al., 2024) and class-conditional conformal prediction under class imbalance (Ding et al., 2023). While standard marginal conformal prediction guarantees valid overall coverage ($1-\alpha$), it frequently suffers from severe conditional under-coverage on the rare class in highly imbalanced datasets, motivating class-conditional split conformal methods (Sadinle et al., 2019). Under temporal non-stationarity, standard exchangeability is violated and coverage must be explicitly bounded through distribution drift tracking, such as Adaptive Conformal Inference (ACI) (Gibbs and Candès, 2021). Unlike heuristic uncertainty frameworks, C-STGB leverages distribution-free Conformal Risk Control to deliver rigorous finite-sample class-conditional coverage bounds ($\geq 1-\alpha$), backed by Martingale convergence under ACI tracking, while delineating the boundary where GNN message passing is indispensable vs. where tabular trees remain competitive.

3. Problem Formulation & C-STGB Methodology

3.1. Operational Architecture Profiles: C-STGB-Fast vs. C-STGB-Full

To satisfy diverse deployment constraints across financial infrastructures, C-STGB is instantiated into two operational configurations:

1. **C-STGB-Fast (Real-Time Authorization Path):** Tailored for high-throughput transactional authorization (31,200 tx/s multi-partition throughput, single-event latency of 0.45 ms, P99: 0.82 ms). It executes cached 1-hop subgraph retrieval, quantized tri-band temporal projections, and evaluates the streaming fast path without offline multi-hop GraphSMOTE expansion (90.85% F1 on `elliptic_v1`).
2. **C-STGB-Full (Forensic Investigation Path):** Tailored for deep forensic investigation and batch reconciliation (2.10 ms latency, achieving maximum accuracy of 91.42% F1 on `elliptic_v1`). It executes comprehensive 2-hop causal subgraph retrieval, multi-scale continuous Hawkes dynamics, and full latent GraphSMOTE oversampling.

Unless explicitly designated as C-STGB-Fast, benchmark scorecards (Table 2) evaluate C-STGB-Full, while operational triage funnels (Figure 1) and production latency profiles document C-STGB-Fast.

3.2. Problem Formulation and Adversarial Threat Model

We formalize financial crime surveillance over a continuous-time dynamic transaction graph $\mathcal{G}_t = (\mathcal{V}_t, \mathcal{E}_t, \mathbf{X}_v^{(t)}, \mathbf{X}_e^{(t)})$, where $\mathcal{V}_t$ represents active transacting accounts, $\mathcal{E}_t = \{(u, v, t_e, \mathbf{e}_{uv}) : t_e \leq t\}$ denotes directed fund transfers occurring at or before timestamp t, $\mathbf{X}_v^{(t)} \in \mathbb{R}^{|\mathcal{V}_t| \times d_v}$ comprises




Figure 1: End-to-end operational architecture and real-time triage workflow of the C-STGB financial surveillance platform: (1) Zero-copy streaming ingestion via Apache Arrow and DuckDB with 12-D physical mass-flow invariants; (2) C-STGB neural core combining continuous-time 3-band harmonic temporal attention, learnable edge-trust gating ($\hat{g}_{ij} \geq \delta_{\text{floor}}$), typology-clustered latent GraphSMOTE, evidence-adaptive fusion (α_u), and cost-sensitive Bayes risk calibration ($\tau^* = 0.18$); and (3) Class-conditional Conformal Risk Control (CRC) decision diamond ($1-\alpha \geq 99\%$) routing streaming transactions across 3 operational tiers (Tier 1 High-Risk Quarantine with SHA-256 Merkle audit receipts, Tier 2 Compliance Review Desk, Tier 3 Automated Straight-Through Clearing) under a 0.45 ms Fast-Path authorization SLA.

entity features, and $\mathbf{X}_e^{(t)} \in \mathbb{R}^{|\mathcal{E}_t| \times d_e}$ denotes edge features (transfer amount, currency rail, transaction fees). Each entity $u \in \mathcal{V}_t$ carries ground-truth label $y_u \in \{0, 1\}$, where $y_u = 1$ denotes confirmed illicit activity and $y_u = 0$ denotes benign transactions, under extreme class skew $\pi = \mathbb{P}(y_u = 1) \ll 0.01$. In transaction streams lacking explicit account graphs (e.g., PaySim), transactions are mapped to event vertices, establishing an exact 1:1 formulation.

Adversarial Threat Model: Adversarial syndicates evade forensic detection through two coordinated strategies:

1. *Velocity Obfuscation:* Interweaving sub-minute structuring bursts with multi-week dormant holding periods to evade static temporal windows;
2. *Structural Camouflage:* Actively attaching transactional chaff to high-degree, reputable commercial hubs (e.g., payment gateways, exchanges) to dilute illicit representations during spatial message aggregation.

Operational Objectives: The surveillance expert system optimizes two complementary operational objectives:

1. **Cost-Sensitive Classification:** Learn an inductive hypothesis $f_\Theta : \mathcal{V}_t \times \mathcal{G}_t \to [0, 1]$ predicting anomaly posterior $\hat{p}_u = f_\Theta(u \mid \mathcal{G}_t)$ that minimizes asymmetric regulatory Bayes risk.
2. **Risk-Controlled Queue Triage:** Construct a class-conditional conformal mapping $\Gamma : \mathcal{V}_t \to 2^{\{0,1\}}$ routing transactions to operational action sets $\Gamma(u) \subseteq \{0, 1\}$. Under within-class exchangeability, Γ provides finite-sample coverage $\mathbb{P}(y_u \in \Gamma(u) \mid y_u = y) \geq 1-\alpha_y$ at specified significance $\alpha_y \in (0, 1)$, with provable bounds under temporal distribution shift. Decisive singletons are routed to automated workflows ($\Gamma(u) = \{1\}$ to Tier 1 Escalation; $\Gamma(u) = \{0\}$ to Tier 3 Straight-Through Clearance), restricting human officer investigation to ambiguous sets ($\Gamma(u) = \{0, 1\}$ in Tier 2).

3.3. 12-Dimensional Canonical Mass-Flow and Velocity Invariants

Design Rationale: Standard GNNs evaluate node features without domain mass-conservation constraints. In money laundering, intermediate pass-through mules require capital to enter and exit rapidly with near-zero retention. C-STGB formalizes 12-dimensional domain-informed mass-flow and relational invariants $\mathbf{z}_{\text{inv}}(u, t) \in \mathbb{R}^{12}$:

1. **Flow Regularity and Degree Asymmetry Ratios:**

$$\Phi_{\text{flow}}(u, t) = \frac{\sum_{e \in \mathcal{E}_{\text{out}}(u)} \text{Amount}(e)}{\sum_{e \in \mathcal{E}_{\text{in}}(u)} \text{Amount}(e) + \epsilon}, \tag{1}$$

$$\Psi_{\text{asym}}(u, t) = \frac{|d_{\text{in}}(u) - d_{\text{out}}(u)|}{d_{\text{in}}(u) + d_{\text{out}}(u) + \epsilon} \tag{2}$$

with $\epsilon = 10^{-5}$. Intermediate mules operate near unity ($\Phi_{\text{flow}} \approx 1.0$), whereas legitimate commercial accounts exhibit accumulation or disbursement variance. For numerical stability, flow is scaled as $\tilde{\Phi}_{\text{flow}}(u, t) = \log(1 + \Phi_{\text{flow}}(u, t))$.

2. **Hawkes Point Process Arrival Intensity:**

$$\lambda_u(t) = \mu_u + \sum_{t_i < t} \alpha_H \exp\left(-\beta_H (t - t_i)\right) \tag{3}$$

parameterized over causal backward event history $[t - \Delta T_{\text{hist}}, t]$ ($\Delta T_{\text{hist}} = 72$ hours, with baseline intensity

$\mu_0 = 0.01\,\mathrm{h}^{-1}$, excitation $\alpha_H = 0.45$, and decay $\beta_H = 0.90\,\mathrm{h}^{-1}$, where $\alpha_H/\beta_H = 0.50 < 1.0$ guarantees sub-critical stability and asymptotic stationarity) to model transaction burst acceleration, with baseline intensity $\mu_u \geq 0$, excitation parameter $\alpha_H > 0$, and decay parameter $\beta_H > 0$. We enforce sub-critical branching $\alpha_H/\beta_H < 1.0$ and clamp $\tilde{\lambda}_u(t) = \log\min(\max(\lambda_u(t), 10^{-5}), 10^4)$.

3. **Causal Historical Taint Propagation (Zero-Leakage):**

$$\mathbf{s}_{\mathrm{fwd}} = (1-\alpha_{\mathrm{ppr}})(\mathbf{I} - \alpha_{\mathrm{ppr}}\mathbf{P}^T)^{-1}\mathbf{s}_{\mathrm{seed}}, \tag{4}$$

$$\mathbf{s}_{\mathrm{bwd}} = (1-\alpha_{\mathrm{ppr}})(\mathbf{I} - \alpha_{\mathrm{ppr}}\mathbf{P})^{-1}\mathbf{s}_{\mathrm{seed}} \tag{5}$$

computed exclusively over causal historical subgraphs ($t_e \leq t$). To preclude label self-leakage during training, we enforce leave-one-out seed masking: when computing taint features for target node u, we set $\mathbf{s}_{\mathrm{seed}}(u) = 0$, ensuring taint propagates strictly from external confirmed historical seeds ($\mathbf{s}_{\mathrm{seed}}(v,t) = 1.0$ strictly if $v \in \mathcal{V}^{\mathrm{train}}_{\mathrm{illicit}} \setminus \{u\}$ and confirmation timestamp $t_{\mathrm{conf}}(u) \leq t - \Delta T_{\mathrm{delay}}$, and 0.0 otherwise, where $\Delta T_{\mathrm{delay}} \in [30, 90]$ days models investigative delay. Truncated Power Iteration ($\alpha_{\mathrm{ppr}} = 0.15$, fixed $T_{\mathrm{iter}} = 3$ iterations) over degree-capped graph $\mathcal{G}_t^{(K)}$ ($K \leq 15$) ensures deterministic $O(K \cdot T_{\mathrm{iter}})$ computation with < 0.08 ms overhead. All validation, calibration, and test nodes receive $\mathbf{s}_{\mathrm{seed}}(u) \equiv 0.0$, strictly precluding label leakage.

4. **Complete 12-D Descriptor Vector:**

$$\mathbf{z}_{\mathrm{inv}}(u,t) = \big[\tilde{\Phi}_{\mathrm{flow}}, \Psi_{\mathrm{asym}}, \lambda_u, \mathbf{s}_{\mathrm{fwd}}, \mathbf{s}_{\mathrm{bwd}}, \mu_A, \sigma_A^2, \gamma_A, \kappa_A, \upsilon_A, \nu_{\mathrm{io}}, \sigma_{\Delta t}\big]^T \tag{6}$$

where $\{\mu_A, \sigma_A^2, \gamma_A, \kappa_A, \upsilon_A\}$ denote the 5-moment causal ego-statistics of transaction amounts, ν_{io} is the input/output velocity ratio, and $\sigma_{\Delta t}$ is the inter-arrival temporal dispersion.

3.4. Continuous-Time Tri-Band Harmonic Temporal Attention

Design Rationale: Standard temporal GNNs use single exponential decay kernels ($\exp(-\lambda\Delta t)$), which extinguish rapidly over multi-week holding chains or blur sub-minute structuring bursts. C-STGB projects continuous time deltas $\Delta t = t_v - t_u \geq 0$ into a harmonic positional space $\Phi_{\mathrm{time}}(\Delta t) \in \mathbb{R}^{d_t}$ with $\omega_k = 10000^{-2k/d_t}$:

$$\Phi_{2k}(\Delta t) = \sin\left(\omega_k \log(1+\Delta t)\right), \tag{7}$$

$$\Phi_{2k+1}(\Delta t) = \cos\left(\omega_k \log(1+\Delta t)\right) \tag{8}$$

Dynamic temporal attention weights synthesize three distinct velocity bands:

$$\kappa_{\mathrm{temp}}(\Delta t) = \sum_{b\in\mathcal{B}} \beta_b \left[w_{\min} + (1-w_{\min})e^{-\lambda_b \Delta t}\right] \times \left(1 + \tanh(\gamma_b \lambda_u(t))\right) \tag{9}$$

where $\mathcal{B} = \{\mathrm{burst}, \mathrm{diurnal}, \mathrm{seasonal}\}$ with learnable mixture weights $\sum_{b\in\mathcal{B}} \beta_b = 1.0$ via softmax. All time intervals Δt are evaluated in hours. The burst band ($\lambda_{\mathrm{burst}} = 0.80\,\mathrm{h}^{-1}$, half-life $t_{1/2} \approx 52$ min) captures sub-hour rapid smurfing bursts; the diurnal band ($\lambda_{\mathrm{diurnal}} = 0.04\,\mathrm{h}^{-1}$, $t_{1/2} \approx 17.3$ h) captures harmonic 24-hour operational business cycles; and the seasonal band ($\lambda_{\mathrm{seasonal}} = 0.0015\,\mathrm{h}^{-1}$, $t_{1/2} \approx 19.25$ days $= 462$ hours) retains exponential memory that decays toward calibrated baseline floor $w_{\min} = 0.05$ across 90- to 180-day dormant holding horizons.

3.5. Context-Aware Adaptive Edge Trust Filter & Unified Attention

Design Rationale: Adversarial launderers deliberately inject high-volume transactional chaff connecting to reputable commercial hubs. Because standard isotropic convolutions average neighbor representations, these camouflage edges drag illicit embeddings toward benign centroids. C-STGB computes a context-aware unfloored edge-trust gate $g_{ij} \in [0,1]$:

$$\mathbf{c}_{ij} = [\mathbf{q}_i \,\|\, \mathbf{k}_j \,\|\, \mathbf{e}_{ij} \,\|\, \Phi_{\mathrm{time}}(\Delta t) \,\|\, \mathbf{z}_{\mathrm{inv}}(j,t)], \tag{10}$$

$$g_{ij} = \sigma\big(\mathbf{W}_{g2}\,\mathrm{LeakyReLU}(\mathbf{W}_{g1}\mathbf{c}_{ij} + \mathbf{b}_{g1}) + b_{g2}\big), \tag{11}$$

$$\hat{g}_{ij} = \delta_{\mathrm{floor}} + (1-\delta_{\mathrm{floor}})g_{ij} \in [\delta_{\mathrm{floor}}, 1.0] \tag{12}$$

Edges with unfloored trust $g_{ij} < \tau_{\mathrm{gate}}$ (with threshold $\tau_{\mathrm{gate}} = 0.10$) are hard-pruned from the computational ego-graph, removing 65.9% of synthetic camouflage chaff edges while retaining 92.1% of legitimate transaction connections. For surviving edges ($g_{ij} \geq \tau_{\mathrm{gate}}$), soft message-passing weight $\hat{g}_{ij}$ enforces a safety floor $\delta_{\mathrm{floor}} = 0.10$ to prevent vanishing gradients. During training on split $\mathcal{E}_{\mathrm{train}}$, auxiliary supervision $\mathbf{g}_{ij}^{\mathrm{target}} \in \{0,1\}$ evaluates raw unfloored gate g_{ij} (Eq. 23) using hub-degree heuristics ($\deg_{\mathrm{out}}(j) \geq 50$ or rate > 100 tx/day receives 0.0, standard edges receive 1.0). At inference time, the trained MLP evaluates unseen edges strictly via multi-modal representations $\mathbf{c}_{ij}$ without external targets or static degree cutoffs.

Unified Spatio-Temporal Attention: Message passing integrates structural compatibility, temporal decay, and edge-trust gating over degree-capped causal incoming neighborhoods ($\mathcal{N}_K^{\mathrm{in}}(u), K \leq 15$):

$$\tilde{\alpha}_{uv}^{(t)} = \frac{\Omega(u,v,t)}{\sum_{w\in\mathcal{N}_K^{\mathrm{in}}(u)} \Omega(u,w,t)}, \tag{13}$$

$$\Omega(u,v,t) = \exp\left(\frac{\mathbf{q}_u^T(\mathbf{k}_v + \mathbf{W}_E\mathbf{e}_{uv})}{\sqrt{d_k}}\right) \cdot \kappa_{\mathrm{temp}}(\Delta t_{uv}) \cdot \hat{g}_{uv} \tag{14}$$

3.6. Typology-Clustered Latent GraphSMOTE & Flow Regularity

Design Rationale: Real-world financial crime encompasses distinct operational archetypes (smurfing dispersal,

pooling fan-in, wash-trading loops, and pass-through layering). Naive Euclidean oversampling across the global minority class synthesizes hybrid instances that violate domain flow-balance regularity. C-STGB partitions minority illicit nodes strictly within the training split into latent typology clusters:

$$\mathcal{C}_k = \{v \in \mathcal{V}_{\text{illicit}}^{\text{train}} \mid \cos(\mathbf{h}_v, \boldsymbol{\mu}_k) \geq \tau_{\text{sim}}\} \tag{15}$$

where centroids $\boldsymbol{\mu}_k$ ($K = 4$) are optimized via latent silhouette validation on $\mathcal{D}_{\text{train}}$, and $\tau_{\text{sim}} = 0.75$ enforces tight cluster membership. Synthetic representations are interpolated strictly along trajectories within the same cluster: $\mathbf{h}_{\text{syn}} = (1 - \rho_{\text{interp}})\mathbf{h}_u + \rho_{\text{interp}}\mathbf{h}_v$, with $\rho_{\text{interp}} \sim \mathcal{U}(0, 1)$ and $u, v \in \mathcal{C}_k \subseteq \mathcal{V}_{\text{train}}$. Bilinear links to candidate training nodes $w \in \mathcal{V}_{\text{train}}$ are generated under topological edge reconstruction supervision:

$$\hat{\mathbf{A}}_{\text{syn},w} = \mathbb{I}\left(\sigma\left(\mathbf{h}_{\text{syn}}^T \mathbf{W}_{\text{edge}} \mathbf{h}_w\right) > \tau_{\text{edge}}\right) \cdot \mathbb{I}(t_w \leq t_{\text{syn}}) \tag{16}$$

where $t_{\text{syn}} = \max(t_u, t_v)$ defines the causal birth timestamp, strictly precluding acausal edge formation with future transactions. To guarantee sub-linear computational scalability over million-node transaction graphs, candidate nodes for bilinear edge generation ($\hat{\mathbf{A}}_{\text{syn},w}$) are constrained to the parent 2-hop neighborhood $\mathcal{N}_2(u) \cup \mathcal{N}_2(v)$ plus the top $K_{\text{cand}} = 50$ nearest neighbors indexed via Hierarchical Navigable Small World (HNSW) search ($M = 16, ef_{\text{search}} = 100, \mathcal{O}(\log|\mathcal{V}_{\text{train}}|)$ complexity), precluding quadratic memory and compute bottlenecks.

Preservation of Flow Conservation Regularity: Incoming links connect from candidate sources $w \in \mathcal{N}_{\text{in}}(u) \cup \mathcal{N}_{\text{in}}(v)$ and outgoing links connect to candidate destinations $w' \in \mathcal{N}_{\text{out}}(u) \cup \mathcal{N}_{\text{out}}(v)$. Synthetic amounts are parameterized linearly: $A_{\text{syn}} = (1 - \rho_{\text{interp}})A_u + \rho_{\text{interp}}A_v$ and $B_{\text{syn}} = (1 - \rho_{\text{interp}})B_u + \rho_{\text{interp}}B_v$. Under strictly positive inflows ($A_u, A_v > 0$) and outflows ($B_u, B_v > 0$), the synthetic flow regularity ratio evaluates to a convex combination of parent flow ratios:

$$\Phi_{\text{flow}}(\mathbf{h}_{\text{syn}}) = \lambda\Phi_{\text{flow}}(u) + (1 - \lambda)\Phi_{\text{flow}}(v), \tag{17}$$
$$\text{where } \lambda = \frac{(1 - \rho_{\text{interp}})A_u}{(1 - \rho_{\text{interp}})A_u + \rho_{\text{interp}}A_v} \in (0, 1).$$

Because $\lambda \in (0, 1)$, $\Phi_{\text{flow}}(\mathbf{h}_{\text{syn}})$ lies strictly within parent bounds $[\min(\Phi_u, \Phi_v), \max(\Phi_u, \Phi_v)]$, preserving domain mass-balance regularity without artificial distortion.

3.7. Evidence-Adaptive Graph-Tabular Fusion for Cold-Starts

Design Rationale: In production payment rails, 38.4% of newly activated money mules possess sparse connectivity ($\deg(u) \leq 2$). Pure spatial message passing starves on isolated stubs (18.4% F1). C-STGB resolves this via an evidence-adaptive gating parameter $\alpha_u \in [0, 1]$ acting as a continuous topological confidence estimator:

$$\mathbf{h}_u^* = \alpha_u \mathbf{h}_u^{(L)} + (1 - \alpha_u)\left(\mathbf{W}_{\text{proj}}\left[\mathbf{z}_{\text{inv}}(u, t) \,\|\, \mathbf{x}_u\right] + \mathbf{b}_{\text{proj}}\right), \tag{18}$$

$$\alpha_u = \sigma\left(\mathbf{w}_\alpha^T\left[\mathbf{h}_u^{(L)} \,\|\, \mathbf{z}_{\text{inv}}(u, t) \,\|\, \mathbf{x}_u\right] + b_\alpha\right) \tag{19}$$

where $\mathbf{W}_{\text{proj}} \in \mathbb{R}^{d \times (12 + d_v)}$ linearly aligns the concatenated domain tabular invariants with the GNN embedding space. When neighborhood evidence is sparse ($\deg(u) \leq 1$), $\alpha_u \to 0$ (empirically $\alpha_u \in [0.08, 0.12]$), gracefully transferring predictive mass to the 12-D canonical invariants $\mathbf{z}_{\text{inv}}(u, t)$ and achieving 89.60% F1 on cold-start stubs. Conversely, when local topology is dense, $\alpha_u \to 1.0$, harnessing high-order multi-hop structural representations.

3.8. Cost-Sensitive Optimization & Bayes Risk Minimization

Anomaly posterior probabilities evaluate as $\hat{p}_u = \sigma(\text{MLP}(\mathbf{h}_u^*))$. The multi-objective loss function is formulated as:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{task}}(y, \hat{p}) + \lambda_{\text{recon}}\mathcal{L}_{\text{recon}}(\mathbf{A}_{\text{train}}, \hat{\mathbf{A}}_{\text{train}}) + \lambda_{\text{aux}}\mathcal{L}_{\text{aux}} \tag{20}$$

where $\mathcal{L}_{\text{task}}$ is the Asymmetric Focal Tversky Loss prioritizing minority recall:

$$\mathcal{L}_{\text{task}}(y, \hat{p}) = \left(1 - \frac{\text{TP} + \epsilon}{\text{TP} + \alpha_{\text{tversky}}\text{FN} + \beta_{\text{tversky}}\text{FP} + \epsilon}\right)^{\gamma_{\text{focal}}}, \tag{21}$$
$$\text{where TP} = \sum_i y_i\hat{p}_i, \quad \text{FN} = \sum_i y_i(1 - \hat{p}_i),$$
$$\text{FP} = \sum_i (1 - y_i)\hat{p}_i,$$

parameterized by $\alpha_{\text{tversky}} = 0.70, \beta_{\text{tversky}} = 0.30, \gamma_{\text{focal}} = 1.5$, heavily penalizing false negatives. Bilinear edge reconstruction loss $\mathcal{L}_{\text{recon}}$ evaluates positive training edges $\mathcal{E}_{\text{train}}$ against a $1:5$ time-conditioned negative non-edge sample $\mathcal{E}_{\text{neg}}$:

$$\mathcal{L}_{\text{recon}} = -\frac{1}{|\mathcal{E}_{\text{train}}|}\sum_{(u,v)\in\mathcal{E}_{\text{train}}} \log \hat{A}_{uv} - \frac{1}{|\mathcal{E}_{\text{neg}}|}\sum_{(u,w)\in\mathcal{E}_{\text{neg}}} \log(1 - \hat{A}_{uw}) \tag{22}$$

with $\hat{A}_{uv} = \sigma(\mathbf{h}_u^T\mathbf{W}_{\text{edge}}\mathbf{h}_v)$. Auxiliary loss $\mathcal{L}_{\text{aux}}$ enforces edge-trust classification via Binary Cross-Entropy and tri-band orthogonality ($\lambda_{\text{recon}} = 0.50, \lambda_{\text{aux}} = 0.10, \lambda_{\text{ortho}} = 0.05$):

$$\mathcal{L}_{\text{aux}} = \frac{1}{|\mathcal{E}_{\text{train}}|}\sum_{(i,j)\in\mathcal{E}_{\text{train}}} \ell_{\text{BCE}}(g_{ij}, \mathbf{g}_{ij}^{\text{target}}) + \lambda_{\text{ortho}}\|\mathbf{W}_{\text{burst}}^T\mathbf{W}_{\text{seas}}\|_F^2 \tag{23}$$

Operational decision threshold τ^* is calibrated over validation split $\mathcal{D}_{\text{val}}$ to minimize empirical cost under asymmetric penalty ratio $C_{\text{FN}}/C_{\text{FP}} = 15.0$:

$$\tau^* = \arg\min_{\tau\in[0,1]} \mathbb{E}\left[C_{\text{FN}} \cdot \mathbb{I}(\hat{p} < \tau, Y = 1) + C_{\text{FP}} \cdot \mathbb{I}(\hat{p} \geq \tau, Y = 0)\right] \tag{24}$$

The penalty ratio $C_{\text{FN}}/C_{\text{FP}} = 15.0$ reflects statutory bank operations: the average legal penalty, remediation cost, and enforcement forfeiture of an undetected false-negative money laundering incident ($\sim \$1,500$) is approximately 15 times the average analyst labor cost required to investigate a benign false-positive alert ($\sim \$100$). Optimizing τ^* reduces operational loss by 78.4% relative to default uncalibrated thresholding ($\tau = 0.50$).

3.9. Class-Conditional Split Conformal Prediction & 3-Tier Triage

Over independent holdout calibration split $\mathcal{D}_{\text{cal}}$, empirical class-conditional non-conformity quantiles $\hat{q}^{(y)}$ are computed ($y \in \{0, 1\}$):

$$\hat{q}^{(y)} = \text{Quantile}\left(\{s_i^{(y)}\}_{i=1}^{n(y)}; \frac{\lceil (n(y)+1)(1-\alpha_y) \rceil}{n(y)} \right) \quad (25)$$

where non-conformity scores are $s_i^{(y)} = 1 - \hat{p}_i(y)$.

Decoupled Theoretical Guarantees:

1. **Guarantee A (Exact Finite-Sample Validity):** Under within-class exchangeability on holdout split $\mathcal{D}_{\text{cal}}$, split conformal prediction guarantees exact class-conditional containment: $\mathbb{P}(Y \in \Gamma(X) \mid Y = y) \geq 1 - \alpha_y, \forall y \in \{0, 1\}$.
2. **Guarantee B (Non-Asymptotic Bound under Distribution Drift):** In financial streams where concept drift breaks strict exchangeability, we bound coverage degradation following Barber et al. (2023). Under bounded total variation shift $d_{\text{TV}}(\mathcal{P}_t^{(y)}, \mathcal{P}_{\text{cal}}^{(y)}) \leq \epsilon_{\text{drift}}$, class-conditional coverage satisfies:

$$\mathbb{P}_t(Y \in \Gamma(X) \mid Y = y) \geq 1 - \alpha_y - \epsilon_{\text{drift}} - \sqrt{\frac{\ln(2/\delta)}{2n(y)}} - \frac{1}{n(y)} \quad (26)$$

   with probability $\geq 1 - \delta$. For $n(1) = 372$ illicit calibration nodes on Elliptic-v1, the empirical process estimation term evaluates to $\Delta_n \approx 0.070$ (7.0 pp). In streaming deployment, C-STGB mitigates drift via streaming ACI recalibration.
3. **Guarantee C (Deterministic ACI Tracking under Feedback Delay):** Ground-truth confirmation incurs investigative delay $\tau \leq \Delta T_{\text{delay}} \in [30, 90]$ days. Streaming Adaptive Conformal Inference (ACI) updates target error rates online: $\alpha_t \leftarrow \alpha_{t-1} + \eta_{\text{aci}}(\alpha - \text{err}_{t-\tau(t)})$, where $\text{err}_{t-\tau(t)} = \mathbb{I}(y_{t-\tau(t)} \notin \Gamma_{t-\tau(t)}(x_{t-\tau(t)}))$ with step size $\eta_{\text{aci}} = 0.005$. By telescoping analysis for delayed feedback sequences (Gibbs and Candès, 2021), average coverage error satisfies:

$$\left| \frac{1}{T} \sum_{t=1}^{T} \text{err}_t - \alpha \right| \leq \frac{\max(\alpha, 1-\alpha) + \eta_{\text{aci}} \tau_{\max}}{\eta_{\text{aci}} T} \to 0 \quad \text{as } T \to \infty. \quad (27)$$

Algorithm 1 C-STGB Unified Multi-Stage Pipeline

Require: Transaction graph $\mathcal{G}_t = (\mathcal{V}_t, \mathcal{E}_t)$, Error levels α_0, α_1, Cost ratio $\frac{C_{\text{FN}}}{C_{\text{FP}}}$.
Ensure: Model parameters Θ, Threshold τ^*, Prediction set $\Gamma(u)$.
Phase 1: Feature & Temporal Invariant Extraction
Compute 12-D flow invariants $\mathbf{z}_{\text{inv}}(u, t)$ for $u \in \mathcal{V}_t$ via truncated power iteration taint and Hawkes arrival intensity $\lambda_u(t)$.
Compute continuous tri-band temporal embeddings $\Phi_{\text{time}}(\Delta t)$.
Phase 2: Topology Filtering & Typology Oversampling
Evaluate unfloored edge-trust gates g_{uv} (Eq. 11) and prune edges with $g_{uv} < \tau_{\text{gate}}$; apply floored weights $\hat{g}_{uv}$ to retained edges.
Partition minority training nodes into $K = 4$ typology clusters $\mathcal{C}_k$.
Synthesize latent representations $\mathbf{h}_{\text{syn}}$ and bilinear causal edges $\hat{\mathbf{A}}_{\text{syn}}$ preserving flow regularity within parent bounds.
Phase 3: Deep Representation & Adaptive Fusion
Aggregate multi-scale temporal messages over causal incoming neighbors $\mathcal{N}_K^{\text{in}}(u)$, $K \leq 15$ to obtain $\mathbf{h}_u^{(L)}$.
Compute evidence-adaptive gating α_u and fused state $\mathbf{h}_u^*$ (Eq. 18).
Phase 4: Optimization & Conformal Calibration
Optimize Θ minimizing multi-objective loss $\mathcal{L}_{\text{total}}$ (Eq. 20).
Calibrate decision threshold τ^* on validation split $\mathcal{D}_{\text{val}}$ (Eq. 24).
Compute class-conditional quantiles $\hat{q}^{(0)}, \hat{q}^{(1)}$ on calibration split $\mathcal{D}_{\text{cal}}$ (Eq. 25).
Phase 5: Streaming Inference & Operational Triage
Predict posterior risk $\hat{p}_u = \sigma(\text{MLP}(\mathbf{h}_u^*))$.
Form prediction set $\Gamma(u) = \{y \in \{0, 1\} : 1 - \hat{p}_u(y) \leq \hat{q}^{(y)}\}$.
Triage: $\Gamma = \{1\} \to$ Tier 1; $\Gamma = \{0, 1\} \to$ Tier 2; $\Gamma = \{0\} \to$ Tier 3.

Operational 3-Tier Queue Mapping: Conformal prediction sets $\Gamma(X) \subseteq \{0, 1\}$ partition transactions into three operational workflows: (i) **Tier 1 (High-Risk Escalation):** $\Gamma(X) = \{1\}$, flagged for immediate compliance hold and automated SAR compilation ($\approx 0.18\%$ of volume); (ii) **Tier 2 (Selective Abstention Queue):** $\Gamma(X) = \{0, 1\}$, routed to compliance officers as ambiguous cases ($\approx 0.50\%$ of volume); and (iii) **Tier 3 (Straight-Through Low-Risk Screening Tier):** $\Gamma(X) = \{0\}$, cleared straight-through without human intervention ($\approx 99.32\%$ of volume; decisive singletons total 99.50%).

3.10. Unified Algorithmic Specification & Systems Complexity

The complete end-to-end execution of the C-STGB intelligent decision-support pipeline is formalized in Algorithm 1.

Computational Complexity and Streaming SLAs: Ingesting a streaming transaction requires: (1) DuckDB/Arrow descriptor extraction (0.11 ms); (2) Top-15 causal subgraph retrieval (0.18 ms); (3) Temporal forward pass (0.12 ms); and (4) Conformal set routing (0.04 ms). The total streaming Fast-Path latency is **0.45** ms per event (P99: 0.82 ms) with 428 MB peak VRAM, sustaining **31,200** tx/s line-rate throughput and strictly bounded $O(K \cdot T_{\text{iter}})$ per-node complexity.

4. Experimental Evaluation

4.1. Benchmark Dataset Corpus & Topological Regimes

To evaluate model generalization across diverse financial rails, we benchmark C-STGB across 14 financial transaction

Table 1
Structural Overview of the 14 Benchmark Financial Networks across Topological Archetypes (9, 534, 980 Entities and 9, 528, 355 Transactions).

Archetype Group	Dataset Identifier	Entities / Events ($\lvert\mathcal{V}\rvert$)	Transactions ($\lvert\mathcal{E}\rvert$)	Features (d)	Illicit (π)	Temporal Span
Group A (Crypto Ledgers, 4)	`elliptic_v1` (Bitcoin UTXO) (Weber et al., 2019)	203,769	234,355	166	2.23%	49 Timesteps (2 Weeks)
	`elliptic_v2` (Multi-Asset) (Bellei et al., 2024)	122,279	186,400	166	0.85%	49 Timesteps (2 Weeks)
	`xblock_eth` (Smart Contracts) (Zheng et al., 2020)	2,150,000	2,800,000	14	0.09%	Continuous (1 Year)
	`mtgox_leaked` (Exchange Trades) (Gandal et al., 2018)	145,000	210,000	9	1.82%	Continuous (3 Years)
Group B (Banking & FinTech, 9)	`saml_d` (15-Bank Wire Mesh) (Oztas et al., 2023)	980,000	1,450,000	12	0.05%	Continuous (90 Days)
	`paysim1` (Single-Hop Mobile Money) (Lopez-Rojas and Axelsson, 2016)	636,262	636,262	9	0.13%	744 Timesteps (30 Days)
	`paysim_extended` (Mobile Multi-Event) (Lopez-Rojas and Axelsson, 2016)	1,048,575	1,048,575	9	0.13%	744 Timesteps (30 Days)
	`ibm_amlsim_hi_small` (Synthetic HI Small) (Altman et al., 2023)	100,000	180,000	11	0.23%	Continuous (100 Days)
	`ibm_amlsim_hi_medium` (Synthetic HI Medium) (Altman et al., 2023)	300,000	550,000	11	0.23%	Continuous (100 Days)
	`ibm_amlsim_li_small` (Synthetic LI Small) (Altman et al., 2023)	100,000	180,000	11	0.75%	Continuous (100 Days)
	`ibm_amlsim_li_medium` (Synthetic LI Medium) (Altman et al., 2023)	300,000	550,000	11	0.75%	Continuous (100 Days)
	`data_generator` (Complex Cycle Sim.)	100,000	250,000	12	1.50%	Continuous (30 Days)
	`dgraphfin` (Dynamic Credit Graph) (Huang et al., 2022b)	3,064,288	967,956	17	1.30%	Continuous (180 Days)
Group C (Card Streams, 1)	`cc_transactions` (Card Forensics) (Dal Pozzolo et al., 2018)	284,807	284,807	30	0.17%	Continuous (2 Days)
Total Benchmark Corpus	**14 Financial Networks**	**9,534,980**	**9,528,355**	**9–166**	**0.05%–2.23%**	**Multi-Horizon**

*In bipartite card streams (`cc_transactions`) and single-hop mobile logs (`paysim1`, `paysim_extended`), each record represents a transaction event vertex ($\lvert\mathcal{V}\rvert = \lvert\mathcal{E}\rvert$), modeled as an event-incidence graph. Relational networks (Elliptic-v1/v2, SAML-D, AMLworld, DGraphFin) model genuine persistent account entities. Citations: SAML-D (Oztas et al., 2023), AMLworld (Altman et al., 2023), DGraphFin (Huang et al., 2022b).

networks spanning public cryptocurrency ledgers, multi-bank wire systems, and mobile financial services, summarized in Table 1. The corpus comprises 9, 534, 980 entities and 9, 528, 355 transactions across three distinct topological archetypes:

1. **Group A (Public Crypto Ledgers & Exchange Logs, 4 Networks):** Directed Acyclic Graphs (DAGs), smart-contract transaction meshes, and exchange order-book trades (Elliptic-v1 (Weber et al., 2019), Elliptic-v2 (Bellei et al., 2024), XBlock-ETH (Zheng et al., 2020), MtGox Leaked) characterized by global ledger observability and structural transparency.
2. **Group B (Multi-Bank, Mobile & FinTech, 9 Networks):** Inter-bank wire meshes, mobile draining trees, and dynamic credit networks (SAML-D, PaySim1, PaySim Extended, IBM-AMLSim HI/LI Small/Medium, Synthetic Typology, DGraphFin) with extreme imbalance ($\pi \leq 1.50\%$). DGraphFin is a large-scale fintech dynamic credit lending network (3.06M nodes) capturing borrowing and default contagion. In PaySim Extended (`paysim_extended` (Lopez-Rojas and Axelsson, 2016)), each mobile log record maps to a transaction event vertex ($\lvert\mathcal{V}\rvert = \lvert\mathcal{E}\rvert = 1,048,575$).
3. **Group C (Card Fraud Streams, 1 Network):** High-throughput card-terminal bipartite transaction streams (`cc_transactions` (Dal Pozzolo et al., 2018)).

4.2. Temporal Partitioning & Zero-Leakage Audit

To prevent temporal lookahead bias and evaluate realistic forward inductive deployment, all datasets follow a strict 4-way chronological partition:

1. **Parameter Training Split ($\mathcal{D}_{\text{train}}$, 60%):** used strictly for neural parameter updates;
2. **Validation Split ($\mathcal{D}_{\text{val}}$, 10%):** used for early stopping and Bayes threshold calibration (τ^*);
3. **Calibration Split ($\mathcal{D}_{\text{cal}}$, 10%):** dedicated holdout split for computing non-conformity quantiles $\hat{q}^{(0)}, \hat{q}^{(1)}$ (zero weight updates, zero threshold tuning); and
4. **Forward Out-of-Time Test Split ($\mathcal{D}_{\text{test}}$, 20%):** strictly future horizon for final evaluation.

For discrete UTXO graphs (e.g., Elliptic-v1 with 49 timesteps), Timesteps 1–30 (61.22%) form $\mathcal{D}_{\text{train}}$, Timesteps 31–34 (8.16%) form $\mathcal{D}_{\text{val}}$, Timesteps 35–38 (8.16%) form $\mathcal{D}_{\text{cal}}$, and Timesteps 39–49 (22.45%) serve as $\mathcal{D}_{\text{test}}$. Continuous transaction stream datasets (PaySim, SAML-D, IBM-AMLSim, Ethereum) follow an identical non-overlapping timestamp horizon partition ($t_0 \rightarrow t_{\text{train}} \rightarrow t_{\text{val}} \rightarrow t_{\text{cal}} \rightarrow t_{\text{test}}$). In Bitcoin UTXO transaction graphs, each vertex represents a unique transaction identifier created at that block, making transaction nodes naturally disjoint across forward timesteps ($\mathcal{V}_{\text{test}} \cap \mathcal{V}_{\text{train}} = \emptyset$). On recurring account networks (SAML-D, PaySim), accounts persist across horizons with dynamic edge arrival, assessing genuine inductive temporal generalization.

Randomness Accounting across Seeds: While temporal split boundaries are strictly chronological and deterministic (60/10/10/20 partition), reported metrics reflect empirical variation across five locked random seeds ($S \in \{42, 101, 2024, 7, 999\}$). Seed variation governs four explicit stochastic components: (1) parameter initialization; (2) minibatch shuffling trajectories; (3) latent GraphSMOTE stochastic interpolation coefficients $\rho_{\text{interp}} \sim \mathcal{U}(0, 1)$; and (4) Monte Carlo dropout masks ($p = 0.20$, evaluated during offline diagnostic uncertainty audits).

Deterministic Topological Leakage Verification: A formal verification suite executes three topological invariant checks prior to training: (1) *Entity Boundary Isolation:* verifies strict temporal forward ordering for unseen accounts; (2) *Taint Masking Invariant:* enforces analytical taint seeds $\mathbf{s}_{\text{seed}}(u) \equiv 0$ for all $u \in \mathcal{D}_{\text{val}} \cup \mathcal{D}_{\text{cal}} \cup \mathcal{D}_{\text{test}}$, ensuring test evaluations compute diffusion exclusively from historical training seeds; and (3) *Directional Time Invariance:* confirms that every edge $(u, v, t) \in \mathcal{E}_{\text{train}}$ strictly satisfies $t \leq t_{\text{train}}$. The verification suite confirms 0.00% entity overlap and zero future-timestamp propagation across all 14 empirical benchmarks.

4.3. Baseline Architectures & Fair Optimization Protocol

We benchmark C-STGB against 12 distinct baseline architectures across six canonical model paradigms:

1. *Tabular Tree Ensembles:* XGBoost (Chen and Guestrin, 2016), CatBoost (Prokhorenkova et al., 2018), and LightGBM (Ke et al., 2017);
2. *Spatial GNNs:* GCN, GraphSAGE, GAT, and GIN (Kipf and Welling, 2017; Hamilton et al., 2017; Veličković et al., 2018; Xu et al., 2019);
3. *Heterogeneous GNNs:* Vanilla HGT (Hu et al., 2020);
4. *Adversarial Fraud Detectors:* CARE-GNN (Dou et al., 2020);
5. *Dynamic Snapshot Models:* EvolveGCN (Pareja et al., 2020); and
6. *Continuous Temporal GNNs:* TGN (Rossi et al., 2020) (alongside classical linear and autoencoding anomaly detectors in Supplementary Table S3).

Evaluating these 12 baselines alongside C-STGB across 14 benchmark datasets yields 13 model configurations and exactly 182 dataset × model evaluation pairs, evaluated over five locked random seeds (910 total experimental executions). To ensure rigorous parity, gradient-boosted decision trees (XGBoost, CatBoost, LightGBM) and spatial GNN baselines were evaluated on both raw transactional features and the 12-dimensional canonical invariant vector $\mathbf{z}_{\text{inv}}$ under identical validation-tuned threshold search grids.

Positioning Against Recent Flagship Literature: We contextualize C-STGB against three recent flagship works:

1. *H^2IDE* (Fu et al., 2025): isolates camouflaged fraudsters over multi-relational graphs via disentangled homophily and heterophily, but operates over static relations and lacks continuous-time streaming edge dynamics (Δt);
2. *CamFD* (Ou et al., 2026): filters camouflaged fraudsters over discrete relational schemas without post-hoc finite-sample risk guarantees ($\geq 99\%$ coverage); and
3. *Group-Aware GNN* (Cheng et al., 2023): clusters account groups on static ledgers rather than streaming transaction-level conformal calibration.

2×2 **Factorial Feature Attribution Protocol:** To rigorously isolate whether performance gains stem from the C-STGB neural architecture, engineered domain invariants, or threshold optimization, Figure 2 reports a controlled 2×2 factorial evaluation contrasting tabular trees and GNNs with and without the 12-D canonical invariant vector $\mathbf{z}_{\text{inv}}$ under validation-calibrated thresholding τ^*.

Mechanistic Divergence Analysis: This controlled factorial comparison reveals a fundamental mechanistic divergence. Isotropic spatial convolutions linearly average feature representations across multi-hop neighborhoods. When illicit accounts connect to high-degree commercial hubs (deg $>$ 50), localized scalar signatures in $\mathbf{z}_{\text{inv}}$ (e.g., flow regularity $\Phi_{\text{flow}} \approx 1.0$ and burst intensity λ_u) are arithmetically diluted by dozens of benign neighbors into the majority mean. Consequently, augmenting GCN with $\mathbf{z}_{\text{inv}}$ yields only a marginal +1.07 pp macro uplift (23.78% → 24.85%). In contrast, tree ensembles evaluate axis-aligned orthogonal splits on unmixed features, isolating Φ_{flow} directly without topological smoothing and surging to 90.80% on Elliptic-v1. However, on complex multi-hop relational networks (SAML-D and IBM-AMLSim HI), C-STGB decisively outperforms invariant-augmented XGBoost (93.68% vs 91.15%, and 46.85% vs 41.20%), confirming that higher-order spatio-temporal message passing with edge-trust gating is indispensable for tracking distributed laundering rings.




Figure 2: 2×2 Factorial Feature Attribution Analysis: Contrasting tabular tree ensembles and graph neural networks with Native Features versus Invariant-Augmented Features ($[\mathbf{x}_u \,\|\, \mathbf{z}_{\text{inv}}]$) under validation-calibrated decision thresholds τ^* across (a) Elliptic-v1 and (b) 14-Dataset Macro-Average minority F1-scores (%).

4.4. Evaluation Metrics & Statistical Testing Protocol

Under extreme class imbalance ($\pi \ll 0.01$), traditional ROC-AUC is overly optimistic due to the dominant true negative denominator, and binary macro F1 arithmetic means are artificially dominated by the $>$ 99% benign class ($F_1^{(0)} \approx 1.0$). We evaluate:

1. **PR-AUC:** Precision-recall trade-offs on the minority class;
2. **Minority F1 ($F_1^{(1)}$) & Recall:** Utility on confirmed illicit entities under validation-tuned threshold τ^*; and
3. **Set Efficiency ($\mathbb{E}[|\Gamma(X)|]$):** Conformal prediction set tightness.

Across the corpus, Macro-Averages denote the unweighted arithmetic mean of minority F1 across all 14 datasets ($\frac{1}{14}\sum_{i=1}^{14} F_1^{(1)}(i)$). All models undergo paired threshold optimization on $\mathcal{D}_{\text{val}}$ under identical search grids minimizing $\mathcal{L}_{\text{ops}}$ ($C_{\text{FN}}/C_{\text{FP}} = 15.0$). Statistical significance is evaluated via two-sided Wilcoxon Signed-Rank Tests across all 14 benchmark networks, with Benjamini–Hochberg False Discovery Rate (FDR) multiple-testing correction.

4.5. Comparative Baseline Performance & Benchmark Scorecard

Table 2 reports benchmark comparisons across all 14 benchmark networks under validation-calibrated decision thresholds τ^*. Evaluated on native transactional features, gradient-boosted decision trees attain an unweighted macro




Figure 3: Empirical Precision-Recall and ROC performance on the Elliptic-v1 benchmark ($\pi = 9.76\%$ illicit prevalence on labeled evaluation nodes; 2.23% total graph prevalence), contrasting C-STGB (PR-AUC 0.9312, F1 91.42%) against native-feature XGBoost (PR-AUC 0.8900, F1 88.35%), CatBoost (PR-AUC 0.8800, F1 87.90%), and deep spatial/temporal GNNs over 5 locked seeds.

F1 of 64.76% (0.6500 PR-AUC) for XGBoost and 64.25% (0.6400 PR-AUC) for CatBoost, while C-STGB achieves 68.05% macro F1 (0.6974 PR-AUC), demonstrating a +3.29 pp global uplift over native XGBoost alongside statistically significant superiority over deep GNN baselines (+44.27 pp mean uplift over GCN; $W = 105.0, p_{\text{adj}} < 0.001$).

Feature-Boosted XGBoost Ablation Study: To isolate the predictive contribution of the engineered 12-dimensional canonical invariant vector $\mathbf{z}_{\text{inv}}$, we execute an ablation study by training XGBoost on the concatenated feature vector $[\mathbf{x}_u \,\|\, \mathbf{z}_{\text{inv}}]$. On `elliptic_v1`, invariant-augmented XGBoost surges from 88.35% to 90.80% F1 (+2.45 pp uplift), corroborating that our domain invariants capture essential physical flow conservation and arrival burst dynamics that benefit both tree ensembles and graph networks. However, on complex multi-hop relational benchmarks (e.g., IBM-AMLSim HI and SAML-D), standalone trees with invariants still trail C-STGB, confirming that multi-hop spatio-temporal message passing captures higher-order topological dependencies that axis-aligned decision trees cannot represent.

Statistical Hypothesis Testing & GNN Superiority: Empirical evidence demonstrates that C-STGB delivers statistically significant outperformance over all evaluated deep spatial and dynamic GNN baselines: +44.27 pp mean uplift over GCN (median +40.11 pp, IQR 68.01 pp; 14 wins, 0 losses), +43.74 pp over GraphSAGE (median +39.80 pp, IQR 66.13 pp; 14 wins, 0 losses), and +49.11 pp over EvolveGCN (median +40.09 pp, IQR 56.53 pp; 14 wins, 0 losses) ($W^+ = 105.0, W^- = 0.0, n = 14, p = 1.22 \times 10^{-4}, p_{\text{adj}} = 1.71 \times 10^{-4}$). Non-parametric paired testing in Table 2 confirms this divergence across all topological regimes.




Figure 4: Latent manifold t-SNE projection: baseline GNN (left) exhibits severe feature over-smoothing around commercial hubs, whereas C-STGB under Typology GraphSMOTE (right) induces dense, distinct clustering of confirmed illicit topologies ($K = 4$) with sharp boundary separation.

When Graph Learning Helps – and When It Does Not: This performance pattern highlights a critical domain boundary:

1. *Relational Regimes:* On complex networks with multi-hop laundering chains, degree variance, and camouflage (e.g., IBM-AMLSim HI, SAML-D, Elliptic-v1/v2), C-STGB outperforms both base GNNs (+9.98 pp to +48.3 pp) and native tree ensembles (+3.07 pp on Elliptic-v1, +7.30 pp and +7.35 pp on AMLSim HI). Spatio-temporal message passing captures coordinated flow across account chains that flat tabular models cannot represent.
2. *Flat Transaction Streams:* On `paysim1`, C-STGB achieves 16.66% F1, trailing XGBoost (18.90%) and CatBoost (17.76%). In `paysim1`, fraud signals reside in localized tabular balance discrepancies within isolated transactions without multi-hop chains, where graph aggregation provides no structural gain over axis-aligned decision trees.

Statistical Hypothesis Testing: Table 2 presents non-parametric hypothesis testing with paired observations across all $n = 14$ benchmarks: two-sided Wilcoxon signed-rank tests yield maximal rank sum $W = 105.0$ ($W_- = 0.0, n = 14$), with exact $p = 1.22 \times 10^{-4}$ and Benjamini–Hochberg adjusted $p_{\text{adj}} = 6.10 \times 10^{-4} < 0.001$ against GCN, GraphSAGE, and EvolveGCN. Furthermore, against native-feature tree baselines, C-STGB achieves statistically significant superiority over XGBoost (+3.29 pp mean uplift, $W^+ = 99.5, W^- = 5.5, p_{\text{adj}} = 3.17 \times 10^{-3}$) and CatBoost (+3.80 pp mean uplift, $W^+ = 102.0, W^- = 3.0, p_{\text{adj}} = 7.12 \times 10^{-4}$). Re-testing against invariant-augmented GNNs ($[\mathbf{x}_u \,\|\, \mathbf{z}_{\text{inv}}]$) preserves full significance ($W = 105.0$, 14 wins, 0 losses, $p_{\text{adj}} < 0.001$).

4.6. Class-Conditional Conformal Risk Control & Queue Triage

Table 4 and Figure 5 evaluate Class-Conditional Conformal Risk Control (CRC) across benchmark archetypes at significance level $\alpha = 0.01$ (99.0% target true label coverage). Specifically, split-conformal calibration operates on chronologically held-out calibration splits $\mathcal{D}_{\text{cal}}$ ($n_0 = 3{,}306$ benign, $n_1 = 372$ illicit on the Elliptic-v1 calibration split $\mathcal{D}_{\text{cal}}$, drawn from total corpus labels $N_0 = 42{,}019$, $N_1 = 4{,}545$). While exact coverage $\mathbb{P}(Y \in \Gamma(X) \mid Y = y) \geq 1 - \alpha_y$ holds under within-class exchangeability, production financial streams encounter temporal drift. Under bounded total variation drift $d_{\text{TV}}(\mathcal{P}_t^{(y)}, \mathcal{P}_{\text{cal}}^{(y)}) \leq \epsilon_{\text{drift}}$, coverage degradation is mathematically bounded by the Dvoretzky–Kiefer–Wolfowitz (DKW) empirical concentration bound plus d_{TV} (Proposition S1 in Supplementary Material), while online Adaptive Conformal Inference

Table 2
Comprehensive Benchmark Comparison across All 14 Financial Networks: Minority (Illicit) Class F1-Score (%) and PR-AUC with Validation-Tuned Thresholds τ^* under Asymmetric Operational Loss against Literature Baselines († indicates statistically significant corpus-wide improvement over deep GNNs at $W^+ = 105.0, W^- = 0.0, p_{\text{adj}} < 0.001$ under two-sided Wilcoxon signed-rank test across all 14 benchmark networks).

Dataset Identifier	XGBoost	CatBoost	GCN	GraphSAGE	CARE-GNN	EvolveGCN	TGN	C-STGB (Ours)
Group A: Public Blockchain Ledgers & Relational DAGs (4 Networks)								
elliptic_v1	88.35/0.8900	87.90/0.8800	43.55/0.3482	49.07/0.4254	64.50/0.6800	51.04/0.4243	68.40/0.7200	**91.42 ± 0.65/0.9312**
elliptic_v2	96.50/0.9814	95.80/0.9580	0.00/0.0237	0.24/0.0230	58.20/0.6100	0.00/0.0258	62.10/0.6500	**99.10 ± 0.45/0.9950**
xblock_eth	93.80/0.9400	92.90/0.9300	6.53/0.0212	6.75/0.0206	63.20/0.6600	6.62/0.0211	67.50/0.7100	**97.40 ± 0.50/0.9920**
mtgox_leaked	68.40/0.7400	67.80/0.7300	20.30/0.2038	22.16/0.1801	52.40/0.5600	22.12/0.0956	55.80/0.6000	**74.20 ± 0.95/0.8350**
Group B: Multi-Bank, Mobile Synthetic & FinTech Rails (9 Networks)								
saml_d	89.20/0.8950	88.60/0.8850	1.69/0.0109	3.16/0.0071	55.80/0.5900	3.81/0.0077	59.40/0.6300	**93.68 ± 0.60/0.9574**
paysim1	18.90/0.1254	17.76/0.1061	3.50/0.0084	0.56/0.0016	2.20/0.0180	3.98/0.0097	2.50/0.0220	**16.66 ± 0.80/0.1350**
paysim_extended	99.72/0.9996	99.77/0.9996	96.22/0.9825	96.05/0.9799	69.40/0.7200	92.64/0.7521	73.10/0.7600	**99.80 ± 0.10/0.9993**
ibm_amlsim_hi_small	32.40/0.3100	31.80/0.3000	2.46/0.0101	2.46/0.0080	25.40/0.2800	2.31/0.0080	28.40/0.3200	**39.70 ± 1.20/0.4000**
ibm_amlsim_hi_medium	39.50/0.4200	38.90/0.4100	3.88/0.0135	3.95/0.0126	31.80/0.3500	7.06/0.0350	35.20/0.3900	**46.85 ± 1.10/0.5100**
ibm_amlsim_li_small	14.20/0.1300	13.80/0.1300	0.84/0.0060	1.50/0.0057	11.80/0.1300	1.18/0.0052	12.90/0.1400	**15.83 ± 0.95/0.1493**
ibm_amlsim_li_medium	21.50/0.1900	20.90/0.1900	3.41/0.0143	2.30/0.0073	17.50/0.2000	4.29/0.0238	19.20/0.2200	**23.74 ± 1.10/0.2139**
data_generator	99.90/0.9990	99.85/0.9985	99.74/0.9979	99.63/0.9956	78.50/0.8100	62.72/0.6327	81.50/0.8400	**99.93 ± 0.05/1.0000**
dgraphfin	96.07/0.9900	95.82/0.9628	2.60/0.0129	3.26/0.0161	2.50/0.0450	2.59/0.0094	3.20/0.0250	**97.91 ± 0.40/0.9979**
Group C: Bipartite Card Transaction Streams (1 Network)								
cc_transactions	48.20/0.4900	47.90/0.4800	48.16/0.3472	49.24/0.3555	34.20/0.3800	4.79/0.0215	38.20/0.4200	**56.48 ± 0.70/0.6476**
Overall Macro Mean	64.76/0.6500	64.25/0.6400	23.78/0.2143	24.31/0.2170	40.53/0.4309	18.94/0.1480	43.39/0.4605	**68.05 ± 0.48/0.6974**†
Non-Parametric Statistical Testing & Effect Sizes vs. C-STGB ($n = 14$ Benchmark Networks)								
Wins / Ties / Losses	13 / 0 / 1	13 / 0 / 1	14 / 0 / 0	14 / 0 / 0	14 / 0 / 0	14 / 0 / 0	14 / 0 / 0	–
Mean Advantage (Δ)	+3.29 pp	+3.80 pp	+44.27 pp	+43.74 pp	+27.52 pp	+49.11 pp	+24.66 pp	–
Median [IQR] Δ	+2.84 [3.79] pp	+3.41 [4.03] pp	+40.11 [68.01] pp	+39.80 [66.13] pp	+22.04 [18.64] pp	+40.09 [56.53] pp	+18.42 [16.82] pp	–
Wilcoxon W^+, W^-	99.5, 5.5	102.0, 3.0	105.0, 0.0	105.0, 0.0	105.0, 0.0	105.0, 0.0	105.0, 0.0	–
Raw p-value	3.17×10^{-3}	6.10×10^{-4}	1.22×10^{-4}	1.22×10^{-4}	1.22×10^{-4}	1.22×10^{-4}	1.22×10^{-4}	–
Adjusted p_{adj}	$\mathbf{3.17 \times 10^{-3}}$	$\mathbf{7.12 \times 10^{-4}}$	$\mathbf{1.71 \times 10^{-4}}$	$\mathbf{1.71 \times 10^{-4}}$	$\mathbf{1.71 \times 10^{-4}}$	$\mathbf{1.71 \times 10^{-4}}$	$\mathbf{1.71 \times 10^{-4}}$	–

Minority (illicit) class F1-Score evaluates harmonic precision and recall on confirmed illicit transactions ($y = 1$) under validation-calibrated threshold τ^*; Macro-Average represents the unweighted arithmetic mean across benchmark dataset scores, alongside median and interquartile range. Tabular tree models (XGBoost, CatBoost) are reported on native transaction features (64.76% and 64.25% macro F1); augmenting XGBoost with the 12-D flow invariants $\mathbf{z}_{\text{inv}}$ elevates its score to 90.80% on Elliptic-v1 as detailed in Section 4.5. † indicates statistically significant corpus-wide improvement over deep GNNs at $W^+ = 105.0, W^- = 0.0, p_{\text{adj}} < 0.001$ under two-sided Wilcoxon signed-rank test across all 14 benchmark networks with Benjamini–Hochberg FDR correction across $m = 7$ comparisons. Group A: 4 Public Crypto Ledgers; Group B: 9 Multi-Bank, Mobile & FinTech Networks; Group C: 1 Bipartite Card Stream.

Table 3
Non-Parametric Statistical Significance and Distributional Effect Sizes of C-STGB vs. Baselines across All $n = 14$ Benchmark Networks (Two-Sided Paired Wilcoxon Signed-Rank Test with Benjamini–Hochberg FDR Correction across $m = 7$ Comparisons).

Baseline	W / T / L	Mean Δ	Median [IQR]	W^+, W^-	Adjusted p_{adj}
XGBoost (Tabular)	13 / 0 / 1	+3.29 pp	+2.84 [3.79] pp	99.5, 5.5	$\mathbf{3.17 \times 10^{-3}}^{**}$
CatBoost (Industrial)	13 / 0 / 1	+3.80 pp	+3.41 [4.03] pp	102.0, 3.0	$\mathbf{7.12 \times 10^{-4}}^{***}$
GCN (Spatial)	14 / 0 / 0	+44.27 pp	+40.11 [68.01] pp	105.0, 0.0	$\mathbf{1.71 \times 10^{-4}}^{***}$
GraphSAGE (Inductive)	14 / 0 / 0	+43.74 pp	+39.80 [66.13] pp	105.0, 0.0	$\mathbf{1.71 \times 10^{-4}}^{***}$
CARE-GNN (Camouflage)	14 / 0 / 0	+27.52 pp	+22.04 [18.64] pp	105.0, 0.0	$\mathbf{1.71 \times 10^{-4}}^{***}$
EvolveGCN (Dynamic)	14 / 0 / 0	+49.11 pp	+40.09 [56.53] pp	105.0, 0.0	$\mathbf{1.71 \times 10^{-4}}^{***}$
TGN (Continuous Time)	14 / 0 / 0	+24.66 pp	+18.42 [16.82] pp	105.0, 0.0	$\mathbf{1.71 \times 10^{-4}}^{***}$

*Under invariant representations $[\mathbf{x}_u \,\|\, \mathbf{z}_{\text{inv}}]$, C-STGB preserves 14/0/0 wins over standard GNNs ($W^+ = 105.0, W^- = 0.0, p_{\text{adj}} < 0.001$). Full per-dataset evaluation matrix is provided in Supplementary Material Table S3.




Figure 5: Class-conditional conformal calibration analysis: (a) Nominal target coverage $1 - \alpha \in [0.90, 0.999]$ versus empirical out-of-sample coverage on chronological test splits, with shaded 95% DKW finite-sample confidence bands; (b) Selective risk (residual false-negative leakage on Tier-3 cleared stream) versus straight-through automation rate, highlighting the calibrated operating point at $\alpha = 0.01$ (99.50% automation, 0.18% selective risk).

(ACI) tracks non-stationary drift over confirmed operational queues. Across all datasets, empirical coverage satisfies the nominal 99.0% bound (99.02%–99.28%, macro 99.12%).

Crucially, the high coverage guarantee (99.12% macro-average) is achieved with prediction set efficiency: across all 9.53 million transactions, singleton decisive prediction sets ($|\Gamma(X)| = 1$) account for 99.50% of volume (Tier 1 auto-quarantine ≈ 0.18% + Tier 3 auto-clear ≈ 99.32%), while ambiguous abstention sets ($|\Gamma(X)| = 2$, Tier 2) comprise exactly 0.50%. The empty prediction set rate $\mathbb{P}(\Gamma(X) = \emptyset)$ is verified to be exactly 0.00%, yielding an average prediction set size of $\mathbb{E}[|\Gamma(X)|] = 1.0050$, confirming that coverage guarantees are operationally tight.

4.7. Modular Stepwise & Leave-One-Out Ablation Study

To evaluate architectural contributions, Table 5 details both cumulative stepwise progression from baseline static GNN to full C-STGB across three financial archetypes and leave-one-out removals on Elliptic-v1. Baseline GCN

Table 4
Class-Conditional Conformal Prediction Triage Evaluation across All 14 Benchmark Financial Networks ($\alpha = 0.01$, Nominal 99.0% Target True-Class Containment; Denominator: Forward Chronological Test Set N_{test}).

Archetype Group	Dataset Identifier	Test Size (N_{test}) (Stated Denom.)	Empirical Cov. ($\geq 99.0\%$ Target)	Selective Risk (Tier 3 FN Rate)	Review Rate (Tier 2) (Officer Queue Count, %)	Efficiency (Workload Red.)	Tier Breakdown (T1/T2/T3 per 10k)
Group A (Crypto, 4)	elliptic_v1	20,377	99.12%	0.08%	98 (0.48%)	−99.52%	18 / 48 / 9,934
	elliptic_v2	24,456	99.05%	0.08%	135 (0.55%)	−99.45%	12 / 55 / 9,933
	xblock_eth	430,000	99.18%	0.06%	2,150 (0.50%)	−99.50%	4 / 50 / 9,946
	mtgox_leaked	29,000	99.08%	0.14%	145 (0.50%)	−99.50%	25 / 50 / 9,925
Group B (Banking, 9)	saml_d	196,000	99.15%	0.05%	882 (0.45%)	−99.55%	3/45/9,952
	paysim1	127,252	99.11%	0.10%	611 (0.48%)	−99.52%	8/48/9,944
	paysim_extended	209,715	99.22%	0.12%	797 (0.38%)	−99.62%	8/38/9,954
	ibm_amlsim_hi_small	20,000	99.06%	0.19%	104 (0.52%)	−99.48%	15 / 52 / 9,933
	ibm_amlsim_hi_med	60,000	99.08%	0.22%	312 (0.52%)	−99.48%	16 / 52 / 9,932
	ibm_amlsim_li_small	20,000	99.04%	0.20%	102 (0.51%)	−99.49%	38/51/9,911
	ibm_amlsim_li_med	60,000	99.07%	0.21%	306 (0.51%)	−99.49%	40 / 51 / 9,909
	data_generator	20,000	99.28%	0.09%	88 (0.44%)	−99.56%	55 / 44 / 9,901
	dgraphfin	612,858	99.18%	0.13%	2,574 (0.42%)	−99.58%	62 / 42 / 9,896
Group C (Cards, 1)	cc_transactions	56,961	99.10%	0.15%	330 (0.58%)	−99.42%	11 / 58 / 9,931
Macro-Average	**All 14 Networks**	**1,846,619**	**99.12%**	**0.13%**	**8,638 (0.49%)**	**−99.51%**	**22/49/9,929**

Evaluated on the forward out-of-time test splits (N_{test}) using class-conditional non-conformity quantiles $\hat{q}^{(0)}, \hat{q}^{(1)}$ calibrated on independent holdout splits D_{cal}. Tier 1: Quarantined immediate hold / regulatory SAR dossier ($\Gamma = \{1\}$); Tier 2: Ambiguous cases routed to compliance officer queue ($\Gamma = \{0, 1\}$); Tier 3: Straight-through automated clearance ($\Gamma = \{0\}$). Selective risk is the proportion of confirmed illicit transactions erroneously cleared in Tier 3 (macro-average 0.13%, strictly below 0.22% across all 14 datasets). Workload reduction is −99.51% relative to exhaustive manual review and represents an 85.7%–95.8% operational alert reduction compared to commercial rule-based filters at matched 90.10% recall.

achieves 43.55% F1 at $\tau = 0.50$ (Step 1a) and 51.04% at τ^* (Step 1b). Adding Continuous Temporal Encoding (+Mod 1, 68.50%), Edge Trust Gating (+Mod 2, 76.20%), Typology GraphSMOTE (+Mod 3, 86.12%), Adaptive Fusion (+Mod 4, 89.80%), and Cost-Sensitive Thresholding (+Mod 5) progressively drives performance to 91.42% F1 (Recall 90.10%, Precision 92.80%, PR-AUC 0.9312). Conformal Risk Control (+Mod 6) delivers uncertainty triage without altering point F1. Leave-one-out removals confirm Cost-Sensitive Thresholding (−12.26 pp) and Typology GraphSMOTE (−9.92 pp) provide the largest individual margins.

4.8. Latency-Memory Pareto Frontier & Systems Profiling

To avoid confounding model capacity with operational latency, we explicitly distinguish two operational configurations:

1. **C-STGB-Fast (Streaming Triage):** Designed for wire-speed inline transaction scoring. Evaluates degree-capped 1-hop causal neighborhoods ($K \leq 15$) with pre-computed DuckDB descriptors. Achieves a streaming single-event latency of 0.45 ms (P99: 0.82 ms) and 428 MB peak VRAM (31,200 tx/s, Figure 6). For real-time streaming scoring, Monte Carlo dropout is deactivated (eval mode), ensuring single-pass deterministic inference.
2. **C-STGB-Full (Full Forensics):** Uses multi-scale triband attention with 2-hop neighborhood expansion, achieving the benchmark accuracy in Table 2. Single-event streaming latency is 2.10 ms (3.30 ms batch-64 latency) with 894 MB peak VRAM and 19,400 tx/s throughput.




Figure 6: Operational Systems Scaling and Latency Profile: Streaming single-event latency versus peak VRAM memory footprint and event throughput across evaluated configurations on benchmark hardware.

4.9. Adversarial Threat Model & Topological Camouflage Defense

Fig. 7 evaluates robustness across progressive perturbation ratios $\rho \in [0, 0.80]$ with 95% confidence bands across five seeds. Standard GCN collapses from 43.55% clean F1 to 4.10 ± 0.85% F1 under gradient attacks, GraphSAGE collapses from 49.07% to 5.80±0.95%, and Vanilla HGT degrades from 48.20% to 9.80±0.85% F1. In contrast, C-STGB demonstrates exceptional resilience: from a clean score of 91.42 ± 0.65% F1, C-STGB retains 84.20 ± 0.85% F1 under white-box gradient topological perturbation, preserving a relative retention of 92.1%.

Table 5
Unified Architectural Ablation Study: (a) Cumulative Stepwise Forward Progression; (b) Leave-One-Out Component Removals on Elliptic-v1 (5 Seeds). Note: Step (1a) represents an uncalibrated Vanilla 2-layer GCN at fixed default threshold $\tau = 0.50$ without threshold search (89.50% on PaySim Extended, 7.85% on IBM-AMLSim HI Medium), whereas Table 2 evaluates optimized GCN benchmarks under validation-calibrated threshold search τ^* (96.22% on PaySim Extended).

(a) Cumulative Stepwise Forward Progression (Recall / F1-Score (%) across 5 Seeds)

Ablation Progression	Elliptic-v1		PaySim Extended		IBM-AMLSim HI Med	
	Rec.	F1	Rec.	F1	Rec.	F1
(1a) Base Static GNN ($\tau = 0.50$)	34.20	43.55	84.20	89.50	4.10	7.85
(1b) Base Static GNN (τ^*)	34.20	43.55	92.40	96.22	2.80	3.88
(2) + Mod 1: Continuous Time	64.10	68.50	94.50	96.20	11.20	16.30
(3) + Mod 2: Edge Trust Gate	74.20	76.20	96.80	97.50	14.80	21.40
(4) + Mod 3: Typology SMOTE	83.50	86.12	98.10	98.60	19.50	28.60
(5) + Mod 4: Adaptive Fusion	88.20	89.80	99.10	99.30	23.10	33.80
(6a) + Mod 5: Cost-Sensitive τ^*	**90.10**	**91.42**	**99.65**	**99.80**	**25.55**	**46.85**
(6b) + Mod 6: Conformal Risk Control	*Preserves point F1; delivers 99.12% coverage with 1.005 avg set size*					

(b) Leave-One-Out Component Removal on Elliptic-v1 (Margin vs. Full Architecture)

Ablated Component	Recall (%)	F1-Score (%)	Precision (%)
Full C-STGB Architecture	$\mathbf{90.10 \pm 0.72}$	$\mathbf{91.42 \pm 0.65}$	$\mathbf{92.80 \pm 0.58}$
w/o Typology GraphSMOTE	75.60 ± 0.90	81.50 ± 0.82 (−9.92 pp)	88.40 ± 0.75
w/o Edge-Gating Filter (g_{ij})	88.50 ± 0.65	85.80 ± 0.72 (−5.62 pp)	83.20 ± 0.80
w/o Tri-Band Temporal Decay	84.20 ± 0.75	86.10 ± 0.70 (−5.32 pp)	88.10 ± 0.68
w/o Evidence-Adaptive Fusion (α_u)	86.80 ± 0.70	88.12 ± 0.65 (−3.30 pp)	89.50 ± 0.62
w/o Hawkes Point Process Intensity	87.80 ± 0.68	89.12 ± 0.64 (−2.30 pp)	90.50 ± 0.60
w/o 12-D Domain Descriptors ($\mathbf{z}_{\text{inv}}$)	82.40 ± 0.85	83.96 ± 0.80 (−7.46 pp)	85.60 ± 0.78
w/o Cost-Sensitive Threshold (τ^*)	76.20 ± 0.85	79.16 ± 0.80 (−12.26 pp)	82.40 ± 0.90

We explicitly disclose an inductive construct overlap between Module 2 training supervision and degree-matched camouflage testing: auxiliary edge-trust loss (Eq. 23) guides $\hat{g}_{ij}$ during training using hub-degree heuristics ($\deg_{\text{out}}(j) \geq 50$) on $\mathcal{E}_{\text{train}}$, aligning with the structural pattern manipulated in degree-matched camouflage. Consequently, retention under degree camouflage partly reflects this intended architectural bias.

To rigorously validate defense capabilities beyond this heuristic, we evaluate attacks completely outside the degree-matched construct: (1) *White-box gradient topology attacks:* where perturbations are guided strictly by $\nabla_{\mathcal{E}}\mathcal{L}$ without targeting node degrees, where C-STGB retains 84.20% F1; (2) *Low-degree camouflage:* connecting to low-degree accounts, where C-STGB retains 90.10% F1 due to flow-balance descriptors; and (3) *Temporal delay camouflage:* diluting velocity over weeks, where tri-band harmonic attention preserves 89.80% F1. On Elliptic-v1 under $\rho = 0.20$ degree-matched camouflage injection, edge-trust gating achieves 65.9% synthetic camouflage chaff pruning ($g_{ij} < 0.10$), while preserving 92.1% of legitimate commercial edges (91.4% precision, 88.7% recall, AUROC 0.942).




Figure 7: Adversarial Camouflage Robustness: Macro F1 retention across perturbation ratios $\rho \in [0, 0.80]$ on Elliptic-v1 under degree-matched and gradient-based evasion attacks (95% confidence bands, 5 seeds).

4.10. Hyperparameter Sensitivity & Stability Analysis

We evaluate operational stability across four key hyperparameters:

1. *Edge-Trust Floor* ($\delta_{\text{floor}} \in [0.02, 0.30]$): Macro F1 remains stable across $\delta_{\text{floor}} \in [0.06, 0.16]$ (±0.35 pp around 91.42%).
2. *Operational Cost Ratio* ($C_{\text{FN}}/C_{\text{FP}} \in [5, 30]$): Calibrated decision thresholds adapt monotonically from

$\tau^* = 0.42$ ($C_{FN}/C_{FP} = 5$) to $\tau^* = 0.18$ ($C_{FN}/C_{FP} = 15$) and $\tau^* = 0.11$ ($C_{FN}/C_{FP} = 30$). Expected operational loss remains within 4.2% of optimum across $[10, 20]$.

3. *Degree Cap* ($K \in [5, 30]$): F1 plateaus at $K = 15$ (91.42%), capturing 98.6% of multi-hop laundering while bounding retrieval latency to 0.18 ms (2.14 ms at $K = 50$).
4. *Adaptive Conformal Step Size* ($\gamma \in [0.001, 0.05]$): Coverage remains within 98.83%–99.34%, where $\gamma = 0.005$ achieves optimal tracking stability.

5. Discussion & Operational Implications

5.1. Architectural Synergy & Division of Labor Across Modules

Empirical evaluations across 14 benchmark networks yield five operational insights. Ablations (Table 5) confirm performance stems from structured module specialization: (1) **Continuous Temporal Attention** captures microsecond bursts alongside 90-day dormancy (43.55% → 68.50% F1 on Elliptic-v1); (2) **Camouflage Filtration** prunes 65.9% of injected camouflage links ($g_{ij} < 0.10$), preserving a +5.62 pp margin; (3) **Latent Typology GraphSMOTE** elevates illicit recall from 34.20% (base static GNN) to 83.50% (and 90.10% in the fully tuned system; removing GraphSMOTE incurs a −14.50 pp recall drop to 75.60%, +9.92 pp F1 to reach 91.42% on Elliptic-v1 under invariant Bayes thresholding); and (4) **Evidence-Adaptive Gating** acts as a safety valve: on dense graphs ($d \geq 5$), the GNN captures multi-hop loops, while on sparse stubs ($d \leq 2$), weight shifts to tabular descriptors ($\mathbf{z}_{inv}$), securing 89.60% F1 on cold-start entities.

5.2. Relational Topology vs. Tabular Tree Baseline Nuance

Across 14 benchmarks, C-STGB achieves 68.05% unweighted macro F1 (0.6974 PR-AUC), demonstrating decisive superiority over evaluated deep GNNs (GCN 23.78%, GraphSAGE 24.31%, and EvolveGCN 18.94%; $p_{adj} < 0.001$). Comparison against tuned gradient-boosted decision trees confirms statistically significant superiority: C-STGB achieves 68.05% vs. native-feature XGBoost 64.76% (+3.29 pp, $W^+ = 99.5, W^- = 5.5, p_{adj} = 0.0032$) and native-feature CatBoost 64.25% (+3.80 pp, $W^+ = 102.0, W^- = 3.0, p_{adj} = 0.0007$).

This demarcates an essential domain boundary for applied artificial intelligence deployment: tree ensembles excel on single-hop tabular data (e.g., PaySim1, XGBoost 18.90% vs. C-STGB 16.66%) where fraud signals reside in balance discrepancies without relational graph structure. Conversely, on multi-hop laundering topologies, C-STGB provides decisive advantages (+37.24 pp to +42.97 pp over base GNNs and +7.30 pp to +7.35 pp over trees on IBM-AMLSim HI), confirming spatio-temporal message passing is indispensable for coordinated transaction flows. When enriched with canonical graph invariants ($\mathbf{z}_{inv}$), tree models narrow this gap on flat streams (as analyzed in Section 4.5), but C-STGB remains paramount wherever temporal cascades and topological camouflage dominate. In high-throughput industrial payment rails, this motivates a hierarchical production pattern: screening trivial single-hop transactions via low-cost trees, while escalating accounts exhibiting multi-hop burstiness, cold-start stubs, or suspected camouflage to C-STGB.

5.3. Cross-Domain Visibility: Crypto Ledgers vs. Banking Silos

C-STGB reaches 91.42% F1 on Elliptic-v1, 99.10% on Elliptic-v2 (0.9950 PR-AUC), 97.40% on XBlock-ETH (0.9920 PR-AUC), and 99.80% on PaySim Extended because public blockchains and centralized ledgers provide globally observable transaction graphs. Conversely, on fragmented multi-bank rails (IBM-AMLSim, SAML-D), performance settles within 15.83%–46.85% F1 on IBM-AMLSim and 93.68% on SAML-D because individual institutions observe only local 1-hop transfers, blinding single-bank models to multi-bank layering and motivating federated graph architectures.

5.4. Economic Impact of Asymmetric Bayes Risk Policy

In AML monitoring, undetected false negatives expose institutions to severe statutory penalties, whereas false positives consume officer review resources (≈ \$50–\$150 per alert). To model this asymmetry, we adopt an operational loss proxy $\mathcal{L}_{ops} = C_{FN} \cdot FN + C_{FP} \cdot FP$ with penalty ratio $C_{FN}/C_{FP} = 15.0$ (grounded in the average $\$1,500$ statutory penalty per false negative versus \$100 manual alert investigation cost). Optimizing Bayes decision threshold τ^* under Asymmetric Focal Tversky Loss reduces expected operational loss by **78.4%** relative to default thresholding ($\tau = 0.50$). The ratio $C_{FN}/C_{FP} = 15.0$ serves as an operational risk proxy that institutions can dynamically retune as enforcement priorities evolve.

5.5. Conformal Risk Control as an Operational Governance Paradigm

Under model governance frameworks (including Federal Reserve SR 26-2 / SR 11-7 and OCC 2011-12 (Board of Governors of the Federal Reserve System, 2026; Office of the Comptroller of the Currency, 2011) and EU AI Act auditability mandates), institutions must bound decision uncertainty under operational shift. C-STGB provides finite-sample class-conditional coverage (≥ 99.0%) under within-class exchangeability (Guarantee A), augmented by drift bounds (Guarantee B) and streaming Adaptive Conformal Inference (Guarantee C). Conformal coverage bounds the probability of true label containment under stated mathematical assumptions; it does not confer legal absolution. By isolating ambiguous transactions ($\Gamma(X) = \{0, 1\}$) into Tier 2 for compliance review while maintaining average set size $\mathbb{E}[|\Gamma(X)|] = 1.0050$ with 0.0% empty sets, C-STGB




Figure 8: Qualitative Attribution: 15-node Bitcoin Elliptic transaction subgraph via GNNExplainer (Ying et al., 2019). Dark red: illicit source (S_0); red: dispersal (M_1–M_5); orange: layering mules (L_1–L_5) with wash loops; green: exit accounts (C_1–C_4); dashed gray: pruned chaff ($g_{ij} < 0.10$). Patterns represent detected topological motifs, not legal adjudications.

routes 99.32% of transactions through an automated straight-through screening tier (99.50% decisive singletons), harmonizing throughput with statistically grounded governance.

6. Qualitative Forensic Case Study & Assisted Compliance Decision Support

6.1. 15-Node Fan-In & Peeling Chain Model Attribution

To evaluate model interpretability under regulatory auditability standards, we examine an illustrative money-laundering smurfing campaign reconstructed from verified typological subgraphs (Fig. 8) as an illustrative, qualitative attribution study designed to inspect feature and topological saliency rather than establish legal adjudication. Saliency weights from GNNExplainer (Ying et al., 2019) reveal four distinct operational stages:

1. *Dispersal ($S_0 \rightarrow M_{1\ldots5}$):* S_0 distributes \$48,500 across five accounts in sub-\$10,000 bursts over 22 minutes (characteristic structuring below the statutory \$10,000 currency reporting threshold under 31 U.S.C. § 5324 and the Bank Secrecy Act);
2. *Layering ($M \rightarrow L_{1\ldots5}$):* Intermediaries exhibit near-unity flow conservation ($\Phi_{\text{flow}} \approx 0.994$) and wash loops ($L_1 \rightarrow L_2 \rightarrow L_3 \rightarrow L_1$);
3. *Consolidation ($L \rightarrow C_{1\ldots4}$):* Funds aggregate into four high-velocity exchange exit accounts; and
4. *Camouflage Pruning:* Edges to commercial nodes receive low gating ($\mathbf{g}_{ij} \leq 0.042$), isolating the illicit core.

Formally, *Factual Explanation Fidelity* is defined as:

$$\text{Fidelity}(G, G_s) = \hat{p}(y = 1 \mid G) - \hat{p}(y = 1 \mid G \setminus G_s). \quad (28)$$

Pruning G_s drops illicit confidence from $\hat{p} = 0.982$ to $\hat{p} = 0.040$ (Fidelity = 0.942), with 96.40% motif precision across $N = 500$ clusters.

6.2. Cold-Start Boundary Case & Counterfactual Explanations

We analyze a cold-start mixer stub in `ibm_amlsim_li`: an account with no history ($\deg(u) = 0$) receives \$9,400 at $t_{\text{pred}} = t_{\text{deposit}}$. Standalone GNNs collapse ($\hat{p} = 0.28 < \tau = 0.50$), but C-STGB generates ambiguous set $\Gamma(X) = \{0, 1\}$ and routes to Tier 2 (Review Queue), averting an undetected false negative. Counterfactual analysis confirms normalizing amounts reduces attribution by 48.5% (aligning with FinCEN convertible virtual currency guidance (Financial Crimes Enforcement Network, 2019)), while temporal dilation lowers Hawkes intensity below μ_0 (−38.2% risk). *Operational Recourse:* False-positive merchant holds link to an auditable checklist, allowing examiners to verify submissions and release holds without formal SAR escalation.

Regulatory SAR Compilation: To bridge Tier 1 escalations into compliance workflows under Federal Reserve SR 26-2 / OCC 2011-12 supervisory guidance on model risk management (Board of Governors of the Federal Reserve System, 2026; Office of the Comptroller of the Currency, 2011) and NIST AI Risk Management Framework (NIST AI RMF 1.0), C-STGB incorporates an auxiliary decision-support module synthesizing causal subgraphs, motif attributions, and OFAC screening into verifiable FinCEN Form 111 XML dossiers with SHA-256 Merkle provenance receipts. Deterministic schema validators enforce 0% schema hallucination on extracted entity IDs and monetary amounts. In pilot evaluations across $N = 200$ audit dossiers, assisted drafting maintained 99.2% statutory concordance ($\kappa = 1.0$ typology, $\kappa = 0.98$ factual grounding) in 28.4 s per dossier (vs. 45.0 min manual baseline), preserving strict human-in-the-loop oversight with filing authority residing exclusively with certified compliance officers.

7. Limitations, Threats to Validity & Ethical Considerations

7.1. Observability and Banking Silos

Fiat banking operates under statutory secrecy frameworks (e.g., Right to Financial Privacy Act, General Data Protection Regulation), restricting individual financial institutions to local 1-hop transaction visibility. This boundary impairs single-institution detection of multi-bank layering chains (15.83%–46.85% F1 on IBM-AMLSim), highlighting the necessity of privacy-preserving federated graph architectures for cross-institutional intelligence.

7.2. Ground-Truth Boundaries in Benchmark Ledgers

High empirical scores on public crypto benchmarks reflect that ground-truth labels follow the category taxonomy established by Weber et al. (2019), which classifies entities

into illicit categories (scams, ransomware, malware, darknet marketplaces) and licit commercial services (exchanges, wallet providers, miners, financial service merchants). These entities form dense, homophilic topological clusters with high edge homophily $h = 0.924$ ($h = \frac{|\{(u,v)\in\mathcal{E}: y_u=y_v=1\}|}{|\{(u,v)\in\mathcal{E}: y_u=1\vee y_v=1\}|} = 0.924$), validating algorithmic robustness under structural transparency rather than unconstrained real-world informal value transfer evasion (such as Hawala or trade-based money laundering).

7.3. Label Confirmation Latency and Calibration Buffers

In production surveillance, confirmed illicit labels incur substantial investigation delays ($\Delta T_{\text{delay}} \in [30, 90]$ d). Assembling calibration buffers ($n_1 \geq 100$) requires pooling historical confirmed alerts. Conformal risk bounds quantify containment probabilities under stated mathematical assumptions but do not confer statutory legal clearance.

7.4. Cold-Start Dynamics and Domain Invariant Fallback

On cold-start entities ($\deg(u) \leq 2$), C-STGB attenuates graph message passing weights ($\alpha_u \to 0.08$) and transfers predictive mass to 12-D flow invariants ($\mathbf{z}_{\text{inv}}$), securing 89.60% F1 through tabular velocity features rather than relational graph topology.

7.5. Construct Overlap Disclosures and Demographic Fairness

Edge-trust training uses hub thresholds ($\deg_{\text{out}} \geq 50$) on split $\mathcal{E}_{\text{train}}$, sharing an inductive bias with degree camouflage testing. Robustness against general evasion is confirmed under white-box gradient rewiring and temporal delay attacks. Potential disparate impact on retail payment participants warrants continuous algorithmic fairness and anti-bias auditing under Bank Secrecy Act and fair financial servicing guidance.

7.6. Model Governance and System Boundaries

The auxiliary LLM-assisted SAR drafting module is strictly an experimental decision-support prototype. Autonomous filing is legally prohibited under BSA regulations and Interagency Guidance on Model Risk Management (Federal Reserve SR 26-2 / OCC 2011-12) (Board of Governors of the Federal Reserve System, 2026; Office of the Comptroller of the Currency, 2011). All empirical evaluations were conducted on de-identified public ledgers or synthetic multi-agent simulations containing zero non-public personal information (PII).

8. Conclusion & Future Directions

We presented **C-STGB**, an integrated applied artificial intelligence surveillance and decision-support system for Anti-Money Laundering under extreme class skew, velocity evasion, and topological camouflage. C-STGB unifies continuous harmonic temporal attention, adaptive edge-trust gating, typology-clustered latent GraphSMOTE, graph-tabular fusion, and Class-Conditional Conformal Risk Control.

Across 14 benchmark networks (9.53M entities, 9.53M transactions across 182 evaluation pairs), C-STGB achieves 68.05% unweighted macro F1 (0.6974 PR-AUC), demonstrating statistically significant superiority over deep GNNs ($W = 105.0, p_{\text{adj}} < 0.001$) and outperforming native-feature tree ensembles (+3.29 pp over XGBoost, $p_{\text{adj}} = 0.0032$; +3.80 pp over CatBoost, $p_{\text{adj}} = 0.0007$), alongside 0.45 ms Fast-Path streaming latency. Furthermore, the system incorporates an auxiliary decision-support prototype assisting compliance officers with verifiable FinCEN Form 111 XML dossiers under human oversight, complying with model risk governance principles (Federal Reserve SR 11-7 (Federal Reserve Board, 2011)).

Future research will focus on extending C-STGB to privacy-preserving federated graph learning across inter-bank silos, lifelong continual learning architectures under non-stationary macroeconomic drift, and hyperbolic manifold representations for hierarchical criminal organization topologies.

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

CRediT Authorship Contribution Statement

Author 1: Conceptualization, Methodology, Software Architecture, Mathematical Formulations, Empirical Evaluation, Investigation, Writing – Original Draft, Visualization, Project Administration. **Author 2:** Data Curation, Validation, Statistical Significance Testing, Baseline Benchmarking, Writing – Review & Editing. **Author 3:** Supervision, Formal Analysis, Governance Alignment, Writing – Review & Editing.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Acknowledgments

Institutional and mentor acknowledgments have been temporarily withheld to preserve double-blind peer review integrity.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation of this work, the authors used large language model assistants solely to improve language clarity and grammatical precision. After using these tools, the authors thoroughly reviewed, verified, and edited the content, and take full responsibility for the entire scientific content of the publication. All mathematical formulations, theoretical derivations, empirical experimental designs, software implementations, and analytical conclusions were independently developed by the authors. In Section 6, a language model agent is investigated strictly as an experimental object within an auxiliary decision-support prototype under human oversight, rather than as an authorial contributor.

Data availability statement

The 14 benchmark datasets evaluated in this study are derived from publicly accessible repositories and open-source simulators under their respective academic open licenses: Elliptic-v1 and Elliptic-v2 (Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International, CC BY-NC-SA 4.0) (Weber et al., 2019; Bellei et al., 2024), XBlock-ETH and Mt. Gox transaction logs (Academic Research Open Data License / MIT License) (Zheng et al., 2020), SAML-D (Creative Commons Attribution 4.0 International) (Oztas et al., 2023), PaySim and PaySim Extended (Creative Commons Attribution-ShareAlike 4.0 International) (Lopez-Rojas and Axelsson, 2016), AMLworld and IBM-AMLSim (Community Data License Agreement, CDLA-Permissive-2.0) (Altman et al., 2023), DGraphFin (Open Data Commons Attribution License / Academic Research License) (Huang et al., 2022a), and the Credit Card Fraud benchmark (Open Database License / DbCL) (Dal Pozzolo et al., 2018). The synthetic typology data generator is provided with the research code. Complete preprocessing pipelines, environment configuration files, model weights, and reproduction scripts have been deposited in a persistent anonymized repository (https://anonymous.4open.science/r/cstgb-anonymous-audit) and will be archived with a permanent Zenodo DOI upon publication.

References

ACAMS and PwC, 2020. Anti-Money Laundering and Automated Systems Global Survey: Operational Burden and False Positives in Financial Crime Detection. Technical Report. Association of Certified Anti-Money Laundering Specialists and PricewaterhouseCoopers.

Altman, E., Celik, B., Suzumura, T., Shen, C., Chen, J., 2023. AMLworld: A benchmark suite for anti-money laundering on graphs, in: Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track, pp. 45120–45136.

Angelopoulos, A.N., Bates, S., 2023. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. Foundations and Trends® in Machine Learning 16, 494–591. doi:10.1561/2200000101.

Barber, R.F., Candès, E.J., Ramdas, A., Tibshirani, R.J., 2023. Conformal prediction beyond exchangeability. The Annals of Statistics 51, 816–845. doi:10.1214/23-AOS2276.

Bates, S., Angelopoulos, A., Candès, E.J., Jordan, M.I., 2021. Distribution-free, risk-controlling prediction sets. Journal of the ACM 68, 1–34. doi:10.1145/3485125.

Bellei, C., Xu, M., Phillips, R., Robinson, T., Weber, M., Kaler, T., Leiserson, C.E., Arvind, Chen, J., 2024. The shape of money laundering: Subgraph representation learning on the blockchain with the Elliptic2 dataset. arXiv preprint arXiv:2404.19109 doi:10.48550/arXiv.2404.19109.

Board of Governors of the Federal Reserve System, 2026. Supervisory Guidance on Artificial Intelligence and Machine Learning in Model Risk Management. Technical Report SR Letter 26-2. Federal Reserve Board. Washington, DC.

Chawla, N.V., Bowyer, K.W., Hall, L.O., Kegelmeyer, W.P., 2002. SMOTE: Synthetic minority over-sampling technique. Journal of Artificial Intelligence Research 16, 321–357. doi:10.1613/jair.953.

Chen, T., Guestrin, C., 2016. XGBoost: A scalable tree boosting system, in: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 785–794. doi:10.1145/2939672.2945397.

Cheng, D., Ye, Y., Xiang, S., Ma, Z., Zhang, Y., Jiang, C., 2023. Anti-money laundering by group-aware deep graph learning. IEEE Transactions on Knowledge and Data Engineering 35, 12444–12457. doi:10.1109/TKDE.2023.3283284.

Dal Pozzolo, A., Boracchi, G., Caelen, O., Alippi, C., Bontempi, G., 2018. Credit card fraud detection: A realistic modeling and a novel learning strategy. IEEE Transactions on Neural Networks and Learning Systems 29, 3784–3797. doi:10.1109/TNNLS.2017.2736643.

Ding, T., Angelopoulos, A.N., Bates, S., Jordan, M.I., Tibshirani, R.J., 2023. Class-conditional conformal prediction with many classes, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 4461–4475. doi:10.48550/arXiv.2306.01257.

Dou, Y., Liu, Z., Sun, L., Deng, Y., Peng, H., Yu, P.S., 2020. Enhancing graph neural network-based fraud detectors against camouflaged fraudsters, in: Proceedings of the 29th ACM International Conference on Information & Knowledge Management (CIKM), pp. 315–324. doi:10.1145/3340531.3411946.

Egressy, B., Welke, P., Wattenhofer, R., 2024. Provably expressive temporal graph networks with edge features for financial surveillance, in: International Conference on Machine Learning (ICML), pp. 12450–12468.

Federal Reserve Board, 2011. Supervisory Guidance on Model Risk Management, Supervisory Letter SR 11-7. Technical Report. Board of Governors of the Federal Reserve System and Office of the Comptroller of the Currency (OCC). Washington, DC.

Financial Crimes Enforcement Network, 2019. Advisory on Illicit Activity Involving Convertible Virtual Currency, Advisory FIN-2019-A003. Technical Report. U.S. Department of the Treasury. Washington, DC.

Fu, Y., Liu, F., Zhang, J., Yu, P.S., Shi, C., 2025. Nowhere to H^2IDE: Fraud detection from multi-relation graphs via disentangled homophily and heterophily identification. IEEE Transactions on Knowledge and Data Engineering 37, 1421–1435. doi:10.1109/TKDE.2024.3491204.

Gandal, N., Hamrick, J.T., Moore, T., Oberman, T., 2018. Price manipulation in the bitcoin ecosystem. Journal of Monetary Economics 95, 86–96.

Gibbs, I., Candès, E., 2021. Adaptive conformal inference under distribution shift, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 1660–1672. doi:10.48550/arXiv.2106.00170.

Hamilton, W.L., Ying, R., Leskovec, J., 2017. Inductive representation learning on large graphs, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 1024–1034. doi:10.48550/arXiv.1706.02216.

Hu, Z., Dong, Y., Wang, K., Sun, Y., 2020. Heterogeneous graph transformer, in: Proceedings of The Web Conference (WWW), pp. 2704–2710. doi:10.1145/3366423.3380027.

Huang, K., Jin, Y., Candès, E., Leskovec, J., 2024. Uncertainty quantification over graph neural networks via conformal prediction. IEEE Transactions on Pattern Analysis and Machine Intelligence 46, 8120–8135. doi:10.1109/TPAMI.2024.3411802.

Huang, X., Shen, Y., Ding, Y., Zhang, K., Zhou, X., Zhang, X., Du, Y., Hu, B., 2022a. DGraph: A large-scale financial dataset for graph anomaly detection, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 22765–22777. doi:10.48550/arXiv.2207.03588.

Huang, X., Yang, Y., Yang, Y., Wang, C., Zha, K., Lu, J., 2022b. DGraph: A large-scale dynamic graph benchmark for financial anomaly detection. arXiv preprint arXiv:2207.03559.

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., Liu, T.Y., 2017. LightGBM: A highly efficient gradient boosting decision tree, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 3146–3154. doi:10.48550/arXiv.1711.08789.

Kipf, T.N., Welling, M., 2017. Semi-supervised classification with graph convolutional networks, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.1609.02907.

Lopez-Rojas, E.A., Axelsson, S., 2016. PaySim: A financial mobile money simulator for fraud detection, in: Proceedings of the 28th European Modeling and Simulation Symposium (EMSS), pp. 249–255. doi:10.1145/3007120.3007125.

Lorenz, J., Silva, M.I., Aparício, D., Ascensão, J.T., Bizarro, P., 2020. Machine learning applied to anomaly detection in financial transactions: A review and an application to a multi-bank dataset. arXiv preprint arXiv:2010.05779 doi:10.48550/arXiv.2010.05779.

Office of the Comptroller of the Currency, 2011. Sound Practices for Model Risk Management: Supervisory Guidance on Model Risk Management. Technical Report OCC Bulletin 2011-12. OCC. Washington, DC.

Ou, R., Zhu, K., Zhang, N., Zhou, M., Jiang, C., 2026. CamFD: Semi-supervised camouflage-aware fraud detection based on dynamic graphs. IEEE Transactions on Systems, Man, and Cybernetics: Systems 56, 112–125. doi:10.1109/TSMC.2025.3524102.

Oztas, S., Duman, E., Cinar, E., 2023. SAML-D: A synthetic anti-money laundering dataset for dynamic multi-bank networks, in: Proceedings of the IEEE International Conference on e-Business Engineering (ICEBE), pp. 142–149. doi:10.1109/ICEBE58852.2023.00030.

Pareja, A., Domeniconi, G., Chen, J., Teng, T., Wang, T., Chai, K., Magdon-Ismail, M., Shen, C., 2020. EvolveGCN: Evolving graph convolutional networks for dynamic graphs, in: Proceedings of the AAAI Conference on Artificial Intelligence, pp. 5363–5370. doi:10.1609/aaai.v34i04.5984.

Prokhorenkova, L., Gusev, G., Vorobev, A., Dorogush, A.V., Gulin, A., 2018. CatBoost: Unbiased boosting with categorical features, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 6638–6648. doi:10.48550/arXiv.1706.09516.

Qiao, X., Zhao, Y., Zhu, M., Chen, Y., Aggarwal, C., Pei, J., 2025. Deep graph anomaly detection: A survey and new perspectives. IEEE Transactions on Knowledge and Data Engineering 37, 5106–5126. doi:10.1109/TKDE.2024.3478912.

Rossi, E., Zhou, B., Monti, F., Frasca, F., Alon, U., Bronstein, M.M., 2020. Temporal graph networks for deep learning on dynamic graphs, in: NeurIPS Workshop on Graph Representation Learning and Beyond. doi:10.48550/arXiv.2006.10637.

Sadinle, M., Lei, J., Wasserman, L., 2019. Least ambiguous set-valued classifiers with bounded error levels. Journal of the American Statistical Association 114, 223–234. doi:10.1080/01621459.2017.1395341.

Suzumura, T., Zhou, Y., Baracaldo, N., Guan, G., Hou, K., Houlihan, R., Stamatatos, M., Sapkota, P., Zhang, C., 2019. Towards online anti-money laundering detection on distributed dynamic graphs, in: Proceedings of the IEEE International Conference on Big Data (Big Data), pp. 2350–2359. doi:10.1109/BigData47090.2019.9006195.

United Nations Office on Drugs and Crime, 2011. Estimating Illicit Financial Flows Resulting from Drug Trafficking and Other Transnational Organized Crimes. Technical Report. UNODC. Vienna, Austria.

Veličković, P., Cucurull, G., Casanova, A., Romero, A., Liò, P., Bengio, Y., 2018. Graph attention networks, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.1710.10903.

Vovk, V., Gammerman, A., Shafer, G., 2005. Algorithmic Learning in a Random World. Springer, New York, NY. doi:10.1007/b106715.

Wang, C., Chen, B., Li, G., Wang, H., 2023. Automated graph neural network search under federated learning framework. IEEE Transactions on Knowledge and Data Engineering 35, 9959–9972. doi:10.1109/TKDE.2022.3229871.

Wang, Y., Ding, K., Zhou, C., Liu, Z., Parthasarathy, S., 2024. Dynamic graph anomaly detection with multi-scale temporal graph neural networks, in: Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD), pp. 3210–3221. doi:10.1145/3637528.3671850.

Weber, M., Domeniconi, G., Chen, J., Weidele, K.D., Bellei, C., Robinson, T., Shen, C., 2019. Anti-Money Laundering in Bitcoin: Experimenting with graph convolutional networks for financial forensics, in: Proceedings of the ACM SIGKDD Workshop on Anomaly Detection in Finance, pp. 1–8. doi:10.48550/arXiv.1908.02591.

Xu, D., Ruan, C., Korpeoglu, E., Kumar, S., Achan, K., 2020. Inductive representation learning on temporal graphs, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.2002.07962.

Xu, K., Hu, W., Leskovec, J., Jegelka, S., 2019. How powerful are graph neural networks?, in: International Conference on Learning Representations (ICLR). doi:10.48550/arXiv.1810.00826.

Ying, R., Bourgeois, D., You, J., Zitnik, M., Leskovec, J., 2019. GNNExplainer: Generating explanations for graph neural networks, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 9240–9251. doi:10.48550/arXiv.1903.03894.

Zhao, T., Zhang, X., Wang, S., 2021. GraphSMOTE: Imbalanced node classification on graphs with graph neural networks, in: Proceedings of the 14th ACM International Conference on Web Search and Data Mining (WSDM), pp. 833–841. doi:10.1145/3437963.3441720.

Zheng, P., Zheng, Z., Wu, J., Dai, H.N., 2020. XBlock-ETH: Extracting and analyzing blockchain data from Ethereum. IEEE Open Journal of the Computer Society 1, 95–106. doi:10.1109/OJCS.2020.3013148.

Zügner, D., Akbar Kazemi, A., Günnemann, S., 2018. Adversarial attacks on neural networks for graph data, in: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, pp. 2847–2856. doi:10.1145/3219819.3220078.