

DR-4308P



- Total incoming throughput 270Mbps
- Up to 240ips Full HD real-time recording
- Supports H.265 / H.264 codec
- Supports UHD display
- Up to 240ips live display
- Easy to install, set-up and play with DirectIP cameras
- Built-in 8 channel PoE Switch
- Expandable up to 72TB using eSATA storage
- Supports one click network configuration through FEN service
- Supports third-party cameras (Axis, Panasonic, ONVIF)



SPECIFICATIONS

VIDEO	
Video Inputs	8 IP channels
Max. Incoming Throughput	270Mbps
Supported Camera	DirectIP, Axis, Panasonic, ONVIF
Video Outputs	1 HDMI, 1 VGA
Display Resolution	3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 240ips
Digital Zoom	x2 ~ x12
RECORDING	
Max. Throughput	140Mbps, 240ips@UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)
Compression	H.265, H.264
Intelligent Codec	Supported
Recording Mode	Time-lapse, Event, Pre-event, Panic
Trigger Events	Alarm In, Audio Detection, Motion Detection, Trip Zone, Tampering, Video Loss, Text-in, ANPR, Etc.
PLAYBACK	
Performance	8ch Full HD Synchronous Playback 4ch 4K Playback
Search Mode	Time-lapse, Event Log, Thumbnail, Motion, Text-in
Digital Zoom	x2 ~ x12
STORAGE	
HDD	SATA x4, eSATA x2, (Up to 8TB capacity for each disk)
Total Capacity	96TB = 8TB x (4 + 2 x 4)
NETWORK	
Client Connection	Gigabit Ethernet (Client) x1
Video In Connection	Fast Ethernet (IP Camera) x 8 + Gigabit Ethernet(Ext) x 1
Transmission Speed	50Mbps / 100Mbps(BRP Mode)
Camera Power	PoE(IEEE 802.3at class 4) Supported 8 ports, 120W
Remote Data Export	IDIS Player, AVI, JPG
Event Notification	Email (Attach Clip (.cbf) .MP4), Callback to Remote S/W, Push Notification (IDIS Mobile), SNS (Twitter)
Two-way Audio	Yes (NVR ↔ Camera, iRAS ↔ Camera)
Client Viewer	IDIS Center, IDIS Mobile, IDIS Web, IDIS Solution Suite
INTERFACE	
Audio In / Out	Local (NVR) : 1 RCA / 1 RCA + 1HDMI IP Camera : 8 / 8 (Depending on IP Camera)
Alarm In / Out	Local(NVR) : 4 / 1 IP Camera : 8 / 8 (Depending on IP Camera)
Alarm Reset In	1
Serial Interface	RS232 (Terminal Block)
USB	USB 2.0 x 1, USB 3.0 x 1
User Interface	Mouse, IR Remote Control, Network Remote Keyboard
GENERAL	
Operating System	Embedded Linux
Unit Dimensions (W x H x D)	430mm x 88mm x 410.8mm (16.9" x 3.5" x 16.2")
Unit Weight	6.0kg (13.2lb) (with 1 HDD)
Working Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Power Input	AC 100-240 V, 50/60Hz, 3.0 - 1.5A
Power Consumption	Max. 200W (With 4 HDDs)
Approvals	FCC, CE, KC, CB, UL, PSE

DIMENSIONS



- | | | |
|------------------------|------------------------|------------------|
| 1 Factory Reset Button | 7 HDMI Out Port | 13 Power In Port |
| 2 Video In / PoE Ports | 8 Alarm Connection Out | 14 Vent |
| 3 Video In / Ext. Port | 9 Alarm Connection In | |
| 4 Network Port | 10 RS-485 Port | |
| 5 eSATA Port | 11 RS-232 Port | |
| 6 VGA Out Port | 12 Audio Ports | |

ACCESSORIES (OPTIONAL)



DH-2212PF



DA-ES1104