SM-F322



SPECIFICATIONS

PANEL	
Type	LED
Screen Size	32 Inch
Active Display Area	698.40mm(H) x 392.85mm(V)
Max. Resolution	1920 x 1080 @ 60Hz
Panel Technology	IPS(In-Plane Switching)
Anti Glare	Yes
Pixel Pitch	0.36375mm(H) x 0.36375mm(V)
Brightness	250cd/m²
Contrast Ratio	1200:1
Aspect Ratio	16:9
Viewing Angle(H/V)	178°/178°
Display Color	16.7 Millions
H-Scanning Frequency	30~80Khz
V-Scanning Frequency	50~75Khz
Response Time (G2G)	<6.5ms
Refresh Rate	60Hz
Panel Life Time	50,000Hours
INTERFACE	
Hybrid(AHD,TVI,CVI,CVBS) In/Out	1/1
HDMI In	1
Display Port	-
VGA Input	1
DVI Input	-
Audio In/Out	1/1
BNC Video In/Out	1/1
S-Video In/Out	-
Component Y/pb/Pr In	-
S/PIDF Output	-
RS232 In/Out	-
USB	1
GENERAL	
Outline Dimension(WxHXD)	741.2mmx472.9mmx180.0 mm (29.18"x18.62"x7.09")
Bezel width (Spec. for VideoWall)	-
Net Weight/Gross Weight	12.5Kg(27.56lb)/15.6Kg(34.4lb)
Material/Color	Metal / Black
Warranty-Parts/Labor	3 Year / 3 Year
MTBF	50,000 Hours(Panel)
Power Supply	AC100~240V(50/60Hz)
Power Consumption - Typical	50W
Power Consumption - Stand by	<0.5W
Power Savings(DPMS)	Yes
Operating Temperature	-10°~50°C(14°F~122°F)
Storange Temperature	-20°~60°C(-4°F~140°F)
Built-In Speaker	Yes(5Wx2)
Remote Control	Yes
VESA Mount Size	200mm x 200mm / M6 x 10 Screws
Operation Hours	24/7
Prevent Burn-In	Yes
OPTIONS	
Android Board	-
OPS	-
EXTERNAL CONTROLS	
IR Sensor(For Remote Control)	Built-In
Serial In/Out	-
USB	For Firmware Update

DIMENSIONS

(Unit - mm)