

Open API

MagicINFO Server allows you to implement content management, schedule management, device management, and such by calling Open API (v2.0).

To use Open API (v2.0), you will first need to go through an authentication process. Use a separate swagger page to test each API.

Authentication

When calling all Open API (v2.0) items, api_token must be included in the header. If this is not included, a "401 Unauthorized." error is returned.

An obtained token expires and becomes unavailable for use after a specified period of time. If this is the case, you should obtain a new token.

api_token can be obtained by calling the following api.

Service Name	API call	Call Type	Description
authenticationRequest	/auth	POST	Imports a token value for authentication using the user ID and password.
authenticationRequest	/auth /refresh	GET	Creates a new token to extend the expire time. It is possible to call REST API without logging in again

OPEN API (v2.0)

MagicINFO Server Open API (v2.0) provides a variety of functions. Configuration of each function is shown below.

Category	Controller	Description
Content	content-controller	Content file management
	content-group-controller	Content group management
Playlist	playlist-controller	Managing Playlists
	playlist-group-controller	Playlist group management
Schedule	content-schedule-controller	Content schedule management
	content-schedule-group-controller	Content schedule group management
	message-schedule-controller	Managing Message Schedules
	message-schedule-group-controller	Message schedule group management
Device	device-controller	Device management
	device-group-controller	Device group management
User	user-controller	User management
	user-group-controller	User group management
Setting	environment-controller	Setting

Content

Upload, approve, or delete content. Manage content lists. Content-related services are accessible to authenticated users with privileges to read, write, and manage content.

Available content management services are as follows:

Service Name	API call	Call Type	Description
listAllContent	/restapi/v1.0/cms/contents	GET	Imports a list of uploaded content. Content thumbnails, names, file types, and other basic information are included in the list. Lists can be imported per page, using paging information.
listDashboardContentInfo	/restapi/v1.0/cms/contents/dashboard	GET	Imports general content information to be displayed on the dashboard.
listContent	/restapi/v1.0/cms/contents/filter	POST	Imports a list of content filtered based on conditions. Lists can be imported per page, using paging information.
forcedDeleteContent	/restapi/v1.0/cms/contents/force/{contentId}	DELETE	Deletes content, whether or not the content is included in a playlist or schedule.
deleteContent	/restapi/v1.0/cms/contents/{contentId}	DELETE	Deletes content after checking that the content is not included in a playlist or schedule. If attempting to delete content included in a playlist or schedule, the content will not be deleted and an error code will be returned.
getActiveContentInfo	/restapi/v1.0/cms/contents/{contentId}	GET	Whenever content is modified, its version is updated. The active version of content details is fetched.
approveContents	/restapi/v1.0/cms/contents/{contentId}/approval	PUT	Approves/rejects content. Approved content is moved to the general content list and can be used in playlists or schedules.

upload Content	/restapi/v1. 0/cms /contents/ {groupId}	POST	Uploads new content.
listDe faultG roup	/restapi/v1. 0/cms /contents /groups	GET	Imports a list of default content groups.
getGro up	/restapi/v1. 0/cms /contents /groups/ {groupId}	GET	Fetches details of the {groupId} group.
listCh ildGro up	/restapi/v1. 0/cms /contents /groups/ {groupId} /child	GET	Fetches a list of sub groups under the {groupId} group.

Playlist

Use content to create, edit, or delete playlists. Playlist-related services are accessible to authenticated users with privileges to read, write, and manage content.

Available playlist management services are as follows:

Service Name	API call	Call Type	Description
listAllPlaylists	/restapi/v1.0 /cms/playlists	GET	Imports a list of all playlists. Playlist names, main content thumbnails, playlist types, and other basic information are included in the list. Lists can be imported per page, using paging information.
createPlaylist	/restapi/v1.0 /cms/playlists	POST	Creates a new playlist.
getDashboardPlaylistInfo	/restapi/v1.0 /cms/playlists /dashboard	GET	Imports necessary playlist information from the dashboard.
listPlaylist	/restapi/v1.0 /cms/playlists /filter	POST	Imports a list of playlists filtered based on conditions. Lists can be imported per page, using paging information.
deletePlaylist	/restapi/v1.0 /cms /playlists/ {playlistId}	DELETE	Deletes the selected playlist. If attempting to delete a playlist included in a schedule, the playlist will not be deleted and an error code will be returned.
getActivePlaylistInfo	/restapi/v1.0 /cms /playlists/ {playlistId}	GET	Imports details of an activated version of a playlist. The version of a playlist is updated each time the playlist is edited.
editPlaylist	/restapi/v1.0 /cms /playlists/ {playlistId}	PUT	Modifies the {playlistId} playlist. Editing a playlist updates the playlist version, and causes the device playing the playlist to automatically play the updated playlist.

copyPlaylist	/restapi/v1.0 /cms /playlists/ {playlistId} /copy	PUT	Copies the {playlistId} playlist. A duplicate copy of the playlist is created.
listDefaultGroup	/restapi/v1.0 /cms/playlists /groups	GET	Imports a list of default playlist groups.
getGroup	/restapi/v1.0 /cms/playlists /groups/ {groupId}	GET	Fetches details of the {groupId} group.
listChildGroup	/restapi/v1.0 /cms/playlists /groups/ {groupId} /child	GET	Fetches a list of sub groups under the {groupId} group.

Schedule

Create new content or message schedules. Publish schedules to devices for playback. Edit or delete schedules.

Schedule-related services are accessible to authenticated users with privileges to read, write, and manage schedules.

Available schedule management services are as follows:

Service Name	API call	Call Type	Description
listContentsScheduleAll	/restapi/v1.0/dms/schedule/contents	GET	Imports a list of all content schedules. Content schedule names, dates of creation, device types, and other basic information are included in the list. Lists can be imported per page, using paging information.
createContentSchedule	/restapi/v1.0/dms/schedule/contents	POST	Creates a new content schedule. A content schedule may contain multiple channels and frames. Publish a schedule to devices and play the desired content or playlist at a specified time.
listDashboardScheduleInfo	/restapi/v1.0/dms/schedule/contents/dashboard	GET	Imports necessary content schedule information from the dashboard.
listContentsScheduleByGroup	/restapi/v1.0/dms/schedule/contents/filter	POST	Imports a list of content schedules filtered based on different conditions. Lists can be imported per page, using paging information.
deleteContentSchedule	/restapi/v1.0/dms/schedule/contents/{programId}	DELETE	Deletes a content schedule. If deleting a schedule previously published to a device, the device automatically plays the default content.
getProgramInfo	/restapi/v1.0/dms/schedule/contents/{programId}	GET	Imports details of the selected schedule.

editContentsSchedule	/restapi/v1.0 /dms/schedule /contents/ {programId}	PUT	Edits a content schedule. If editing a schedule previously published to a device, the device automatically plays the edited schedule.
copyContentsSchedule	/restapi/v1.0 /dms/schedule /contents/ {programId}/copy	PUT	Copies the {programId} content schedule. The content schedule such as {programId} is newly created.
deployContentSchedule	/restapi/v1.0 /dms/schedule /contents/ {programId} /deploy	PUT	Publishes a content schedule to a specific device group.
getPublishStatus	/restapi/v1.0 /dms/schedule /contents/ {programId} /publishStatus	GET	Imports real-time content schedule download status from a device.
getRootGroups	/restapi/v1.0 /dms/schedule /contents/groups	GET	Imports a list of root groups for a content schedule.
listContentsScheduleGroupInfo	/restapi/v1.0 /dms/schedule /contents /groups/ {groupId}	GET	Fetches details of the {groupId} group.
listAllMessageSchedule	/restapi/v1.0 /dms/schedule /messages	GET	Imports a list of all message schedules.
createMessageSchedule	/restapi/v1.0 /dms/schedule /messages	POST	Creates a new message schedule.
listMessage	/restapi/v1.0 /dms/schedule /messages/filter	POST	Imports a list of message schedules filtered based on different conditions. Lists can be imported per page, using paging information.

deleteMessageSchedule	/restapi/v1.0/dms/schedule/messages/{messageId}	DELETE	Deletes the selected message schedule. If deleting a message schedule previously published to a device, the change is automatically applied to the device.
getMessageInfo	/restapi/v1.0/dms/schedule/messages/{messageId}	GET	Imports details of the selected message schedule.
editMessageSchedule	/restapi/v1.0/dms/schedule/messages/{messageId}	PUT	Edits the selected message schedule. If editing a message schedule previously published to a device, the change is automatically applied to the device.
copyMessageSchedule	/restapi/v1.0/dms/schedule/messages/{messageId}/copy	PUT	Copies the selected message schedule. A duplicate copy of the message schedule is created.
deployMessageSchedule	/restapi/v1.0/dms/schedule/messages/{messageId}/deploy	PUT	Publishes the selected message schedule to a device group.
getRootGroups	/restapi/v1.0/dms/schedule/messages/groups	GET	Imports a list of root groups for a content schedule.
listMessageScheduleGroupInfo	/restapi/v1.0/dms/schedule/messages/groups/{groupId}	GET	Fetches details of the {groupId} group.
getChildGroups	/restapi/v1.0/dms/schedule/messages/groups/{groupId}/child	GET	Imports a list of sub-groups under a specific group.

Device

Control and manage devices. Device-related services are accessible to authenticated users with privileges to read, write, and manage devices.

Available device management services are as follows:

Service Name	API call	Call Type	Description
listAllDevice	/restapi/v1.0/rms/devices	GET	Imports a list of all devices. Device power status, thumbnail info, device error status, and other basic information are included in the list. Lists can be imported per page, using paging information.
getDashboardDeviceInfo	/restapi/v1.0/rms/devices/dashboard	GET	Imports necessary device information from the dashboard.
filterDeviceList	/restapi/v1.0/rms/devices/filter	POST	Imports a list of devices filtered based on different conditions. Lists can be imported per page, using paging information.
deleteDevice	/restapi/v1.0/rms/devices/{deviceId}	DELETE	Deletes the selected device.
getDevice	/restapi/v1.0/rms/devices/{deviceId}	GET	Imports details of the selected device.
approveDevice	/restapi/v1.0/rms/devices/{deviceId}/approval	PUT	Approves the selected device to a specific group.
getCabinetList	/restapi/v1.0/rms/devices/{deviceId}/cabinet	POST	Imports information about cabinets connected to an LED device. The imported information is valid only when the cabinets are connected to an LED device.
updateCabinetInfo	/restapi/v1.0/rms/devices/{deviceId}/cabinet	PUT	Edits information about cabinets connected to an LED device.

getDisplayControlInfo	/restapi/v1.0/rms /devices/ {deviceId} /display	GET	Imports device display control information from the database. If control information is not present, an information request should be sent to the device.
updateDisplayInfo	/restapi/v1.0/rms /devices/ {deviceId} /display	PUT	Sends edited display control information to a device. Only edited values in display information are sent as a protocol to the device.
getUpdatedDisplayInfoResult	/restapi/v1.0/rms /devices/ {deviceId} /display/ {requestId}	GET	Receives edited display control information from a device. This API is run after executing the updateDisplayInfo API.
getGeneralInfo	/restapi/v1.0/rms /devices/ {deviceId} /general	GET	Imports general device information from the database. General device information is updated when the device connects to the server.
updateGeneralInfo	/restapi/v1.0/rms /devices/ {deviceId} /general/info	PUT	Sends edited device information to a device. Only edited values in basic device information are sent as a protocol to the device.
getUpdatedGeneralInfoResult	/restapi/v1.0/rms /devices/ {deviceId} /general/ {requestId}	GET	Receives edited device information from a device. This API is run after executing the updateGeneralInfo API.
moveDevice	/restapi/v1.0/rms /devices/ {deviceId}/move	PUT	Moves a device to another group.
startRmServerVnc	/restapi/v1.0/rms /devices/ {deviceId} /rmserver/start	GET	Sends an RM start protocol to a device. A device that received an RM start protocol sends information periodically via the Remote control Server.
stopRmServerVnc	/restapi/v1.0/rms /devices/ {deviceId} /rmserver/stop	GET	Sends an RM stop protocol to a device. A device that received a stop protocol stops the corresponding function immediately.

getSetupInfo	/restapi/v1.0/rms/ /devices/ {deviceId}/setup	GET	Imports device settings. Device settings are updated when the device connects to the server.
updateSetupInfo	/restapi/v1.0/rms/ /devices/ {deviceId}/setup	PUT	Sends edited device settings to a device. Only edited values in settings are sent as a protocol to the device.
getUpdatedSetupInfoResult	/restapi/v1.0/rms/ /devices/ {deviceId}/setup/ {requestId}	GET	Receives edited device settings from a device. This API is run after executing the updateSetupInfo API.
getCurrentStatusDisplay	/restapi/v1.0/rms/ /devices/ {deviceId}/status/ /display	GET	Sends a current display control information request to a device. When calling this API, requestId is returned as the response value.
getCurrentStatusDisplay	/restapi/v1.0/rms/ /devices/ {deviceId}/status/ /display/ {requestId}	GET	Imports display control information sent from a device. This option is used for two actions: sending a request for information to a device and receiving actual device information.
getCurrentStatusTime	/restapi/v1.0/rms/ /devices/ {deviceId}/status/ /time	GET	Sends a current time information request to a device. When calling this API, requestId is returned as the response value.
getCurrentStatusTime	/restapi/v1.0/rms/ /devices/ {deviceId}/status/ /time/{requestId}	GET	Imports time information sent from a device. requestId received by calling getCurrentStatusTime must be sent as a parameter.
getTimeInfo	/restapi/v1.0/rms/ /devices/ {deviceId}/time	GET	Imports device time information from the database. If control information is not present, an information request should be sent to the device.
updateTimeInfo	/restapi/v1.0/rms/ /devices/ {deviceId}/time	PUT	Sends edited time information to a device. Only edited values in time information are sent as a protocol to the device.
getUpdatedTimeInfoResult	/restapi/v1.0/rms/ /devices/ {deviceId}/time/ {requestId}	GET	Receives edited device time information from a device. This API is run after executing the getUpdatedTimeInfoResult API.

listDeviceGroupOrgan	/restapi/v1.0/rms/devices/groups	GET	Imports a list of organizations.
listDeviceGroupInfo	/restapi/v1.0/rms/devices/groups/{groupId}	GET	Fetches details of the {groupId} group.
listDeviceGroupChild	/restapi/v1.0/rms/devices/groups/{groupId}/child	GET	Fetches sub groups under {groupId}.

User

Add users and manage user information. User-related services are accessible to authenticated users with privileges to read, write, and manage user information.

Available user management services are as follows:

Service Name	API call	Call Type	Description
create User	/restapi/v1.0/ums/users	POST	Adds a user.
listDashboardUserInfo	/restapi/v1.0/ums/users/dashboard	GET	Imports necessary user information from the dashboard.
update MyInfo	/restapi/v1.0/ums/users/me	PUT	Edits user information.
listUserOrganization	/restapi/v1.0/ums/users/organization	GET	Imports a list of organizations. This option can be used to configure a group tree.
listUserGroupOrganization	/restapi/v1.0/ums/users/groups	GET	Imports a list of organizations.
listUserGroupInfo	/restapi/v1.0/ums/users/groups/{groupId}	GET	Fetches details of the {groupId} group.
listUserGroupChild	/restapi/v1.0/ums/users/groups/{groupId}/child	GET	Fetches a list of sub groups under the {groupId} group.

Setting

In addition to main functions, you can use many other functions to create and manage tags and categories, and edit the dashboard.

Service Name	API call	Call Type	Description
getCategoryInfo	/restapi/v1.0/ems/category/{categoryId}	GET	Imports a list of categories.
deleteDashboard	/restapi/v1.0/ems/dashboard	DELETE	Deletes specific dashboard information.
listDashboardInfo	/restapi/v1.0/ems/dashboard	GET	Imports content to be displayed on the customized dashboard. It is possible to display only specific information on the dashboard.
updateDashboardPriority	/restapi/v1.0/ems/dashboard	PUT	Changes the order of items displayed on the dashboard.
createDashboard	/restapi/v1.0/ems/dashboard/create	GET	Activates an idle dashboard.
listDashboardLoginInfo	/restapi/v1.0/ems/dashboard/login	GET	Imports login information to be displayed on the dashboard.
listDashboardNoticeInfo	/restapi/v1.0/ems/dashboard/notice	GET	Imports bulletin board information to be displayed on the dashboard.
deleteNoticeInfo	/restapi/v1.0/ems/dashboard/notice/edit	DELETE	Deletes a post from the bulletin board.
listEditNoticeInfo	/restapi/v1.0/ems/dashboard/notice/edit	GET	Imports details of the selected post.

create Notice Info	/restapi/v1.0 /ems/dashboard /notice/edit	POST	Adds posts to the bulletin board.
update Notice Info	/restapi/v1.0 /ems/dashboard /notice/edit	PUT	Edits the selected post on the bulletin board.
listDa shboar dStora geInfo	/restapi/v1.0 /ems/dashboard /storage	GET	Imports storage information to be displayed on the dashboard.
listLi cense	/restapi/v1.0 /ems/license	GET	Imports a list of licenses registered on the server.
getSer verSet upInfo	/restapi/v1.0 /ems/setup	GET	Imports server settings. Server setting items include options that can turn on or off different functions on the server.
getTag ListIn fo	/restapi/v1.0 /ems/tag	POST	Imports a list of tags registered on the server.

Open API Details (swagger UI)

<http://184.169.167.38:7001/MagicInfo/swagger-ui.html>