

# **Gitlab Configuration Details**

Version 1.18-SNAPSHOT

2018-12-11

## **Table of Contents**

1. Introduction	. 2
2. Server configuration	
3. Project creation	. 2
3.1. Configure rebase without merge commit	
3.2. Protect master branch	. 3
3.3. Configure Eclipse	. 4
3.4. Merge Requests workflow	. 4
3.5. Pipeline creation	
4. Troobleshooting	. 7
4.1. I pushed on a deleted branch	. 7
5. Appendix	. 9
5.1. Revision marks	. 9

Table 1. History

Date	Author	Detail
2018-12-11	bcouetil	- Added reveal plugins and background - Fixed reveal css following change in structure in asciidoc-reveal master (from previous version : 1.1.3) - Implemented Zenika layout in HTML and PDF - Reported back reveal-js enhancements
2018-11-28	bcouetil	- Updated reveal css for all syntax elements, for both light and dark themes : asciidoc-syntax-quick-reference is now nicely output - Refactored light and dark css, extracting common items into reveal-zenika.css - Added syntax quick reference in all format generated and linked in asciidoc page
2018-11-02	bcouetil	- reorganized asciidoc best practices - added some Geek & Poke images - reveal.js themes Zenika dark + light + parallax - updated asciidoc/reveal versions in pom.xml
2018-09-19	bcouetil	- Sample asciidoctor maven project published on Github - Github & LinkedIn links - Sample project tree - new images + resizing and positioning
2018-09-05	bcouetil	Minor changes
2018-08-29	bcouetil	Asciidoc HTML look & feel changes
2018-08-24	bcouetil	Reworked asciidoc index.html
2018-08-24	bcouetil	Icones added for download + favicon added for webpage
2018-08-23	bcouetil	Initial commit

#### OLD ADAGES EXPLAINED



WHEN PUSH COMES TO SHOVE

### 1. Introduction

Gitlab in his free online plan offers some nice features :

- 2,000 CI pipeline minutes per group per month on our shared runners
- Unlimited private projects and collaborators
  - Built-in CI/CD
  - Cycle Analytics
  - Issue Boards
  - Time tracking
  - Preview your changes with Review Apps
  - · Publish static websites for free with GitLab Pages
  - Git LFS 2.0 support

## 2. Server configuration



TODO



## 3. Project creation


- Create a project in web interface.
  - · check Create README.md or else master branch is not created

- Import git project in Eclipse
- Change git config, adding:

```
[user]
name = yourname
email = youraccount@yourprovider.com
```

#### 3.1. Configure rebase without merge commit

- In the web interface, go to **Project** → **Settings** → **General** → **Merge request**, and configure as follow:
  - ☑ Fast-forward merge
  - ☑ Only allow merge requests to be merged if the pipeline succeeds
  - ☐ Only allow merge requests to be merged if all discussions are resolved



#### 3.2. Protect master branch

Gitlab workflow is not as straightforward as Gerrit's (see below). In Eclipse, it's too easy to push to master instead of our current Merge Request's branch.

Here is how to protect it:

- In Gitlab interface, navigate to your project → Settings → Repository → expend Protected Branches and configure :
  - Branch = master
  - Allowed to merge = Maintainers
  - Allowed to push = No one


#### When I commit on the wrong project



### 3.3. Configure Eclipse

Clone the repository as you would do for any Git repository, see Eclipse Best Practices for details.





#### 3.4. Merge Requests workflow

We assume that we will be the only one to push on that branch, so we do not check-out the branch, and just push there. This helps do fewer interactions in Eclipse.

- In Gitlab
  - Go to Issues → New issue
  - · Set information and create
  - Click Create merge request
- In Eclipse
  - right click on your repo → Pull
    - The branch should appear under Branches → Remote Tracking
  - In Remotes → origin, right click on the second address and choose Configure Push...
  - Click Add...

Remote branch = <type the number to get the full branch>

☑ Force update

The specification should be something like

```
+HEAD:refs/heads/4-minor-asciidoc-changes
```

Press OK then Save

Eclipse should now be ready to handle smoothly Gitlab workflow. You can check your repository git config which should be like:

#### git/config

```
[core]
    repositoryformatversion = 0
    filemode = false
    logallrefupdates = true
[remote "origin"]
    url = https://gitlab.com/bcouetil/academy.git
    fetch = +refs/heads/*:refs/remotes/origin/*
    push = +HEAD:refs/heads/4-minor-asciidoc-changes
[branch "master"]
    remote = origin
    merge = refs/heads/master
    rebase = true
[user]
    name = myname
    email = myaccount@myprovider.com
```

dev iterations

- The first time
  - Update your files...
  - Go to Git Staging view
  - Stage your files
  - Hit Commit and Push... and Close
- On each new iteration do the same and

change the text if needed



Don't toggle on **Add Change-Id**, this changes the behavior of **Commit and Push...** towards Gerrit style.



More details and screenshots in Eclipse Best Practices


Now a pipeline should be launched in Gitlab interface.

Merge in Gitlab

Browse the Merge Request in Gitlab

☑ Remove source branch

Pull in Eclipse to be up to date



### 3.5. Pipeline creation

#### **Pipeline**

```
image: maven:latest

stages:
    - build
    - test
    - deploy

variables:
    #MAVEN_CLI_OPTS: "-s cg-settings.xml --batch-mode"
    MAVEN_CLI_OPTS: "--batch-mode"
    MAVEN_OPTS: "-Dmaven.repo.local=.m2/repository"

cache:
    paths:
    - .m2/repository/

build:
    stage: build
    script:
```

```
- apt-get update -qq && apt-get install -qq --assume-yes libc6-i386
    - mvn clean dependency:purge-local-repository
    - mvn install -DskipTests -Dassembly.skipAssembly=true -Dadoc.skip=true
# the pipeline step must be named 'pages' for gitlab to deploy locally (in addition to github)
  stage: build
  script:
   #- ./src/scripts/asciidocOnlyModified.sh
   - ./src/scripts/asciidocHistory.sh .
   - apt-get update -qq && apt-get install -qq --assume-yes graphviz
   - git config --global user.email "gitlab@noreply.com"
   - git config --global user.name "GitLab"
    - mkdir public
   #SAMPLE
   mvn -f cg-asciidoctor-sample/pom.xml
   - mv --verbose cg-asciidoctor-sample/src/docs/asciidoc/*.adoc cg-asciidoctor-sample/target/generated-docs/
   - mv --verbose cg-asciidoctor-sample/target/generated-docs public/sample
   - mvn generate-resources --non-recursive
   - mv --verbose src/docs/asciidoc/*.adoc target/generated-docs/
   - mv --verbose src/docs/asciidoc/subdocs target/generated-docs/subdocs
   - mvn scm-publish:publish-scm
    - mv target/generated-docs/* public/
  artifacts:
    paths:
      # nothing else than public folder will work :(
      - public
  #only:
  # - master
unit-test:
 stage: test
  script:
    - mvn test -Dcheckstyle.skip=true -Dadoc.skip=true -pl cg-utils
integration-test:
 stage: test
  script:
   - mvn verify failsafe:verify -Dcg.ut.skip=true -Dcheckstyle.skip=true -Dadoc.skip=true -pl cg-utils
assembly:
 stage: deploy
  script:
   - mvn install -DskipTests -Dcheckstyle.skip=true -Dadoc.skip=true -pl cg-utils
  #onlv:
  # - master
```

## 4. Troobleshooting


### 4.1. I pushed on a deleted branch

If you have accidently pushed on a merged branch, it will be recreated.

You have to:

- Reset mixed on the master
- Configure your push to the good branch

- Push
- Delete the other branch



# 5. Appendix

## 5.1. Revision marks

Differences since last tag