

Nexus3 Configuration Details

Version 1.18-SNAPSHOT

2018-08-22

Table of Contents

1.	Server configuration	. 1
	1.1. URL	. 1
	1.2. Set SNAPSHOT retention	. 1
	1.3. Add a proxy (=remote) repository	. 1
2.	Appendix	. 4
	2.1 Revision marks	4

Date	Author	Detail
2018-08-22	NeVraX	HTML Asciidoc to Github

1. Server configuration



This has to be done only for a new Production Line



The technical account has to be created in CORP and defined in LAM as an administrator

1.1. URL

Repositories, release, snapshot and group, should already be created.

The public repository address can be found there:

- · Click on the wheel
- Repository → Repositories → maven-public
- Get the URL

1.2. Set SNAPSHOT retention



This has to be done only for a new Production Line

- Go to Administration (wheel) \rightarrow System \rightarrow Tasks \rightarrow Create task
- Type = Remove Snapshots From Maven Repository
- Fields
 - Name = Delete old snapshots
 - Repository = (All Repositories)
 - Minimum snapshot count = 5
 - Snapshot retention (days) = 7
 - Delete immediately = [x]
 - Task frequency = Daily
 - Time to run this task = 8:00

1.3. Add a proxy (=remote) repository

- · Connect to Nexus
- Click on Administration (wheel) → Repositories → Repository → Create repository

- Choose maven2 (proxy)
- · Fill repository data
 - Name = Wakaleo
 - Remote Storage = http://www.wakaleo.com/maven/repos
 - Download Remote Indexes = False
- Save
- On the corresponding line in the list, click on Analyze

Now artifacts should be accessible via maven if the settings.xml is well configured to reach the Nexus:

Settings.xml using Nexus

```
<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"</pre>
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0 http://maven.apache.org/xsd/settings-1.0.0.xsd">
    <servers>
    <!-- tag::server[] -->
        <server>
           <id>nexus-local</id>
            <username>svc-fr-cric</username>
            <password>ESBpwd2018</password>
        </server>
    <!-- end::server[] -->
        <server>
            <id>iserver-dev</id>
            <username>devops</username>
            <password>devopswm</password>
        </server>
        <server>
           <!-- Gerrit credentials for maven-scm-plugin, which search with the hostname
               as server id -->
            <id>cric.pl.s2-eu.nvx.com</id>
            <username>svc-fr-cric</username>
            <!-- Gerrit does not use the CORP password, we use the UI generated one -->
            <password>ptTpilL5FS47RHDFV8541owV4zkbZ0tVrxyqRsmGhw</password>
        </server>
    </servers>
    <!-- tag::mirrors[] -->
    <mirrors>
        <mirror>
           <id>nexus-local</id>
            <mirrorOf>*</mirrorOf>
            <url>https://cric.pl.s2-eu.nvx.com/nexus3/repository/maven-public/</url>
        </mirror>
    </mirrors>
    <!-- end::mirrors[] -->
    <!-- tag::profiles[] -->
    ofiles>
        corofile>
            <id>nexus-local</id>
            <repositories>
                <repository>
                    <id>central</id>
                    <url>http://central</url>
                    <releases>
                        <enabled>true</enabled>
                    </releases>
                    <snapshots>
```

```
<enabled>true</enabled>
                    </snapshots>
                </repository>
            </repositories>
            <pluginRepositories>
                <pluginRepository>
                   <id>central</id>
                    <url>http://central</url>
                   <releases>
                       <enabled>true</enabled>
                   </releases>
                   <snapshots>
                        <enabled>true</enabled>
                    </snapshots>
                </pluginRepository>
            </pluginRepositories>
            cproperties>
                <snapshotUrl>https://cric.pl.s2-eu.nvx.com/nexus3/repository/maven-snapshots/</snapshotUrl>
                <releaseUrl>https://cric.pl.s2-eu.nvx.com/nexus3/repository/maven-releases//releaseUrl>
            </properties>
        </profile>
   </profiles>
   <!-- end::profiles[] -->
   <!-- tag::activeProfiles[] -->
   <activeProfiles>
        <activeProfile>nexus-local</activeProfile>
   </activeProfiles>
   <!-- end::activeProfiles[] -->
</settings>
```

Repositories to add

• For SchemaSpy: http://www.wakaleo.com/maven/repos

2. Appendix

2.1. Revision marks

Differences since last tag