





ABIDE BY ROHS





Linear Silent shaft




Specification :

- 1. Rating : 12V AC/DC max. 2V DC min.
10mA AC/DC max. 10 μ A DC min.
- 2. Contact Resistance : 200m Ω Max
- 3. Insulation Resistance : 100M Ω Min (DC500V)
- 4. Withstand Voltage : AC100V (50-60Hz) for 1 minute
- 5. Bounce Time : ≤ 5 msec (3~4 times/s)
- 6. Operation Force : 40 ± 10 gf
- 7. Pre travel : $1.9\text{mm} \pm 0.4\text{mm}$
- 8. Total travel : $3.7 \pm 0.3\text{mm}$
- 9. Operating Life : 70,000,000 Cycles(min).


<Feel is allowed to have difference before and after life test>





SWITCH FUNCTION



轴倾斜角度



⑨	Rubber 2	—	2	TPE/SUS	Nature	—
⑧	Rubber 1	—	2	TPE/SUS	Nature	—
⑦	Base	—	1	PA66	Senior grey	—
⑥	Spring	—	1	Stainless Steel	—	—
⑤	contact	—	2	Composite gold	—	—
④	Cover	—	1	PC	Transparent	—
③	Keystroke	—	1	POM	Senior grey	—
②	static plate	—	1	Brass	Sn / NI-plating	—
①	movable plate	—	1	Phosphor Copper	—	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS			DATE	 DONGGUAN CITY KAIHUA ELECTRONICS CO.,LTD			
DRAWN	Guyuexin	2022.08.30	Kailh				
CHECKED				TITLE:	PG1511 Silent Keystroke Switch		
APPROVALS				PART NO.	CPG151101S153		
TOLERANCES ARE		30<L	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ: 
		10<L≤30	±0.20				
		5<L≤10	±0.15				
		L≤5	±0.10				
			±2°	DRAWING NO.	KHA-PG1511-363EN	SHEET	1 OF 1

ECN NO.	REV.	DATE.
---------	------	-------

4

NEW
DESCRIPTION.

3

CHANGE.	CHECK.	APPRO.
---------	--------	--------

2

1




凱華電子
KAIHUA EEELECTRONICS

Document Number:

KH-PS2204-05

产品规格书

Product Specification



Linear Silent shaft


P/N: _____

CPG151101S153

Title :

PG1511 Silent Keystroke Switch

Rev.	ECN	Release and Revision Description:	Prepared By /Date:	Checked By/Date:	Approved By/Date:
A	— —	New releasing 初版发行	谷跃新 2022-06-30	胡远锋 2022-06-30	郑建军 2022-06-30

 <div> 凱華電子 KAIHUA EEELETRONICS </div>	Product Specification			
	P/N: CPG151101S153	DOC. No.: KH-PS2204-05	Rev.: A	Page: 2/12

--	--	--	--	--	--

Content

目录

1. Scope/范围:	3
2. Product Application/产品应用：	3
3. Technology Parameters/技术参数	3
4. Ratings/额定性能要求	3
5. Profile Dimensions /外形尺寸	3
6. Electrical Performance/电气性能	4
7. Mechanical Performance/机械性能	5-7
8. Environmental Performance/环境性能	7-9
9. Recommended PCB Layout/推荐的 PCB 安装焊盘规格	10
10. Loading Parameter Specification/荷重参数规格	11
11. Packaging/包装	11
12. Precaution/注意事项	11-12



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101S153	KH-PS2204-05	A	3/12

1. Scope/范围:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

本规格书内容涵盖机械键盘开关产品的要求，包括性能指标、测试方法及质量保证方面等。

2. Product Application/产品应用:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

主要适用于电脑键盘，收银机、工业设备和人机界面。


3. Technology Parameters/技术参数

Ambient Humidity 工作湿度:	45~85% R.H.;
Operating Temperature Range 使用温度范围:	-10℃~+70℃;
Storage Temperature Range 保存温度范围:	-20℃~+70℃;
Suggested storage period 贮存期限:	about 6 months 最多 6 个月
Require the tin part on the switch terminals should keep good after storage guarantee date 要求贮存期后开关端子部分上锡仍然良好。	
Normal Condition:	
Ambient temperature 环境温度:	20±2℃
Relative humidity 相对湿度:	65%±5% R.H.;
Air pressure 气压:	86~101KPa;
Solder Ability 可焊性:	锡铅焊 245±5℃ 5±0.5s; 无铅焊 255±5℃ 5±0.5s;
Withstand Soldering Temperature 耐焊接热:	波峰焊焊接: 260±5℃ 5±0.5s;

4. Ratings/额定性能要求

Rating 额定负荷:	12V AC/DC max.2V DC min. 10mA AC/DC max.10 μ A DC min;
Insulation Resistance 绝缘电阻:	≥100MΩ/DC 500V;
Withstand Voltage 耐电压:	100V AC 1 Minute;
Mechanical Life 机械寿命:	70,000,000 Cycles.

5. Profile Dimensions /外形尺寸




" Confidential "

All Right Reserved COPYRIGHT Kailh Electronics Co, LTD





6. Electrical Performance/电气性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
6.1	Contact Resistance 接触电阻	Static load: (Operation force)x2, which is applied on the center of Switch stem. 静态负载: 动作力的 2 倍, 施加在手柄中心. Measurement tool: Contact resistance Meter. 测量工具: 微电流接触电阻计(1KHz, 20mV,5~50mA) 在低电流 ($\leq 100\text{mA}$) 条件下测试. Measured at low currnt (100mA or less).	200m Ω Max 200m Ω 以下
6.2	Insulation Resistance 绝缘电阻	Apply a Voltage of DC 500 V for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 500V DC 电压 1 分钟, 按如下接触方法测试: (1) 端子与端子之间. (2) 端子与外壳之间.	100M Ω Min 100 兆欧以上
6.3	Dielectric withstanding voltage 耐电压	Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 100V AC 电压 1 分钟, 按如下接触方法测试: (1) 端子与端子之间. (2) 端子与外壳之间.	No evidence of breakdown 无瞬断、击穿等破坏.
6.4	Bouncing 触点抖动	Operation speed: 3~4 times/s 操作速度: 每秒 3~4 次 Oscillo scope 示波器 Switch Bouncing Test Circuit 抖动测定回路. 	Before Life cycle: On:5ms MAX,5 毫秒以下 Off: 5ms MAX,5 毫秒以下 After Life cycle: On:10ms MAX,10 毫秒以下 Off: 10ms MAX,10 毫秒以下



7. Mechanical Performance/机械性能


Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
7.1	Load Curve 荷重曲线	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> 	See page 11 见第 11 页
7.2	Loading parameter 荷重参数	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> 	See page 11 见第 11 页



7.3

Static
Strength
静止强度

A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds.
在手柄动作方向施加 3kgf 的静负荷 60 秒, 然后测试参数.



No damage
(Electrical)
And mechanical)
电气和机械性能正常.

7.4

Stem Pull
Strength
手柄拉拔强度


Break by a pull force applied opposite to the direction of stem operation.
在推柄动作方向反向垂直施加拉力, 使其破坏的程度.

5kgf Min

7.5

Shock
机械冲击

Measured by according to the below condition:
(1) Acceleration: 80g 加速度
(2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles.
试验次数: 每个方向 3 次, 6 个方向共 18 次.



Shall meet No.6, 7.1,
7.2.
满足 6, 7.1, 7.2 要求.

7.6

Life Test
寿命测试

1) D.C.12V 10mA resistance load
D.C 12V 10mA 电阻负荷
2) Operation speed : 10 times / s
动作速度: 10 次/ 秒
3) Applying Force: 250 ± 50gf (by spring)
按力: 250±50gf
4) Operation number: 70,000,000cycles
动作次数: 70, 000, 000 次


Contact resistance:
1000 mΩ Max
接触电阻: 1000 毫欧以下
Bouncing: 10ms Max
触点抖动: 10 毫秒以下
Operation force:
Variation rate within ± 30%
操作力的变化范围在初始值的±30%以内.



7.7

Noise Test
噪音测试

1、Decibel meter model : BK2250-L
分贝仪型号: BK2250-L
2、background noise: 10 dB Max
背景噪音: 10 dB Max
3、Metal strip to click product 3 times per second for 10 seconds, to maximize the noise test results by dB
金属头按击产品每秒 3 次持续 10 秒, 测试结果取噪音最大值 dB



A=麦克风角度: 30°
B=麦克风摆放高度: 135mm
C=麦克风与产品距离: 150mm
①: 麦克风
②: 按压传动杆
③: 测试产品
④: 金属按压头

Pure switch pressing sound without keycap
<37 dB
不带键帽的裸轴按压声音值 37 分贝 MAX

8. Environmental Performance/环境性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
8.1	Cold test 耐寒性	(1) Temperature : $-20 \pm 2^{\circ}\text{C}$ 温度: $-20 \pm 2^{\circ}\text{C}$ (2) Duration of test: 48h 持续时间: 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件: 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2
8.2	Heat test 耐热性	(1) Temperature : $70 \pm 2^{\circ}\text{C}$ 温度: $70 \pm 2^{\circ}\text{C}$ (2) Duration of test: 48h 持续时间: 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件: 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2



8.3

Temperature
cycle
温度循环

- (1) Test cycles: 5 cycles
试验周期: 5 个周期
(2) Standard condition after test: 1h
试验后的放置条件: 1 小时


	Temperature 温度	Duration of test 持续时间
1 cycle 一次循环	20±5℃	1h
	-20±5℃	1h
	20±5℃	1h
	70±5℃	1h

Contact resistance:
200mΩ Max
Shall meet :
No. 6.2 to 6.4
No. 7.1 to 7.2
接触电阻 200mΩ 以下
满足:
No. 6.2 to 6.4
No. 7.1 to 7.2

8.4

Soldering
heat test
耐焊接热

- Soldering area: T/2 of PWB thickness.
(PWB: T=1.6mm)
焊接面积: 印刷基板的 1/2 厚度处
Soldering temperature: 260±5℃
Soldering time: 5±0.5s
焊接温度: 260±5℃
焊接时间: 5±0.5 秒



Appearance:
No abnormality.
外观无异常

8.5

Solder
ability
可焊性

- Lead-tin soldering 锡铅焊接:
Soldering temperature: 245±5℃
Soldering time: 5±0.5s
焊接温度: 245±5℃
焊接时间: 5±0.5 秒

Lead free soldering 无铅焊接:
Soldering temperature: 255±5℃
Soldering time: 5±0.5s
焊接温度: 255±5℃
焊接时间: 5±0.5 秒

At least 90% of surface
area of immersed portion
shall be covered by
solder.
浸焊面积大于 90% 以上.

<div><div>凱華電子</div><div>KAIHUA EEELETRONICS</div></div>		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG151101S153	KH-PS2204-05	A	9/12
8.6	Humidity test 耐湿性	(1) Temperature : 60±2℃ 温度: 60±2℃ (2) relative humidity: 90~95% R.H. 相对湿度:90~95% R.H. (3) Duration of test: 48h 持续时间: 48 小时 (4) Take off a drop water 去掉水珠 (5) Standard conditions after test: 1h 试验后的放置条件: 1 小时		Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2	
8.7	Salt Spray 盐雾测试	Apply the following environment to test: 根据下列条件进行测试: (1) Temperature : 35±5℃ 温度: 35±5℃; (2) Salt water density: 5±1% 盐水浓度: 5±1%; (3) Duration: 12hours 持续时间: 12 小时; (4) After test, the salt deposit shall be removed by running water. 实验后将盐沉积物用水冲掉		Appearance: No corrosion spot, no crack, no base plate naked. 外观: 无腐蚀点, 无裂纹, 无裸露基材. Contact Resistance: 200 m Ω Max 接触电阻: 200 毫欧以下	
8.8	Wobbling of Button 按柄摇摆偏 移	Apply 1N force as shown below 在按钮侧臂施 加1N的力测量其最大偏移尺寸 (横向纵向) 		Displacement 0.35mm Max 开关按柄最大偏移尺寸为 0.35mm	

9. Recommended PCB Layout 推荐的 PCB 安装焊盘规格

Mounting Options 安装选项



PCB (With pins)



Metal Frane (With pins)

" Confidential "

All Right Reserved COPYRIGHT Kailh Electronics Co, LTD



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:
CPG151101S153

DOC. No.:
KH-PS2204-05


Rev.:
A

Page:
10/12


Circuit Board Layouts 电路板布局

Grid line spacing = 1.27mm 网格线间距= 1.27毫米

Keyswitch without fixation pins
按键开关不带定位柱



Keyswitch with fixation pins
按键开关带定位柱



Metal Frame Cutout Dimensions



10. Loading Parameter (FP/OP/PT/OF /TT) Specification 荷重参数规格：

Parameter	Unit	Specification	Remark
FP(自由位置)	mm	15.25±0.2	
OP(动作位置)	mm	13.35±0.7	
PT(导通行程)	mm	1.9±0.4	
OF(操作力)	g f	40±10	
TT(总行程)	mm	3.7±0.3	

11. Packaging 包装

Packaging type: Tray, 1000Pcs/Tray, 4000Pcs/Carton.

" Confidential "

All Right Reserved COPYRIGHT Kailh Electronics Co, LTD





凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101S153	KH-PS2204-05	A	11/12

包装方式: Tray 盘,1000Pcs/盘, 4000Pcs/箱.



12.Precaution 注意事项

12.1 Immersion Soldering condition 浸焊

ITEM 项目	CONDITION 条件
Preheat temperature 预热温度	110°C Max (Ambient temperature of soldering surface of P.W.B) 110°C 以下(印刷基板焊锡面周围的温度)
Preheat time 预热时间	60s, Max 60 秒以内
Area of flux 助焊剂面积	1/2 Max of PWB Thickness 印刷基板厚度的 1/2 以内
Temperature of solder 焊锡温度	260±5°C 260±5°C
Time of immersion 浸焊时间	5s±0.5s 5 秒±0.5 秒
Number of soldering 焊接次数	2time Max (But should down heat of the first soldering) 2 次以内
Printed wiring board 印刷基板	Single side copper-clad laminates 单面铜箔

(1) After switches were soldered, please be careful not to clean switches with solvent

开关浸焊后,注意不要用溶剂清洗.

(2) Under the condition of using soldering iron, soldering temperature shall be 350°C max within 3 sec.

在使用烙铁的情况下,焊锡温度应在350°C以下,焊接时间3秒以内.

12.2 Notes 注意点

(1) Please be cautious not to give excessive static load or shock to switches.

注意不要施加超负荷的压力或晃动开关.

(2) Please be careful not to stack up P. W. B. after switches were soldered.

开关焊接以后,印刷基板注意不要叠放.

(3) Preservation under high temperature and high humidity or corrosive gas should be avoided

Especially. When you need to preserve for a long period, do not open the carton.

保管时尤其应注意避开高湿高温和有腐蚀性气体的环境.如需长时间保存,请不要打开包装箱.

(4) The standard storage period is 3 months, with maximum up to 6months, preferably to be used as soon as possible. After opening the package, you should put the remaining switches in a plastic bag to prevent

" Confidential "

All Right Reserved COPYRIGHT Kailh Electronics Co, LTD



凱華電子
KAIHUA EEELECTRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101S153	KH-PS2204-05	A	12/12

from damp and corrosive gas.

保存标准为 3 个月，限度为 6 个月以内，请尽早使用。打开包装后，有剩余品时，应将剩余部分以胶袋包装好以同外界隔离，请进行合适的防湿，防腐蚀气体等处理后进行保管。

- (5) This Product Specification is considered as the technical agreement on product between the receiving customer and Kailh. Any information on Product Catalogue which is in conflict with or different from the corresponding information of this document is considered as invalid.

该规格书为客户与凯华公司产品在技术方面的共识，其他相关数据上与该规格书不一致的内容都是无效的。

- (6) It will be considered that customer already confirmed and accepted this specification if customer issue purchase order to us directly.

无论顾客收到规格书后有没有信息反馈直接向我公司订货，我们将认为顾客对此产品已验证合格。

- (7) If there is no order or no request for new specification after 1 year upon this specification is issued, the specification will be regarded as invalid.

本产品规格书从生效日起 1 年后，如果没有订货或再次申请最新规格书时请做无效处理。

- (8) Products meet the ROHS & REACH environmental management substances control standards

产品满足 **ROHS & REACH** 环境管理物质管制标准