








红 轴 (新结构)






■ 电路图



■ 轴倾斜角度



- **产品规格:**
- 1. 额定值: 12 VAC/DC max. 2 VDC min.
10mA AC/DC max. 10 μ A DC min.
 - 2. 接触阻抗: 200毫欧 最大
 - 3. 绝缘阻抗: 100兆欧 最小(DC100V)
 - 4. 耐高压: 交流100伏 (50~60赫兹)持续 1 分钟
 - 5. 动作力: 45 \pm 10gf 
 - 6. 回复力: \geq 15gf 
 - 7. 导通行程: 1.80 \pm 0.4 (PT) 
 - 8. 总行程: 3.60 \pm 0.3mm
 - 9. 机械寿命: 8000万次以上
 - 10. 防护等级: IP54
 - 11. 该产品需符合凯华环境有害物质管制标准

明细表:

2 G	⑨	BSPG1511F-02002	2#基座	——	1	Nylon	白 色	——
	⑧	BSPG1511F-05034	3#活动块	——	1	POM	绿 色	——
	⑦	BSPG1511F-07001	防水盖	——	1	Nylon	本 色	——
	⑥	BWPG1511F-03002	A款弹簧	——	1	不锈钢	亮 面	——
	⑤	BWPG1511-09010	焊点金线	——	2	复合线	——	——
3 G	④	BSPG1511F-04002	2#盖子	——	1	PC	透 明	——
	③	BSPG1511F-05053	7#红导芯	——	1	POM	红 色	——
	②	BZPG1511F-03010	2#静片	——	1	磷铜	本 色	——
	①	BZPG1511F-03012	6#动片	——	1	铜合金	——	——
4 G	序号	物料料号	零件名称	端子料号	用量	材料	镀层/颜色	备注
5 G								

备注:

◇：表示重点管控尺寸，一般为功能尺寸，首检时需量测。

△: 表示次重点管控尺寸, 一般为装配尺寸, 首检时需量测。

1) 重点及次重点管控尺寸中的序号不可重复, 需依次往后增加。若其中有某个尺寸在变更或其它状况下, 尺寸消失或不要求管控时, 原序号不可再用。有其它尺寸需要增加管控时, 序号往后增加。

2) 版次定义: 新开发而未转量产之产品图面版次为A1,A2,A3...

已转量产之产品图面版次为A,B,C...

ECN-2011-01	G	2020/11/04	图示 \oplus 处动片引脚加长, \oplus ~ \oplus 处物料表料号更新, \oplus 处防护等级更新	肖奕江		
ECN-1904-30	F	2019/05/16	图示 \oplus 处静片材料由黄铜改为磷铜, \oplus 处行程由 1.80 ± 0.3 改为 1.80 ± 0.4 , \oplus 处基座底部由有孔改为无孔, \oplus 处盖子小台阶改为平面	张林		
	A	2017/01/03	初使版本	张林		
工程变更单号	版次	日期	说明	修 改	审 核	核 准

承 认		日期	<div><div>东莞市凯华电子有限公司 DONGGUAN CITY KAIHUA ELECTRONICS CO.,LTD</div></div>				
设 计	肖奕江	2020.10.24	<div></div>				
审 核			名 称	PG1511F红轴按键开关 (2#盖子)			
核 准			料 号	CPG1511F01S04			
未注尺寸公差	30<L		±0.30	角 度	单位: mm	比例: 1:1	视 角 
	10<L≤30		±0.20				
	5<L≤10		±0.15				
	L≤5		±0.10				
			±2°				
图 号:				KHA-PG1511F-004	页次 1 OF 1		




凱華電子
KAIHUA EEELETRONICS

Document Number:

KH-PS1612-14

产品规格书

Product Specification



Red Shaft

P/N:

CPG1511F01S04

Title :

PG1511F Keyboard Switch

Rev.	ECN	Release and Revision Description:	Prepared By /Date:	Checked By/Date:	Approved By/Date:
E	— —	更新成品外形/静片材料/规格	张林/2019.05.16	张林/2019.05.16	王锋/2019.05.16
F	— —	动片引脚加长/防水等级更新	肖奕江/2020.11.02	吕攀豪/2020.11.02	郑建军/2020.11.02



凱華電子
KAIHUA EEELECTRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG1511F01S04	KH-PS1612-14	F	2/12

Content

目录

1. Scope/范围:	3
2. Product Application/产品应用 :	3
3. Technology Parameters/技术参数	3
4. Ratings/额定性能要求	3
5. Profile Dimensions /外形尺寸	3
6. Electrical Performance/电气性能	4
7. Mechanical Performance/机械性能	5~6
8. Environmental Performance/环境性能	7-8
9. Recommended PCB Layout/推荐的 PCB 安装焊盘规格	9
10. Loading Parameter Specification/荷重参数规格	10
11. Packaging/包装	10~11
12. Precaution/注意事项	11



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG1511F01S04	KH-PS1612-14	F	3/12

1. Scope/范围:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

本规格书内容涵盖机械键盘开关产品的要求，包括性能指标、测试方法及质量保证方面等。

2. Product Application/产品应用:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

主要适用于电脑键盘、收银机、工业设备和人机界面。

3. Technology Parameters/技术参数

Ambient Humidity 工作湿度: 45~85% R.H.;

Operating Temperature Range 使用温度范围: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$;

Storage Temperature Range 保存温度范围: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$;

Suggested storage period 贮存期限: about 6 months 最多 6 个月

Require the tin part on the switch terminals should keep good after storage guarantee date
要求贮存期后开关端子部分上锡仍然良好。

Normal Condition:

Ambient temperature 环境温度: $20 \pm 2^{\circ}\text{C}$

Relative humidity 相对湿度: $65\% \pm 5\%$ R.H.;

Air pressure 气压: 86~101KPa;

4. Ratings/额定性能要求


Rating 额定负荷: 12V AC/DC max. 2V DC min.
10mA AC/DC max. 10 μA DC min;

Insulation Resistance 绝缘电阻: $\geq 100\text{M}\Omega/\text{DC } 100\text{V}$;

Withstand Voltage 耐电压: 100 AC 1 Minute;


Mechanical Life 机械寿命: 80,000,000 Cycles.

5. Profile Dimensions /外形尺寸







6. Electrical Performance/电气性能



Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
6.1	Contact Resistance 接触电阻	<p>Static load: (Operation force)x2, which is applied on the center of Switch stem.Be measured when the switch contact stabilization. 静态负载：动作力的 2 倍，施加在手柄中心。开关接触稳定时量测。</p> <p>Measurement tool: Contact resistance Meter. 测量工具：微电流接触电阻计(1KHz, 20mV,5~50mA)</p> <p>在低电流（≤100mA）条件下测试。 Measured at low current (100mA or less).</p>	200mΩ Max 200mΩ 以下
6.2	Insulation Resistance 绝缘电阻	<p>Apply a Voltage of DC 100 V for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body.</p> <p>输入 100V DC 电压 1 分钟，按如下接触方法测试： (1) 端子与端子之间。 (2) 端子与外壳之间。</p>	100MΩ Min 100 兆欧以上
6.3	Dielectric withstanding voltage 耐电压	<p>Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body.</p> <p>输入 100V AC 电压 1 分钟，按如下接触方法测试： (1) 端子与端子之间。 (2) 端子与外壳之间。</p>	No evidence of breakdown 无瞬断、击穿等破坏。
6.4	Bouncing 触点抖动	<p>Operation speed: 3~4 times/s 操作速度：每秒 3~4 次</p> <p>Oscillo scope 示波器</p> <p>Switch Bouncing Test Circuit 抖动测定回路。</p> 	<p>Before Life cycle: On:5ms MAX,5 毫秒以下 Off: 5ms MAX,5 毫秒以下</p> <p>After Life cycle: On:10ms MAX,10 毫秒以下 Off: 10ms MAX,10 毫秒以下</p>



7. Mechanical Performance/机械性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
7.1	Load Curve 荷重曲线	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> <p>Force-Travel-diagram 操作力-行程-图解</p> 	See page 10 见第 10 页
7.2	Loading parameter 荷重参数	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> 	See page 10 见第 10 页




7.3	Static Strength 静止强度	<p>A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds. 在手柄动作方向施加 3kgf 的静负荷 60 秒, 然后测试参数.</p> 	No damage (Electrical) And mechanical) 电气和机械性能正常.
7.4	Stem Pull Strength 手柄拉拔强度	<p>Break by a pull force applied opposite to the direction of stem operation. 在推柄动作方向反向垂直施加拉力, 使其破坏的程度.</p>	5kgf Min
7.5	Shock 机械冲击	<p>Measured by according to the below condition: (1) Acceleration: 80g 加速度 (2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles. 试验次数: 每个方向 3 次, 6 个方向共 18 次.</p> 	Shall meet No.6, 7.1, 7.2. 满足 6, 7.1, 7.2 要求.
7.6	Life Test 寿命测试	<p>1) D.C. 12V 10mA resistance load D.C 12V 10mA 电阻负荷 2) Operation speed : 5-6 times / s 动作速度: 5-6 次/ 秒 3) Push force : 150gf 按力: 150gf 5) Push travel : 3.6mm 按压行程: 3.6mm 6) Operation number: 80,000,000cycles 动作次数: 80, 000, 000 次</p>	Contact resistance: 1 Ω Max 接触电阻: 1 欧以下 Bouncing: 10ms Max 触点抖动: 10 毫秒以下 Operation force: Variation rate within ± 30% 操作力的变化范围在初始值的±30%以内.



8. Environmental Performance/环境性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求															
8.1	Cold test 耐寒性	(1) Temperature : - 20±2℃ 温度： - 20±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2															
8.2	Heat test 耐热性	(1) Temperature : 70±2℃ 温度： 70±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2															
8.3	Temperature cycle 温度循环	(1) Test cycles: 5 cycles 试验周期： 5 个周期 (2) Standard condition after test:1h 试验后的放置条件： 1 小时 <table><tr><td></td><td>Temperature 温度</td><td>Duration of test 持续时间</td></tr><tr><td>1 cycle 一次循环</td><td>20±5℃</td><td>1h</td></tr><tr><td></td><td>-20±5℃</td><td>1h</td></tr><tr><td></td><td>20±5℃</td><td>1h</td></tr><tr><td></td><td>70±5℃</td><td>1h</td></tr></table>		Temperature 温度	Duration of test 持续时间	1 cycle 一次循环	20±5℃	1h		-20±5℃	1h		20±5℃	1h		70±5℃	1h	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2
	Temperature 温度	Duration of test 持续时间																
1 cycle 一次循环	20±5℃	1h																
	-20±5℃	1h																
	20±5℃	1h																
	70±5℃	1h																
8.4	Soldering heat test 耐焊接热	Soldering area: T/2 of PWB thickness. (PWB: T=1.6mm) 焊接面积： 印刷基板的 1/2 厚度处 Soldering temperature: 260±5℃ Soldering time: 3±0.5s 焊接温度： 260±5℃ 焊接时间： 3±0.5 秒	Appearance: No abnormality. 外观无异常															



8.5	Solder ability 可焊性	<p>1. Hand soldering 手工焊接: Please practice according to below condition: (1) Soldering Temperature : $350 \pm 5^{\circ}\text{C}$ 焊接温度: $350 \pm 5^{\circ}\text{C}$ (2) Continual soldering time: $3 \pm 0.5\text{s}$ 连续焊接时间: 3 ± 0.5 秒 (1) Capacity of soldering iron: $\leq 20\text{w}$ 电烙铁功率: 20 瓦以下</p> <p>2. Automatic PIP soldering 自动插板焊接: For the product of T/H according to below condition:</p> <p>波峰焊温度曲线图(单波峰)</p> 	<p>At least 95% of surface area of immersed portion shall be covered by solder. 浸焊面积大于 95%以上.</p>
8.6	Humidity test 耐湿性	<p>(1) Temperature : $60 \pm 2^{\circ}\text{C}$ 温度: $60 \pm 2^{\circ}\text{C}$ (2) relative humidity: 90~95% R.H. 相对湿度: 90~95% R.H. (3) Duration of test: 48h 持续时间: 48 小时 (4) Take off a drop water 去掉水珠 (5) Standard conditions after test: 1h 试验后的放置条件: 1 小时</p>	<p>Contact resistance: $200\text{m}\Omega$ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 $200\text{m}\Omega$ 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2</p>
8.7	Salt Spray 盐雾测试	<p>Apply the following environment to test(Only for contact test) : 根据下列条件进行测试(仅针对触点测试): (1) Temperature : $35 \pm 5^{\circ}\text{C}$ 温度: $35 \pm 5^{\circ}\text{C}$; (2) Salt water density: $5 \pm 1\%$ 盐水浓度: $5 \pm 1\%$; (3) Duration: 12hours 持续时间: 12 小时; (4) After test, the salt deposit shall be removed by running water. 实验后将盐沉积物用水冲掉</p>	<p>Appearance: No corrosion spot, no crack, no base plate naked. 外观: 无腐蚀点, 无裂纹, 无裸露基材.</p> <p>Contact Resistance: $200\text{m}\Omega$ Max 接触电阻: 200 毫欧以下</p>



8.8

Protection
Against ingress
of dust(IP5X)
防尘

The switches are placed in a position of normal use inside the test chamber. The test is carried out according to the second enclosure of IEC60529/GB4208. The test shall be continued for a period of 8h.

测试样品以正常使用位置在防尘箱中安装；
按 IEC60529 或 GB4208 防护标准测试条件
进行试验；
试验应持续 8 小时；

After test:
Operating is normal
Between terminals,
terminal and surface of
the crust,
Dielectric withstand in
voltage $\geq 100V$

动作正常；
端子之间及端子与外壳
表面耐电压强度 $\geq 100V$

8.9

Protection
against ingress
water(IPX4)
防水

The switches are placed in a position of normal use inside the test table. The test is carried out according to the second enclosure of IEC60529/GB4208.


测试样品以正常使用位置在防尘箱中安装；
按 IEC60529 或 GB4208 防护标准测试条件
进行试验；

After test:
Operating is normal.
Water don't enter
electric parts of the
switch inside.
Between terminals,
terminal and surface of
the crust,
Dielectric withstand in
voltage $\geq 100V$


动作正常；
水不能进入开关内带电
部份
端子之间及端子与外壳
表面耐电压强度 $\geq 100V$

9. Recommended PCB Layout 推荐的 PCB 安装焊盘规格

Mounting Options 安装选项



PCB (with pins)



Metal Frame (without pins)



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:
CPG1511F01S04

DOC. No.:
KH-PS1612-14


Rev.:
F

Page:
10/12


Circuit Board Layouts 电路板布局

Grid line spacing = 1.27mm 网格线间距= 1.27毫米


Keyswitch without fixation pins
按键开关不带定位柱



Keyswitch with fixation pins
按键开关带定位柱



Metal Frame Cutout Dimensions



10. Loading Parameter (TT/PT/OT /OF/TF/RF) Specification 荷重参数规格：

Parameter	Unit	Specification	Remark
TT(总行程)	mm	3.60±0.3	
PT(导通行程)	mm	1.80±0.4	
OT(过行程)	mm	1.30	Min.
OF(动作力)	gf	45±10	
RF(回弹力)	gf	15	Min.

11. Packaging 包装

Packaging type: Tray, 1000Pcs/Tray, 4000Pcs/Carton.



包装方式: Tray 盘,1000Pcs/盘, 4000Pcs/箱.



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG1511F01S04	KH-PS1612-14	F	11/12



12. Precaution 注意事项

12.1 Immersion Soldering condition 浸焊条件

ITEM 项目	CONDITION 条件
Preheat temperature 预热温度	110°C Max (Ambient temperature of soldering surface of P.W.B) 110°C 以下(印刷基板焊锡面周围的温度)
Preheat time 预热时间	60s, Max 60 秒以内
Area of flux 助焊剂面积	1/2 Max of PWB Thickness 印刷基板厚度的 1/2 以内
Temperature of solder 焊锡温度	260±5°C 260±5°C
Time of immersion 浸焊时间	3s±0.5s 3s±0.5s
Number of soldering 焊接次数	2time Max (But should down heat of the first soldering) 2 次以内
Printed wiring board 印刷基板	Single side copper-clad laminates 单面铜箔

(1) After switches were soldered, please be careful not to clean switches with solvent

开关浸焊后,注意不要用溶剂清洗.

(2) Under the condition of using soldering iron, soldering temperature shall be 350°C±5°C with 3±0.5s.

在使用烙铁的情况下,焊锡温度应在350°C±5°C,焊接时间3±0.5秒.

12.2 Notes 注意点

(1) Please be cautious not to give excessive static load or shock to switches.

注意不要施加超负荷的压力或晃动开关.

(2) Please be careful not to stack up P. W. B. after switches were soldered.

开关焊接以后,印刷基板注意不要叠放.

(3) Preservation under high temperature and high humidity or corrosive gas should be avoided

Especially. When you need to preserve for a long period, do not open the carton.

保管时尤其应注意避开高湿高温和有腐蚀性气体的环境.如需长时间保存,请不要打开包装箱.

(4) The standard storage period is 3 months, with maximum up to 6months, preferably to be used as soon as possible. After opening the package, you should put the remaining switches in a plastic bag to prevent from damp and corrosive gas.



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG1511F01S04	KH-PS1612-14	F	12/12

保存标准为 3 个月，限度为 6 个月以内，请尽早使用。打开包装后，有剩余品时，应将剩余部分以胶袋包装好以同外界隔离，请进行合适的防湿，防腐蚀气体等处理后进行保管。

- (5) This Product Specification is considered as the technical agreement on product between the receiving customer and Kailh. Any information on Product Catalogue which is in conflict with or different from the corresponding information of this document is considered as invalid.

该规格书为客户与凯华公司产品在技术方面的共识，其他相关数据上与该规格书不一致的内容都是无效的。

- (6) If customer issue purchase orders without confirmation by signature of this specification after receipt, such confirmation will be considered as granted upon receipt of the first purchase order.

如果顾客收到规格书后没有信息反馈而直接向我公司订货，我们将认为贵客已接受此规格书。

- (7) If there is no order or no request for new specification after 1 year upon this specification is issued, the specification will be regarded as invalid.

本产品规格书从生效日起 1 年后，如果没有订货或再次申请最新规格书时请做无效处理。

- (8) Products meet the ROHS & REACH environmental management substances control standards

产品满足 [ROHS & REACH](#) 环境管理物质管制标准