








遵守欧盟WEEE和ROHS之规定

临时版



Recommended PCB Layout
(Pattern Side)



Specification :

- 1.Rating :12DC 10mA
- 2.Contact Resistance : 200m Ω Max
- 3.Insulation Resistance :100M Ω Min (DC100V)
- 4.Withstand Voltage :AC100V(50-60Hz) for 1 minute
- 5.Operation Force :43 \pm 10gf
- 6.Return force: 15gf min
- 7.Conduction travel:1.2mm \pm 0.30mm
- 8.Total travel: 2.8 \pm 0.25mm
- 9.Operating Life(Resistance load DC12V 10mA) :
50,000,000 Cycles

序号	零件	端子编号	用量	材 料	镀层/颜色	备 注
承 认		日期		<div><div>东莞市凯华电子有限公司 KAIHUA ELECTRONICS CO.,LTD</div></div>		
设 计	吕攀豪	2023.05.12				
审 核				名 称	PG1353 静音键盘开关(红轴)	
核 准				料 号	CPG1353S01D01-01	
未注尺寸公差	30<L		±0.30	角 度	单位: mm	比例: 1:1
	10<L≤30		±0.20			
	5<L≤10		±0.15			
	L≤5		±0.10			
			±2°			
				图 号	KHA-PG1353-*****	
				页次 1 OF 1		

	AO	2023.05.12		NEW					
工程变更单号	版次	日期	说明	修改	审核	核准			



1. General specification 基本事项

- 1.1 Switch action : Push-on type S. P. S. T
开关种类 : 按键开关
- 1.2 Switch rating 额定值 : 12 VAC/DC max. 2 VDC min. 10mA AC/DC max. 10 μ A DC min.
- 1.3 Operation temperature range 使用温度试验范围 : - 40°C ~ +70°C
- 1.4 Storage temperature range 保存温度范围 : - 40°C ~ + 80°C

1.5 Suggested storage period 贮存期限 : about 6 months 最多六个月

Require the tin part on the switch terminals should keep good after storage guarantee date
要求贮存期后开关端子部分上锡仍然良好

1.6 Appearance and dimensions 外形及尺寸 : See outside drawing page 见外形尺寸图

1.7 Standard condition Unless otherwise specified, the test and measurements shall be
试验、测定状态 carried out as follows:

Ambient temperature 温度: 20 \pm 2°C

Relative humidity 相对湿度: 45% ~ 85%

Air pressure 气压: 86 ~ 106kPa (860~1060mbar)

However, if doubt arises on the decision based on the measured

Values under the above-mentioned conditions, the following conditions shall be employed:


但是在对判定产生疑义时,按下述状态实施:

Ambient temperature 温度: 20 \pm 2°C Relative humidity 相对湿度: 65 \pm 5%




Air pressure 气压: 86 ~ 106kPa (860~1060mbar)

2. Performance 性能

2.1 Electrical characteristics 电气性能

No.	Item 项目	Test condition 试验条件	Performance 规格
2.1.1	Contact resistance 接触电阻	Push force: (Operation force) x 2. 测定时的负荷: 操作方向动作力基准值的2 倍。 Measurement tool : Contact resistance meter 测定器: 微电流接触电阻计 (1kHz, 20mV, 5~50mA)	200m Ω MAX 200m Ω 以下
2.1.2	Insulation resistance 绝缘电阻	D. C. 100V (Between terminals) (端子间)	100M Ω min 100M Ω 以上
2.1.3	Withstand voltage 耐电压	A. C100V for 1 min (Between terminals) (端子间)	No. insulation destruction. 无绝缘破坏.
2.1.4	Bouncing 触点抖动	Operation speed : 3~4 times/s 操作速度: 每秒3~4 次 Oscillo scope 示波器 Switch Bouncing Test Circuit 抖动测定回路  Switch Bouncing Test Circuit 抖动测定回路 "ON" "OFF"	ON: 5ms max 以下 OFF: 5ms max 以下

2.2 Mechanical Characteristics 机械性能

No.	Item 项目	Test condition 试验条件	Performance 规格
2.2.1	Operation force 动作力 Travel to closure 动作行程(见图表)	 <p>Force-Travel-diagram 操作力-行程-图解</p> <p>Force力 (gf)</p> <p>Travel行程 (mm)</p> <p>operating point</p> <p>return point</p>	<p>operating force 动作力 43±10gf</p> <p>Return force (回弹力): 15gf min</p> <p>Full Travel: 2.8mm±0.25</p> <p>Pre Travel 预: 1.2mm±0.30</p>
2.2.2	Push strength 按压强度	<p>30N (3Kgf) for 15 sec 30N (3Kgf) 15 秒</p> 	<p>No damage (Electrical and mechanical) 无异常(电气、机械性能)</p>
2.2.3	Pull strength 推压强度	<p>Break by drawing push plate in the direction of right diagram 抽拔推杆使其破坏的强度.</p>	<p>30N min (3kgf min)</p>
2.2.4	Vibration test 耐振性	<p>1) Amplitude 全振幅: 1.5 mm 2) Sweep rate: 10-55-10HZ for 1 minute 扫描速度: 10-55-10HZ 1 分钟 3) Sweep method: Logarithmic frequency sweep rate 扫描方式: 对数频率扫描速度 4) Vibration direction: X, Y, Z (3 directions) 振动方向: X, Y, Z (3 方向) 5) Time: Each direction 2 hours (Total 6 hours) 时间: 每个方向2 个小时(共6 个小时)</p>	<p>No. 2.1 and 2.2.1 to 2.2.2 shall be satisfied 满足2.1 项和2.2.1 至 2.2.2 项.</p>
2.2.5	Soldering heat test 耐焊接热	<p>端子焊接部分浸入焊炉, 焊炉温度 260±5°C, 焊接时间 5±1 秒。(焊接时不可于端子施加外力). Terminals shall be dipped in the solder bath at 260±5°C for 5±1 seconds without additional force for terminals.</p>	<p>No damage (electrical and mechanical) 无异常。 (电气和机械特性)</p>
2.2.6	Solderability 可焊性	<p>After sprated flux / 涂上助焊剂后 temperature : 260± 5°C / 温度: 260± 5°C soldering time : 2±0.5 sec/ 焊接时间: 2±0.5 秒</p>	<p>90% or more of surface area of the portion immersed in solder shall be covered by new solder / 90% 或更多的浸焊面能被焊锡覆盖.</p>
2.2.7	Wobbling of Button 按钮摇摆偏移	<p>Apply 1N force as shown below 在按钮侧臂施加1N的力测量其最大偏移尺寸(横向纵向).</p> 	<p>Displacement 0.35mm Max 开关按钮最大偏移尺寸为0.35mm</p>




2.3 Climatic characteristics 耐候性能

No.	Item 项目	Test condition 试验条件	Performance 规格												
2.3.1	Cold test 耐 性	1) Temperature : $-40\pm2^{\circ}\text{C}$ 温度: $-40\pm2^{\circ}\text{C}$ 2) Duration of test: 48h 持续时间: 48 小时 3) Take off a drop water 去掉水珠 4) Standard conditions after test : 1h 试验后的放置条件: 1 小时	Contact resistance 200mΩ max No. 2.1.2 to 2.1.4 and No. 2.2.1 to 2.2.2 shall Be satisfied 接触电阻 200mΩ 以下 满足2.1.2 到2.1.4 项、 2.2.1 到2.2.2 项.												
2.3.2	Heat test 耐热性	1) Temperature : $70\pm2^{\circ}\text{C}$ 温度: $70\pm2^{\circ}\text{C}$ 2) Duration of test: 48h 持续时间: 48 小时 3) Standard conditions after test : 1h 试验后的放置条件: 1 小时	Contact resistance 200mΩ max No. 2.1.2 to 2.1.4 and No. 2.2.1 to 2.2.2 shall Be satisfied 接触电阻 200mΩ 以下 满足2.1.2 到2.1.4 项、2.2.1 到2.2.2 项.												
2.3.3	Temperature cycle 温度循环	1) Test cycles :20 cycles 试验周期: 20 个周期 2) Standard condition after test :1h 试验后的放置条件: 1 小时 <table><tr><td></td><td>temperature 温度</td><td>duration of test 持续时间</td></tr><tr><td rowspan="4">1 cycle 一次 循环</td><td>$20\pm5^{\circ}\text{C}$</td><td>1h</td></tr><tr><td>$-40\pm2^{\circ}\text{C}$</td><td>1h</td></tr><tr><td>$20\pm5^{\circ}\text{C}$</td><td>1h</td></tr><tr><td>$60\pm5^{\circ}\text{C}$</td><td>1h</td></tr></table>		temperature 温度	duration of test 持续时间	1 cycle 一次 循环	$20\pm5^{\circ}\text{C}$	1h	$-40\pm2^{\circ}\text{C}$	1h	$20\pm5^{\circ}\text{C}$	1h	$60\pm5^{\circ}\text{C}$	1h	Contact resistance 200mΩ max No. 2.1.2 to 2.1.4 and No. 2.2.1 to 2.2.2 shall be satisfied 接触电阻 200mΩ 以下 满足2.1.2 到2.1.4 项、 2.2.1 到2.2.2 项.
	temperature 温度	duration of test 持续时间													
1 cycle 一次 循环	$20\pm5^{\circ}\text{C}$	1h													
	$-40\pm2^{\circ}\text{C}$	1h													
	$20\pm5^{\circ}\text{C}$	1h													
	$60\pm5^{\circ}\text{C}$	1h													
2.3.4	Humidity test 耐湿性	1) Temperature : $70\pm2^{\circ}\text{C}$ 温度: $70\pm2^{\circ}\text{C}$ 2) relative humidity: 90~95% 相对温度:90~95% 3) Duration of test: 96h 持续时间: 96 小时 3) Take off a drop water 去掉水珠 5) Standard conditions after test : 1h 试验后的放置条件: 1 小时	Contact resistance 200mΩ max No. 2.1.2 to 2.1.4 and No. 2.2.1 to 2.2.2 shall Be satisfied 接触电阻 200mΩ 以下 满足2.1.2 到2.1.4 项、 2.2.1 到2.2.2 项.												


2.3 Climatic characteristics 耐候性能

2.3.5	temperature /humidity Cycling 温度/湿度循 环	<p>(1) Temperature : -5℃~55℃ 温度: -5℃~55℃</p> <p>(2) humidity: 20~95% R.H. 湿度:20~95% R.H.</p> <p>(3) Duration of test: 74h 持续时间: 74 小时</p> <p>(4) Take off a drop water 去掉水珠</p> <p>(5) Standard conditions after test: 1h 试验后的放置条件: 1 小时</p>	<p>Contact resistance 200mΩ max</p> <p>No. 2.1.2 to 2.1.4 and No. 2.2.1 to 2.2.2 shall be satisfied</p> <p>接触电阻 200mΩ 以下 满足2.1.2 到2.1.4 项、 2.2.1 到 2.2.2 项.</p>
-------	--	--	---

Temperature & Humidity test profile - Non-operating INDOOR



3. Acoustic Noise 噪音测试

No.	Item 项目	Test condition 试验条件	Performance 规格
3.1.1	Acoustic Noise 噪音测试	<p>Background Noise: 10dB Max. 背景噪音最大: 10dB Max</p> <p>手指按压 Pressing by fingers</p> <p>Sound Level Meter Position 声纳计摆放位置</p> <p>1) Distance 距离 (C) : 150 mm</p> <p>2) Vertical 高度 (B) : 135mm</p> <p>3) Angle 角度 (A) : 30 deg</p> <p>Drop Height 开关按压行程: 2.5mm</p> <p>Operation speed 按压频率: 1次/秒</p> <div data-bbox="437 994 1107 1666">  <p>A=麦克风角度: 30° B=麦克风摆放高度: 135mm C=麦克风与产品距离: 150mm</p> <p>①: 麦克风 ②: 测试产品</p> </div>	<p>下压最大噪音: 25 dB</p> <p>Maximum sound while pressing: 25dB</p>



4. Precaution 注意事项

4.1 Soldering condition 浸焊条件

ITEM 项目	CONDITION 条 件
Preheat temperature 预热温度	110°C max (Embilomental temperature of soldering surface of P. W. E) 110°C 以下 (印刷基板焊锡面周围的温度)
Preheat time 预热时间	60 sec, max 60 秒以内
Area of flux 助焊剂的面积	1/2 max of P. W. B. thickness 印刷基板厚度的1/2 以内
Temperature of solder 焊锡温度	260±5°C 260±5°C
Time of immersion 浸焊时间	Within 5 sec 5 秒以内
Soldering number 浸焊次数	Within 2 times (But should bring down heat of the first soldering) 2 次以内 (但应把第一次焊锡的温度降下来)

1) After switches were soldered, please be careful not to clean switches with solvent
开关浸焊后, 注意不要用溶剂清洗.

2) In the case of using soldering iron, soldering conditions shall be 350°C max and 3 sec. max
在使用烙铁的情况下, 焊锡温度应在350±10°C 以下, 3 秒以内.

3) Right after switches were soldered; please be careful not to load on the knobs of switches.
浸焊后, 注意不要在顶部施加负荷.

4.2 Note(注意点)

1) Please be cautious not to give excessive static load or shock to switches.
注意不要施加超负荷的压力或晃动开关.

2) Please be careful not to pile up P. W. B. after switches were soldered.
开关焊接以后, 印刷基板注意不要叠放.

3) Preservation under high temperature and high humidity or corrosive gas should be avoided especially. When you need to preserve for a long period, do not open the carton.
保管时尤其应注意避开高湿高温和有腐蚀性气体的环境. 如需长时间保存, 请不要打开包装箱.

4) Panasert RH and RH6 shall be used as the standard insert machine (use N type clinch).
使用标准插入机器PANASERT 和RH6 (使用N 式钉)

5) CONTROL HAZARDOUS SUBSTANCE: THE PRODUCT SHOULD BE MEET ROHS SPECIFICATION.
产品应满足 ROHS 环境管理物质管制标准

力和行程说明 The explanation for force and travel:

动作力 Operation Force: 导通位置的力. The pressing force while conduction

回弹力 Return force: 断开位置的力. The force of off-conduction position

导通行程 Conduction travel: 从自由位置到导通位置的距离. The distance from free position to conduction position

全行程 Total travel: 从自由位置到触底位置的距离. The distance from free position to bottom position