




深蓝轴



- 1. 额定值: 12V AC/DC max. 2V DC min.
10mA AC/DC max. 10 μ A DC min.
- 2. 接触阻抗: 100毫欧 最大
- 3. 绝缘阻抗: 100兆欧 最小 (DC500V)
- 4. 耐高压: 交流100伏 (50-60赫兹) 持续 1 分钟
- 5. 抖动时间: $\leq 5\text{msec}$ (3-4次/秒, 按压速度)
- 6. 回弹力: 10gf 以上
- 7. 操作力: $70 \pm 20\text{gf}$
- 8. 触感力: $95 \pm 20\text{gf}$
- 9. 导行程: $1.2\text{mm} \pm 0.5\text{ (PT)}$
- 10. 全行程: $3.5 \pm 0.5\text{mm}$
- 11. 操作寿命: 5000万次以上
- 12. 该产品需符合凯华环境有害物质管制标准

A diagram of a T-junction. It consists of a horizontal line with two small circles at its ends, labeled 1 and 2. A vertical line segment is attached to the midpoint of the horizontal line, extending upwards.

⑧	BWPG1511F-03008	PG1511F扭簧	——	1	SUS 304	——	B款扭簧 线径0.3
⑦	BSPG1511-02020	厚金轴基座	——	1	Nylon	白 色	——
⑥	BSPG1511-04022	厚金轴盖	——	1	PC	透 明	——
⑤	BSPG1511-05051	厚金轴导芯	——	1	poM	深蓝色	——
④	BZPG1511-01026	9#动片	——	1	Copper Alloy	——	——
③	BZPG1511-01017	3#静片	——	1	Brass	——	——
②	BWPG1511-03022	B-4款弹簧	——	1	Stainless Steel	——	——
①	BWPG1511-09010	焊点金线	——	2	——	——	——
序号	物料料号	零件名称	端子料号	用量	材料	镀层/颜色	备注

Diagram illustrating the rotation of the top cover. The top cover features the K&L logo. The rotation is limited to a maximum of 1° in both clockwise (CW) and counter-clockwise (CCW) directions.

已转量产之产品图面版次为A, B, C...

承 认		日期	 东莞市凯华电子有限公司 DONGGUAN CITY KAIHUA ELECTRONICS CO.,LTD		
设 计	易金平	2018/01/02	名 称	PG1511 按键开关（深蓝轴）	
审 核			料 号	CPG151101D234	
核 准			单 位: mm	比 例: 1:1	视 角: 
未注尺寸公差	30<L	±0.30	角 度	图 号:	KHA-PG1511-205
	10<L≤30	±0.20			
	5<L≤10	±0.15			
	1≤L	±0.10			
		±2°			页次 1 OF




凱華電子
KAIHUA EEELECTRONICS

Document Number:

KH-PS1801-02

产品规格书

Product Specification



P/N: CPG151101D234			Title : PG1511 Keyboard Switch		
Rev.	ECN	Release and Revision Description:	Prepared By /Date:	Checked By/Date:	Approved By/Date:
A	— —	New releasing 初版发行	易金平 2018-1-2	胡远锋 2018-1-2	David 2018-1-2



凱華電子
KAIHUA EEELECTRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101D234	KH-PS1801-02	A	2/12

Content

目录

1. Scope/范围:	3
2. Product Application/产品应用:	3
3. Technology Parameters/技术参数	3
4. Ratings/额定性能要求	3
5. Profile Dimensions /外形尺寸	3
6. Electrical Performance/电气性能	4
7. Mechanical Performance/机械性能	5-6
8. Environmental Performance/环境性能	7-9
9. Recommended PCB Layout/推荐的 PCB 安装焊盘规格	10
10. Loading Parameter Specification/荷重参数规格	11
11. Packaging/包装	11
12. Precaution/注意事项	11-12



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101D234	KH-PS1801-02	A	3/12

1. Scope/范围:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

本规格书内容涵盖机械键盘开关产品的要求，包括性能指标、测试方法及质量保证方面等。

2. Product Application/产品应用:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

主要适用于电脑键盘，收银机、工业设备和人机界面。

3.

Technology




Parameters/技术参数

Ambient Humidity 工作湿度:	45~85% R.H.;
Operating Temperature Range 使用温度范围:	-10℃~+70℃;
Storage Temperature Range 保存温度范围:	-20℃~+70℃;
Suggested storage period 贮存期限:	about 6 months 最多 6 个月
Require the tin part on the switch terminals should keep good after storage guarantee date 要求贮存期后开关端子部分上锡仍然良好。	
Normal Condition:	
Ambient temperature 环境温度:	20±2℃
Relative humidity 相对湿度:	65%±5% R.H.;
Air pressure 气压:	86~101KPa;

4. Ratings/额定性能要求


Rating 额定负荷:	12V AC/DC max.2V DC min. 10mA AC/DC max.10 μ A DC min.;
Insulation Resistance 绝缘电阻:	≥100M Ω /DC 500V;
Withstand Voltage 耐电压:	100V AC 1 Minute;
Mechanical Life 机械寿命:	50,000,000 Cycles (Without load).

5. Profile Dimensions /外形尺寸







6. Electrical Performance/电气性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
6.1	Contact Resistance 接触电阻	Static load: (Operation force)x2, which is applied on the center of Switch stem. 静态负载: 动作力的 2 倍, 施加在手柄中心. Measurement tool: Contact resistance Meter. 测量工具: 微电流接触电阻计(1KHz, 20mV,5~50mA) 在低电流 ($\leq 100\text{mA}$) 条件下测试. Measured at low current (100mA or less).	100m Ω Max 100m Ω 以下
6.2	Insulation Resistance 绝缘电阻	Apply a Voltage of DC 500 V for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 500V DC 电压 1 分钟, 按如下接触方法测试: (1) 端子与端子之间. (2) 端子与外壳之间.	100M Ω Min 100 兆欧以上
6.3	Dielectric withstanding voltage 耐电压	Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 100V AC 电压 1 分钟, 按如下接触方法测试: (1) 端子与端子之间. (2) 端子与外壳之间.	No evidence of breakdown 无瞬断、击穿等破坏.
6.4	Bouncing 触点抖动	Operation speed: 3~4 times/s 操作速度: 每秒 3~4 次 Oscillo scope 示波器 Switch Bouncing Test Circuit 抖动测定回路. 	Before Life cycle: On:5ms MAX,5 毫秒以下 Off: 5ms MAX,5 毫秒以下 After Life cycle: On:10ms MAX,10 毫秒以下 Off: 10ms MAX,10 毫秒以下



7. Mechanical Performance/机械性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
7.1	Load Curve 荷重曲线	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> 	See page 11 见第 11 页
7.2	Loading parameter 荷重参数	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止.</p> 	See page 11 见第 11 页
7.3	Static Strength 静止强度	<p>A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds. 在手柄动作方向施加 3kgf 的静负荷 60 秒，然后测试参数.</p>	No damage (Electrical) And mechanical) 电气和机械性能正常.



凱華電子
KAIHUA EEELETRONICS


Product Specification

P/N:
CPG151101D234

DOC. No.:
KH-PS1801-02

Rev.:
A

Page:
6/12



7.4

Stem Pull
Strength
手柄拉拔强度


Break by a pull force applied opposite to the direction of stem operation.
在推柄动作方向反向垂直施加拉力, 使其破坏的程度.

5kgf Min

7.5

Shock
机械冲击

Measured by according to the below condition:
(1) Acceleration: 80g 加速度
(2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles.
试验次数: 每个方向 3 次, 6 个方向共 18 次.



Shall meet No.6, 7.1, 7.2.
满足 6, 7.1, 7.2 要求.

7.6

Life Test
寿命测试

1) D.C. 12V 10mA resistance load
D.C 12V 10mA 电阻负荷
2) Operation speed : 5-6 times / s
动作速度: 5-6 次/ 秒
3) Push force : 150gf
按力: 150gf
5) Push travel : 3.5mm
按压行程: 3.5mm
6) Operation number: 50,000,000cycles
动作次数: 50, 000, 000 次

Contact resistance:
1000 mΩ Max
接触电阻: 1000 毫欧以下
Bouncing: 10ms Max
触点抖动: 10 毫秒以下
Operation force:
Variation rate within ± 30%
操作力的变化范围在初始值的±30%以内.


8. Environmental Performance/环境性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
------------	---------------------	---------------------	------------------



8.1	Cold test 耐寒性	(1) Temperature : - 20±2℃ 温度： - 20±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.2	Heat test 耐热性	(1) Temperature : 70±2℃ 温度： 70±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.3	Temperature cycle 温度循环	(1) Test cycles: 5 cycles 试验周期： 5 个周期 (2) Standard condition after test:1h 试验后的放置条件： 1 小时 <table><tr><td></td><td>Temperature 温度</td><td>Duration of test 持续时间</td></tr><tr><td rowspan="4">1 cycle 一次循环</td><td>20±5℃</td><td>1h</td></tr><tr><td>-20±2℃</td><td>1h</td></tr><tr><td>20±5℃</td><td>1h</td></tr><tr><td>70±5℃</td><td>1h</td></tr></table>		Temperature 温度	Duration of test 持续时间	1 cycle 一次循环	20±5℃	1h	-20±2℃	1h	20±5℃	1h	70±5℃	1h	Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200m Ω 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2
	Temperature 温度	Duration of test 持续时间													
1 cycle 一次循环	20±5℃	1h													
	-20±2℃	1h													
	20±5℃	1h													
	70±5℃	1h													
8.4	Soldering heat test 耐焊接热	Soldering area: T/2 of PWB thickness. (PWB: T=1.6mm) 焊接面积： 印刷基板的 1/2 厚度处 Soldering temperature: 260±5℃ Soldering time: 5±0.5s 焊接温度： 260±5℃ 焊接时间： 5±0.5 秒	Appearance: No abnormality. 外观无异常												



8.5	Solder ability 可焊性	<p>1. Hand soldering 手工焊接: Please practice according to below condition: (1) Soldering Temperature : $350 \pm 5^{\circ}\text{C}$ 焊接温度: $350 \pm 5^{\circ}\text{C}$ (2) Continual soldering time: $3 \pm 0.5\text{s}$ 连续焊接时间: 3 ± 0.5 秒 (1) Capacity of soldering iron: $\leq 20\text{w}$ 电烙铁功率: 20 瓦以下</p> <p>2. Automatic PIP soldering 自动插板焊接: For the product of T/H according to below condition:</p> <p>波峰焊温度曲线图(单波峰)</p> 	<p>At least 95% of surface area of immersed portion shall be covered by solder. 侵焊面积大于 95%以上.</p>
8.6	Humidity test 耐湿性	<p>(1) Temperature : $60 \pm 2^{\circ}\text{C}$ 温度: $60 \pm 2^{\circ}\text{C}$ (2) relative humidity: 90~95% R.H. 相对湿度: 90~95% R.H. (3) Duration of test: 48h 持续时间: 48 小时 (4) Take off a drop water 去掉水珠 (5) Standard conditions after test: 1h 试验后的放置条件: 1 小时</p>	<p>Contact resistance: $200\text{m}\Omega$ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 $200\text{m}\Omega$ 以下满足: No. 6.2 to 6.4 No. 7.1 to 7.2</p>
8.7	Salt Spray 盐雾测试	<p>Apply the following environment to test: 根据下列条件进行测试: (1) Temperature : $35 \pm 5^{\circ}\text{C}$ 温度: $35 \pm 5^{\circ}\text{C}$; (2) Salt water density: $5 \pm 1\%$ 盐水浓度: $5 \pm 1\%$; (3) Duration: 12hours 持续时间: 12 小时; (4) After test, the salt deposit shall be removed by running water. 实验后将盐沉积物用水冲掉</p>	<p>Appearance: No corrosion spot, no crack, no base plate naked. 外观: 无腐蚀点, 无裂纹, 无裸露基材.</p> <p>Contact Resistance: $200\text{m}\Omega$ Max 接触电阻: 200 毫欧以下</p>



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG151101D234	KH-PS1801-02	A	9/12

8.8	Withstand K ₂ S 硫化测试	Apply the following environment to test: 根据下列条件进行测试 (1) Temperature: 35±5℃ 温度: 35±5℃ (2) K ₂ S Density: 2%; 硫化钾浓度: 2% (3) Duration: 2 minute. 持续时间: 2 分钟	Appearance: No corrosion spot, no crack, no base plate naked. 外观: 无腐蚀点, 无裂纹, 无裸露基材. Contact Resistance: 1000 mΩ Max 接触电阻: 1000 毫欧以 下
-----	---------------------------------------	---	---



凱華電子
KAIHUA EEELETRONICS

Product Specification

P/N:
CPG151101D234


DOC. No.:
KH-PS1801-02

Rev.:
A


Page:
10/12

9. Recommended PCB Layout 推荐的 PCB 安装焊盘规格

Mounting Options 安装选项



PCB (with pins)




Metal Frame (without pins)

Circuit Board Layouts 电路板布局


Grid line spacing = 1.27mm 网格线间距= 1.27毫米

Keyswitch without fixation pins
按键开关不带定位柱


1-Pole



1-Pole w/LED



1-Pole w/Diode



ø3.99±0.1




ø1.50±0.05




ø1.0±0.1

Keyswitch with fixation pins
按键开关带定位柱


1-Pole



1-Pole w/LED



1-Pole w/Diode



ø3.99±0.1



ø1.70±0.05





ø1.50±0.05



ø1.0±0.1

Metal Frame Cutout Dimensions







10. Loading Parameter (FP/OP/PT/OT /MD/CF/OF) Specification 荷重参数规格:

Parameter	Unit	Specification	Remark
FP(自由行程)	mm	15.25 ± 0.2	
OP(动作位置)	mm	14.05 ± 0.7	
PT(导通行程)	mm	1.20 ± 0.50	
OF(操作力)	gf	70 ± 20	
TF(触感力)	gf	95 ± 20	
OT(过行程)	mm	1.8	Min
MD(差动行程)	mm	0.6	Max
TT (全行程)	mm	3.5 ± 0.50	

11. Packaging 包装

(1). Packaging type: Tray, 1000Pcs/Tray, 4000Pcs/Carton.

包装方式: Tray 盘, 1000Pcs/盘, 4000Pcs/箱.





12. Precaution 注意事项

12.1 Immersion Soldering condition 浸焊条件

ITEM 项目	CONDITION 条件
Preheat temperature 预热温度	110°C Max (Ambient temperature of soldering surface of P.W.B) 110°C 以下(印刷基板焊锡面周围的温度)
Preheat time 预热时间	60s, Max 60 秒以内
Area of flux 助焊剂面积	1/2 Max of PWB Thickness 印刷基板厚度的 1/2 以内
Temperature of solder 焊锡温度	260±5°C 260±5°C
Time of immersion 浸焊时间	Within 5s 5 秒以内
Number of soldering 焊接次数	2time Max (But should down heat of the first soldering) 2 次以内
Printed wiring board 印刷基板	Single side copper-clad laminates 单面铜箔

(1) After switches were soldered, please be careful not to clean switches with solvent

开关浸焊后,注意不要用溶剂清洗.

(2) Under the condition of using soldering iron, soldering temperature shall be 350°C max within 3 sec.

在使用烙铁的情况下,焊锡温度应在350°C以下,焊接时间3秒以内.

12.2 Notes 注意点

(1) Please be cautious not to give excessive static load or shock to switches.

注意不要施加超负荷的压力或晃动开关.

(2) Please be careful not to stack up P. W. B. after switches were soldered.

开关焊接以后,印刷基板注意不要叠放.

(3) Preservation under high temperature and high humidity or corrosive gas should be avoided

Especially. When you need to preserve for a long period, do not open the carton.

保管时尤其应注意避开高湿高温和有腐蚀性气体的环境.如需长时间保存,请不要打开包装箱.

(4) Products meet the ROHS & REACH environmental management substances control standards

产品满足 [ROHS & REACH](#) 环境管理物质管制标准