

# RF Exposure Evaluation Report

**Applicant:** Nebra Ltd

**Address of Applicant:** Unit 4 Bells Yew Green Business Court, Bells Yew Green,  
Tunbridge Wells TN3 9BJ

**Equipment Under Test (EUT)**

Product Name: Nebra Smart Indoor LoRa Gateway / Nebra HNT Indoor  
Hotspot Miner

Model No.: HNTIN-470-G, HNTIN-868-G, HNTIN-915-G, HNTIN-433-G,  
HNTIN-470, HNTIN-868, HNTIN-915, HNTIN-433

**FCC ID:** 2AZDM-HNTIN

**Applicable standards:** FCC CFR Title 47 Part 2 Subpart J Section 2.1091

**Date of sample receipt:** 12 Mar., 2021

**Date of Test:** 13 Mar., to 19 Apr., 2021

**Date of report issue:** 23 Apr., 2021

**Test Result:** PASS\*

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	23 Apr., 2021	Original

Tested by: Yao Wu  
Test Engineer

Date: 23 Apr., 2021

Reviewed by: Winner Zhang  
Project Engineer

Date: 23 Apr., 2021

### 3 Contents

Page

1	COVER PAGE.....	1
2	VERSION .....	2
3	CONTENTS .....	3
4	GENERAL INFORMATION.....	4
4.1	CLIENT INFORMATION .....	4
4.2	GENERAL DESCRIPTION OF E.U.T. ....	4
4.3	OPERATING MODES .....	4
4.4	LABORATORY FACILITY .....	5
4.5	LABORATORY LOCATION .....	5
5	TECHNICAL REQUIREMENTS SPECIFICATION IN FCC CFR TITLE 47 PART 2.1091 .....	6
5.1	LIMITS .....	6
5.2	TEST PROCEDURE.....	6
5.3	RESULT .....	7
5.4	CONCLUSION .....	7

## 4 General Information

### 4.1 Client Information

Applicant:	Nebra Ltd
Address:	Unit 4 Bells Yew Green Business Court, Bells Yew Green, Tunbridge Wells TN3 9BJ
Manufacturer:	Nebra Ltd
Address:	Unit 4 Bells Yew Green Business Court, Bells Yew Green, Tunbridge Wells TN3 9BJ
Factory:	SUNSOAR TECH CO., LIMITED
Address:	4/F, Block E, Fengze Building, Huafeng No.2 Industrial Park, Hangkong Road, XiXiang Town, BaoAn District, Shenzhen, China

### 4.2 General Description of E.U.T.

Product Name:	Nebra Smart Indoor LoRa Gateway / Nebra HNT Indoor Hotspot Miner
Model No.:	HNTIN-470-G, HNTIN-868-G, HNTIN-915-G, HNTIN-433-G, HNTIN-470, HNTIN-868, HNTIN-915, HNTIN-433
Operation Frequency:	2.4G Wi-Fi: 2412MHz~2462MHz BLE: 2402MHz~2480MHz Lora: 923.3MHz~927.5MHz
Modulation technology:	802.11b: DSSS, 802.11g/n: OFDM BLE: GFSK Lora: FSK
Antenna Type:	BLE/Wi-Fi: Internal antenna Lora: External Antenna
Antenna gain:	BLE: 1.0 dBi; Wi-Fi: 0 dBi; LoRa: 3 dBi
Test Sample Condition:	The test samples were provided in good working order with no visible defects.
Remark:	<p>Model No.: Model: HNTIN-470-G, HNTIN-868-G, HNTIN-915-G, HNTIN-433-G, HNTIN-470, HNTIN-868, HNTIN-915, HNTIN-433 has the same internal circuit design, layout, components and internal wiring. The difference is that the ones with the -G suffix have GPS function, while those without the suffix do not. Each model has two appearances, except for the appearance, the interior is exactly the same. In addition, the corresponding frequency of each model of LoRa module is different, as follows:</p> <p>The Nebra HNT Indoor Hotspot is available in 4 variants to support multiple regions.</p> <p>It is available in the following frequency variants:</p> <ul style="list-style-type: none"> <li>• 433 MHz (HNTIN-433)</li> <li>• 470 Mhz (HNTIN-470)</li> <li>• 868 Mhz (HNTIN-868)</li> <li>• 915 Mhz (HNTIN-915)</li> </ul>

### 4.3 Operating Modes

Operating mode	Detail description
BLE mode	Keep the EUT in continuously transmitting in BLE mode
Lora mode	Keep the EUT in continuously transmitting in Lora mode
2.4G WIFI mode	Keep the EUT in continuously transmitting in 2.4G WIFI mode

### 4.4 Additions to, deviations, or exclusions from the method

No
----

#### 4.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

#### 4.6 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: [info@ccis-cb.com](mailto:info@ccis-cb.com), Website: <http://www.ccis-cb.com>

## 5 Technical Requirements Specification in FCC CFR Title 47 Part 2.1091

### 5.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

### 5.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

### 5.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm <sup>2</sup> )	Limits for General Population/ Uncontrolled Exposure (mW/cm <sup>2</sup> )
2.4G Wi-Fi							
2462	12.51	17.82	0	1.00	20.00	0.0035	1.0
BT & BLE							
2402	-0.85	0.82	1	1.26	20.00	0.0002	1.0
LoRa							
925.7	17.50	56.23	3	2.00	20.00	0.0223	0.617

Note: Just the worst case mode was shown in report.

Simultaneous transmission assessment(Worst mode):

WiFi Result/Limits + BLE Result/Limit + Lora Result/Limit < 0.617

$0.0035/1 + 0.0002/1 + 0.0223/0.617 = 0.0398 < 0.617$

### 5.4 Conclusion

The device is exempt from the RF exposure evaluation.

-----End of report-----