

# IC RF Test Report

## (DTS)

**Applicant:** Nebra Ltd

**Address of Applicant:** Unit 4 Bells Yew Green Business Court Bells Yew Green

**Equipment Under Test (EUT)**

**Product Name:** Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version

**Model No.:** NEBHNT-HHRK4-915, NEBHNT-HHRK4-915-2, NEBHNT-HHRK4-915-3

**Canada IC:** 27187-HHRK4

**Applicable Standards:** RSS-Gen Issue 5, RSS-247 Issue 2

**Date of Sample Receipt:** 05 Jan., 2022

**Date of Test:** 06 Jan., to 08 May, 2022

**Date of Report Issued:** 18 May, 2022

**Test Result:** PASS

**Tested by:**  
Test Engineer**Date:**

18 May, 2022

**Reviewed by:**  
Project Engineer**Date:**

18 May, 2022

**Approved by:**  
Manager**Date:**

18 May, 2022

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	09 May, 2022	Original
01	13 May, 2022	Updated page1, 4

### 3 Contents

	Page
<b>1 Cover Page .....</b>	<b>1</b>
<b>2 Version .....</b>	<b>2</b>
<b>3 Contents.....</b>	<b>3</b>
<b>4 General Information .....</b>	<b>4</b>
4.1 Client Information .....	4
4.2 General Description of E.U.T. ....	4
4.3 Test Mode and Test Environment .....	5
4.4 Description of Support Units.....	5
4.5 Measurement Uncertainty.....	5
4.6 Additions to, Deviations, or Exclusions from the Method.....	5
4.7 Laboratory Facility.....	5
4.8 Laboratory Location .....	5
4.9 Test Instruments List .....	6
<b>5 Measurement Setup and Procedure .....</b>	<b>7</b>
5.1 Test Channel .....	7
5.2 Test Setup.....	7
5.3 Test Procedure .....	9
<b>6 Test Results.....</b>	<b>10</b>
6.1 Summary .....	10
6.2 Antenna requirement .....	12
6.3 AC Power Line Conducted Emission .....	13
6.4 Conducted Output Power .....	15
6.5 Emission Bandwidth .....	16
6.6 Power Spectral Density.....	17
6.7 Spurious Emission .....	18

## 4 General Information

### 4.1 Client Information

Applicant:	Nebra Ltd
Address:	Unit 4 Bells Yew Green Business Court Bells Yew Green
Manufacturer/Factory::	Nebra Ltd
Address:	Unit 4 Bells Yew Green Business Court Bells Yew Green

### 4.2 General Description of E.U.T.

Product Name:	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version
Model No.:	NEBHNT-HHRK4-915, NEBHNT-HHRK4-915-2, NEBHNT-HHRK4-915-3
Operation Frequency:	923.3 MHz – 927.5 MHz
Channel Numbers:	8
Modulation Technology:	LoRa
Antenna Type:	External Antenna
Antenna Gain:	3.0dBi (declare by applicant)
AC Adapter:	Model No.:R241-1202500I Input: AC100-240V, 50/60Hz 1.5 A Output: DC 12.0V, 2.5A
Remark:	Model No.: NEBHNT-HHRK4-915, NEBHNT-HHRK4-915-2, NEBHNT-HHRK4-915-3 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.
Test model, sample#	NEBHNT-HHRK4-915, WSZR122200089
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

### 4.3 Test Mode and Test Environment

Test Mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1010 mbar

### 4.4 Description of Support Units

The EUT has been tested as an independent unit.
---

### 4.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	±3.11 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.62 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	±4.45 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	±5.34 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	±5.34 dB

**Note:** All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### 4.6 Additions to, Deviations, or Exclusions from the Method

No
----

### 4.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

### 4.8 Laboratory Location

<p>JianYan Testing Group Shenzhen Co., Ltd.  Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.  Tel: +86-755-23118282, Fax: +86-755-23116366  Email: info-JYTee@lets.com, Website: <a href="http://jyt.lets.com">http://jyt.lets.com</a></p>
--

## 4.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal.Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	01-19-2021	01-18-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	06-20-2021	06-19-2022
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	06-18-2021	06-17-2022
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXG001-7	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXG001-3	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXG001-9	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-03-2021	03-02-2022
				02-17-2022	02-16-2023
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	11-27-2021	11-26-2022
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	03-07-2021	03-06-2022
				02-17-2022	02-16-2023
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal.Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI 3	WXJ003	03-03-2021	03-02-2022
				02-17-2022	02-16-2023
RF Switch	TOP PRECISION	RSU0301	WXG003	03-03-2021	03-02-2022
				02-17-2022	02-16-2023
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	03-18-2021	03-17-2022
				02-17-2022	02-16-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	06-18-2021	06-17-2022
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	03-03-2021	03-02-2022
				02-17-2022	02-16-2023
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-20-2022	01-20-2023
DC Power Supply	Keysight	E3642A	WXJ025-2	10-25-2021	10-24-2022

## 5 Measurement Setup and Procedure

## 5.1 Test Channel

According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:


Channel		Frequency		Channel	
1	923.3MHz	4	925.1MHz	7	926.9MHz
2	923.9MHz	5	925.7MHz	8	927.5MHz
3	924.5MHz	6	926.3MHz		

*Note:*

*Channel No. 1, 5 & 8 were selected as Lowest, Middle and Highest channel.*

## 5.2 Test Setup


**1) Conducted emission measurement:**




**Note:** The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

## 2) Radiated emission measurement:


Below 1GHz (3m SAC)



Above 1GHz (3m SAC)



### 3) Conducted test method





### 5.3 Test Procedure

Test method	Test step
Conducted emission	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.</li> </ol>
Radiated emission	<p><b>For below 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> <p><b>For above 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol>
Conducted test method	<ol style="list-style-type: none"> <li>1. The antenna port of EUT was connected to the test port of the test system through an RF cable.</li> <li>2. The EUT is keeping in continuous transmission mode and tested in all modulation modes.</li> <li>3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.</li> </ol>

## 6 Test Results

### 6.1 Summary

#### 6.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	RSS-GEN Section 6.8	See Section 6.2	Pass
AC Power Line Conducted Emission	RSS-GEN Section 8.8	See Section 6.3	Pass
Conducted Output Power	RSS-247 Section 5.4(d)	See Section 6.4	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	RSS-247 Section 5.2(a)	See Section 6.5	Pass
Power Spectral Density	RSS-247 Section 5.2(b)	See Section 6.6	Pass
Spurious Emission	RSS-GEN Section 6.13 RSS-GEN Section 8.10 RSS-247 Section 5.5	See Section 6.7	Pass
<b>Remark:</b> 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).			
<b>Test Method:</b>	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

### 6.1.2 Test Limit


Test items	Limit																																								
AC Power Line Conducted Emission	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBμV)</th></tr><tr><th>Quasi-Peak</th><th>Average</th></tr><tr><td>0.15 – 0.5</td><td>66 to 56 <small>Note</small></td><td>56 to 46 <small>Note</small></td></tr><tr><td>0.5 – 5</td><td>56</td><td>46</td></tr><tr><td>5 – 30</td><td>60</td><td>50</td></tr><tr><td colspan="3"><b>Note:</b> The level decreases linearly with the logarithm of the frequency.</td></tr></table>	Frequency (MHz)	Limit (dBμV)		Quasi-Peak	Average	0.15 – 0.5	66 to 56 <small>Note</small>	56 to 46 <small>Note</small>	0.5 – 5	56	46	5 – 30	60	50	<b>Note:</b> The level decreases linearly with the logarithm of the frequency.																									
Frequency (MHz)	Limit (dBμV)																																								
	Quasi-Peak	Average																																							
0.15 – 0.5	66 to 56 <small>Note</small>	56 to 46 <small>Note</small>																																							
0.5 – 5	56	46																																							
5 – 30	60	50																																							
<b>Note:</b> The level decreases linearly with the logarithm of the frequency.																																									
Conducted Output Power	For DTSSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).																																								
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.																																								
99% Occupied Bandwidth	N/A																																								
Power Spectral Density	The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).																																								
Spurious Emission	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required:</p> <table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBμV/m)</th><th rowspan="2">Detector</th></tr><tr><th>@ 3m</th><th>@ 10m</th></tr><tr><td>30 – 88</td><td>40.0</td><td>30.0</td><td>Quasi-peak</td></tr><tr><td>88 – 216</td><td>43.5</td><td>33.5</td><td>Quasi-peak</td></tr><tr><td>216 – 960</td><td>46.0</td><td>36.0</td><td>Quasi-peak</td></tr><tr><td>960 – 1000</td><td>54.0</td><td>44.0</td><td>Quasi-peak</td></tr><tr><td colspan="4"><b>Note:</b> The more stringent limit applies at transition frequencies.</td></tr><tr><th rowspan="2">Frequency</th><th colspan="2">Limit (dBμV/m) @ 3m</th><th rowspan="2"></th></tr><tr><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>54.0</td><td>74.0</td><td></td></tr><tr><td colspan="4"><b>Note:</b> The measurement bandwidth shall be 1 MHz or greater.</td></tr></table>	Frequency (MHz)	Limit (dBμV/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	<b>Note:</b> The more stringent limit applies at transition frequencies.				Frequency	Limit (dBμV/m) @ 3m			Average	Peake	Above 1 GHz	54.0	74.0		<b>Note:</b> The measurement bandwidth shall be 1 MHz or greater.			
Frequency (MHz)	Limit (dBμV/m)		Detector																																						
	@ 3m	@ 10m																																							
30 – 88	40.0	30.0	Quasi-peak																																						
88 – 216	43.5	33.5	Quasi-peak																																						
216 – 960	46.0	36.0	Quasi-peak																																						
960 – 1000	54.0	44.0	Quasi-peak																																						
<b>Note:</b> The more stringent limit applies at transition frequencies.																																									
Frequency	Limit (dBμV/m) @ 3m																																								
	Average	Peake																																							
Above 1 GHz	54.0	74.0																																							
<b>Note:</b> The measurement bandwidth shall be 1 MHz or greater.																																									

## 6.2 Antenna requirement

<b>Standard requirement:</b>	RSS-Gen Section 6.8
The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.	
<b>E.U.T Antenna:</b>	
The LoRa antenna is an External antenna which cannot replace by end-user, the best case gain of the antenna is 3 dBi. See product internal photos for details.	

### 6.3 AC Power Line Conducted Emission

<b>Product name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test by:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test frequency:</b>	150 kHz ~ 30 MHz	<b>Phase:</b>	Line
<b>Test voltage:</b>	AC 120 V/60 Hz		




	Freq	Read	LISN	Cable	Level	Limit	Over	Remark
	MHz	dBuV	Factor	Loss	dBuV	dBuV	dB	
1	0.150	34.03	0.00	0.01	34.04	56.00	-21.96	Average
2	0.150	46.77	0.00	0.01	46.78	66.00	-19.22	QP
3	0.162	46.61	0.00	0.01	46.62	65.34	-18.72	QP
4	0.170	45.90	0.00	0.01	45.91	64.94	-19.03	QP
5	0.211	42.33	0.00	0.03	42.36	63.18	-20.82	QP
6	0.369	39.80	0.00	0.03	39.83	58.52	-18.69	QP
7	0.373	34.30	0.00	0.03	34.33	48.43	-14.10	Average
8	1.819	22.27	0.00	0.19	22.46	46.00	-23.54	Average
9	2.213	26.44	0.00	0.17	26.61	46.00	-19.39	Average
10	2.213	31.25	0.00	0.17	31.42	56.00	-24.58	QP
11	2.750	24.56	0.00	0.10	24.66	46.00	-21.34	Average
12	11.498	18.16	0.00	0.11	18.27	50.00	-31.73	Average

**Remark:**

1. Level = Read level + LISN Factor + Cable Loss.

<b>Product name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test by:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test frequency:</b>	150 kHz ~ 30 MHz	<b>Phase:</b>	Neutral
<b>Test voltage:</b>	AC 120 V/60 Hz		



	Freq	Read	LISN	Cable	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	35.04	0.00	0.01	35.05	56.00	-20.95	Average
2	0.150	47.00	0.00	0.01	47.01	66.00	-18.99	QP
3	0.158	46.54	0.00	0.01	46.55	65.56	-19.01	QP
4	0.369	33.59	0.00	0.03	33.62	48.52	-14.90	Average
5	0.369	40.93	0.00	0.03	40.96	58.52	-17.56	QP
6	1.680	24.52	0.00	0.17	24.69	46.00	-21.31	Average
7	1.829	31.84	0.00	0.19	32.03	56.00	-23.97	QP
8	2.167	32.68	0.00	0.18	32.86	56.00	-23.14	QP
9	2.213	26.55	0.00	0.17	26.72	46.00	-19.28	Average
10	2.692	25.49	0.00	0.11	25.60	46.00	-20.40	Average
11	11.021	35.72	0.00	0.11	35.83	60.00	-24.17	QP
12	11.807	27.71	0.00	0.10	27.81	50.00	-22.19	Average

**Remark:**


1. Level = Read level + LISN Factor + Cable Loss.



## 6.4 Conducted Output Power

Test Channel	Maximum Output Power (dBm)	Limit(dBm)	Result
Lowest channel	27.12	30.00	Pass
Middle channel	26.98		
Highest channel	26.81		


Test plot as follows:



## 6.5 Emission Bandwidth

Test Channel	6dB Emission Bandwidth (KHz)	Limit (kHz)	Result
Lowest channel	597.1	>500	Pass
Middle channel	593.7		
Highest channel	593.2		
Test Channel	99% Occupy Bandwidth (KHz)	Limit (kHz)	Result
Lowest channel	648.37	N/A	N/A
Middle channel	645.92		
Highest channel	645.33		

Test plot as follows:






## 6.6 Power Spectral Density

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest channel	7.27	8.00	Pass
Middle channel	7.03		
Highest channel	6.63		


Test plot as follows:




## 6.7 Spurious Emission

### 6.7.1 Band-edge Emission

Lowest Channel




Highest Channel




## 6.7.2 Conducted Spurious Emission


Lowest channel



Middle channel




Highest channel



### 6.7.3 Emissions in Restricted Frequency Bands

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Channel:</b>	960 MHz ~ 1 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120/60Hz		




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	978.317	15.00	22.98	3.60	0.00	41.58	54.00	-12.42	

**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Channel:</b>	960 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz		




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	982.640	14.82	23.00	3.61	0.00	41.43	54.00	-12.57	

**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product Model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Channel:</b>	1000 MHz ~ 1240 MHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120/60Hz		




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1124.320	23.85	54.05	30.20	74.00	19.95	PK	Vertical
2	1125.040	13.12	43.32	30.20	54.00	10.68	AV	Vertical

**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product Model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Channel:</b>	1000 MHz ~ 1240 MHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz		



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1125.040	13.77	43.97	30.20	54.00	10.03	AV	Horizontal
2	1125.280	23.51	53.71	30.20	74.00	20.29	PK	Horizontal


**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Pre-amplifier Factor).

## 6.7.4 Emissions in Non-restricted Frequency Bands

Below 1GHz:

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product Model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	72.005	43.37	26.37	-17.00	40.00	13.63	PK	Vertical
2	75.013	45.83	28.73	-17.10	40.00	11.27	PK	Vertical
3	95.870	43.86	26.93	-16.93	43.50	16.57	PK	Vertical
4	171.634	50.30	33.31	-16.99	43.50	10.19	PK	Vertical
5	500.012	42.40	35.44	-6.96	46.00	10.56	PK	Vertical
6	750.103	38.80	35.06	-3.74	46.00	10.94	PK	Vertical

**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).



<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product Model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	72.005	42.66	25.66	-17.00	40.00	14.34	PK	Horizontal
2	250.018	42.57	28.78	-13.79	46.00	17.22	PK	Horizontal
3	399.995	44.70	34.24	-10.46	46.00	11.76	PK	Horizontal
4	600.029	36.90	31.42	-5.48	46.00	14.58	PK	Horizontal
5	800.063	35.64	32.94	-2.70	46.00	13.06	PK	Horizontal
6	975.068	36.67	35.77	-0.90	54.00	18.23	PK	Horizontal

**Remark:**

1. Level = Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).

### Above 1GHz:

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	1 GHz ~ 10 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120/60Hz		




**Suspected Data List**

NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	1808.75	57.87	36.90	-20.97	74.00	37.10	PK	Vertical
2	1810.60	48.86	27.90	-20.96	54.00	26.10	AV	Vertical
3	2715.90	48.10	30.96	-17.14	54.00	23.04	AV	Vertical
4	2715.90	55.92	38.78	-17.14	74.00	35.22	PK	Vertical
5	3621.20	47.84	33.29	-14.55	54.00	20.71	AV	Vertical
6	3621.20	55.33	40.78	-14.55	74.00	33.22	PK	Vertical
7	4526.50	47.84	37.09	-10.75	54.00	16.91	AV	Vertical
8	4526.50	54.59	43.84	-10.75	74.00	30.16	PK	Vertical
9	5431.80	54.83	48.84	-5.99	74.00	25.16	PK	Vertical
10	5431.80	45.67	39.68	-5.99	54.00	14.32	AV	Vertical
11	6337.10	45.46	41.63	-3.83	54.00	12.37	AV	Vertical
12	6337.10	52.63	48.80	-3.83	74.00	25.20	PK	Vertical
13	7242.40	44.96	44.88	-0.08	54.00	9.12	AV	Vertical
14	7242.40	51.90	51.82	-0.08	74.00	22.18	PK	Vertical
15	8147.70	43.97	44.77	0.80	54.00	9.23	AV	Vertical
16	8147.70	51.30	52.10	0.80	74.00	21.90	PK	Vertical
17	9053.00	53.47	55.31	1.84	74.00	18.69	PK	Vertical
18	9053.00	45.40	47.24	1.84	54.00	6.76	AV	Vertical

### Remark:

1. Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

<b>Product Name:</b>	Nebra Indoor LoRa Gateway ROCK Pi 4 Version / Nebra Indoor Helium Hotspot ROCK Pi 4 Version	<b>Product model:</b>	NEBHNT-HHRK4-915
<b>Test By:</b>	Mike	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	1 GHz ~ 10 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz		



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	1810.60	49.07	28.11	-20.96	54.00	25.89	AV	Horizontal
2	1818.50	59.02	38.10	-20.92	74.00	35.90	PK	Horizontal
3	2715.90	48.68	31.54	-17.14	54.00	22.46	AV	Horizontal
4	2715.90	55.69	38.55	-17.14	74.00	35.45	PK	Horizontal
5	3621.20	46.76	32.21	-14.55	54.00	21.79	AV	Horizontal
6	3621.20	54.57	40.02	-14.55	74.00	33.98	PK	Horizontal
7	4526.50	47.31	36.56	-10.75	54.00	17.44	AV	Horizontal
8	4526.50	54.27	43.52	-10.75	74.00	30.48	PK	Horizontal
9	5431.80	54.57	48.58	-5.99	74.00	25.42	PK	Horizontal
10	5431.80	46.69	40.70	-5.99	54.00	13.30	AV	Horizontal
11	6337.10	45.51	41.68	-3.83	54.00	12.32	AV	Horizontal
12	6337.10	52.94	49.11	-3.83	74.00	24.89	PK	Horizontal
13	7242.40	44.78	44.70	-0.08	54.00	9.30	AV	Horizontal
14	7242.40	52.05	51.97	-0.08	74.00	22.03	PK	Horizontal
15	8147.70	44.73	45.53	0.80	54.00	8.47	AV	Horizontal
16	8147.70	52.55	53.35	0.80	74.00	20.65	PK	Horizontal
17	9053.00	54.18	56.02	1.84	74.00	17.98	PK	Horizontal
18	9053.00	45.85	47.69	1.84	54.00	6.31	AV	Horizontal

**Remark:**

1. Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

-----End of report-----