

# phylo2vec: a library for vector-based phylogenetic tree manipulation

Neil Scheidwasser<sup>1\*</sup>, Ayush Nag<sup>2\*</sup>, Matthew J Penn<sup>1</sup>, Anthony MV Jakob<sup>4</sup>, Frederik Mølkjær Andersen<sup>1</sup>, Mark P Khurana<sup>1</sup>, Landung Setiawan<sup>2</sup>, Madeline Gordon<sup>2</sup>, David A Duchêne<sup>1</sup>, and Samir Bhatt<sup>1,3¶</sup>

<sup>1</sup> Section of Health Data Science and AI, University of Copenhagen, Copenhagen <sup>2</sup> eScience Institute, University of Washington, Seattle, United States <sup>3</sup> MRC Centre for Global Infectious Disease Analysis, Imperial College London, London, United Kingdom <sup>4</sup> Independent researcher ¶ Corresponding author \* These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished


## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

## Summary

Phylogenetics is a fundamental component of many analysis frameworks in biology (Yang, 2014) as well as linguistics (Atkinson & Gray, 2005) to study the evolutionary relationships of different entities. Recently, the advent of large-scale genomics and the SARS-CoV-2 pandemic has underscored the necessity for phylogenetic software to handle large datasets of genomes or phylogenetic trees (Attwood et al., 2022; Kapli et al., 2020; Khurana et al., 2024; Kraemer et al., 2025). While significant efforts have focused on scaling optimisation algorithms (De Maio et al., 2023; Sanderson, 2021; Turakhia et al., 2021), visualization (Sanderson, 2022), and lineage identification (McBroome et al., 2024), an emerging body of research has been dedicated to efficient representations of data for genomes (Deorowicz et al., 2023) and phylogenetic trees such as phylo2vec (Chauve et al., 2025; Penn et al., 2024; Richman et al., 2025). Compared to traditional tree representations such as the Newick format (Felsenstein, 2004), which represents trees using strings of nested parentheses, modern representations of phylogenetic trees utilize integer vectors to define the tree topology traversal. This approach offers several advantages, including easier manipulability, increased memory efficiency, and applicability to downstream tasks such as machine learning.

Here, we present the latest release of phylo2vec (or Phylo2Vec), a high-performance software package for encoding, manipulating, and analysing binary phylogenetic trees. At its core, the package is based on the phylo2vec (Penn et al., 2024) representation of binary trees, which defines a bijection from any tree topology with  $n$  leaves into an integer vector of size  $n - 1$ . Compared to the traditional Newick format, phylo2vec is designed to enable fast sampling and comparison of binary trees. This release features a core implementation in Rust, providing significant performance improvements and memory efficiency (Figure 1), while remaining available in Python (superseding the release described in the original paper (Penn et al., 2024)) and R via dedicated wrappers, making it accessible to a broad audience in the bioinformatics community.



**Figure 1:** Benchmark times for converting a phylo2vec vector to a Newick string (left) and vice versa (right). For each size, we evaluated the execution time for a minimum of 20 rounds using pytest-benchmark. We compare the execution time of the Python functions in the latest release, which rely on Rust bindings via PyO3, with the previous release (Penn et al., 2024), which make use of just-in-time (JIT) compilation of Python functions using Numba (Lam et al., 2015). Execution times were benchmarked on an AMD Ryzen Threadripper PRO 5995WX with a 64-core CPU @ 7 GHz and 256 GB of RAM.

## Statement of need


The purpose of the phylo2vec library is threefold. First, the core of the library aims at providing a robust phylogenetic tree manipulation library in Rust, complementing other efforts such as light\_phylogeny (Duchemin et al., 2018), which focuses on tree visualization and manipulation of reconciled phylogenies (Nakhleh, 2013), and rust-bio (Köster, 2016), a comprehensive bioinformatics library which does not yet cover phylogenetics. Second, phylo2vec aims at complementing existing phylogenetic libraries such as ape (Paradis & Schliep, 2019) in R, and ete3 (Huerta-Cepas et al., 2016) and DendroPy (Moreno et al., 2024) in Python, by providing fast tree sampling, fast tree comparison and efficient tree data compression (Penn et al., 2024). Third, the inherent tree representation of phylo2vec offers a pathway to several optimisation frameworks for phylogenetic inference. A notable example is GradME (Penn et al., 2023), a gradient descent-based algorithm which uses a relaxed representation of phylo2vec into a continuous space.

## Features

The presented release of phylo2vec addresses several limitations of (Penn et al., 2024). From an optimisation perspective, it introduces efficient  $\mathcal{O}(n \log n)$  implementations for both vector-to-Newick and Newick-to-vector conversions, leveraging Adelson-Velsky and Landis (AVL) trees (Adelson-Velsky & Landis, 1962) and Fenwick trees (Fenwick, 1994), respectively.

In terms of new features, it supports branch length annotations by extending the vector representation of size  $n - 1$  to a matrix of size  $(n - 1) \times 3$ , where  $n$  denotes the number of leaves (or taxa) in a tree (Figure 2). Further enhancements include several leaf-level operations (pruning, placement, MRCA identification), fast cophenetic distance matrix calculation, and various optimisation schemes based on phylo2vec tree representations, notably hill-climbing and GradME (Penn et al., 2023). Bayesian phylogenetic inference via Markov Chain Monte Carlo (MCMC) with phylo2vec matrices is also made possible by a likelihood function that leverages tree representation similarities between phylo2vec and BEAGLE, a highly optimised library that

underpins a number of phylogenetic software (Ayres et al., 2012; Suchard & Rambaut, 2009). Finally, user-friendliness is enhanced by step-by-step demos of the inner workings of phylo2vec's representations and their conversion to commonly used phylogenetic tree formats (e.g., Newick string, list of edges).



**Figure 2:** Recovering a tree from a phylo2vec vector: example for  $v = [0, 2, 0, 4]$ . (a) Main algorithm for leaf placement described in (Penn et al., 2024). (b) Augmenting the phylo2vec vector into a matrix  $m$  with branch lengths. We use an intermediary ancestry matrix whereby each row describes a cherry (two children nodes and the parent node), which we augment with two columns of branch lengths. The node with the smallest descendant will have the branch length in the 2nd column, and the other the branch length in the 3rd column.

## Maintenance

With Phylo2Vec, we aim to support long-term maintenance through implementing recommended software practices explicitly into the structure of the project and development workflow. More specifically, we have structured the project such that the Rust API contains the core algorithms, and all other language components are APIs that bind to the Rust functions. This avoids tight coupling, as it allows for the possibility of adding new languages to bind to the Rust API's, without needing to change anything in the Rust project itself. Additionally, we have

74 established a robust continuous integration (CI) pipeline using GitHub Actions, which features:

- 75 ■ Unit test frameworks for Rust ([cargo](#)), Python ([pytest](#)), and R (testthat ([Wickham, 2011](#)))
- 76 ■ Benchmarking on the Rust code ([criterion](#)) and its Python bindings ([pytest-benchmark](#))

77

78 Lastly, to complement Jupyter Notebook demos, comprehensive documentation is provided

79 using [Jupyter Book](#) and [Read The Docs](#).

## 80 Acknowledgements

81 S.B. acknowledges funding from the MRC Centre for Global Infectious Disease Analysis

82 (reference MR/X020258/1), funded by the UK Medical Research Council (MRC). This UK

83 funded award is carried out in the frame of the Global Health EDCTP3 Joint Undertaking.

84 S.B. acknowledges support from the Danish National Research Foundation via a chair grant

85 (DNRF160) which also supports N.S. and M.P.K. S.B. acknowledges support from The Eric and

86 Wendy Schmidt Fund For Strategic Innovation via the Schmidt Polymath Award (G-22-63345)

87 which also supports M.J.P. and F.M.A. S.B. acknowledges support from the Novo Nordisk

88 Foundation via The Novo Nordisk Young Investigator Award (NNF20OC0059309). D.A.D.

89 is supported by a Data Science - Emerging researcher award from Novo Nordisk Fonden

90 (NNF23OC0084647).

## 91 References

- 92 Adelson-Velsky, Georgii, & Landis, E. (1962). An algorithm for the organization of information.
- 93 *Soviet Math.*, 3, 1259–1263.
- 94 Atkinson, Q. D., & Gray, R. D. (2005). Curious parallels and curious connections—phylogenetic
- 95 thinking in biology and historical linguistics. *Systematic Biology*, 54(4), 513–526.
- 96 Attwood, S. W., Hill, S. C., Aanensen, D. M., Connor, T. R., & Pybus, O. G. (2022).
- 97 Phylogenetic and phylodynamic approaches to understanding and combating the early
- 98 SARS-CoV-2 pandemic. *Nature Reviews Genetics*, 23(9), 547–562.
- 99 Ayres, D. L., Darling, A., Zwickl, D. J., Beerli, P., Holder, M. T., Lewis, P. O., Huelsenbeck,
- 100 J. P., Ronquist, F., Swofford, D. L., Cummings, M. P., & others. (2012). BEAGLE: An
- 101 application programming interface and high-performance computing library for statistical
- 102 phylogenetics. *Systematic Biology*, 61(1), 170–173.
- 103 Chauve, C., Colijn, C., & Zhang, L. (2025). A vector representation for phylogenetic trees.
- 104 *Philosophical Transactions B*, 380(1919), 20240226.
- 105 De Maio, N., Kalaghatgi, P., Turakhia, Y., Corbett-Detig, R., Minh, B. Q., & Goldman,
- 106 N. (2023). Maximum likelihood pandemic-scale phylogenetics. *Nature Genetics*, 55(5),
- 107 746–752.
- 108 Deorowicz, S., Danek, A., & Li, H. (2023). AGC: Compact representation of assembled
- 109 genomes with fast queries and updates. *Bioinformatics*, 39(3), btad097.
- 110 Duchemin, W., Gence, G., Arigon Chifolleau, A.-M., Arvestad, L., Bansal, M. S., Berry, V.,
- 111 Boussau, B., Chevenet, F., Comte, N., Davín, A. A., Dessimoz, C., Dylus, D., Hasic, D.,
- 112 Mallo, D., Planel, R., Posada, D., Scornavacca, C., Szöllősi, G., Zhang, L., ... Daubin,
- 113 V. (2018). RecPhyloXML: A format for reconciled gene trees. *Bioinformatics*, 34(21),
- 114 3646–3652. <https://doi.org/10.1093/bioinformatics/bty389>
- 115 Felsenstein, J. (2004). *Inferring phylogenies* (Vol. 2). Sinauer Associates.
- 116 Fenwick, P. M. (1994). A new data structure for cumulative frequency tables. *Software:*
- 117 *Practice and Experience*, 24(3), 327–336.

- 118 Huerta-Cepas, J., Serra, F., & Bork, P. (2016). ETE 3: Reconstruction, analysis, and  
119 visualization of phylogenomic data. *Molecular Biology and Evolution*, 33(6), 1635–1638.
- 120 Kapli, P., Yang, Z., & Telford, M. J. (2020). Phylogenetic tree building in the genomic age.  
121 *Nature Reviews Genetics*, 21(7), 428–444.
- 122 Khurana, M. P., Curran-Sebastian, J., Scheidwasser, N., Morgenstern, C., Rasmussen, M.,  
123 Fonager, J., Stegger, M., Tang, M.-H. E., Juul, J. L., Escobar-Herrera, L. A., & others.  
124 (2024). High-resolution epidemiological landscape from ~ 290,000 SARS-CoV-2 genomes  
125 from denmark. *Nature Communications*, 15(1), 7123.
- 126 Köster, J. (2016). Rust-bio: A fast and safe bioinformatics library. *Bioinformatics*, 32(3),  
127 444–446.
- 128 Kraemer, M. U., Tsui, J. L.-H., Chang, S. Y., Lytras, S., Khurana, M. P., Vanderslott, S., Bajaj,  
129 S., Scheidwasser, N., Curran-Sebastian, J. L., Semenova, E., & others. (2025). Artificial  
130 intelligence for modelling infectious disease epidemics. *Nature*, 638(8051), 623–635.
- 131 Lam, S. K., Pitrou, A., & Seibert, S. (2015). Numba: A llvm-based python jit compiler.  
132 *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC*, 1–6.
- 133 McBroome, J., Bernardi Schneider, A. de, Roemer, C., Wolfinger, M. T., Hinrichs, A. S.,  
134 O'Toole, A. N., Ruis, C., Turakhia, Y., Rambaut, A., & Corbett-Detig, R. (2024). A  
135 framework for automated scalable designation of viral pathogen lineages from genomic  
136 data. *Nature Microbiology*, 9(2), 550–560.
- 137 Moreno, M. A., Holder, M. T., & Sukumaran, J. (2024). DendroPy 5: A mature python  
138 library for phylogenetic computing. *Journal of Open Source Software*, 9(101), 6943.  
139 <https://doi.org/10.21105/joss.06943>
- 140 Nakhleh, L. (2013). Computational approaches to species phylogeny inference and gene tree  
141 reconciliation. *Trends in Ecology & Evolution*, 28(12), 719–728.
- 142 Paradis, E., & Schliep, K. (2019). Ape 5.0: An environment for modern phylogenetics and  
143 evolutionary analyses in R. *Bioinformatics*, 35, 526–528.
- 144 Penn, M. J., Scheidwasser, N., Khurana, M. P., Duchêne, D. A., Donnelly, C. A., & Bhatt, S.  
145 (2024). Phylo2Vec: A vector representation for binary trees. *Systematic Biology*, syae030.
- 146 Penn, M. J., Scheidwasser, N., Penn, J., Donnelly, C. A., Duchêne, D. A., & Bhatt, S. (2023).  
147 Leaping through tree space: Continuous phylogenetic inference for rooted and unrooted  
148 trees. *Genome Biology and Evolution*, 15(12), evad213.
- 149 Richman, H., Zhang, C., & IV, F. A. M. (2025). *Vector encoding of phylogenetic trees by*  
150 *ordered leaf attachment*. <https://arxiv.org/abs/2503.10169>
- 151 Sanderson, T. (2021). Chronumetal: Time tree estimation from very large phylogenies. In  
152 *bioRxiv* (pp. 2021–2010). Cold Spring Harbor Laboratory.
- 153 Sanderson, T. (2022). Taxonium, a web-based tool for exploring large phylogenetic trees. *Elife*,  
154 11.
- 155 Suchard, M. A., & Rambaut, A. (2009). Many-core algorithms for statistical phylogenetics.  
156 *Bioinformatics*, 25(11), 1370–1376.
- 157 Turakhia, Y., Thornlow, B., Hinrichs, A. S., De Maio, N., Gozashti, L., Lanfear, R., Haussler,  
158 D., & Corbett-Detig, R. (2021). Ultrafast sample placement on existing tRees (USHER)  
159 enables real-time phylogenetics for the SARS-CoV-2 pandemic. *Nature Genetics*, 53(6),  
160 809–816.
- 161 Wickham, H. (2011). Testthat: Get started with testing. *The R Journal*, 3(1), 5–10.
- 162 Yang, Z. (2014). *Molecular evolution: A statistical approach*. Oxford University Press.